fn make_np_sum

Michael Shoemate

February 27, 2024

This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of `make_np_sum` in `__init__.py` at commit f5bb719 (outdated[1]).

`make_np_sum` accepts an `input_domain` and `input_metric`, and returns a stable Transformation that computes the vector-valued sum with bounded L_p sensitivity.

PR History

- Pull Request #490

1 Hoare Triple

Preconditions

None

Pseudocode

```python
def make_np_sum(input_domain: Domain, input_metric: Metric) -> Transformation:
    """Construct a Transformation that computes a sum over the row axis of a 2-dimensional array.

    :param input_domain: instance of `np_array2_domain(size=_, num_columns=_)`
    :param input_metric: instance of `symmetric_distance()`

    :returns a Measurement that computes the DP sum
    """
    import opendp.prelude as dp
    import numpy as np  # type: ignore[import]

    dp.assert_features("contrib", "floating-point")

    if not str(input_domain).startswith("NPArray2Domain"):  #
        raise ValueError("input_domain must be an NPArray2Domain")

    if input_metric != dp.symmetric_distance():  #
        raise ValueError("input_metric must be the symmetric distance")

    input_desc = input_domain.descriptor
    norm = input_desc.norm
    if norm is None: #
        raise ValueError("input_domain must have bounds. See make_np_clamp")
```

[1] See new changes with `git diff f5bb719..e3096de2 python/src/opendp/_extrinsics/_make_np_sum/__init__.py`

```python

    output_metric = {1: dp.l1_distance, 2: dp.l2_distance}[input_desc.p]  #

    if input_desc.size is None:
        origin = np.atleast_1d(input_desc.origin)
        norm += np.linalg.norm(origin, ord=input_desc.p)
        stability = lambda d_in: d_in * norm
    else:
        stability = lambda d_in: d_in // 2 * 2 * norm

    return dp.t.make_user_transformation(
        input_domain,
        input_metric,
        dp.vector_domain(dp.atom_domain(T=input_desc.T)),
        output_metric(T=input_desc.T),
        lambda arg: arg.sum(axis=0),  #
        stability,
    )
```

Postcondition

For every setting of the input parameters `(input_domain, input_metric)` to `make_np_sum` such that the given preconditions hold, `make_np_sum` raises an exception (at compile time or run time) or returns a valid transformation. A valid transformation has the following properties:

1. (Appropriate output domain). For every element v in `input_domain`, `function`(v) is in `output_domain` or raises a data-independent runtime exception.

2. (Stability guarantee). For every pair of elements u, v in `input_domain` and for every pair (`d_in`, `d_out`), where `d_in` has the associated type for `input_metric` and `d_out` has the associated type for `output_metric`, if u, v are `d_in`-close under `input_metric`, `stability_map`(`d_in`) does not raise an exception, and `stability_map`(`d_in`) $\leq$ `d_out`, then `function`(u), `function`(v) are `d_out`-close under `output_metric`.

2 Proof

Proof. Let u and v be datasets that are `d_in`-close with respect to `input_metric`. By 14, the input domain is `NPArray2Domain`, and by 17 input metric is the `SymmetricDistance`. By 22 and 25, the input data has row-p-norm bounded by at most R.

2.1 Appropriate Output Domain

Since the input data is a 2-dimensional numpy array, then the output is a 1-dimensional numpy array of the same type. Therefore the output is a member of the output vector domain.

2.2 Stability Guarantee

Now consider two cases: when the data set size is known, and when it is not known.

2.2.1 Known Size

WLOG, assume u, v only differ on the leading $\lfloor d_{in}/2 \rfloor$ elements.

$$
\begin{aligned}
& \max_{x \sim x'} d_{Lp}(\text{sum}(x), \text{sum}(x')) && \text{by definition of stability} && (1)\\
= & \max_{x \sim x'} \|\sum_{i=1}^{N} x_i - \sum_{i=1}^{N} x'_i\|_p && \text{substitute the function and metric} && (2)\\
= & \max_{x \sim x'} \|\sum_{i=1}^{\lfloor d_{in}/2 \rfloor} x_i - \sum_{i=1}^{\lfloor d_{in}/2 \rfloor} x'_i\|_p && \text{all trailing terms cancel} && (3)\\
\leq & \max_{x \sim x'} \sum_{i=1}^{\lfloor d_{in}/2 \rfloor} \|x_i - x'_i\|_p && \text{by triangle inequality} && (4)\\
\leq & \sum_{i=1}^{\lfloor d_{in}/2 \rfloor} 2 \cdot R && \text{each row has bounded p-norm of } R && (5)\\
= & \lfloor d_{in}/2 \rfloor \cdot 2 \cdot R && && (6)
\end{aligned}
$$

Therefore we've shown that for every pair of elements $u, v \in$ `input_domain` and every $d_{Sym}(u, v) \leq$ `d_in`, if u, v are `d_in`-close then `function`(u), `function`(v) are `privacy_map`(`d_in`)-close under `output_metric` (the L^p distance).

2.2.2 Unknown Size

WLOG, assume v has an additional d_{in} trailing rows.

$$
\begin{aligned}
& \max_{x \sim x'} d_{Lp}(\text{sum}(x), \text{sum}(x')) && \text{by definition of stability} && (7)\\
= & \max_{x \sim x'} \|\sum_{i=1}^{N} x_i - \sum_{i=1}^{N'} x'_i\|_p && \text{substitute the function and metric} && (8)\\
= & \max_{x \sim x'} \|\sum_{i=1}^{d_{in}} x'_{N+i}\|_p && \text{all but the last terms cancel} && (9)\\
\leq & \max_{x \sim x'} \sum_{i=1}^{d_{in}} \|x'_{N+i}\|_p && \text{by triangle inequality} && (10)\\
\leq & \sum_{i=1}^{d_{in}} (\|O\|_p + R) && \text{each row has bounded p-norm of } R \text{ at } O && (11)\\
= & d_{in} \cdot (\|O\|_p + R) && && (12)
\end{aligned}
$$

Therefore we've shown that for every pair of elements $u, v \in$ `input_domain` and every $d_{Sym}(u, v) \leq$ `d_in`, if u, v are `d_in`-close then `function`(u), `function`(v) are `privacy_map`(`d_in`)-close under `output_metric` (the L^p distance).

□