

fn then_saturating_cast_hashmap

Michael Shoemate (@Shoeboxam)

This proof resides in “**contrib**” because it has not completed the vetting process.

Proves soundness of the implementation of `then_saturating_cast_hashmap` in `mod.rs` at commit `f5bb719` (outdated¹).

1 Hoare Triple

Precondition

Compiler-verified

- Generic TK implements trait `Hashable`
- Generic TV implements trait `SaturatingCast<IBig>`

Caller-verified

None

Pseudocode

```
1 def then_saturating_cast_hashmap() -> Function[HashMap[TK, IBig], HashMap[TK, TV]]:  
2   return Function.new(lambda x: {k: TV.saturating_cast(v) for k, v in x.items()})
```

Postcondition

Theorem 1.1. For every setting of the input parameters (TK, TV) to `then_saturating_cast_hashmap` such that the given preconditions hold, `then_saturating_cast_hashmap` raises an error (at compile time or run time) or returns a valid postprocessor. A valid postprocessor has the following property:

1. (Data-independent errors). For every pair of members x and x' in `input_domain`, `function(x)`, `function(x')` either both raise the same error, or neither raise an error.

Proof. Since `T.saturating_cast` is infallible, the function is infallible, meaning that the function cannot raise data-dependent errors. Therefore the function is a valid postprocessor. $\square$

¹See new changes with `git diff f5bb719..8a3a63e rust/src/measurements/noise_threshold/nature/integer/mod.rs`