fn match_datetime_component

Michael Shoemate (@Shoeboxam)

This proof resides in **"contrib"** because it has not completed the vetting process.

Proves soundness of `match_datetime_component` in `mod.rs` at commit f5bb719 (outdated[1]).

`match_datetime_component` returns the data type and number of possible unique values of a compute operation that retrieves a datetime component.

1 Hoare Triple

Precondition

Compiler-verified

- Argument `temporal_function` of type `TemporalFunction`

Caller-verified

None

Pseudocode

```
def match_datetime_component(
    temporal_function: TemporalFunction,
) -> DataType | None:
    return (
        {
            Millennium: DataType.UInt32,
            Century: DataType.Int32,
            Year: DataType.Int32,
            IsoYear: DataType.Int32,
            Quarter: DataType.Int8,
            Month: DataType.Int8,
            Week: DataType.Int8,
            WeekDay: DataType.Int8,
            Day: DataType.Int8,
            OrdinalDay: DataType.Int16,
            Hour: DataType.Int8,
            Minute: DataType.Int8,
            Second: DataType.Int8,
            Millisecond: DataType.Int32,
            Microsecond: DataType.Int32,
            Nanosecond: DataType.Int32,
        }
    ).get(temporal_function)
```

[1] See new changes with `git diff f5bb719..00154e4 rust/src/transformations/make_stable_expr/namespace_dt/expr_datetime_component/mod.rs`

Postcondition

Theorem 1.1. For any choice of `temporal_function`, returns the data type of the output if the input is an infallible row-by-row temporal expression, otherwise returns none.

Proof. For each choice of `temporal_function`, the data type is directly verified via testing. Infallible row-by-row is verified by inspection of the Polars source code. □