

# fn make\_np\_sum

Michael Shoemate

October 6, 2026

This proof relies on an idealized model of numeric computation that ignores finite-machine limitations such as non-closure and overflow, so the corresponding API belongs behind the “**idealized-numeric**” feature flag.

This proof resides in “**contrib**” because it has not completed the vetting process.

Proves soundness of `make_np_sum` in `__init__.py` at [commit f5bb719](#) (outdated<sup>1</sup>).

`make_np_sum` accepts an `input_domain` and `input_metric`, and returns a stable Transformation that computes the vector-valued sum with bounded  $L_p$  sensitivity.

## 1 Hoare Triple

### Preconditions

None

### Pseudocode

```
1
2 def make_np_sum(input_domain: Domain, input_metric: Metric) -> Transformation:
3     """Construct a Transformation that computes a sum over the row axis of a 2-dimensional
4     array.
5
6     :param input_domain: instance of 'array2_domain(size=_, num_columns=_)'
7     :param input_metric: instance of 'symmetric_distance()'
8
9     :return: a Measurement that computes the DP sum
10    """
11    import opendp.prelude as dp
12
13    np = import_optional_dependency("numpy")
14
15    dp.assert_features("contrib", "idealized-numeric")
16
17    if not str(input_domain).startswith("NumpyArray2Domain"): #
18        raise ValueError(
19            f"input_domain ({input_domain}) must be NumpyArray2Domain"
20        ) # pragma: no cover
21
22    if input_domain.descriptor.nan:
23        raise ValueError(
```

---

<sup>1</sup>See new changes with `git diff f5bb719..adf030e python/src/opendp/extras/numpy/_make_np_sum/__init__.py`

```

23         f"input_domain ({input_domain}) must not permit NaN elements"
24     ) # pragma: no cover
25
26     if input_metric != dp.symmetric_distance(): #
27         raise ValueError(
28             "input_metric must be the symmetric distance"
29         ) # pragma: no cover
30
31     input_desc = input_domain.descriptor
32     norm = input_desc.norm
33     if norm is None: #
34         raise ValueError(
35             f"input_domain ({input_domain}) must have bounds. See make_np_clamp"
36         ) # pragma: no cover
37
38     output_metric = {1: dp.l1_distance, 2: dp.l2_distance}[
39         input_desc.p
40     ] #
41
42     if input_desc.size is None:
43         origin = np.atleast_1d(input_desc.origin)
44         norm += np.linalg.norm(origin, ord=input_desc.p)
45         stability = lambda d_in: d_in * norm
46     else:

```

## Postcondition

**Theorem 1.1.** For every setting of the input parameters (`input_domain`, `input_metric`) to `make_np_sum` such that the given preconditions hold, `make_np_sum` raises an error (at compile time or run time) or returns a valid transformation. A valid transformation has the following properties:

1. (Data-independent runtime errors). For every pair of members  $x$  and  $x'$  in `input_domain`, `invoke(x)` and `invoke(x')` either both return the same error or neither return an error.
2. (Appropriate output domain). For every member  $x$  in `input_domain`, `function(x)` is in `output_domain` or raises a data-independent runtime error.
3. (Stability guarantee). For every pair of members  $x$  and  $x'$  in `input_domain` and for every pair  $(d_{in}, d_{out})$ , where  $d_{in}$  has the associated type for `input_metric` and  $d_{out}$  has the associated type for `output_metric`, if  $x, x'$  are  $d_{in}$ -close under `input_metric`, `stability_map(d_in)` does not raise an error, and `stability_map(d_in) = d_out`, then `function(x), function(x')` are  $d_{out}$ -close under `output_metric`.

*Proof.* Let  $x$  and  $x'$  be arbitrary members of `input_domain`. By 16, `input_domain` is an `NArray2Domain`, and by 26, `input_metric` is `SymmetricDistance`. Let  $R$  denote `input_domain.descriptor.norm`, and let  $O$  denote `input_domain.descriptor.origin`. By 33,  $R$  is defined, and by 40, the output metric is the  $L^p$  metric with  $p \in \{1, 2\}$ . Because this proof is under `idealized-numeric`s, we ignore machine arithmetic issues such as overflow and treat vector addition as associative and commutative.

**Data-independent runtime errors.** All runtime checks in `make_np_sum` occur before the transformation is returned. For any member of `input_domain`, the function on line ?? applies `sum(axis=0)` to a 2-dimensional numpy array, which is defined for every such input. Therefore, for every pair  $x, x' \in \text{input\_domain}$ , neither `invoke(x)` nor `invoke(x')` raises a runtime error.

**Appropriate output domain.** Each member of `input_domain` is a 2-dimensional numpy array whose entries have type `input_domain.descriptor.T` and do not contain NaNs. Applying `sum(axis=0)` removes axis zero and returns a 1-dimensional numpy array of the same atomic type. Under idealized numerics, summing non-NaN values yields non-NaN values. Hence `function(x)` is a member of `output_domain`.

**Stability guarantee.** Fix any  $d_{\text{in}}$  and  $d_{\text{out}}$  such that  $x$  and  $x'$  are  $d_{\text{in}}$ -close under `input_metric` and `stability_map(d_in) = d_out`. Let  $M$  and  $M'$  be the multisets of rows in  $x$  and  $x'$ . Let  $C = M \cap M'$ ,  $A = M \setminus C$ , and  $B = M' \setminus C$ . Since addition is commutative, all rows in  $C$  cancel, so

$$\text{function}(x) - \text{function}(x') = \sum_{a \in A} a - \sum_{b \in B} b.$$

By the definition of `SymmetricDistance`,

$$|A| + |B| = d_{\text{Sym}}(x, x') \leq d_{\text{in}}.$$

Now consider two cases.

**Case 1: Known size.** If `input_domain.descriptor.size` is known, then  $x$  and  $x'$  have the same number of rows, so  $|A| = |B|$ . Let  $m = |A| = |B|$ . Then  $2m \leq d_{\text{in}}$ , so  $m \leq \lfloor d_{\text{in}}/2 \rfloor$ . Enumerate  $A = \{a_1, \dots, a_m\}$  and  $B = \{b_1, \dots, b_m\}$ . Since every row lies in the  $L^p$  ball of radius  $R$  centered at  $O$ ,

$$\begin{aligned} \|\text{function}(x) - \text{function}(x')\|_p &= \left\| \sum_{i=1}^m (a_i - b_i) \right\|_p \\ &\leq \sum_{i=1}^m \|a_i - b_i\|_p && \text{by triangle inequality} \\ &\leq \sum_{i=1}^m (\|a_i - O\|_p + \|b_i - O\|_p) \\ &\leq \sum_{i=1}^m 2R \\ &= 2mR \\ &\leq 2\lfloor d_{\text{in}}/2 \rfloor R. \end{aligned}$$

This is exactly the known-size stability map returned by `make_np_sum`.

**Case 2: Unknown size.** If `input_domain.descriptor.size` is unknown, then `make_np_sum` sets

$$\text{stability\_map}(d_{\text{in}}) = d_{\text{in}} \cdot (R + \|O\|_p).$$

For every row  $v$  in either  $A$  or  $B$ ,

$$\|v\|_p \leq \|v - O\|_p + \|O\|_p \leq R + \|O\|_p.$$

Therefore,

$$\begin{aligned} \|\text{function}(x) - \text{function}(x')\|_p &= \left\| \sum_{a \in A} a - \sum_{b \in B} b \right\|_p \\ &\leq \sum_{a \in A} \|a\|_p + \sum_{b \in B} \|b\|_p && \text{by triangle inequality} \\ &\leq (|A| + |B|)(R + \|O\|_p) \\ &\leq d_{\text{in}}(R + \|O\|_p). \end{aligned}$$

This is exactly the unknown-size stability map returned by `make_np_sum`.

In both cases, `function(x)` and `function(x')` are  $d_{\text{out}}$ -close under `output_metric`. □