

fn sample_uniform_ubig_below

Michael Shoemate (@Shoeboxam)

October 6, 2026

This proof resides in “contrib” because it has not completed the vetting process.

This document proves that the implementation of `sample_uniform_ubig_below` in `mod.rs` at commit `f5bb719` (outdated¹) satisfies its definition. This algorithm uses the same algorithm and argument as used for unsigned native integers, but this time the bit depth is dynamically chosen to fill the last byte of a series of bytes long enough to hold `upper`.

PR History

- Pull Request #473

1 Hoare Triple

Precondition

Compiler-verified

- `upper` is of type `UBig`.

Caller-verified

None

Pseudocode

```
1 def sample_uniform_ubig_below(upper: UBig) -> UBig:
2     byte_len = upper.bit_len().div_ceil(8)
3     max = UBig.from_be_bytes([u8.MAX] * byte_len)
4     threshold = max - max % upper
5
6     buffer = [0] * byte_len
7     while True:
8         fill_bytes(buffer)
9
10        sample = UBig.from_be_bytes(buffer)
11        if sample < threshold:
12            return sample % upper
```

Postcondition

Theorem 1.1. For any setting of the input parameter `upper`, `sample_uniform_ubig_below` either

¹See new changes with `git diff f5bb719..4e331c2 rust/src/traits/samplers/uniform/mod.rs`

- raises an exception if there is a lack of system entropy,
- returns `out` where `out` is uniformly distributed between $[0, upper)$.

Proof. `byte_len` is the fewest number of bytes necessary to represent `upper`, which works out to $\text{ceil}(\text{ceil}(\log_2(\text{upper}))/8)$. Let `max` denote the largest integer representable in this many bytes ($2^{\text{byte_len}} - 1$). We can sample uniformly from $[0, \text{max})$ by filling this many bytes with bits uniformly at random.

You could (naively) sample from $[0, upper)$ by rejecting any `sample` greater than or equal to `upper`. To reduce the probability of rejecting (and improve computational performance), partition the numbers into two sets:

- the leading $upper \cdot k = \text{threshold}$ numbers that wrap evenly modulo `upper`
- the remaining trailing $(\text{max} \bmod upper)$ numbers

It is equivalent to only reject trailing numbers, and return the sample modulo `upper`. Since $\text{max} = \text{threshold} + (\text{max} \bmod upper)$, then $\text{threshold} = \text{max} - (\text{max} \bmod upper)$. Therefore, for any value of `upper`, the function satisfies the postcondition. □