

Reset Passwords

openemail Admin Account

Reset mailcow admin to `admin:moohoo`. Older mailcow: dockerized installations may find `openemail-reset-admin.sh` in their openemail root directory (`openemail_path`).

```
cd openemail_path
./helper-scripts/openemail-reset-admin.sh
```

Reset MySQL Passwords

Stop the stack by running `docker-compose stop`.

When the containers came to a stop, run this command:

```
docker-compose run --rm --entrypoint '/bin/sh -c "gosu mysql mysqld --skip-grant-tables & sleep 10 && mysql -hlocalhost -uroot && exit 0"' mysql-openemail
```

1. Find database name

```
# source openemail.conf
# docker-compose exec mysql-openemail mysql -u${DBUSER} -p${DBPASS} ${DBNAME}
MariaDB [(none)]> show databases;
+-----+
| Database                |
+-----+
| information_schema      |
| openemail_database      | <=====
| mysql                   |
| performance_schema     |
+-----+
4 rows in set (0.00 sec)
```

2. Reset one or more users

Both "password" and "authentication_string" exist. Currently "password" is used, but better set both.

```

MariaDB [(none)]> SELECT user FROM mysql.user;
+-----+
| user          |
+-----+
| openemail_user | <====
| root          |
+-----+
2 rows in set (0.00 sec)

MariaDB [(none)]> FLUSH PRIVILEGES;
MariaDB [(none)]> UPDATE mysql.user SET authentication_string =
PASSWORD('gotr00t'), password = PASSWORD('gotr00t') WHERE User = 'root' AND
Host = '%';
MariaDB [(none)]> UPDATE mysql.user SET authentication_string =
PASSWORD('mookuh'), password = PASSWORD('mookuh') WHERE User = 'openemail'
AND Host = '%';
MariaDB [(none)]> FLUSH PRIVILEGES;

```

Remove Two-Factor Authentication

This works similar to resetting a MySQL password, now we do it from the host without connecting to the MySQL CLI:

```

source openemail.conf
docker-compose exec mysql-openemail mysql -u${DBUSER} -p${DBPASS} ${DBNAME}
-e "DELETE FROM tfa WHERE username='YOUR_USERNAME';"

```