

Roundcube

Download Roundcube 1.3.x to the web htdocs directory and extract it (here `rc/`):

```
cd data/web
wget -O - https://github.com/roundcube/roundcubemail/releases/download/
1.3.x/roundcubemail-1.3.x-complete.tar.gz | tar xfvz -
# Change folder name
mv roundcubemail-1.3.x rc
# Change permissions
chown -R root: rc/
```

Create a file `data/web/rc/config/config.inc.php` with the following content.

Change the `des_key` parameter to a random value. It is used to temporarily store your IMAP password.

```
<?php
error_reporting(0);
if (!file_exists('/tmp/mime.types')) {
file_put_contents("/tmp/mime.types", fopen("http://svn.apache.org/repos/asf/
httpd/httpd/trunk/docs/conf/mime.types", 'r'));
}
$config = array();
$config['db_dsnw'] = 'mysql://' . getenv('DBUSER') . ':' .
getenv('DBPASS') . '@mysql/' . getenv('DBNAME');
$config['default_host'] = 'tls://dovecot';
$config['default_port'] = '143';
$config['smtp_server'] = 'tls://postfix';
$config['smtp_port'] = 587;
$config['smtp_user'] = '%u';
$config['smtp_pass'] = '%p';
$config['support_url'] = '';
$config['product_name'] = 'Roundcube Webmail';
$config['des_key'] = 'yourrandomstring_changeme';
$config['log_dir'] = '/dev/null';
$config['temp_dir'] = '/tmp';
$config['plugins'] = array(
    'archive',
    'managesieve'
);
$config['skin'] = 'larry';
$config['mime_types'] = '/tmp/mime.types';
$config['imap_conn_options'] = array(
    'ssl' => array('verify_peer' => false, 'verify_peer_name' => false,
    'allow_self_signed' => true)
);
$config['enable_installer'] = true;
$config['smtp_conn_options'] = array(
```

```

    'ssl' => array('verify_peer' => false, 'verify_peer_name' => false,
    'allow_self_signed' => true)
);

$config['managesieve_port'] = 4190;
$config['managesieve_host'] = 'tls://dovecot';
$config['managesieve_conn_options'] = array(
    'ssl' => array('verify_peer' => false, 'verify_peer_name' => false,
    'allow_self_signed' => true)
);
// Enables separate management interface for vacation responses (out-of-
office)
// 0 - no separate section (default),
// 1 - add Vacation section,
// 2 - add Vacation section, but hide Filters section
$config['managesieve_vacation'] = 1;

```

Point your browser to `https://myserver/rc/installer` and follow the instructions. Initialize the database and leave the installer.

Delete the directory `data/web/rc/installer` after a successful installation!

Enable change password function in Roundcube

Open `data/web/rc/config/config.inc.php` and enable the password plugin:

```

...
$config['plugins'] = array(
    'archive',
    'password',
);
...

```

Open `data/web/rc/plugins/password/password.php`, search for `case 'sha':` and add above:

```

    case 'sha256':
        $salt = rcube_utils::random_bytes(8);
        $crypt = base64_encode( hash('sha256', $password . $salt,
TRUE ) . $salt );
        $prefix = '{SSHA256}';
        break;

```

Open `data/web/rc/plugins/password/config.inc.php` and change the following parameters (or add them at the bottom of that file):

```

$config['password_driver'] = 'sql';
$config['password_algorithm'] = 'sha256';
$config['password_algorithm_prefix'] = '{SSHA256}';

```

```
$config['password_query'] = "UPDATE mailbox SET password = %P WHERE  
username = %u";
```

Optionally, you can add Roundcube's link to the mailcow Apps list. To do this, open or create `data/web/inc/vars.local.inc.php` and add the following code-block:

NOTE: Don't forget to add the `<?php` delimiter on the first line

```
...  
$MAILCOW_APPS = array(  
    array(  
        'name' => 'SOGGo',  
        'link' => '/SOGGo/'  
    ),  
    array(  
        'name' => 'Roundcube',  
        'link' => '/rc/'  
    )  
);  
...
```