

Performance Impact of `-fno-omit-frame-pointer` on IA

Intel


Annita Zhang

Background

<https://fedoraproject.org/wiki/Changes/fno-omit-frame-pointer>

- Problem Statement
 - Fedora added `-fno-omit-frame-pointer` and `-mno-omit-leaf-frame-pointer` to the default C/C++ compilation flags
- Purpose:
 - Improve the effectiveness of profiling and debugging
- Status:
 - It was added into Fedora Linux 38 and 40
 - Ubuntu 24.04 LTS enabled it by default
- Cost:
 - Save, setup and restore frame pointer in each function => 3 instructions
 - Lose 1 GPR register for register allocation
- Performance Impact:
 - Some performance loss is expected

SPEC2017 performance impact on EMR



Performance Impact by Fedora and Suse


- Benchmark Measurement Reported by Fedora
 - Compiling the kernel with GCC is 2.4% slower with frame pointers
 - Running Blender to render a frame is 2% slower on our specific testcase
 - openssl/botan/zstd do not seem to be affected significantly when built with frame pointers
 - The impact on CPython benchmarks can be anywhere from 1-10% depending on the specific benchmark
 - Redis benchmarks do not seem to be significantly impacted when built with frame pointers
- Benchmark reported by Suse
 - Possible 5~10% range depending on the particular software

Performance Impact reported by Phoronix

- The geomean performance penalty is 14% out of 100 tests

Geometric Mean Of All Test Results

Result Composite - Fedora Linux -fno-omit-frame-pointer Performance Impact



<https://www.phoronix.com/review/fedora-frame-pointer/5>

Proposal

- Given the performance impact, suggest not to enable `-fno-omit-frame-pointer` by default in GCC for OpenEuler releases
- Explore alternative approaches to improve profiling and debugging
 - Dwarf
 - ORC
 - LBR
 - CTF Frame
 - Shadow Stack
- Redhat is developing “eu-stacktrace” w/o frame pointer
 - <https://www.phoronix.com/news/Red-Hat-eu-stacktrace>