OGC® DOCUMENT: 25-019

External identifier of this OGC® document: http://www.opengis.net/doc/{doc-type}/{standard}/{m.n}

Open Geospatial Consortium

OGC EMISSION EVENT MODELING LANGUAGE (EMISSIONML) PART I: DATA MODEL

DRAFT STANDARD

CANDIDATE SWG DRAFT

Version: 1.0
Submission Date: 2025-xx-xx
Approval Date: 2025-xx-xx
Publication Date: 2025-xx-xx
Editor: Steve Liang, Ryan Ahola

Notice: This document is not an OGC Standard. This document is an OGC Draft Standard and is therefore not an official position of the OGC membership. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an OGC Standard. Further, an OGC Draft Standard should not be referenced as required or mandatory technology in procurements.

License Agreement

Use of this document is subject to the license agreement at https://www.ogc.org/license

Copyright notice

Copyright © 2026 Open Geospatial Consortium
To obtain additional rights of use, visithttps://www.ogc.org/legal

Note

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

CONTENTS

I. ABSTRACT vi

II. KEYWORDS vi

III. PREFACE vii

IV. SECURITY CONSIDERATIONS viii

V. SUBMITTING ORGANIZATIONS ix

VI. SUBMITTERS ix

1. SCOPE 2

2. CONFORMANCE 4

3. NORMATIVE REFERENCES 6

4. TERMS AND DEFINITIONS 8

5. KEYWORDS 11

6. SUBMITTING ORGANIZATIONS 13

7. CONVENTIONS 15
   - 7.1. Overview 15
   - 7.2. Identifiers 15

8. CLAUSES NOT CONTAINING NORMATIVE MATERIAL 17
   - 8.1. Clauses not containing normative material sub-clause 1 17
   - 8.2. Clauses not containing normative material sub-clause 2 17

9. EMISSION EVENT DATA MODEL 19
   - 9.1. Overview 19
   - 9.2. Emission Event Class 21
   - 9.3. Feature Class 22
   - 9.4. Source Class 23
   - 9.5. Source Type Class 24
   - 9.6. Mechanism Class 24
   - 9.7. Emission Quantity Class 25
   - 9.8. Unit of Measure Class 26

9.9. Temporal Bound Class 27
9.10. Observation Class 27
9.11. Emission Intent Enumeration 28
9.12. Procedure Class 28
9.13. Determination Procedure Class 29

ANNEX A (INFORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE (NORMATIVE) 32
A.1. Abstract tests for Emission Event Conceptual Data Model Core 32

ANNEX B (INFORMATIVE) RELATIONSHIP WITH OGC FEATURES AND OBSERVATIONS 39
B.1. Overview 39
B.2. EmissionML and OGC Features 40
B.3. EmissionML and OMS 3.0 Observations 40
B.4. EmissionML and OMS 3.0 Procedures 41
B.5. Why Explicit Domain Modeling 41

BIBLIOGRAPHY 44

LIST OF TABLES

Table — Submitters ix
Table 1 — UML relationship notation used in this standard 19
Table 2 — Requirements class — Emission Event Conceptual Data Model Core 20
Table 3 — Requirement 1 — Emission Event Class 21
Table 4 — Attributes of an Emission Event class 21
Table 5 — Direct relation between an Emission Event class and other class types 21
Table 6 — Requirement 11 — Feature Class 22
Table 7 — Attributes of a Feature class 22
Table 8 — Direct relation between a Feature class and other class types 23
Table 9 — Requirement 2 — Source Class 23
Table 10 — Attributes of a Source class (own attributes; geometry is inherited from Feature) 23
Table 11 — Direct relation between a Source class and other class types 23
Table 12 — Requirement 3 — Source Type Class 24
Table 13 — Attributes of a Source Type class 24
Table 14 — Direct relation between a Source Type class and other class types 24
Table 15 — Requirement 4 — Mechanism Class 24
Table 16 — Attributes of a Mechanism class 25
Table 17 — Direct relation between a Mechanism class and other class types 25
Table 18 — Requirement 5 — Emission Quantity Class 25

Table 19 — Attributes of an Emission Quantity class 25
Table 20 — Direct relation between an Emission Quantity class and other class types 26
Table 21 — Requirement 6 — Unit of Measure Class 26
Table 22 — Attributes of a Unit of Measure class 26
Table 23 — Direct relation between a Unit of Measure class and other class types 26
Table 24 — Requirement 7 — Temporal Bound Class 27
Table 25 — Attributes of a Temporal Bound class 27
Table 26 — Direct relation between a Temporal Bound class and other class types 27
Table 27 — Requirement 8 — Observation Class 28
Table 28 — Requirement 9 — Emission Intent Enumeration 28
Table 29 — Enumeration values of Emission Intent 28
Table 30 — Requirement 12 — Procedure Class 29
Table 31 — Attributes of a Procedure class 29
Table 32 — Direct relation between a Procedure class and other class types 29
Table 33 — Requirement 10 — Determination Procedure Class 29
Table 34 — Attributes of a Determination Procedure class (own attributes) 29
Table A.1 — Conformance test — Emission Event Conceptual Data Model Core 32
Table A.2 — Conformance test — Emission Event 32
Table A.3 — Conformance test — Source 33
Table A.4 — Conformance test — Source Type 33
Table A.5 — Conformance test — Mechanism 34
Table A.6 — Conformance test — Emission Quantity 34
Table A.7 — Conformance test — Unit of Measure 34
Table A.8 — Conformance test — Temporal Bound 35
Table A.9 — Conformance test — Observation 35
Table A.10 — Conformance test — Emission Intent 35
Table A.11 — Conformance test — Determination Procedure 36
Table A.12 — Conformance test — Feature 36
Table A.13 — Conformance test — Procedure 36

LIST OF FIGURES

Figure 1 — EmissionML Abstract Conceptual Model 19
Figure B.1 — Conceptual layering of EmissionML on foundational ISO/OGC standards 39

I ABSTRACT

This OGC Standard defines EmissionML, a conceptual data model for representing emission events. EmissionML provides a domain-specific ontology for describing the release of substances into the atmosphere, including the source from which an emission originates, the mechanism by which it occurs, the quantity of substance released, and the temporal bounds of the event.

EmissionML distinguishes itself through three key design principles. First, it incorporates an evidence chain linking emission determinations to supporting Observations, enabling traceability from reported values to underlying measurements. Second, it provides explicit uncertainty provenance by attaching data quality metadata to both emission quantities and temporal bounds, ensuring that the confidence and precision of each determination are recorded alongside the values themselves. Third, it offers clear spatial and temporal context — spatial through Feature (as the ultimate feature of interest) and Source (as the emission origin), temporal through start time, end time, and the phenomenon time of supporting Observations. By adopting the OMS 3.0 Observation model, EmissionML provides a common framework for reconciling heterogeneous sensor observations — from remote sensing satellites to ground-based continuous monitoring stations — within a single, unified evidence chain.

The model builds on foundational OGC and ISO standards. Source inherits from Feature (ISO 19109), DeterminationProcedure inherits from Procedure (ISO/OGC 19156:2023), and Observations conform to the OMS 3.0 Observation model (ISO/OGC 19156:2023). The standard defines twelve requirements specifying the structure and constraints of the core data model.

By making emission semantics, evidence chains, and uncertainty provenance explicit and machine-verifiable, EmissionML enables credibility of reported emission values, traceability from determinations to their supporting observations and procedures, and reproducibility of emission assessments across organizations and jurisdictions.

The intended audience includes environmental regulators, greenhouse gas reporting frameworks, emissions monitoring system developers, and geospatial data infrastructure implementers who require a standardized, interoperable representation of emission event data.

II KEYWORDS

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, EmissionML, emission event, atmospheric emissions, greenhouse gas, air quality, emission source, emission quantity, observation, data quality, uncertainty provenance, evidence chain, interoperability, net-zero, methane emissions, sensor web

PREFACE

NOTE: Insert Preface Text here. Give OGC specific commentary: describe the technical content, reason for document, history of the document and precursors, and plans for future work. > Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

IV SECURITY CONSIDERATIONS

No security considerations have been made for this Standard.

V SUBMITTING ORGANIZATIONS

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- SensorUp Inc.
- Natural Resources Canada
- University of Calgary

VI SUBMITTERS

All questions regarding this submission should be directed to the editor or the submitters:

Table — Submitters

Name	Affiliation
Steve Liang	University of Calgary / SensorUp
Ryan Ahola	Natural Resources Canada

1

SCOPE

1 SCOPE

This document defines a conceptual data model for emission events, for features from which emissions originate and mechanisms by which they occur, and for observations and procedures that provide evidence for emission determinations. These provide models for the exchange of information describing emission events and their associated quantities, temporal bounds, sources, and mechanisms, both within and between different regulatory, scientific, and technical communities.

Emission events commonly involve observations of an ultimate feature-of-interest at varying spatial scales. This document defines a common set of classes for describing emission sources, mechanisms, quantities, temporal bounds, determination procedures, and supporting observations. The schema includes relationships between emission events and their evidence chains, linking reported values to underlying observations and procedures, and attaches data quality metadata to emission quantities and temporal bounds.

This document concerns only externally visible interfaces and places no restriction on the underlying implementations other than what is needed to satisfy the interface specifications in the actual situation.

2

CONFORMANCE

2 CONFORMANCE

This Standard defines a conceptual data model for emission events.

Requirements for one standardization target type are considered:

- Data Model

Conformance with this Standard shall be checked using all the relevant tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to be achieved to claim conformance are specified in the OGC Compliance Testing Policies and Procedures and the OGC Compliance Testing web site.

In order to conform to this OGC® Standard, a software implementation shall choose to implement:

- The Emission Event Conceptual Data Model Core conformance class specified in Annex A (normative).

All requirements-classes and conformance-classes described in this document are owned by the Standard(s) identified.

3

NORMATIVE REFERENCES

3 NORMATIVE REFERENCES

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO: ISO 19101-1:2014, *Geographic information — Reference model — Part 1: Fundamentals*. International Organization for Standardization, Geneva (2014). https://www.iso.org/standard/59164.html.

ISO: ISO 19107:2019, *Geographic information — Spatial schema*. International Organization for Standardization, Geneva (2019). https://www.iso.org/standard/66175.html.

ISO: ISO 19108:2002, *Geographic information — Temporal schema*. International Organization for Standardization, Geneva (2002). https://www.iso.org/standard/26013.html.

ISO: ISO 19109:2015, *Geographic information — Rules for application schema*. International Organization for Standardization, Geneva (2015). https://www.iso.org/standard/59193.html.

ISO: ISO 19157:2013, *Geographic information — Data quality*. International Organization for Standardization, Geneva (2013). https://www.iso.org/standard/32575.html.

ISO: ISO 19156:2023, *Geographic information — Observations, measurements and samples*. International Organization for Standardization, Geneva (2023). https://www.iso.org/standard/82463.html.

4

TERMS AND DEFINITIONS

4 TERMS AND DEFINITIONS

No terms and definitions are listed in this document.

This document uses the terms defined in OGC Policy Directive 49, which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word "shall" (not "must") is the verb form used to indicate a requirement to be strictly followed to conform to this Standard and OGC documents do not use the equivalent phrases in the ISO/IEC Directives, Part 2.

This document also uses terms defined in the OGC Standard for Modular specifications (OGC 08-131r3), also known as the 'ModSpec'. The definitions of terms such as standard, specification, requirement, and conformance test are provided in the ModSpec.

For the purposes of this document, the following additional terms and definitions apply.

Determination Procedure	A Determination Procedure describes the steps performed to determine the quantity or temporal bounds of an Emission Event.
Emission Event	An Emission Event represents the release of a substance into the atmosphere over a non-zero duration. It is characterized by its start time and end time, the Source Feature from which the substance originated, and the identity and quantity of the emitted substance.
Emission Quantity	An Emission Quantity is the physical quantity representing the total mass of substance released to the atmosphere during a defined Emission Event or over a specified time interval.
Emission Intent	Emission Intent is a code list describing whether an emission is intentional, unintentional, or unknown.
Feature	Abstraction of real world phenomena (Source: ISO 19101-1:2014)
Measurement	Set of operations having the object of determining the value of a quantity (Source: ISO/OGC 19156:2023)
Mechanism	A Mechanism is a classification of the specific physical, chemical, or operational process that constitutes the direct cause or pathway for an emission. It is defined independently of the Source—including its identity, structure, or purpose—allowing Mechanisms to be consistently reused across different types of Source.
Observation	Act carried out by an observer to determine the value of an observable property of an object (feature-of-interest) by using a procedure, with the value provided as the result (Source: ISO/OGC 19156:2023)
Procedure	Description of steps performed (Source: ISO/OGC 19156:2023)
Source	A Source represents the feature from which an emission originates. A Source is an ISO 191xx feature whose geometry provides the geospatial reference for one or more Emission Events. A Source is

	characterised by its own identity, geometry, intended function, and lifecycle, and is explicitly agnostic to the Mechanism by which any associated Emission Event occurs.
Source Type	A Source Type classifies a Source by its category.
Temporal Bound	A Temporal Bound is a value object representing a temporal determination (e.g., start time or end time) that MAY have associated data quality metadata.
Unit of Measure	Reference quantity chosen from a unit equivalence group (Source: ISO/OGC 19156:2023)

5

KEYWORDS

5 KEYWORDS

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, EmissionML, emission event, atmospheric emissions, greenhouse gas, air quality, emission source, emission quantity, observation, data quality, uncertainty provenance, evidence chain, interoperability, net-zero, methane emissions, sensor web

6

SUBMITTING ORGANIZATIONS

6 SUBMITTING ORGANIZATIONS

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- SensorUp Inc.
- Natural Resources Canada
- University of Calgary

7

CONVENTIONS

7 CONVENTIONS

7.1. Overview

This section provides details and examples for any conventions used in the document. Examples of conventions are symbols, abbreviations, use of XML schema, or special notes regarding how to read the document.

7.2. Identifiers

The normative provisions in this Standard are denoted by the URI

http://www.opengis.net/spec/emissionml/1.0

All requirements and conformance tests that appear in this document are denoted by partial URIs which are relative to this base.

8

CLAUSES NOT CONTAINING NORMATIVE MATERIAL

8 CLAUSES NOT CONTAINING NORMATIVE MATERIAL

8.1. Clauses not containing normative material sub-clause 1

Paragraph

8.2. Clauses not containing normative material sub-clause 2

9

EMISSION EVENT DATA MODEL

9 EMISSION EVENT DATA MODEL

9.1. Overview

The EmissionML conceptual model is described as a class diagram in Figure 1. The schema is fully described in x.x.x.



Figure 1 — EmissionML Abstract Conceptual Model

Table 1 — UML relationship notation used in this standard

SYMBOL	NAME	MEANING
	Composition	The target is owned by and cannot exist without the source (e.g., EmissionEvent owns its EmissionQuantity and TemporalBound instances)
	Association	A directional reference between independent classes (e.g., EmissionEvent refers to a Source)

Use the following table for Requirements Classes.

Table 2 — Requirements class — Emission Event Conceptual Data Model Core

Emission Event Conceptual Data Model Core	
http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core	
Target type	Data Model
Dependency	http://www.opengis.net/doc/as/om/3.0/req/obs-basic
Requirement 1	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/emission-event This requirement defines the Emission Event.
Requirement 2	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/source This requirement defines the Source.
Requirement 3	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/source-type This requirement defines the Source Type.
Requirement 4	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/mechanism This requirement defines the Mechanism.
Requirement 5	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/emission-quantity This requirement defines the Emission Quantity.
Requirement 6	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/unit-of-measure This requirement defines the Unit of Measure.
Requirement 7	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/temporal-bound This requirement defines the Temporal Bound.
Requirement 8	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/observation This requirement defines the Observation.
Requirement 9	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/emission-intent This requirement defines the Emission Intent.
Requirement 10	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/determination-procedure This requirement defines the Determination Procedure.
Requirement 11	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/feature This requirement defines the Feature.
Requirement 12	http://www.opengis.net/spec/emissionml/1.0/req/datamodel/core/procedure This requirement defines the Procedure.

9.2. Emission Event Class

An Emission Event represents the release of a substance into the atmosphere over a non-zero duration. It is characterized by its start time and end time, the Source Feature from which the substance originated, and the identity and quantity of the emitted substance.

NOTE 1: Conceptually, an Emission Event corresponds to an occurrent in upper-ontology terms, as it unfolds over time and has temporal parts.

NOTE 2: For reporting or accounting purposes, a long-running emission event is often segmented into multiple time-bounded emission events (e.g., annual records). This segmentation reflects reporting conventions and does not imply physical cessation or re-initiation of the emission.

Table 3 — Requirement 1 — Emission Event Class

Requirement 1: Emission Event Class	/req/datamodel/core/emission-event Each Emission Event class shall have the mandatory attributes listed in Table 4. Each Emission Event class shall have the direct relation between an Emission Event class and other classes listed in Table 5.

Table 4 — Attributes of an Emission Event class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
pollutant Type	The URI linking to an external definition of the pollutantType of the Emission Event.	URI	1 (mandatory)

Table 5 — Direct relation between an Emission Event class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
hasMechanism	The mechanism by which the emission occurred.	Mechanism	1 (mandatory)
hasSource	The source from which the emission originated.	Source	1 (mandatory)
startTime	The start time of the emission event.	TemporalBound	1 (mandatory)
endTime	The end time of the emission event.	TemporalBound	0..1 (optional)

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
hasQuantity	The quantity of the substance emitted.	EmissionQuantity	1 (mandatory)
hasStartTimeBasis	The procedure used to determine the start time.	Determination Procedure	1 (mandatory)
hasEndTimeBasis	The procedure used to determine the end time.	Determination Procedure	0..1 (optional)
hasQuantityBasis	The procedure used to determine the emission quantity.	Determination Procedure	1 (mandatory)
hasStartTime Evidence	Observations providing evidence for the start time determination.	Observation	0..* (optional)
hasEndTimeEvidence	Observations providing evidence for the end time determination.	Observation	0..* (optional)
hasQuantityEvidence	Observations providing evidence for the quantity determination.	Observation	0..* (optional)

9.3. Feature Class

A Feature is an abstraction of real world phenomena (Source: ISO 19101-1:2014). In EmissionML, Feature serves as the base class for entities that can be the ultimate feature of interest of an Observation. A Feature's `geometry` attribute provides the geospatial reference for the phenomenon it represents.

Table 6 — Requirement 11 — Feature Class

Requirement 11: Feature Class	/req/datamodel/core/feature + Each Feature class shall have the mandatory attributes listed in Table 7.

Table 7 — Attributes of a Feature class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
geometry	The spatial geometry of the feature.	GM_Object	1 (mandatory)

Table 8 — Direct relation between a Feature class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
-	No direct relations are defined for Feature in the core model (it is referenced by Source via inheritance and by Observation via ultimateFeatureOfInterest).	-	-

9.4. Source Class

A Source represents the feature from which an emission originates. A Source is an ISO 191xx feature whose geometry provides the geospatial reference for one or more Emission Events. A Source is characterised by its own identity, geometry, intended function, and lifecycle, and is explicitly agnostic to the Mechanism by which any associated Emission Event occurs.

NOTE: A Source is a continuant that may exist independently of any emission, whereas an Emission Event is an occurrent. The identity and lifecycle of a Source are independent of the existence, absence, or frequency of Emission Events.

Table 9 — Requirement 2 — Source Class

Requirement 2: Source Class	/req/datamodel/core/source + Each Source class shall inherit from Feature. Each Source class shall have the optional attributes listed in Table 10. Each Source class shall have the direct relation between a Source class and other classes listed in Table 11.

Table 10 — Attributes of a Source class (own attributes; geometry is inherited from Feature)

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
name	A human-readable name for the source.	CharacterString	0..1 (optional)

Table 11 — Direct relation between a Source class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
hasType	The type classification of the source.	SourceType	0..1 (optional)

9.5. Source Type Class

A Source Type classifies a Source by its category.

Table 12 — Requirement 3 — Source Type Class

Requirement 3: Source Type Class	/req/datamodel/core/source-type + Each Source Type class shall have the mandatory attributes listed in Table 13.

Table 13 — Attributes of a Source Type class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
label	A human-readable label for the source type.	CharacterString	1 (mandatory)
description	A detailed description of the source type.	CharacterString	0..1 (optional)
definition	The URI linking to an external definition of the source type.	URI	1 (mandatory)

Table 14 — Direct relation between a Source Type class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
-	No direct relations are defined for SourceType in the core model (it is referenced by Source).	-	-

9.6. Mechanism Class

A Mechanism is a classification of the specific physical, chemical, or operational process that constitutes the direct cause or pathway for an emission. It is defined independently of the Source—including its identity, structure, or purpose—allowing Mechanisms to be consistently reused across different types of Source.

Table 15 — Requirement 4 — Mechanism Class

Requirement 4: Mechanism Class	/req/datamodel/core/mechanism + Each Mechanism class shall have the mandatory attributes listed in Table 16. Each Mechanism class shall have the direct relation listed in Table 17.

Table 16 — Attributes of a Mechanism class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
label	A human-readable label for the mechanism.	CharacterString	1 (mandatory)
description	A detailed description of the mechanism.	CharacterString	0..1 (optional)

Table 17 — Direct relation between a Mechanism class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
has Intent	The emission intent associated with the mechanism.	EmissionIntent	1 (mandatory)

9.7. Emission Quantity Class

An Emission Quantity is the physical quantity representing the total mass of substance released to the atmosphere during a defined Emission Event or over a specified time interval.

Table 18 — Requirement 5 — Emission Quantity Class

Requirement 5: Emission Quantity Class	/req/datamodel/core/emission-quantity + Each Emission Quantity class shall have the mandatory attributes listed in Table 19. Each Emission Quantity class shall have the direct relation between an Emission Quantity class and other classes listed in Table 20.

Table 19 — Attributes of an Emission Quantity class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
value	The numeric value of the emission quantity.	Real	1 (mandatory)
quality	A data quality element describing the quality of the emission quantity value.	DQ_Element	0..* (optional)

Table 20 — Direct relation between an Emission Quantity class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
has Unit	The unit of measure associated with the emission quantity.	UnitOfMeasure	1 (mandatory)

9.8. Unit of Measure Class

A Unit of Measure is a reference quantity chosen from a unit equivalence group (Source: ISO/OGC 19156:2023)

Table 21 — Requirement 6 — Unit of Measure Class

Requirement 6: Unit of Measure Class	/req/datamodel/core/unit-of-measure + Each Unit of Measure class shall have the mandatory attributes listed in Table 22.

Table 22 — Attributes of a Unit of Measure class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
label	A human-readable label for the unit of measure.	CharacterString	1 (mandatory)
symbol	A short symbol representing the unit of measure.	CharacterString	1 (mandatory)
definition	The URI linking to an external definition of the unit of measure.	URI	1 (mandatory)

Table 23 — Direct relation between a Unit of Measure class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
-	No direct relations are defined for UnitOfMeasure in the core model.	-	-

9.9. Temporal Bound Class

A Temporal Bound is a value object representing a temporal determination (e.g., start time or end time) that MAY have associated data quality metadata. The determination procedure and supporting evidence for a Temporal Bound are tracked at the Emission Event level.

Table 24 — Requirement 7 — Temporal Bound Class

Requirement 7: Temporal Bound Class	/req/datamodel/core/temporal-bound + Each Temporal Bound class shall have the mandatory attributes listed in Table 25.

Table 25 — Attributes of a Temporal Bound class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
time	The time instant value of this Temporal Bound.	TM_Instant	1 (mandatory)
quality	A data quality element describing the quality of the temporal bound.	DQ_Element	0..* (optional)

Table 26 — Direct relation between a Temporal Bound class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
-	No direct relations are defined for TemporalBound in the core model (determination procedure and evidence are tracked at the EmissionEvent level).	-	-

9.10. Observation Class

An Observation is an act carried out by an observer to determine the value of an observable property of an object (feature-of-interest) by using a procedure, with the value provided as the result (Source: ISO/OGC 19156:2023). In EmissionML, an Observation is evidence that may support an Emission Quantity or Temporal Bound determination.

NOTE: The Ultimate Feature of Interest of an Observation identifies a Feature — which may be a Source or another feature at a different spatial scale — associated with the Emission Event. It is common for a single Emission Event to be observed by multiple Observations whose Ultimate Features of Interest are defined at different spatial scales. For example, a satellite remote sensing image Observation typically has an area-based Ultimate Feature of Interest (e.g.,

a facility area or region), whereas the same Emission Event may also be observed by a person carrying an Optical Gas Imaging camera, for which the Ultimate Feature of Interest is a specific Source such as a component of an item of equipment from which pollutants are released.

Table 27 — Requirement 8 — Observation Class

Requirement 8: Observation Class	/req/datamodel/core/observation + Each Observation class shall be an ISO/OGC 19156:2023 (OGC OMS 3.0) Observation.

9.11. Emission Intent Enumeration

Emission Intent is a code list describing whether an emission is intentional, unintentional, or unknown.

Table 28 — Requirement 9 — Emission Intent Enumeration

Requirement 9: Emission Intent Enumeration	/req/datamodel/core/emission-intent + The Emission Intent enumeration shall support the enumeration values listed in Table 29.

Table 29 — Enumeration values of Emission Intent

NAME	DEFINITION
intentional	The emission occurred intentionally.
unintentional	The emission occurred unintentionally.
unknown	The intent of the emission is unknown.

9.12. Procedure Class

A Procedure is a description of steps performed (Source: ISO/OGC 19156:2023). In EmissionML, Procedure serves as the base class for process descriptions such as DeterminationProcedure.

Table 30 — Requirement 12 — Procedure Class

Requirement 12: Procedure Class	/req/datamodel/core/procedure + Each Procedure class shall be an ISO/OGC 19156:2023 (OGC OMS 3.0) Procedure.

Table 31 — Attributes of a Procedure class

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
-	No own attributes are defined for Procedure in the core model (see the standard for complete specification).	-	-

Table 32 — Direct relation between a Procedure class and other class types

ROLE	DESCRIPTION	TARGET CLASS TYPE	MULTIPLICITY AND USE
-	No direct relations are defined for Procedure in the core model (it is referenced by DeterminationProcedure via inheritance).	-	-

9.13. Determination Procedure Class

A Determination Procedure describes the steps performed to determine the quantity or temporal bounds of an Emission Event. DeterminationProcedure inherits from Procedure, aligning it with the OMS 3.0 process model.

Table 33 — Requirement 10 — Determination Procedure Class

Requirement 10: Determination Procedure Class	/req/datamodel/core/determination-procedure + Each Determination Procedure class shall inherit from Procedure. Each Determination Procedure class shall have the mandatory attributes listed in Table 34.

Table 34 — Attributes of a Determination Procedure class (own attributes)

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
label	A human-readable label for the determination procedure.	CharacterString	1 (mandatory)

NAMES	DEFINITION	DATA TYPES AND VALUES	MULTIPLICITY AND USE
description	A detailed description of the determination procedure.	CharacterString	0..1 (optional)
definition	The URI linking to an external definition of the determination procedure.	URI	0..1 (optional)

A

ANNEX A (INFORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE (NORMATIVE)

A ANNEX A (INFORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE (NORMATIVE)

A.1. Abstract tests for Emission Event Conceptual Data Model Core

A.1.1. Emission Event Conceptual Data Model Core

Table A.1 — Conformance test — Emission Event Conceptual Data Model Core

Conformance class	/conf/datamodel/core
Requirements	/req/datamodel/core
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.2. Emission Event

Table A.2 — Conformance test — Emission Event

Conformance class	/conf/datamodel/core/emission-event
Requirements	/req/datamodel/core/emission-event

Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.3. Source

Table A.3 — Conformance test — Source

Conformance class	/conf/datamodel/core/source
Requirements	/req/datamodel/core/source
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.4. Source Type

Table A.4 — Conformance test — Source Type

Conformance class	/conf/datamodel/core/source-type
Requirements	/req/datamodel/core/source-type
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.5. Mechanism

Table A.5 — Conformance test — Mechanism

Conformance class	/conf/datamodel/core/mechanism
Requirements	/req/datamodel/core/mechanism
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.6. Emission Quantity

Table A.6 — Conformance test — Emission Quantity

Conformance class	/conf/datamodel/core/emission-quantity
Requirements	/req/datamodel/core/emission-quantity
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.7. Unit of Measure

Table A.7 — Conformance test — Unit of Measure

Conformance class	/conf/datamodel/core/unit-of-measure
Requirements	/req/datamodel/core/unit-of-measure
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.8. Temporal Bound

Table A.8 — Conformance test — Temporal Bound

Conformance class	/conf/datamodel/core/temporal-bound
Requirements	/req/datamodel/core/temporal-bound
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.9. Observation

Table A.9 — Conformance test — Observation

Conformance class	/conf/datamodel/core/observation
Requirements	/req/datamodel/core/observation
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.10. Emission Intent

Table A.10 — Conformance test — Emission Intent

Conformance class	/conf/datamodel/core/emission-intent
Requirements	/req/datamodel/core/emission-intent
Test purpose	Verify that all requirements from the requirements class have been fulfilled.

Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.11. Determination Procedure

Table A.11 — Conformance test — Determination Procedure

Conformance class	/conf/datamodel/core/determination-procedure
Requirements	/req/datamodel/core/determination-procedure
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.12. Feature

Table A.12 — Conformance test — Feature

Conformance class	/conf/datamodel/core/feature
Requirements	/req/datamodel/core/feature
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

A.1.13. Procedure

Table A.13 — Conformance test — Procedure

Conformance class	/conf/datamodel/core/procedure

Requirements	/req/datamodel/core/procedure
Test purpose	Verify that all requirements from the requirements class have been fulfilled.
Test method	Inspect the documentation of the application, schema or profile.
Test type	Capability

B

ANNEX B (INFORMATIVE) RELATIONSHIP WITH OGC FEATURES AND OBSERVATIONS

B ANNEX B (INFORMATIVE) RELATIONSHIP WITH OGC FEATURES AND OBSERVATIONS

B.1. Overview

EmissionML is a domain-specific conceptual model that builds on two foundational OGC concepts: **Features** (ISO 19109 General Feature Model) and **Observations** (ISO/OGC 19156:2023, OMS 3.0). This annex explains how EmissionML relates to each and why explicit domain modeling is preferred over generic usage.

Figure B.1 illustrates the conceptual layering of EmissionML on top of these foundational standards.



Figure B.1 — Conceptual layering of EmissionML on foundational ISO/OGC standards

B.2. EmissionML and OGC Features

The OGC General Feature Model (ISO 19109) defines a *Feature* as an abstraction of a real-world phenomenon — any entity with an identity, properties, and optionally a geometry. EmissionML makes this alignment explicit by introducing a concrete **Feature** class (stereotyped `<<ISO 19109>>`) into the conceptual model.

The Feature class carries a mandatory `geometry` attribute of type `GM_Object` and serves as the base class for domain-specific feature types. **Source** inherits from Feature, gaining its geometry by inheritance. This structural inheritance — rather than a notional stereotype — makes the ISO 19109 alignment unambiguous and machine-verifiable.

Because Feature is concrete, an Observation's `ultimateFeatureOfInterest` can reference any Feature — not only a Source. This enables observations whose feature of interest is defined at a different spatial scale (e.g., a facility area, a region, or a monitoring zone) to participate in the evidence chain without being forced into the Source class.

EmissionEvent is also a real-world phenomenon — an occurrent that unfolds over time. In principle, an Emission Event *could* be modeled as a generic Feature. However, EmissionML gives it explicit structure: temporal bounds (start time, end time), a quantity of emitted substance, a mechanism describing the physical or operational process, an intent classification, and an evidence chain linking the event to supporting Observations.

Without this explicit modeling, a Source would be indistinguishable from any other Feature, and an emission event would be "just another Feature" with ad-hoc properties. The semantic relationships that give emission data its meaning — `hasSource`, `hasMechanism`, `hasQuantity`, `hasStartTimeEvidence` — would be lost or require convention-based interpretation.

B.3. EmissionML and OMS 3.0 Observations

OMS 3.0 (ISO/OGC 19156:2023) defines an Observation as an act of determining the value of an observable property. An Observation has a well-defined structure: a feature of interest, an observed property, a procedure, and a result.

EmissionML incorporates OMS 3.0 Observation **by reference** (Requirement 8) — it does not redefine or extend the Observation class. In EmissionML, Observations serve as **evidence** supporting emission quantity and temporal bound determinations, linked through the `hasQuantityEvidence`, `hasStartTimeEvidence`, and `hasEndTimeEvidence` associations.

One might ask: *Why not model the entire emission event as an Observation result?* Because an Emission Event is richer than what a single Observation captures. An Emission Event has a source, a mechanism, an intent, multiple temporal bounds, and can be supported by *multiple* Observations at different spatial and temporal scales. For example:

- A satellite remote sensing Observation may detect a methane plume over a broad area.

- An Optical Gas Imaging (OGI) camera Observation may pinpoint the leak to a specific component.
- A continuous emissions monitoring system (CEMS) Observation may quantify the emission rate over time.

All three Observations can serve as evidence for a single Emission Event, each contributing to the determination of quantity, start time, or end time. The Observation's `ultimateFeatureOfInterest` references a Feature — which may be a Source or any other Feature at a different spatial scale. The satellite Observation's feature of interest may be a Feature representing an entire facility, while the OGI Observation's feature of interest is a Source representing a single valve.

B.4. EmissionML and OMS 3.0 Procedures

OMS 3.0 defines a **Procedure** as "a description of steps performed" and introduces **ObservingProcedure** as a specialization that describes steps performed to determine the value of an observable property. EmissionML follows this same specialization pattern.

The EmissionML conceptual model introduces a **Procedure** class (stereotyped `<<ISO 19156:2023>>`) as the base class for process descriptions. **DeterminationProcedure** inherits from Procedure and describes the steps performed to determine a value — such as an emission quantity or temporal bound. This structural inheritance mirrors how ObservingProcedure specializes Procedure in OMS 3.0.

By making Procedure an explicit base class rather than a notional reference, EmissionML ensures that its process descriptions are structurally aligned with OMS 3.0 — not merely by naming convention, but by class hierarchy. This parallels the Feature/Source pattern: just as Source inherits from Feature to make ISO 19109 alignment concrete, DeterminationProcedure inherits from Procedure to make OMS 3.0 alignment concrete.

B.5. Why Explicit Domain Modeling

The alternative. One could model everything with generic Features and Observations — Sources as plain Features, emission data as Observation results, and relationships as ad-hoc properties. This approach uses only existing OGC standards without defining new classes.

The problem. Generic modeling loses domain semantics. Without EmissionML's explicit classes, systems cannot:

- distinguish a Source from any other Feature,
- enforce that an emission has a Mechanism and an Intent,

- trace the evidence chain from Observation to Emission Quantity to Emission Event,
- validate that required relationships are present (e.g., every Emission Event must have a Source, a Mechanism, and a Determination Procedure).

What explicit modeling provides:

Interoperability	Systems exchanging EmissionML data share a common vocabulary. EmissionEvent, Source, Mechanism, and EmissionQuantity are unambiguous — they mean the same thing in every implementation.
Validation	Requirements can be formally specified and enforced. For example, Requirement 1 mandates that every Emission Event has a Source, a Mechanism, start time, quantity, and their corresponding Determination Procedures.
Usability	Domain experts work with emission concepts directly — *emission events*, *sources*, *mechanisms* — rather than mapping to and from generic abstractions. This reduces the cognitive burden and the risk of misinterpretation.

Analogy. Just as CityGML defines explicit Building, Road, and Vegetation classes rather than using generic Features, EmissionML defines explicit emission domain classes. The General Feature Model provides the abstract foundation; EmissionML provides the domain-specific vocabulary that makes emission data interoperable and actionable.

BIBLIOGRAPHY

BIBLIOGRAPHY

[1] Katharina Schleidt, Ilkka Rinne: OGC 20-082r4, *Topic 20 — Observations, measurements and samples*. Open Geospatial Consortium (2023). http://www.opengis.net/doc/as/om/3.0.