OGC® DOCUMENT: YY-999

External identifier of this OGC® document: http://www.opengis.net/doc/WP/geosparql3d

Open Geospatial Consortium

GEOSPARQL 3D WHITE PAPER

TECHNICAL PAPER

DRAFT

Version: 1.0
Submission Date: 2029-03-30
Approval Date: 2029-03-30
Publication Date: 2029-03-30
Editor: Editor One, Editor Two

Notice: This document is not an OGC Standard. This document is an OGC Technical Paper and is therefore not an official position of the OGC membership. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an OGC Standard. Further, an OGC Technical Paper should not be referenced as required or mandatory technology in procurements.

License Agreement

Use of this document is subject to the license agreement at https://www.ogc.org/license

Copyright notice

Copyright © 2026 Open Geospatial Consortium
To obtain additional rights of use, visithttps://www.ogc.org/legal

Note

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

CONTENTS

I. KEYWORDS vi

II. PREFACE vii

III. SECURITY CONSIDERATIONS viii

IV. SUBMITTING ORGANIZATIONS ix

V. SUBMITTERS ix

1. SCOPE 2

2. CONFORMANCE 4

3. NORMATIVE REFERENCES 6

4. TERMS AND DEFINITIONS 8

5. ABSTRACT 10

6. KEYWORDS 12

7. CONVENTIONS 14

8. INTRODUCTION 16

9. MOTIVATION 18
- 9.1. Why do we want 3D semantic modeling? 18
  - 9.1.1. A geo-spatial 3D specification would support data consumers by: 19
  - 9.1.2. A geo-spatial 3D specification would support data providers by: 19

10. RELATED WORK 21
- 10.1. CityGML 21
  - 10.1.1. CityJSON and CityRDF 21
- 10.2. Medicine & Chemistry 22
- 10.3. 3D data formats and ontologies 23
  - 10.3.1. STereoLithography (STL) 23
  - 10.3.2. Wavefront OBJ Format (OBJ) 23
  - 10.3.3. Polygon File Format (PLY) 23
  - 10.3.4. CARARE Metadata Schema 24
  - 10.3.5. IIIF 3D 24

10.3.6. X3D and X3D Ontology ... 24
10.3.7. Geometry Metadata Ontology (GOM) ... 24
10.3.8. Ontology for Managing Geometry (OMG) ... 24
10.3.9. File Ontology for Geometry Formats (FOG) ... 25
10.4. To consider ... 25
10.5. Cultural Heritage ... 25
10.5.1. Use Cases ... 26
10.5.2. Research applications making use of 3D models in Cultural Heritage ... 26
10.5.2.1. 3D models of cuneiform tablets ... 26
10.6. IFC and BIM ... 27
10.6.1. Industry Foundation Classes (IFC) and BIM ... 27
10.6.1.1. Product model ... 27
10.6.1.2. Evolving views on geometry ... 28
10.6.1.3. Use cases ... 29
10.6.1.4. Implications and questions: ... 29
10.7. Implementations ... 30
10.7.1. CGAL → SFCGAL → PostGIS ... 30
10.7.2. OpenCASCADE ... 30
10.7.2.1. OpenCASCADE-inspired BRep ontology ... 30
10.7.2.2. Topologic ... 30
10.7.3. BRep vs mesh/polyhedron ... 30

11. CURRENT CAPABILITIES ... 33
11.1. GeoSPARQL ... 33
11.1.1. Requirements addressed ... 33
11.1.1.1. Dimensionality ... 33
11.1.1.2. Vocabulary ... 34
11.1.1.3. Core Module ... 34
11.1.1.4. Query functions with 3D support ... 36
11.1.2. Adoption of GeoSPARQL 1.1 ... 37
11.1.2.1. GeoSPARQL Aligments ... 37
11.1.2.2. Geometry Topology Extension ... 37
11.1.2.3. RDFS Entailment Extension ... 37
11.1.2.4. Query Rewrite Extension ... 37

12. REQUIREMENTS FOR GEOSPARQL 3D ... 39
12.1. 5.1 Existing implementation of 3D geometry in GeoSPARQL ... 39
12.1.1. Proposed extensions for GeoSPARQL 3D ... 39
12.1.1.1. Extension 1: 3D representations ... 39
12.1.1.2. Extension 2: Relations of 3D geometries ... 40
12.1.1.3. Extension 3: Appearance of 3D geometries ... 40
12.1.1.4. Extension 4: Multi-component 3D geometries ... 41
12.1.1.5. Extension 5: Positioning of 3D geometries ... 41
12.1.1.6. Extension 6: Alignments of GeoSPARQL 3D ... 42
12.1.1.7. Extension 7: Alignments of Engineering CRS to Geospatial CRS ... 42
12.1.1.8. Extension 8: Geometry Extrusion ... 43
12.1.1.9. Extension 9: Geometry Attributes ... 43

12.1.1.10. Extension 10: Non-topological Query Functions — 3D Extension 44
12.2. 5.2 3D Geometry available in IFC 44
12.3. 5.3 Vanilla 3D geometry handling in the Semantic Web 45
12.4. 5.4 Concluding overview of requirements for 3D geometry in the semantic web 45

13. BENEFICIARIES AND BENEFITS 47
13.1. Semantic-functional value of 3D-GeoSPARQL 47
13.1.1. Meaningful creation and querying of 3D geometry 47
13.1.2. Meaningful creation and querying of 3D topological relationships 47
13.1.3. Derivation of geometric and topological knowledge 48
13.2. Value for user experience, visualization, and application use of 3D-GeoSPARQL 48
13.2.1. Visualization 48
13.2.2. Calculation and analysis 48
13.2.3. Spatial querying 48
13.2.4. Machine control 49
13.2.5. Modeling, simulation and planning 49
13.3. Added value of the 3D-GeoSPARQL for Organisations 49
13.3.1. Brings together different domains (GIS, BIM, CG) 49
13.3.2. Enables extension to vocabularies from other domains 49
13.3.3. Facilitates better interoperability between knowledge domains with spatial components (geography, aerospace, architecture, product design, (bio)chemistry, IoT, ...) 49

14. ANNEX N: ALIGNMENT GEOSPARQL AND OPEN SOURCE RELATIONAL DATABASES WITH GEOSPATIAL SUPPORT 51

15. ALIGNMENT: GEOSPARQL AND OPEN SOURCE RELATIONAL DATABASES WITH GEOSPATIAL SUPPORT 53
15.1. Formatting functions 53
15.2. Convert geometries 54
15.3. Create geometries 56
15.4. Edit geometries 63
15.5. Topological Relations 72
15.6. Measure 76
15.7. Count 80
15.8. Properties 81
15.9. Topography 86
15.10. Triangulation 87
15.11. Export/export 88
15.12. Other 89

16. ANNEX B: ALLIGNMENT OF GEOMETRY 103

17. ANNEX O: HISTORY 120

BIBLIOGRAPHY 124

I KEYWORDS

The following are keywords to be used by search engines and document catalogues.

OGC, GeoSPARQL, 3D

II PREFACE

To come...

III SECURITY CONSIDERATIONS

The following security considerations apply...

IV SUBMITTING ORGANIZATIONS

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- Organization one
- Organization two
- Organization three

V SUBMITTERS

NAME	AFFILIATION	OGC MEMBER
Nicholas J. Car	KurrawongAI	Yes

1

SCOPE

1 SCOPE

2

CONFORMANCE

2 CONFORMANCE

3

NORMATIVE REFERENCES

3 NORMATIVE REFERENCES

There are no normative references in this document.

4

TERMS AND DEFINITIONS

4 TERMS AND DEFINITIONS

No terms and definitions are listed in this document.

5

ABSTRACT

5 ABSTRACT

To come...

6

KEYWORDS

6 KEYWORDS

To come...

7

CONVENTIONS

7 CONVENTIONS

8

INTRODUCTION

8 INTRODUCTION

OGC GeoSPARQL is an open standard that enables storage and exchange of spatial data on the Web, based on the Resource Description Framework (RDF). In 2020 the OGC white paper Benefits of Representing Spatial Data Using Semantic and Graph Technologies was published. It explained the benefits of GeoSPARQL and described the ways in which GeoSPARQL version 1.0 could be improved. In the meantime, GeoSPARQL version 1.1 has been published, having many improvements described in aforementioned white paper, see also this introduction to GeoSPARQL 1.1 [26].

Although not specifically bound, GeoSPARQL 1.1 is mainly geared towards spatial objects having zero to two dimensions. In other words, things that can be displayed on a flat surface. However, for three-dimensional spatial objects both supply and demand are increasing.

Two new versions of GeoSPARQL are in development: 1.2 and 1.3. GeoSPARQL 1.2 will be an adaption of GeoSPARQL 1.1 which enables GeoSPARQL to be published as an ISO standard. Version 1.2 will have no substantive changes with respect to version 1.1. GeoSPARQL 1.3 is expected to have extended capabilities supporting three-dimensional (3D) space. Not only would that make GeoSPARQL more useful for 3D geospatial data, it would also help in industries and knowledge domains that are not mainly focused on geospatial data, like Building Information Modelling (BIM) and Computer Graphics (CG). This paper describes which extensions to GeoSPARQL for 3D are possible, which are most desirable, and how they could be achieved.

This paper consists of three main parts. The first section describes current capabilities of GeoSPARQL: in its current state, GeoSPARQL does allow modelling three-dimensional objects, but with relevant limitations. The second section describes requirements for extended 3D capabilities in GeoSPARQL. This is based on a market consultation, which resulted in a collection of use cases for additional 3D capabilities. By analysing those use cases, as well as current developments within and outside the OGC, insight in the most needed extensions to GeoSPARQL can be obtained. Requirements are then weighed against feasibility; some extensions are easier to achieve than others. The third and final section describes the expected benefits for additional 3D capabilities in GeoSPARQL for different domains and different roles.

This paper should be interesting for the following audiences:

- Current and prospective users of GeoSPARQL;
- Current and prospective implementers of GeoSPARQL;
- Members of related OGC working groups.

A deep understanding of the Semantic Web and graph technologies is not required for readers of this white paper, but some interest in those topics is assumed, as well as familiarity with the aformentioned white paper Benefits of Representing Spatial Data Using Semantic and Graph Technologies. This paper focuses on specifically on 3D capabilities of GeoSPARQL, not its general benefits.

9

MOTIVATION

9 MOTIVATION

9.1. Why do we want 3D semantic modeling?

The white paper: “OGC Benefits of Representing Spatial Data Using Semantic and Graph Technologies” describes the beneficiaries and benefits of representing data, including geospatial data, using semantic and graph technologies Abhayaratna2020wp. This section describes the motivation of adding 3D functionality to the GeoSPARQL standard.

While humans can often resolve 3D spatial questions such as “Is cube A inside cylinder B?” — even when the underlying data comes from different systems like GIS and BIM — this typically relies on implicit understanding, conventions, or direct communication between the data creators. For datasets to be meaningfully aligned, the people who created them often need to clarify assumptions, data structures, coordinate systems, or modeling intentions. Without such human-to-human explanation, machines struggle to interpret spatial relationships across heterogeneous sources. A conversion process is required, in which data is made homogeneous for analysis through extraction, transformation, and loading. Based on a homogeneous dataset, conclusions can then be drawn. Performing conversions may result in geometric simplifications, which can limit or even eliminate the functionality of spatial queries Biljecki2019. If one desires digital, automated processing or analysis of 3D spatial questions without requiring conversion, spatial information must be structured in an explicitly machine-readable format. When this is done, initiatives based on federated systems with heterogeneous datasets can obtain computer-generated answers to spatial 3D queries. This requires semantic alignment and standardized geometry processing in machine-driven analysis. In other words, a common vocabulary is needed to semantically define the 3D objects and its 3D sptatial function.

Imagine a constructor who wants to use real-time sensor data at a construction site in combination with modelled 3D data and 3D base registration data. By combining this the person wants to visualize the site, perform accurate spatial checks and calculations, and automatically update machine instructions for safe, efficient and autonomous execution”

The system uses 3D GeoSPARQL to integrate the data of the 3D design model, the 3D base registration model and 3D real-time sensor data to: - Spatially associate sensor data with objects in the design and registration model - Calculate the permissible tolerances - Detect the deviations - Dynamic adjust the design model - Instruct the machine with the changes - Visualize the new situation

For both humans and machines, it must be unambiguous what is meant by the queries that are needed to do the job and the resulting answers. It should not matter whether the data is provided in a 3D-GIS, 3D-BIM or 3D-CG standard vocabulary.

9.1.1. A geo-spatial 3D specification would support data consumers by:

- access and understanding of 3D-geometry and 3D-topology from multiple sources;
- the integration of 3D-data geospatial and non-geospatial;
- data quality evaluation of the given 3D-data;
- Geometric and topological description in natural language.

9.1.2. A geo-spatial 3D specification would support data providers by:

- Maximizing the use of 3D-geometry and 3D-topology data;
- Defining multiple 3D topology or geometries;
- Assuring the quality of 3D geospatial data.

10

RELATED WORK

10 RELATED WORK

This is still just a dump of resources. To be transformed into actual text.

10.1. CityGML

CityGML [koble2005citygml] is an open standardized data model for the exchange of 3D models of cities and landscapes. Since its standardization by OGC, CityGML has seen a wide variety of proposed extensions and alignments to other data standards.

10.1.1. CityJSON and CityRDF

[27] proposed the extension of the CityGML and its accompanying serialization CityJSON as an ontology model. Currently, the CityRDF standardization group works towards the standardization of this CityGML data model in RDF.

The proposed CityRDF model, even though focused on CityGML and 3D building contents, contains valuable data descriptions which could be generalized in a GeoSPARQL 3D approach. One such element is the description of the appearance of a 3D-modeled building using colors or textures, so-called surface materials. In addition, CityGML includes relations of 3D primitives between each other, which could serve as an inspiration for similary-named functions or properties in the GeoSPARQL 3D ontology model.

[27] describes the CityGML Ontology, which is an ontology model to formalize the CityGML standard towards a representation in OWL. It shows a workflow of identification, classification and selection of the relevant data points needed to describe 3D city models in OWL as derived from building and city models. In addition, it introduces the concept of Level of Information Need, defining the granularity of the information on the various levels of the building and the types of information retrieval — direct/indirect, i.e. information which is commonly obtained directly from a dataset or using a calculation or reasoning approach. The paper exemplifies the concept in a study case for property unit cost and indoor daylight. The contribution outlined here became the basis of the CityGML ontology which can serve as one broad application area for GeoSPARQL 3D.

Following on this publication [22] presents a system architecture and a set of interfaces that can represent city modeling approaches using dynamic geospatial knowledge graphs. The paper proves the viability of a transition between a SQL based system for 3D building management to a SPARQL based system using a SQL2SPARQL Transformer component. It therefore proves the feasibility of employing linked open data technologies for 3D building data and in particular the CityGML model in practice.

[30] introduces CityGML 3.0 with a newly added Core module including a new space concept and Level Of Detail concept. The given publication sets the standard especially for Level of Detail in 3D buildings, which may be considered for adoption as GeoSPARQL 3D concepts too.

In addition, CityGML 3.0 proposes the addition of 3D point clouds for the representation of 3D goemetires of physical spaces and space boundaries. A mapping from IFC to CityGML 3.0 is also proposed by these authors.

CityGML 3.0 therefore represents many of the elements that a GeoSPARQL 3D ontology would need to implement on a more abstract level and can give ideas about future query functions to be implemented in the GeoSPARQL query language.

In addition, a master thesis hansson2024citygml proved the feasibility of not only converting CityGML to a knowledge graph representation, but also its application in triple stores such as Ontop or 3DCityDB. The mapping of CityGML to the knowledge graph was tested using a set of SPARQL queries retrieving different components of building parts. While the thesis could construct a knowledge graph representation from CityGML, it points out that the incorporation of sptaial operations is left to future work and could provide a possible field for GeoSPARQL 3D adoption.

Finally, [21] proposed OntoCityGML, an extension go the CityGML ontolog https://www.sciencedirect.com/science/article/pii/S2666546821000574?via%3Dihub Semantic 3D City Database — An enabler for a dynamic geospatial knowledge graph

Other details and history of Onto CityGML.

CityRDF working group https://github.com/ogcincubator/cityrdf

10.2. Medicine & Chemistry

The medicine and chemistry domains contain a variety of usecases for 3D applications.

In particular, 3D metadata of microscopy is a common application field, which yielded for instance the 3D Microscopy Metadata Standards (3D-MMS) [32] developed by the BRAIN 3D Microscopy Working Group. This standard helps ensuring that a 3D microscopy dataset is sufficiently described to support its re-use by other scientists not involved in data creation. Its adoption will therefore enable investigators willing to share their data to evaluate and decide which data can be combined.

https://onlinelibrary.wiley.com/doi/abs/10.1111/cgf.13083 Ontology-Based Representation and Modelling of Synthetic 3D Content: A State-of-the-Art Review

[24]

A range of approaches have been proposed to permit semantic representation and modelling of synthetic 3D content. These approaches differ in the methodologies and technologies used as well as their scope and application domains. This paper provides a review of the current state of the art in representation and modelling of 3D content based on semantic web ontologies, together with a classification, characterization and discussion of the particular approaches.

https://www.inderscienceonline.com/doi/abs/10.1504/IJMSO.2017.087702 A novel ontology for 3D semantics: ontology-based 3D model indexing and content-based video retrieval applied to the medical domain

[25]

This paper presents the most comprehensive formally grounded 3D ontology to date that maps the entire XSD-based vocabulary of the industry standard X3D (ISO/IEC 19775-19777) to OWL 2, complemented by fundamental concepts and roles of the 3D modelling industry not covered by X3D.

10.3. 3D data formats and ontologies

A new GeoSPARQL standard should be compatible with existing approaches to encode 3D data. Semantic technologies should enable users to encode important metadata in the knowledge graph, while retaining the possibility to use already well-known 3D geometry formats either as String literals or file references. bonduel2019including shows how common widespread geometry formats could be included into knowledge graphs, which could be one starting point to investigate the integration within GeoSPARQL.

10.3.1. STereoLithography (STL)

STL files describe only the surface geometry of a three-dimensional object without any representation of color, texture or other common CAD model attributes. The STL format specifies both ASCII and binary representations and was invented by the Albert Consulting Group for 3D Systems in 1987. Nowadays it is mainly used for 3D printing purposes, which makes is a plausible candidate for support in GeoSPARQL 3D settings of movable objects such as in cultural heritage. Since the STL format does not contain a geospatial reference, the reference needs to be provided externally if STL files were to be used in a geospatial context. However, STL objects could be used in local CRS contexts as well.

10.3.2. Wavefront OBJ Format (OBJ)

The OBJ format is a file format developed by Wavefront Technologies for the Advanced 3D Visualizer animation package. Its roots therefore lie in the world of 3D animation. The format represents vertex coordinates, texture coordinates, as well as vertex normals, parameter space vertices and faces of a 3D model. These are all elements which would need to be considered and supported in an upcoming GeoSPARQL 3D release.

10.3.3. Polygon File Format (PLY)

The Polygon File Format is a format which was designed to store 3D data from 3D scanning environments, which makes it especially widespread in the Cultural Heritage application area. The format consists of a vertex list and a faces list with optional parameters per vertex. Like the

OBJ format, supporting PLY would imply including support for vertices and faces of a 3D model and their relationships in a knowledge graph.

10.3.4. CARARE Metadata Schema

The CARARE metadata schema d2013carare is a harvesting schema intended for delivering metadata about an organisation's online collections, heritage assets and their digital resources. The strength of the schema lies with its ability to support the full range of descriptive information about monuments, building, landscape areas and their representations. The CARARE metadata schema builds on existing standards and best practice from a number of different countries in Europe and the rest of the world.

10.3.5. IIIF 3D

The International Image Interoperability Framework (IIIF) standard snydman2015international is currently developing a specification for the standardization of 3D viewers. The viewer specification includes the visualization of 3D models including lighting positions, a scene graph and annotations in the form of additional 3D objects added to a 3D scene. A GeoSPARQL 3D standard might need to be compatible with, or include a compatibility statement of, converting 3D objects encoded in GeoSPARQL to the IIIF viewer specification. A prototype implementation might be necessary to comply with this specification.

10.3.6. X3D and X3D Ontology

The X3D format feichtenhofer2020×3d, brutzman2010×3d, X3DOM behr2009x3dom and its Ontology version brutzman2020×3d provide a data format and a blueprint for how 3D data is handled in computer vision approaches. X3D is an interesting format to investigate for 3D components which need to be modeled within a GeoSPARQL 3D specification. It is a likely candidate for a literal format and might be integrated using interlinking approaches to the already existing X3D vocabulary. However, since X3D was invented with computer vision approaches in mind it does not define any geospatial aspects that could be considered by a GeoSPARQL 3D implementation.

10.3.7. Geometry Metadata Ontology (GOM)

The Geometry Metadata Ontology (GOM) introduces classes for surfaces which are common in the 3D world, but uncommon for 3D geometries, for instance Meshes or NURBS surfaces. The ontology can serve as an inspiration for extensions in GeoSPARQL 3D and may or may not be fully or partly adopted in the process of standardization.

10.3.8. Ontology for Managing Geometry (OMG)

The Ontology for Managing Geometry (OMG) describes states and derivation of geometries which may be useful to the description of data in GeoSPARQL 3D. For example. an extrusion in

3D from a 2D geometry template would have a derivation relation from the 2D geometry which one might want to see modeled in GeoSPARQL 3D.

10.3.9. File Ontology for Geometry Formats (FOG)

The File Ontology for Geometry Formats (FOG) provides a bridge between ontology descriptions of geometries and data file descriptions of 3D contents. Since many 3D datasets are of considerable size, their inclusion into the knowledge graph as String literals might hinder the query performance of said knowledge graph. It therefore stands to reason whether to adopt the same or a similar method of geometry access that FOG provides for GeoSPARQL 3D.

10.4. To consider

https://link.springer.com/article/10.1007/s10845-023-02246-6 Ontology of 3D virtual modeling in digital twin: a review, analysis and thinking

[33]

To help novice engineers understand and scheme 3D virtual modeling in digital twin for future research and applications, this paper reviews 106 digital twin 3D modeling cases with their characteristics, including deployment targets, purposes & roles, collaborative models, data flows, the autonomy of 3D modeling, fidelity, twinning rates, enabling technologies, and enabling tools.

Open standard for particle-mesh data (openPMD)

The openPMD standard, short for open standard for particle-mesh data files is not a file format per se. It provides guidance for meta-data and naming schemes. openPMD provides naming and attribute conventions that allow the exchange of particle and mesh based data from scientific simulations and experiments. Its primary goal is to define a minimal set/kernel of meta information that allows to share and exchange data to achieve portability between various applications and different algorithms, a unified open-access description for scientific data (publishing and archiving), and a unified description for post-processing, visualization and analysis. If outputs from programs, devices (such as cameras), simulations or post-processed data-sets, contain a minimal set of meta information as provided by openPMD, data can be exchanged between those with minimal effort, with the same tools used for visualization.

[19]

10.5. Cultural Heritage

In the research domain of cultural heritage, 3D models of either cultural heritage artifacts (possibly georeferenced), 3D models of archaeological sites or simply 3D models of ancient buildings are becoming increasinly common.

10.5.1. Use Cases

Use Cases in the Cultural Heritage domain include, but are not limited to, the following main interests:

Visualization: The visualization of 3D models for the presentation of such 3D models, for example in the context of a museum. 3D models may be styled with a particular set of textures or modeled with a specific set of colours to highlight certain relevant aspects. The visualization of 3D models is currently standardized by the IIIF 3D working group [29], which aims to create viewing parameter descriptions that 3D viewers may implement, similar to the specifications of IIIF 2D for images.

Object Annotation: 3D models are seen as the subject of a research question in absence of the original artifact for political, practical or other restrictive reasons. Out of all known methods of the representation of cultural heritage artifacts, 3D models provide the most detail when being delivered as a digital artifact and are therefore very often preferred in a research context. Researchers mark noteworthy aspects of the cultural artifact as 3D annotations [28] which may include surface descriptions, volumes of the 3D model or 3D models which are created and placed adjacent to the to-be-annotated 3D model [20].

Relation of Objects: Objects of a specific collections always exist in a spatio-temporal context. It is important to relate these representations via meaningful relations, so that relevant objects of a collection can be retrieved more easily

AI Applications in Cultural Heritage: Usage for annotated areas on 3D models or their derivations for machine learning classifications Stotzner_2023_ICCV 10.2312/gch.20231157

Knowledge Graphs as Metadata descriptions: With the advent of more 3D models being published, the relevance of their creation parameters [31], their contents and their object metadata increases for the usecases of filtering them and also for the possibly automated selection of suitable cultural heritage metadata for e.g. machine learning classifications. Currently, many metadata standards fulfil parts of the description chain and a unified vocabulary to described data types seems to be missing.

10.5.2. Research applications making use of 3D models in Cultural Heritage

This section discusses research projects with 3D contents based on the technologies they use as elaborated in the previous section.

10.5.2.1. 3D models of cuneiform tablets

Cuneiform tablets from ancient Iran provide an interesting research area, since they combine a 3D artifact with textual imprints that are of interest to a variety of research communities including Assyriologsts, Digital Humanists, Computational Linguists and last but not least Computer Scientists. The creation of 3D models of cuneiform tablets provides the best accessibility to the specificities of the original artifact in its absence and 3D scans have been

used by computer scientists as the basis for certain machine learning application tasks, even though to this day only as a provision for 2D renderings of their surfaces. Interests of the research community include the description of interesting features such as cuneiform signs on cuneiform tablet surfaces and their connection to other text contents or other cuneiform artifacts. Knowledge graphs provide machine learning approaches Stotzner_2023_ICCV stotzner2023r with unique opportunities to connect different kinds of data using a unified data format.

To describe 3D meshes, several vocabularies have been developed in the context of the cuneiform studies project:

- MeshSPARQL: A vocabulary to describe essential mesh elements
- Gigamesh Metadata Vocabulary: A vocabulary which describes metadata of a 3D model. The metadata can be generated using the Gigamesh Software Framework
- 3DCAP Vocabularies: An ontology model to describe the creation of a 3D model. It has been applied to different scanning softwares

10.6. IFC and BIM

10.6.1. Industry Foundation Classes (IFC) and BIM

BIM is a paradigm in which object-model definitions — with machine-interpretable semantics — are exchanged, rather than relying on CAD drawings that convey only graphical semantics. The predominant open exchange standard is Industry Foundation Classes (IFC). **IFC is unique in the sense that it allows expressing both geometrical as well as non-geometrical semantics.**

Non-geometrical: taxonomy of objects (building elements, relational constructs, scheduling information) and related properties

Geometrical: appromximately 250 constructs related to geometry; even standards with only a geometric focus such as geosparql or collada do not reach that breadth in definitions

IFC has its idiosyncrasies and challenges, but is **unrivaled in terms of market adoption in a highly fragmented industry**.

10.6.1.1. Product model

In IFC, a construction work is decomposed into a set of products. These products can have **multiple representations**. For example, a wall can be described as a solid body as well as a two-dimensional axis. These representations facilitate different views on the same data: an editable line segment or an easily visualized volume. The Object-relational nature of the IFC EXPRESS schema allows intricate relationships such as a representation context that communicates

additional intent for the representation or presentation styles that can be granularly assigned to individual faces.

At the same time, such a product separates the **placement** (an hierarchical transformation) from the actual geometry definition. The consequence of this is that in spite of its object-relational nature, IFC product representations cannot be used for building-level topological relationships between solids, because even if two solids are touching in 3D, the fact the the placement is externalized out of the geometry definition (or the fact that faces are constructed procedurally and do not exist explicitly), means that the two faces cannot be opposite oriented twins. As such, relational geometric constructs such as space boundaries are provided as additional supplementary geometries. (Identifying faces in procedural geometries is also challenging (toplogical naming problem), so using geometric semantic overlays to annotate potentially procedural geometries makes sense)

In principle, the IFC schema has been designed in a modular fashion with independent modules for, for example, geometry, materials and meta-data. However in other cases, **semantics and geometry are intertwined** such as tapered extrusions (lofts) where the begin and end profile of a duct carry important semantics.

IFC also allows for **decomposition**, where a whole is aggregated into multiple parts for richer semantics. This allows for example to connect materials and meta-data to the frame and the glazing separately, while still being able to identify the aggregate as a single window. This is not used as frequently, partially due to inability to efficiently instantiate such aggregates as geometry instances.

10.6.1.2. Evolving views on geometry

IFC is heavily influenced by the ISO 10303 (STEP) family of standards, but over time adopted its own geometric paradigms:

- Procedural geometry and boolean operations became less prominent with the adoption of ReferenceView in IFC4. Tessellated geometry definitions were added for more compact exchange.
- **Infrastructure definitions** were added with precise mathematical transition curves and a composition of a horizontal, vertical and cant (inclination) profile.
- IFC5 with an **explicit** (most likely triangulated) geometry schema at the core, with semantic overlays to encode the same procedural semantics as a non-mandatory or use-case specific layer. Heavily inspired by USD with layer-based composition for collaborative exchange.

Especially the handling of **tolerances** means that the standard cannot effectively prescribe a consistent outcome in all cases. Tolerances are needed for BRep model with non-linear underlying geometry and/or fixed precision coordinate values, e.g higher degree nurbs curves are typically intersected with numerical approximation, so a vertex that connects two of such curves needs to have seen as a sphere with the local tolerance as its radius. This tolerance is also applied to boolean operations: an subtraction volume can be slightly inwards of the first operand but is still expected to pierce through the volume and increase surface genus. This contrasts

with the desire of using IFC as a legal basis in contracts. NB Tolerances stand in the way of using existing approaches for SFA geometry predicates such as PostGIS+SFCGAL which is based on arbitrary precision boolean logic as implemented in CGAL without tolerances.

10.6.1.3. Use cases

The most successful use case on BIM data is **coordination and visualization** where multiple aspect models are geometrically overlaid in order to find issues, which are then communicated to the authoring software where they are addressed. This approach works, because it respects that individual disciplines all have their own specialistic software.

Design to design workflows are much harder to realize, although some Model View Definitions have been developed on top of IFC that enable the transfer of design intent in specific and constrained scenarios, such as precast concrete and structural steel.

Long-term preservation of building information is difficult because of the fact that IFC models are difficult to mutate, because they are so explicit and don't contain the vendor-specific design intelligence. Therefore native software cannot always re-import IFC models, but also the native models degrade over time because of the need to migrate to newer editions of the software. Software that can directly operate on IFC to make modifications is still experimental.

BIM-GIS integration is challenging because it requires familiarity with both domains on where to draw the line between euclidean and non-euclidean geometries and acceptable error metrics.

Simulations on IFC building models are often challenging because the 'bag of individual elements' does not provide a good foundation higher order topological representations required for flow-of-energy type of simulations. For e.g thermal simulation a topological view of space boundaries is required. They have been added as secondary set of ternary relationships, but usage of more specific-purpose and simpler schemas sees still more usage in industry. In general, IFC models are created for a specific purpose and wide-spread usage of those models in nieghbouring domaisn remain challenging because modelling for those neighbouring purposes requires alignment on the worldviews and levels of detail that is often beyond the scope in which such models are procured.

10.6.1.4. Implications and questions:

- Euclidean / non-euclidean; is a CRS required?
- Separate representation+placement → enables efficient reinstantiation, but hinders topological relationships because you require the pair of placement+geometry to locate in space
- Geometry as leaf-values or object-relational model : cannot encapsulate geometry into a single literal, but allows for richer semantics
- BRep model (topology + geometry + orientation + location) vs polyhedral model (e.g halfedge) vs explicit loops of point coordinates
- Procedural vs implicit (e.g constraints) vs explicit (polyhedra)

- Tolerances
- Decomposition inside or outside of the 'geometry ontology'
- Are infra geometries (hor + ver alignment + cant, for positioning and sweeps) in scope?

10.7. Implementations

10.7.1. CGAL → SFCGAL → PostGIS

10.7.2. OpenCASCADE

10.7.2.1. OpenCASCADE-inspired BRep ontology

Perzylo, A., Somani, N., Rickert, M., & Knoll, A. (2015, September). An ontology for CAD data and geometric constraints as a link between product models and semantic robot task descriptions. In 2015 IEEE/RSJ international conference on intelligent robots and systems (IROS) (pp. 4197-4203). IEEE.

https://ieeexplore.ieee.org/abstract/document/7353971

[23]

10.7.2.2. Topologic

Jabi, W., & Chatzivasileiadi, A. (2021, January). Topologic: exploring spatial reasoning through geometry, topology, and semantics. In Formal Methods in Architecture: Proceedings of the 5th International Symposium on Formal Methods in Architecture (5FMA), Lisbon 2020 (pp. 277-285). Cham: Springer International Publishing.

https://topologic.app/

[2]

10.7.3. BRep vs mesh/polyhedron

BRep

- Curved surfaces
- Topology: connected components as shells, solids with inner voids, etc.

- Clean APIs due to inheritance: e.g `fn extrude(Topo) → Topo`, for vertex → edge; edge → face; face → solid; solid → solid
- Extra indirections: edge → vertex[] → point
- Depending on implementation can be inefficient, e.g outer wire of face not explicitly marked need to be checked wrt infinite point
- Data integrity and validation a bit harder

Mesh/polyhedron

- Potentially fewer indirections
- Triangle meshes robust and well understood
- Many different data models though, e.g half-edge (only manifold), indexed faceset (no adjacency info), winged/quad/radial edge

11

CURRENT CAPABILITIES

11 CURRENT CAPABILITIES

11.1. GeoSPARQL

GeoSPARQL is the most common geospatial extension of SPARQL. It was accepted as an OGC standard in 2012 and revised as GeoSPARQL 1.1 in 2024.

According to the standard document, "The OGC GeoSPARQL standard supports representing and querying geospatial data on the Semantic Web. GeoSPARQL defines a vocabulary for representing geospatial data in RDF, and it defines an extension to the SPARQL query language for processing geospatial data".

11.1.1. Requirements addressed

In order to define which capabilities GeoSPARQL needs to adopt for full 3D compatibility, we first take a look at GeoSPARQL 1.1 current capabilities with regards to 3D.

11.1.1.1. Dimensionality

In this white paper, when we discuss three dimensional data, we mean three dimensional geometries; instances of the class geo:Geometry. GeoSPARQL 1.1 defines three different properties for geometry that have to do with dimensionality:

1. geo:dimension, or *topological dimension*: This is the number of perpendicalar directions in which a geometry extends. A point, for example, extends in no direction, so its topological dimension is 0. A line has a length, but no width or height. Its topological dimension is 1. A cube has a topological dimension of 3.

2. geo:coordinateDimension: In the geometric model that GeoSPARQL uses, points are the basic building blocks of geometry. A point geometry can have a different number of coordinates, depending on the space in which it is placed. A point on a flat map, or on the surface of a sphere, needs two coordinates. The *coordinate dimension* is the number of coordinates in the points that define a Geometry.

3. geo:spatialDimension: In order to support linear referencing, geometries in GeoSPARQL can have a measure value. This is a relative position along a line or a curve, and does not extend the Geometry in space. The *spatial dimension*, therefore, can be used to denote the number of coordinates in a point, excluding the measurement value.

The extended capabilities for GeoSPARQL discussed in this white paper concern the cases where the *spatial dimension* (wich can be expressed with property geo:spatialDimension) of geometry has the value 3.

The table below shows the values of the three dimension properties for some Geometries (expressed as Well Known Text (WKT)).

Table 1

GEOMETRY (WKT)	GEO:DIMENSION	GEO:COORDINATEDIMENSION	GEO:SPATIALDIMENSION
point (4 15)	0	2	2
point Z (4 15 3)	0	3	3
linestring (4 15, 13 2)	1	2	2
point M (4 15 60)	0	3	2
point ZM (4 15 3 60)	0	4	3

11.1.1.2. Vocabulary

GeoSPARQL version 1.1 consists of a Core module, a Topology Vocabulary extension, a Geometry extension, a Geometry Topology extension, an RDFS Entailment extension, and a Query Rewrite extension. Each of these modules will be briefly explained below.

11.1.1.3. Core Module

GeoSPARQL version 1.1 includes a CORE module. This defines the basic classes, relationships, and literals. These classes are suitable for both 2D and 3D.

11.1.1.3.1. Topology Vocabulary Extension

This extension provides standard definitions for spatial relationships that can exist between one spatial object and another.

Relations between geometries have been defined using three different sets of rules:

- Simple Features Relations
- Egenhofer Relations
- Region Connection Calculus RCC8

These topological definitions specify topological relations in a 2D-context.

11.1.1.3.2. Geometry Extension

GeoSPARQL 1.1 geometry module defines a class `Geometry` as a subclass of `SpatialObject`.

An instance of `Geometry` is not restricted to two dimensions.

A fine-grained classification of `Geometry` can use the Simple Feature Vocabulary which extends the class `Geometry` with further types, such as *Point*, *Polygon* etc.

The Simple Features vocabulary allows for the definition of 3D variants of:

- (Multi)Points
- (Multi)LineStrings
- (Multi)Polygons
- Polyhedralsurface

It does not include commons 3D primitives, such as *Cube* or *Mesh* surfaces which are integral parts of 3D representations. Nor does it include extruded geometry.



Figure 1 — Possible approaches for representing 3D objects in IFC

Concerning metadata of 3D models, GeoSPARQL 1.1 provides properties which can be reused in 3D contexts. In particular, the properties are:

- `geo:hasVolume`
- `geo:hasMetricVolume`

Further 3D-related metadata properties such as projection matrices are not part of the current GeoSPARQL 1.1 standard.

A first requirement for 3D support is the ability to save 3D data in a knowledge graph.

The Geometry extension enables geometries to be defined within the GeoSPARQL framework. Supported geometry formats include RDF literals in WKT, GML, GeoJSON, and KML.

These literals are investigated for the storage of 3D data.



Figure 2 — Difference between 2D, 2.5D and 3D geometry

Table 2

Literal Type	Z-Coordinate Supported	2.5D	3D
WKT Literal	Yes	Yes	Yes
GML Literal	Yes	Yes	Only with extension Schema
KML Literal	Yes	Yes	As import from COLLADA
GeoJSON Literal	Yes	Yes	Yes
DGGS Literal			

GeoSPARQL 1.1 also does not restrict the usage of coordinate reference systems with 3D support. There are currently almost 300 coordinate reference systems in the database epsg.io which can be used to describe 3D data encoded in the GeoSPARQL graph literals listed above.

GeoSPARQL allready supports linking multiple geometries (e.g., 2D and 2.5D) to a single feature. We aim to extend this with 3D geometries.

For example, a tree in the real world may be represented in databases with both a 2D and a 3D geometry.

This should not require duplication of the tree entity — there can be one tree instance with both geometries linked, avoiding redundancy in the data model.

11.1.1.4. Query functions with 3D support

GeoSPARQL 1.1 functions currently do not offer fully-featured 3D support. However, there are functions which may take into account the Z coordinate, if they are available.

Table 3

GeoSPARQL function	Z-Coordinate Supported	2.5D	3D
geof:is3D	Yes	Yes	Yes
geof:minZ	Yes	Yes	Yes
geof:maxZ	Yes	Yes	Yes

These functions check for the presence of Z coordinates or filter out maximum and minimum Z coordinates of the given geometry.

11.1.2. Adoption of GeoSPARQL 1.1

11.1.2.1. GeoSPARQL Aligments

See Annex A and Annex B (Text to write)

11.1.2.2. Geometry Topology Extension

Another extension is the Geometry Topology extension. This provides query functions that return relationships between different geometries based on the topology vocabulary extension.

11.1.2.3. RDFS Entailment Extension

The RDFS Entailment extension provides rules for reasoning over geometries. Based on specific statements, additional information can be inferred. This kind of logical inference can also be applied to geometry. GeoSPARQL includes logic for reasoning over simple features geometries.

11.1.2.4. Query Rewrite Extension

GeoSPARQL allows queries such as whether “Feature A” is located within “Feature B” using its vocabulary. The Query Rewrite extension specifies a RIF rule that enables query rewriting. However, this extension does not support the rewriting of 3D queries.

12

REQUIREMENTS FOR GEOSPARQL 3D

12 REQUIREMENTS FOR GEOSPARQL 3D

12.1. 5.1 Existing implementation of 3D geometry in GeoSPARQL

This section provides an overview of feedback received on the current version of the GeoSPARQL standard (version 1.1) regarding 3D usage. It helps to identify some of the barriers to use, and to outline requirements that have not been addressed that may encourage greater uptake.

12.1.1. Proposed extensions for GeoSPARQL 3D

12.1.1.1. Extension 1: 3D representations

12.1.1.1.1. GitHub Issue URI

https://github.com/opengeospatial/ogc-geosparql/issues/583

12.1.1.1.2. Category

Semantic improvement

12.1.1.1.3. Description

GeoSPARQL should include ways to represent 3D data in a knowledge graph.

3D data should be included in common 3D formats and 3D data should be includable as a text literal and a file representation.

Some common formats which could be considered for inclusion are:

- Polygon File Format (PLY)
- Wavefront OBJ Format (OBJ)
- GLTF Format (GLTF)
- X3D Format

12.1.1.2. Extension 2: Relations of 3D geometries

12.1.1.2.1. GitHub Issue URI

https://github.com/opengeospatial/ogc-geosparql/issues/416

12.1.1.2.2. Category

Semantic improvement

12.1.1.2.3. Description

GeoSPARQL should include ways to represent relations between 3D geometries and relations between 3D geometries and geometries of lower dimensions. The relations should be expressable in property relations and should be queryable using SPARQL extension functions.

12.1.1.3. Extension 3: Appearance of 3D geometries

12.1.1.3.1. GitHub Issue URI

- https://github.com/opengeospatial/ogc-geosparql/issues/584
- https://github.com/opengeospatial/ogc-geosparql/issues/592

12.1.1.3.2. Category

Semantic improvement

12.1.1.3.3. Description

GeoSPARQL should include ways to represent materials and textures of 3D geometries, so that geometries can be styled accordingly.

Materials include:

- Colors of surfaces with light diffusion parameters
- Images as textures, which are associated with surfaces of the 3D object

12.1.1.4. Extension 4: Multi-component 3D geometries

12.1.1.4.1. GitHub Issue URI

https://github.com/opengeospatial/ogc-geosparql/issues/591

12.1.1.4.2. Category

Semantic improvement

12.1.1.4.3. Description

GeoSPARQL should include ways to define multi-component 3D geometries, whereas each component expresses its own semantics. For example, parts of a building could have different semantics according to the function of the building components and would be classified as such in an RDF graph.

12.1.1.5. Extension 5: Positioning of 3D geometries

12.1.1.5.1. GitHub Issue URI

- https://github.com/opengeospatial/ogc-geosparql/issues/587
- https://github.com/opengeospatial/ogc-geosparql/issues/588
- https://github.com/opengeospatial/ogc-geosparql/issues/589
- https://github.com/opengeospatial/ogc-geosparql/issues/591

12.1.1.5.2. Category

Semantic improvement

12.1.1.5.3. Description

GeoSPARQL should include ways to position 3D geometries in a 3D space. Commonly 3D geometries are rotated, translated and scaled using commonly defined operators in computer graphics. Similar operations are needed for the relative positioning of 3D objects in GeoSPARQL, as properties and potentially as functions.

12.1.1.6. Extension 6: Alignments of GeoSPARQL 3D

12.1.1.6.1. GitHub Issue URI

- https://github.com/opengeospatial/ogc-geosparql/issues/590
- https://github.com/opengeospatial/ogc-geosparql/issues/574
- https://github.com/opengeospatial/ogc-geosparql/issues/571

12.1.1.6.2. Category

Semantic improvement

12.1.1.6.3. Description

GeoSPARQL 3D should be aligned to other vocabularies and standard which currently provide 3D support in different knowledge domains. Especially alignments to ifcOWL and the X3D vocabulary would position the GeoSPARQL vocabulary as a link between these different standards.

12.1.1.7. Extension 7: Alignments of Engineering CRS to Geospatial CRS

12.1.1.7.1. GitHub Issue URI

https://github.com/opengeospatial/ogc-geosparql/issues/586

12.1.1.7.2. Category

Semantic improvement

12.1.1.7.3. Description

GeoSPARQL 3D should provide the opportunity to align a local coordinate system in which most 3D geometries are defined with a coordinate reference. While this work might only be partially done within the scope of GeoSPARQL itself, GeoSPARQL should be aligned with the emerging Ontology CRS developments of OGC and provide necessary functions or properties to create the link.

12.1.1.8. Extension 8: Geometry Extrusion

12.1.1.8.1. GitHub Issue URI

- https://github.com/opengeospatial/ogc-geosparql/issues/556
- https://github.com/opengeospatial/ogc-geosparql/issues/547

12.1.1.8.2. Category

Semantic improvement

12.1.1.8.3. Description

GeoSPARQL 3D should provide the opportunity to extrude 2D geometries to 3D geometries and vice versa.

12.1.1.9. Extension 9: Geometry Attributes

12.1.1.9.1. GitHub Issue URI

- https://github.com/opengeospatial/ogc-geosparql/issues/568
- https://github.com/opengeospatial/ogc-geosparql/issues/550
- https://github.com/opengeospatial/ogc-geosparql/issues/549
- https://github.com/opengeospatial/ogc-geosparql/issues/548
- https://github.com/opengeospatial/ogc-geosparql/issues/558

12.1.1.9.2. Category

Semantic improvement

12.1.1.9.3. Description

GeoSPARQL 3D should provide functions and properties that describe essential properties of a 3D Geometry such as its minimum and maximum height, width and depth and its CompactnessRatio.

12.1.1.10. Extension 10: Non-topological Query Functions — 3D Extension

12.1.1.10.1. GitHub Issue URI

- https://github.com/opengeospatial/ogc-geosparql/issues/556

12.1.1.10.2. Category

Semantic improvement

12.1.1.10.3. Description

GeoSPARQL 3D should provide the opportunity to execute non-topological query functions on 2D and 3D geometries commonly used in geospatial databases. Proposed extensions include following functions:

- geometry extrusion to the specified line segment
- geometry extrusion to the specified height
- spatiotemporal geometry extrusion to the specified line segment with specific start and end time

12.2. 5.2 3D Geometry available in IFC

This section describes what kind of geometry is available in IFC, and how that relates to (1) different modelling kernels, and (2) geoSPARQL and geospatial geometry engines.

@Thomas Krijnen, Alex Donkers, Pieter Pauwels == to write here please

12.3. 5.3 Vanilla 3D geometry handling in the Semantic Web

This section describes in what other ways 3D geometry is currently handled in the Semantic Web, for example in BOT ontology, OMG and FOG ontologies, and few more.

12.4. 5.4 Concluding overview of requirements for 3D geometry in the semantic web

A concluding summary with a list of requirements to be taken into account for future development in different places and organisations.

13

BENEFICIARIES AND BENEFITS

13 BENEFICIARIES AND BENEFITS

This section describes the beneficiaries and benefits of representing data, including geospatial data, using semantic and graph technologies. Furthermore, a collection of use cases demonstrate how semantic and graph technologies are used together with spatial data to tackle real world problems.

13.1. Semantic-functional value of 3D-GeoSPARQL

Value for data reasoning, formal description, and semantic interoperability

13.1.1. Meaningful creation and querying of 3D geometry

Whether manually or programmatically defining 3D geometries in BIM, GEO or CG environments, the GeoSPARQL standard could provide or connect to vocabulary to represent 3D structures. A 3D cube, for example, can be represented in multiple ways:

- As a set of bounding points, lines, and faces;
- As a base surface with an extrude function;
- As an 3D geometric primitive (e.g., the concept of a 'cube' as a spatial figure).

Once GeoSPARQL offers the means to define and link 3D geometries in these different ways, it will allow both humans and machines to interpret and interact with the data effectively.

13.1.2. Meaningful creation and querying of 3D topological relationships

Is "3D Geometry A" inside, touching, overlapping, intersecting or above "3D Geometry B"?

Being able to describe and use such topological relationships is crucial for conducting spatial analyses, formulating rules, and deriving knowledge from different heterogeneous datasets.

Beyond describing topological relationships, one should be able to query them:

What is the spatial relationship between 3D Geometry A and 3D Geometry B?

Such queries should return the appropriate topological result (e.g., "intersects"), which is essential for use cases like clash detection in design validation

13.1.3. Derivation of geometric and topological knowledge

From explicitly modeled geometric and topological data, one should be able to infer implicit knowledge.

For instance, if 3D Geometry A is 3D inside 3D Geometry B, then we can infer that:

> A does not “touch” B, and A does not “overlap” with B,

even if these facts are not explicitly stated.

For entailment an application that is compliant with the geo-spatial 3D specification would be able to answer queries like: “Does this tree have a 3D geometry?”

If the tree is defined using a MultiSolid geometry, then the answer should be “yes,” even if this is not explicitly declared as such.

13.2. Value for user experience, visualization, and application use of 3D-GeoSPARQL

13.2.1. Visualization

There is a growing need to visualize how 3D data in BIM and GIS relate to one another. Stakeholders want to see BIM and/or 3D Geo data of a newly planned structure visualized within the 3D Geo and/or BIM context of the existing digital city. A shared vocabulary that can present both domains in an integrated way supports this goal.

13.2.2. Calculation and analysis

Semantic modelled 3D-model enables powerful computation and analysis. Analytical results can be displayed in dashboards operating within the GeoBIM domain. This creates a bridge between asset management (typically GIS-oriented) and project management (typically BIM-oriented), allowing for cross-domain collaboration and decision-making.

13.2.3. Spatial querying

Spatial querying is a key function within a federated GeoBIM Network. Questions such as “What material is located in this area?” or “Where is space available for new cables and pipelines?” are examples of 3D spatial queries that can be answered when GeoSPARQL 3D is functioning effectively across systems and semantics.

13.2.4. Machine control

A shared semantic GeoBIM Network also supports machine control. The GIS domain typically describes the existing situation, while the BIM domain describes the intended or future situation. This combination can be used to automatically instruct and guide machines in the built environment.

13.2.5. Modeling, simulation and planning

A network of datasets with 3D-data should support the modeling, simulation and planning of future changes to the built environment. Users — whether human or machine — can use the network and GeoSPARQL 3D to propose and model modifications in either BIM or GIS formats. A well-functioning 3D semantic GeoBIM Network enables this kind of forward-looking spatial planning and design.

13.3. Added value of the 3D-GeoSPARQL for Organisations

13.3.1. Brings together different domains (GIS, BIM, CG)

GeoSPARQL 3D can help in bringing together different domains that work with 3D information.

13.3.2. Enables extension to vocabularies from other domains

The vocabulary can have the possiblity to extend to vocabulaires with 3D geometry or topology from other domains, for example the Building Ontology Topology (BOT) or RELOC Ontology. Multi-domain models with georeferenced 3D and 2D city models could be also linked by CityRDF ontology based on CityGML 3.0 standard. GeoSPARQL 3D would be important enabler for data retrieval, update and analysis for such models. In addition to ontologies, it can also establish relationships to 3D file formats from other domains, such as glTF.

13.3.3. Facilitates better interoperability between knowledge domains with spatial components (geography, aerospace, architecture, product design, (bio)chemistry, IoT, ...)

A unified geometric language can help by migrating ideas and methods across fields, accelerating innovation. For example a parametic design algoritm, rule, or llm making use of geometry and topology originated in aerospace, can be re-used in the architecture domain.

14

ANNEX N: ALIGNMENT GEOSPARQL AND OPEN SOURCE RELATIONAL DATABASES WITH GEOSPATIAL SUPPORT .

14 ANNEX N: ALIGNMENT GEOSPARQL AND OPEN SOURCE RELATIONAL DATABASES WITH GEOSPATIAL SUPPORT .

Based on:

GeoSPARQL: PostGIS: https://postgis.net/docs/PostGIS_Special_Functions_Index.html#PostGIS_3D_Functions (PostGIS Functions that support 3D) H2GIS: https://h2gis.readthedocs.io/en/latest/index.html (paragraph Geometry 3D/4D functions) Spatiallite: https://www.gaia-gis.it/gaia-sins/spatialite-sql-latest.html

15

ALIGNMENT: GEOSPARQL AND OPEN SOURCE RELATIONAL DATABASES WITH GEOSPATIAL SUPPORT

15 ALIGNMENT: GEOSPARQL AND OPEN SOURCE RELATIONAL DATABASES WITH GEOSPATIAL SUPPORT

15.1. Formatting functions

Table 4

GeoSPARQL	PostGIS	H2GIS	Spatialite
geof:asGeoJSON	st_asgeojson	ST_AsGeoJson	asgeojson
geof:asGML	st_asgml	st_asgml	asgml
geof:asKML	st_askml	ST_AsKML	askml
geof:asWKT		st_aswkt	aswkt
geof:asEWKB	st_asewkb	AsEWKB	asewkb
	st_ashexewkb		
	ST_AsX3D		asx3d
	link:st_asewkt		asewkt
	st_assvg		assvg
	st_astext	st_astext	astext
			astwkb
	st_asbinary	st_asbinary	asbinary
geof:asDGGS			
geof:asGeocode			

			asfgf
			asgpb
			asencodedpolyline
			atm_astext
			gcp_astext
			proj_asprojstring
			proj_aswkt

15.2. Convert geometries

Table 5

GeoSPARQL	PostGIS	H2GIS	Spatialite
	st_Force2d	st_force2d	
	st_ForceCurve		
	st_force_3d	st_force3d	
	st_force_3dm	st_force3dm	
	st_force_3dz		
	st_force_4d	st_Force4D	
	st_force_collection		
			forceasnull
	st_forcerhr		
	CG_ForceLHR		forcelhr

st_forcerSFS		
ForcePolygonCCW		forcepolygonccw
ForcePolygonCW		forcepolygoncw
		normalizelonlat
		project
		spatnetfromgeom
		spatnetfromtgeo
		sridfromauthcrs
st_shift_longitude		st_shift_longitude
st_wkbtosql		st_wkbtosql
st_wkttosql		st_wkttosql
		tinypointencode
		togars
		uncompressgeometry
		xb_getgeometry
	st_projectpoint	
	st_tomultipoint	
	st_tomultisegments	
st_curvetoline		
st_geogfromtext		
st_geogfromwkb		
st_geographyfromtext		

	st_geometryfromtext		
	st_gmltosql		
	st_linefromwkb		
	st_linestringfromwkb		
	st_linetocurve		

15.3. Create geometries

Table 6

	st_extrude	st_extrude	
	CG_Extrude		
		st_geometryshadow	
geof:boundary	st_boundary	st_boundary	boundary
geof:boundingCircle		st_boundingcircle	
	st_BoundingDiagonal		
	st_minimumboundingcircle		
geof:concaveHull			concavehull
geof:convexHull	st_convexhull	st_convexhull	convexhull
	CG_3DConvexHull		
geof:difference	st_difference	st_difference	difference
	CG_3DDifference		
geof:envelope	st_envelope	st_envelope	envelope

geof:symDifference	st_symdifference	st_symdifference	symdifference
geof:union	st_union	st_union	gunion
	CG_3DUnion		
geof:patchN	st_PatchN		
	CG_MakeSolid		
	ST_LineSubstring		
			atm_create
			atm_createrotate
			atm_createscale
			atm_createtranslate
			atm_createxroll
	st_bdmpolyfromtext		bdmpolyfromtext
			bdmpolyfromwkb
	st_bdpolyfromtext		bdpolyfromtext
			bdpolyfromwkb
			blobfromfile
	st_buildarea		buildarea
			buildcirclembr
			buildmbr
			castautomagic
			casttoblob
			casttodouble

			casttogeometycollection
			casttointeger
			casttolinestring
			casttomulti
		st_tomultiline	casttomultilinestring
			casttomultipoint
			casttomultipolygon
			casttopoint
			casttopolygon
			casttosingle
			casttotext
			casttoxy
			casttoxym
			casttoxyz
			casttoxyzm
	st_collect	st_collect	collect
	st_collectionextract	st_collectionextract	collectionextract
			createnetwork
			createroutingnodes
			createtopogeo
			createtopology
			dissolvepoints

		dissolvesegments
		elementarygeometries
		extractmultilinestring
		extractmultipoint
		extractmultipolygon
		geomcollfromtext
		geomcollfromwkb
		geometrycollectionfromtext
		geometrycollectionfromwkb
		geometrypointencode
st_geomfromewkb		geomfromewkb
st_geomfromewkt		geomfromewkt
		geomfromexifgpsblob
		geomfromfgf
st_GeomFromGeoJSON		geomfromgeojson
st_geomfromgml	st_geomfromgml	geomfromgml
		geomfromgpb
st_geomfromkml		geomfromkml
st_geomfromtext	st_geomfromtext	geomfromtext
st_geomfromwkb	st_geomfromwkb	geomfromwkb
		geosconcavehull
		gpkgmakepoint

			gpkgmakepointm
			gpkgmakepointz
			gpkgmakepointzm
			gunion
			hexagonalgrid
			hilbertcode
			linefromencodedpolyline
	st_linefromtext	st_linefromtext	“linefromtext linestringfromtext”
			“linefromwkb linestringfromwkb”
			linesfromrings
			linestringfromtext
			linestringfromwkb
			makearc
			makecircle
			makecircularsector
			makecircularstripe
		st_makeellipse	makeellipse
			makeellipticarc
			makeellipticsector
	st_makeline	st_makeline	makeline
	st_makepoint	st_makepoint	makepoint
	st_makepointm		makepointm

			makepointz
			makepointzm
	st_makepolygon	st_makepolygon	makepolygon
			mlinefromtext
			mlinefromwkb
			mpointfromtext
	st_mpointfromtext	st_mpointfromtext	“mpointfromtext multipointfromtext”
			“mpointfromwkb multipointfromwkb”
			mpolyfromtext
			mpolyfromwkb
			multilinestringfromtext
			multilinestringfromwkb
			multipolygonfromtext
			multipolygonfromwkb
			orientedenvelope
	st_pointfromtext	st_pointfromtext	pointfromtext
	st_pointfromwkb	st_pointfromwkb	pointfromwkb
	st_pointonsurface	st_pointonsurface	pointonsurface
			polyfromtext
			polyfromwkb
			polygonfromtext
			polygonfromwkb

	st_polygonize	st_polygonize	polygonize
			squaregrid
	st_point	st_point	st_point
			topogeo_polygonize
			triangulargrid
			voronojdiagram
		st_isovist	
		st_linefromwkb	
		st_makeenvelope	
		st_makegrid	
		st_makegridpoints	
		st_minimumrectangle	
	st_mlinefromtext	st_mlinefromtext	
	st_mpolyfromtext	st_mpolyfromtext	
		st_octogonalenvelope	
	st_polygonfromtext	st_polyfromtext	
		st_polyfromwkb	
		st_ringbuffer	
		st_ringsidebuffer	
		st_sidebuffer	
		st_tessellate	
	CG_Tesselate		

	st_linefrommultipoint		
	st_makebox2d		
	st_makebox3d		
	st_makeenvelope		
	st_multi		
	st_polygon		

15.4. Edit geometries

Table 7

GeoSPARQL	PostGIS	H2GIS	Spatialite
		st_addz	
	AddGeometryColumn		addgeometrycolumn
	st_addmeasure		addmeasure
	st_addpoint	st_addpoint	addpoint
			addedgemodface
			addedgenewfaces
			addfdogeometrycolumn
	DropGeometryColumn		
			addisoedge
			addisonetnode
			addisonode

		addlink
		addtemporarygeometrycolumn
		gpkgaddgeometrycolumn
		gpkgaddgeometrytriggers
		gpkgaddspatialindex
		gpkgaddtiletriggers
		topogeo_addlinestring
		topogeo_addlinestringnoface
		topogeo_addpoint
		xb_addfileid
		xb_addparentid
	st_interpolate3dline	
ST_InterpolatePoint		interpolatepoint
ST_LineInterpolatePoint		
ST_LineInterpolatePoints		
ST_3DLineInterpolate Point		
		line_interpolate_equidistant_ points
st_line_interpolate_point		line_interpolate_point
		trajectoryinterpolatepoint
	st_multiplyz	
st_reverse	st_reverse	reverse
	st_reverse3dline	

	UpdateGeometrySRID		
			storedvar_updatetitle
			storedvar_updatevalue
			se_updatevectorcoverageextent
			storedproc_updatesqlbody
			storedproc_updatetitle
			topogeo_updateseeds
			toponet_updateseeds
			updatelayerstatistics
			updatemetacatalogstatistics
		st_zupdatelineextremities	
		st_updatez	
geof:buffer	st_buffer	st_buffer	buffer
geof:transform	st_transform	st_transform	transform
geof:metricBuffer			
geof:transform CRS84			
	CG_ChaikinWmooting		
	ST_Scroll		
	ST_WrapX		
			atm_invert
			atm_multiply
			atm_rotate

	atm_scale
	atm_transform
	atm_translate
	atm_xroll
	atm_yroll
	blobtofile
	bufferoptions_reset
	bufferoptions_setendcapstyle
	bufferoptions_setjoinstyle
	bufferoptions_setmitrelimit
	bufferoptions_ setquadrantsegments
	changeedgegeom
	changelinkgeom
	compressgeometry
	discardfdogeometrycolumn
	discardgeometrycolumn
	drapeline
	drapelineexceptions
	dropnetwork
	droptopology
	dropvirtualgeometry
	ensureclosedrings

	st_expand	st_expand	expand
			gcp_transform
			gcp2atm
			geosdensify
			geosmakevalid
			gpkginsertepsgsrid
			inittopogeo
			inittoponet
	st_line_substring		line_substring
	st_linemerge	st_linemerge	linemerge
			linescutatnodes
			loginetfromtgeo
	st_makevalid	st_makevalid	makevalid
			makevaliddiscarded
			modedgeheal
			modedgesplit
			modgeolinksplit
			modlinkheal
			modloglinksplit
			moveisonetnode
			moveisonode
			newedgeheal

	newedgessplit
	newgeolinksplit
	newlinkheal
	newloglinksplit
	offestcurve
	reduceprecision
	reflectcoordinates
	reflectcoords
	remedgemodface
	remedgenewface
	remisoedge
	remisonetnode
	remisonode
	removelink
st_removepoint	removepoint
	ringscutatnodes
	rotatecoordinates
	rotatecoords
	sanitizegeometry
	scalecoordinates
	scalecoords
st_segmentize	segmentize

			setdecimalprecision
			setendpoint
			setmultiplepoints
	st_setpoint		setpoint
			setstartpoint
			shiftcoordinates
			shiftcoords
	st_simplify	st_simplify	simplify
	CG_Simplify		
	st_ simplifypreservetopology	st_simplifypreservetopology	simplifypreservetopology
			singlesidedbuffer
		st_snap	snap
			snapandsplit
	st_snaptogrid		snaptogrid
		st_split	split
			splitleft
			splitright
			st_cutter
	st_node	st_node	st_node
			st_subdivide
	st_translate	st_translate	st_translate
	CG_3DTranslate		

	swapcoordinates
swapordinates	
	swapcoords
	topogeo_clone
	topogeo_createtopolayer
	topogeo_ disambiguatesegmentedges
	topogeo_inittopolayer
	topogeo_ insertfeaturefromtopolayer
	topogeo_modedgeheal
	topogeo_newedgeheal
	topogeo_newedgessplit
	topogeo_removedanglingedges
	topogeo_removedanglingnodes
	topogeo_removesmallfaces
	topogeo_removetopolayer
	topogeo_snaplinetoseed
	topogeo_snappedgeotable
	topogeo_snappointtoseed
	topogeo_subdividelines
	topogeo_toposnap
	toponet_clone
	toponet_ disambiguatesegmentlinks

			transformxy
			transformxyz
	st_UnaryUnion		unaryunion
		st_densify	
		st_explode	
	ST_FlipCoordinates	st_flipcoordinates	
		st_normalize	
		st_precisionreducer	
		st_ removeduplicatedcoordinates	
		st_removeholes	
		st_removepoints	
	ST_RemoveRepeated Points	st_removerepeatedpoints	
	st_rotate	st_rotate	
	CG_3DRotate		
	st_rotatex		
	CG_RotateX		
	CG_RotateY		
	CG_RotateZ		
	st_rotatey		
	st_rotatez		
	st_scale	st_scale	
	CG_3DScale		

	CG_3DScaleAroundCenter		
		st_split	
	st_affine		
	st_dump		
	st_DumpPoints		
	st_dumprings		
	st_dumpsegments		
	st_memunion		
	st_transscale		

15.5. Topological Relations

Table 8

GeoSPARQL	PostGIS	H2GIS	Spatialite
geof:sfContains	st_contains	st_contains	contains
geof:ehCoveredBy	st_coveredby		coveredby
geof:ehCovers	st_covers	st_covers	covers
geof:sfCrosses	st_crosses	st_crosses	crosses
geof:sfDisjoint	st_disjoint	st_disjoint	mbrdisjoint
geof:sfEquals	st_equals	st_equals	equals
	TG_Equals		
geof:intersection	st_intersection	st_intersection	intersection

	CG_3DIntersection		
geof:sfIntersects	st_intersects	st_intersects	intersects
	tg_intersects		
	ST_3DIntersects		
geof:sfOverlaps	st_overlaps	st_overlaps	overlaps
	&&&		
	&&&(geometry,gidx)		
	&&&(gidx, geometry)		
	&&&(gidx,gidx)		
geof:sfTouches	st_touches	st_touches	touches
geof:sfWithin	st_within	st_within	within
	st_dfullywithin		
	st_3DDFullyWithin		
geof:ehContains			
geof:ehDisjoint			
geof:ehEquals			
geof:ehInside			
geof:ehMeet			
geof:ehOverlap			
geof:rcc8dc			
geof:rcc8ec			
geof:rcc8eq			

geof:rcc8ntpp			
geof:rcc8ntppi			
geof:rcc8po			
geof:rcc8tpp			
geof:rcc8tppi			
geof:relate	st_relate	st_relate	relate
	st_CPAWithin		
			buildmbrfilter
	st_closestpoint	st_closestpoint	closestpoint
	ST_ClosestPointOfApproach		
	ST_3DClosestPoint		
		st_envelopesintersect	envelopesintersects
			filtermbrcontains
			filtermbrintersects
			filtermbrwithin
			garsmbr
			getfacebypoint
			getfaceedges
			getfacegeometry
			getlinkbypoint
			getnetnodebypoint
			getnodebypoint

		mbrcontains
		mbrdisjoint
		mbrequal
		mbrintersects
		mbroverlaps
		mbrtouches
		mbrwithin
		ptdistwithin
		relatematch
st_setsrid	st_setsrid	setsrid
		sharedpaths
		validatetopogeo
		validlogicalnet
		validspatialnet
st_dwithin	st_dwithin	
	st_lineintersector	
	st_orderingequals	
@		
&&		
&<		
&<|		
&>		

	<<
	<<|
	=
	>>
	|&>
	|>>
	~
	~=
	st_containsproperly
	st_linecrossingdirection
	st_orderingequals
	st_point_inside_circle

15.6. Measure

Table 9

GeoSPARQL	PostGIS	H2GIS	Spatialite
geof:area	st_area	st_area	area
	CG_3DArea	st_3darea	
geof:perimeter	st_perimeter	st_perimeter	perimeter
	st_perimeter2d		
	st_perimeter3d	st_3dperimeter	

geof:metricPerimeter			
geof:length	st_length	st_length	length
	ST_3DLength	ST_3DLength	3dlength
geof:metricArea			
geof:metricLength			
			geodesic length
			geodesicarcarea
			geodesicarcheight
			geodesicarclength
			geodesiccentralangle
			geodesicchordlength
			great circle length
			linestringavgsegmentlength
	st_length_spheroid		
	st_length2d		
	st_length2d_spheroid		
	st_length3d_spheroid		
			linestringminsegmentlength
		st_svf	
		st_sunposition	
geof:distance	st_distance	st_distance	distance
	st_distanceCPA		

geof:metricDistance			
	ST_3DDistance		3ddistance
	CG_Volume		
	ST_GeometricMedian		
			abs
			acos
			asin
			atan
			atan2
	st_azimuth	st_azimuth	azimuth
			ceil
			ceiling
			centimeter
			circularity
			cos
			cot
			curvosityindex
			dd to dms
			decimeter
			degrees
			distancewithin
			dms to dd

			downhillheight
			exp
	st_extent	st_extent	extent
	ST_3DExtent		
			floor
			frechetdistance
			gcp_compute
			geosmaximuminscribedcircle
			geosminimumboundingcenter
			geosminimumboundingcircle
			geosminimumboundingradius
			geosminimumclearance
			geosminimumclearanceline
			geosminimumrotatedrectangle
			geosminimumwidth
			getlayerextent
			getvirtualtableextent
	st_hausdorffdistance		hausdorffdistance
	st_line_locate_point		line_locate_point
	st_locate_along_measure		locatealongmeasure
	st_locate_between_measures		locatebetweenmeasures
	st_maxdistance	st_maxdistance	maxdistance

	3DMaxDistance		3dmaxdistance
	st_shortestline	st_shortestline	shortestline
	st_3dshortestline		
			updownheight
			uphillheight
		st_closestcoordinate	
		st_furthestcoordinate	
		st_locatealong	
	st_longestline	st_longestline	
	st_3DLongestLine		
	st_distance_sphere		
	st_distance_spheroid		

15.7. Count

Table 10

GeoSPARQL	PostGIS	H2GIS	Spatialite
geof:numGeometries	st_numgeometries	st_numgeometries	numgeometries
geof:numPoints	st_numpoints	st_numpoints	numpoints
	st_numpatches		
geof:numInteriorRing			
geof:numPatches			

	ST_NumCurves		
	st_npoints	st_npoints	npoints
	st_nrings		nrings
	st_numinteriorring	st_numinteriorring	numinteriorring
	st_numinteriorrings	st_numinteriorrings	numinteriorrings
	st_locatebetweenelevations		

15.8. Properties

Table 11

GeoSPARQL	PostGIS	H2GIS	Spatialite
		st_is3d	is3d
geof:x	st_x	st_x	x
geof:maxX	st_xmax	st_xmax	
geof:minX	st_xmin	st_xmin	
geof:y	st_y	st_y	y
geof:maxY	st_ymax	st_ymax	
geof:minY	st_ymin	st_ymin	
geof:z	st_z	st_z	z
geof:maxZ	st_zmax	st_zmax	maxz
geof:minZ	st_zmin	st_zmin	minz
geof:m	st_m	ST_M	m

geof:centroid	st_centroid	st_centroid	centroid
geof:geometryN	st_geometryn	st_geometryn	geometryn
geof:getSRID	st_srid	st_srid	srid
	geof:isEmpty	st_isempty	st_isempty
isempty	geof:isSimple	st_issimple	st_issimple
issimple	geof:endPoint	st_endpoint	st_endpoint
endpoint	geof:exteriorRing	st_exteriorring	st_exteriorring
exteriorring	geof:interiorRingN	st_interiorringn	st_interiorringn
interiorringn	geof:isRing	st_isring	st_isring
isring	geof:pointN	st_pointn	st_pointn
pointn	geof:startPoint	st_startpoint	st_startpoint
startpoint	geof:easting		
	geof:northing		
	geof:isClosed	st_isclosed	st_isclosed
isclosed		CG_IsPlanar	
		CG_IsSolid	
		ST_IsCollection	
atm_determinant			
atm_isinvertible			
atm_isvalid			
bufferoptions_getendcapstyle			

bufferoptions_getjoinstyle		
bufferoptions_getmitrelimit		
bufferoptions_getquadrantsegments		
checkwithoutrowid		
checkspatialindex		
checkspatialmetadata	st_coorddim	st_coorddim
coorddimension	st_dimension	st_dimension
dimension		
gcp_isvalid	st_geohash	
geohash	Geometrytype	
geometrytype		
getdecimalprecision		
getgpkgamphibiousmode		
getgpkgmode		
getisometadataid		
getpointindex		
gpkg_isassignable		
gpkggetimagetype		
gpkggetnormalrow		
gpkggetnormalzoom		
hasepsg		
hasfreexl		

hasgcp
hasgeocallbacks
hasgeopackage
hasgeos
hasgeos3100
hasgeos3110
hasgeosadvanced
hasgeosonlyreentrant
hasgeosreentrant
hasgeostrunk
hasiconv
hasknn
haslibxml2
hasmathsql
hasminizip
hasproj
hasproj6
hasrouting
hasrttopo
hastopology
isgeometryblob
iscompressedgeometryblob

ismeasured	ST_IsPolygonCCW	
ispolygonccw	ST_IsPolygonCW	
ispolygoncw	st_isvalid	st_isvalid
isvalid	st_IsValidTrajectory	
		st_isvaliddetail
isvaliddetail	st_isvalidreason	st_isvalidreason
isvalidreason		
isvalidtrajectory		
maxm		
mbrmaxx		
mbrmaxy		
mbrminx		
mbrminy		
minm	st_ndims	
ndims		
selfintersections		
topogeo_getedgeseed		
topogeo_getfaceseed		
topogeo_lineedgeslist		
topogeo_polyfaceslist		
toponet_getlinkseed		
toponet_linelinkslist		

xb_getabstract		
xb_getdocument		
xb_getdocumentsize		
xb_getencoding		
xb_getfileid		
xb_getinternalschemauri		st_compactnessratio
	st_geometrytype	st_geometrytype
		st_geometrytypecode
		st_holes
		st_isrectangle
	box3d	
	st_curveN	
	st_estimated_extent	
	st_extent3d	
	st_hasarc	
	st_hasM	
	st_hasZ	
	st_summary	
	st_zmflag	

15.9. Topography

Table 12

GeoSPARQL	PostGIS	H2GIS	Spatialite
		st_drape	
		st_triangleaspect	
		st_trianglecontouring	
		st_triangledirection	
		st_triangleslope	
		st_voronoi	
	CG_ApproximateMedialAxis		
	CG_Orientation		
	CG_StraightSkeleton		
	CG_Visibility		
			geoslargestemptycircle
	st_mem_size		

15.10. Triangulation

Table 13

GeoSPARQL	PostGIS	H2GIS	Spatialite
		st_constraineddelaunay	constraineddelaunaytriangulation
	st_DelaunayTriangles		
	CG_ConstrainedDelaunayTriangles		
			delaunaytriangulation

			st_delaunay
	CG_AlphaWrapping		

15.11. Export/export

Table 14

GeoSPARQL	PostGIS	H2GIS	Spatialite
			exportdbf
			exportdxf
			exportgeojson2
			exportkml
			exportshp
			importdbf
			importdxf
			importdxffromdir
			importgeojson
			importshp
			importwfs
			importxls
			importzipdbf
			importzipshp
			initfdospatialmetadata

			initspatialmetadata
			initspatialmetadatafull
			insertepsgsrid
			topogeo_exporttopolayer
			topogeo_fromgeotable
			topogeo_fromgeotableext
			topogeo_fromgeotablenoface
			topogeo_fromgeotablenofaceext
			topogeo_togeotable
			topogeo_togeotablegeneralize
			toponet_fromgeotable
			toponet_togeotable
			toponet_togeotablegeneralize
	find_srid		

15.12. Other

Table 15

GeoSPARQL	PostGIS	H2GIS	Spatialite
			autofdostart
			autofdostop
			autogpkgstart

	autogpkgstop
	check_strict_sql_quoting
	checkduplicaterows
	checkgeopackagemetadata
	checkshadowedrowid
	clonetable
	countunsafetriggers
	createclonedtable
	createisometadatatables
	creatembrcache
	createmetacatalogtables
	createmissingrasterlite2columns
	createmissingsystemtables
	createrastercoveragestable
	createrouting
	createrouting_getlasterror
	createspatialindex
	createstylingtables
	createtemporaryspatialindex
	createtopotables
	createuuid
	createvectorcoveragestables

	decodeurl
	dirnamefrompath
	disablegpkgamphibiousmode
	disablegpkgmode
	disablepause
	disablespatialindex
	disabletinypoint
	droptable
	enablegpkgamphibiousmode
	enablegpkgmode
	enablepause
	enabletinypoint
	encodeurl
	eval
	fileextfrompath
	filenamefrompath
	freexl_version
	fullfilenamefrompat
	geos_version
	getcuttermessage
	getdbobjectscope
	getlastnetworkexception

	getlasttopologyexception
	getmimetype
	gpkgcreatebasetables
	gpkgcreatetilestable
	gpkgcreatetileszoomlevel
	indian chain
	indian foot
	indian yard
	international chain
	international fathom
	international foot
	international inch
	international link
	international nautical mile
	international statute mile
	international yard
	invalidatelayerstatistics
	isdecimalnumber
	isexifblob
	isexifgpsblob
	isgifblob
	isinteger

	isjp2blob
	isjpegblob
	islowascii
	isnumber
	ispauseenabled
	ispdfblob
	ispngblob
	istiffblob
	istinypointblob
	istinypointenabled
	isvalidgpb
	iswebpblob
	iszipblob
	kilometer
	libxml2_version
	ln
	log
	log10
	log2
	makestringlist
	md5checksum
	md5totalchecksum

	millimeter
	pause
	pi
	postgresql_getlasterror
	postgresql_resetlasterror
	postgresql_setlasterror
	pow
	power
	proj_getdatabasepath
	proj_guesssridfromshp
	proj_guesssridfromwkt
	proj_guesssridfromzipshp
	proj_setdatabasepath
	proj_version
	radians
	rebuildgeometrytriggers
	recoverfdogeometrycolumn
	recovergeometrycolumn
	recoverspatialindex
	recreateisometarefstriggers
	recreaterastercoveragestriggers
	recreatestylingtriggers

	recreatetopotriggers
	recreatevectorcoveragestriggers
	registerdatalicense
	registerisometadata
	registervirtualgeometry
	removeduplicaterows
	removeextraspaces
	renamecolumn
	renamedatalicense
	renametable
	rl2_mapconfigurationabstractn
	rl2_mapconfigurationnamen
	rl2_mapconfigurationtitlen
	rl2_nummapconfigurations
	rl2_registermapconfiguration
	rl2_reloadmapconfiguration
	rl2_unregistermapconfiguration
	rttopo_version
	se_autoregisterstandardbrushes
	se_registerexternalgraphic
	se_registerrastercoveragekeyword
	se_registerrastercoveragesrid

	se_registerrasterstyle
	se_registerrasterstyledlayer
	se_registerspatialviewcoverage
	se_registertopogeocoverage
	se_registertoponetcoverage
	se_registervectorcoverage
	se_registervectorcoveragekeyword
	se_registervectorcoveragesrid
	se_registervectorstyle
	se_registervectorstyledlayer
	se_registervirtualtablecoverage
	se_reloadvectorstyle
	se_setvectorcoveragecopyright
	se_setvectorcoverageinfos
	se_setvectorcoveragevisibilityrange
	se_unregisterexternalgraphic
	se_unregisterrastercoveragekeyword
	se_unregisterrastercoveragesrid
	se_unregisterrasterstyle
	se_unregisterrasterstyledlayer
	se_unregistervectorcoverage
	se_unregistervectorcoveragekeyword

	se_unregistervectorcoveragesrid
	se_unregistervectorstyle
	se_unregistervectorstyledlayer
	sequence_currval
	sequence_lastval
	sequence_nextval
	sequence_setval
	setdatalicenseurl
	sign
	sin
	spatialite_target_cpu
	spatialite_version
	sqlproc_allvariables
	sqlproc_cookedsql
	sqlproc_execute
	sqlproc_executeloop
	sqlproc_fromfile
	sqlproc_fromtext
	sqlproc_getlasterror
	sqlproc_getlogfile
	sqlproc_isvalid
	sqlproc_numvariables

	sqlproc_rawsql
	sqlproc_return
	sqlproc_setlogfile
	sqlproc_variablen
	sqlproc_varvalue
	sqrt
	stddev_pop
	stddev_samp
	storedproc_createtables
	storedproc_delete
	storedproc_execute
	storedproc_executeloop
	storedproc_get
	storedproc_register
	storedvar_delete
	storedvar_get
	storedvar_getvalue
	storedvar_register
	tan
	u.s. chain
	u.s. foot
	u.s. inch

	u.s. statute mile
	u.s. yard
	unregisterdatalicense
	upgradegeometrytriggers
	var_pop
	var_samp
	wms_createtables
	wms_defaultrefsys
	wms_defaultsetting
	wms_getfeatureinforequesturl
	wms_getmaprequesturl
	wms_registergetcapabilities
	wms_registergetmap
	wms_registerrefsys
	wms_registersetting
	wms_registerstyle
	wms_setgetcapabilitiesinfos
	wms_setgetmapcopyright
	wms_setgetmapinfos
	wms_setgetmapoptions
	wms_unregistergetcapabilities
	wms_unregistergetmap

	wms_unregisterrefsys
	wms_unregistersetting
	xb_cacheflush
	xb_compress
	xb_create
	xb_getlastparseerror
	xb_getlastvalidateerror
	xb_getlastxpatherror
	xb_getparentid
	xb_getpayload
	xb_getschemauri
	xb_gettitle
	xb_iscompressed
	xb_isgpx
	xb_isisometadata
	xb_ismapconfig
	xb_isschemavalidated
	xb_issldsevectorstyle
	xb_issldstyle
	xb_issvg
	xb_isvalid
	xb_isvalidxpathexpression

		xb_loadxml
		xb_mlinefromgpx
		xb_schemavalidate
		xb_setfileid
		xb_setparentid
		xb_storexml
		xb_uncompress
		zipfile_dbfn
		zipfile_numdbf
		zipfile_numshp
		zipfile_shpn
st_accum	st_accum	
	st_googlemaplink	
	st_osmmaplink	

16

ANNEX B: ALLIGNMENT OF GEOMETRY

16 ANNEX B: ALLIGNMENT OF GEOMETRY

Overview of ISO 19107 GML IFC STEP OpenCascade WKT X3D Geometries

Dit overzicht van geometriën laat zien welke geometrieen dicht bij elkaar zitten. Het is geen 10% match

Points:

Table 16

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
		IfcCartesianPoint	cartesian_point	Geom2d_Cartesian Point Geom_Cartesian Point	
GM_ Point	gml: Point			Geom2d_Point Geom_Point	POINT (x y (z) (m))
			cylindrical_point		
			spherical_point		
			polar_point		
		IfcPointByDistance Expression			
		IfcPointOnCurve	point_on_curve		
		IfcPointOnSurface	point_on_surface		
			point_in_volume		
			point_replica		
			degenerate_pcurve		
			evaluated_degenerate_ pcurve		

Lines and Curves:

Table 17

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
GM_Curve	gml:Curve				
GM_Orientable Curve	gml:Orientable Curve				
GM_Arc	gml:Arc				CIRCULARSTRING (x y (z)(m))
GM_Arc ByBulge	gml:ArcByBulge				
GM_ArcString	gml:ArcString				
GM_ArcString ByBulge	gml:ArcString ByBulge				
	gml:Circle ByCenterPoint				
	gml:CubicSpline				
	gml:Knot				
	gml:Affine Placement				
	gml:Abstract Surface				
	gml:Polygon				POLYGON(x y (z) (m))
GM_Polygon	gml:Polygonpatch				
GM_Ring	gml:Ring				
	gml:AbstractRing				
	gml:LinearRing				
	gml:Surface				
	gml:Patches				
	gml:AbstractRing				
GM_Orientable Surface	gml:Orientable Surface				

	gml:Bspline	IfcBSplineCurveWithKnots	B_ splir curv with knot	Geom2d_BSpline Curve Geom_BSpline Curve
		IfcRationalBSplineCurveWith Knots		
GM_Bezier	gml:Bezier		bezi curv	Geom2D_Bezier Curve Geom_Bezier Curve
			ratic b_ splir curv	
			loca b_ splir	
			unif curv	
			quas unif curv	
			loca refir splir curv	
			ratic loca refir splir curv	
			trim curv	Geom2d_Trimmed Curve Geom_Trimmed Curve
		IfcCompositeCurveOnSurface		
		IfcBoundaryCurve	bou curv	
		IfcOuterBoundaryCurve	oute bou curv	

		IfcGradientCurve			
		IfcSegmentedReferenceCurve			
		IfcIndexedPolyCurve			
GM_LineString	gml:LineString Segment				LINESTRING(x y (z)(m))
	gml:LineString	IfcPolyline	poly	TopoDS_Wire	
		IfcTrimmedCurve			
GM_Circle	gml:Circle	IfcCircle	circl	Geom2d_Circle Geom_Circle	
		IfcElipse	elips	Geom2d_Ellipse Geom_Ellipse	
		IfcLine	line	Geom2d_Line Geom_Line	
			hype	Geom2d_ Hyperbola Geom_Hyperbola	
			para	Geom2d_Parabola Geom_Parabola	
	gml:OffsetCurve	IfcOffsetCurve2D	offs curv 2d	Geom2d_Offset Curve Geom_Offset Curve	
		IfcOffsetCurve3D	offs curv 3d		
		IfcOffsetCurveByDistances			
		IfcPcurve	pcur		
			bou pcur		
		IfcPolynomialCurve			
		IfcClothoid	clotl		
			circu invo		

	IfcCosineSpiral			
	IfcSecondOrderPolynomialSpiral			
	IfcThirdOrderPolynomialSpiral			
	IfcSeventhOrderPolynomialSpiral			
	IfcSineSpiral			
	IfcSurfaceCurve	surf curv		
	ifcIntersectionCurve	inte curv		
		sear curv		
		bou surf curv		
		com curv on_ surf		
		curv repli		
	IfcSeamCurve			
			Geom2d_Vector WithMagnitude Geom_Vector WithMagnitude	
				shapeExtend_ ComplexCurve

Surface:

Table 18

ISO 19107	GML	IFC	STI OpenCascade	WKT X3D
GM_Surface	gml:Surface			
GM_Polyhedral Surface	gml:PolyhedralSurface			

GM_Triangulated Surface	gml:TriangulatedSurface	IfcTriangulatedFaceSet	tria fac	
GM_Tin	gml:Tin			
GM_SurfacePatch	gml:AbstractSurfacePatch			
	gml:Triangle			
	gml:Rectangle			
GM_PointGrid	gml:PointGrid			
GM_Parametric CurveSurface	gml:AbstractParametric CurveSurface			
GM_Gridded Surface	gml:AbstractGridded Surface			
		IfcPlane	pla	Geom_Plane
		IfcCylindricalSurface	cyli sur	Geom_Cylindrical Surface
			cor sur	Geom_Conical Surface
		IfcSphericalSurface	sph sur	Geom_Spherical Surface
		IfcToroidalSurface	tor sur	Geom_Toroidal Surface
			deg tor sur	
			dup cyc sur	
		IfcBSplineSurface	b_ spli sur	Geom_BSpline Surface
		IfcBSplineSurfaceWith Knots	b_ spli sur wit knc	
			uni sur	

		uas uni sur	
		bez sur	Geom_BezierSurface
		rati b_ spli sur	
		loc refi spli sur	
		rati loc refi spli sur	
	IfcCurveBoundedPlane IfcCurveBoundedSurface	cur bou sur	
		sur pat	
		off sur	Geom_OffsetSurface
		ori sur	
		sur rep	
			Geom_Surface
			Geom_Osculating Surface
	IfcRectangularTrimmed Surface	rec trin sur	Geom_Rectangular TrimmedSurface
	IfcSectionedSurface		

Primitives:

A primitive (like a block or ellipsoid) can be defined with just a few parameters. It is more efficient than describing the same shape with triangles (mesh) or surfaces (B-rep). It keeps files smaller and mathematically exact.

Table 19

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
		IfcBlock	block	TopoDS_Solid (BRepPrimAPI_MakeBox)	
		IfcRectangularPyramid	rectangular_pyramid		
GM_Cone	gml:Cone	IfcRightCircularCone	right_circular_cone eccentric_cone	TopoDS_Solid (BRepPrimAPI_MakeCone)	
GM_Cylinder	gml:Cylinder	IfcRightCircular Cylinder	right_circular_ cylinder	TopoDS_Solid (BRepPrimAPI_MakeCylinder)	
			ellipsoid		
				TopoDS_Solid (BRepPrimAPI_MakeHalfSpace)	
				TopoDS_Solid (BRepPrimAPI_MakePrism)	
				TopoDS_Solid (BRepPrimAPI_MakeRevol)	
				TopoDS_Solid (BRepPrimAPI_Make Revolution)	
GM_Sphere	gml:Sphere	IfcSphere	sphere	TopoDS_Solid (BRepPrimAPI_MakeSphere)	
				TopoDS_Solid (BRepPrimAPI_MakePipe)	
				TopoDS_Solid (BRepPrimAPI_MakePipeShell)	
			torus	TopoDS_Solid (BRepPrimAPI_MakeTorus)	
			right_angular_wedge	TopoDS_Solid (BRepPrimAPI_MakeWedge)	
			tetrahedron		
			convex_hexahedron		
			faceted_primitive		

Boolean Geometry: Defined constructively, not by its boundary. Boolean geometry is the representation of 3D shapes by combining or subtracting simpler solids using Boolean operations like union, intersection, and difference.

Table 20

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
		IfcCsgSolid	Csg_solid		
		IfcBooleanResult	boolean_result	BRepAlgoAPI_BooleanOperation	

Solid/Shell: A solid is a topological object that encloses a region of space and a shell is a set of connected surfaces that form a boundary. A Solid is a closed shell.

Table 21

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
	gml:Abstract Solid				
GM_Solid	gml:Solid	IfcFacetedBrep	manifold_solid_brep	TopoDS_Solid (TopoDS_Face)	
		IfcFacetedBrepWithVoids			
		IfcAdvancedBrep	advanced_brep_shape_representation		
		IfcAdvancedBrepWithVoids			
		IfcSectionedSolidHorizontal			
		IfcFixedReferenceSweptAreaSolid			
		IfcDirectrixDerivedReferenceSweptAreaSolid			
		IfcExtrudedAreaSolid	extruded_area_solid		
		IfcExtrudedAreaSolidTapered			
		IfcRevolvedAreaSolid			
		IfcRevolvedAreaSolidTapered			

GM_Shell	gml:Shell				
				solid_replica	
				brep_2d	
		IfcSectionedSpine		sectioned_spine	
		IfcBoxedHalfSpace		boxed_half_space	
		IfcPolygonalBoundedHalfSpace			
				tesselated_solid	

Swept Surface:

A swept surface is a type of surface in geometric modeling created by moving a profile (curve) along a trajectory (path).

Table 22

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
		IfcSurfaceCurveSweptAreaSolid			
		IfcSweptDiskSolid	swept_disk_solid		
		IfcSweptDiskSolidPolygonal			
			swept_face_solid		
			swept_area_solid		
		IfcSurfaceOfLinearExtrusion	surface_of_linear_extrusion	Geom_SurfaceOfLinearExtrusion	
		IfcSurfaceOfRevolution	surface_of_revolution	Geom_SurfaceOfRevolution	
		IfcSweptSurface	surface_curve_swept_surface		
			fixed_reference_swept_surface		
			revolved_face_solid		

			extruded_face_solid			
			surface_curve_swept_area_solid			
			swept_disk_solid			

Volume:

Volume geometry is a way of representing a 3D object by directly defining the entire region of space it occupies, rather than just its boundary.

Table 23

ISO 19107	GML	IFC	STEP	OpenCascade	WKT	X3D
			block_volume			
			pyramid_volume			
			eccentric_conical_volume			
			spherical_volume			
			ellipsoid_volume			
			cylindrical_volume			
			wedge_volume			
			tetrahedron_volume			
			hexadron_volume			
			toroidal_volume			
			bezier_volume			
			uniform_volume			
			quasi_uniform_volume			
			rational_b_spline_volume			
			trimmed_volume			

			locally_refined_spline_volume		
			rational_locally_refined_spline_volume		
			b_spline_volume		
			b_spline_volume_with_knots		

Axis/Placement:

Used to define orientation or alignment of objects, where to be placed and in what direction to extrude.

Table 24

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
		IfcAxis1Placement	axis1_placement	Geom_Axis1Placement	
		IfcAxis2Placement2D IfcAxis2Placement3D	axis2_placement_2d axis2_placement_3d	Geom_Axis2Placement	

Grids:

Table 25

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
	gml:RectifiedGrid				
	gml:RectifiedGridCoverage				
	gml:GridCoverage				

Operators:

Table 26

ISO 19107	GML	IFC	STEP	Open Cascade	WKT
			cartesian_transformation_operator		

	IfcCartesianTransformationOperator3D	cartesian_ transformation_ operator_3d		
	IfcCartesianTransformationOperator2D IfcCartesianTransformationOperator2Dnon Uniform	cartesian_ transformation_ operator_2d		gp_Trsf2d

Geometric complex/ composites:

Table 27

ISO 19107	GML	IFC	STEP	Open Cascade	WKT
GM_Complex	gml:Geometric Complex				
GM_Composite Point					
GM_Composite Curve	gml:Composite Curve	IfcComposite Curve	composite_ curv	composite_ curve	COMPOUNDCURVE (x y (z)(m))
GM_Composite Surface	gml:Composite Surface				
GM_Composite Solid	gml:Composite Solid				
			composite_ curve_segment		
			reparametrised_ composite_ curve_segment		
			rectangular_ composite_ surface		

Geometric Agggregates:

Table 28

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
GM_MultiPoint	gml:MultiPoint				MULTIPOINT
GM_MultiCurve	gml:MultiCurve				MULTILINESTRING
GM_MultiSurface	gml:MultiSurface				MULTIPOLYGON

GM_MultiSolid	gml:MultiSolid					
			IfcCartesianPointList2D			
			IfcCartesianPointList3D			

Interface Query:

Table 29

ISO 19107	GML	IFC	STEP	OpenCascade	WKT
boundary:Geometry					
convexHull:Geometry					
distance				gp_Circ::Distance() gp_Circ2d::Distance() gp_Lin::Distance(const gp_Pnt &theP) const gp_Lin::Distance(const gp_Lin &theOther) const gp_Lin2d::Distance(const gp_Pnt2d &theP) const gp_Lin2d::Distance(const gp_Lin2d &theOther) gp_Pln::Distance gp_Circ::Distance() etc	
buffer					
intersection				BRepClass_Intersector	
difference					
symDifference					
union					
contains				BRepClass3d_SolidClassifier	
crosses					
disjoint					
equals					
intersects					

overlaps	
touches	
within	
withinDistance	
relate	
3Dboundary:Geometry	
3DconvexHull:Geometry	
3Ddistance	
3Dbuffer	
3Dintersection	BRepClass3d_Intersector3d
3Ddifference	
3DsymDifference	
3Dunion	
3Dcontains	
3Dcrosses	
3Ddisjoint	
3Dequals	
3Dintersects	
3Doverlaps	
3Dtouches	
3Dwithin	
3DwithinDistance	

3Drelate

https://dev.opencascade.org/doc/refman/html/ https://old.opencascade.com/doc/occt-7.5.0/overview/html/index.htmlhttps://ifc43-docs.standards.buildingsmart.org/IFC/RELEASE/IFC4x3/HTML/lexical/IfcGeometricRepresentationItem.htm

https://www.web3d.org/documents/specifications/19775-1/V4.0/index.html

17

ANNEX O: HISTORY

17 ANNEX O: HISTORY

BIBLIOGRAPHY

BIBLIOGRAPHY

[1] Abhayaratna J, van den Brink L, Car N, Atkinson R, Homburg T, Knibbe F, McGlinn K, Wagner A, Bonduel M, Rasmussen MH, Thiery F: Abhayaratna2020wp, *OGC Benefits of Representing Spatial Data Using Semantic and Graph Technologies*. Open Geospatial Consortium (2020). http://www.opengis.net/doc/wp/using-semantic-graph.

[2] Jabi W, Chatzivasileiadi A: Topologic: Exploring Spatial Reasoning Through Geometry, Topology, and Semantics. In: p. 277. Springer International Publishing, Cham. (2021).

[3] Filip Biljecki HT: QUALITY OF BIM–GIS CONVERSION. (2019).

[4] Anne Göbels JB: Relative Location Ontology: An ontological model for representing directional topological relationships between spatial entities in oriented space. (2024).

[5] *World Wide Web Consortium: RDF 1.1 Concepts and Abstract Syntax, W3C Recommendation*, https://www.w3.org/TR/rdf11-concepts/ (25 February 2014).

[6] St\"otzner E, Homburg T, Mara H: CNN Based Cuneiform Sign Detection Learned from Annotated 3D Renderings and Mapped Photographs with Illumination Augmentation. In: pp. 1680–1688. (2023).

[7] *World Wide Web Consortium: RDF 1.1 Turtle Terse RDF Triple Language, W3C Recommendation*, https://www.w3.org/TR/turtle (25 February 2014).

[8] Behr J, Eschler P, Jung Y, Z{\"o}llner M: X3DOM: a DOM-based HTML5/X3D integration model. In: p. 127. (2009).

[9] Bonduel M, Wagner A, Pauwels P, Vergauwen M, Klein R: Including widespread geometry formats in semantic graphs using RDF literals. In: vol. 1, p. 341. (2019).

[10] Brutzman D, Daly L: *X3D: extensible 3D graphics for Web authors*. Elsevier, n.p. (2010).

[11] Brutzman D, Floty{\'n}ski J: X3D ontology for querying 3D models on the semantic web. In: p. 1. (2020).

[12] D'Andrea A, Fernie K: CARARE 2.0: a metadata schema for 3D Cultural Objects. In: vol. 2, p. 137. (2013).

[13] Donkers S, Ledoux H, Zhao J, Stoter J: Automatic conversion of IFC datasets to geometrically and semantically correct CityGML LOD3 buildings. *Transactions in GIS* vol. 20, p. 547 (2016).

[14] Feichtenhofer C: X3d: Expanding architectures for efficient video recognition. In: p. 203. (2020).

[15] Hansson F: Linked geodata: CityGML represented as a virtual knowledge graph. *Student thesis series INES* (2024).

[16] Kolbe TH, Gr{\”o}ger G, Pl{\”u}mer L: CityGML: Interoperable access to 3D city models. In: p. 883. Springer. (2005).

[17] Snydman S, Sanderson R, Cramer T: The International Image Interoperability Framework (IIIF): A community & technology approach for web-based images. In: vol. 12, p. 16. (2015).

[18] St{\”o}tzner E, Homburg T, Bullenkamp JP, Mara H: R-CNN based PolygonalWedge Detection Learned from Annotated 3D Renderings and Mapped Photographs of Open Data Cuneiform Tablets. (2023).

[19] [NO INFORMATION AVAILABLE]

[20] [NO INFORMATION AVAILABLE]

[21] Chadzynski A, Krdzavac N, Farazi F, Lim MQ, Li S, Grisiute A, Herthogs P, von Richthofen A, Cairns S, Kraft M: Semantic 3D City Database — An enabler for a dynamic geospatial knowledge graph. *Energy and AI* vol. 6, p. 100106 (2021).

[22] Chadzynski A, Li S, Grišiūtė A, Chua J, Hofmeister M, Yan J, Tai HY, Lloyd E, Tsai YK, Agarwal M, Akroyd J, Herthogs P, Kraft M: Semantic 3D city interfaces—Intelligent interactions on dynamic geospatial knowledge graphs. *Data-Centric Engineering* vol. 4 (2023).

[23] Perzylo A, Somani N, Rickert M, Knoll A: An ontology for CAD data and geometric constraints as a link between product models and semantic robot task descriptions. In: *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. pp. 4197–4203. IEEE. (2015).

[24] Flotyński J, Walczak K: Ontology-Based Representation and Modelling of Synthetic 3D Content: A State-of-the-Art Review. *Computer Graphics Forum* vol. 36 no. 8, pp. 329–353 (2017).

[25] Sikos LF: A novel ontology for 3D semantics: ontology-based 3D model indexing and content-based video retrieval applied to the medical domain. *International Journal of Metadata, Semantics and Ontologies* vol. 12 no. 1, p. 59 (2017).

[26] Car NJ, Homburg T: GeoSPARQL 1.1: Motivations, Details and Applications of the Decadal Update to the Most Important Geospatial LOD Standard. *ISPRS International Journal of Geo-Information* vol. 11 no. 2, p. 117 (2022).

[27] El Yamani S, Hajji R, Billen R: IFC-CityGML Data Integration for 3D Property Valuation. *ISPRS International Journal of Geo-Information* vol. 12 no. 9, p. 351 (2023).

[28] Homburg T, Zwick R, Mara H, Bruhn K: Annotated 3D-Models of Cuneiform Tablets. *Journal of Open Archaeology Data* vol. 10 (2022).

[29] Haynes R: Evolving Standards in Digital Cultural Heritage – Developing a IIIF 3D Technical Specification. In: *Lecture Notes in Computer Science*. pp. 50–64. Springer International Publishing, Cham. (2023).

[30] Kutzner T, Chaturvedi K, Kolbe TH: CityGML 3.0: New Functions Open Up New Applications. *PFG – Journal of Photogrammetry, Remote Sensing and Geoinformation Science* vol. 88 no. 1, pp. 43–61 (2020).

[31] Homburg T, Cramer A, Raddatz L, Mara H: Metadata schema and ontology for capturing and processing of 3D cultural heritage objects. *Heritage Science* vol. 9 no. 1 (2021).

[32] Ropelewski AJ, Rizzo MA, Swedlow JR, Huisken J, Osten P, Khanjani N, Weiss K, Bakalov V, Engle M, Gridley L, Krzyzanowski M, Madden T, Maiese D, Mandal M, Waterfield J, Williams D, Hamilton CM, Huggins W: Standard metadata for 3D microscopy. *Scientific Data* vol. 9 no. 1 (2022).

[33] Wang Y, Wang X, Liu A, Zhang J, Zhang J: Ontology of 3D virtual modeling in digital twin: a review, analysis and thinking. *Journal of Intelligent Manufacturing* vol. 36 no. 1, pp. 95–145 (2023).