

# OGC GeoSPARQL - A Geographic Query Language for RDF Data

# Table of Contents

i. Preface .....	4
ii. Submitting organizations .....	5
iii. Submission contact points .....	5
Clarifications .....	6
v. Changes to the OGC® Abstract Specification .....	7
Foreword .....	8
Introduction .....	9
RDF .....	9
SPARQL .....	9
GeoSPARQL Standard structure .....	10
OGC GeoSPARQL - A Geographic Query Language for RDF Data .....	13
1. Scope .....	14
2. Conformance .....	15
3. Normative references .....	17
4. Terms and definitions .....	18
4.1. Semantic Web .....	18
4.2. Spatial .....	18
5. Conventions .....	20
5.1. Symbols and abbreviated terms .....	20
5.2. Namespaces .....	20
5.3. Placeholder IRIs .....	21
5.4. RDF Serializations .....	21
6. Core .....	22
6.1. SPARQL .....	22
6.2. Classes .....	23
6.3. Standard Properties for geo:SpatialObject .....	25
6.4. Standard Properties for geo:Feature .....	30
7. Topology Vocabulary Extension .....	33
7.1. Parameters .....	33
7.2. Simple Features Relation Family .....	33
7.3. Egenhofer Relation Family .....	34
7.4. RCC8 Relation Family .....	35
7.5. Equivalent RCC8, Egenhofer and Simple Features Topological Relations .....	36
8. Geometry Extension .....	37
8.1. Rationale .....	37
8.2. GeoSPARQL and Simple Features (SFA-CA) .....	37
8.3. Recommendation for units of measure .....	38
8.4. Influence of Reference Systems on computations .....	38

8.5. Parameters	39
8.6. Geometry Class	39
8.7. Standard Properties for geo:Geometry	41
8.8. Geometry Serializations	44
8.9. Non-topological Query Functions	54
8.10. Spatial Aggregate Functions	62
9. Geometry Topology Extension	65
9.1. Parameters	65
9.2. Common Query Functions	65
9.3. Simple Features Relation Family	66
9.4. Egenhofer Relation Family	66
9.5. RCC8 Relation Family	67
10. RDFS Entailment Extension	69
10.1. Parameters	69
10.2. Common Requirements	69
10.3. WKT Serialization	69
10.4. GML Serialization	70
11. Query Rewrite Extension	72
11.1. Parameters	73
11.2. Simple Features Relation Family	73
11.3. Egenhofer Relation Family	73
11.4. RCC8 Relation Family	74
11.5. Special Considerations	74
12. Future Work	76
Annex A - Abstract Test Suite (normative)	77
A.0 Overview	78
A.1 Conformance Class: Core	79
A.1.1 SPARQL	79
A.1.2 RDF Classes & Properties	79
A.2 Conformance Class: Topology Vocabulary Extension	81
A.2.1 Simple Features Relation Family	81
A.2.2 Egenhofer Relation Family	81
A.2.3 RCC8 Relation Family	81
A.3 Conformance Class: Geometry Extension	83
A.3.1 Tests for all Serializations except DGGS	83
A.3.2 WKT Serialization	85
A.3.3 GML Serialization	87
A.3.4 GeoJSON Serialization	88
A.3.5 KML Serialization	90
A.3.6 DGGS Serialization	91
A.3.DGGS Conformance Class: Geometry Extension - DGGS	93

A.3.DGGS.1 Tests for DGGS Serializations . . . . .	93
A.3.DGGS.2 DGGS Serialization . . . . .	95
A.4 Conformance Class: Geometry Topology Extension . . . . .	97
A.4.1 Tests for all relation families . . . . .	97
A.4.2 Simple Features Relation Family . . . . .	97
A.4.3 Egenhofer Relation Family . . . . .	97
A.4.4 RCC8 Relation Family . . . . .	98
A.5 Conformance Class: RDFS Entailment Extension . . . . .	99
A.5.1 Tests for all implementations . . . . .	99
A.5.2 WKT Serialization . . . . .	99
A.5.3 GML Serialization . . . . .	99
A.6 Conformance Class: Query Rewrite Extension . . . . .	101
A.6.1 Simple Features Relation Family . . . . .	101
A.6.2 Egenhofer Relation Family . . . . .	101
A.6.3 RCC8 Relation Family . . . . .	102
Annex B - Functions Summary (normative) . . . . .	103
B.0 Overview . . . . .	104
B.1 Functions Summary Table . . . . .	105
B.2 GeoSPARQL to SFA Functions Mapping . . . . .	110
Annex C - GeoSPARQL Examples (informative) . . . . .	112
C.0 Overview . . . . .	113
C.1 RDF Examples . . . . .	114
C.1.1 Classes . . . . .	114
C.1.2 Properties . . . . .	121
C.2 Example SPARQL Queries & Rules . . . . .	127
C.2.1 Example Data . . . . .	127
C.2.2 Example Queries . . . . .	129
C.2.3 Example Rule Application . . . . .	132
C.2.4 Example Geometry Serialization Conversion Functions . . . . .	133
Annex D - Usage of SHACL shapes (informative) . . . . .	134
D.0 Overview . . . . .	135
D.1 Tools . . . . .	136
D.2 Scope of SHACL Shapes provided with GeoSPARQL . . . . .	137
D.3 Table of SHACL Shapes . . . . .	138
Annex E - Alignments (informative) . . . . .	144
E.0 Overview . . . . .	145
E.1 ISA Programme Location Core Vocabulary (LOCN) . . . . .	146
E.2 WGS84 Geo Positioning: an RDF vocabulary (POS) . . . . .	148
E.3 W3C Activity Streams Vocabulary . . . . .	149
E.4 Geonames Ontology (GN) . . . . .	150
E.5 NeoGeo Vocabulary . . . . .	151

E.6 Juso Ontology .....	153
E.7 Time Ontology in OWL (TIME) .....	154
E.8 schema.org .....	156
E.9 Semantic Sensor Network Ontology (SSN) .....	157
E.10 DCMI Metadata Terms (DCTERMS) .....	158
E.11 The Provenance Ontology (PROV) .....	159
E.12 WikiData .....	161
E.13 OpenStreetMap Ontologies .....	165
E.13.1 LinkedGeoData .....	165
E.13.2 OpenStreetMap RDF (Sophox) .....	165
E.13.3 Routable Tiles Ontology .....	166
E.14 Ordnance Survey UK Spatial Ontology .....	167
E.15 CIDOC CRM Geo .....	168
E.16 Basic Formal Ontology (BFO) .....	170
Annex F - CQL / GeoSPARQL Mapping (informative) .....	172
F.0 Overview .....	173
F.1 Accessing spatial Features in a SPARQL endpoint .....	174
F.2 Mappings from CQL2 statements to GeoSPARQL queries .....	176
F.2.1 Query Parameters .....	176
F.2.2 Literal Values .....	176
F.2.3 Property references .....	177
F.2.4 Comparison Predicates .....	177
F.2.5 Spatial Operators .....	178
F.2.6 Temporal Operators .....	178
F.3 Mappings from Simple Features for SQL .....	180
Annex G - Revision History .....	184
Bibliography .....	186

```
<style>
  .imageblock > .title {
    text-align: inherit;
  }
</style>
```

## Open Geospatial Consortium

Submission Date: <yyyy-mm-dd>

Approval Date: <yyyy-mm-dd>

Publication Date: <yyyy-mm-dd>

External identifier of this OGC® document: <http://www.opengis.net/doc/IS/geosparql/1.1>

Internal reference number of this OGC® document: 22-047

Version: 1.1

Category: OGC® Implementation Specification

Editors: Nicholas J. Car, Timo Homburg, Matthew Perry, John Herring, Frans Knibbe, Simon J.D. Cox, Joseph Abhayaratna and Mathias Bonduel

Contributors: Paul J. Cripps, Krzysztof Janowicz

## OGC GeoSPARQL - A Geographic Query Language for RDF Data

### Copyright notice

Copyright © 2021 Open Geospatial Consortium

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>

### Warning

This document is not an OGC standard. This document is distributed for review and comment. This document is subject to change without notice and may not be referred to as an OGC Standard

Document type: OGC® Standard

Document subtype: Encoding

Document stage: Draft

Document language: English

## License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications.

This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

None of the Intellectual Property or underlying information or technology may be downloaded or otherwise exported or reexported in violation of U.S. export laws and regulations. In addition, you are responsible for complying with any local laws in your jurisdiction which may impact your right to import, export or use the Intellectual Property, and you represent that you have complied with any regulations or registration procedures required by applicable law to make this license enforceable.



# i. Preface

The OGC GeoSPARQL Standard defines:

- A formal *profile*;
- **this document**;
- A core RDF/OWL ontology for geographic information representation;
- A set of SPARQL extension functions;
- A Functions & Rules vocabulary, derived from the ontology;
- A Simple Features geometry types vocabulary;
- SHACL shapes for RDF data validation.

This document authoritatively defines many of the Standard's elements, including the ontology classes and properties, SPARQL functions, and function and rule vocabulary concepts. Complete descriptions of the Standard's parts and their roles are given in the Introduction in the section [GeoSPARQL Standard structure](#).

## ii. Submitting organizations

The following organizations submitted this Implementation Standard to the Open Geospatial Consortium Inc.:

- a. CSIRO
- b. Cubewerx Inc.
- c. Defence Science and Technology Laboratory (DSTL)
- d. Geonovum
- e. Geoscape Australia
- f. Geoscience Australia
- g. Mainz University Of Applied Sciences
- h. Oracle America
- i. OSGeo
- j. SURROUND Australia Pty Ltd.

## iii. Submission contact points

All questions regarding this submission should be directed to the editor or the submitters:

Contact	Company
Simon J.D. Cox	CSIRO
Panagiotis (Peter) A. Vretanos	Cubewerx Inc.
Paul Cripps	DSTL
Linda van den Brink	Geonovum
Joseph Abhayaratna	Geoscape Australia
Irina Bastrakova	Geoscience Australia
Timo Homburg	Mainz University Of Applied Sciences
Matthew Perry	Oracle America
Dimitris Kotzinos	OSGeo
Nicholas J. Car	SURROUND Australia Pty Ltd.

# Clarifications

- The terms [Spatial Reference System \(SRS\)](#) and [Coordinate Reference System \(CRS\)](#) are no longer interchangeable. Spatial Reference System is now taken to be a broader category than Coordinate Reference System. These are defined in the [Clause 4](#) section.
- Class definitions were updated to be more self-contained and easier to understand for people without a background in geoinformatics. The definitions are no longer dependent on other standards' definitions, only informed by them.
- A section was added on [the specification of units of measurement](#).
- A section was added on the [\[Influence of Coordinate Reference Systems on geometric computations\]](#).

## **v. Changes to the OGC® Abstract Specification**

The OGC® Abstract Specification does not require changes to accommodate this OGC® standard.

# Foreword

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights. However, to date, no such rights have been claimed or identified.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the specification set forth in this document, and to provide supporting documentation.

# Introduction

The W3C Semantic Web Activity defines a collection of technologies that enables a “web of data” where information is easily shared and reused across applications. Some key pieces of this technology stack are the Resource Description Framework (RDF) data model [\[RDF\]](#), [\[RDFS\]](#), the OWL Web Ontology Language [\[OWL2\]](#) and the SPARQL Protocol and RDF Query Language [\[SPARQL\]](#).

## RDF

RDF is, among other things, a data model built on edge-node “graphs.” Each link in a graph consists of three elements (with many aliases depending on the mapping from other types of data models):

- Subject (start node, instance, entity, feature)
- Predicate (verb, property, attribute, relation, member, link, reference)
- Object (value, end node, non-literal values can be used as a Subject)

Any of the three values in a triple can be represented with an Internationalized Resource Identifier (IRI) [\[IETF3987\]](#), which globally and uniquely identifies the resource referenced. IRIs are an extension to Uniform Resource Identifiers (URIs) that allow for non-ASCII characters. In addition to functioning as identifiers, IRIs are usually, but not necessarily, resolvable. This means a person or machine can “dereference” them (*click on them* or otherwise execute them) and be taken to more information about the resource, perhaps in a web browser.

Subjects and objects within an RDF triple are called nodes and can also be represented with a blank node (a local identifier without meaning outside the graph it is defined within). Objects can further be represented with a literal value. RDF uses the basic literal values from XML [\[XSD2\]](#) however the basic types can be extended for specialized purposes. Indeed, this document extends the basic types to include geometry data. The figure below shows a basic triple.



Figure 1. An RDF Triple

Note that the same node may be a subject in some triples, and an object in others.

Almost all data can be presented or represented in RDF. In particular, there are similarities to the (feature-instance-by-id, attribute, value) tuples of the General Feature Model [\[ISO19109\]](#), and to the relational model as well (table primary key, column, value).

## SPARQL

From [\[SPARQL\]](#):

SPARQL ... is a set of specifications that provide languages and protocols to

query and manipulate RDF graph content on the Web or in an RDF store.

From Wikipedia<sup>[1]</sup>:

SPARQL (pronounced "sparkle" /ˈspɑːrkəl/, a recursive acronym for SPARQL Protocol and RDF Query Language) is an RDF query language - that is, a semantic query language for databases — able to retrieve and manipulate data stored in Resource Description Framework (RDF) format. It was made a standard by the RDF Data Access Working Group (DAWG) of the World Wide Web Consortium, and is recognized as one of the key technologies of the semantic web. On 15 January 2008, SPARQL 1.0 was acknowledged by W3C as an official recommendation, and SPARQL 1.1 in March, 2013.

SPARQL queries work on RDF representations of data by finding patterns that match templates in the query, in effect finding information graphs in the RDF data based on the templates and filters (constraints on nodes and edges) expressed in the query. This query template is represented in the SPARQL query by a set of parameterized “query variables” appearing in a sequence of RDF triples and filters. If the query processor finds a set of triples in the data (converted to an RDF graph in some predetermined standard manner) then the values that the “query variables” take on in those triples become a solution to the query request. The values of the variables are returned in the query result in a format based on the “SELECT” clause of the query (similar to SQL).

In addition to predicates defined in this manner, the SPARQL query may contain filter functions that can be used to further constrain the query. Several mechanisms are available to extend filter functions to allow for predicates calculated directly on data values. Section 17.6<sup>[2]</sup> of the SPARQL specification [SPARQL] describes the mechanism for invocation of such a filter function.

The OGC GeoSPARQL Standard supports representing and querying geospatial data on the Semantic Web. GeoSPARQL defines a vocabulary for representing geospatial data in RDF. It also defines extensions to the SPARQL query language for processing geospatial data.

GeoSPARQL does not directly provide support for temporality. Predicates for temporal relations may be used from the OWL Time Ontology [TIME], but query extension functions for spatiotemporal operations are not present in the GeoSPARQL standard.

## GeoSPARQL Standard structure

The GeoSPARQL Standard consists of multiple parts, or *profile resources*. The comprehensive listing of these parts is given in the GeoSPARQL *profile definition*, (see <http://www.opengis.net/def/geosparql>). Below is an overview of the major parts:

### 1. *profile definition*

- <http://www.opengis.net/def/geosparql>
- Formally defined as an ontology, defined according to the *Profiles Vocabulary* [PROF];
- This relates the parts in the standard together, provides access to them, and declares

dependencies on other standards.

## 2. Standard document (this document)

- <http://www.opengis.net/doc/IS/geosparql/1.1>
- Defines many of the standard's parts;
- Includes normative RDF/OWL [RDF],[OWL2] ontology element definitions, conformance requirements and function signatures based on the General Feature Model [ISO19109], Simple Features [OGCSFACA] [ISO19125-1] and SQL MM [ISO13249];
- Also includes non-normative examples and mappings to other modelling and function systems.

## 3. Domain model RDF/OWL [RDF],[OWL2] ontology

- <http://www.opengis.net/ont/geosparql>;
- For geographic information representation;
- Based on the General Feature Model [ISO19109], Simple Features Access [OGCSFACA] [ISO19125-1], Geography Markup Language [GML] and SQL MM [ISO13249]
- Defined within the specification document and also delivered in RDF.

## 4. Functions & Rules vocabulary

- <http://www.opengis.net/def/geosparql/funcsrules>;
- Derived from the ontology;
- Presented as a [SKOS] taxonomy.

## 5. Simple Features vocabulary

- <http://www.opengis.net/ont/sf>;
- Derived from the class model defined in Simple Features Access [OGCSFACA] [ISO19125-1];
- Presented as an OWL Section 4.1.3 ontology.

## 6. SPARQL [SPARQL] extension functions defined within this document.

## 7. RDF data validator

- <http://www.opengis.net/def/geosparql/validator>;
- Defined using SHACL [SHACL];
- Presented within a single RDF file.

## 8. SPARQL 1.1 Service description for GeoSPARQL

- <http://www.opengis.net/def/geosparql/servicedescription>;
- Defined using [SPARQLSERVDESC].

This document follows a modular design and contains the following components:

- A *core* component defining the top-level RDFS/OWL classes for spatial objects.
- A *topology vocabulary* component defining the RDF properties for asserting and querying topological relationships between spatial objects.



- A *geometry* component defining RDFS data types for serializing geometry data, geometry-related RDF properties, and non-topological spatial query functions for geometry objects.
- A *geometry topology* component defining topological query functions.
- An *RDFS entailment* component defining mechanisms for matching implicit RDF triples that are derived based on RDF and RDFS semantics.
- A *query rewrite* component defining rules for transforming a simple triple pattern that tests a topological relationship between two features into an equivalent query involving concrete geometries and topological query functions.

Each of these components forms a set of *Requirements* known as a *GeoSPARQL Conformance Class*. Implementations can provide various levels of functionality by choosing which *Conformance Classes* to support. For example, a system based purely on qualitative spatial reasoning may support only the core and topological vocabulary Classes.

In addition, GeoSPARQL is designed to accommodate systems based on qualitative spatial reasoning and systems based on quantitative spatial computations. Systems based on qualitative spatial reasoning, (e.g. those based on Region Connection Calculus [QUAL], [LOGIC]) do not usually model explicit geometries, so queries in such systems will likely test for binary spatial relationships between features rather than between explicit geometries. To allow queries for spatial relationships between features in quantitative systems, GeoSPARQL defines a series of query transformation rules that expand a feature-only query into a geometry-based query. With these transformation rules, queries about spatial relationships between features will have the same specification in both qualitative systems and quantitative systems. The qualitative system will likely evaluate the query with a backward-chaining spatial “reasoner”, and the quantitative system can transform the query into a geometry-based query that can be evaluated with computational geometry.

[1] <https://en.wikipedia.org/wiki/SPARQL>

[2] <https://www.w3.org/TR/sparql11-query/#extensionFunctions>

# OGC GeoSPARQL - A Geographic Query Language for RDF Data

# Chapter 1. Scope

The OGC GeoSPARQL Standard is comprised of multiple parts. See the Introduction section [GeoSPARQL Standard structure](#) for details of the parts.

GeoSPARQL does not define a comprehensive vocabulary for representing spatial information. Instead GeoSPARQL defines a core set of classes, properties and datatypes that can be used to construct query patterns. Many useful extensions to this vocabulary are possible, and we intend for the Semantic Web and Geospatial communities to develop additional vocabularies for describing spatial information.

# Chapter 2. Conformance

Conformance with this Standard shall be checked using all the relevant tests specified in [Annex A - Abstract Test Suite \(normative\)](#). The framework, concepts, and methodology for testing, and the criteria to be achieved to claim conformance are specified in *ISO 19105: Geographic information — Conformance and Testing* [ISO19105].

This document establishes many individual Requirements and Conformance Classes which contain tests for one or more Requirements. GeoSPARQL implementations need not conform to all Conformance Classes but must state which individual ones they do conform to. GeoSPARQL implementations claiming conformance to a Conformance Class must pass all the tests defined for it in [Annex A - Abstract Test Suite \(normative\)](#).

Requirements and Conformance Class tests have IRIs that are relative to versioned namespace IRIs. Requirements and Conformance Class tests that are defined in GeoSPARQL 1.0 have IRIs relative to <http://www.opengis.net/spec/geosparql/1.0/> and those added in GeoSPARQL 1.1 have IRIs relative to <http://www.opengis.net/spec/geosparql/1.1/>.

Many Conformance Classes are parameterized, and any parameters are explained in the detailed clauses for those Conformance Classes.

Table 1. Conformance Classes

Conformance Class	Description	Subclause of the abstract test suite
Core	Defines top-level spatial vocabulary components	A.1
Topology Vocabulary Extension	Defines topological relation vocabulary	A.2
Geometry Extension	Defines geometry vocabulary and non-topological query functions	A.3
Geometry Extension - DGGS	Defines the properties and functions of the Geometry Extension Conformance Classes for use with Discrete Global Grid System geometry representations	A.3.DGGS
Geometry Topology Extension	Defines topological query functions for geometry objects	A.4
RDFS Entailment Extension	Defines a mechanism for matching implicit RDF triples that are derived based on RDF and RDFS semantics	A.5

Conformance Class	Description	Subclause of the abstract test suite
Query Rewrite Extension	Defines query transformation rules for computing spatial relations between spatial objects based on their associated geometries	A.6

Dependencies between each GeoSPARQL Conformance Class are shown below in Figure 2. To support a Conformance Class for a given set of parameter values, an implementation must support each dependent Conformance Class with the same set of parameter values.



Figure 2. Conformance Class Dependency Graph

# Chapter 3. Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this document. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies.

Items in this list are linked to their full citation in the [Bibliography](#).

- [\[OGCSFACA\]](#) [\[ISO19125-1\]](#), *ISO 19125-1: Geographic information — Simple feature access — Part 1: Common architecture*
- [\[OGCOM\]](#) [\[ISO19156\]](#), *ISO 19156: Geographic information — Observations and measurements*
- [\[OGC07-036\]](#), *OGC 07-036: Geography Markup Language (GML) Encoding Standard*
- [\[IETF3987\]](#), Internet Engineering Task Force, *RFC 3987: Internationalized Resource Identifiers (IRIs)*
- [\[OWL2\]](#) *OWL 2 Web Ontology Language Document Overview (Second Edition)*
- [\[RDF\]](#), *RDF 1.1 Concepts and Abstract Syntax*
- [\[RDFS\]](#) *RDF Schema 1.1*
- [\[RIFCORE\]](#), *RIF Core Dialect (Second Edition)*
- [\[SPARQL\]](#), *SPARQL 1.1 Query Language*
- [\[SPARQLENT\]](#), *SPARQL 1.1 Entailment Regimes*
- [\[SPARQLPROT\]](#), *SPARQL 1.1 Protocol*
- [\[SPARQLRESX\]](#), *SPARQL Query Results XML Format (Second Edition)*
- [\[SPARQLRESJ\]](#), *SPARQL 1.1 Query Results JSON Format*

# Chapter 4. Terms and definitions

For the purposes of this document, the terms and definitions given in the above normative references apply, as well as those reproduced or created in this section.

## 4.1. Semantic Web

The following terms and their definitions relate to Semantic Web models, tools and methods.

### 4.1.1. RDF

The Resource Description Framework (RDF) is a framework for representing information in the Web. RDF graphs are sets of subject-predicate-object triples, where the elements may be IRIs, blank nodes, or datatyped literals. They are used to express descriptions of resources. [\[RDF\]](#)

### 4.1.2. RDFS

RDF Schema provides a data-modelling vocabulary for RDF data. RDF Schema is an extension of the basic RDF vocabulary. [\[RDFS\]](#)

### 4.1.3. OWL

The OWL 2 Web Ontology Language, informally OWL 2, is an ontology language for the Semantic Web with formally defined meaning. OWL 2 ontologies provide classes, properties, individuals, and data values and are stored as Semantic Web documents. OWL 2 ontologies can be used along with information written in RDF, and OWL 2 ontologies themselves are primarily exchanged as RDF documents. [\[OWL2\]](#)

### 4.1.4. SPARQL

SPARQL is a query language for RDF. The results of SPARQL queries can be result sets or RDF graphs. [\[SPARQL\]](#)

## 4.2. Spatial

The following terms and their definitions relate to spatial science and data.

### 4.2.1. coordinate system

A coordinate system is a set of mathematical rules for specifying how coordinates are to be assigned to points.

### 4.2.2. coordinate reference system

A coordinate reference system (CRS) is a coordinate system that is related to an object by a datum.

### **4.2.3. datum**

A datum is a parameter or set of parameters that define the position of the origin, the scale, and the orientation of a coordinate system.

### **4.2.4. discrete global grid system**

A discrete global grid system (DGGS) is a spatial reference system that represents the Earth, or any other globe-like object, with a tessellation of nested cells. Generally, a DGGS will exhaustively partition the globe in closely packed hierarchical tessellations, each cell representing a homogenous value, with a unique identifier or indexing that allows for linear ordering, parent-child operations, and nearest neighbor algebraic operations.

### **4.2.5. spatial reference system**

A spatial reference system (SRS) is a system for establishing spatial position. A spatial reference system can use geographic identifiers (place names, for example), coordinates (in which case it is a coordinate reference system), or identifiers with structured geometry (in which case it is a discrete global grid system).



# Chapter 5. Conventions

## 5.1. Symbols and abbreviated terms

In this specification, the following common acronyms are used:

CRS	Coordinate Reference System
DGGS	Discrete Global Grid System
GeoJSON	Geographic JavaScript Object Notation
GFM	General Feature Model (as defined in ISO 19109)
GIS	Geographic Information System
GML	Geography Markup Language
IRI	Internationalized Resource Identifier
KML	Keyhole Markup Language
OWL	OWL 2 Web Ontology Language
RCC	Region Connection Calculus
RDF	Resource Description Framework
RDFS	RDF Schema
RIF	Rule Interchange Format
SPARQL	SPARQL Protocol and RDF Query Language
SQL	Structured Query Language
SRS	Spatial Reference System
URI	Universal Resource Identifier
WKT	Well Known Text (as defined by Simple Features or ISO 19125)
W3C	World Wide Web Consortium ( <a href="http://www.w3.org/">http://www.w3.org/</a> )
XML	Extensible Markup Language

## 5.2. Namespaces

The following IRI namespace prefixes are used throughout this document:

ex:	<a href="http://example.com/">http://example.com/</a>
geo:	<a href="http://www.opengis.net/ont/geosparql#">http://www.opengis.net/ont/geosparql#</a>
geof:	<a href="http://www.opengis.net/def/function/geosparql/">http://www.opengis.net/def/function/geosparql/</a>
geor:	<a href="http://www.opengis.net/def/rule/geosparql/">http://www.opengis.net/def/rule/geosparql/</a>
gml:	<a href="http://www.opengis.net/ont/gml#">http://www.opengis.net/ont/gml#</a>
my:	<a href="http://example.org/ApplicationSchema#">http://example.org/ApplicationSchema#</a>

ogc: <http://www.opengis.net/>  
owl: <http://www.w3.org/2002/07/owl#>  
rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>  
rdfs: <http://www.w3.org/2000/01/rdf-schema#>  
sf: <http://www.opengis.net/ont/sf#>  
skos: <http://www.w3.org/2004/02/skos/core#>  
xsd: <http://www.w3.org/2001/XMLSchema#>

## 5.3. Placeholder IRIs

All of these namespace prefixes in the previous section resolve to resources that contain their namespace content except for **ex:** (<http://example.com/>), which is used just for examples, and **ogc:** (<http://www.opengis.net/>), which is used as a placeholder, for example, **ogc:geomLiteral** is used to indicate any one of the specific geometry literal serializations defined here, such as **geo:wktLiteral**.

## 5.4. RDF Serializations

Three RDF serializations are used in this document. Terse RDF Triple Language (turtle) [\[TURTLE\]](#) is used for RDF snippets placed within the main body of the document, and turtle, JSON-LD [\[JSON-LD\]](#) & RDF/XML [\[RDFXML\]](#) are used for the examples in *Annex B — GeoSPARQL Examples*.

# Chapter 6. Core

This clause establishes the **Core** Requirements class, with IRI [/req/core](#), which has a corresponding Conformance Class, **Core**, with IRI [/conf/core](#). These Requirements define a set of classes and properties for representing geospatial data. The resulting vocabulary - an ontology - can be used to construct SPARQL graph patterns for querying appropriately modeled geospatial data. The RDFS and OWL vocabularies have both been used so that the vocabulary can be understood by systems that support only RDFS entailment and by systems that support OWL-based reasoning.

The figure below gives an overview of the classes and properties defined by GeoSPARQL in the **Core**, **Topology Vocabulary Extension** and **Geometry Extension**, **Geometry Topology Extension** and **RDFS Entailment Extension** Conformance Classes.




Figure 3. An overview of the Classes and Properties defined in GeoSPARQL. Where specific Classes and Properties are indicated, the prefixed forms of their ontology identifiers (IRIs) are given. Where types or collections of properties are given, they are described in *italics*. Where unspecified Classes are given, they are represented with a question mark. For cardinalities and other ontology restrictions, see the ontology document. Subproperties of **geo:hasSize**, its metric equivalent and **geo:hasSerialization** are not shown for clarity.

## 6.1. SPARQL

**Req 1** Implementations shall support the SPARQL Query Language for RDF [\[SPARQL\]](#), the SPARQL Protocol [\[SPARQLPROT\]](#) and the SPARQL Query Results XML [\[SPARQLRESX\]](#) and JSON [\[SPARQLRESJ\]](#) Formats.

<http://www.opengis.net/spec/geosparql/1.0/req/core/sparql-protocol>

## 6.2. Classes

Two main classes are defined: `geo:SpatialObject` and `geo:Feature`.

Two container classes are defined: `Spatial Object Collection` and `Feature Collection`.

### 6.2.1. Class: `geo:SpatialObject`

The class `geo:SpatialObject` is defined by the following:

```
geo:SpatialObject
  a rdfs:Class, owl:Class ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Spatial Object"@en ;
  skos:definition "Anything spatial (being or having a shape, position or an
extent)."@en ;
  skos:note "Subclasses of this class are expected to be used for instance data."@en
;
```

**Req 2** Implementations shall allow the RDFS class `geo:SpatialObject` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/core/spatial-object-class>

**Example:**

```
eg:x
  a geo:SpatialObject ;
  skos:prefLabel "Object X";
.
```

### 6.2.2. Class: `geo:Feature`

The class `geo:Feature` is equivalent to the class `GFI_Feature` [OGCOM] [ISO19156] and is defined by the following:

```
geo:Feature
  a rdfs:Class, owl:Class ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Feature"@en ;
  rdfs:subClassOf geo:SpatialObject ;
  owl:disjointWith geo:Geometry ;
  skos:definition "A discrete spatial phenomenon in a universe of discourse."@en ;
  skos:note "A Feature represents a uniquely identifiable phenomenon, for example
a river or an apple. While such phenomena (and therefore the Features
used to represent them) are bounded, their boundaries may be crisp
(e.g., the declared boundaries of a state), vague (e.g., the
```

delineation of a valley versus its neighboring mountains), and change with time (e.g., a storm front). While discrete in nature, Features may be created from continuous observations, such as an isochrone that determines the region that can be reached by ambulance within 5 minutes."@en ;

**Req 3** Implementations shall allow the RDFS class `geo:Feature` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/core/feature-class>

### 6.2.3. Class: `geo:SpatialObjectCollection`

The class `geo:SpatialObjectCollection` is defined by the following:

```
geo:SpatialObjectCollection
  a owl:Class ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Spatial Object Collection" ;
  skos:definition "A collection of individual Spatial Objects. This is the
                  superclass of Feature Collection and Geometry Collection."@en ;
  skos:note "This is the superclass of Feature Collection and Geometry
Collection."@en ;
  rdfs:subClassOf rdfs:Container ;
  rdfs:subClassOf [
    a owl:Restriction ;
    owl:allValuesFrom geo:SpatialObject ;
    owl:onProperty rdfs:member ;
  ] ;
.
```

Membership of the generic `rdfs:Container` that defines this class is restricted to instances of `Spatial Object`. `geo:SpatialObjectCollection` members are to be indicated with the `rdfs:member` property.

**Req 5** Implementations shall allow the RDFS class `geo:SpatialObjectCollection` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/core/spatial-object-collection-class>

### 6.2.4. Class: `geo:FeatureCollection`

The class `geo:FeatureCollection` is defined by the following:

```
geo:FeatureCollection
  a owl:Class ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Feature Collection" ;
  skos:definition "A collection of individual Features."@en ;
```

```

rdfs:subClassOf geo:SpatialObjectCollection ;
rdfs:subClassOf [
  a owl:Restriction ;
  owl:allValuesFrom :Feature ;
  owl:onProperty rdfs:member ;
] ;
.

```

Membership of the more general [Spatial Object Collection](#) that defines this class is restricted to instances of [Feature](#). [geo:FeatureCollection](#) members are to be indicated with the [rdfs:member](#) property.

**Req 6** Implementations shall allow the RDFS class [geo:FeatureCollection](#) to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/core/feature-collection-class>

## 6.3. Standard Properties for geo:SpatialObject

Properties are defined for associating Spatial Objects with scalar spatial measurements (sizes) .

**Req 7** Implementations shall allow the properties [geo:hasSize](#), [geo:hasMetricSize](#), [geo:hasLength](#), [geo:hasMetricLength](#), [geo:hasPerimeterLength](#), [geo:hasMetricPerimeterLength](#), [geo:hasArea](#), [geo:hasMetricArea](#), [geo:hasVolume](#) and [geo:hasMetricVolume](#). to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/core/spatial-object-properties>

### 6.3.1. Property: geo:hasSize

The property [geo:hasSize](#) is the superproperty of all properties that can be used to indicate the size of a Spatial Object in case (only) metric units (meter, square meter or cubic meter) cannot be used. If it is possible to express size in metric units, subproperties of [geo:hasMetricSize](#) should be used. This property has no range specification. This makes it possible to use other vocabularies for expressions of size, for example vocabularies for units of measurement or vocabularies for specifying measurement quality.

GeoSPARQL 1.1 defines the following subproperties of this property: [geo:hasLength](#), [geo:hasPerimeterLength](#), [geo:hasArea](#) and [geo:hasVolume](#).

```

geo:hasSize
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:domain geo:SpatialObject ;
  skos:definition "Subproperties of this property are used to indicate the size of a
                    Spatial Object as a measurement or estimate of one or more
dimensions
                    of the Spatial Object's spatial presence."@en ;
  skos:prefLabel "has size"@en ;

```

.

### 6.3.2. Property: `geo:hasMetricSize`

The property `geo:hasMetricSize` is the superproperty of all properties that can be used to indicate the size of a Spatial Object using metric units (meter, square meter or cubic meter). Using a subproperty of this property is the recommended way to specify size, because using a standard unit of length (meter) benefits data interoperability and simplicity. Subproperties of `geo:hasSize` can be used if more complex expressions are necessary, for example if the unit of length cannot be converted to meter, or if additional data are needed to describe the measurement or estimate of size.

GeoSPARQL 1.1 defines the following subproperties of this property: `geo:hasMetricLength`, `geo:hasMetricPerimeterLength`, `geo:hasMetricArea` and `geo:hasMetricVolume`.

```
geo:hasMetricSize
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:domain geo:SpatialObject ;
  rdfs:range xsd:double ;
  skos:definition "Subproperties of this property are used to indicate the size of a
    Spatial Object, as a measurement or estimate of one or more
dimensions
    of the Spatial Object's spatial presence. Units are always metric
    (meter, square meter or cubic meter)."@en ;
  skos:prefLabel "has metric size"@en ;
.
```

### 6.3.3. Property: `geo:hasLength`

The property `geo:hasLength` can be used to indicate the length of a Spatial Object if it is not possible to use the property `geo:hasMetricLength`. It is a subproperty of `geo:hasSize`.

```
geo:hasLength
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasSize ;
  rdfs:domain geo:SpatialObject ;
  skos:definition "The length of a Spatial Object."@en ;
  skos:prefLabel "has length"@en ;
.
```

### 6.3.4. Property: `geo:hasMetricLength`

The property `geo:hasMetricLength` can be used to indicate the length of a Spatial Object in meters (m). It is a subproperty of `geo:hasMetricSize`. This property can be used for Spatial Objects having one, two, or three dimensions.

```

geo:hasMetricLength
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasMetricSize ;
  rdfs:domain geo:SpatialObject ;
  rdfs:range xsd:double ;
  skos:definition "The length of a Spatial Object in meters."@en ;
  skos:prefLabel "has length in meters"@en ;
.

```

### 6.3.5. Property: `geo:hasPerimeterLength`

The property `geo:hasPerimeterLength` can be used to indicate the length of the outer boundary of a Spatial Object if it is not possible to use the property `geo:hasMetricPerimeterLength`. It is a subproperty of `geo:hasSize`.

```

geo:hasPerimeterLength
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasSize ;
  skos:definition "The length of the perimeter of a Spatial Object."@en ;
  skos:prefLabel "has perimeter length"@en ;
.

```

### 6.3.6. Property: `geo:hasMetricPerimeterLength`

The property `geo:hasMetricPerimeterLength` can be used to indicate the length of the outer boundary of a Spatial Object in meters (m). It is a subproperty of `geo:hasMetricSize`. Circumference is considered a type of perimeter, so this property can be used for circular or curved objects too. This property can be used for Spatial Objects having two or three dimensions.

```

geo:hasMetricPerimeterLength
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasMetricSize ;
  rdfs:domain geo:SpatialObject ;
  rdfs:range xsd:double ;
  skos:definition "The length of the perimeter of a Spatial Object in meters."@en ;
  skos:prefLabel "has perimeter length in meters"@en ;
.

```

#### TIP

A consistency check can be applied to Geometry instances indicating both this property and the property `geo:dimension`: if supplied, the `geo:dimension` property's range value must be the literal integer 2 or 3. The following SPARQL query will return `true` if applied to a graph where this is not the case for all Geometries:



```

PREFIX geo: <http://www.opengis.net/ont/geosparql#>
ASK
WHERE {
    ?g geo:hasMetricPerimeterLength ?p ;
    geo:dimension ?d .

    FILTER (?d < 2)
}

```

### 6.3.7. Property: geo:hasArea

The property **geo:hasArea** can be used to indicate the area of a Spatial Object if it is not possible to use the property **geo:hasMetricArea**. It is a subproperty of **geo:hasSize**.

```

geo:hasArea
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasSize ;
  rdfs:domain geo:SpatialObject ;
  skos:definition "The area of a Spatial Object."@en ;
  skos:prefLabel "has area"@en ;
.

```

### 6.3.8. Property: geo:hasMetricArea

The property **geo:hasMetricArea** can be used to indicate the area of a Spatial Object in square meters (m<sup>2</sup>). It is a subproperty of **geo:hasMetricSize**. This property can be used for Spatial Objects having two or three dimensions.

```

geo:hasMetricArea
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasMetricSize ;
  rdfs:domain geo:SpatialObject ;
  rdfs:range xsd:double ;
  skos:definition "The area of a Spatial Object in square meters."@en ;
  skos:prefLabel "has area in meters"@en ;
.

```

#### TIP

A consistency check can be applied to Geometry instances indicating both this property and the property **geo:dimension**: if supplied, the **geo:dimension** property's range value must be the literal integer 2 or 3. The following SPARQL query will return **true** if applied to a graph where this is not the case for all Geometries:

```

PREFIX geo: <http://www.opengis.net/ont/geosparql#>

```

```

ASK
WHERE {
    ?g geo:hasMetricArea ?a ;
        geo:dimension ?d .

    FILTER (?d < 2)
}

```

### 6.3.9. Property: `geo:hasVolume`

The property `geo:hasVolume` can be used to indicate the volume of a Spatial Object if it is not possible to use the property `geo:hasMetricVolume`. It is a subproperty of `geo:hasSize`.

```

geo:hasVolume
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasSize ;
  rdfs:domain geo:SpatialObject ;
  skos:definition "The volume of a three-dimensional Spatial Object."@en ;
  skos:prefLabel "has volume"@en ;
.

```

### 6.3.10. Property: `geo:hasMetricVolume`

The property `geo:hasMetricVolume` can be used to indicate the volume of a Spatial Object in cubic meters (m<sup>3</sup>). It is a subproperty of `geo:hasMetricSize`. This property can be used for Spatial Objects having three dimensions.

```

geo:hasMetricVolume
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf :hasMetricSize ;
  rdfs:domain geo:SpatialObject ;
  rdfs:range xsd:double ;
  skos:definition "The volume of a Spatial Object in cubic meters."@en ;
  skos:prefLabel "has area in meters"@en ;
.

```

#### TIP

A consistency check can be applied to Geometries indicating both this property and the property `geo:dimension`: if supplied, the property `geo:dimension` property's range value must be the literal integer 3. The following SPARQL query will return `true` if applied to a graph where this is not the case for all Geometries:

```
PREFIX geo: <http://www.opengis.net/ont/geosparql#>
```

```

ASK
WHERE {
    ?g geo:hasMetricVolume ?v ;
        geo:dimension ?d .

    FILTER (?d != 3)
}

```

## 6.4. Standard Properties for geo:Feature

Properties are defined for associating `geo:Feature` instances with `geo:Geometry` instances.

**Req 8** Implementations shall allow the properties `geo:hasGeometry`, `geo:hasDefaultGeometry`, `geo:hasCentroid` and `geo:hasBoundingBox` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/feature-properties>

### 6.4.1. Property: `geo:hasGeometry`

The property `geo:hasGeometry` is used to link a Feature with a Geometry that represents its spatial extent. A given Feature may have many associated geometries.

```

geo:hasGeometry
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:domain geo:Feature ;
  rdfs:range geo:Geometry ;
  skos:prefLabel "has Geometry"@en ;
  skos:definition "A spatial representation for a given Feature."@en ;
.

```

### 6.4.2. Property: `geo:hasDefaultGeometry`

The property `geo:hasDefaultGeometry` is used to link a Feature with its default Geometry. The default geometry is the Geometry that should be used for spatial calculations in the absence of a request for a specific geometry (e.g. in the case of query rewrite).

```

geo:hasDefaultGeometry
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:domain geo:Feature ;
  rdfs:range geo:Geometry ;
  skos:prefLabel "has Default Geometry"@en ;
  skos:definition "The default geometry to be used in spatial calculations,
                  usually the most detailed geometry."@en ;
  rdfs:subPropertyOf geo:hasGeometry ;
.

```

GeoSPARQL does not restrict the cardinality of the [has default geometry](#) property. It is thus possible for a Feature to have more than one distinct default geometry or to have no default geometry. This situation does not result in a query processing error; SPARQL graph pattern matching simply proceeds as normal. Certain queries may, however, give logically inconsistent results. For example, if a Feature `my:f1` has two asserted default geometries, and those two geometries are disjoint polygons, the query below could return a non-zero count on a system supporting the GeoSPARQL Query Rewrite Extension (rule `geor:sfDisjoint`).

```
PREFIX geo: <http://www.opengis.net/ont/geosparql#>

SELECT (COUNT(*) AS ?cnt)
WHERE { :f1 geo:sfDisjoint :f1 }
```

Such cases are application-specific data modeling errors and are therefore outside of the scope of the GeoSPARQL specification, however it is recommended that multiple geometries indicated with `geo:hasDefaultGeometry` should be differentiated by `Geometry` class properties, perhaps relating to precision, SRS etc.

### 6.4.3. Property: `geo:hasBoundingBox`

The property `geo:hasBoundingBox` is used to link a Feature with a simplified geometry-representation corresponding to the envelope of the feature's geometry. Bounding-boxes are typically used in indexing and discovery.

```
geo:hasBoundingBox
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasGeometry ;
  rdfs:domain geo:Feature ;
  rdfs:range geo:Geometry ;
  skos:prefLabel "has bounding box"@en ;
  skos:definition "The minimum or smallest bounding or enclosing box of a given
Feature."@en ;
  skos:scopeNote "The target is a geometry that defines a rectilinear region whose
edges are
                aligned with the axes of the coordinate reference system, which
exactly
                contains the geometry or Feature e.g. sf:Envelope"@en ;
  .
```

GeoSPARQL does not restrict the cardinality of the `geo:hasBoundingBox` property. A Feature may be associated with more than one bounding-box, for example in different coordinate reference systems.

### 6.4.4. Property: `geo:hasCentroid`

The property `geo:hasCentroid` is used to link a Feature with a point geometry corresponding with

the centroid of its geometry. The centroid is typically used to show location on a low-resolution image, and for some indexing and discovery functions.

```
geo:hasCentroid
  a rdf:Property, owl:ObjectProperty ;
  rdfs:isDefinedBy geo: ;
  rdfs:subPropertyOf geo:hasGeometry ;
  rdfs:domain geo:Feature ;
  rdfs:range geo:Geometry ;
  skos:prefLabel "has centroid"@en ;
  skos:definition "The arithmetic mean position of all the geometry points
                  of a given Feature."@en ;
  skos:scopeNote "The target geometry shall describe a point, e.g. sf:Point"@en ;
  .
```

GeoSPARQL does not restrict the cardinality of the `geo:hasCentroid` property. A Feature may be associated with more than one centroid, for example computed using different rules or in different coordinate reference systems.

# Chapter 7. Topology Vocabulary Extension

This clause establishes the *Topology Vocabulary Extension* parameterized Requirements class. The IRI base is [/req/topology-vocab-extension](#), which has a single corresponding Conformance Class *Topology Vocabulary Extension*, with IRI [/conf/topology-vocab-extension](#). This Requirements class defines a vocabulary for asserting and querying topological relations between spatial objects. The class is parameterized so that different families of topological relations may be used, such as RCC8 and Egenhofer. These relations are generalized so that they may connect features as well as geometries.

A Dimensionally Extended 9-Intersection Model (DE-9IM) pattern, which specifies the spatial dimension of the intersections of the interiors, boundaries and exteriors of two geometric objects, is used to describe each spatial relation. Possible pattern values are `-1` (empty), `0`, `1`, `2`, `T` (true) = `{0, 1, 2}`, `F` (false) = `{-1}`, `*` (don't care) = `{-1, 0, 1, 2}`. In the following descriptions, the notation `X/Y` is used to denote applying a spatial relation to geometry types `X` and `Y` (i.e., `x relation y` where `x` is of type `X` and `y` is of type `Y`). The symbol `P` is used for 0-dimensional geometries (e.g. points). The symbol `L` is used for 1-dimensional geometries (e.g. lines), and the symbol `A` is used for 2-dimensional geometries (e.g. polygons). Consult the Simple Features specification [\[OGCSFACA\]](#) [\[ISO19125-1\]](#) for a more detailed description of DE-9IM intersection patterns.

## 7.1. Parameters

The following parameter is defined for the *Topology Vocabulary Extension* Requirements.

**relation\_family**: Specifies the set of topological spatial relations to support.

## 7.2. Simple Features Relation Family

This clause defines Requirements for the *Simple Features* relation family.

**Req 9** Implementations shall allow the properties `geo:sfEquals`, `geo:sfDisjoint`, `geo:sfIntersects`, `geo:sfTouches`, `geo:sfCrosses`, `geo:sfWithin`, `geo:sfContains` and `geo:sfOverlaps` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/topology-vocab-extension/sf-spatial-relations>

Topological relations in the *Simple Features* family are summarized in [Table 2](#). Multi-row intersection patterns should be interpreted as a logical **OR** of each row.

Table 2. Simple Features Topological Relations

Relation Name	Relation IRI	Domain/Range	Applies To Geometry Types	DE-9IM Intersection Pattern
<code>equals</code>	<code>geo:sfEquals</code>	<code>geo:SpatialObject</code>	All	(TFFFTFFFT)
<code>disjoint</code>	<code>geo:sfDisjoint</code>	<code>geo:SpatialObject</code>	All	(FF**FF****)

Relation Name	Relation IRI	Domain/Range	Applies To Geometry Types	DE-9IM Intersection Pattern
intersects	geo:sfIntersects	geo:SpatialObject	All	(T***** *T***** ***T***** ****T****)
touches	geo:sfTouches	geo:SpatialObject	All except P/P	(FT***** F**T***** F***T****)
within	geo:sfWithin	geo:SpatialObject	All	(TF***F****)
contains	geo:sfContains	geo:SpatialObject	All	(T*****FF*)
overlaps	geo:sfOverlaps	geo:SpatialObject	A/A, P/P, L/L	(T*T***T**) for A/A, P/P; (1*T***T**) for L/L
crosses	geo:sfCrosses	geo:SpatialObject	P/L, P/A, L/A, L/L	(T*T***T**) for P/L, P/A, L/A; (0******) for L/L

## 7.3. Egenhofer Relation Family

This clause defines Requirements for the 9-intersection model for the binary topological relations (*Egenhofer*) relation family. The reader should consult references [FORMAL] and [CATEG] for a more detailed discussion of *Egenhofer* relations.

**Req 10** Implementations shall allow the properties `geo:ehEquals`, `geo:ehDisjoint`, `geo:ehMeet`, `geo:ehOverlap`, `geo:ehCovers`, `geo:ehCoveredBy`, `geo:ehInside` and `geo:ehContains` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/topology-vocab-extension/eh-spatial-relations>

Topological relations in the *Egenhofer* family are summarized in Table 3. Multi-row intersection patterns should be interpreted as a logical OR of each row.

Table 3. *Egenhofer* Topological Relations

Relation Name	Relation IRI	Domain/Range	Applies To Geometry Types	DE-9IM Intersection Pattern
equals	geo:ehEquals	geo:SpatialObject	All	(TFFFTFFFT)
disjoint	geo:ehDisjoint	geo:SpatialObject	All	(FF*FF****)
meet	geo:ehMeet	geo:SpatialObject	All except P/P	(FT***** F**T***** F***T****)
overlap	geo:ehOverlap	geo:SpatialObject	All	(T*T***T**)

Relation Name	Relation IRI	Domain/Range	Applies To Geometry Types	DE-9IM Intersection Pattern
covers	<a href="#">geo:ehCovers</a>	<a href="#">geo:SpatialObject</a>	A/A, A/L, L/L	(T*TFT*FF*)
covered by	<a href="#">geo:ehCoveredBy</a>	<a href="#">geo:SpatialObject</a>	A/A, L/A, L/L	(TFF*TFT**)
inside	<a href="#">geo:ehInside</a>	<a href="#">geo:SpatialObject</a>	All	(TFF*FFT**)
contains	<a href="#">geo:ehContains</a>	<a href="#">geo:SpatialObject</a>	All	(T*TFF*FF*)

## 7.4. RCC8 Relation Family

This clause defines Requirements for the region connection calculus basic 8 (*RCC8*) relation family. The reader should consult references [\[QUAL\]](#) and [\[LOGIC\]](#) for a more detailed discussion of *RCC8* relations.

**Req 11** Implementations shall allow the properties [geo:rcc8eq](#), [geo:rcc8dc](#), [geo:rcc8ec](#), [geo:rcc8po](#), [geo:rcc8tppi](#), [geo:rcc8tpp](#), [geo:rcc8ntpp](#), [geo:rcc8ntppi](#) to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/topology-vocab-extension/rcc8-spatial-relations>

Topological relations in the *RCC8* family are summarized in [Table 4](#).

*Table 4. RCC8 Topological Relations*

Relation Name	Relation IRI	Domain/Range	Applies To Geometry Types	DE-9IM Intersection Pattern
equals	<a href="#">geo:rcc8eq</a>	<a href="#">geo:SpatialObject</a>	A/A	(TFFFTFFFT)
disconnected	<a href="#">geo:rcc8dc</a>	<a href="#">geo:SpatialObject</a>	A/A	(FFFTFTTTT)
externally connected	<a href="#">geo:rcc8ec</a>	<a href="#">geo:SpatialObject</a>	A/A	(FFFTFTTTT)
partially overlapping	<a href="#">geo:rcc8po</a>	<a href="#">geo:SpatialObject</a>	A/A	(TTTTTTTTT)
tangential proper part inverse	<a href="#">geo:rcc8tppi</a>	<a href="#">geo:SpatialObject</a>	A/A	(TTFTTFFFT)
tangential proper part	<a href="#">geo:rcc8tpp</a>	<a href="#">geo:SpatialObject</a>	A/A	(TFFTTFTTT)
non-tangential proper part	<a href="#">geo:rcc8ntpp</a>	<a href="#">geo:SpatialObject</a>	A/A	(TFFFTFTTT)
non-tangential proper part inverse	<a href="#">geo:rcc8ntppi</a>	<a href="#">geo:SpatialObject</a>	A/A	(TTTFFTFFFT)



## 7.5. Equivalent RCC8, Egenhofer and Simple Features Topological Relations

Table 5 summarizes the equivalences between *Egenhofer*, *RCC8* and *Simple Features* spatial relations for closed, non-empty regions. The symbol + denotes logical OR, and the symbol ¬ denotes negation.

Table 5. Equivalent Simple Features, RCC8 and Egenhofer relations

Simple Features	RCC8	Egenhofer
equals	equals	equals
disjoint	disconnected	disjoint
intersects	¬ disconnected	¬ disjoint
touches	externally connected	meet
within	non-tangential proper part + tangential proper part	inside + coveredBy
contains	non-tangential proper part inverse + tangential proper part inverse	contains + covers
overlaps	partially overlapping	overlap

# Chapter 8. Geometry Extension

This clause defines the *Geometry Extension* parameterized Requirements class with the base IRI [/req/geometry-extension](#). There is a single corresponding conformance class *Geometry Extension*, with the IRI [/conf/geometry-extension](#). These Requirements define a vocabulary for asserting and querying information about geometry data, and define query functions for operating on geometry data.

As part of the vocabulary, RDFS datatypes are defined for encoding detailed geometry information as a literal value. A literal representation of a geometry is needed so that geometric values may be treated as a single unit. Such a representation allows geometries to be passed to external functions for computations and to be returned from a query.

## 8.1. Rationale

Other schemes for encoding simple geometry data in RDF have been implemented. The W3C Basic Geo vocabulary<sup>[1]</sup> was an early (2003) RDF vocabulary for "representing lat(itude), long(itude) and other information about spatially-located things. Geo specifies WGS84 as the reference datum". Further, many widely used Semantic Web vocabularies contain some spatial data support. For example, *Dublin Core Terms* provides a *Location* class<sup>[2]</sup> for "A spatial region or named place." and *schema.org* provides a number of spatial object and geometry classes, such as [GeoCoordinates](#)<sup>[3]</sup> and [GeoShape](#)<sup>[4]</sup>.

Many vocabularies such as the above provide little specific support for detailed geometries and only specify using the WGS84 Coordinate Reference System (CRS).

Since the first version of GeoSPARQL, many ontologies have imported GeoSPARQL. For example, the *ISA Programme Location Core Vocabulary*<sup>[5]</sup> whose usage notes provide examples containing GeoSPARQL literals and the use of GeoSPARQL's "geometry class". The W3C's more recent *Data Catalog Vocabulary, Version 2* (DCAT2) standard<sup>[6]</sup> similarly contains usage notes for [geometry](#), [bbox](#) and other properties that suggest the use of GeoSPARQL literals.

Some of the properties defined in these vocabularies, such as DCAT2's [dcat:spatialResolution](#) have motivated the inclusion of new properties in this version of GeoSPARQL. In this case the equivalent property is [geo:hasSpatialResolution](#). The GeoSPARQL 1.1 Standards Working Group charter [\[CHARTER\]](#) contains references to a number of vocabularies/ontologies that were influential in the generation of this version of GeoSPARQL.

## 8.2. GeoSPARQL and Simple Features (SFA-CA)

The GeoSPARQL Geometry Extension is largely based on the ISO/OGC Simple Features Access - Common Architecture (SFA-CA) Standard [\[OGCSFACA\]](#). Contrary to what the name may imply, SFA-CA is about Geometry and not about Features. SFA-CA describes simple geometry, meaning that geometric shapes are based on points and straight lines (linear interpolations) between points. Within a single Geometry, these lines may not cross.

Neither GeoSPARQL nor SFA-CA support full three dimensional geometry. Coordinates may be three-dimensional, which means that points may have a Z-coordinate next to an X- and Y-

coordinate. The Z-coordinate then holds the value of height or depth. However, lines or surfaces can only have one Z value for any explicit or interpolated X,Y pair. This approach is often referred to as 2.5 dimensional geometry. Geometric functions working with Geometries that have Z values will ignore Z values in calculations and first project geometry onto the Z=0 level.

SFA-CA also describes M coordinate values that may be part of geometry encodings. The M value represents a measure, a value that can be used in information systems that support linear referencing. GeoSPARQL at the moment does not support linear referencing. Like Z values in coordinates, M values are to be ignored.

SFA-CA specifies a class hierarchy for Geometry. Although these classes are not part of the GeoSPARQL ontology, the GeoSPARQL SWG does publish a vocabulary of Simple Features geometry: <http://www.opengis.net/ont/sf>. Geometry types defined in this vocabulary can be considered safe to use with GeoSPARQL. The two Geometry serializations that were specified in GeoSPARQL 1.0, WKT and GML, fully support all SFA-CA geometry types. However, the two Geometry serializations that were introduced in GeoSPARQL 1.1 do not. Some SFA-CA geometry types are not supported by either the OGC KML [OGCKML] or the GeoJSON format. For example, neither KML nor GeoJSON support the Triangulated Integrated Network (TIN) or Triangle geometry types.

## 8.3. Recommendation for units of measure

For geometric data to be interpreted and used correctly, the units of measure should be known. Typically, the particular Spatial Reference System (SRS) that is associated with a Geometry instance will specify a unit of measurement. However, some elements of GeoSPARQL allow arbitrary units of distance to be used, for example the property `geo:hasSpatialResolution` or the function `geof:buffer`. In those cases it is advisable to make use of a well-known web vocabulary for units of measurement. Making the unit of measurement explicit will improve data interoperability. The recommended vocabulary for units of measurement for GeoSPARQL is the *Quantities, Units, Dimensions and Types (QUDT)* ontology<sup>[7]</sup> but others may be used, as long as they are well-described.

## 8.4. Influence of Reference Systems on computations

A Geometry object consists of a set of coordinates and a specification on how the coordinates should be interpreted. This specification is known as a Spatial reference System (SRS). Taken together, coordinates and SRS allow performing computations on Geometry objects. For example, sizes can be calculated or new Geometry objects can be created. Some Spatial Reference Systems describe a two-dimensional flat space. In that case, coordinates are understood to be Cartesian, and Cartesian geometric computations can be performed. But Spatial Reference Systems can describe other types of spaces, to which Cartesian computations are not applicable. For example, if CRS `<http://www.opengis.net/def/crs/OGC/1.3/CRS84>` is used, coordinates are to be interpreted as decimal degrees of latitude and longitude, designating positions on a spheroid. The distance between two points using this CRS is different from the distance between two points that have the same coordinates but are based on a Cartesian CRS or other SRS.

To avoid erroneous computations involving Geometry, data publishers are recommended to clearly indicate the type of space that is described by the SRS.

## 8.5. Parameters

The following parameters are defined for the *Geometry Extension* Requirements.

### serialization

Specifies the serialization standard to use when generating geometry literals as well as the supported geometry types.

#### NOTE

A serialization strongly affects the geometry conceptualization. The WKT serialization aligns the geometry types with *ISO 19125 Simple Features* [OGCSFACA] [ISO19125-1]; the GML serialization aligns the geometry types with *ISO 19107 Spatial Schema* [ISO19107].

### version

Specifies the version of the serialization format used.

## 8.6. Geometry Class

A single root geometry class is defined: **geo:Geometry**. In addition, properties are defined for describing geometry data and for associating geometries with features.

One container class is defined: **Geometry Collection**.

### 8.6.1. Class: geo:Geometry

The class **geo:Geometry** is conceptually derived from UML class **Geometry** in [ISO19107] which is that standard's "root class of the geometric object taxonomy and supports interfaces common to all geographically referenced geometric objects". **geo:Geometry** is defined by the following:

```
geo:Geometry
  a rdfs:Class, owl:Class ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Geometry"@en ;
  rdfs:subClassOf geo:SpatialObject ;
  owl:disjointWith geo:Feature;
  skos:definition "A coherent set of direct positions in space. The positions
                  are held within a Spatial Reference System (SRS)."@en ;
  skos:note "Geometry can be used as a representation of the shape, extent or
            location of a Feature and may exist as a self-contained entity."@en ;
  .
```

**Req 12** Implementations shall allow the RDFS class **geo:Geometry** to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/geometry-class>

## 8.6.2. Class: `geo:GeometryCollection`

The class `Geometry Collection` is defined by the following:

```
geo:GeometryCollection
  a owl:Class ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Geometry Collection"@en ;
  skos:definition "A collection of individual Geometries."@en ;
  rdfs:subClassOf geo:SpatialObjectCollection ;
  rdfs:subClassOf [
    a owl:Restriction ;
    owl:allValuesFrom geo:Geometry ;
    owl:onProperty rdfs:member ;
  ] ;
.
```

Membership of the general `Spatial Object Collection` that defines this class is restricted to instances of `Geometry`. `geo:GeometryCollection` members are to be indicated with the `rdfs:member` property.

### NOTE

There is no RDF/ontology relationship between this `geo:GeometryCollection` class and the Simple Features Vocabulary's `sf:GeometryCollection` class since the former is a collection of `geo:Geometry` objects and the latter is to be used for compound geometry literals.

`sf:GeometryCollection` instances can act as input or output of GeoSPARQL functions whereas `geo:GeometryCollection` instances are more likely to be used for grouping `geo:Geometry` objects for other purposes.

Many geometry literal formats also have the ability to represent multiple geometries. Both the OGC Geography Markup Language (GML) and KML use a *MultiGeometry* type and Well Known Text (WKT) and GeoJSON use a *GeometryCollection* type. While the names of some of these objects are the same as this class' and all the concepts are similar, there is also no RDF/ontology relationship between this class and these literals. This class contains whole `geo:Geometry` instances, which may have more information within them than just a geometry serialization.

As per the expected use of `sf:GeometryCollection` instances mentioned above: the uses of multi-geometry literals and `geo:GeometryCollection` instances is expected to be different too.

**Req 13** Implementations shall allow the RDFS class `geo:GeometryCollection` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/core/geometry-collection-class>

## 8.7. Standard Properties for geo:Geometry

Properties are defined for describing geometry metadata.

**Req 14** Implementations shall allow the properties `geo:dimension`, `geo:coordinateDimension`, `geo:spatialDimension`, `geo:hasSpatialResolution`, `geo:hasMetricSpatialResolution`, `geo:hasSpatialAccuracy`, `geo:hasMetricSpatialAccuracy`, `geo:isEmpty`, `geo:isSimple` and `geo:hasSerialization` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geometry-properties>

### 8.7.1. Property: `geo:dimension`

The property `geo:dimension` is used to link a Geometry object to its topological dimension, which must be less than or equal to the coordinate dimension. In non-homogeneous collections, this will return the largest topological dimension of the contained objects.

```
geo:dimension
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "dimension"@en ;
  skos:definition "The topological dimension of this geometric object, which
                  must be less than or equal to the coordinate dimension. In
                  non-homogeneous collections, this is the largest
                  topological dimension of the contained objects."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range xsd:integer ;
  .
```

### 8.7.2. Property: `geo:coordinateDimension`

The property `geo:coordinateDimension` is defined to link a Geometry object to the dimension of direct positions (coordinate tuples) used in the Geometry's definition.

```
geo:coordinateDimension
  a rdf:Property, owl:DatatypeProperty;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "coordinate dimension"@en ;
  skos:definition "The number of measurements or axes needed to describe the
                  position of this Geometry in a coordinate system."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range xsd:integer ;
  .
```

### 8.7.3. Property: `geo:spatialDimension`

The property `geo:spatialDimension` is defined to link a Geometry object to the dimension of the

spatial portion of the direct positions (coordinate tuples) used in its serializations. If the direct positions do not carry a measure coordinate, this will be equal to the coordinate dimension.

```
geo:spatialDimension
  a rdf:Property, owl:DatatypeProperty;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "spatial dimension"@en ;
  skos:definition "The number of measurements or axes needed to describe the
                  spatial position of this Geometry in a coordinate system."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range xsd:integer ;
.
```

#### 8.7.4. Property: `geo:hasSpatialResolution`

The property `geo:hasSpatialResolution` is defined to indicate the spatial resolution of the elements within a Geometry. Spatial resolution specifies the level of detail of a Geometry. It is the smallest distinguishable distance between adjacent coordinate sets. This property is not applicable to a point Geometry, because a point consists of a single coordinate set.

Since this property is defined for a `geo:Geometry`, all literal representations of that Geometry instance must have the same spatial resolution.

```
geo:hasSpatialResolution
  a rdf:Property, owl:ObjectProperty;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "has spatial resolution"@en ;
  skos:definition "The spatial resolution of a Geometry"@en ;
  rdfs:domain geo:Geometry ;
.
```

**NOTE**     See the [\[Recommendation for specification of units of measurement\]](#).

#### 8.7.5. Property: `geo:hasMetricSpatialResolution`

The property `geo:hasMetricSpatialResolution` is similar to `geo:hasSpatialResolution`, except that the unit of resolution is always meter (the standard distance unit of the International System of Units).

```
geo:hasMetricSpatialResolution
  a rdf:Property, owl:ObjectProperty;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "has spatial resolution in meters"@en ;
  skos:definition "The spatial resolution of a Geometry in meters."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range xsd:double ;
.
```

### 8.7.6. Property: `geo:hasSpatialAccuracy`

The property `geo:hasSpatialAccuracy` is applicable when a Geometry is used to represent a Feature. It is expressed as a distance that indicates the truthfulness of the positions (coordinates) that define the Geometry. In this case accuracy defines a zone surrounding each coordinate within which the real positions are known to be. The accuracy value defines this zone as a distance from the coordinate(s) in all directions (e.g. a line, a circle or a sphere, depending on spatial dimension).

```
geo:hasSpatialAccuracy
  a rdf:Property, owl:ObjectProperty;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "has spatial accuracy"@en ;
  skos:definition "The positional accuracy of the coordinates of a Geometry."@en ;
  rdfs:domain geo:Geometry ;
  .
```

**NOTE** See the [\[Recommendation for specification of units of measurement\]](#).

### 8.7.7. Property: `geo:hasMetricSpatialAccuracy`

The property `geo:hasMetricSpatialAccuracy` is similar to `has spatial accuracy`, but is easier to specify and use because the unit of distance is always meter (the standard distance unit of the International System of Units).

```
geo:hasMetricSpatialAccuracy
  a rdf:Property, owl:ObjectProperty;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "has spatial accuracy in meters"@en ;
  skos:definition "The positional accuracy of the coordinates of a Geometry in meters."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range xsd:double ;
  .
```

### 8.7.8. Property: `geo:isEmpty`

The property `geo:isEmpty` will indicate a Boolean object set to `true` if and only if the Geometry contains no information.

```
geo:isEmpty
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "is empty"@en ;
  skos:definition "(true) if this geometric object is the empty Geometry. If true, then this geometric object represents the empty point set for the coordinate space."@en ;
  rdfs:domain geo:Geometry ;
  .
```



```
rdfs:range xsd:boolean ;
```

```
.
```

### 8.7.9. Property: `geo:isSimple`

The property `geo:isSimple` will indicate a Boolean object set to `true` if and only if the Geometry contains no self-intersections, with the possible exception of its boundary.

```
geo:isSimple
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "is simple"@en ;
  skos:definition "(true) if this geometric object has no anomalous geometric
                  points, such as self intersection or self tangency."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range xsd:boolean ;
.
```

### 8.7.10. Property: `geo:hasSerialization`

The property `geo:hasSerialization` is defined to connect a Geometry with its text-based serialization (e.g., its WKT serialization).

```
geo:hasSerialization
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "has serialization"@en ;
  skos:definition "Connects a Geometry object with its text-based serialization."@en
;
  rdfs:domain geo:Geometry ;
  rdfs:range rdfs:Literal ;
.
```

#### NOTE

this property is the generic property used to connect a Geometry with its serialization. GeoSPARQL also contains a number of sub properties of this property for connecting serializations of common types with geometries, for example [as GeoJSON](#) which can be used for GeoJSON [\[GEOJSON\]](#) literals.

## 8.8. Geometry Serializations

This section establishes the Requirements class for representing Geometry data in RDF literals, according to different non-RDF systems.

GeoSPARQL presents specializations of the `geo:hasSerialization` property for indicating particular serializations and specialized datatype literals for containing them. It does not provide comprehensive definitions of their content since these are given in standards external to

GeoSPARQL, all of which are referenced.

GeoSPARQL does present some Requirements for literal structure which extend the serialization-defining standards, for example the requirement to allow indications of spatial reference systems within WKT geometry representations.

GeoSPARQL's expectation of RDF literal representations of geometry data is that it is related to the *Simple Features Access* (SFA) [OGCSFACA] [ISO19125-1] standard's conceptualization of geometry which defines classes such as **Point**, **Curve** and **Surface** and specialized variants of them which it presents in a hierarchy. All SFA classes are represented in OWL in the *Simple Features Vocabulary* presented within GeoSPARQL as an independent profile element, see [GeoSPARQL Standard structure](#).

Some geometry representation systems given here do not use the same terminology as SFA, in particular Discrete Global Grid Systems. To know the extent to which geometry literal representations listed here support SFA, or map to SFA, please see their definitions.

### 8.8.1. Well-Known Text

This section establishes the requirements for representing Geometry data in RDF based on Well-Known Text (WKT) as defined by *Simple Features Access* [OGCSFACA] [ISO19125-1]. It defines one RDFS Datatype: **WKT Literal** and one property, as **WKT**.

#### 8.8.1.1. RDFS Datatype: **geo:wktLiteral**

The datatype **geo:wktLiteral** is used to contain the Well-Known Text (WKT) serialization of a Geometry.

```
geo:wktLiteral
  a rdfs:Datatype ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "Well-known Text literal"@en ;
  skos:definition "A Well-known Text serialization of a Geometry object."@en ;
  .
```

**Req 15** All RDFS Literals of type **geo:wktLiteral** shall consist of an optional IRI identifying the coordinate reference system and a required Well Known Text (WKT) description of a geometric value. Valid **geo:wktLiteral** instances are formed by either a WKT string as defined in [ISO13249] or by concatenating a valid absolute IRI, as defined in [IETF3987], enclosed in angled brackets (< & >) followed by whitespace as a separator, and a WKT string as defined in [ISO13249].

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/wkt-literal>

The following *ABNF* [IETF5234] syntax specification formally defines this literal:

```
wktLiteral ::= opt-iri-and-whitespace geometry-data
```

```
opt-iri-and-space = "<" IRI ">" LWSP / ""
```

The token **opt-iri-and-whitespace** may be either an IRI and whitespace (spaces, tabs, newlines) or nothing (""), the token **IRI** (Internationalized Resource Identifier) is essentially a web address and is defined in [IETF3987] and the token **LWSP**, is one or more white space characters, as defined in [IETF5234]. **geometry-data** is the Well-Known Text representation of the Geometry, defined in [ISO13249].

In the absence of a leading spatial reference system IRI, the following spatial reference system IRI will be assumed: <http://www.opengis.net/def/crs/OGC/1.3/CRS84>. This IRI denotes WGS 84 longitude-latitude.

**Req 16** The IRI <http://www.opengis.net/def/crs/OGC/1.3/CRS84> shall be assumed as the spatial reference system for **geo:wktLiteral** instances that do not specify an explicit spatial reference system IRI.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/wkt-literal-default-srs>

The OGC maintains a set of SRS IRIs under the <http://www.opengis.net/def/crs/> namespace and IRIs from this set are recommended for use. However others may also be used, as long as they are valid IRIs.

**Req 17** Coordinate tuples within **geo:wktLiteral** shall be interpreted using the axis order defined in the spatial reference system used.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/wkt-axis-order>

The example **WKT Literal** below encodes a point Geometry using the default WGS84 geodetic longitude-latitude spatial reference system:

```
"Point(-83.38 33.95)"^^<http://www.opengis.net/ont/geosparql#wktLiteral>
```

A second example below encodes the same point as encoded in the example above but using a SRS identified by <http://www.opengis.net/def/SRS/EPSSG/0/4326>: a WGS 84 geodetic latitude-longitude spatial reference system (note that this spatial reference system defines a different axis order):

```
"<http://www.opengis.net/def/crs/EPSSG/0/4326> Point(33.95  
-83.38)"^^<http://www.opengis.net/ont/geosparql#wktLiteral>
```

**Req 18** An empty RDFS Literal of type **geo:wktLiteral** shall be interpreted as an empty Geometry.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/wkt-literal-empty>

#### 8.8.1.2. Property: **geo:asWKT**

The property **geo:asWKT** is defined to link a Geometry with its WKT serialization.

**Req 19** Implementations shall allow the RDF property `geo:asWKT` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/geometry-as-wkt-literal>

```
geo:asWKT
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:subPropertyOf geo:hasSerialization ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "as WKT"@en ;
  skos:definition "The WKT serialization of a Geometry."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range geo:wktLiteral ;
  .
```

#### 8.8.1.3. Function: `geof:asWKT`

```
geof:asWKT (geom: ogc:geomLiteral): geo:wktLiteral
```

The function `geof:asWKT` converts `geom` to an equivalent WKT representation preserving the spatial reference system.

**Req 20** Implementations shall support `geo:asWKT` as a SPARQL extension function.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/asWKT-function>

### 8.8.2. Geography Markup Language

This section establishes a Requirements class for representing Geometry data in RDF based on GML as defined by the Geography Markup Language Encoding Standard [OGC07-036]. It defines one RDFS Datatype: `GML Literal` and one property, `as GML`.

#### 8.8.2.1. RDFS Datatype: `geo:gmlLiteral`

The datatype `geo:gmlLiteral` is used to contain the Geography Markup Language (GML) serialization of a Geometry.

```
geo:gmlLiteral
  a rdfs:Datatype ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "GML literal"@en ;
  skos:definition "The datatype of GML literal values"@en ;
  .
```

Valid `GML Literal` instances are formed by encoding Geometry information as a valid element from the GML schema that implements a subtype of `GM_Object`. For example, in GML 3.2.1 this is every element directly or indirectly in the substitution group of the element

{<http://www.opengis.net/ont/gml/3.2>}AbstractGeometry. In GML 3.1.1 and GML 2.1.2 this is every element directly or indirectly in the substitution group of the element {<http://www.opengis.net/ont/gml>}\_Geometry.

**Req 21** All `geo:gmlLiteral` instances shall consist of a valid element from the GML schema that implements a subtype of `GM_Object` as defined in [OGC07-036].

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/gml-literal>

The example [GML Literal](#) below encodes a point Geometry in the WGS 84 geodetic longitude-latitude spatial reference system using GML version 3.2:

```
"""
<gml:Point
  srsName="http://www.opengis.net/def/crs/OGC/1.3/CRS84\"
  xmlns:gml="http://www.opengis.net/gml/3.2\">
  <gml:pos>-83.38 33.95</gml:pos>
</gml:Point>
""""^<http://www.opengis.net/ont/geosparql#gmlLiteral>
```

**Req 22** An empty `geo:gmlLiteral` shall be interpreted as an empty Geometry.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/gml-literal-empty>

**Req 23** Implementations shall document supported GML profiles.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/gml-profile>

#### 8.8.2.2. Property: `geo:asGML`

The property `geo:asGML` is defined to link a Geometry with its GML serialization.

**Req 24** Implementations shall allow the RDF property `geo:asGML` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/geometry-as-gml-literal>

```
geo:asGML
  a rdf:Property ;
  rdfs:subPropertyOf geo:hasSerialization ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "as GML"@en ;
  skos:definition "The GML serialization of a Geometry."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range geo:gmlLiteral ;
.
```

#### 8.8.2.3. Function: `geo:asGML`

```
geof:asGML (geom: ogc:geomLiteral, gmlProfile: xsd:string): geo:gmlLiteral
```

The function `geof:asGML` converts `geom` to an equivalent GML representation defined by a `gmlProfile` version string preserving the coordinate reference system.

**Req 25** Implementations shall support `geof:asGML` as a SPARQL extension function.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/asGML-function>

### 8.8.3. GeoJSON

This section establishes a Requirements class for representing Geometry data in RDF based on Geographic JavaScript Object Notation (GeoJSON) as defined by [Section 8.8.3](#). It defines one RDFS Datatype: [GeoJSON Literal](#) and one property, [as GeoJSON](#).

#### 8.8.3.1. RDFS Datatype: `geo:geoJSONLiteral`

The datatype `geo:geoJSONLiteral` is used to contain the GeoJSON serialization of a Geometry.

```
geo:geoJSONLiteral a rdfs:Datatype ;  
  rdfs:isDefinedBy geo: ;  
  skos:prefLabel "GeoJSON Literal"@en ;  
  skos:definition "A GeoJSON serialization of a Geometry object."@en .
```

Valid [GeoJSON Literal](#) instances are formed by encoding Geometry information as a Geometry object as defined in the GeoJSON specification [\[GEOJSON\]](#).

**Req 26** All `geo:geoJSONLiteral` instances shall consist of the Geometry objects as defined in the GeoJSON specification [\[GEOJSON\]](#).

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geojson-literal>

**Req 27** RDFS Literals of type `geo:geoJSONLiteral` do not contain a SRS definition. All literals of this type shall, according to the GeoJSON specification, be encoded only in, and be assumed to use, the WGS84 geodetic longitude-latitude spatial reference system (<http://www.opengis.net/def/crs/OGC/1.3/CRS84>).

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geojson-literal-srs>

The example [GeoJSON Literal](#) below encodes a point Geometry using the default WGS84 geodetic longitude-latitude spatial reference system for Simple Features 1.0:

```
""  
{ "type": "Point", "coordinates": [-83.38, 33.95] }  
""^^<http://www.opengis.net/ont/geosparql#geoJSONLiteral>
```

**Req 28** An empty RDFS Literal of type `geo:geoJSONLiteral` shall be interpreted as an empty Geometry, i.e. `{"geometry": null}` in GeoJSON .

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geojson-literal-empty>

#### 8.8.3.2. Property: `geo:asGeoJSON`

The property `geo:asGeoJSON` is defined to link a Geometry with its GeoJSON serialization.

**Req 29** Implementations shall allow the RDF property `geo:asGeoJSON` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geometry-as-geojson-literal>

```
geo:asGeoJSON
  a rdf:Property, owl:DatatypeProperty ;
  rdfs:subPropertyOf geo:hasSerialization ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "as GeoJSON"@en ;
  skos:definition "The GeoJSON serialization of a Geometry."@en ;
  rdfs:domain geo:Geometry ;
  rdfs:range geo:geoJSONLiteral ;
  .
```

#### 8.8.3.3. Function: `geof:asGeoJSON`

```
geof:asGeoJSON (geom: ogc:geomLiteral): geo:geoJSONLiteral
```

The function `geof:asGeoJSON` converts `geom` to an equivalent GeoJSON representation. Coordinates are converted to the CRS84 coordinate system, the only valid coordinate system to be used in a GeoJSON literal.

**Req 30** Implementations shall support `geof:asGeoJSON` as a SPARQL extension function.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/asGeoJSON-function>

### 8.8.4. Keyhole Markup Language

This section establishes the Requirements class for representing Geometry data in RDF based on KML as defined by [OGCKML]. It defines one RDFS Datatype: `KML Literal` and one property, `as KML`.

#### 8.8.4.1. RDFS Datatype: `geo:kmlLiteral`

The datatype `geo:kmlLiteral` is used to contain the Keyhole Markup Language (KML) serialization of a Geometry.

```
geo:kmlLiteral
  a rdfs:Datatype ;
  rdfs:isDefinedBy geo: ;
```

```
skos:prefLabel "KML Literal"@en ;
skos:definition "A KML serialization of a Geometry object."@en ;
```

Valid **KML Literal** instances are formed by encoding Geometry information as a Geometry object as defined in the KML specification [OGCKML].

**Req 31** All `geo:kmlliteral` instances shall consist of the Geometry objects as defined in the KML specification [OGCKML].

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/kml-literal>

**Req 32** RDFS Literals of type `geo:kmlliteral` do not contain a SRS definition. All literals of this type shall according to the KML specification only be encoded in and assumed to use the WGS84 geodetic longitude-latitude spatial reference system (<http://www.opengis.net/def/crs/OGC/1.3/CRS84>).

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/kml-literal-srs>

The example **KML Literal** below encodes a point Geometry using the default WGS84 geodetic longitude-latitude spatial reference system for Simple Features 1.0:

```
"""
<Point xmlns="http://www.opengis.net/kml/2.2">
  <coordinates>-83.38,33.95</coordinates>
</Point>
""""^<http://www.opengis.net/ont/geosparql#kmlliteral>
```

**Req 33** An empty RDFS Literal of type `geo:kmlliteral` shall be interpreted as an empty Geometry .

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/kml-literal-empty>

#### 8.8.4.2. Property: `geo:asKML`

The property `geo:asKML` is defined to link a Geometry with its KML serialization.

**Req 34** Implementations shall allow the RDF property `geo:asKML` to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geometry-as-kml-literal>

The property `as KML` is used to link a geometric element with its KML serialization.

```
geo:asKML
  a rdf:Property, owl:DatatypeProperty;
  rdfs:subPropertyOf geo:hasSerialization ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "as KML"@en ;
  skos:definition "The KML serialization of a Geometry."@en ;
  rdfs:domain geo:Geometry ;
```



```
rdfs:range geo:kmlLiteral ;
```

```
.
```

#### 8.8.4.3. Function: `geof:asKML`

```
geof:asKML (geom: ogc:geomLiteral): geo:kmlLiteral
```

The function `geof:asKML` converts `geom` to an equivalent KML representation. Coordinates are converted to the CRS84 coordinate system, the only valid coordinate system to be used in a KML literal.

**Req 35** Implementations shall support `geof:asKML` as a SPARQL extension function.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/asKML-function>

#### 8.8.5. Discrete Global Grid System

This section establishes the Requirements class for representing Discrete Global Grid System (DGGS) Geometry data as RDF literals. The form of geometry data representation is specific to individual DGGS implementations: known DGGSes are not compatible or even very similar.

The Requirements class defines one RDFS Datatype `http://www.opengis.net/ont/geosparql#dggsLiteral` and one property, `http://www.opengis.net/ont/geosparql#asDGGS`.

##### 8.8.5.1. RDFS Datatype: `geo:dggsLiteral`

The datatype `geo:dggsLiteral` is used to contain the Discrete Global Grid System (DGGS) serialization of a Geometry.

```
geo:dggsLiteral
  a rdfs:Datatype ;
  rdfs:isDefinedBy geo: ;
  skos:prefLabel "DGGS Literal"@en ;
  skos:definition "A textual serialization of a Discrete Global Grid System (DGGS)
  Geometry object."@en
.
```

Valid `DGGS Literal` instances are formed by encoding Geometry information according to a specific DGGS implementation. The specific implementation should be indicated by use of a subclass of the `geo:dggsLiteral` datatype.

**Req 36** All RDFS Literals of type `geo:dggsLiteral` shall consist of an IRI identifying the specific DGGS and a representation of the DGGS geometry data. The IRI shall be enclosed in angled brackets (`<` & `>`) followed by whitespace as a separator, and then the DGGS geometry data, formulated according to the identified DGGS.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/dggs-literal>

The following *ABNF* [IETF5234] syntax specification formally defines this literal:

```
dggsLiteral ::= iri-and-whitespace dggs-geometry-data  
  
iri-and-whitespace = "<" IRI ">" LWSP
```

The token *iri-and-whitespace* is an IRI and whitespace. The token *IRI* (Internationalized Resource Identifier) is essentially a web address and is defined in [IETF3987]. The token *LWSP* is one or more whitespace characters, as defined in [IETF5234]. *dggs-geometry-data* is geometry data formulated according to the DGGS identified by *IRI*.

An example of a DGGS literal for the AusPIX DGGS could be:

```
"<https://w3id.org/dggs/auspix> CELL (R3234)"^^geo:dggsLiteral
```

Where AusPIX is identified with the IRI <https://w3id.org/dggs/auspix> and *CELL (R3234)* is the representation of a geometry according to AusPIX.

**NOTE** What *R3234* means, or the meaning of any other element within a DGGS' geometry data is not handled by GeoSPARQL, just as GeoPSARQL does not delve into the internals of other Geometry formats such as WKT or GeoJSON.

**Req 37** An empty RDFS Literal of type *geo:dggsLiteral*, shall be interpreted as an empty *geo:Geometry*.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/dggs-literal-empty>

The following *ABNF* [IETF5234] syntax specification formally defines this literal:

```
dggsLiteral ::= iri-and-space dggs-geometry-data  
  
iri-and-whitespace = "<" IRI ">" LWSP / ""
```

The tokens used above are as per the DGGS *ABNF* above.

#### 8.8.5.2. Property: *geo:asDGGS*

The property *geo:asDGGS* is defined to link a Geometry with its DGGS serialization.

**Req 38** Implementations shall allow the RDF property *geo:asDGGS* to be used in SPARQL graph patterns.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/geometry-as-dggs-literal>

```
geo:asDGGS  
  a rdf:Property, owl:DatatypeProperty ;  
  rdfs:subPropertyOf geo:hasSerialization ;
```

```

rdfs:isDefinedBy geo: ;
skos:prefLabel "as DGGs"@en ;
skos:definition "A DGGs serialization of a Geometry."@en ;
rdfs:domain geo:Geometry ;
rdfs:range geo:dggLiteral ;
.

```

### 8.8.5.3. Function: `geof:asDGGs`

`geof:asDGGs (geom: ogc:geomLiteral, specificDggsDatatype: xsd:anyURI): geo:DggsLiteral`

The function `geof:asDGGs` converts `geom` to an equivalent DGGs representation, formulated according to the specific DGGs literal indicated by the IRI required to be present in the DGGs literal.

**Req 39** Implementations shall support `geof:asDGGs` as a SPARQL extension function.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/asDGGs-function>

## 8.9. Non-topological Query Functions

This Requirements class defines SPARQL functions for performing non-topological spatial operations.

**Req 40** Implementations shall support the functions `geof:boundary`, `geof:boundingCircle`, `geof:metricBuffer`, `geof:buffer`, `geof:convexHull`, `geof:concaveHull`, `geof:coordinateDimension`, `geof:difference`, `geof:dimension`, `geof:metricDistance`, `geof:distance`, `geof:envelope`, `geof:geometryType`, `geof:getSRID`, `geof:intersection`, `geof:is3D`, `geof:isEmpty`, `geof:isMeasured`, `geof:isSimple`, `geof:spatialDimension`, `geof:symDifference`, `geof:transform` and `geof:union` as SPARQL extension functions, consistent with definitions of these functions in Simple Features [OGCSFACA] [ISO19125-1], for non-DGGs geometry literals.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/query-functions>

**Req 41** Implementations shall support the functions `geof:metricLength`, `geof:length`, `geof:metricPerimeter`, `geof:perimeter`, `geof:metricArea`, `geof:area`, `geof:geometryN`, `geof:maxX`, `geof:maxY`, `geof:maxZ`, `geof:minX`, `geof:minY`, `geof:minZ` and `geof:numGeometries` as SPARQL extension functions which are defined in this standard, for non-DGGs geometry literals.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/query-functions-non-sf>

#### NOTE

The Requirements to support non-topological query functions for DGGs geometry literals are separated from the Requirements to support them for traditional geometry literals as it is expected that implementing these functions for DGGs literals will be significantly more difficult. This is due to the novelty of DGGs literals and thus the lack of existing software libraries for their manipulation.

**Req 42** Implementations shall support the functions of Requirement 40 for DGGs geometry literals as SPARQL extension functions, in a manner which is consistent with definitions of these functions in Simple Features [OGCSFACA] [ISO19125-1], for non-DGGs geometry literals.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/query-functions-dggs>

**Req 43** Implementations shall support the functions of Requirement 41 for DGGs geometry literals as SPARQL extension functions which are defined in this standard, for non-DGGs geometry literals.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/query-functions-non-sf-dggs>

Functions from this Requirements class are listed below, alphabetically.

### 8.9.1. Function notes

These notes apply to all of the following functions in this section.

An invocation of any of the following functions with invalid arguments produces an error. An invalid argument includes any of the following:

- An argument of an unexpected type
- An invalid geometry literal value
- A non-fitting geometry type for the given function
- A geometry literal from a spatial reference system that is incompatible with the spatial reference system used for calculations
- An invalid unit IRI

A more detailed description of expected inputs and expected outputs of the given functions is shown in Annex B.

Unless otherwise stated in the function definition, the following behaviors should be followed by all SPARQL extension functions defined in the GeoSPARQL standard:

- Functions returning a new geometry literal should follow the literal format of the first geometry literal input parameter. If no geometry literal input parameter is present, a WKT literal shall be returned.
- Functions returning a new geometry literal should follow the SRS defined in the literal format of the first geometry literal input parameter. If no geometry literal input parameter is present, a geometry result should be returned in the CRS84 SRS.

For further discussion of the effects of errors during FILTER evaluation, consult Section 17<sup>[8]</sup> of the SPARQL specification [SPARQL].

Note that returning values instead of raising an error serves as an extension mechanism of SPARQL.

From Section 17.3.1<sup>[9]</sup> of the SPARQL specification [SPARQL]:

SPARQL language extensions may provide additional associations between

operators and operator functions; ... No additional operator may yield a result that replaces any result other ... . The consequence of this rule is that SPARQL **FILTER** s will produce at least the same intermediate bindings after applying a **FILTER** as an unextended implementation.

This extension mechanism enables GeoSPARQL implementations to simultaneously support multiple geometry serializations. For example, a system that supports **WKT Literal** serializations may also support **GML Literal** serializations and consequently would not raise an error if it encounters multiple geometry datatypes while processing a given query.

#### NOTE

Several non-topological query functions use a unit of measure IRI. See the [Recommendation for specification of units of measurement](#). Also, the OGC has recommended units of measure vocabularies for use, see the OGC Definitions Server<sup>[10]</sup>.

### 8.9.2. Function: **geof:metricArea**

```
geof:metricArea (geom: ogc:geomLiteral): xsd:double
```

Returns the area of **geom** in square meters. Must return zero for all geometry types other than Polygon. This function is similar to **geof:area** but does not need a specification of measurement unit.

### 8.9.3. Function: **geof:area**

```
geof:area (geom: ogc:geomLiteral, units: xsd:anyURI): rdf:Resource
```

Returns the area of **geom**. Must return zero for all geometry types other than Polygon. This function is similar to **geof:metricArea**, which does not need a specification of measurement unit.

#### NOTE

See the [Recommendation for specification of units of measurement](#).

### 8.9.4. Function: **geof:boundary**

```
geof:boundary (geom: ogc:geomLiteral): ogc:geomLiteral
```

This function returns the closure of the boundary of **geom**. Calculations are in the spatial reference system of **geom**.

### 8.9.5. Function: **geof:boundingCircle**

```
geof:boundingCircle (geom: ogc:geomLiteral): ogc:geomLiteral
```

This function returns the minimum bounding circle around **geom**. Calculations are in the spatial reference system of **geom**.

### 8.9.6. Function: **geof:metricBuffer**

```
geof:metricBuffer (geom: ogc:geomLiteral,  
                  radius: xsd:double): ogc:geomLiteral
```

Returns a geometric object that represents all Points whose distance from **geom** is less than or equal to the **radius** measured in meters. Calculations are in the coordinate reference system of **geom**. This function is similar to **geof:buffer**, but does not need a specification of measurement unit.

### 8.9.7. Function: **geof:buffer**

```
geof:buffer (geom: ogc:geomLiteral,  
            radius: xsd:double,  
            units: xsd:anyURI): ogc:geomLiteral
```

Returns a geometric object that represents all Points whose distance from **geom** is less than or equal to the **radius** measured in **units**. Calculations are in the spatial reference system of **geom**. This function is similar to **geof:metricBuffer**, which does not need a specification of measurement unit.

**NOTE** | See the [Recommendation for specification of units of measurement](#).

### 8.9.8. Function: **geof:convexHull**

```
geof:convexHull (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:convexHull** returns a geometric object that represents all Points in the convex hull of **geom**. Calculations are in the spatial reference system of **geom**.

### 8.9.9. Function: **geof:concaveHull**

```
geof:concaveHull (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:concaveHull** returns a geometric object that represents all Points in the concave hull of **geom**. Calculations are in the spatial reference system of **geom**.

### 8.9.10. Function: **geof:coordinateDimension**

```
geof:coordinateDimension (geom: ogc:geomLiteral): xsd:integer
```

Returns the coordinate dimension of **geom**.

### 8.9.11. Function: geof:difference

```
geof:difference (geom1: ogc:geomLiteral,  
                geom2: ogc:geomLiteral): ogc:geomLiteral
```

This function returns a geometric object that represents all Points in the set difference of **geom1** with **geom2**. Calculations are in the spatial reference system of **geom1**.

### 8.9.12. Function: geof:dimension

```
geof:dimension (geom: ogc:geomLiteral): xsd:integer
```

Returns the dimension of **geom**. In non-homogeneous geometry collections, this will return the largest topological dimension of the contained objects.

### 8.9.13. Function: geof:metricDistance

```
geof:metricDistance (geom1: ogc:geomLiteral,  
                    geom2: ogc:geomLiteral): xsd:double
```

Returns the shortest distance in meters between any two Points in the two geometric objects. Calculations are in the coordinate reference system of **geom1**. This function is similar to **geof:distance**, but does not need a specification of measurement unit.

### 8.9.14. Function: geof:distance

```
geof:distance (geom1: ogc:geomLiteral,  
              geom2: ogc:geomLiteral,  
              units: xsd:anyURI): xsd:double
```

Returns the shortest distance in **units** between any two Points in the two geometric objects. Calculations are in the spatial reference system of **geom1**. This function is similar to **geof:metricDistance**, which does not need a specification of measurement unit.

**NOTE** | See the [Recommendation for specification of units of measurement](#).

### 8.9.15. Function: geof:envelope

```
geof:envelope (geom: ogc:geomLiteral): ogc:geomLiteral
```

This function returns the minimum bounding box - a rectangle - of **geom**. Calculations are in the spatial reference system of **geom**.

### 8.9.16. Function: geof:geometryN

```
geof:geometryN (geom: ogc:geomLiteral, geomindex: xsd:integer): ogc:geomLiteral
```

Returns the nth geometry of **geom** if it is a GeometryCollection that is defined in a literal type (such as in the case of a sf:GeometryCollection) or **geom** if it is a Geometry. This function is not applicable to the type geo:GeometryCollection, as elements in geo:GeometryCollection are not guaranteed to be ordered.

### 8.9.17. Function: geof:geometryType

```
geof:geometryType (geom: ogc:geomLiteral): xsd:anyURI
```

Returns the URI of the subtype of Geometry of which this geometric object is a member. No attempt to reconcile different geometry subtypes across all support literals need be made.

### 8.9.18. Function: geof:getSRID

```
geof:getSRID (geom: ogc:geomLiteral): xsd:anyURI
```

Returns the spatial reference system IRI for **geom**.

### 8.9.19. Function: geof:intersection

```
geof:intersection (geom1: ogc:geomLiteral,  
                  geom2: ogc:geomLiteral): ogc:geomLiteral
```

Returns a geometric object that represents all Points in the intersection of **geom1** with **geom2**. Calculations are in the spatial reference system of **geom1**.

### 8.9.20. Function: geof:is3D

```
geof:is3D (geom: ogc:geomLiteral): xsd:boolean
```

Returns true if **geom** has z coordinate values.

### 8.9.21. Function: geof:isEmpty

```
geof:isEmpty (geom: ogc:geomLiteral): xsd:boolean
```

Returns true if **geom** is an empty geometry, i.e. contains no coordinates.



### 8.9.22. Function: geof:isMeasured

```
geof:isMeasured (geom: ogc:geomLiteral): xsd:boolean
```

Returns true if **geom** has m coordinate values.

### 8.9.23. Function: geof:isSimple

```
geof:isSimple (geom: ogc:geomLiteral): xsd:boolean
```

Returns true if **geom** is a simple geometry, i.e. has no anomalous geometric points, such as self intersection or self tangency.

### 8.9.24. Function: geof:metricLength

```
geof:metricLength (geom: ogc:geomLiteral): xsd:double
```

Returns the length of **geom** in meters. The longest length from any one dimension is returned. This function is similar to **geof:length** but does not need a specification of measurement unit.

### 8.9.25. Function: geof:length

```
geof:length (geom: ogc:geomLiteral, units: xsd:anyURI): xsd:double
```

Returns the length of **geom**. The longest length from any one dimension is returned. This function is similar to **geof:metricLength**, which does not need a specification of measurement unit.

#### NOTE

See the [Recommendation for specification of units of measurement](#).

### 8.9.26. Function: geof:maxX

```
geof:maxX (geom: ogc:geomLiteral): xsd:double
```

The function **geof:maxX** returns the maximum X coordinate for **geom**.

### 8.9.27. Function: geof:maxY

```
geof:maxY (geom: ogc:geomLiteral): xsd:double
```

The function **geof:maxY** returns the maximum Y coordinate for **geom**.

### 8.9.28. Function: geof:maxZ

```
geof:maxZ (geom: ogc:geomLiteral): xsd:double
```

The function **geof:maxZ** returns the maximum Z coordinate for **geom**.

### 8.9.29. Function: geof:minX

```
geof:minX (geom: ogc:geomLiteral): xsd:double
```

The function **geof:minX** returns the minimum X coordinate for **geom**.

### 8.9.30. Function: geof:minY

```
geof:minY (geom: ogc:geomLiteral): xsd:double
```

The function **geof:minY** returns the minimum Y coordinate for **geom**.

### 8.9.31. Function: geof:minZ

```
geof:minZ (geom: ogc:geomLiteral): xsd:double
```

The function **geof:minZ** returns the minimum Z coordinate for **geom**.

### 8.9.32. Function: geof:numGeometries

```
geof:numGeometries (geom: ogc:geomLiteral): xsd:integer
```

Returns the number of geometries of **geom**.

### 8.9.33. Function: geof:spatialDimension

```
geof:spatialDimension (geom: ogc:geomLiteral): xsd:integer
```

Returns the spatial dimension of **geom**.

### 8.9.34. Function: geof:symDifference

```
geof:symDifference (geom1: ogc:geomLiteral,  
                   geom2: ogc:geomLiteral): ogc:geomLiteral
```

This function returns a geometric object that represents all Points in the set symmetric difference of **geom1** with **geom2**. Calculations are in the spatial reference system of **geom1**.

### 8.9.35. Function: **geof:transform**

```
geof:transform (geom: ogc:geomLiteral, srsIRI: xsd:anyURI): ogc:geomLiteral
```

**geof:transform** converts **geom** to a spatial reference system defined by **srsIRI**. The function raises an error if a transformation is not mathematically possible.

#### NOTE

We recommend that implementers use the same literal type as a result of this function as the type of the input literal.

### 8.9.36. Function: **geof:union**

```
geof:union (geom1: ogc:geomLiteral,  
            geom2: ogc:geomLiteral): ogc:geomLiteral
```

This function returns a geometric object that represents all Points in the union of **geom1** with **geom2**. Calculations are in the spatial reference system of **geom1**.

**Req 44** Implementations shall support **geof:getSRID** as a SPARQL extension function.

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-extension/srid-function>

## 8.10. Spatial Aggregate Functions

This clause defines SPARQL functions for performing spatial aggregations of data.

**Req 45** Implementations shall support **geof:aggBoundingBox**, **geof:aggBoundingBox**, **geof:aggCentroid**, **geof:aggConcaveHull**, **geof:aggConvexHull** and **geof:aggUnion** as a SPARQL extension functions.

<http://www.opengis.net/spec/geosparql/1.1/req/geometry-extension/sa-functions>

### 8.10.1. Function: **geof:aggBoundingBox**

```
geof:aggBoundingBox (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:aggBoundingBox** calculates a minimum bounding box - rectangle - of the set of given geometries.

### 8.10.2. Function: **geof:aggBoundingBox**

```
geof:aggBoundingCircle (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:aggBoundingCircle** calculates a minimum bounding circle of the set of given geometries.

### 8.10.3. Function: geof:aggCentroid

```
geof:aggCentroid (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:aggCentroid** calculates the centroid of the set of given geometries.

### 8.10.4. Function: geof:aggConcaveHull

```
geof:aggConcaveHull (geom: ogc:geomLiteral, targetPercent: xsd:double):  
ogc:geomLiteral
```

The function **geof:aggConcaveHull** calculates the concave hull of the set of given geometries.

### 8.10.5. Function: geof:aggConvexHull

```
geof:aggConvexHull (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:aggConvexHull** calculates the convex hull of the set of given geometries.

#### NOTE

This function is similar in name to **geof:convexHull** used to calculate the convex hull of just one geometry.

### 8.10.6. Function: geof:aggUnion

```
geof:aggUnion (geom: ogc:geomLiteral): ogc:geomLiteral
```

The function **geof:aggUnion** calculates the union of the set of given geometries.

#### NOTE

This function is similar in name to **geof:union** used to calculate the union of just two geometries.

[1] <http://www.w3.org/2003/01/geo/>

[2] <http://purl.org/dc/terms/Location>

[3] <https://schema.org/GeoCoordinates>

[4] <https://schema.org/GeoShape>

[5] <https://www.w3.org/ns/locn>

[6] <https://www.w3.org/TR/vocab-dcat/#spatial-properties>

[7] <http://www.qudt.org>

[8] <https://www.w3.org/TR/sparql11-query/#expressions>

[9] <https://www.w3.org/TR/sparql11-query/#operatorExtensibility>

[10] <https://www.ogc.org/def-server>

# Chapter 9. Geometry Topology Extension

This clause establishes the *Geometry Topology Extension* parameterized Requirements class with base IRI [/req/geometry-topology-extension](#), which defines a collection of topological query functions that operate on geometry literals. These Requirements are parameterized to give implementations flexibility in the topological relation families and geometry serializations that they choose to support. These Requirements have a single corresponding conformance class *Geometry Topology Extension*, with IRI [/conf/geometry-topology-extension](#).

The Dimensionally Extended Nine Intersection Model (DE-9IM) [\[DE-9IM\]](#) has been used to define the relation tested by the query functions introduced in this section. Each query function is associated with a defining DE-9IM intersection pattern. Possible pattern values are:

- **-1** (empty)
- **0, 1, 2, T** (true) = {0, 1, 2}
- **F** (false) = {-1}
- **\*** (don't care) = {-1, 0, 1, 2}

In the following descriptions, the notation **X/Y** is used to denote applying a spatial relation to geometry types **X** and **Y** (i.e., **x relation y** where **x** is of type **X** and **y** is of type **Y**). The symbol **P** is used for 0-dimensional geometries (e.g. points). The symbol **L** is used for 1- dimensional geometries (e.g. lines), and the symbol **A** is used for 2-dimensional geometries (e.g. polygons). Consult the Simple Features specification [\[OGCSFACA\]](#) [\[ISO19125-1\]](#) for a more detailed description of DE-9IM intersection patterns.

## 9.1. Parameters

- **relation\_family**: Specifies the set of topological spatial relations to support.
- **serialization**: Specifies the serialization standard to use for geometry literals.
- **version**: Specifies the version of the serialization format used.

## 9.2. Common Query Functions

**Req 46** Implementations shall support **geof:relate** as a SPARQL extension function, consistent with the relate operator defined in Simple Features [\[OGCSFACA\]](#) [\[ISO19125-1\]](#).

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-topology-extension/relate-query-function>

```
geof:relate (geom1: ogc:geomLiteral,  
            geom2: ogc:geomLiteral,  
            pattern-matrix: xsd:string): xsd:boolean
```

Returns **true** if the spatial relationship between **geom1** and **geom2** corresponds to one with acceptable values for the specified **pattern-matrix**. Otherwise, this function returns **false**.

represents a DE-9IM intersection pattern consisting of **T** (true) and **F** (false) values. The spatial reference system for **geom1** is used for spatial calculations.

## 9.3. Simple Features Relation Family

This clause establishes Requirements for the *Simple Features* relation family.

**Req 47** Implementations shall support **geof:sfEquals**, **geof:sfDisjoint**, **geof:sfIntersects**, **geof:sfTouches**, **geof:sfCrosses**, **geof:sfWithin**, **geof:sfContains** and **geof:sfOverlaps** as SPARQL extension functions, consistent with their corresponding DE-9IM intersection patterns, as defined by Simple Features [OGCSFACA] [ISO19125-1].

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-topology-extension/sf-query-functions>

Boolean query functions defined for the Simple Features relation family, along with their associated DE-9IM intersection patterns, are shown in Table 6 below. Multi-row intersection patterns should be interpreted as a logical OR of each row. Each function accepts two arguments (**geom1** and **geom2**) of the geometry literal *serialization* type *specified* by serialization and version. Each function returns an **xsd:boolean** value of **true** if the specified relation exists between **geom1** and **geom2** and returns false otherwise. In each case, the spatial reference system of **geom1** is used for spatial calculations.

Table 6. Simple Features Query Functions

Query Function	Defining DE-9IM Intersection Pattern
<b>geof:sfEquals</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(TFFFTFFFT)
<b>geof:sfDisjoint</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(FF*FF****)
<b>geof:sfIntersects</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(FT***** F**T***** F***T****)
<b>geof:sfTouches</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(FT***** F**T***** F***T****)
<b>geof:sfCrosses</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(T*T***T**) for P/L, P/A, L/A; (0*T***T**) for L/L
<b>geof:sfWithin</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(T*F**F***)
<b>geof:sfContains</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(T*****FF*)
<b>geof:sfOverlaps</b> (geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean	(T*T***T**) for A/A, P/P; (1*T***T**) for L/L

## 9.4. Egenhofer Relation Family

This clause establishes Requirements for the *Egenhofer* relation family. Consult references [FORMAL] and [CATEG] for a more detailed discussion of *Egenhofer* relations.

**Req 48** Implementations shall support `geof:ehEquals`, `geof:ehDisjoint`, `geof:ehMeet`, `geof:ehOverlap`, `geof:ehCovers`, `geof:ehCoveredBy`, `geof:ehInside` and `geof:ehContains` as SPARQL extension functions, consistent with their corresponding DE-9IM intersection patterns, as defined by Simple Features [OGCSFACA] [ISO19125-1].

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-topology-extension/eh-query-functions>

Boolean query functions defined for the *Egenhofer* relation family, along with their associated DE-9IM intersection patterns, are shown in Table 7 below. Multi-row intersection patterns should be interpreted as a logical OR of each row. Each function accepts two arguments (`geom1` and `geom2`) of the geometry literal serialization type specified by *serialization* and *version*. Each function returns an `xsd:boolean` value of `true` if the specified relation exists between `geom1` and `geom2` and returns `false` otherwise. In each case, the spatial reference system of `geom1` is used for spatial calculations.

Table 7. Egenhofer Query Functions

Query Function	Defining DE-9IM Intersection Pattern
<code>geof:ehEquals(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TFFFTFFFT)
<code>geof:ehDisjoint(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(FF*FF****)
<code>geof:ehMeet(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(FT***** F**T***** F***T****)
<code>geof:ehOverlap(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(T*T***T**)
<code>geof:ehCovers(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(T*TFT*FF*)
<code>geof:ehCoveredBy(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TFF*TFT**)
<code>geof:ehInside(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TFF*FFT**)
<code>geof:ehContains(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(T*TFF*FF*)

## 9.5. RCC8 Relation Family

This clause establishes Requirements for the *RCC8* relation family. Consult references [QUAL] and [LOGIC] for a more detailed discussion of *RCC8* relations.

**Req 49** Implementations shall support `geof:rcc8eq`, `geof:rcc8dc`, `geof:rcc8ec`, `geof:rcc8po`, `geof:rcc8tppi`, `geof:rcc8tpp`, `geof:rcc8ntpp` and `geof:rcc8ntppi` as SPARQL extension functions, consistent with their corresponding DE-9IM intersection patterns, as defined by Simple Features [OGCSFACA] [ISO19125-1].

<http://www.opengis.net/spec/geosparql/1.0/req/geometry-topology-extension/rcc8-query-functions>

Boolean query functions defined for the *RCC8* relation family, along with their associated DE-9IM intersection patterns, are shown in Table 8 below. Each function accepts two arguments (`geom1` and `geom2`) of the geometry literal serialization type specified by *serialization* and *version*. Each function



returns an `xsd:boolean` value of `true` if the specified relation exists between `geom1` and `geom2` and returns `false` otherwise. In each case, the spatial reference system of `geom1` is used for spatial calculations.

Table 8. RCC8 Query Functions

Query Function	Defining DE-9IM Intersection Pattern
<code>geof:rcc8eq(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TFFFTFFFT)
<code>geof:rcc8dc(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(FFTFITTTT)
<code>geof:rcc8ec(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(FFTFITTTT)
<code>geof:rcc8po(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TTTTTTTTT)
<code>geof:rcc8tppi(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TTTFITFFT)
<code>geof:rcc8tpp(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TFFTITTTT)
<code>geof:rcc8ntpp(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TFFTITTTT)
<code>geof:rcc8ntppi(geom1: ogc:geomLiteral, geom2: ogc:geomLiteral): xsd:boolean</code>	(TTTFITFFT)

# Chapter 10. RDFS Entailment Extension

This clause establishes the *RDFS Entailment Extension* parameterized Requirements class with base IRI [/req/rdfs-entailment-extension](#), which defines a mechanism for matching implicitly-derived RDF triples in GeoSPARQL queries. This class is parameterized to give implementations flexibility in the topological relation families and geometry types that they choose to support. These Requirements have a single corresponding conformance class *RDFS Entailment Extension*, with IRI [/conf/rdfs-entailment-extension](#).

## 10.1. Parameters

- **relation\_family**: Specifies the set of topological spatial relations to support.
- **serialization**: Specifies the serialization standard to use for geometry literals.
- **version**: Specifies the version of the serialization format used.

## 10.2. Common Requirements

The basic mechanism for supporting RDFS entailment has been defined by the W3C SPARQL 1.1 RDFS Entailment Regime [\[SPARQLENT\]](#).

**Req 50** Basic graph pattern matching shall use the semantics defined by the RDFS Entailment Regime [\[SPARQLENT\]](#).

<http://www.opengis.net/spec/geosparql/1.0/req/rdfs-entailment-extension/bgp-rdfs-ent>

## 10.3. WKT Serialization

This section establishes the requirements for representing geometry data in RDF based on WKT as defined by Simple Features [\[OGCSFACA\]](#) [\[ISO19125-1\]](#).

### 10.3.1. Geometry Class Hierarchy

The Simple Features specification presents a geometry class hierarchy. It is straightforward to represent this class hierarchy in RDFS and OWL by constructing IRIs for geometry classes using the following pattern: <http://www.opengis.net/ont/sf#{geometry class}> and by asserting appropriate `rdfs:subClassOf` statements. The *Simple Features Vocabulary* resource within GeoSPARQL 1.1 (sibling resource to this specification) does this. The following list gives the class hierarchy with each indented item being a subclass of the item in the line above. The class hierarchy starts with GeoSPARQL's `geo:Geometry` class of which `sf:Geometry` is a subclass:

```
geo:Geometry
  sf:Geometry
    sf:Curve
      sf:LineString
        sf:Line
          sf:LinearRing
```

```

sf:GeometryCollection
  sf:MultiCurve
    sf:MultiLineString
  sf:MultiPoint
  sf:MultiSurface
    sf:MultiPolygon
sf:Point
sf:Surface
  sf:Polygon
    sf:Envelope
    sf:Triangle
  sf:PolyhedralSurface
    sf:TIN

```

The following example RDF snippet below encodes the *Simple Features vocabulary* Polygon class:

```

sf:Polygon
  a rdfs:Class, owl:Class ;
  rdfs:isDefinedBy <http://www.opengis.net/ont/sf> ;
  skos:prefLabel "Polygon"@en ;
  rdfs:subClassOf sf:Surface ;
  skos:definition "A planar surface defined by 1 exterior boundary and 0 or
    more interior boundaries"@en ;
.

```

**Req 51** Implementations shall support graph patterns involving terms from an RDFS/OWL class hierarchy of geometry types consistent with the one in the specified version of Simple Features [OGCSFACA] [ISO19125-1].

<http://www.opengis.net/spec/geosparql/1.0/req/rdfs-entailment-extension/wkt-geometry-types>

## 10.4. GML Serialization

This section establishes Requirements for representing geometry data in RDF based on GML as defined by Geography Markup Language Encoding Standard [OGC07-036].

### 10.4.1. Geometry Class Hierarchy

An RDF/OWL class hierarchy can be generated from the GML schema that implements *GM\_Object* by constructing IRIs for geometry classes using the following pattern: <http://www.opengis.net/ont/gml#{GML Element}> and by asserting appropriate *rdfs:subClassOf* statements.

The example RDF snippet below encodes the Polygon class from GML 3.2.

```

gml:Polygon
  a rdfs:Class, owl:Class ;
  skos:prefLabel "Polygon"@en ;

```

```
rdfs:subClassOf gml:SurfacePatch ;  
skos:definition "A planar surface defined by 1 exterior boundary and 0 or  
more interior boundaries."@en ;  
.
```

**Req 52** Implementations shall support graph patterns involving terms from an RDFS/OWL class hierarchy of geometry types consistent with the GML schema that implements **GM\_Object** using the specified *version* of GML [OGC07-036].

<http://www.opengis.net/spec/geosparql/1.0/req/rdfs-entailment-extension/gml-geometry-types>

# Chapter 11. Query Rewrite Extension

This clause establishes the *Query Rewrite Extension* parameterized Requirements class with base IRI `/req/query-rewrite-extension`, which has a single corresponding conformance class *Query Rewrite Extension*, with IRI `/conf/query-rewrite-extension`. These Requirements define a set of RIF rules [RIF] that use topological extension functions defined in Clause 9 to establish the existence of direct topological predicates defined in Clause 7. One possible implementation strategy is to transform a given query by expanding a triple pattern involving a direct spatial predicate into a series of triple patterns and an invocation of the corresponding extension function as specified in the RIF rule.

The following rule specified using the RIF Core Dialect [RIFCORE] and shown in *Presentation Syntax* is used as a template to describe rules in the remainder of this clause. `ogc:relation` is used as a placeholder for the spatial relation IRIs defined in Clause 7, and `ogc:function` is used as a placeholder for the spatial functions defined in Clause 9. `ogc:asGeomLiteral` is used to indicate one of the properties that link `geo:Geometry` instances to serialisations, such as `geo:asWKT` or `geo:asGeoJSON`. The variables `?so1` & `?so2` represent `geo:SpatialObject` instances (either `geo:Feature` or `geo:Geometry` instances), `?g1` & `?g2` `geo:Geometry` instances only and `?g1Serial` & `?g2Serial` represent `geo:Geometry` instance serializations, e.g. `geo:asWKT` etc. literals.

```
Forall ?so1 ?so2 ?g1 ?g2 ?g1Serial ?g2Serial (
  ?so1[ogc:relation->?so2] :- Or (
    And (
      # feature - feature rule
      ?so1[geo:hasDefaultGeometry->?g1]
      ?so2[geo:hasDefaultGeometry->?g2]
      ?g1[ogc:asGeomLiteral->?g1Serial]
      ?g2[ogc:asGeomLiteral->?g2Serial]
      External(ogc:function(?g1Serial, ?g2Serial))
    )
    And (
      # feature - geometry rule
      ?so1[geo:hasDefaultGeometry->?g1]
      ?g1[ogc:asGeomLiteral->?g1Serial]
      ?so2[ogc:asGeomLiteral->?g2Serial]
      External(ogc:function(?g1Serial, ?g2Serial))
    )
    And (
      # geometry - feature rule
      ?so1[ogc:asGeomLiteral->?g1Serial]
      ?so2[geo:hasDefaultGeometry->?g2]
      ?g2[ogc:asGeomLiteral->?g2Serial]
      External(ogc:function(?g1Serial, ?g2Serial))
    )
    And (
      # geometry - geometry rule
      ?so1[ogc:asGeomLiteral->?g1Serial]
      ?so2[ogc:asGeomLiteral->?g2Serial]
      External(ogc:function(?g1Serial, ?g2Serial))
    )
  )
)
```

```
)
)
)
```

## 11.1. Parameters

- **relation\_family**: Specifies the set of topological spatial relations to support.
- **serialization**: Specifies the serialization standard to use for geometry literals.
- **version**: Specifies the version of the serialization format used.

## 11.2. Simple Features Relation Family

This clause defines Requirements for the *Simple Features* relation family. [Table 9](#) specifies the function and property substitutions for each rule in the *Simple Features* relation family.

**Req 53** Basic graph pattern matching shall use the semantics defined by the RIF Core Entailment Regime [\[SPARQLENT\]](#) for the RIF rules [\[RIFCORE\]](#) `geor:sfEquals`, `geor:sfDisjoint`, `geor:sfIntersects`, `geor:sfTouches`, `geor:sfCrosses`, `geor:sfWithin`, `geor:sfContains` and `geor:sfOverlaps`.

<http://www.opengis.net/spec/geosparql/1.0/req/query-rewrite-extension/sf-query-rewrite>

Table 9. Simple Features Query Transformation Rules

Rule	ogc:relation	ogc:function
<code>geor:sfEquals</code>	<code>geo:sfEquals</code>	<code>geof:sfEquals</code>
<code>geor:sfDisjoint</code>	<code>geo:sfDisjoint</code>	<code>geof:sfDisjoint</code>
<code>geor:sfIntersects</code>	<code>geo:sfIntersects</code>	<code>geof:sfIntersects</code>
<code>geor:sfTouches</code>	<code>geo:sfTouches</code>	<code>geof:sfTouches</code>
<code>geor:sfCrosses</code>	<code>geo:sfCrosses</code>	<code>geof:sfCrosses</code>
<code>geor:sfWithin</code>	<code>geo:sfWithin</code>	<code>geof:sfWithin</code>
<code>geor:sfContains</code>	<code>geo:sfContains</code>	<code>geof:sfContains</code>
<code>geor:sfOverlaps</code>	<code>geo:sfOverlaps</code>	<code>geof:sfOverlaps</code>

## 11.3. Egenhofer Relation Family

This clause defines Requirements for the *Egenhofer* relation family. [Table 10](#) specifies the function and property substitutions for each rule in the *Egenhofer* relation family.

**Req 54** Basic graph pattern matching shall use the semantics defined by the RIF Core Entailment Regime [\[SPARQLENT\]](#) for the RIF rules [\[RIFCORE\]](#) `geor:ehEquals`, `geor:ehDisjoint`, `geor:ehMeet`, `geor:ehOverlap`, `geor:ehCovers`, `geor:ehCoveredBy`, `geor:ehInside` and `geor:ehContains`.

<http://www.opengis.net/spec/geosparql/1.0/req/query-rewrite-extension/eh-query-rewrite>

Table 10. Egenhofer Query Transformation Rules

Rule	ogc:relation	ogc:function
geor:ehEquals	geo:ehEquals	geof:ehEquals
geor:ehDisjoint	geo:ehDisjoint	geof:ehDisjoint
geor:ehMeet	geo:ehMeet	geof:ehMeet
geor:ehOverlap	geo:ehOverlap	geof:ehOverlap
geor:ehCovers	geo:ehCovers	geof:ehCovers
geor:ehCoveredBy	geo:ehCoveredBy	geof:ehCoveredBy
geor:ehInside	geo:ehInside	geof:ehInside
geor:ehContains	geo:ehContains	geof:ehContains

## 11.4. RCC8 Relation Family

This clause defines Requirements for the *RCC8* relation family. [Table 11](#) specifies the function and property substitutions for each rule in the *RCC8* relation family.

**Req 55** Basic graph pattern matching shall use the semantics defined by the RIF Core Entailment Regime [\[SPARQL-ENT\]](#) for the RIF rules [\[RIFCORE\]](#) `geor:rcc8eq`, `geor:rcc8dc`, `geor:rcc8ec`, `geor:rcc8po`, `geor:rcc8tppi`, `geor:rcc8tpp`, `geor:rcc8ntpp` and `geor:rcc8ntppi`.

<http://www.opengis.net/spec/geosparql/1.0/req/query-rewrite-extension/rcc8-query-rewrite>

Table 11. *RCC8* Query Transformation Rules

Rule	ogc:relation	ogc:function
geor:rcc8eq	geo:rcc8eq	geof:rcc8eq
geor:rcc8dc	geo:rcc8dc	geof:rcc8dc
geor:rcc8ec	geo:rcc8ec	geof:rcc8ec
geor:rcc8po	geo:rcc8po	geof:rcc8po
geor:rcc8tppi	geo:rcc8tppi	geof:rcc8tppi
geor:rcc8tpp	geo:rcc8tpp	geof:rcc8tpp
geor:rcc8ntpp	geo:rcc8ntpp	geof:rcc8ntpp
geor:rcc8ntppi	geo:rcc8ntppi	geof:rcc8ntppi

## 11.5. Special Considerations

The applicability of GeoSPARQL rules in certain circumstances has intentionally been left undefined.

The first situation arises for triple patterns with unbound predicates. Consider the query pattern below:

```
{ my:feature1 ?p my:feature2 }
```

When using a query transformation strategy, this triple pattern could invoke none of the

GeoSPARQL rules or all of the rules. Implementations are free to support either of these alternatives.

The second situation arises when supporting GeoSPARQL rules in the presence of RDFS Entailment. The existence of a topological relation (possibly derived from a GeoSPARQL rule) can entail other RDF triples. For example, if `geo:sfOverlaps` has been defined as an `rdfs:subPropertyOf` the property `my:overlaps`, and the RDF triple `my:feature1 geo:sfOverlaps my:feature2` has been derived from a GeoSPARQL rule, then the RDF triple `my:feature1 my:overlaps my:feature2` can be entailed. Implementations may support such entailments but are not required to.



# Chapter 12. Future Work

Many future extensions of this standard are possible and, since the release of GeoSPARQL 1.0, many extensions have been made.

The GeoSPARQL 1.1 release incorporates many additions requested of the GeoSPARQL 1.0 Standard, including the use of particular new serializations: where GeoSPARQL 1.0 supported GML & WKT, GeoSPARQL 1.1 also supports GeoJSON, KML and a generic DGGs literal. GeoSPARQL 1.1 also supports spatial scalar properties.

Plans for future GeoSPARQL releases have been suggested but won't be articulated here. Instead they will be discussed and decided upon by the OGC GeoSPARQL Standards Working Group and related groups. Readers of this document are encouraged to seek out those groups' lists of issues and standards change requests rather than looking for ideas here that will surely age badly.

# **Annex A - Abstract Test Suite (normative)**

# A.0 Overview

This Annex lists tests for the Conformance Classes defined in the main body sections of this Specification with links to their Requirements and test purpose method and type. Conformance classes may be used to signify the compatibility of a given implementation to parts of the GeoSPARQL standard. They may be stated as part of a SPARQL 1.1 Service Description [\[SPARQLSERVDESC\]](#).

# A.1 Conformance Class: Core

Conformance Class IRI: [/conf/core](#)

## A.1.1 SPARQL

### A.1.1.1 [/conf/core/sparql-protocol](#)

**Requirement:** [/req/core/sparql-protocol](#)

Implementations shall support the SPARQL Query Language for RDF [\[SPARQL\]](#), the SPARQL Protocol for RDF [\[SPARQLPROT\]](#) and the SPARQL Query Results XML Format [\[SPARQLRESX\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that the implementation accepts SPARQL queries and returns the correct results in the correct format, according to the SPARQL Query Language for RDF, the SPARQL Protocol for RDF and SPARQL Query Results XML Format W3C specifications.
- c. **Reference:** [Section 4.1.4](#)
- d. **Test Type:** Capabilities

## A.1.2 RDF Classes & Properties

### A.1.2.1 [/conf/core/spatial-object-class](#)

**Requirement:** [/req/core/spatial-object-class](#)

Implementations shall allow the RDFS class `geo:SpatialObject` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving `geo:SpatialObject` return the correct result on a test dataset.
- c. **Reference:** [Section 6.2.1](#)
- d. **Test Type:** Capabilities

### A.1.2.2 [/conf/core/feature-class](#)

**Requirement:** [/req/core/feature-class](#) Implementations shall allow the RDFS class `geo:Feature` to be used in SPARQL graph patterns.

- a. **Test purpose:** check conformance with this requirement
- b. **Test method:** verify that queries involving `geo:Feature` return the correct result on a test dataset.
- c. **Reference:** [Section 6.2.2](#)
- d. **Test Type:** Capabilities

### A.1.2.3 /conf/core/spatial-object-collection-class

**Requirement:** /req/core/spatial-object-collection-class

Implementations shall allow the RDFS class `geo:SpatialObjectCollection` to be used in SPARQL graph patterns.

- a. **Test purpose:** check conformance with this requirement
- b. **Test method:** verify that queries involving `geo:SpatialObjectCollection` return the correct result on a test dataset.
- c. **Reference:** [Section 6.2.3](#)
- d. **Test Type:** Capabilities

### A.1.2.4 /conf/core/feature-collection-class

**Requirement:** /req/core/feature-collection-class

Implementations shall allow the RDFS class `geo:FeatureCollection` to be used in SPARQL graph patterns.

- a. **Test purpose:** check conformance with this requirement
- b. **Test method:** verify that queries involving `geo:FeatureCollection` return the correct result on a test dataset.
- c. **Reference:** [Section 6.2.4](#)
- d. **Test Type:** Capabilities

### A.1.2.5 /conf/core/spatial-object-properties

Implementations shall allow the properties `geo:hasSize`, `geo:hasMetricSize`, `geo:hasLength`, `geo:hasMetricLength`, `geo:hasPerimeterLength`, `geo:hasMetricPerimeterLength`, `geo:hasArea`, `geo:hasMetricArea`, `geo:hasVolume` and `geo:hasMetricVolume`. to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.
- c. **Reference:** [Section 6.3](#)
- d. **Test Type:** Capabilities

# A.2 Conformance Class: Topology Vocabulary Extension

Conformance Class IRI: [/conf/topology-vocab-extension](#)

## A.2.1 Simple Features Relation Family

### A.2.1.1 [/conf/topology-vocab-extension/sf-spatial-relations](#)

**Requirement:** [/req/topology-vocab-extension/sf-spatial-relations](#)

Implementations shall allow the properties [geo:sfEquals](#), [geo:sfDisjoint](#), [geo:sfIntersects](#), [geo:sfTouches](#), [geo:sfCrosses](#), [geo:sfWithin](#), [geo:sfContains](#) and [geo:sfOverlaps](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.
- c. **Reference:** [Section 7.2](#)
- d. **Test Type:** Capabilities

## A.2.2 Egenhofer Relation Family

### A.2.2.1 [/conf/topology-vocab-extension/eh-spatial-relations](#)

**Requirement:** [/req/topology-vocab-extension/eh-spatial-relations](#)

Implementations shall allow the properties [geo:ehEquals](#), [geo:ehDisjoint](#), [geo:ehMeet](#), [geo:ehOverlap](#), [geo:ehCovers](#), [geo:ehCoveredBy](#), [geo:ehInside](#) and [geo:ehContains](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.
- c. **Reference:** [Section 7.3](#)
- d. **Test Type:** Capabilities

## A.2.3 RCC8 Relation Family

### A.2.3.1 [/conf/topology-vocab-extension/rcc8-spatial-relations](#)

**Requirement:** [/req/topology-vocab-extension/rcc8-spatial-relations](#)

Implementations shall allow the properties [geo:rcc8eq](#), [geo:rcc8dc](#), [geo:rcc8ec](#), [geo:rcc8po](#),

`geo:rcc8tppi`, `geo:rcc8tpp`, `geo:rcc8ntpp`, `geo:rcc8ntppi` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.
- c. **Reference:** [Section 7.4](#)
- d. **Test Type:** Capabilities

## A.3 Conformance Class: Geometry Extension

This Conformance Class applies to non-DGGS geometries. See [A.3.DGGS Conformance Class: Geometry Extension - DGGS](#) for DGGS geometries.

**Conformance Class IRI:** [/conf/geometry-extension](#)

### A.3.1 Tests for all Serializations except DGGS

#### A.3.1.1 [/conf/geometry-extension/geometry-class](#)

**Requirement:** [/req/geometry-extension/geometry-class](#)

Implementations shall allow the RDFS class [geo:Geometry](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving [geo:Geometry](#) return the correct result on a test dataset
- c. **Reference:** [Section 8.6.1](#)
- d. **Test Type:** Capabilities

#### A.3.1.2 [/conf/geometry-extension/geometry-collection-class](#)

**Requirement:** [/req/geometry-extension/geometry-collection-class](#)

Implementations shall allow the RDFS class [Geometry Collection](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** check conformance with this requirement
- b. **Test method:** verify that queries involving [Geometry Collection](#) return the correct result on a test dataset
- c. **Reference:** [Section 8.6.2](#)
- d. **Test Type:** Capabilities

#### A.3.1.3 [/conf/geometry-extension/feature-properties](#)

**Requirement:** [/req/geometry-extension/feature-properties](#)

Implementations shall allow the properties [geo:hasGeometry](#), [geo:hasDefaultGeometry](#), [geo:hasLength](#), [geo:hasArea](#), [geo:hasVolume](#), [geo:hasCentroid](#), [geo:hasBoundingBox](#) and [geo:hasSpatialResolution](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.



c. **Reference:** [Section 6.4](#)

d. **Test Type:** Capabilities

#### A.3.1.4 /conf/geometry-extension/geometry-properties

**Requirement:** /req/geometry-extension/geometry-properties

Implementations shall allow the properties `geo:dimension`, `geo:coordinateDimension`, `geo:spatialDimension`, `geo:isEmpty`, `geo:isSimple` and `geo:hasSerialization` to be used in SPARQL graph patterns.

a. **Test purpose:** Check conformance with this requirement

b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.

c. **Reference:** [Section 8.7](#)

d. **Test Type:** Capabilities

#### A.3.1.5 /conf/geometry-extension/query-functions

**Requirement:** /req/geometry-extension/query-functions

Implementations shall support the functions `geof:distance`, `geof:buffer`, `geof:intersection`, `geof:union`, `geof:isEmpty`, `geof:isSimple`, `geof:area`, `geof:length`, `geof:numGeometries`, `geof:geometryN`, `geof:transform`, `geof:dimension`, `geof:difference`, `geof:symDifference`, `geof:envelope` and `geof:boundary` as SPARQL extension functions, consistent with the definitions of their corresponding functions in Simple Features [\[OGCSFACA\]](#) [\[ISO19125-1\]](#) (`distance`, `buffer`, `intersection`, `union`, `isEmpty`, `isSimple`, `area`, `length`, `numGeometries`, `geometryN`, `transform`, `dimension`, `difference`, `symDifference`, `envelope` and `boundary` respectively) and other attached definitions and also `geof:maxX`, `geof:maxY`, `geof:maxZ`, `geof:minX`, `geof:minY` and `geof:minZ` SPARQL extension functions.

a. **Test purpose:** Check conformance with this requirement

b. **Test method:** Verify that a set of SPARQL queries involving each of the following functions returns the correct result for a test dataset when using the specified serialization and version: `geof:distance`, `geof:buffer`, `geof:intersection`, `geof:union`, `geof:isEmpty`, `geof:isSimple`, `geof:area`, `geof:length`, `geof:numGeometries`, `geof:geometryN`, `geof:transform`, `geof:dimension`, `geof:difference`, `geof:symDifference`, `geof:envelope` and `geof:boundary`.

c. **Reference:** [Section 8.9](#)

d. **Test Type:** Capabilities

#### A.3.1.6 /conf/geometry-extension/srid-function

**Requirement:** /req/geometry-extension/srid-function

Implementations shall support `get SRID` as a SPARQL extension function.

a. **Test purpose:** Check conformance with this requirement

- b. **Test method:** Verify that a SPARQL query involving the [get SRID](#) function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.9.18](#)
- d. **Test Type:** Capabilities

### A.3.1.7 /conf/geometry-extension/sa-functions

**Requirement:** /req/geometry-extension/sa-functions

Implementations shall support [geof:aggBoundingBox](#), [geof:aggBoundingBox](#), [geof:aggCentroid](#), [geof:aggConcaveHull](#), [geof:aggConvexHull](#) and [geof:aggUnion](#) as a SPARQL extension functions.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these functions return the correct result for a test dataset.
- c. **Reference:** [Section 8.10](#)
- d. **Test Type:** Capabilities

## A.3.2 WKT Serialization

### A.3.2.1 /conf/geometry-extension/wkt-literal

**Requirement:** /req/geometry-extension/wkt-literal

All RDFS Literals of type [geo:wktLiteral](#) shall consist of an optional IRI identifying the coordinate reference system and a required Well Known Text (WKT) description of a geometric value. Valid [geo:wktLiteral](#) instances are formed by either a WKT string as defined in [\[ISO13249\]](#) or by concatenating a valid absolute IRI, as defined in [\[IETF3987\]](#), enclose in angled brackets (< & >) followed by a single space (Unicode U+0020 character) as a separator, and a WKT string as defined in [\[ISO13249\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving [WKT Literal](#) values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.1.1](#)
- d. **Test Type:** Capabilities

### A.3.2.2 /conf/geometry-extension/wkt-literal-default-srs

**Requirement:** /req/geometry-extension/wkt-literal-default-srs

The IRI [<http://www.opengis.net/def/crs/OGC/1.3/CRS84>](#) shall be assumed as the spatial reference system for [geo:wktLiteral](#) instances that do not specify an explicit spatial reference system IRI.

- a. **Test purpose:** Check conformance with this requirement

- b. **Test method:** Verify that queries involving [WKT Literal](#) values without an explicit encoded SRS IRI return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.1.1](#)
- d. **Test Type:** Capabilities

### A.3.2.3 [/conf/geometry-extension/wkt-axis-order](#)

**Requirement:** [/req/geometry-extension/wkt-axis-order](#)

Coordinate tuples within [WKT Literal](#) instances shall be interpreted using the axis order defined in the SRS used.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving [WKT Literal](#) values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.1.1](#)
- d. **Test Type:** Capabilities

### A.3.2.4 [/conf/geometry-extension/wkt-literal-empty](#)

**Requirement:** [/req/geometry-extension/wkt-literal-empty](#)

An empty RDFS Literal of type [WKT Literal](#) shall be interpreted as an empty geometry.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty [WKT Literal](#) values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.1.1](#)
- d. **Test Type:** Capabilities

### A.3.2.5 [/conf/geometry-extension/geometry-as-wkt-literal](#)

**Requirement:** [/req/geometry-extension/geometry-as-wkt-literal](#)

Implementations shall allow the RDF property [geo:asWKT](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the [geo:asWKT](#) property return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.1.2](#)
- d. **Test Type:** Capabilities

### A.3.2.6 [/req/geometry-extension/asWKT-function](#)

**Requirement:** [/req/geometry-extension/asWKT-function](#)

Implementations shall support `geof:asWKT`, as a SPARQL extension function

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:asWKT` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.8.1.3](#)
- d. **Test Type:** Capabilities

## A.3.3 GML Serialization

### A.3.3.1 `/conf/geometry-extension/gml-literal`

**Requirement:** `/req/geometry-extension/gml-literal`

All `geo:gmlLiteral` instances shall consist of a valid element from the GML schema that implements a subtype of `GM_Object` as defined in [OGC 07-036].

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving `geo:gmlLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.2.1](#)
- d. **Test Type:** Capabilities

### A.3.3.2 `/conf/geometry-extension/gml-literal-empty`

**Requirement:** `/req/geometry-extension/gml-literal-empty`

An empty `geo:gmlLiteral` shall be interpreted as an empty geometry.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty `geo:gmlLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.2.1](#)
- d. **Test Type:** Capabilities

### A.3.3.3 `/conf/geometry-extension/gml-profile`

**Requirement:** `/req/geometry-extension/gml-profile`

Implementations shall document supported GML profiles.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Examine the implementation's documentation to verify that the supported GML profiles are documented.
- c. **Reference:** [Section 8.8.2.1](#)

- d. **Test Type:** Documentation

#### A.3.3.4 `/conf/geometry-extension/geometry-as-gml-literal`

**Requirement:** `/req/geometry-extension/geometry-as-gml-literal`

Implementations shall allow the RDF property `geo:asGML` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the `geo:asGML` property return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.2.2](#)
- d. **Test Type:** Capabilities

#### A.3.3.5 `/req/geometry-extension/asGML-function`

**Requirement:** `/req/geometry-extension/asGML-function`

Implementations shall support `geof:asGML`, as a SPARQL extension function

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:asGML` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.8.2.3](#)
- d. **Test Type:** Capabilities

### A.3.4 GeoJSON Serialization

#### A.3.4.1 `/req/geometry-extension/geojson-literal`

**Requirement:** `/req/geometry-extension/geojson-literal`

All `geo:geoJSONLiteral` instances shall consist of valid JSON that conforms to the GeoJSON specification [\[GEOJSON\]](#)

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving `geo:geoJSONLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.2.2](#)
- d. **Test Type:** Capabilities

#### A.3.4.2 `/req/geometry-extension/geojson-literal-srs`

**Requirement:** `/req/geometry-extension/geojson-literal-default-srs`

The IRI `<http://www.opengis.net/def/crs/OGC/1.3/CRS84>` shall be assumed as the SRS for

`geo:geoJSONLiteral` instances that do not specify an explicit SRS IRI.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving `geo:geoJSONLiteral` values without an explicit encoded SRS IRI return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.3.1](#)
- d. **Test Type:** Capabilities

#### A.3.4.3 `/req/geometry-extension/geojson-literal-empty`

**Requirement:** `/req/geometry-extension/geojson-literal-empty`

An empty `geo:geoJSONLiteral` shall be interpreted as an empty geometry.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty `geo:geoJSONLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.3.1](#)
- d. **Test Type:** Capabilities

#### A.3.4.4 `/req/geometry-extension/geometry-as-geojson-literal`

**Requirement:** `/req/geometry-extension/geometry-as-geojson-literal`

Implementations shall allow the RDF property `geo:asGeoJSON` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the `geo:asGeoJSON` property return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.3.2](#)
- d. **Test Type:** Capabilities

#### A.3.4.5 `/req/geometry-extension/asGeoJSON-function`

**Requirement:** `/req/geometry-extension/asGeoJSON-function`

Implementations shall support `geof:asGeoJSON`, as a SPARQL extension function

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:asGeoJSON` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.8.3.3](#)
- d. **Test Type:** Capabilities

## A.3.5 KML Serialization

### A.3.5.1 /req/geometry-extension/kml-literal

**Requirement:** /req/geometry-extension/kml-literal

All `geo:kmlLiteral` instances shall consist of a valid element from the KML schema that implements a `kml:AbstractObjectGroup` as defined in [OGCKML].

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving `geo:kmlLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.4.1](#)
- d. **Test Type:** Capabilities

### A.3.5.2 /req/geometry-extension/kml-literal-srs

**Requirement:** /req/geometry-extension/kml-literal-default-srs

The IRI `<http://www.opengis.net/def/crs/OGC/1.3/CRS84>` shall be assumed as the SRS for `geo:kmlLiteral` instances that do not specify an explicit SRS IRI.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving `geo:kmlLiteral` values without an explicit encoded SRS IRI return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.4.1](#)
- d. **Test Type:** Capabilities

### A.3.5.3 /req/geometry-extension/kml-literal-empty

**Requirement:** /req/geometry-extension/kml-literal-empty

An empty `geo:kmlLiteral` shall be interpreted as an empty geometry.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty `geo:kmlLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.4.1](#)
- d. **Test Type:** Capabilities

### A.3.5.4 /req/geometry-extension/geometry-as-kml-literal

**Requirement:** /req/geometry-extension/geometry-as-kml-literal

Implementations shall allow the RDF property `geo:asKML` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the `geo:asKML` property return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.4.2](#)
- d. **Test Type:** Capabilities

### A.3.5.5 `/req/geometry-extension/asKML-function`

**Requirement:** `/req/geometry-extension/asKML-function`

Implementations shall support `geof:asKML`, as a SPARQL extension function

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:asKML` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.8.4.3](#)
- d. **Test Type:** Capabilities

## A.3.6 DGGs Serialization

### A.3.6.1 `/req/geometry-extension/dggs-literal`

**Requirement:** `/req/geometry-extension/dggs-literal`

All RDFS Literals of type `geo:dggsLiteral` shall consist of an IRI identifying the specific DGGs and a representation of the DGGs geometry data. The IRI shall be enclosed in angled brackets (`<` & `>`) followed by whitespace as a separator, and then the DGGs geometry data, formulated according to the identified DGGs.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty `geo:dggsLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.5.1](#)
- d. **Test Type:** Capabilities

### A.3.6.2 `/req/geometry-extension/dggs-literal-empty`

**Requirement:** `/req/geometry-extension/dggs-literal-empty`

An empty RDFS Literal of type `geo:dggsLiteral`, shall be interpreted as an empty `geo:Geometry`.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty `geo:dggsLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.5.1](#)



- d. **Test Type:** Capabilities

#### A.3.6.3 `/req/geometry-extension/geometry-as-dggs-literal`

**Requirement:** `/req/geometry-extension/geometry-as-dggs-literal`

Implementations shall allow the RDF property `geo:asDggs` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the `geo:asDggs` property return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.5.2](#)
- d. **Test Type:** Capabilities

#### A.3.6.4 `/req/geometry-extension/asDggs-function`

**Requirement:** `/req/geometry-extension/asDggs-function`

Implementations shall support `geof:asDggs`, as a SPARQL extension function.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:asDggs` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.8.5.3](#)
- d. **Test Type:** Capabilities

# A.3.DGGS Conformance Class: Geometry Extension - DGGS

This conformance Class applies only to DGGS geometries. See [A.3 Conformance Class: Geometry Extension](#) for other geometries.

Conformance Class IRI: [/conf/geometry-extension](#)

## A.3.DGGS.1 Tests for DGGS Serializations

### A.3.DGGS.1.1 [/conf/geometry-extension/geometry-class](#)

**Requirement:** [/req/geometry-extension/geometry-class](#)

Implementations shall allow the RDFS class [geo:Geometry](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving [geo:Geometry](#) return the correct result on a test dataset
- c. **Reference:** [Section 8.6.1](#)
- d. **Test Type:** Capabilities

### A.3.DGGS.1.2 [/conf/geometry-extension/geometry-collection-class](#)

**Requirement:** [/req/geometry-extension/geometry-collection-class](#)

Implementations shall allow the RDFS class [geo:GeometryCollection](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** check conformance with this requirement
- b. **Test method:** verify that queries involving [geo:GeometryCollection](#) return the correct result on a test dataset
- c. **Reference:** [Section 8.6.2](#)
- d. **Test Type:** Capabilities

### A.3.DGGS.1.3 [/conf/geometry-extension/feature-properties](#)

**Requirement:** [/req/geometry-extension/feature-properties](#)

Implementations shall allow the properties [geo:hasGeometry](#), [geo:hasDefaultGeometry](#), [geo:hasLength](#), [geo:hasArea](#), [geo:hasVolume](#), [geo:hasCentroid](#), [geo:hasBoundingBox](#) and [geo:hasSpatialResolution](#) to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these properties return the correct result for a test

dataset.

c. **Reference:** [Section 6.4](#)

d. **Test Type:** Capabilities

### A.3.DGGS.1.4 /[conf/geometry-extension/geometry-properties](#)

**Requirement:** /[req/geometry-extension/geometry-properties](#)

Implementations shall allow the properties [geo:dimension](#), [geo:spatialDimension](#), [geo:isEmpty](#), [geo:isSimple](#) and [geo:hasSerialization](#) to be used in SPARQL graph patterns.

a. **Test purpose:** Check conformance with this requirement

b. **Test method:** Verify that queries involving these properties return the correct result for a test dataset.

c. **Reference:** [Section 8.7](#)

d. **Test Type:** Capabilities

### A.3.DGGS.1.5 /[conf/geometry-extension/query-functions](#)

**Requirement:** /[req/geometry-extension/query-functions](#)

Implementations shall support the functions [geof:distance](#), [geof:buffer](#), [geof:intersection](#), [geof:union](#), [geof:isEmpty](#), [geof:isSimple](#), [geof:area](#), [geof:length](#), [geof:numGeometries](#), [geof:geometryN](#), [geof:transform](#), [geof:dimension](#), [geof:difference](#), [geof:symDifference](#), [geof:envelope](#) and [geof:boundary](#) as SPARQL extension functions

a. **Test purpose:** Check conformance with this requirement

b. **Test method:** Verify that a set of SPARQL queries involving each of the following functions returns the correct result for a test dataset when using the specified serialization and version: [geof:distance](#), [geof:buffer](#), [geof:intersection](#), [geof:union](#), [geof:isEmpty](#), [geof:isSimple](#), [geof:area](#), [geof:length](#), [geof:numGeometries](#), [geof:geometryN](#), [geof:transform](#), [geof:dimension](#), [geof:difference](#), [geof:symDifference](#), [geof:envelope](#) and [geof:boundary](#).

c. **Reference:** [Section 8.9](#)

d. **Test Type:** Capabilities

### A.3.DGGS.1.6 /[conf/geometry-extension/srid-function](#)

**Requirement:** /[req/geometry-extension/srid-function](#)

Implementations shall support [geof:getSRID](#) as a SPARQL extension function.

a. **Test purpose:** Check conformance with this requirement

b. **Test method:** Verify that a SPARQL query involving the [geof:getSRID](#) function returns the correct result for a test dataset when using the specified serialization and version.

c. **Reference:** [Section 8.9.18](#)

- d. **Test Type:** Capabilities

### A.3.DGGS.1.7 /conf/geometry-extension/sa-functions

**Requirement:** /req/geometry-extension/sa-functions

Implementations shall support `geof:boundingBox`, `geof:boundingCircle`, `geof:centroid`, `geof:concatLines`, `geof:concaveHull`, `geof:convexHull` and `geof:union2` as a SPARQL extension functions.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving these functions return the correct result for a test dataset.
- c. **Reference:** [Section 8.10](#)
- d. **Test Type:** Capabilities

## A.3.DGGS.2 DGGS Serialization

### A.3.DGGS.2.1 /req/geometry-extension/dggs-literal

**Requirement:** /req/geometry-extension/dggs-literal

All RDFS Literals of type `geo:dggsLiteral` shall consist of a DGGS geometry serialization formulated according to a specific DGGS literal type identified by a datatype specializing this generic datatype.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries do not use use this datatype but instead use specializations of it.
- c. **Reference:** [Section 8.8.5.1](#)
- d. **Test Type:** Capabilities

### A.3.DGGS.2.2 /req/geometry-extension/dggs-literal-empty

**Requirement:** /req/geometry-extension/dggs-literal-empty

An empty `geo:dggsLiteral` shall be interpreted as an empty geometry.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving empty `geo:dggsLiteral` values return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.5.1](#)
- d. **Test Type:** Capabilities

### A.3.DGGS.2.3 /req/geometry-extension/geometry-as-dggs-literal

**Requirement:** /req/geometry-extension/geometry-as-dggs-literal

Implementations shall allow the RDF property `geo:asDGGS` to be used in SPARQL graph patterns.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the `geo:asDGGS` property return the correct result for a test dataset.
- c. **Reference:** [Section 8.8.5.2](#)
- d. **Test Type:** Capabilities

### A.3.DGGS.2.4 /req/geometry-extension/asDGGS-function

**Requirement:** /req/geometry-extension/asDGGS-function

Implementations shall support `geof:asDGGS`, as a SPARQL extension function

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:asDGGS` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 8.8.5.3](#)
- d. **Test Type:** Capabilities

# A.4 Conformance Class: Geometry Topology Extension

Conformance Class IRI: </conf/geometry-topology-extension>

## A.4.1 Tests for all relation families

### A.4.1.1 </conf/geometry-topology-extension/relate-query-function>

**Requirement:** </req/geometry-topology-extension/relate-query-function>

Implementations shall support `geof:relate` as a SPARQL extension function, consistent with the relate operator defined in Simple Features [\[OGCSFACA\]](#) [\[ISO19125-1\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving the `geof:relate` function returns the correct result for a test dataset when using the specified serialization and version.
- c. **Reference:** [Section 9.2](#)
- d. **Test Type:** Capabilities

## A.4.2 Simple Features Relation Family

### A.4.2.1 </conf/geometry-topology-extension/sf-query-functions>

**Requirement:** </req/geometry-topology-extension/sf-query-functions>

Implementations shall support `geof:sfEquals`, `geof:sfDisjoint`, `geof:sfIntersects`, `geof:sfTouches`, `geof:sfCrosses`, `geof:sfWithin`, `geof:sfContains` and `geof:sfOverlaps` as SPARQL extension functions, consistent with their corresponding DE-9IM intersection patterns, as defined by Simple Features [\[OGCSFACA\]](#) [\[ISO19125-1\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving each of the following functions returns the correct result for a test dataset when using the specified serialization and version: `geof:sfEquals`, `geof:sfDisjoint`, `geof:sfIntersects`, `geof:sfTouches`, `geof:sfCrosses`, `geof:sfWithin`, `geof:sfContains`, `geof:sfOverlaps`.
- c. **Reference:** [Section 7.2](#)
- d. **Test Type:** Capabilities

## A.4.3 Egenhofer Relation Family

#### A.4.3.1 /conf/geometry-topology-extension/eh-query-functions

**Requirement:** /req/geometry-topology-extension/eh-query-functions

Implementations shall support `geof:ehEquals`, `geof:ehDisjoint`, `geof:ehMeet`, `geof:ehOverlap`, `geof:ehCovers`, `geof:ehCoveredBy`, `geof:ehInside` and `geof:ehContains` as SPARQL extension functions, consistent with their corresponding DE-9IM intersection patterns, as defined by Simple Features [OGCSFACA] [ISO19125-1].

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving each of the following functions returns the correct result for a test dataset when using the specified serialization and version: `geof:ehEquals`, `geof:ehDisjoint`, `geof:ehMeet`, `geof:ehOverlap`, `geof:ehCovers`, `geof:ehCoveredBy`, `geof:ehInside`, `geof:ehContains`.
- c. **Reference:** [Section 7.3](#)
- d. **Test Type:** Capabilities

### A.4.4 RCC8 Relation Family

#### A.4.4.1 /conf/geometry-topology-extension/rcc8-query-functions

**Requirement:** /req/geometry-topology-extension/rcc8-query-functions

Implementations shall support `geof:rcc8eq`, `geof:rcc8dc`, `geof:rcc8ec`, `geof:rcc8po`, `geof:rcc8tppi`, `geof:rcc8tpp`, `geof:rcc8ntpp` and `geof:rcc8ntppi` as SPARQL extension functions, consistent with their corresponding DE-9IM intersection patterns, as defined by Simple Features [OGCSFACA] [ISO19125-1].

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving each of the following functions returns the correct result for a test dataset when using the specified serialization and version: `geof:rcc8eq`, `geof:rcc8dc`, `geof:rcc8ec`, `geof:rcc8po`, `geof:rcc8tppi`, `geof:rcc8tpp`, `geof:rcc8ntpp`, `geof:rcc8ntppi`.
- c. **Reference:** [Section 7.4](#)
- d. **Test Type:** Capabilities

# A.5 Conformance Class: RDFS Entailment Extension

Conformance Class IRI: [/conf/rdfs-entailment-extension](#)

## A.5.1 Tests for all implementations

### A.5.1.1 [/conf/rdfs-entailment-extension/bgp-rdfs-ent](#)

**Requirement:** [/req/rdfs-entailment-extension/bgp-rdfs-ent](#)

Basic graph pattern matching shall use the semantics defined by the RDFS Entailment Regime [\[SPARQLENT\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving entailed RDF triples returns the correct result for a test dataset using the specified serialization, version and relation\_family.
- c. **Reference:** [Section 10.2](#)
- d. **Test Type:** Capabilities

## A.5.2 WKT Serialization

### A.5.2.1 [/conf/rdfs-entailment-extension/wkt-geometry-types](#)

**Requirement:** [/req/rdfs-entailment-extension/wkt-geometry-types](#)

Implementations shall support graph patterns involving terms from an RDFS/OWL class hierarchy of geometry types consistent with the one in the specified version of Simple Features [\[OGCSFACA\]](#) [\[ISO19125-1\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving WKT Geometry types returns the correct result for a test dataset using the specified version of Simple Features.
- c. **Reference:** [Section 10.3.1](#)
- d. **Test Type:** Capabilities

## A.5.3 GML Serialization

### A.5.3.1 [/conf/rdfs-entailment-extension/gml-geometry-types](#)

**Requirement:** [/req/rdfs-entailment-extension/gml-geometry-types](#)

Implementations shall support graph patterns involving terms from an RDFS/OWL class hierarchy of geometry types consistent with the GML schema that implements GM\_Object using the specified



version of GML [\[OGC07-036\]](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that a set of SPARQL queries involving GML Geometry types returns the correct result for a test dataset using the specified version of GML.
- c. **Reference:** [Section 10.4.1](#)
- d. **Test Type:** Capabilities

# A.6 Conformance Class: Query Rewrite Extension

Conformance Class IRI: </conf/query-rewrite-extension>

## A.6.1 Simple Features Relation Family

### A.6.1.1 </conf/query-rewrite-extension/sf-query-rewrite>

**Requirement:** </req/query-rewrite-extension/sf-query-rewrite>

Basic graph pattern matching shall use the semantics defined by the RIF Core Entailment Regime [\[SPARQLENT\]](#) for the RIF rules [\[RIFCORE\]](#) [geor:sfEquals](#), [geor:sfDisjoint](#), [geor:sfIntersects](#), [geor:sfTouches](#), [geor:sfCrosses](#), [geor:sfWithin](#), [geor:sfContains](#) and [geor:sfOverlaps](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the following query transformation rules return the correct result for a test dataset when using the specified serialization and version:  
[geor:sfEquals](#), [geor:sfDisjoint](#), [geor:sfIntersects](#), [geor:sfTouches](#), [geor:sfCrosses](#),  
[geor:sfWithin](#), [geor:sfContains](#) and [geor:sfOverlaps](#).
- c. **Reference:** [Section 7.2](#)
- d. **Test Type:** Capabilities

## A.6.2 Egenhofer Relation Family

### A.6.2.1 </conf/query-rewrite-extension/eh-query-rewrite>

**Requirement:** </req/query-rewrite-extension/eh-query-rewrite>

Basic graph pattern matching shall use the semantics defined by the RIF Core Entailment Regime [\[SPARQLENT\]](#) for the RIF rules [\[RIFCORE\]](#) [geor:ehEquals](#), [geor:ehDisjoint](#), [geor:ehMeet](#), [geor:ehOverlap](#), [geor:ehCovers](#), [geor:ehCoveredBy](#), [geor:ehInside](#) and [geor:ehContains](#).

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the following query transformation rules return the correct result for a test dataset when using the specified serialization and version:  
[geor:ehEquals](#), [geor:ehDisjoint](#), [geor:ehMeet](#), [geor:ehOverlap](#), [geor:ehCovers](#), [geor:ehCoveredBy](#),  
[geor:ehInside](#), [geor:ehContains](#).
- c. **Reference:** [Section 7.3](#)
- d. **Test Type:** Capabilities

## A.6.3 RCC8 Relation Family

### A.6.3.1 `/conf/query-rewrite-extension/rcc8-query-rewrite`

**Requirement:** `/req/query-rewrite-extension/rcc8-query-rewrite`

Basic graph pattern matching shall use the semantics defined by the RIF Core Entailment Regime [SPARQLENT] for the RIF rules [RIFCORE] `geor:rcc8eq`, `geor:rcc8dc`, `geor:rcc8ec`, `geor:rcc8po`, `geor:rcc8tppi`, `geor:rcc8tpp`, `geor:rcc8ntpp` and `geor:rcc8ntppi`.

- a. **Test purpose:** Check conformance with this requirement
- b. **Test method:** Verify that queries involving the following query transformation rules return the correct result for a test dataset when using the specified serialization and version: `geor:rcc8eq`, `geor:rcc8dc`, `geor:rcc8ec`, `geor:rcc8po`, `geor:rcc8tppi`, `geor:rcc8tpp`, `geor:rcc8ntpp`, `geor:rcc8ntppi`.
- c. **Reference:** [Section 7.4](#)
- d. **Test Type:** Capabilities

# **Annex B - Functions Summary (normative)**

## B.0 Overview

This annex summarizes all the functions defined in GeoSPARQL, providing descriptions of their parameters and return types.

The value `ogc:geomLiteral` indicates any one of the specific geometry serializations datatypes defined in this Specification, for example `geo:wktLiteral`.

The geometry subtypes - Polygon, Point, CellList etc. - are the *Simple Features specification* [OGCSFACA] [ISO19125-1] or DGS types, as implemented by the various geometry serialization specifications referenced here. See [Section 8.8](#) for the individual specification references.

# B.1 Functions Summary Table

Simple Features Functions				
Function	Input Datatypes	Input Subtypes	Output Datatype	Output Subtype
<a href="#">sfContains</a>	2x ogc:geomLiteral	1x Polygon, 1x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">sfCrosses</a>	2x ogc:geomLiteral	1x Point or LineString, 1 x LineString or Polygon	<a href="#">xsd:boolean</a>	
<a href="#">sfDisjoint</a>	2x ogc:geomLiteral	2x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">sfEquals</a>	2x ogc:geomLiteral	2x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">sfIntersects</a>	2x ogc:geomLiteral	2x Polygon	<a href="#">xsd:boolean</a>	
<a href="#">sfOverlaps</a>	2x ogc:geomLiteral	2x Point or 2x LineString or 2x Polygon	<a href="#">xsd:boolean</a>	
<a href="#">sfTouches</a>	2x ogc:geomLiteral	2x Geometry but not Point	<a href="#">xsd:boolean</a>	
<a href="#">sfWithin</a>	2x ogc:geomLiteral	1x Geometry, 1x Polygon	<a href="#">xsd:boolean</a>	
Egenhofer Functions				
Function	Input Datatypes	Input Subtypes	Output Datatype	Output Subtype
<a href="#">ehContains</a>	2x ogc:geomLiteral	1x Polygon, 1x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">ehCoveredBy</a>	2x ogc:geomLiteral	1x Polygon, 1x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">ehCovers</a>	2x ogc:geomLiteral	1x Polygon, 1x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">ehDisjoint</a>	2x ogc:geomLiteral	2x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">ehEquals</a>	2x ogc:geomLiteral	2x Geometry	<a href="#">xsd:boolean</a>	
<a href="#">ehMeet</a>	2x ogc:geomLiteral	2x Geometry but not Point	<a href="#">xsd:boolean</a>	
<a href="#">ehOverlap</a>	2x ogc:geomLiteral	2x Geometry	<a href="#">xsd:boolean</a>	

ehInside	2x ogc:geomLiteral	2x Geometry	xsd:boolean	
<b>Region Connection Calculus Functions</b>				
<b>Function</b>	<b>Input Datatypes</b>	<b>Input Subtypes</b>	<b>Output Datatype</b>	<b>Output Subtype</b>
rcc8dcc	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8ecc	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8eq	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8ntpp	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8ntppi	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8po	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8tp	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
rcc8tpi	2x ogc:geomLiteral	2x Polygon	xsd:boolean	
<b>Spatial Aggregate Functions</b>				
<b>Function</b>	<b>Input Datatypes</b>	<b>Input Subtypes</b>	<b>Output Datatype</b>	<b>Output Subtype</b>
aggBoundingBox	1 or more ogc:geomLiteral		ogc:geomLiteral	square Polygon (not DGGS),  CellList (DGGS)
aggBoundingCircle	1 or more ogc:geomLiteral		ogc:geomLiteral	Polygon (not DGGS)  CellList (DGGS)
aggCentroid	1 or more ogc:geomLiteral		ogc:geomLiteral	Point (not DGGS),  Cell (DGGS)
aggConcaveHull	1 or more ogc:geomLiteral		ogc:geomLiteral	Polygon (not DGGS),  CellList (DGGS)
aggConvexHull	1 or more ogc:geomLiteral		ogc:geomLiteral	Polygon (not DGGS),  CellList (DGGS)

<a href="#">aggUnion</a>	1 or more ogc:geomLiteral		ogc:geomLiteral	Polygon (not DGGs),  CellList (DGGs)
<b>Non-topological Query Functions</b>				
<b>Function</b>	<b>Input Datatypes</b>	<b>Input Subtypes</b>	<b>Output Datatype</b>	<b>Output Subtype</b>
<a href="#">metricArea</a>	1x ogc:geomLiteral	Polygon	<a href="#">xsd:double</a>	
<a href="#">area</a>	1x ogc:geomLiteral	Polygon	<a href="#">xsd:double</a>	
<a href="#">boundary</a>	1x ogc:geomLiteral	Geometry	ogc:geomLiteral	LineString (not DGGs),  OrderedCellList (DGGs)
<a href="#">buffer</a>	1x ogc:geomLiteral,  1x <a href="#">xsd:double</a> ,  1x <a href="#">xsd:anyURI</a>	any	ogc:geomLiteral	(Multi)Polygon (not DGGs),  CellList (DGGs)
<a href="#">convexHull</a>	1x ogc:geomLiteral	Geometry	ogc:geomLiteral	LineString (not DGGs)
<a href="#">coordinateDimension</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:integer</a>	
<a href="#">difference</a>	2x ogc:geomLiteral	2x Geometry	ogc:geomLiteral	(Multi)Polygon (not DGGs),  CellList (DGGs)
<a href="#">dimension</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">metricDistance</a>	2x ogc:geomLiteral,  1x <a href="#">xsd:anyURI</a>	2x Geometry	<a href="#">xsd:double</a>	
<a href="#">distance</a>	2x ogc:geomLiteral,  1x <a href="#">xsd:anyURI</a>	2x Geometry	<a href="#">rdfs:Resource</a>	



<a href="#">envelope</a>	1x ogc:geomLiteral,  1x xsd:anyURI	Geometry	ogc:geomLiteral	(Multi)Polygon (not DGGs),  CellList (DGGs)
<a href="#">geometryN</a>	1x ogc:geomLiteral	GeometryCollection (not DGGs)	<a href="#">xsd:double</a>	
<a href="#">geometryType</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:anyURI</a>	
<a href="#">getSRID</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:anyURI</a>	
<a href="#">intersection</a>	2x ogc:geomLiteral	2x Geometry	ogc:geomLiteral	Polygon (not DGGs),  CellList (DGGs)
<a href="#">is3D</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:boolean</a>	
<a href="#">isEmpty</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:boolean</a>	
<a href="#">isMeasured</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:boolean</a>	
<a href="#">isSimple</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:boolean</a>	
<a href="#">metricLength</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">length</a>	1x ogc:geomLiteral	Geometry	<a href="#">rdfs:Resource</a>	
<a href="#">numGeometries</a>	1x ogc:geomLiteral	Geometry (not DGGs)	<a href="#">xsd:double</a>	
<a href="#">metricPerimeter</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">perimeter</a>	1x ogc:geomLiteral	Geometry	<a href="#">rdfs:Resource</a>	
<a href="#">spatialDimension</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:integer</a>	
<a href="#">symDifference</a>	2x ogc:geomLiteral	2x Geometry	ogc:geomLiteral	(Multi)Polygon (not DGGs),  CellList DGGs)
<a href="#">transform</a>	1x ogc:geomLiteral, 1x <a href="#">xsd:anyURI</a>	Geometry	ogc:geomLiteral	Geometry

<a href="#">union</a>	2x ogc:geomLiteral	2x Geometry	ogc:geomLiteral	Polygon (not DGGS),  CellList (DGGS)
<b>Serialization Functions</b>				
<b>Function</b>	<b>Input Datatypes</b>	<b>Input Subtypes</b>	<b>Output Datatype</b>	<b>Output Subtype</b>
<a href="#">asDGGS</a>	1x ogc:geomLiteral	Geometry	geo:dggsLiteral	
<a href="#">asGeoJSON</a>	1x ogc:geomLiteral	Geometry	geo:geoJSONLiteral	
<a href="#">asGML</a>	1x ogc:geomLiteral, 1x <a href="#">xsd:string</a>	Geometry	geo:gmlLiteral	
<a href="#">asKML</a>	1x ogc:geomLiteral	Geometry	geo:kmlLiteral	
<a href="#">asWKT</a>	1x ogc:geomLiteral	Geometry	geo:wktLiteral	
<b>Extent Functions</b>				
<b>Function</b>	<b>Input Datatypes</b>	<b>Input Subtypes</b>	<b>Output Datatype</b>	<b>Output Subtype</b>
<a href="#">getSRID</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:anyURI</a>	
<a href="#">maxX</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">maxY</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">maxZ</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">minX</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">minY</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<a href="#">minZ</a>	1x ogc:geomLiteral	Geometry	<a href="#">xsd:double</a>	
<b>Other Functions</b>				
<b>Function</b>	<b>Input Datatypes</b>	<b>Input Subtypes</b>	<b>Output Datatype</b>	<b>Output Subtype</b>
<a href="#">relate</a>	2x ogc:geomLiteral		<a href="#">xsd:string</a>	

## B.2 GeoSPARQL to SFA Functions Mapping

The following table indicates which GeoSPARQL non-topological query functions map to Simple Features Access ([OGCSFACA] [ISO19125-1]) functions and in which GeoSPARQL version the functions are defined.

Where the Simple Features Access function has the same name as the GeoSPARQL function, 'x' is recorded.

GeoSPARQL Function	in 1.0	in 1.1	SFA
metricArea		x	Area
area		x	Area
			AsBinary
asWKT*	x	x	AsText
boundary	x	x	Boundary
buffer	x	x	Buffer
			Centroid
convexHull	x	x	ConvexHull
coordinateDimension		x	
difference	x	x	Difference
dimension		x	Dimension
metricDistance		x	Distance
distance	x	x	Distance
			EndPoint
envelope	x	x	Envelope
geometryN		x	GeometryN
geometryType		x	GeometryType
getSRID	x	x	SRID
			InteriorRingN
intersection	x	x	Intersection
is3D		x	
			IsClosed
isEmpty		x	IsEmpty
isMeasured		x	
			IsRing
isSimple		x	IsSimple
metricLength		x	Length

GeoSPARQL Function	in 1.0	in 1.1	SFA
length		x	Length
maxX		x	
maxY		x	
maxZ		x	
minX		x	
minY		x	
minZ		x	
numGeometries		x	NumGeometries
			NumInteriorRing
			NumPoints
perimeterLength		x	
perimeter		x	
			PointN
			PointOnSurface
spatialDimension		x	
			StartPoint
symDifference	x	x	SymDifference
transform		x	
union	x	x	Union
			X
			Y

\* GeoSPARQL's **asWKT** is only a partial implementation of **asText** since **asWKT** only returns WKT, not textual geometry literal data in general.

# **Annex C - GeoSPARQL Examples (informative)**

## C.0 Overview

This Annex provides examples of the GeoSPARQL ontology and functions. In addition to these, extended examples are provided separately by the GeoSPARQL 1.1 profile. See the [GeoSPARQL Standard structure](#) for the link to those examples.

# C.1 RDF Examples

This Section illustrates GeoSPARQL ontology modelling with extended examples.

## C.1.1 Classes

### C.1.1.1 *SpatialObject*

The *SpatialObject* class is defined in [Section 6.2.1](#).

#### C.1.1.1.1 Basic use

Basic use (as per the example in the class definition)

```
eg:x
  a geo:SpatialObject ;
  skos:prefLabel "Object X";
.
```

#### NOTE

It is unlikely that users of GeoSPARQL will create many instances of *geo:SpatialObject* as its two more concrete subclasses, *geo:Feature* & *geo:Geometry*, are more directly relatable to real-world phenomena and use.

#### C.1.1.1.2 Size Properties

The "size" properties - *geo:hasSize*, *geo:hasMetricSize*, *geo:hasLength*, *geo:hasMetricLength*, *geo:hasPerimeterLength*, *geo:hasMetricPerimeterLength*, *geo:hasArea*, *geo:hasMetricArea*, *geo:hasVolume* and *geo:hasMetricVolume* - are all applicable to instances of *geo:SpatialObject* although, as per the note in the section above, they are likely to be used with *geo:Feature* & *geo:Geometry* instances.

```
@prefix qudt: <http://qudt.org/schema/qudt/> .
@prefix unit: <http://qudt.org/vocab/unit/> .

eg:moreton-island
  a geo:SpatialObject ;

  skos:prefLabel "Moreton Island" ;
  rdfs:seeAlso "https://en.wikipedia.org/wiki/Moreton_Island"^^xsd:anyURI ;

  geo:hasPerimeterLength [
    qudt:numericValue "92.367"^^xsd:float ;
    qudt:unit unit:KiloM ;
  ];
  geo:hasMetricPerimeterLength "92367"^^xsd:double ;
.
```

Here a spatial object, Moreton Island, has the distance of its coastline given with two properties: `geo:hasPerimeterLength` & `geo:hasMetricPerimeterLength`. The object for the first is a Blank Node with a QUDT value property of 92.367 and a QUDT unit property of `unit:KiloM` (kilometre). The object for the second is the literal `92367` (a double) which is, by the property's definition, a number of metres.

The use of the *Quantities, Units, Dimensions and Types (QUDT)* ontology<sup>[1]</sup> and its `qudt:numericValue` & `qudt:unit` is just one of many possible ways to convey the value of `geo:hasPerimeterLength` and any subproperty of `geo:hasSize`.

### C.1.1.2 Feature

The **Feature** class is defined in [Section 6.2.2](#).

#### C.1.1.2.1 Basic use

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X" ;
  .
```

Here a **Feature** is declared and given a preferred label.

#### C.1.1.2.2 A Feature related to a Geometry

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X" ;
  geo:hasGeometry [
    geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.06062 -35.23604, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ;
  .
```

Here a `geo:Feature` is declared, given a preferred label and a Geometry for that `geo:Feature` is indicated with the use of `geo:hasGeometry`. The **Geometry** indicated is described using a *Well-Known Text* literal value, indicated by the property `geo:asWKT` and the literal type `geo:wktLiteral`.

#### C.1.1.2.3 Feature with Geometry and size (area)

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X" ;
  geo:hasGeometry [
    geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.06062 -35.23604, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ;
  geo:hasMetricArea "8.9E4"^^xsd:double ;
```



.

This example and the example below (B 1.1.2.4) show the same **geo:Feature**, but with a different specification of its area. This example shows the recommended way to express size: by using a subproperty of **geo:hasMetricSize** (in this case, **[Property: geo:MetricArea]**). These subproperties have fixed units based on meter (the unit of distance in the International System of Units).

#### C.1.1.2.4 **Feature with Geometry and non-metric size**

```
@prefix qudt: <http://qudt.org/schema/qudt/> .

eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X";
  geo:hasGeometry [
    geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.06062 -35.23604, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ;
  geo:hasArea [
    qudt:numericValue "2.2E5"^^xsd:double ;
    qudt:unit <http://qudt.org/vocab/unit/AC> ; # international acre
  ] ;
.
```

Here a **geo:Feature** is described as per the previous example but its area is expressed in non-metric units: the acre.

#### C.1.1.2.5 **Feature with two different Geometry instances indicated**

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X";
  geo:hasGeometry [
    rdfs:label "Official boundary" ;
    rdfs:comment "Official boundary from the Department of Xxx" ;
    geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.06062 -35.23604, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ,
  [
    rdfs:label "Unofficial boundary" ;
    rdfs:comment "Unofficial boundary as actually used by everyone" ;
    geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.06062 -35.23604, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ;
.
```

In this example, **Feature X** has two different **Geometry** instances indicated with their difference explained in annotation properties. No GeoSPARQL ontology properties are used to indicate a

difference in these **Geometry** instances thus machine use of this **Feature** would not be easily able to differentiate them.

#### C.1.1.2.6 **Feature** with two different **Geometry** instances with different property values

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X";
  geo:hasGeometry [
    geo:hasMetricSpatialResolution "100"^^xsd:double ;
    geo:asWKT "MULTIPOLYGON (((149.0601 -35.2361, 149.0606 -35.2360, ... ,
149.0601 -35.2361)))"^^geo:wktLiteral ;
  ] ,
  [
    geo:hasMetricSpatialResolution "5"^^xsd:double ;
    geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.06062 -35.23604, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ;
.
```

In this example, **Feature X** has two different **Geometry** instances indicated with different spatial resolutions. Machine use of this **Feature** would be able to differentiate the two **Geometry** instances based on this use of **geo:hasMetricSpatialResolution**.

#### C.1.1.2.7 **Feature** with non-metric size

```
@prefix dbp: <http://dbpedia.org/resource/> .
@prefix qudt: <http://qudt.org/schema/qudt/> .

ex:Seleucia_Artemita
  a geo:Feature ;
  skos:prefLabel "The route from Seleucia to Artemita"@en ;
  geo:hasLength [
    qudt:unit ex:Schoenus ;
    qudt:value "15"^^xsd:integer ;
  ]
.
ex:Schoenus
  a qudt:Unit;
  skos:exactMatch dbp:Schoenus;
.
```

In this example it is not possible to convert the length of the feature to meters, because the historical length unit does not have a known precise conversion factor.

#### C.1.1.2.8 **Feature** with two different types of **Geometry** instances

```
eg:x
```

```

a geo:Feature ;
skos:prefLabel "Feature X";
geo:hasGeometry [
    geo:asWKT "POLYGON ((149.06016 -35.23610, 149.060620 -35.236043, ... ,
149.06016 -35.23610))"^^geo:wktLiteral ;
] ;
geo:hasCentroid [
    geo:asWKT "POINT (149.06017784 -35.23612321)"^^geo:WktLiteral ;
] ;
.

```

Here a **Feature** instance has two geometries, one indicated with the general property **hasGeometry** and a second indicated with the specialized property **hasCentroid** which suggests the role that the indicated geometry plays. Note that while **hasGeometry** may indicate any type of **Geometry**, **hasCentroid** should only be used to indicate a point geometry. It may be informally inferred that the polygonal geometry is the **Feature** instance's boundary.

#### C.1.1.2.9 **Feature** with multiple sizes

```

ex:lake-x
a geo:Feature ;
skos:prefLabel "Lake X" ;
eg:hasFeatureCategory <http://example.com/cat/lake> ;
geo:hasMetricArea "9.26E4"^^xsd:double ;
geo:hasMetricVolume "6E5"^^xsd:double ;
.

```

This example shows a **Feature** instance with area and volume declared. A categorization of the Feature is given through the use of the **eg:hasFeatureCategory** dummy property which, along with the Feature's preferred label, indicate that this Feature is a lake. Having both an area and a volume makes sense for a lake.

### C.1.1.3 **Geometry**

The **Geometry** class is defined in [Section 8.6.1](#).

#### C.1.1.3.1 Basic Use

```

eg:y a geo:Geometry ;
skos:prefLabel "Geometry Y";
.

```

Here a **Geometry** is declared and given a preferred label.

From GeoSPARQL 1.0 use, the most commonly observed use of a **Geometry** is in relation to a **Feature** as per the example in [\[B 1.1.2.2 A Feature related to a Geometry\]](#) and often the **Geometry** is indirectly declared by the use of **hasGeometry** on the **Feature** instance indicating a Blank Node. However, it is

entirely possible to declare **Geometry** instances without any **Feature** instances. The next basic example declares a **Geometry** instance with an absolute URI and data.

```
<https://example.com/geometry/y>
  a geo:Geometry ;
  skos:prefLabel "Geometry Y";
  geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.060620 -35.236043, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
.
```

Here the **Geometry** instance has data in WKT form and, since no CRS is declared, WGS84 is the assumed, default, CRS.

#### C.1.1.3.2 A **Geometry** with multiple serializations

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X";
  geo:hasGeometry [
    geo:asWKT "<http://www.opengis.net/def/crs/EPSG/0/4326> MULTIPOLYGON
(((149.06016 -35.23610, 149.060620 -35.236043, ... , 149.06016
-35.23610)))"^^geo:wktLiteral ;
    geo:asDGGS "<https://w3id.org/dggs/auspix> CELLLIST ((R1234 R1235 R1236 ...
R1256))"^^geo:dggsLiteral ;
  ] ;
.
```

Here a single **Geometry**, linked to a **Feature** instance, is expressed using two different serializations: Well-known Text and the DGGS with the AusPIX DGGS indicated by its IRI.

#### C.1.1.3.3 **Geometry** with scalar spatial property

```
eg:x
  a geo:Feature ;
  skos:prefLabel "Feature X";
  geo:hasGeometry eg:x-geo ;
.

eg:x-geo
  a geo:Geometry ;
  geo:asWKT "MULTIPOLYGON (((149.06016 -35.23610, 149.060620 -35.236043, ... ,
149.06016 -35.23610)))"^^geo:wktLiteral ;
  geo:hasMetricArea "8.7E4"^^xsd:double;
.
```

This example shows a **Feature**, **eg:x**, with a **Geometry**, **eg:x-geo**, which has both a serialization (WKT) indicated with the predicate **geo:asWKT** and a scalar area indicated with the predicate

**geo:hasMetricArea**. While it is entirely possible that scalar areas can be calculated from polygons, it may be efficient to store a pre-calculated scalar area in addition to the polygon. Perhaps the polygon is large and detailed and a one-time calculation with results stored is efficient for repeated use.

This use of a scalar spatial measurement property with a Geometry, here **geo:hasMetricArea**, is possible since the domain of such properties is **geo:SpatialObject**, the superclass of both **geo:Feature** and **geo:Geometry**.

#### C.1.1.4 SpatialObjectCollection

**geo:SpatialObjectCollection** isn't really intended to be implemented - it's essentially an abstract class - therefore no examples of its use are given. See the following two sections for examples of the concrete **geo:FeatureCollection** & **geo:GeometryCollection** classes.

#### C.1.1.5 FeatureCollection

This example shows a **FeatureCollection** instance containing 3 **Feature** instances.

```
ex:fc-x
  a geo:FeatureCollection ;
  dcterms:title "Feature Collection X" ;
  rdfs:member
    ex:feature-something ,
    ex:feature-other ,
    ex:feature-another ;
.
```

All of the GeoSPARQL collection classes are unordered since they are subclasses of the generic **rdfs:Container**, however implementers should consider that there are many ways to order the members of a **FeatureCollection** such as the **Feature** instance labels, their areas, geometries or any other property.

#### C.1.1.6 GeometryCollection

This example shows a **GeometryCollection** instance containing 3 **Geometry** instances.

```
ex:gc-x
  a geo:GeometryCollection ;
  dcterms:title "Geometry Collection X" ;
  rdfs:member
    ex:geometry-shape ,
    ex:geometry-othershape ,
    ex:geometry-anothershape ;
.
```

As per **FeatureCollection**, the **GeometryCollection** itself doesn't impose any ordering on its member

**Geometry** instances, however there are many ways to order them, based on their own properties.

### C.1.1.7 Simple Features classes

Most of the geometry serializations used in GeoSPARQL define the geometry type - point, polygon etc. *within* the literal, e.g. WKT can encode **POLYGON()** or 'POINT()', however the *Simple Features Vocabulary* resource within GeoSPARQL 1.1 contains specialised Geometry RDF classes such as **sf:Polygon**, **sf:PolyhedralSurface** and others.

It may be appropriate to use these specialized forms of Geometry in circumstances when geometry type differentiation is required within RDF and not withing specialized literal handling. This is the case when type differentiation must occur within plain SPARQL, not GeoSPARQL.

The following example shows a **Feature** instance with two **Geometry** instances where the *Simple Features Vocabulary* classes are used to indicate the Geometry type:

```
ex:x
  a geo:Feature ;
  rdfs:label "Feature X" ;
  geo:hasGeometry [
    a sf:Point ;
    geo:asWKT "POINT(...)" ;
    rdfs:comment "A point geometry for Feature X, possibly a centroid though not
declared one" ;
  ] ;
  geo:hasGeometry [
    a sf:Polygon ;
    geo:asWKT "POLYGON(...)" ;
    rdfs:comment "A polygon geometry for Feature X" ;
  ] ;
```

There are several GeoSPARQL properties that suggest they could be used with particular *Simple Features Vocabulary* geometry types, for instance, **geo:hasCentroid** indicates is could be used with a **sf:Point** and **geo:hasBoundingBox** indicates use with an **sf:Envelope**.

## C.1.2 Properties

### C.1.2.1 Spatial Object Properties

See the section [C.1.1.1.2 Size Properties](#) above.

### C.1.2.2 Feature Properties

This example shows a **geo:Feature** instance with each of the properties defined in [Section 6.4](#) used, except for the properties **geo:hasMetricSize** and **geo:hasSize**, that are intended to be used through their subproperties and **geo:hasMetricPerimeterLength** and **geo:hasPerimeterLength** which are exemplified in [C.1.1.1.2 Size Properties](#).

```
@prefix qudt: <http://qudt.org/schema/qudt/> .
```

```
eg:x
```

```
  a geo:Feature ;
  skos:preferredLabel "Feature X" ;
  geo:hasGeometry [
    geo:asWKT "<http://www.opengis.net/def/crs/EPSSG/0/4326> POLYGON ((149.06016
-35.23610, ... , 149.06016 -35.23610)))"^^geo:wktLiteral ;
  ] ;
  geo:hasDefaultGeometry [
    geo:asWKT "<http://www.opengis.net/def/crs/EPSSG/0/4326> POLYGON ((149.0601
-35.2361, ... , 149.0601 -35.2361)))"^^geo:wktLiteral ;
  ] ;
  geo:hasMetricLength "355"^^xsd:double ;
  geo:hasLength [
    qudt:numericValue 355 ;
    qudt:unit <http://qudt.org/vocab/unit/M> ; # meter
  ] ;
  geo:hasMetricArea "8.7E4"^^xsd:double ;
  geo:hasArea [
    qudt:numericValue 8.7 ;
    qudt:unit <http://qudt.org/vocab/unit/HA> ; # hectare
  ] ;
  geo:hasMetricVolume "624432"^^xsd:double ;
  geo:hasVolume [
    qudt:numericValue 624432 ;
    qudt:unit <http://qudt.org/vocab/unit/M3> ; # cubic meter
  ] ;
  geo:hasCentroid [
    geo:asWKT "POINT (149.06017 -35.23612)"^^geo:wktLiteral ;
  ] ;
  geo:hasBoundingBox [
    geo:asWKT "<http://www.opengis.net/def/crs/EPSSG/0/4326> POLYGON ((149.060
-35.236, ... , 149.060 -35.236)))"^^geo:wktLiteral ;
  ] ;
  geo:hasMetricSpatialResolution "5"^^xsd:double ;
  geo:hasSpatialResolution [
    qudt:numericValue 5 ;
    qudt:unit <http://qudt.org/vocab/unit/M> ; # meter
  ] ;
  .
```

The properties defined for this example's **Feature** instance are vaguely aligned in that the values are not real but are not unrealistic either. It is outside the scope of GeoSPARQL to validate **Feature** instances' property values.

Note that this **Feature** has a 2D **Geometry** and yet a property indicating a scalar volume: **geo:hasVolume**. Used in this way, the scalar property is indicating information that cannot be calculated from other information about the **Feature** such as its geometry. Perhaps a volume for the

feature has been estimated or measured in such a way that a 3D geometry was not created.

### C.1.2.3 Geometry Properties

This example shows a **Geometry** instance, a Blank Node, declared in relation to a **Feature** instance, with each of the properties defined in [Section 8.7](#) used.

```
@prefix qudt: <http://qudt.org/schema/qudt/> .
@prefix unit: <http://qudt.org/vocab/unit/> .

eg:x
  a geo:Feature ;
  geo:hasGeometry [
    skos:prefLabel "Geometry Y" ;
    geo:dimension 2 ;
    geo:coordinateDimension 2 ;
    geo:spatialDimension 2 ;
    geo:isEmpty false ;
    geo:isSimple true ;
    geo:hasSerialization "<http://www.opengis.net/def/crs/EPSSG/0/4326> POLYGON
((149.060 -35.236, ... , 149.060 -35.236)))"^^geo:wktLiteral ;
    geo:hasSpatialAccuracy [
      qudt:numericValue "30"^^xsd:float ;
      qudt:unit unit:CentiM ; # centimetres
    ] ;
    geo:hasMetricSpatialAccuracy "0.3"^^xsd:double ;
  ] ;
.
```

In this example, each of the properties defined for a **Geometry** instance has realistic values. For example, the **is empty** property is set to **false** since the **Geometry** contains information.

### C.1.2.4 Geometry Serializations

This section shows a **Geometry** instance for a **Feature** instance which is represented in all supported GeoSPARQL serializations. The geometry values given are real geometry values and approximate [Moreton Island](#) in Queensland, Australia.

Note that the concrete DGGS serialization used is for example purposes only as it is not formally defined in GeoSPARQL.

```
eg:x
  a geo:Feature ;
  geo:hasGeometry [
    geo:asWKT ""<http://www.opengis.net/def/crs/EPSSG/0/4326>
      POLYGON ((
        153.3610112 -27.0621757,
        153.3658177 -27.1990606,
        153.421436 -27.3406573,
```



```

153.4269292 -27.3607835,
153.4434087 -27.3315078,
153.4183848 -27.2913403,
153.4189391 -27.2039578,
153.4673476 -27.0267166,
153.3610112 -27.0621757
))""^geo:wktLiteral ;

geo:asGML ""<gml:Polygon
  srsName="http://www.opengis.net/def/crs/EPSG/0/4326">
  <gml:exterior>
    <gml:LinearRing>
      <gml:posList>
        -27.0621757 153.3610112
        -27.1990606 153.3658177
        -27.3406573 153.421436
        -27.3607835 153.4269292
        -27.3315078 153.4434087
        -27.2913403 153.4183848
        -27.2039578 153.4189391
        -27.0267166 153.4673476
        -27.0621757 153.3610112
      </gml:posList>
    </gml:LinearRing>
  </gml:exterior>
</gml:Polygon>""^go:gmlLiteral ;

geo:asKML ""<Polygon>
  <outerBoundaryIs>
    <LinearRing>
      <coordinates>
        153.3610112,-27.0621757
        153.3658177,-27.1990606
        153.421436,-27.3406573
        153.4269292,-27.3607835
        153.4434087,-27.3315078
        153.4183848,-27.2913403
        153.4189391,-27.2039578
        153.4673476,-27.0267166
        153.3610112,-27.0621757
      </coordinates>
    </LinearRing>
  </outerBoundaryIs>
</Polygon>""^go:kmlLiteral ;

geo:asGeoJSON ""{
  "type": "Polygon",
  "coordinates": [[
    [153.3610112, -27.0621757],
    [153.3658177, -27.1990606],
    [153.421436, -27.3406573],

```

```
[153.4269292, -27.3607835],  
[153.4434087, -27.3315078],  
[153.4183848, -27.2913403],  
[153.4189391, -27.2039578],  
[153.4673476, -27.0267166],  
[153.3610112, -27.0621757]  
]]  
}""^^geo:geoJSONLiteral ;
```

```
geo:asDGGs ""<https://w3id.org/dggs/auspex> CELLLIST ((R8346031 R8346034  
R8346037  
R83460058 R83460065 R83460068 R83460072 R83460073 R83460074 R83460075  
R83460076  
R83460077 R83460078 R83460080 R83460081 R83460082 R83460083 R83460084  
R83460085  
R83460086 R83460087 R83460088 R83460302 R83460305 R83460308 R83460320  
R83460321  
R83460323 R83460324 R83460326 R83460327 R83460332 R83460335 R83460338  
R83460350  
R83460353 R83460356 R83460362 R83460365 R83460380 R83460610 R83460611  
R83460612  
R83460613 R83460614 R83460615 R83460617 R83460618 R83460641 R83460642  
R83460644  
R83460645 R83460648 R83460672 R83460686 R83463020 R83463021 R834600487  
R834600488  
R834600557 R834600558 R834600564 R834600565 R834600566 R834600567  
R834600568  
R834600571 R834600572 R834600573 R834600574 R834600575 R834600576  
R834600577  
R834600578 R834600628 R834600705 R834600706 R834600707 R834600708  
R834600712  
R834600713 R834600714 R834600715 R834600716 R834600717 R834600718  
R834601334  
R834601335 R834601336 R834601337 R834601338 R834601360 R834601361  
R834601363  
R834601364 R834601366 R834601367 R834601600 R834601601 R834601603  
R834601606  
R834601630 R834601633 R834603220 R834603221 R834603223 R834603224  
R834603226  
R834603227 R834603250 R834603251 R834603253 R834603256 R834603280  
R834603283  
R834603510 R834603511 R834603512 R834603513 R834603514 R834603515  
R834603516  
R834603517 R834603540 R834603541 R834603543 R834603544 R834603546  
R834603547  
R834603570 R834603573 R834603576 R834603681 R834603682 R834603684  
R834603685  
R834603687 R834603688 R834603810 R834603830 R834603831 R834603832  
R834603833  
R834603834 R834603835 R834603836 R834603837 R834603860 R834603861  
R834603863
```

```

R834603864 R834603866 R834603867 R834606021 R834606022 R834606024
R834606025
R834606028 R834606052 R834606055 R834606160 R834606161 R834606162
R834606164
R834606165 R834606167 R834606168 R834606200 R834606203 R834606206
R834606230
R834606233 R834606236 R834606260 R834606263 R834606266 R834606401
R834606402
R834606405 R834606408 R834606432 R834606471 R834606472 R834606474
R834606475
R834606477 R834606478 R834606500 R834606503 R834606506 R834606530
R834606533
R834606536 R834606560 R834606563 R834606566 R834606712 R834606715
R834606718
R834606750 R834606751 R834606752 R834606753 R834606754 R834606755
R834606757
R834606758 R834606781 R834606782 R834606784 R834606785 R834606788
R834606800
R834606803 R834606806 R834606807 R834606830 R834606831 R834606833
R834606834
R834606835 R834606836 R834606837 R834606838 R834606870 R834606873
R834606874
R834606876 R834606877 R834630122 R834630125 R834630226 R834630230
R834630231
R834630232 R834630234 R834630235 R834630237 R834630238 R834630240
R834630241
R834630242 R834630243 R834630244 R834630245 R834630246 R834630247
R834630261
R834630262 R834630264 R834630265 R834630268 R834630270 R834630271
R834630273
R834630276 R834630502))""^^geo:dggsLiteral ;
] ;
.

```

[1] <http://www.qudt.org>

## C.2 Example SPARQL Queries & Rules

This Section provides example data and then illustrates the use of GeoSPARQL functions and the application of rules with that data.

### C.2.1 Example Data

The following RDF data (Turtle format) encodes application-specific spatial data. The resulting spatial data is illustrated in the figure below. The RDF statements define the feature class `my:PlaceOfInterest`, and two properties are created for associating geometries with features: `my:hasExactGeometry` and `my:hasPointGeometry`. `my:hasExactGeometry` is designated as the default geometry for the `my:PlaceOfInterest` feature class.

All the following examples use the parameter values `relation_family = Simple Features`, `serialization = WKT`, and `version = 1.0`.



Figure 4. Illustration of spatial data

```
@prefix geo: <http://www.opengis.net/ont/geosparql#> .
@prefix my: <http://example.org/ApplicationSchema#> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
@prefix sf: <http://www.opengis.net/ont/sf#> .

my:PlaceOfInterest a rdfs:Class ;
  rdfs:subClassOf geo:Feature .

my:A a my:PlaceOfInterest ;
  my:hasExactGeometry my:AExactGeom ;
  my:hasPointGeometry my:APointGeom .

my:B a my:PlaceOfInterest ;
  my:hasExactGeometry my:BExactGeom ;
  my:hasPointGeometry my:BPointGeom .

my:C a my:PlaceOfInterest ;
```

```

my:hasExactGeometry my:CExactGeom ;
my:hasPointGeometry my:CPointGeom .

my:D a my:PlaceOfInterest ;
  my:hasExactGeometry my:DExactGeom ;
  my:hasPointGeometry my:DPointGeom .

my:E a my:PlaceOfInterest ;
  my:hasExactGeometry my:EExactGeom .

my:F a my:PlaceOfInterest ;
  my:hasExactGeometry my:FExactGeom .

my:hasExactGeometry a rdf:Property ;
  rdfs:subPropertyOf geo:hasDefaultGeometry,
    geo:hasGeometry .

my:hasPointGeometry a rdf:Property ;
  rdfs:subPropertyOf geo:hasGeometry .

my:AExactGeom a sf:Polygon ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Polygon((-83.6 34.1, -83.2 34.1, -83.2 34.5,
      -83.6 34.5, -83.6 34.1))""^^geo:wktLiteral.

my:APointGeom a sf:Point ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Point(-83.4 34.3)""^^geo:wktLiteral.

my:BExactGeom a sf:Polygon ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Polygon((-83.6 34.1, -83.4 34.1, -83.4 34.3,
      -83.6 34.3, -83.6 34.1))""^^geo:wktLiteral.

my:BPointGeom a sf:Point ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Point(-83.5 34.2)""^^geo:wktLiteral.

my:CExactGeom a sf:Polygon ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Polygon((-83.2 34.3, -83.0 34.3, -83.0 34.5,
      -83.2 34.5, -83.2 34.3))""^^geo:wktLiteral.

my:CPointGeom a sf:Point ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Point(-83.1 34.4)""^^geo:wktLiteral.

my:DExactGeom a sf:Polygon ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Polygon((-83.3 34.0, -83.1 34.0, -83.1 34.2,
      -83.3 34.2, -83.3 34.0))""^^geo:wktLiteral.

```

```

my:DPointGeom a sf:Point ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Point(-83.2 34.1)""^^geo:wktLiteral.

my:EExactGeom a sf:LineString ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    LineString(-83.4 34.0, -83.3 34.3)""^^geo:wktLiteral.

my:FExactGeom a sf:Point ;
  geo:asWKT ""<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
    Point(-83.4 34.4)""^^geo:wktLiteral.

```

## C.2.2 Example Queries

This Section illustrates the use of GeoSPARQL functions through a series of example queries.

### C.2.2.1

*Find all features that feature **my:A** contains, where spatial calculations are based on **my:hasExactGeometry**.*

```

PREFIX my: <http://example.org/ApplicationSchema#>
PREFIX geo: <http://www.opengis.net/ont/geosparql#>
PREFIX geof: <http://www.opengis.net/def/function/geosparql/>

SELECT ?f
WHERE {
  my:A my:hasExactGeometry ?aGeom .
  ?aGeom geo:asWKT ?aWKT .
  ?f my:hasExactGeometry ?fGeom .
  ?fGeom geo:asWKT ?fWKT .

  FILTER (
    geof:sfContains(?aWKT, ?fWKT) &&
    !sameTerm(?aGeom, ?fGeom)
  )
}

```

**Result:**

?f
my:B
my:F

### C.2.2.2

Find all features that are within a transient bounding box geometry, where spatial calculations are based on `my:hasPointGeometry`.

```
PREFIX my: <http://example.org/ApplicationSchema#>
PREFIX geo: <http://www.opengis.net/ont/geosparql#>
PREFIX geof: <http://www.opengis.net/def/function/geosparql/>

SELECT ?f
WHERE {
  ?f my:hasPointGeometry ?fGeom .
  ?fGeom geo:asWKT ?fWKT .
  FILTER (
    geof:sfWithin(
      ?fWKT,
      "<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
      Polygon ((-83.4 34.0, -83.1 34.0,
                -83.1 34.2, -83.4 34.2,
                -83.4 34.0))"^^geo:wktLiteral
    )
  )
}
```

**Result:**

?f
my:D

### C.2.2.3

Find all features that touch the union of feature `my:A` and feature `my:D`, where computations are based on `my:hasExactGeometry`.

```
PREFIX my: <http://example.org/ApplicationSchema#>
PREFIX geo: <http://www.opengis.net/ont/geosparql#>
PREFIX geof: <http://www.opengis.net/def/function/geosparql/>

SELECT ?f
WHERE {
  ?f my:hasExactGeometry ?fGeom .
  ?fGeom geo:asWKT ?fWKT .
  my:A my:hasExactGeometry ?aGeom .
  ?aGeom geo:asWKT ?aWKT .
  my:D my:hasExactGeometry ?dGeom .
  ?dGeom geo:asWKT ?dWKT .
  FILTER (
    geof:sfTouches(
```

```

        ?fWKT,
        geof:union(?aWKT, ?dWKT)
    )
}

```

**Result:**

?f
my:C

### C.2.2.4

Find the 3 closest features to feature my:C, where computations are based on my:hasExactGeometry.

```

PREFIX uom: <http://www.opengis.net/def/uom/OGC/1.0/>
PREFIX my: <http://example.org/ApplicationSchema#>
PREFIX geo: <http://www.opengis.net/ont/geosparql#>
PREFIX geof: <http://www.opengis.net/def/geosparql/function>

```

```

SELECT ?f
WHERE {
    my:C my:hasExactGeometry ?cGeom .
    ?cGeom geo:asWKT ?cWKT .
    ?f my:hasExactGeometry ?fGeom .
    ?fGeom geo:asWKT ?fWKT .
    FILTER (?fGeom != ?cGeom)
}
ORDER BY ASC (geof:distance(?cWKT, ?fWKT, uom:metre))
LIMIT 3

```

**Result:**

?f
my:A
my:D
my:E

### C.2.2.5

Find the maximum and minimum coordinates of a given set of geometries.

```

PREFIX geo: <http://www.opengis.net/ont/geosparql#>
PREFIX geof: <http://www.opengis.net/def/function/geosparql/>

```

```

SELECT ?minX ?minY ?minZ ?maxX ?maxY ?maxZ
WHERE {

```



```

BIND ("<http://www.opengis.net/def/crs/OGC/1.3/CRS84>
      Polygon Z((-83.4 34.0 0, -83.1 34.0 1,
                -83.1 34.2 1, -83.4 34.2 1,
                -83.4 34.0 0))"^^geo:wktLiteral) AS ?testgeom)
BIND(geof:minX(?testgeom) AS ?minX)
BIND(geof:maxX(?testgeom) AS ?maxX)
BIND(geof:minY(?testgeom) AS ?minY)
BIND(geof:maxY(?testgeom) AS ?maxY)
BIND(geof:maxZ(?testgeom) AS ?maxZ)
BIND(geof:minZ(?testgeom) AS ?minZ)
}

```

**Result:**

?minX	?minY	?minZ	?maxX	?maxY	?maxZ
-83.4	34.0	0	-83.1	34.2	1

## C.2.3 Example Rule Application

This section illustrates the query transformation strategy for implementing GeoSPARQL rules.

### C.2.3.1

*Find all features or geometries that overlap feature **my:A**.*

**Original Query:**

```

PREFIX geo: <http://www.opengis.net/ont/geosparql#>

SELECT ?f
WHERE { ?f geo:sfOverlaps my:A }

```

**Transformed Query (application of transformation rule `geor:sfOverlaps`):**

```

PREFIX my: <http://example.org/ApplicationSchema#>
PREFIX geo: <http://www.opengis.net/ont/geosparql#>
PREFIX geof: <http://www.opengis.net/def/function/geosparql/>

SELECT ?f
WHERE {
  { # check for asserted statement
    ?f geo:sfOverlaps my:A }
  UNION
  { # feature = feature
    ?f geo:hasDefaultGeometry ?fGeom .
    ?fGeom geo:asWKT ?fSerial .
    my:A geo:hasDefaultGeometry ?aGeom .

```

```

    ?aGeom geo:asWKT ?aSerial .
    FILTER (geof:sfOverlaps(?fSerial, ?aSerial))
  }
  UNION
  { # feature → geometry
    ?f geo:hasDefaultGeometry ?fGeom .
    ?fGeom geo:asWKT ?fSerial .
    my:A geo:asWKT ?aSerial .
    FILTER (geof:sfOverlaps(?fSerial, ?aSerial))
  }
  UNION
  { # geometry → feature
    ?f geo:asWKT ?fSerial .
    my:A geo:hasDefaultGeometry ?aGeom .
    ?aGeom geo:asWKT ?aSerial .
    FILTER (geof:sfOverlaps(?fSerial, ?aSerial))
  }
  UNION
  { # geometry → geometry
    ?f geo:asWKT ?fSerial .
    my:A geo:asWKT ?aSerial .
    FILTER (geof:sfOverlaps(?fSerial, ?aSerial))
  }
}

```

#### Result:

?f
my:D
my:DExactGeom
my:E
my:EExactGeom

## C.2.4 Example Geometry Serialization Conversion Functions

For the geometry literal values in [C.1.2.4 Geometry Serializations](#):

Application of the function `geof:asWKT` to the GML, KML, GeoJSON and DGGS literals should return WKT literal and similarly for each of the other conversion methods, `geof:asGML`, `geof:asKML`, `geof:asGeoJSON` & `geof:asDGGS`.

# **Annex D - Usage of SHACL shapes (informative)**

# D.0 Overview

This Annex provides guidance on the usage of the SHACL shapes included with GeoSPARQL 1.1.

The Shapes Constraint Language [SHACL](#) allows the specification of constraints on RDF data, phrased as a set of conditions modeled in "Shape" graphs.

In GeoSPARQL 1.1, SHACL Shapes are defined in such a way that they validate anticipated graph structures expected by Requirements defined in the standard. Users may validate a given RDF document claiming conformance to GeoSPARQL 1.1 by using these Shapes and use the validation results to correct any mistakes.

# D.1 Tools

[SHACL Shapes provided with GeoSPARQL](#) are used to verify the graph structure of GeoSPARQL graphs. There are several SHACL tools that one can use to validate data using this Shapes information:

- [PySHACL](#): A Python implementation based on the RDF library [RDFlib](#)
- [Apache Jena SHACL](#): a Java implementation, based on [Apache Jena](#)
- [SHACL Playground](#): An online, JavaScript-based implementation that allows validation without local tools
- Triple Stores: SHACL validation is part of many triple store implementations:
  - [GraphDB](#)
  - [RDF4J](#)
  - [Apache Jena Fuseki](#)

Validators produce error messages and warnings based on the SHACL standard's defined reporting structure.

## D.2 Scope of SHACL Shapes provided with GeoSPARQL

The SHACL Shapes defined in the GeoSPARQL 1.1 standard all target the verification of specific graph structures, but only in very few cases validate the content of literal types. In particular, the following attributes of the graph are validated:

- **Proper usage of GeoSPARQL classes:** These Shapes check for a proper usage of instances of GeoSPARQL classes. For example, we check that instances of collection classes should at least have one element and that instances of Geometry classes should at least have one serialization to avoid creating graphs which contain nodes without necessary information.
- **Geometry property consistency:** Certain checks are applied for properties describing geometries. For example we check dimensionality properties for corresponding values.
- **Rudimentary checks of literal contents:** The SHACL Shapes defined in this standard do not substitute a verification of literal contents by validators of the respective data formats. However, they define checks using regular expressions to detect a falsely formatted geospatial literal. For example, if a GeoJSON literal is declared using its literal type, a SHACL shape will check for curly brackets to be present (as they are part of the JSON specification).

## D.3 Table of SHACL Shapes

SHACL Shape ID	Severity	Test purpose	Requirements tested
Shape 1a	Violation	Each node with an incoming <a href="#">geo:hasGeometry</a> , or a specialization of it, should have at minimum one outgoing relation that is either <a href="#">geo:hasSerialization</a> , or a specialization of it.	[ <a href="#">req_geometry-extension_feature_properties</a> ], [ <a href="#">req_geometry-extension_geometry_properties</a> ]
Shape 1b	Violation	Each node with an incoming <a href="#">geo:hasGeometry</a> , or a specialization of it, can have a maximum of one outgoing <a href="#">geo:asWKT</a> relation.	[ <a href="#">req_geometry-extension_geometry_properties</a> ] [ <a href="#">req_geometry-extension_geometry-as-wkt-literal</a> ]
Shape 1c	Violation	Each node with an incoming <a href="#">geo:hasGeometry</a> , or a specialization of it, can have a maximum of one outgoing <a href="#">geo:asGML</a> relation.	[ <a href="#">req_geometry-extension_geometry_properties</a> ] [ <a href="#">req_geometry-extension_geometry-as-gml-literal</a> ]
Shape 1d	Violation	Each node with an incoming <a href="#">geo:hasGeometry</a> , or a specialization of it, can have a maximum of one outgoing <a href="#">geo:asGeoJSON</a> relation.	[ <a href="#">req_geometry-extension_geometry_properties</a> ] [ <a href="#">req_geometry-extension_geometry-as-geojson-literal</a> ]
Shape 1e	Violation	Each node with an incoming <a href="#">geo:hasGeometry</a> , or a specialization of it, can have a maximum of one outgoing <a href="#">geo:asKML</a> relation.	[ <a href="#">req_geometry-extension_geometry_properties</a> ] [ <a href="#">req_geometry-extension_geometry-as-kml-literal</a> ]

SHACL Shape ID	Severity	Test purpose	Requirements tested
Shape 2	Violation	Each node with one or more outgoing relations that are either <a href="#">geo:hasSerialization</a> , or a specialization of it, should have at least one incoming <a href="#">geo:hasGeometry</a> relation or a specialization of it.	[req_geometry-extension_geometry-properties]
Shape 3a-c	Violation	A node that has an incoming <a href="#">geo:hasGeometry</a> property, or specialization of it, cannot have an outgoing <a href="#">geo:hasGeometry</a> property, or a specialization of, it at the same time (a <a href="#">geo:Feature</a> cannot be a <a href="#">geo:Geometry</a> at the same time)	[req_geometry-extension_feature-properties]
Shape 4	Violation	The target of a <a href="#">geo:hasSerialization</a> property, or a specialization of, it should be an RDF literal	[req_geometry-extension_geometry-properties]
Shape 5	Violation	The target of a <a href="#">geo:asWKT</a> property should be an RDF literal with datatype <a href="#">geo:wktLiteral</a>	[req_geometry-extension_wkt-literal]
Shape 6	Violation	The target of a <a href="#">geo:asGML</a> property should be an RDF literal with datatype <a href="#">geo:gmlLiteral</a>	[req_geometry-extension_gml-literal]



SHACL Shape ID	Severity	Test purpose	Requirements tested
Shape 7	Violation	The target of a <a href="#">geo:asGeoJSON</a> property should be an RDF literal with datatype <a href="#">geo:geoJSONLiteral</a>	[req_geometry-extension_geojson-literal]
Shape 8	Violation	The target of a <a href="#">geo:asKML</a> property should be an RDF literal with datatype <a href="#">geo:kmlLiteral</a>	[req_geometry-extension_kml-literal]
Shape 9	Violation	A <a href="#">geo:Geometry</a> node should have a maximum of one outgoing <a href="#">geo:coordinateDimension</a> property	[req_geometry-extension_geometry-properties]
Shape 10	Violation	A <a href="#">geo:Geometry</a> node should have a maximum of one outgoing <a href="#">geo:dimension</a> property	[req_geometry-extension_geometry-properties]
Shape 11	Violation	A <a href="#">geo:Geometry</a> node should have a maximum of one outgoing <a href="#">geo:isEmpty</a> property	[req_geometry-extension_geometry-properties]
Shape 12	Violation	A <a href="#">geo:Geometry</a> node should have a maximum one outgoing <a href="#">geo:isSimple</a> property	[req_geometry-extension_geometry-properties]
Shape 13	Violation	A <a href="#">geo:Geometry</a> node should have maximum of one outgoing <a href="#">geo:spatialDimension</a> property	[req_geometry-extension_geometry-properties]
Shape 14a	Violation	A <a href="#">geo:Geometry</a> node should have maximum of one outgoing <a href="#">geo:hasSpatialResolution</a> property	[req_geometry-extension_geometry-properties]

SHACL Shape ID	Severity	Test purpose	Requirements tested
Shape 14b	Violation	A <a href="#">geo:Geometry</a> node should have maximum of one outgoing <a href="#">geo:hasSpatialAccuracy</a> property	[req_geometry-extension_geometry-properties]
Shape 14c	Violation	A <a href="#">geo:Geometry</a> node should have maximum of one outgoing <a href="#">geo:hasMetricSpatialAccuracy</a> property	[req_geometry-extension_geometry-properties]
Shape 14d	Violation	A <a href="#">geo:Geometry</a> node should have maximum of one outgoing <a href="#">geo:hasMetricSpatialResolution</a> property	[req_geometry-extension_geometry-properties]
Shape 15	Violation	The content of an RDF literal with an incoming <a href="#">geo:asWKT</a> relation must conform to a well-formed WKT string, as defined by its official specification (Simple Features Access)	[req_geometry-extension_wkt-literal]
Shape 16	Violation	The content of an RDF literal with an incoming <a href="#">geo:asWKT</a> relation must conform to a well-formed WKT string, as defined by its official specification (Simple Features Access)	[req_geometry-extension_gml-literal]
Shape 17	Violation	The content of an RDF literal with an incoming <a href="#">geo:asGeoJSON</a> relation must conform to a well-formed GeoJSON geometry string, as defined by its official specification	[req_geometry-extension_geojson-literal]

SHACL Shape ID	Severity	Test purpose	Requirements tested
Shape 18	Violation	The content of an RDF literal with an incoming <a href="#">geo:asKML</a> relation must conform to a well-formed KML geometry XML string, as defined by its official specification	<a href="#">[req_geometry-extension_kml-literal]</a>
Shape 20	Violation	If both <a href="#">geo:dimension</a> and <a href="#">geo:coordinateDimension</a> properties are asserted, the value of <a href="#">geo:dimension</a> should be less than or equal to the value of <a href="#">geo:coordinateDimension</a>	<a href="#">[req_geometry-extension_geometry-properties]</a>
Shape 21a	Violation	An instance of <a href="#">geo:FeatureCollection</a> should have at least one outgoing <a href="#">rdfs:member</a> relation	<a href="#">[req_core_spatial-feature-collection-class]</a>
Shape 21b	Violation	An instance of <a href="#">geo:FeatureCollection</a> should only have outgoing <a href="#">rdfs:member</a> going to <a href="#">geo:Feature</a> instances	<a href="#">[req_core_spatial-feature-collection-class]</a>
Shape 22a	Violation	An instance of <a href="#">geo:GeometryCollection</a> should have at least one outgoing <a href="#">rdfs:member</a> relation	<a href="#">[req_core_spatial-geometry-collection-class]</a>
Shape 22b	Violation	An instance of <a href="#">geo:GeometryCollection</a> should only have outgoing <a href="#">rdfs:member</a> relations to <a href="#">geo:Geometry</a> instances	<a href="#">[req_core_spatial-geometry-collection-class]</a>

SHACL Shape ID	Severity	Test purpose	Requirements tested
Shape 23a	Violation	An instance of <a href="#">geo:SpatialObjectCollection</a> should have at least one outgoing <a href="#">rdfs:member</a> relation	[req_core_spatial-object-collection-class]
Shape 23b	Violation	An instance of <a href="#">geo:SpatialObjectCollection</a> should only have outgoing <a href="#">rdfs:member</a> relations going to <a href="#">geo:SpatialObject</a> instances, or subclasses of them	[req_core_spatial-object-collection-class]

# **Annex E - Alignments (informative)**

# E.0 Overview

This Annex provides alignments of GeoSPARQL to other well known ontologies that are either commonly used with GeoSPARQL or could be.

The prefixes used for the ontologies mapped to in all following sections are given in the following table.

as:	<a href="https://www.w3.org/ns/activitystreams#">https://www.w3.org/ns/activitystreams#</a>
dcterms:	<a href="http://purl.org/dc/terms/">http://purl.org/dc/terms/</a>
geo:	<a href="http://www.opengis.net/ont/geosparql#">http://www.opengis.net/ont/geosparql#</a>
geom:	<a href="http://geovocab.org/geometry#">http://geovocab.org/geometry#</a>
gn:	<a href="https://www.geonames.org/ontology#">https://www.geonames.org/ontology#</a>
juso:	<a href="http://rdfs.co/juso/">http://rdfs.co/juso/</a>
lgd:	<a href="http://linkedgeodata.org/ontology/">http://linkedgeodata.org/ontology/</a>
locn:	<a href="https://www.w3.org/ns/locn">https://www.w3.org/ns/locn</a>
obo:	<a href="http://purl.obolibrary.org/obo/">http://purl.obolibrary.org/obo/</a>
osm:	<a href="https://w3id.org/openstreetmap/terms#">https://w3id.org/openstreetmap/terms#</a>
osmm:	<a href="https://www.openstreetmap.org/meta/">https://www.openstreetmap.org/meta/</a>
osmt:	<a href="https://wiki.openstreetmap.org/wiki/Key:">https://wiki.openstreetmap.org/wiki/Key:</a>
pos:	<a href="http://www.w3.org/2003/01/geo/wgs84_pos#">http://www.w3.org/2003/01/geo/wgs84_pos#</a>
prov:	<a href="http://www.w3.org/ns/prov#">http://www.w3.org/ns/prov#</a>
rdf:	<a href="http://www.w3.org/1999/02/22-rdf-syntax-ns#">http://www.w3.org/1999/02/22-rdf-syntax-ns#</a>
rdfs:	<a href="http://www.w3.org/2000/01/rdf-schema#">http://www.w3.org/2000/01/rdf-schema#</a>
sdo:	<a href="https://schema.org">https://schema.org</a>
sosa:	<a href="http://www.w3.org/ns/sosa/">http://www.w3.org/ns/sosa/</a>
spatialuk:	<a href="http://data.ordnancesurvey.co.uk/ontology/spatialrelations/">http://data.ordnancesurvey.co.uk/ontology/spatialrelations/</a>
spatialukgeom:	<a href="http://data.ordnancesurvey.co.uk/ontology/geometry/">http://data.ordnancesurvey.co.uk/ontology/geometry/</a>
spatial:	<a href="http://geovocab.org/spatial#">http://geovocab.org/spatial#</a>
ssn:	<a href="http://www.w3.org/ns/ssn/">http://www.w3.org/ns/ssn/</a>
time:	<a href="http://www.w3.org/2006/time#">http://www.w3.org/2006/time#</a>
wdt:	<a href="http://www.wikidata.org/entity/">http://www.wikidata.org/entity/</a>

# E.1 ISA Programme Location Core Vocabulary (LOCN)

LOCN Source: <https://www.w3.org/ns/locn>

The LOCN specification provides notes on the use of GeoSPARQL literals (see <https://www.w3.org/ns/locn#changes>).

From Element	Mapping relation	To Element	Notes
<code>geo:Feature</code>	<code>rdfs:subClassOf</code>	<code>dcterms:Location</code>	LOCN states that <code>dcterms:Location</code> "represents any location, irrespective of size or other restriction". As such, it can be considered as a superclass of <code>geo:Feature</code> .
<code>locn:Address</code>	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	Although LOCN does not explicitly indicate spatial or geometry properties for <code>locn:Address</code> , this class can be considered as a specialized form of a <code>geo:Feature</code> .
<code>geo:Geometry</code>	<code>rdfs:subClassOf</code>	<code>locn:Geometry</code>	In LOCN, class <code>locn:Geometry</code> "[...] defines the notion of geometry at the conceptual level, and it shall be encoded by using different formats". More precisely, its instances can be either literals or individuals. The GeoSPARQL's class <code>geo:Geometry</code> is more narrowly defined, as its instances can only be individuals, and not literals.

From Element	Mapping relation	To Element	Notes
geo:hasGeometry	rdfs:subPropertyOf	locn:geometry	<p>In LOCN, the usage note to property <code>locn:geometry</code> states that "Depending on how a geometry is encoded, the range of this property may be one of the following: a literal [...], an instance of a geometry class [...], geocoded URIs [...]".</p> <p>The GeoSPARQL's property <code>geo:hasGeometry</code> is more narrowly defined, as it can only be used with instances of <code>geo:Geometry</code>, and not with literals.</p>



## E.2 WGS84 Geo Positioning: an RDF vocabulary (POS)

POS Source: <http://www.w3.org/2003/01/geo/>

From Element	Mapping relation	To Element	Notes
<code>geo:SpatialObject</code>	<code>owl:equivalentClass</code>	<code>pos:SpatialThing</code>	Both classes are unrestricted, essentially abstract classes
<code>pos:Point</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	Via <code>pos:Point</code> <code>rdfs:subClassOf</code> <code>pos:SpatialThing</code> but since <code>pos:Point</code> usage notes indicates direct positioning, it is a form of geometry
<code>pos:Point</code>	<code>owl:equivalentClass</code>	<code>sf:Point</code>	
<code>pos:lat_long</code>	<code>rdfs:subPropertyOf</code>	<code>geo:hasSerialization</code>	A special datatype is not indicated for use with this property by POS, unlike GeoSPARQL's <code>geo:hasSerialization</code> object literals
<code>pos:location</code>	<code>rdfs:subPropertyOf</code>	<code>geo:hasGeometry</code>	

## E.3 W3C Activity Streams Vocabulary

AS Source: <https://www.w3.org/TR/activitystreams-vocabulary/>

From Element	Mapping relation	To Element	Notes
as:Place	owl:equivalentClass	geo:Feature	AS places are only defined for point geometries
as:accuracy	rdfs:subPropertyOf	geo:hasSpatialAccuracy	AS expresses the accuracy in percent
as:altitude			The altitude property can be expressed as a Z coordinate in GeoSPARQL-compatible literals
as:latitude	rdfs:subPropertyOf	geo:hasSerialization	AS defines the range of this property as xsd:float
as:longitude	rdfs:subPropertyOf	geo:hasSerialization	AS defines the range of this property as xsd:float

## E.4 Geonames Ontology (GN)

Geonames source: <http://www.geonames.org/ontology/documentation.html>

From Element	Mapping relation	To Element	Notes
<code>gn:Feature</code>	<code>owl:equivalentClass</code>	<code>geo:Feature</code>	
<code>gn:GeonamesFeature</code>	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	The GN class is defined as "A feature described in geonames database..."
<code>geo:Feature</code>	<code>rdfs:subClassOf</code>	<code>gn:Class</code>	The GN class' definition reads "A class of features"
<code>gn:locatedIn</code>	<code>owl:equivalentProperty</code>	<code>geo:sfWithin</code>	
<code>gn:nearby</code>	<code>rdfs:subPropertyOf</code>	<code>geo:sfDisjoint</code>	A <code>gn:nearby</code> B means A is not within or touching B. The only close SF property is disjoint
<code>gn:neighbour</code>	<code>owl:equivalentProperty</code>	<code>geo:sfTouches</code>	

## E.5 NeoGeo Vocabulary

NeoGeo Source: <http://geovocab.org/> / <http://geovocab.org/doc/neogeo/>

From Element	Mapping relation	To Element	Notes
spatial:Feature	owl:equivalentClass	geo:Feature	
spatial:C	rdfs:subPropertyOf	geo:rcc8ec	Sub proerty not equivalent property since the NeoGeo property has more restrictive domain & range
spatial:DR	rdfs:subPropertyOf	geo:rcc8dc	
spatial:EC	rdfs:subPropertyOf	geo:rcc8ec	
spatial:EQ	rdfs:subPropertyOf	geo:rcc8eq	
spatial:NTPP	rdfs:subPropertyOf	geo:rcc8ntpp	
spatial:NTPPi	rdfs:subPropertyOf	geo:rcc8ntppi	
spatial:O	rdfs:subPropertyOf	geo:sfOverlaps	
spatial:P	rdfs:subPropertyOf	geo:sfWithin	
spatial:PO	rdfs:subPropertyOf	geo:rcc8po	
spatial:PP	rdfs:subPropertyOf	geo:sfWithin	
spatial:PPi	rdfs:subPropertyOf	geo:sfContains	
spatial:Pi	rdfs:subPropertyOf	geo:sfContains	
spatial:TPP	rdfs:subPropertyOf	geo:rcc8tpp	
spatial:TPPi	rdfs:subPropertyOf	geo::rcc8tppi	
geom:Geometry	owl:equivalentClass	geo:Geometry	
geom:BoundingBox	rdfs:subClassOf	geo:Geometry	GeoSPARQL doesn't have a BoundingBox class but has a generic Geometry class that is the range of the <a href="#">geo:hasBoundigBox</a> property
geom:GeometryCollection	owl:equivalentClass	geo:GeometryCollection	
geom:LineString	owl:equivalentClass	sf:LineString	
geom:LinearRing	owl:equivalentClass	sf:LinearRing	
geom:MultiLineString	owl:equivalentClass	sf:MultiLineString	
geom:MultiPoint	owl:equivalentClass	sf:MultiPoint	
geom:MultiPolygon	owl:equivalentClass	sf:MultiPolygon	
geom:Polygon	owl:equivalentClass	sf:Polygon	
geom:Point	owl:equivalentClass	sf:Point	

From Element	Mapping relation	To Element	Notes
geo:hasGeometry	rdfs:subPropertyOf	geom:geometry	geo:hasGeometry has more restrictive domain

- The **geom:bbox** property relates a Geometry to another Geometry and is thus not equivalent to GeoSPARQL's Feature-to-Geometry **geo:hasBoundingBox**.
  - An equivalent to **geo:bbox** could be made using a **geo:Feature** with a **geo:Geometry**, indicated by **geo:hasGeometry** and a second, specialised Bounding Box **geo:Geometry** indicated with **geo:hasBoundingBox**

## E.6 Juso Ontology

Juso Source: <http://rdfs.co/juso/>

Juso contains mappings to GeoSPARQL but uses `owl:sameAs` which it should instead use `owl:equivalentClass`.

From Element	Mapping relation	To Element
juso:SpatialThing	owl:equivalentClass	geo:SpatialObject
juso:Feature	owl:equivalentClass	geo:Feature
juso:Geometry	owl:equivalentClass	geo:Geometry
juso:Point	owl:equivalentClass	sf:Point
juso:geometry	owl:equivalentProperty	geo:hasGeometry
juso:parent	rdfs:subPropertyOf	geo:sfWithin
juso:political_division	rdfs:subPropertyOf	geo:sfContains
juso:within	owl:equivalentProperty	geo:sfWithin

## E.7 Time Ontology in OWL (TIME)

TIME Source: <https://www.w3.org/TR/owl-time/>

There are no direct class or property correspondences between GeoSPARQL and TIME however class patterning is similar:

- TIME uses `time:hasTime` to indicate that something has a temporal projection
- GeoSPARQL uses `geo:hasGeometry` to indicate that a `geo:Feature` has a spatial projection

and

- TIME uses properties such as `time:inXSDDate` to indicate the position of temporal entities on a temporal reference system
- GeoSPARQL uses properties such as `geo:asWKT` to indicate the position of spatial entities (Geometries) on spatial reference systems

OWL TIME sets no domain for `time:hasTime` thus this property may be used with anything, including a GeoSPARQL `geo:Feature` so that a spatio-temporal Feature may be indicated like this:

```
:flooded-area-x
  a geo:Feature ;
  geo:hasGeometry [
    a geo:Geometry ;
    geo:asWKT "POLYGON (((...)))"^^geo:wktLiteral ;
  ] ;
  time:hasTime [
    a time:ProperInterval ;
    time:hasBeginning [
      time:inXSDDate "...^^xsd:date ;
    ] ;
    time:hasEnd [
      time:inXSDDate "...^^xsd:date ;
    ] ;
  ] ;
.
```

In the above example, `:flooded-area-x` is a spatio-temporal Feature that has both a GeoSPARQL spatial projection - a `geo:Geometry` - and a temporal projection - a `time:ProperInterval` which is a specialized form of `time:TemporalEntity`.

Another possible use of TIME with GeoSPARQL is to assign temporality to individual `geo:Geometry` instances. This is allowed given `time:hasTime`'s open domain:

```
:flooded-area-x
  a geo:Feature ;
  geo:hasGeometry [
    a geo:Geometry ;
```

```
    geo:asWKT "POLYGON (((...)))"^^geo:wktLiteral ;  
    time:hasTime [ ... ] ;  
  ] ;  
.
```

In contrast to the first example, **:flooded-area-x** is inferred to be a spatio-temporal Feature but since it is the Geometry of **:flooded-area-x** that has a temporality, it is possible to describe other Geometries of **:flooded-area-x** with other temporalities.



## E.8 schema.org

schema.org Source: <https://schema.org>

From Element	Mapping relation	To Element	Notes
geo:Geometry	rdfs:subClassOf	sdo:GeoShape	A GeoShape can various literal geometry representation
sdo:GeospatialGeometry	owl:equivalentClass	geo:SpatialObject	Since <b>sdo:GeospatialGeometry</b> is the domain of SimpleFeature-like properties and a superclass of GeoShape
sdo:GeoCoordinates	rdfs:subClassOf	geo:Geometry	GoCoordinates uses direct lat, long, elevation etc properties to indicate position, not a while geometry serialization but it is nevertheless a form of a Geometry
sdo:geo	rdfs:subPropertyOf	geo:hasGeometry	
sdo:geoCoveredBy	owl:equivalentProperty	geo:ehCoveredBy	
sdo:geoCovers	owl:equivalentProperty	geo:ehCovers	
sdo:geoCrosses	owl:equivalentProperty	geo:sfCrosses	
sdo:geoDisjoint	owl:equivalentProperty	geo:sfDisjoint	
sdo:geoEquals	owl:equivalentProperty	geo:sfEquals	
sdo:geoIntersects	owl:equivalentProperty	geo:sfIntersects	
sdo:geoOverlaps	owl:equivalentProperty	geo:sfOverlaps	
sdo:geoTouches	owl:equivalentProperty	geo:sfTouches	
sdo:geoWithin	owl:equivalentProperty	geo:sfWithin	
sdo:geoMidpoint	owl:equivalentProperty	geo:hasCentroid	
sdo:Landform	rdfs:subClassOf	geo:Feature	

## E.9 Semantic Sensor Network Ontology (SSN)

SSN Source: <https://www.w3.org/TR/vocab-ssn/>

SSN and GeoSPARQL do not cover overlapping concerns directly and therefore there are no direct class or property correspondences between them, however SSN provides advice on the use of GeoSPARQL for location, see Section 7.1 (<https://www.w3.org/TR/vocab-ssn/#x7-1-location>):

GeoSPARQL ... provides a flexible and relatively complete platform for geospatial objects, that fosters interoperability between geo-datasets. To do so, these entities can be declared as instances of `geo:Feature` and geometries can be assigned to them via the `geo:hasGeometry` property. In case of classes, e.g., specific features of interests such as rivers, these can be defined as subclasses of `geo:Feature`.

## E.10 DCMI Metadata Terms (DCTERMS)

DCTERMS Source: <https://www.dublincore.org/specifications/dublin-core/dcmi-terms/>

From Element	Mapping relation	To Element	Notes
<code>geo:Feature</code>	<code>rdfs:subClassOf</code>	<code>dcterms:Location</code>	A Location is a "A spatial region or named place."
<code>geo:hasGeometry</code>	<code>rdfs:subPropertyOf</code>	<code>dcterms:spatial</code>	<code>dcterms:spatial</code> indicates the "Spatial characteristics of the resource", thus it is a more general form of GeoSPARQL's <code>geo:hasGeometry</code> which indicates geometry spatial information

- `dcterms:spatial`: "Spatial characteristics of the resource". The range of this property includes a `dcterms:Location`, so it is a property for indicating a `geo:Feature`, for which GeoSPARQL has no equivalent, but perhaps also for indicating a `geo:Geometry`, thus the `subPropertyOf` mapping above.
- `dcterms:coverage`: "The spatial or temporal topic of the resource, spatial applicability of the resource, or jurisdiction under which the resource is relevant". This is a more generic form of `dcterms:spatial` but, since there is no direct GeoSPARQL mapping for `dcterms:spatial`, there is no direct mapping for this property either.

DCTERMS-related geometry literals, such as the *DCMI Box Encoding Scheme* <sup>[1]</sup> and the *DCMI Point Encoding Scheme* <sup>[2]</sup> could be indicated as GeoSPARQL geometry literals if a literal datatype were created for each. For example, the *DCMI Point Encoding Scheme* example of "The highest point in Australia" with the literal value `east=148.26218; north=-36.45746; elevation=2228; name=Mt. Kosciusko` might be encoded in GeoSPARQL like this:

```
:mt-kosciusko
  a geo:Feature ;
  geo:hasGeometry [
    a geo:Geometry ;
    geo:hasSerialization "east=148.26218; north=-36.45746; elevation=2228;
name=Mt. Kosciusko"^^ex:dcmiPoint ;
  ] ;
.
```

[1] <https://www.dublincore.org/specifications/dublin-core/dcmi-box/>

[2] <https://www.dublincore.org/specifications/dublin-core/dcmi-point/>

## E.11 The Provenance Ontology (PROV)

PROV Source: <https://www.w3.org/TR/prov-o/>

From GeoSPARQL's point of view, PROV is an "upper" ontology - one dealing with more abstract concepts - and only one of PROV's three main classes of object - **Entity**, **Activity** & **Agent** - has direct relations to GeoSPARQL classes and that is **Entity**. This is because GeoSPARQL characterizes things - spatial objects - which are a kind of **Entity** but does not deal with events (**Activity**) or things with agency (**Agent**).

From Element	Mapping relation	To Element	Notes
<code>geo:SpatialObjectCollection</code>	<code>rdfs:subClassOf</code>	<code>prov:Collection</code>	PROV's class is a generic collection class and GeoSPARQL's property is clearly a specialized form of it that may only consist of certain class instances ( <code>geo:SpatialObject</code> )
<code>geo:SpatialObject</code>	<code>rdfs:subClassOf</code>	<code>prov:Entity</code>	All SpatialObjects fit within PROV's Entity's definition: "An entity is a physical, digital, conceptual, or other kind of thing with some fixed aspects; entities may be real or imaginary."
<code>geo:Feature</code>	<code>rdfs:subClassOf</code>	<code>prov:Location</code>	A Location "...can be an identifiable geographic place (ISO 19112), but it can also be a non-geographic place such as a directory, row, or column" so seem to be wider in scope than GeoSPARQL's Feature although a Feature could indeed be something such as a "directory, row, or column"

- The PROV property `prov:atLocation` indicates `prov:Location` instances, which may be `geo:Feature` instances, but GeoSPARQL has no property to indicate a `geo:Feature`, so no mapping is possible. Indicating features is commonly done in ontologies which use GeoSPARQL but not

within GeoSPARQL.

- Derivative relations between GeoSPARQL objects could be modelled using PROV, for instance a BoundingBox may be indicated as having been derived from a Polygon like this:

```
:bounding-box-y prov:wasDerivedFrom :polygon-x .
```

## E.12 WikiData

From Element	Mapping relation	To Element	Notes
wdt:P625	owl:equivalentProperty	geo:asWKT	The Wikidata description of this property labeled "coordinate location" note that "For Earth, please note that only WGS84 coordinating system is supported at the moment" but that is a system limit, not an ontological one
wdt:P3896	owl:propertyChainAxiom	(geo:hasGeometry geo:asGeoJSON)	This Wikidata property labeled "geoshape" indicated GeoJSON geometry literal content for a Feature, but it allows information other than just Geometry in the GeoJSON whereas GeoSPARQL does not.
wdt:P3096	owl:propertyChainAxiom	(geo:hasGeometry geo:asKML)	This Wikidata property labeled "KML File" links to a KML file which is related to the respective instance. This may not be the same representation as in GeoSPARQL, as GeoSPARQL KML literals only encode the geometry part of a KML.

From Element	Mapping relation	To Element	Notes
wd:Q82794	rdfs:subClassOf	geo:Feature	The Wikidata class is labeled "geographic region" and thus is a subclass of the more general <b>geo:Feature</b> . There are likely many other classes in Wikidata that could be interpreted as subclasses of <b>geo:Feature</b>
wd:Q618123	owl:equivalentClass	geo:Feature	The Wikidata class is labeled "geographical feature" and thus corresponds to <b>geo:Feature</b> .
wd:Q25404640	owl:equivalentClass	geo:SpatialObject	The Wikidata class is labeled "spatial object" and thus corresponds to <b>geo:SpatialObject</b> .
wdt:P150	rdfs:subPropertyOf	geo:sfContains	The Wikidata property is labeled "contains administrative territorial entity" but also alternatively labeled "contains", "has districts" and others. There are likely many other specialized forms of <b>geo:sfContains</b> and <b>geo:sfWithin</b> in Wikidata

From Element	Mapping relation	To Element	Notes
geo:sfWithin	rdfs:subPropertyOf	wdt:P361	The Wikidata property is labeled "part of" and is sometimes used to indicate Feature parthood. There are likely other parthood properties like this in Wikipedia that may also be used as superproperties of GeoSPARQL feature relations properties. The Wikidata inverse is <a href="#">wdt:Q65964571</a> "has part"
geo:sfContains	rdfs:subPropertyOf	wd:Q65964571	The property labeled "has part" is the inverse of <a href="#">wdt:P361</a> (see above)
wdt:P131	rdfs:subPropertyOf	geo:sfContains	The Wikidata property is labeled "located in the administrative territorial entity" and is essentially the inverse of <a href="#">wdt:P150</a> (described above)
wdt:P706	rdfs:subPropertyOf	geo:sfWithin	The Wikidata property is labeled "located in/on physical feature" and is indicated for use with a "(geo)physical feature" and not to be used for administrative features where <a href="#">wdt:P131</a> (see above) should be



From Element	Mapping relation	To Element	Notes
<a href="#">wdt:P4688</a>	<a href="#">rdfs:subClassOf</a>	<a href="#">geo:Feature</a>	The Wikidata class is labeled "geomorphological unit" and is one of many Wikidata feature classes that could be expressed as a subclass of <a href="#">geo:Feature</a> . More specialized geological unit examples are <a href="#">wd:Q5107</a> "continent" and <a href="#">wdt:P4552</a> "mountain range".
<a href="#">wdt:P2046</a>	<a href="#">owl:equivalentProperty</a>	<a href="#">geo:hasArea</a>	The Wikidata property is labeled "area". It indicates a microformat - NUMBER + SPACE + ALLOWED_UNIT_LABEL - with a fixed set of ALLOWED_UNIT_LABELs to present values and units of measure.

## E.13 OpenStreetMap Ontologies

There are several approaches to make OpenStreetMap data accessible in the Linked Open Data cloud.

### E.13.1 LinkedGeoData

LinkedGeoData emerged from a research project connecting OpenStreetMap representations to an ontology model. In this model, specific values of OpenStreetMap tags, e.g. the values of amenity tags are converted to `owl:Class` representations using an automated process. Every class defined in this way represented a `geo:Feature` and is linked to either a Geometry or a latitude longitude representation. Hence, every linked geodata class can be considered a `geo:Feature` in the sense of GeoSPARQL.

From Element	Mapping relation	To Element	Notes
Any LGD Class	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	Any class defined in the LinkedGeoData ontology is a subclass of <code>geo:Feature</code>

### E.13.2 OpenStreetMap RDF (Sophox)

[https://wiki.openstreetmap.org/wiki/Sophox#How\\_OSM\\_data\\_is\\_stored](https://wiki.openstreetmap.org/wiki/Sophox#How_OSM_data_is_stored)

From Element	Mapping relation	To Element	Notes
<code>osmm:loc</code>	<code>owl:equivalentProperty</code>	<code>geo:asWKT</code>	The OpenStreetMap RDF property <code>osmm:loc</code> includes WKT literals which depending on the type of the subject instance describe an OSM node or the centroid of a way or OSM relation
<code>osmm:type 'n'</code>	<code>owl:equivalentClass</code>	<code>sf:Point</code>	The OpenStreetMap RDF property <code>osmm:type</code> with value 'n' describes an OSM Node which is equivalent to a <code>sf:Point</code>
<code>osmm:type 'w'</code>	<code>owl:equivalentClass</code>	<code>sf:LineString</code>	The OpenStreetMap RDF property <code>osmm:type</code> with value 'w' describes an OSM Way which is equivalent to a <code>sf:LineString</code>

From Element	Mapping relation	To Element	Notes
<code>osmm:type 'r'</code>	<code>owl:equivalentClass</code>	<code>sf:GeometryCollection</code>	The OpenStreetMap RDF property <code>osmm:type</code> with value 'r' describes an OSM relation Way which is equivalent to a <code>sf:GeometryCollection</code>
<code>osmm:has</code>	<code>owl:equivalentProperty</code>	<code>geo:sfContains</code> , <code>geo:ehContains</code> , <code>geo:rcc8ntpp</code>	The OpenStreetMap RDF property <code>osmm:has</code> describes that a relation contains a way or that a way contains a node
<code>osmm:isClosed true</code>	<code>owl:equivalentClass</code>	<code>sf:Polygon</code>	The OpenStreetMap RDF property <code>osmm:isClosed</code> indicates whether a Way is closed, i.e. if it constitutes a Polygon
<code>osmm:isClosed false</code>	<code>owl:equivalentClass</code>	<code>sf:LineString</code>	The OpenStreetMap RDF property <code>osmm:isClosed</code> indicates whether a Way is closed, i.e. if it constitutes a Polygon

## E.13.3 Routable Tiles Ontology

<https://github.com/openplannerteam/routable-tiles-ontology>

From Element	Mapping relation	To Element	Notes
<code>osm:Element</code>	<code>owl:equivalentClass</code>	<code>geo:Geometry</code>	The class <code>osm:Element</code> is equivalent to a <code>geo:Geometry</code>
<code>osm:Node</code>	<code>owl:equivalentClass</code>	<code>sf:Point</code>	The class <code>osm:Node</code> is equivalent to a <code>sf:Point</code>
<code>osm:Way</code>	<code>owl:equivalentClass</code>	<code>sf:LineString</code>	The class <code>osm:Way</code> is equivalent to a <code>sf:LineString</code>
<code>osm:Relation</code>	<code>owl:equivalentClass</code>	<code>sf:GeometryCollection</code>	The class <code>osm:Relation</code> is equivalent to a <code>sf:GeometryCollection</code>

## E.14 Ordnance Survey UK Spatial Ontology

<http://www.ordnancesurvey.co.uk/legacy/ontologies/spatialrelations.owl>  
<http://www.ordnancesurvey.co.uk/legacy/ontologies/geometry.owl>

&

: These two ontologies will be withdrawn during 2022.

The ontology authors note: "We are pleased to have contributed to the discussion some ten years ago but recognize that the subject area has moved on. We would not recommend people starting to relate to our ontology now, and we look forward to migrating to some more authoritative one in due course."

From Element	Mapping relation	To Element	Notes
<code>spatialuk:contains</code>	<code>owl:equivalentProperty</code>	<code>geo:sfContains</code>	
<code>spatialuk:disjoint</code>	<code>owl:equivalentProperty</code>	<code>geo:sfDisjoint</code>	
<code>spatialuk:easting</code>	<code>owl:equivalentProperty</code>	-	Distance in metres east of National Grid origin
<code>spatialuk&gt;equals</code>	<code>owl:equivalentProperty</code>	<code>geo:sfEquals</code>	
<code>spatialuk:northing</code>	<code>owl:equivalentProperty</code>	-	Distance in metres north of National Grid origin
<code>spatialuk:touches</code>	<code>owl:equivalentProperty</code>	<code>geo:sfTouches</code>	
<code>spatialuk:within</code>	<code>owl:equivalentProperty</code>	<code>geo:sfWithin</code>	
<code>spatialukgeom:AbstractGeometry</code>	<code>owl:equivalentProperty</code>	<code>geo:Geometry</code>	
<code>spatialukgeom:extent</code>	<code>owl:equivalentProperty</code>	<code>geo:hasGeometry</code>	The range of <code>spatialukgeom:extent</code> is constrained to 2D geometries
<code>spatialukgeom:asGML</code>	<code>owl:equivalentProperty</code>	<code>geo:asGML</code>	The properties are equivalent, but the range of <code>spatialukgeom:asGML</code> is more general: An <code>rdf:XMLLiteral</code>

- `spatialuk:easting` describes a latitude coordinate east of the national UK grid and GeoSPARQL does not contain modelling of individual coordinate reference system elements
- `spatialuk:northing` describes a longitude coordinate north of the national UK grid so, as above, has not GeoSPARQL equivalent

## E.15 CIDOC CRM Geo

CRMGeo Source: [https://www.cidoc-crm.org/crmgeo/sites/default/files/CRMgeo1\\_2.pdf](https://www.cidoc-crm.org/crmgeo/sites/default/files/CRMgeo1_2.pdf)

From Element	Mapping relation	To Element	Notes
<code>cidoc:SP1_PhenomenalSpaceTimeVolume</code>	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	The CIDOC CRMgeo class <code>SP1_PhenomenalSpaceTimeVolume</code> is a subclass of <code>geo:Feature</code> as described in the CRMgeo 1.2 specification document.
<code>cidoc:SP2_PhenomenalPlace</code>	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	The CIDOC CRMgeo class <code>SP2_PhenomenalPlace</code> is a subclass of <code>geo:Feature</code> as described in the CRMgeo 1.2 specification document.
<code>cidoc:SP5_GeometricPlaceExpression</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	The CIDOC CRMgeo class <code>SP5_GeometricPlaceExpression</code> is a subclass of <code>geo:Geometry</code> as described in the CRMgeo 1.2 specification document.
<code>cidoc:SP6_DeclarativePlace</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	The CIDOC CRMgeo class <code>SP6_DeclarativePlace</code> is a subclass of <code>geo:Geometry</code> as described in the CRMgeo 1.2 specification document.
<code>cidoc:SP7_DeclarativePlace</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	The CIDOC CRMgeo class <code>SP7_DeclarativePlace</code> is a subclass of <code>geo:Geometry</code> as described in the CRMgeo 1.2 specification document.

From Element	Mapping relation	To Element	Notes
<code>cidoc:SP10_DeclarativeTimeSpan</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	The CIDOC CRMgeo class <code>SP10_DeclarativeTimeSpan</code> is a subclass of <code>geo:Geometry</code> as described in the CRMgeo 1.2 specification document.
<code>cidoc:SP14_TimeExpression</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	The CIDOC CRMgeo class <code>SP14_TimeExpression</code> is a subclass of <code>geo:Geometry</code> as described in the CRMgeo 1.2 specification document.
<code>cidoc:SP15_Geometry</code>	<code>rdfs:subClassOf</code>	<code>geo:Geometry</code>	The CIDOC CRMgeo class <code>SP15_Geometry</code> is a subclass of <code>geo:Geometry</code> as described in the CRMgeo 1.2 specification document.

## E.16 Basic Formal Ontology (BFO)

BFO Source: <https://basic-formal-ontology.org/bfo-2020.html>, and from there, an OWL ontology of BFO2020 at <https://github.com/BFO-ontology/BFO-2020>

From Element	Mapping relation	To Element	Notes
<code>geo:SpatialObject</code>	<code>rdfs:subClassOf</code>	<code>obo:BFO_0000004</code> "independent continuant"	BFO's "independent continuant" is the superclass of "material entity" & "immaterial entity" which are mapped to Feature & Geometry respectively, so at least some independent continuants must be Spatial Objects
<code>geo:Feature</code>	<code>owl:equivalentClass</code>	<code>obo:BFO_0000006</code> "spatial region"	BFO's "spatial region" class is described as a "spatial projection of a portion of spacetime" so Feature appears to be equivalent since Feature is "A discrete spatial phenomenon in a universe of discourse". The BFO example indicates it's for 1-, 2- & 3-D spatial regions, as Feature is.
<code>geo:Geometry</code>	<code>rdfs:subClassOf</code>	<code>obo:IAO_0000030</code> "information content entity"	BFO's "information content entity" class is described as "an entity that represents information about some other entity", so Geometry appears to be equivalent since in GeoSPARQL, Geometry gives the details of the spatial project of a Feature.
<code>obo:BFO_0000040</code> "material entity"	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	A BFO "material entity" is something that "has some portion of matter as continuant part" so some Features are such, however Features may be imaginary too
<code>obo:BFO_0000029</code> "site"	<code>rdfs:subClassOf</code>	<code>geo:Feature</code>	BFO's sites either covert the same areas as or have locations determined in relation to material entities so sites are Features but not necessarily the other way around
<code>geo:hasGeometry</code>	<code>rdfs:subPropertyOf</code>	<code>obo:BFO_0000211</code> "occupies spatial region at all times"	The BFO property links a thing that is not a spatial region to a spatial region, so it can be used as <code>geo:hasGeometry</code> is used when the thing is taken to be a <code>geo:Feature</code> and the spatial region a <code>geo:Geometry</code> . No GeoSPARQL temporality indicators mean mappings are eternal.
<code>geo:hasGeometry</code>	<code>rdfs:subPropertyOf</code>	<code>obo:BFO_0000210</code> "occupies spatial region at some time"	A transitive mapping from the mapping above. Temporal qualification can be used with GeoSPARQL, see the OWL TIME alignment.

From Element	Mapping relation	To Element	Notes
<code>geo:sfWithin</code>	<code>rdfs:subPropertyOf</code>	<code>obo:BFO_0000082</code> "located in at all times"	The BFO property "located in at all times" is a super property of <code>geo:sfWithin</code> when the thing located in the spatial region are defined to both be instances of <code>geo:Feature</code> . Since GeoSPARQL natively supplies no temporal qualifiers, pure GeoSPARQL assertions are assumed to be eternal: "...at all times"
<code>geo:sfWithin</code>	<code>rdfs:subPropertyOf</code>	<code>obo:BFO_0000171</code> "located in at some time"	A transitive mapping from the mapping above. Temporal qualification can be used with GeoSPARQL, see the OWL TIME alignment.
<code>obo:BFO_0000066</code> "occurs in"	<code>rdfs:range</code>	<code>geo:SpatialObject</code>	The BFO property relates a temporal activity to a spatial region but since GeoSPARQL has no notion of events, no mapping to this property can be made. However, BFO indicates this property should be used with a BFO "spatial region" ( <code>geo:Geometry</code> ) range value but from GeoSPARQL's point of view, it could also be used with a <code>geo:Feature</code> where the "in" would be taken to be within the feature's geometry, so the superclass of feature and geometry is given as the range
<code>obo:BFO_0000216</code> "spatially projects onto at some time"	<code>rdfs:range</code>	<code>geo:SpatialObject</code>	The reasoning is the same as for "occurs in"

- BFO distinguishes between *continuants* & *occurrants*, which *spatial region* & *spatiotemporal region* are subclasses of, respectively. GeoSPARQL has no handling of temporality, so cannot yet map to any *continuants*
  - a future version of GeoSPARQL that handled spatio-temporal Features could perhaps claim that `geo:Feature` is a `rdfs:subClassOf` `obo:BFO_0000011` "spatiotemporal region", however inconsistencies from this mapping will occur due to the current Feature/"spatial region" mapping above and this will need to be handled



# **Annex F - CQL / GeoSPARQL Mapping (informative)**

## F.0 Overview

This annex presents a mapping between the Common Query Language(CQL) [\[CQLDEF\]](#) and GeoSPARQL as well as generic SPARQL [\[SPARQL\]](#). This is likely of relevance to the delivery of GeoSPARQL data via systems such as the OGC's Web Feature Service [\[WFS\]](#) and OGC API Features [\[OGCAPIF\]](#) which implement CQL.

# F.1 Accessing spatial Features in a SPARQL endpoint

Spatial *Features* accessed via SPARQL endpoints [\[SPARQLPROT\]](#) are, as defined in the GeoSPARQL standard, instances of the OWL class `geo:Feature` or of subclasses of it. They may have one or more `geo:hasGeometry` properties indicating `geo:Geometry` instances and other properties related to the Feature. They may also be grouped into `geo:FeatureCollection` instances where `geo:FeatureCollection` is a new class in GeoSPARQL 1.1, specifically for the description of collections of `geo:Feature` instances.

The following example SPARQL query retrieves all Features within the Feature Collection with the IRI `ex:x` within a given SPARQL endpoint.

```
SELECT ?fcollection ?item ?rel ?val ?geom
WHERE {
  ex:x rdfs:member ?item .
  ?item rdfs:subClassOf* geo:Feature .
}
```

GeoSPARQL's `geo:FeatureCollection` definition requires that `geo:Feature` instances are to be linked to the Collection by use of the `rdf:member` property. No inverse property is defined.

## NOTE

Some CQL-implementing systems, such as OGC API, have fixed notions of Feature Collections and require that Features be members of exactly one Feature Collection. There is no such restriction in GeoSPARQL: Features may be members of one or more Feature Collections.

An extension to the above can retrieve any Geometry serializations for the Features within Feature Collection `ex:x`:

```
SELECT ?fcollection ?item ?rel ?val ?geom
WHERE {
  ex:x rdfs:member ?item .
  ?item rdfs:subClassOf* geo:Feature .

  OPTIONAL {
    ?item geo:hasGeometry/geo:hasSerialization ?geom
  }
}
```

Some additional concerns for GeoSPARQL / CQL or OGC API Features Feature Collections mappings are:

- APIs may need more information about the `geo:FeatureCollection` instance for correct handling, in particular, an identifier and perhaps a label. If the back-end data store also contains information for the `geo:FeatureCollection` instance then this may be queried for. If not, the API

might need to create such data

- One particular scenario observed is that OGC APIs require token-like identifiers for Feature Collections and GeoSPARQL IRIs, or their parts, may not be able to be used for such. In these cases, the RDF property `dcterms:identifier` may be used to store appropriate token-like identifiers
- Perhaps only data in a certain namespace is of interest. The solution is to apply FILTER expressions to the SPARQL query

## F.2 Mappings from CQL2 statements to GeoSPARQL queries

This section presents lists of equivalences between Common Query Language (CQL2) [\[CQLDEF\]](#) statements and GeoSPARQL statements.

### F.2.1 Query Parameters

Several query parameters may be given as parameters to the HTTP request of CD-implementing systems, such as the OGC API Features service. These parameters have an influence on the SPARQL query to be executed for the retrieval of a FeatureCollection to be exposed using an OGC API Features service.

Query Parameter	Example	SPARQL Expression	Example	Comment
limit	limit=5	LIMIT	LIMIT 5	
offset	offset=10	OFFSET	OFFSET 10	
bbox	bbox=160.6,-55.95,-170,-25.89	<code>FILTER(geo:sfIntersects())</code>	<code>FILTER(geo:sfIntersects(?geom, "POLYGON((160.6 -55.95,160.6 -25.89, -170 -25.89, -170 -55.95, 160.6 -55.95))"^^geo:wktLiteral))</code>	WKT does not define a type boundingbox, therefore a bbox is converted to a Polygon
datetime	datetime=2018-02-12T23%3A20%3A52Z	-	-	GeoSPARQL doesn't detail temporal aspects of data. Filtering data using RDF temporal properties may be achieved using basic SPARQL queries and also OWL TIME <a href="#">[TIME]</a>

### F.2.2 Literal Values

CQL2 defines literal values for a variety of datatypes. The following table shows the equivalences of these values in RDF which may be used in any GeoSPARQL query.

CQL2 literal	Examples	(Geo)SPARQL literal	Examples
String	"This is a string"	<code>xsd:string</code>	"This is a string"^^xsd:string

CQL2 literal	Examples	(Geo)SPARQL literal	Examples
Number	-100 3.14159	<code>xsd:int</code> , <code>xsd:integer</code> , <code>xsd:double</code>	<code>"-100"^^xsd:integer</code> <code>"3.14159"^^xsd:double</code>
Boolean	true false	<code>xsd:boolean</code>	<code>"true"^^xsd:boolean</code> <code>"false"^^xsd:boolean</code>
Spatial Geometry (WKT)	POINT(1 1)	<a href="#">WKT Literal</a>	<code>"POINT(1 1)"^^geo:wktLiteral</code>
Spatial Geometry (JSON)	<code>{"type": "Point", "coordinates": [1,1]}</code>	<a href="#">GeoJSON Literal</a>	<code>"{"type": "Point", "coordinates": [1,1]}"^^geo:geoJSONLiteral</code>
Temporal Literal	1969-07-20 1969-07-20T20:17:40Z	<code>xsd:date</code> , <code>xsd:dateTime</code> , <code>xsd:dateTimeStamp</code>	<code>"1969-07-20"^^xsd:date</code> <code>"1969-07-20T20:17:40Z"^^xsd:dateTime</code>

## F.2.3 Property references

CQL2 allows the referencing of properties in a Feature Collection it is targeting for filtering. A property reference is converted to a triple pattern as shown in the following example. A SPARQL variable `?item` is assumed to represent the Feature Collection.

Property Reference	Triple pattern
<code>name="OGC"</code>	<code>?item my:name "OGC"^^xsd:string</code>
<code>number=5</code>	<code>?item my:number "5"^^xsd:integer</code>
<code>number&gt;5</code>	<code>?item my:number ?number . FILTER(?number&gt;5)</code>

## F.2.4 Comparison Predicates

CQL2 defines comparison predicates to compare two scalar expressions. A comparison predicate is converted to a triple pattern as shown in the following example. A SPARQL variable `?item` is assumed to represent the Feature Collection.

Comparison predicate	Triple pattern	Comment
<code>name="OGC"</code>	<code>?item my:name "OGC"^^xsd:string</code>	Equality statements can be converted to a triple pattern
<code>number=5</code>	<code>?item my:number "5"^^xsd:integer</code>	
<code>number&gt;5</code>	<code>?item my:number ?number . FILTER(?number&gt;5)</code>	Arithmetic comparisons (<,>,>=,<=) are converted to filter expressions

Comparison predicate	Triple pattern	Comment
number BETWEEN 5 AND 10	<code>?item my:number ?number . FILTER(?number&gt;=5 &amp;&amp; ?number&lt;=10)</code>	BETWEEN statements are converted to arithmetic expressions
name IN ("OGC","W3C")	<code>?item my:name IN ("OGC", "W3C")</code>	IN statements may also be expressed using SPARQL VALUES statements
name IS NOT NULL	<code>EXISTS {?item my:name ?name }</code>	NOT NULL statements are converted to EXIST statements
name LIKE "OGC."	<code>?item my:name ?name . FILTER(regex(?name, "OGC.", "i" ))</code>	LIKE statements are converted to SPARQL regex filters
INTERSECTS(geometry1, geometry2)	<code>FILTER(geof:sfIntersects(?geom etry1,?geometry2))</code>	The INTERSECTS filter statement is converted to a GeoSPARQL FILTER statement

There is no direct GeoSPARQL equivalent to a CRS-based CQL filter, however certain GeoSPARQL geometry literals have explicit CRS/SRS information that may be filtered using SPARQL **REGEX** operators.

## F.2.5 Spatial Operators

GeoSPARQL includes equivalents of many CQL2 filter functions as can be seen in the table below.

CQL2 Filter Expression	GeoSPARQL Filter Function
CONTAINS(geometry1,geometry2)	<code>FILTER(geof:sfContains(?geometry1,?geometry2) )</code>
CROSSES(geometry1,geometry2)	<code>FILTER(geof:sfCrosses(?geometry1,?geometry2))</code>
DISJOINT(geometry1,geometry2)	<code>FILTER(geof:sfDisjoint(?geometry1,?geometry2))</code>
EQUALS(geometry1,geometry2)	<code>FILTER(geof:sfEquals(?geometry1,?geometry2))</code>
INTERSECTS(geometry1,geometry2)	<code>FILTER(geof:sfIntersects(?geometry1,?geometry 2))</code>
OVERLAPS(geometry1,geometry2)	<code>FILTER(geof:sfOverlaps(?geometry1,?geometry2 )</code>
TOUCHES(geometry1,geometry2)	<code>FILTER(geof:sfTouches(?geometry1,?geometry2))</code>
WITHIN(geometry1,geometry2)	<code>FILTER(geof:sfWithin(?geometry1,?geometry2))</code>

## F.2.6 Temporal Operators

Temporal operators are not part of the GeoSPARQL standard.

CQL2 Filter Expression	GeoSPARQL Filter Function
beginTime AFTER 1969-07-16T13:32:00Z	N/A
beginTime BEFORE 1969-07-16T13:32:00Z	N/A
beginTime BEGINS 1969-07-16T13:32:00Z	N/A
beginTime BEGUNBY 1969-07-16T13:32:00Z	N/A
beginTime DURING 1969-07-16T13:32:00Z	N/A
beginTime ENDEDBY 1969-07-16T13:32:00Z	N/A
beginTime ENDS 1969-07-16T13:32:00Z	N/A
beginTime MEETS 1969-07-16T13:32:00Z	N/A
beginTime METBY 1969-07-16T13:32:00Z	N/A
beginTime OVERLAPPEDBY 1969-07-16T13:32:00Z	N/A
beginTime TCONTAINS 1969-07-16T13:32:00Z	N/A
beginTime TEQUALS 1969-07-16T13:32:00Z	N/A
beginTime TOVERLAPS 1969-07-16T13:32:00Z	N/A

As noted above in Section [F.2.1 Query Parameters](#), temporal filtering of RDF data via SPARQL queries is possible with standard SPARQL functions to compare date values (`xsd:date`, `xsd:dateTime` and `xsd:dateTimeStamp` literals) and OWL TIME [\[TIME\]](#) may be used to assert temporal relations between objects.



## F.3 Mappings from Simple Features for SQL

The following table maps the functions and properties from Simple Features for SQL [\[OGCSFACA\]](#) [\[ISO19125-1\]](#) to GeoSPARQL.

Simple Features for SQL	GeoSPARQL Equivalent	Since GeoSPARQL	Related Property Available	Since GeoSPARQL
<b>2.1.1.1 Basic Methods on Geometry</b>				
Dimension(): Double	<code>geof:dimension</code>	-	<code>geo:dimension</code>	1.0
GeometryType(): Integer	Class of geometry instance	1.0	N/A	-
SRID(): Integer	<code>geof:getSRID</code>	1.0	N/A	-
Envelope(): Geometry	<code>geof:envelope</code>	1.0	<code>geo:hasBoundingBox</code>	1.1
AsText(): String	<code>geof:asWKT</code>	1.1	<code>geo:asWKT</code>	1.0
AsBinary(): Binary	N/A	-	N/A	-
IsEmpty(): Integer	<code>geof:isEmpty</code>	-	<code>geo:isEmpty</code>	1.0
IsSimple(): Integer	<code>geof:isEmpty</code>	-	<code>geo:isSimple</code>	1.0
Boundary(): Geometry	<code>geof:boundary</code>	1.0	N/A	-
<b>2.1.1.2 Spatial Relations</b>				
Equals(anotherGeometry: Geometry): Integer	<code>geof:sfEquals</code>	1.0	<code>geo:sfEquals</code>	1.0
Disjoint(anotherGeometry: Geometry): Integer	<code>geof:sfDisjoint</code>	1.0	<code>geo:sfDisjoint</code>	1.0
Intersects(anotherGeometry: Geometry): Integer	<code>geof:sfIntersects</code>	1.0	<code>geo:sfIntersects</code>	1.0
Touches(anotherGeometry: Geometry): Integer	<code>geof:sfTouches</code>	1.0	<code>geo:sfTouches</code>	1.0

Simple Features for SQL	GeoSPARQL Equivalent	Since GeoSPARQL	Related Property Available	Since GeoSPARQL
Crosses(anotherGeometry: Geometry): Integer	<a href="#">geof:sfCrosses</a>	1.0	<a href="#">geo:sfCrosses</a>	1.0
Within(anotherGeometry: Geometry): Integer	<a href="#">geof:sfWithin</a>	1.0	<a href="#">geo:sfWithin</a>	1.0
Contains(anotherGeometry: Geometry): Integer	<a href="#">geof:sfContains</a>	1.0	<a href="#">geo:sfContains</a>	1.0
Overlaps(anotherGeometry: Geometry): Integer	<a href="#">geof:sfOverlaps</a>	1.0	<a href="#">geo:sfOverlaps</a>	1.0
Relate(anotherGeometry: Geometry, IntersectionPatternMatrix: String): Integer	<a href="#">geof:relate</a>	1.0	N/A	-
<b>2.1.1.3 Spatial Analysis</b>				
Buffer(distance: Double): Geometry	<a href="#">geof:buffer</a>	1.0	N/A	-
ConvexHull(): Geometry	<a href="#">geof:convexHull</a>	1.0	N/A	-
Intersection(anotherGeometry: Geometry): Geometry	<a href="#">geof:intersection</a>	1.0	N/A	-
Union(anotherGeometry: Geometry): Geometry	<a href="#">geof:union</a>	1.0	N/A	-
Difference(anotherGeometry: Geometry): Geometry	<a href="#">geof:difference</a>	1.0	N/A	-
SymDifference(anotherGeometry: Geometry): Geometry	<a href="#">geof:symDifference</a>	1.0	N/A	-

Simple Features for SQL	GeoSPARQL Equivalent	Since GeoSPARQL	Related Property Available	Since GeoSPARQL
<b>2.1.2.1 GeometryCollection</b>				
NumGeometries(): Integer	geof:numGeometries	-	N/A	-
GeometryN(N: Integer): Geometry	geof:geometryN	-	N/A	-
<b>2.1.3.1 Point</b>				
X(): Double	N/A	-	N/A	-
Y(): Double	N/A	-	N/A	-
Z(): Double (not in the SQL spec, but a logical extension)	N/A	-	N/A	-
M(): Double (not in the SQL spec, but a logical extension)	N/A	-	N/A	-
<b>2.1.5.1 Curve</b>				
Length(): Double	geof:length	-	geo:hasLength	1.1
StartPoint(): Point	N/A	-	N/A	-
EndPoint(): Point	N/A	-	N/A	-
IsClosed(): Integer	N/A	-	N/A	-
IsRing(): Integer	N/A	-	N/A	-
<b>2.1.6.1 LineString</b>				
NumPoints(): Integer	N/A	-	N/A	-
PointN(N: Integer): Point	N/A	-	N/A	-
<b>2.1.7.1 MultiCurve</b>				
IsClosed(): Integer	N/A	-	N/A	-
Length(): Double	geof:length	-	geo:hasLength	1.1
<b>2.1.9.1 Surface</b>				
Area(): Double	geof:area	-	geo:hasArea	1.1
Centroid(): Point	geof:centroid	1.1	geo:hasCentroid	1.1
PointOnSurface(): Point	N/A	-	N/A	-
<b>2.1.10.1 Polygon</b>				

Simple Features for SQL	GeoSPARQL Equivalent	Since GeoSPARQL	Related Property Available	Since GeoSPARQL
ExteriorRing(): LineString	N/A	-	N/A	-
NumInteriorRing(): Integer	N/A	-	N/A	-
InteriorRingN(N: Integer): LineString	N/A	-	N/A	-
<b>2.1.11.1 MultiSurface</b>				
Area(): Double	geof:area	-	geo:hasArea	1.1
Centroid(): Point	geof:centroid	1.1	geo:hasCentroid	1.1
PointOnSurface(): Point	N/A	-	N/A	-

# Annex G - Revision History

Date	Release	Author	Paragraph modified	Description
27 Oct. 2009	Draft	Matthew Perry	Clause 6	Technical Draft
11 Nov. 2009	Draft	John R. Herring	All	Creation
06 Jan. 2010	Draft	John R. Herring	All	Comment responses
30 March 2010	Draft	Matthew Perry	All	Comment responses
26 Oct. 2010	Draft	Matthew Perry	All	Revision based on working group discussion
28 Jan. 2011	Draft	Matthew Perry	All	Revision based on working group discussion
18 April 2011	Draft	Matthew Perry	All	Restructure with multiple conformance classes
02 May 2011	Draft	Matthew Perry	Clause 6 and Clause 8	Move Geometry Class from core to geometryExtension
05 May 2011	Draft	Matthew Perry	All	Update URIs
13 Jan. 2012	Draft	Matthew Perry	All	Revision based on Public RFC
16 April 2012	Draft	Matthew Perry	All	Revision based on adoption vote comments
19 July 2012	1.0	Matthew Perry	All	Revision of URIs based on OGC Naming Authority recommendations
09 Oct. 2020	1.1 Draft	Joseph Abhayaratna	All	Establishment of the 1.1 Specification

<b>Date</b>	<b>Release</b>	<b>Author</b>	<b>Paragraph modified</b>	<b>Description</b>
10 Oct. 2020  to  02 June. 2022	1.1 Draft	GeoSPARQL 1.1 SWG	All	Addition of GeoSPARQL 1.1 elements

# Bibliography

- Clementini, Eliseo; Di Felice, Paolino and van Oosterom, Peter, *A small set of formal topological relationships suitable for end-user interaction* (1993). In Abel, David; Ooi, Beng Chin (eds.). *Advances in Spatial Databases: Third International Symposium, SSD '93 Singapore, June 23–25, 1993 Proceedings*. Lecture Notes in Computer Science. 692/1993. Springer. pp. 277–295. [doi:10.1007/3-540-56869-7\\_16](https://doi.org/10.1007/3-540-56869-7_16)
- [QUAL] Cohn, Anthony G.; Brandon Bennett; John Gooday; Nicholas Mark Gotts, *Qualitative Spatial Representation and Reasoning with the Region Connection Calculus*, *GeoInformatica*, 1, 275–316 (1997) <https://doi.org/10.1023/A:1009712514511>
- [FORMAL] Egenhofer, M. *A Formal Definition of Binary Topological Relationships* (1989). In: Litwin, W. and Schek, H.J., Eds., *Proceedings of the 3rd International Conference on Foundations of Data Organization and Algorithms (FODO)*, Paris, France, Lecture Notes in Computer Science, 367, (Springer-Verlag, New York, 1989) 457–472. (1989)
- [CATEG] Egenhofer, Max and J. Herring *Categorizing Binary Topological Relations Between Regions, Lines, and Points* (1990). *Geographic Databases*, Technical Report, Department of Surveying Engineering, University of Maine
- [AUSPIX] Geoscience Australia, *AusPIX: An Australian Government implimentation of the rHEALPix DGGS in Python* (2020). [https://github.com/GeoscienceAustralia/AusPIX\\_DGGS](https://github.com/GeoscienceAustralia/AusPIX_DGGS)
- [ISO13249] International Organization for Standardization/International Electrotechnical Commission 13249-3, *ISO/IEC 13249-3: Information technology — Database languages — SQL multimedia and application packages — Part 3: Spatial* (2000)
- [ISO19105] International Organization for Standardization, *ISO 19105: Geographic information — Conformance and testing* (2000)
- [ISO19107] International Organization for Standardization, *ISO 19107: Geographic information — Spatial schema* (2018)
- [ISO19109] International Organization for Standardization, *ISO 19109: Geographic information — Rules for application schemas* (2005)
- [ISO19125-1] International Organization for Standardization, *ISO 19125-1: Geographic information — Simple Feature Access - Part 1: Common Architecture* (2004)
- [ISO19156] International Organization for Standardization, *ISO 19156: Geographic information — Observations and measurements* (2011).
- [IETF3987] Internet Engineering Task Force, *RFC 3987: Internationalized Resource Identifiers (IRIs)*. IETF Request for Comment (January 2005). <https://tools.ietf.org/html/rfc3987>
- [IETF5234] Internet Engineering Task Force, *RFC 5234: Internet Standard 68: Augmented BNF for Syntax Specifications: ABNF*. IETF Request for Comment (2008) <https://tools.ietf.org/html/std68>
- [GEOJSON] Internet Engineering Task Force, *RFC 7946: The GeoJSON Format*. IETF Request for Comment (August 2016). <https://tools.ietf.org/html/rfc7946>
- [OGC07-036] Open Geospatial Consortium, *OGC 07-036r1: OpenGIS Geography Markup Language (GML) Encoding Standard - with corrigendum*, Version 3.2.2 (05 December 2016). <https://www.ogc.org/standards/gml>

- [OGCKML] Open Geospatial Consortium, *OGC KML 2.3*. OGC Implementation Standard (04 August 2015). <http://www.opengis.net/doc/IS/kml/2.3>
- [OGCOM] Open Geospatial Consortium, *OGC Observations and Measurements 2.0*. OGC Abstract Specification (17 September 2013). <http://www.opengis.net/doc/as/om/2.0>
- [OGCSFACA] Open Geospatial Consortium, *OGC 06-103r4 OpenGIS® Implementation Standard for Geographic information - Simple feature access - Part 1: Common architecture*. <http://www.opengis.net/doc/is/sfa/1.2.1>
- [CHARTER] Open Geospatial Consortium, *OGC GeoSPARQL SWG Charter*, OGC Working Group Charter (25 August 2020). [https://github.com/opengeospatial/ogc-geosparql/blob/master/charter/swg\\_charter.pdf](https://github.com/opengeospatial/ogc-geosparql/blob/master/charter/swg_charter.pdf)
- Open Geospatial Consortium, *OGC API - Features - Part 1: Core*. OGC Implementation Standard (14 October 2019). <http://www.opengis.net/doc/IS/ogcapi-features-1/1.0>
- [DGGSAS] Open Geospatial Consortium, *Abstract Standard Topic 21 - Discrete Global Grid Systems - Part 1 Core Reference system and Operations and Equal Area Earth Reference System*, Open Geospatial Consortium Standard (2021) <http://www.opengis.net/doc/AS/dggs/2.0>
- Open Geospatial Consortium, *OGC API - Features - Part 3: Filtering and the Common Query Language (CQL2)* (2021) <http://www.opengis.net/doc/IS/ogcapi-features-3/1.0>
- [WFS] Open Geospatial Consortium, *OpenGIS Web Feature Service 2.0 Interface Standard* (2010). OGC Implementation Standard (2 November 2010). <http://www.opengeospatial.org/standards/wfs>
- [LOGIC] Randell, D. A., Cui, Z. and Cohn, A. G.: A spatial logic based on regions and connection, Proc. 3rd Int. Conf. on Knowledge Representation and Reasoning, Morgan Kaufmann, San Mateo, pp. 165–176 (1992)
- [XSD1] World Wide Web Consortium, *XML Schema Part 1: Structures (Second Edition)*, W3C Recommendation (28 October 2004). <https://www.w3.org/TR/xmlschema-1/>
- [XSD2] World Wide Web Consortium, *XML Schema Part 2: Datatypes (Second Edition)*, W3C Recommendation (28 October 2004). <https://www.w3.org/TR/xmlschema-2/>
- [XML] World Wide Web Consortium, *Extensible Markup Language (XML) 1.0 (Fifth Edition)*, W3C Recommendation (26 November 2008). <http://www.w3.org/TR/xml/>
- [SKOS] World Wide Web Consortium, *SKOS Simple Knowledge Organization System Reference*, W3C Recommendation (18 August 2009). <https://www.w3.org/TR/skos-reference/>
- [XMLNS] World Wide Web Consortium, *Namespaces in XML 1.0 (Third Edition)*, W3C Recommendation (8 December 2009). <https://www.w3.org/TR/xml-names/>
- [OWL2] World Wide Web Consortium, *OWL 2 Web Ontology Language Document Overview (Second Edition)*, W3C Recommendation (11 December 2012). <https://www.w3.org/TR/owl2-overview/>
- [TIME] World Wide Web Consortium, *Time Ontology in OWL*, W3C Candidate Recommendation (26 March 2020). <https://www.w3.org/TR/owl-time/>
- [RIF] World Wide Web Consortium, *RIF Overview (Second Edition)*, W3C Working Group Note (5 February 2013). <https://www.w3.org/TR/rif-overview/>
- [RIFCORE] World Wide Web Consortium, *RIF Core Dialect (Second Edition)*, W3C



Recommendation (5 February 2013) <http://www.w3.org/TR/rif-core/>

- [SPARQL] World Wide Web Consortium, *SPARQL 1.1 Query Language*, W3C Recommendation (21 March 2013). <https://www.w3.org/TR/sparql11-query/>
- [SPARQLENT] World Wide Web Consortium, *SPARQL 1.1 Entailment Regimes*, W3C Recommendation (21 March 2013). <https://www.w3.org/TR/sparql11-entailment/>
- [SPARQLPROT] World Wide Web Consortium, *SPARQL 1.1 Protocol*, W3C Recommendation (21 March 2013) <http://www.w3.org/TR/sparql11-protocol/>
- [SPARQLRESX] World Wide Web Consortium, *SPARQL Query Results XML Format (Second Edition)*, W3C Recommendation (21 March 2013). <https://www.w3.org/TR/rdf-sparql-XMLres/>
- [SPARQLRESJ] World Wide Web Consortium, *SPARQL 1.1 Query Results JSON Format*, W3C Recommendation (21 March 2013). <http://www.w3.org/TR/sparql11-results-json/>
- [TURTLE] World Wide Web Consortium, *RDF 1.1 Turtle - Terse RDF Triple Language*, W3C Recommendation (25 February 2014). <https://www.w3.org/TR/turtle/>
- [RDFXML] World Wide Web Consortium, *RDF 1.1 XML Syntax*, W3C Recommendation (25 February 2014). <https://www.w3.org/TR/rdf-syntax-grammar/>
- [RDF] World Wide Web Consortium, *RDF 1.1 Concepts and Abstract Syntax*, W3C Recommendation (25 February 2014). <https://www.w3.org/TR/rdf11-concepts/>
- [RDFSEM] World Wide Web Consortium, *RDF 1.1 Semantics*, W3C Recommendation (25 February 2014). <https://www.w3.org/TR/rdf11-mt/>
- [RDFS] World Wide Web Consortium, *RDF Schema 1.1*, W3C Recommendation (25 February 2014). <https://www.w3.org/TR/rdf-schema/>
- [SHACL] World Wide Web Consortium, *Shapes Constraint Language (SHACL)*, W3C Recommendation (20 July 2017). <https://www.w3.org/TR/shacl/>
- [PROF] World Wide Web Consortium, *The Profiles Vocabulary*, W3C Working Group Note (18 December 2019). <https://www.w3.org/TR/dx-prof/>
- [JSON-LD] World Wide Web Consortium, *JSON-LD 1.1: A JSON-based Serialization for Linked Data*, W3C Recommendation (16 July 2020). <https://www.w3.org/TR/json-ld11/>
- [SPARQLSERVDESC] World Wide Web Consortium, *SPARQL 1.1 Service Description*, W3C Recommendation (21 March 2013). <https://www.w3.org/TR/sparql11-service-description/>