#### **OGC® DOCUMENT: 25-014**

**External identifier of this OGC® document:** http://www.opengis.net/doc/IS/ogcapiedr-3/1.0



## OGC API -ENVIRONMENTAL DATA RETRIEVAL STANDARD - PART 3: PROFILES

STANDARD Implementation

**DRAFT** 

Version: 1.0

Submission Date: 2025-05-11 Approval Date: 2029-03-30 Publication Date: 2029-03-30

Editor: Mark Burgoyne, Charles Heazel

**Notice for Drafts:** This document is not an OGC Standard. This document is distributed for review and comment. This document is subject to change without notice and may not be referred to as an OGC Standard.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.



#### License Agreement

Use of this document is subject to the license agreement at <a href="https://www.ogc.org/license">https://www.ogc.org/license</a>

Suggested additions, changes and comments on this document are welcome and encouraged. Such suggestions may be submitted using the online change request form on OGC web site: <a href="http://ogc.standardstracker.org/">http://ogc.standardstracker.org/</a>

#### Copyright notice

Copyright © 2025 Open Geospatial Consortium To obtain additional rights of use, visit <a href="https://www.ogc.org/legal">https://www.ogc.org/legal</a>

#### Note

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

## CONTENTS

l.	ABSTRACT	Vi
II.	KEYWORDS	vi
III.	PREFACE	vii
IV.	SECURITY CONSIDERATIONS	viii
V.	SUBMITTING ORGANIZATIONS	ix
VI.	SUBMITTERS	ix
VII.	CONTRIBUTORS	i×
	PREFACE	11
1.	SCOPE	2
2.	CONFORMANCE	4
3.	NORMATIVE REFERENCES	6
4.	TERMS AND DEFINITIONS	8
5.	CONVENTIONS	
6.	CONTEXT	14 14
7.	REQUIREMENT CLASS CORE  7.1. Documentation  7.2. Landing Page  7.3. Collections  7.4. Data Query  7.5. Parameters  7.6. Asynchronous	17 18 19 20
8.	MEDIA TYPES FOR ANY DATA ENCODING(S)	30

	ANNEX A (INFORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE  (NORMATIVE)	
	ANNEX B (INFORMATIVE) TITLE	35
	ANNEX C (INFORMATIVE) REVISION HISTORY	37
	BIBLIOGRAPHY	39
LIST	OF TABLES	
	Table C.1	37
LIST	OF RECOMMENDATIONS	
	REQUIREMENTS CLASS 1: REQUIREMENTS CLASS 'CORE'	17
	REQUIREMENT 1	17
	REQUIREMENT 2	17
	REQUIREMENT 3	18
	REQUIREMENT 4	18
	REQUIREMENT 5	19
	REQUIREMENT 6	20
	REQUIREMENT 7	20
	REQUIREMENT 8	20
	REQUIREMENT 9	21
	REQUIREMENT 10	21
	REQUIREMENT 11	22
	REQUIREMENT 12	22
	REQUIREMENT 13	23
	REQUIREMENT 14	23
	REQUIREMENT 15	23
	DEOLIDEMENT 14	24

REQUIREMENT 17	26
REQUIREMENT 18	26
REQUIREMENT 19	27
REQUIREMENT 20	27
PERMISSION 1	28
CONFORMANCE CLASS A.1	32



<Insert Abstract Text here>



#### **KEYWORDS**

The following are keywords to be used by search engines and document catalogues. ogcdoc, OGC document, API, openapi, html

## PREFACE

The aim of an OGC API EDR profile is to ensure interoperability between API implementations. To achieve this, it is essential that providers use a consistent approach when defining collections and instances of collections. An OGC EDR profile will specify a set of requirements that an API implementation must support to be a compliant implementation.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.



#### SECURITY CONSIDERATIONS

No security considerations have been made for this Standard.



#### SUBMITTING ORGANIZATIONS

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- UK Met Office
- Heazeltech



#### **SUBMITTERS**

All questions regarding this submission should be directed to the editor or the submitters:

Name Affiliation



#### **CONTRIBUTORS**

Additional contributors to this Standard include the following:

Individual name(s), Organization



## PREFACE

**NOTE:** Insert Preface Text here. Give OGC specific commentary: describe the technical content, reason for document, history of the document and precursors, and plans for future work. > Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

1 SCOPE

## 1 SCOPE

**NOTE:** Insert Scope text here. Give the subject of the document and the aspects of that scope covered by the document.

## CONFORMANCE



#### CONFORMANCE

This standard defines XXXX.

Requirements for N standardization target types are considered:

- AAAA
- BBBB

Conformance with this standard shall be checked using all the relevant tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to be achieved to claim conformance are specified in the OGC Compliance Testing Policies and Procedures and the OGC Compliance Testing web site.

In order to conform to this OGC® interface standard, a software implementation shall choose to implement:

- Any one of the conformance levels specified in Annex A (normative).
- Any one of the Distributed Computing Platform profiles specified in Annexes TBD through TBD (normative).

All requirements-classes and conformance-classes described in this document are owned by the standard(s) identified.

## NORMATIVE REFERENCES



#### NORMATIVE REFERENCES

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO: ISO 19106, *Geographic information — Profiles*. International Organization for Standardization, Geneva <a href="https://www.iso.org/standard/26011.html">https://www.iso.org/standard/26011.html</a>.

OGC API — Environmental Data Retrieval Standard

The ModSpec Model — Part 1: Core — A Standard for Designing and Writing Modular Standards

OpenAPI Initiative (OAI). **OpenAPI Specification 3.0** [online]. 2020 [viewed 2025-01-03]. The latest patch version at the time of publication of this standard was 3.0.4, available at <a href="https://spec.openapis.org/oas/v3.0.4">https://spec.openapis.org/oas/v3.0.4</a>

OpenAPI Initiative (OAI). **OpenAPI Specification 3.1** [online]. 2021 [viewed 2025-01-03]. The latest patch version at the time of publication of this standard was 3.1.1, available at <a href="https://spec.openapis.org/oas/v3.1.1">https://spec.openapis.org/oas/v3.1.1</a>

## TERMS AND DEFINITIONS



#### TERMS AND DEFINITIONS

This document uses the terms defined in <u>OGC Policy Directive 49</u>, which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word "shall" (not "must") is the verb form used to indicate a requirement to be strictly followed to conform to this document and OGC documents do not use the equivalent phrases in the ISO/IEC Directives, Part 2.

This document also uses terms defined in the OGC Standard for Modular specifications (OGC 08-131r3), also known as the 'ModSpec'. The definitions of terms such as standard, specification, requirement, and conformance test are provided in the ModSpec.

For the purposes of this document, the following additional terms and definitions apply.

This document uses the terms defined in OGC Policy Directive 49, which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word "shall" (not "must") is the verb form used to indicate a requirement to be strictly followed to conform to this standard.

For the purposes of this document, the following additional terms and definitions apply.

#### 4.1. Collection

Body of resources that belong or are used together. An aggregate, set, or group of related resources.

#### 4.2. Conformance Module; Conformance Test Module

A set of related conformance classes and their associated components.

**Note 1 to entry:** When no ambiguity is possible, the word test may be omitted. i.e. conformance test module is the same as conformance module. Conformance modules may be nested in a hierarchical way.

[**SOURCE**: OGC 08-131r5]

#### 4.3. Conformance Class; Conformance Test Class

A set of conformance tests that must be passed to receive a single certificate of conformance.

**Note 1 to entry:** When no ambiguity is possible, the word *test* may be left out, so conformance test class maybe called a conformance class.

[**SOURCE**: OGC 08-131r5]

#### 4.4. Conformance Test

A test, abstract or real, of one or more requirements contained within a standard, or set of standards.

[**SOURCE**: OGC 08-131r5]

#### 4.5. Requirement

Expression in the content of a standard conveying criteria to be fulfilled if compliance with the standard is to be claimed and from which no deviation is permitted.

[**SOURCE**: OGC 08-131r5]

#### 4.6. Requirements Class

An aggregate of requirements with a single standardization target type that must all be satisfied to pass a conformance test Class.

[**SOURCE**: OGC 08-131r5]

#### 4.7. Requirements Module

A set of related requirement classes and their associated components.

[**SOURCE**: OGC 08-131r5]

#### 4.8. Standardization Goal

A concise statement of the problem that the standard helps address and the strategy envisioned for achieving a solution. This strategy typically identifies real-world entities that need to be modified or constrained. At the abstract level, those entities are the Standardization Target Types.

[**SOURCE**: OGC 08-131r5]

#### 4.9. Standardization Target

Entity to which some requirements of a standard apply.

**Note 1 to entry:** The standardization target is the entity which may receive a certificate of conformance for a requirements class.

[**SOURCE**: OGC 08-131r5]

#### 4.10. Standardization Target Type

Type of entity or set of entities to which the requirement of a standard apply

**Note 1 to entry:** For example, the standardization target type for The OGC API – Features Standard are Web APIs. The standardization target type for the CDB Standard is "datastore". It is important to understand that a standard's root standardization target type can have sub-types, and that there can be a hierarchy of target types. For example, a Web API can have sub types of client, server, security, and so forth. As such, each requirements class can have a standardization target type that is a sub-type of the root.

[**SOURCE**: OGC 08-131r5]

## CONVENTIONS

#### **CONVENTIONS**

This sections provides details and examples for any conventions used in the document. Examples of conventions are symbols, abbreviations, use of XML schema, or special notes regarding how to read the document.

#### 5.1. Identifiers

The normative provisions in this standard are denoted by the URI

http://www.opengis.net/doc/IS/ogcapi-edr-3/1.0

All requirements and conformance tests that appear in this document are denoted by partial URIs which are relative to this base.

#### 5.1.1. Shortcuts

In the interest of readability, the following terms will be used as shorthand for more complex text:

- OGC-EDR: The term OGC-EDR will be used in this document as shorthand for the term "OGC API — Environmental Data Retrieval Standard"

## CONTEXT

## 6 CONTEXT

#### 6.1. Standardization Goal

The goal of this Standard is to ensure interoperabilty between implementations of the OGC API — Environmental Data Retrieval Standard (EDR API).

The OGC EDR Standard does not try to address every possible application domain. Rather, it provides a foundation which can be tailored for a specific domain. The result of this tailoring is a domain specific "profile" of the EDR API Standard.

A significant risk to this approach is that, in the act of profiling, interoperabilty will be compromized. This risk can be mitigated by establishing rules for how the EDR API Standard can be profiled. The goal of this Standard is to define a set of rules sufficient to ensure interoperability while retaining the adaptability needed to support domain-specific requirements.

#### 6.2. Standardization Target Type

The Standardization Target Type for this Standard is the set of standards and specifications which profile the OGC API — Environmental Data Retrieval Standard.

It is important to understand that:

- This Standard is a standard for writing standards. It does not address the EDR API implementation.
- This Standard is a profile of the OGC ModSpec Model Part 1: Core A Standard for Designing and Writing Modular Standards (ModSpec).
- Implementations of this Standard are Profiles of the OGC API Environmental Data Retrieval Standard
- The profiling model used is defined in ISO 19106:2004 Geographic information Profiles

#### 6.3. Profiles

ISO 19106:2004 Geographic information — Profiles is the ISO TC211 Standard for developing profiles of ISO TC211 Standards. This standard defined two conformance classes. These conformance classes can be thought of as two classes of profile.

- A Class 1 profile is a pure subset of the ISO geographic information standards.
- A Class 2 profile has the same basis as Class 1 but include extensions within the contexts permitted in the base standard. Additionally, a Class 2 profile permits the profiling of non-ISO geographic information standards as part of the profile.

In other words, a Class 1 profile restricts the base standard while a Class 2 profile both restricts and extends the base standard.

Both Class 1 and Class 2 Profiles of the OGC-EDR Standard are allowed.

NOTE: Consider organizing requirements based on whether they are Class 1 or Class 2.



## REQUIREMENT CLASS CORÉ

#### REQUIREMENT CLASS CORE

#### Paragraph

REQUIREMENTS CLASS 1: REQUIREMENTS CLASS 'CORE'		
IDENTIFIER	http://www.opengis.net/spec/ABCD/m.n/req/req-class-a	
TARGET TYPE	Web API	
CONFORMANCE CLASS	Conformance class A.1: http://www.opengis.net/spec/name-of-standard/1.0/conf/example1	
NORMATIVE STATEMENTS	Requirement 1-1: /req/req-class-a/req-name-1 Requirement 1-2: /req/req-class-a/req-name-2	

#### 7.1. Documentation

#### 7.1.1. Conformance to the ModSpec

## REQUIREMENT 1 IDENTIFIER /req/core/modspec A profile of the OGC API — Environmental Data Retrieval Standard SHALL be conformant to the OGC Modular Specification.

#### 7.1.2. Profile OGC API — EDR

REQ	QUIREMENT 2
IDEN	NTIFIER /req/core/edr-conformant
Α	A profile of the OGC API — Environmental Data Retrieval Standard SHALL require that a conformant implementation (standardization target) of that profile also demonstrate conformance to the OGC API — Environmental Data Retrieval Standard.

#### 7.1.3. Requirement 2

#### **REQUIREMENT 3**

IDENTIFIER /req/service-profile/conformance-test

For each of the requirements defined in the profile there SHALL be a conformance test which defines how to validate compliance with the requirement.

#### **7.1.4. Requirement 18**

#### **REQUIREMENT 4**

IDENTIFIER /req/core/status-codes

STATEMENT A Profile of the OGC-EDR Standard SHALL require that the definitions of all http status codes SHALL be provided.

These definitions SHALL provide the following:

- A description of the cause of the error.
- A JSON schema for the message body structure

#### 7.1.5. Requirements governing how links must be populated

#### 7.2. Landing Page

#### 7.2.1. Links requirements for service-doc and service-desc

#### 7.2.2. Conformance classes requirements

#### 7.2.3. Requirement 16

IDENTIFIER	/req/core/publishing
STATEMENT	An EDR profile SHALL be published as an OpenAPI JSON document.
Α	The rules described in the requirements SHALL be encoded using the OpenAPI 3.1 specification.
В	The requirement rules <i>SHALL</i> be encoded in either the OpenAPI Path Item or in the Response object schema sections of the document.
	The profile OpenAPI document SHALL describe the profile EDR API as follows:  • The servers attributes of the OpenAPI root object SHALL be blank (the profile is not linked to specific implementations)
	<ul> <li>The Extent requirement rules SHALL be encoded in the JSON schema defined in the 200 responses for the /collections and /collections/{collection} id Paths object of the profile Open API document</li> </ul>
С	<ul> <li>The data_query type requirement rules SHALL be encoded in the JSON schema defined in the 200 responses for the /collections and /collections/{collection} id Paths object of the profile OpenAPI document</li> </ul>
	<ul> <li>The data_query types SHALL be encoded as Paths objects in the OpenAPI document, where appropriate the output_format, default_output_format, crs, within_units, width-units, height- units and limit (paging) requirements SHALL be encoded in the child Parameter objects of the Paths object.</li> </ul>
	<ul> <li>The output_format requirement rules SHALL be encoded in the 200 responses of the data_ query type Paths objects</li> </ul>
	<ul> <li>The Parameter_names requirements SHALL be encoded in the JSON schema defined in the 200 responses for the /collections and /collections/{collection} id Paths object of the profile Open API document.</li> </ul>
D	An EDR API SHALL advertise the location of the profile OpenAPI document it complies with
Е	An EDR API SHALL advertise the location of the profile OpenAPI document it complies with in the links section of the API root with a link relation value of 'profile'

**NOTE:** Consider moving part 3 to a separate requirement.

#### 7.3. Collections

**REQUIREMENT 5** 

#### **7.3.1. Requirement 17**

# REQUIREMENT 6 IDENTIFIER /req/service-profile/requirements-set The profile SHALL consists of a set of requirements for a collection and (if the collection supports instances) the instances of the collection. For each of the attributes listed, if it is in the collection (or instance), there SHALL be a requirement to define it. B A profile MAY include requirements for the landing page. C A profile MAY include requirements for multiple collections.

**NOTE:** Question — what is the purpose of this requirement?

#### 7.3.2. Requirement 14

REQUIREMENT 7	
IDENTIFIER	/req/core/paging-support
STATEMENT	If a Profile of the OGC-EDR Standard is extended to support paging, then:
А	A requirement _SHALL _ be created for each combination of query pattern and output format that must support paging.
В	Each paging requirement SHALL specify the default number of items to return per page request.

#### 7.3.3. Title/Description

#### 7.4. Data Query

#### 7.4.1. Requirement 3

## REQUIREMENT 8 IDENTIFIER /req/core/data-query

REQUIREMENT 8	
STATEMENT	A Profile of the OGC-EDR Standard SHALL require definition of the supported data queries.
А	The data_queries definitions SHALL specify which data queries a service supports. This can be defined as follows:  • Enumerated list of query types
В	Each data_query type listed SHALL also have a requirement definition.

#### 7.4.2. Requirement 4

REQUIREMENT 9	
IDENTIFIER	/req/core/data-query-area
STATEMENT	If a Profile of the OGC-EDR Standard <i>restricts</i> data queries by making the Area query mandatory, then:
Α	The Profile SHALL include a requirement mandating the Area query.
В	The Area query requirement SHALL specify the following:  • Enumerated list of output_format types  • The default_output_format  • Enumerated list of crs_details values  • Enumerated list of the operations that the query supports (i.e. GET, POST)

#### 7.4.3. Requirement 5

REQUIREMENT 10	
IDENTIFIER	/req/core/data-query-corridor
STATEMENT	If a Profile of the OGC-EDR Standard <i>restricts</i> data queries by making the Corridor query mandatory, then:
Α	The Profile SHALL include a requirement mandating the Corridor query.
В	The Corridor requirement SHALL specify the following:  • Enumerated list of output_format types  • The default_output_format

#### **REQUIREMENT 10**

- Enumerated list of crs\_details values
- Enumerated list of width-units values
- Enumerated list of height-units values
- Enumerated list of the operations that the query supports (i.e. GET, POST)

#### 7.4.4. Requirement 6

REQUIREMENT 11	
/req/core/data-query-cube	
If a Profile of the OGC-EDR Standard <i>restricts</i> data queries by making the Cube query mandatory, then:	
The Profile SHALL include a requirement mandating the Cube query.	
The Cube query requirement SHALL specify the following:  • Enumerated list of output_format types  • The default_output_format  • Enumerated list of crs_details values  • Enumerated list of the operations that the query supports (i.e. GET, POST)	

#### 7.4.5. Requirement 7

#### **REQUIREMENT 12**

IDENTIFIER /req/service-profile/instances

A Instances SHALL be defined in the data\_queries enumerated list if the collection has child instances that can be queried.

**NOTE:** The purpose of this requirement is not clear.

#### 7.4.6. Requirement 8

REQUIREMENT 13	
IDENTIFIER	/req/core/position
STATEMENT	If a Profile of the OGC-EDR Standard <i>restricts</i> data queries by making the Position query mandatory, then:
Α	The Profile SHALL include a requirement mandating the Position query.
В	The Position query requirement SHALL specify the following:  • Enumerated list of output_format types  • The default_output_format  • Enumerated list of crs_details values  • Enumerated list of the operations that the query supports (i.e. GET, POST)
С	The position query requirement <i>SHALL</i> also specify the logic used in selecting the data returned by the response, i.e. exact, nearest neighbour, most representative or interpolated.

#### 7.4.7. Requirement 9

REQUIREMENT 14		
IDENTIFIER	/req/core/radius	
STATEMENT	If a Profile of the OGC-EDR Standard <i>restricts</i> data queries by making the Radius query mandatory, then:	
Α	The Profile SHALL include a requirement mandating the Radius query.	
В	The Radius query requirement SHALL specify the following:  • Enumerated list of output_format types  • The default_output_format  • Enumerated list of crs_details values  • Enumerated list of within_units values  • Enumerated list of the operations that the query supports (i.e. GET, POST)	

#### 7.4.8. Requirement 10

REQUIREMENT 15	
IDENTIFIER	/req/core/trajectory

REQUIREMENT 15		
STATEMENT	If a Profile of the OGC-EDR Standard <i>restricts</i> data queries by making the Trajectory query mandatory, then:	
Α	The Profile SHALL include a requirement mandating the Trajectory query.	
В	The Trajectory query requirement SHALL specify the following:  • Enumerated list of output_format types  • The default_output_format  • Enumerated list of crs_details values	
	<ul> <li>Enumerated list of the operations that the query supports (i.e. GET, POST)</li> </ul>	

#### 7.5. Parameters

#### **7.5.1. Requirement 15**

```
REQUIREMENT 16
IDENTIFIER /req/core/parameter-names
            If a Profile of the OGC-EDR Standard restricts the valid values and definitions of parameter_names,
STATEMENT
Α
            Requirements SHALL be defined which specify the parameter_names and their definitions.
            The parameter_names requirement definitions SHALL specify the required parameter_names objects
            in full including:
              • name,
В
                 units.
                 data type and
                 measurement duration
            for example:
            "unit": {
    "label": "Pascals",
STATEMENT
                         "symbol": {
    "value": "Pa",
                              "type": "https://qudt.org/vocab/unit/PA"
```

```
"observedProperty": {
                "id": "http://codes.wmo.int/grib2/codeflag/4.2/_0-3-1",
                "label": "MSL Pressure"
     },
"t2m": {
"+vpo
           "type": "Parameter",
"description": "Air temperature at 2m",
           "unit": {
"label": "Kelvin",
           "symbol": {
                "value": "K",
"type": "https://qudt.org/vocab/unit/K"
           },
"observedProperty": {
    "'''--'/codes.w
           "id": "http://codes.wmo.int/grib2/codeflag/4.2/0-0-0",
           "label": "Air temperature at 2m"
     },
"dd": {
"+v!
           "type": "Parameter",
           "description": "Wind Direction",
           "unit": {
                "label": "degree true",
                "symbol": {
                     "value": "°",
"type": "https://qudt.org/vocab/unit/DEG"
          },
"observedProperty": {
    "'''    "httn://cod
                "id": "http://codes.wmo.int/grib2/codeflag/4.2/0-2-0",
                "label": "Wind Direction"
           "measurementType": {
                "method": "mean",
"duration": "-PT10M"
    },
"ff": {
    "type": "Parameter",
    "description": "10m Wind Speed",
    """/s".
                "symbol": {
  "value": "ms-1",
  "type": "https://qudt.org/vocab/unit/M/s"
          },
"observedProperty": {
    "b+tn·//cod
                "id": "http://codes.wmo.int/grib2/codeflag/4.2/0-2-1",
"label": "10m Wind Speed"
           "measurementType": {
                "method": "mean"
                "duration": "-PT10M"
     }
}
```

#### **7.5.2. Requirement 11**

### IDENTIFIER /req/core/extent Α A requirement MAY be defined specifying the rules for defining the Collection extent. В An extent requirement MAY specify the minimum spatial bounds that SHALL be supported C An extent requirement MAY specify the minimum temporal bounds that SHALL be supported D An extent requirement MAY specify the minimum vertical bounds that SHALL be supported An extent requirement MAY specfiy the minimum bounds of custom extents that SHALL be Ε supported An extent requirements definition SHALL specify the rules for the spatial CRS. The attributes are constrained by one of: F Enumerated list of valid crs values Regular expression defining valid crs string patterns. If the collection has a temporal dimension an extent requirements definition SHALL specify the rules fo temporal TRS. The attributes are constrained by one of: G Enumerated list of valid trs values Regular expression defining valid trs string patterns. If the collection has a vertical dimension an extent requirements definition SHALL specify the rules for the vertical VRS. The attributes are constrained by one of: Н Enumerated list of valid vrs values Regular expression defining valid vrs string patterns. For any custom dimensions an extent requirements definition SHALL specify the rules for the custom reference systems. The attributes are constrained by one of: custom dimension name custom dimension reference value Where applicable enumerated list of valid custom dimension values STATEMENT (Regular expressions could be used to restrict reference system definitions to WKT2 or EPSG values)

**NOTE:** Needs to be re-visited

### **7.5.3. Requirement 12**

### **REQUIREMENT 18**

**REQUIREMENT 17** 

IDENTIFIER /req/core/id

### **REQUIREMENT 18**

A Requirement definition *SHALL* specify the rules that the Collection id string must follow. This can be one of the following:

Α

- identifier string
- Regular expression defining valid string patterns.

**NOTE:** This appears to duplicate /req/core/collectionid

### **7.5.4. Requirement 13**

### **REQUIREMENT 19**

IDENTIFIER /req/core/output-format

For every output\_format specified in any of the data\_query enumerated lists there SHALL be a requirement which defines the schema or structure of the data (depending on the format). Suggested definition approaches are as follows:

JSON - Link to a JSON Schema definition

### **STATEMENT**

- XML Link to a XML Schema definition
- CSV, TSV, PSV, SSV Link to a definition based on the CSV on the web recommendations available from the <u>CSV on the Web Working Group</u>.
- Other types (e.g. binary file types) Link to a description of the format

**NOTE:** Question: Where should the CSV citation point. There are multiple CSV on the Web Recommendataions.

### 7.6. Asynchronous

### 7.6.1. Requirement 1

### **REQUIREMENT 20**

**IDENTIFIER** /req/core/asynchronous

**STATEMENT** If a Profile extends the OGC-EDR Standard with support for asynchronous opperations, then:

A Requirements SHALL be defined for each query type that is asynchronous

### **REQUIREMENT 20**

- B Each asynchronous query type requirement *SHALL* define the HTTP Status Code and provide a message schema and text used to inform the user that the response is asynchronous.
- C Each asynchronous query type requirement SHALL document the mechanism for delivering the result of the asynchronous query.

### **PERMISSION 1**

IDENTIFIER /per/core/asynchronous

**STATEMENT** 

The documentation of the mechanism for delivering the result of the asynchronous query MAY be provided through a link to an external document.

8

# MEDIA TYPES FOR ANY DATA ENCODING(S)



### MEDIA TYPES FOR ANY DATA ENCODING(S)

A section describing the MIME-types to be used is mandatory for any standard involving data encodings. If no suitable MIME type exists in <a href="http://www.iana.org/assignments/media-types/">http://www.iana.org/assignments/media-types/</a> index.html then this section may be used to define a new MIME type for registration with IANA.



# ANNEX A (INFORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE (NORMATIVE)

A

# ANNEX A (INFORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE (NORMATIVE)

**NOTE:** Ensure that there is a conformance class for each requirements class and a test for each requirement (identified by requirement name and number)

### A.1. Conformance Class A

CONFORMANCE CLASS A.1				
IDENTIFIER	http://www.opengis.net/spec/name-of-standard/1.0/conf/example1			
REQUIREMENTS CLASS	Requirements class 1: http://www.opengis.net/spec/ABCD/m.n/req/req-class-a			
TARGET TYPE	Web API			
CONFORMANCE TESTS	Abstract test A.1: /conf/core/map-response Abstract test A.2: /conf/core/http			

### **A.1.1. Example 1**

ABSTRACT TEST A.1				
IDENTIFIER	/conf/core/map-response			
REQUIREMENT	Requirement 1-1: /req/req-class-a/req-name-1			
TEST PURPOSE	Verify that the implementation's response for the map retrieval operation is correct			
TEST METHOD	A single step test method can be documented as a single line.			

### **A.1.2. Example 2**

ABSTRACT TEST A.2				
IDENTIFIER	/conf/core/http			
REQUIREMENT	Requirement 1-2: /req/req-class-a/req-name-2			
TEST PURPOSE	Validate that the resource paths advertised through the API conform with HTTP 1.1 and, where appropriate, TLS.			
DESCRIPTION	Example: A sequential multi-step test method can be documented as shown here. This is the first step. This is the second step.			

В

# ANNEX B (INFORMATIVE) TITLE

В

## ANNEX B (INFORMATIVE) TITLE

**NOTE:** Place other Annex material in sequential annexes beginning with "B" and leave final two annexes for the Revision History and Bibliography



## ANNEX C (INFORMATIVE) REVISION HISTORY

### C ANNEX C (INFORMATIVE) **REVISION HISTORY**

### Table C.1

DATE	RELEASE	EDITOR	PRIMARY CLAUSES MODIFIED	DESCRIPTION
2016-04-28	0.1	G. Editor	all	initial version



### BIBLIOGRAPHY



**NOTE:** The TC has approved Springer LNCS as the official document citation type.

Springer LNCS is widely used in technical and computer science journals and other publications

- Actual References:

[n] Journal: Author Surname, A.: Title. Publication Title. Volume number, Issue number, Pages Used (Year Published)

[1] OGC: OGC Testbed 12 Annex B: Architecture (2015).