



OGC API - DISCRETE GLOBAL GRID SYSTEMS - PART 1: CORE

STANDARD
Implementation

CANDIDATE SWG DRAFT

Version: 1.0

Submission Date: 2029-03-30

Approval Date: 2029-03-30

Publication Date: 2029-03-30

Editor: Dr. Matthew Brian John Purss, Jérôme Jacovella-St-Louis

Notice for Drafts: This document is not an OGC Standard. This document is distributed for review and comment. This document is subject to change without notice and may not be referred to as an OGC Standard.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD. THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

None of the Intellectual Property or underlying information or technology may be downloaded or otherwise exported or reexported in violation of U.S. export laws and regulations. In addition, you are responsible for complying with any local laws in your jurisdiction which may impact your right to import, export or use the Intellectual Property, and you represent that you have complied with any regulations or registration procedures required by applicable law to make this license enforceable.

Suggested additions, changes and comments on this document are welcome and encouraged. Such suggestions may be submitted using the online change request form on OGC web site: http://portal.opengeospatial.org/public_ogc/change_request.php

Copyright notice

Copyright © 2024 Open Geospatial Consortium
To obtain additional rights of use, visit <http://www.ogc.org/legal/>

Note

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

CONTENTS

I.	ABSTRACT	xi
II.	KEYWORDS	xi
III.	PREFACE	xii
IV.	SECURITY CONSIDERATIONS	xiii
V.	SUBMITTING ORGANIZATIONS	xiv
VI.	SUBMITTERS	xiv
1.	SCOPE	2
2.	CONFORMANCE	4
2.1.	Requirements classes defining resources	4
2.2.	Requirements classes defining origins	5
2.3.	Requirements classes defining parameters	5
2.4.	Requirements classes defining resource representations	5
2.5.	Summary of conformance URLs	6
3.	NORMATIVE REFERENCES	10
4.	TERMS AND DEFINITIONS	13
5.	CONVENTIONS	19
5.1.	Identifiers	19
5.2.	Link relations	19
5.3.	Use of HTTPS	21
6.	REQUIREMENT CLASS “CORE”	23
6.1.	Overview	23
6.2.	Requirements	23
7.	REQUIREMENT CLASS “DATA RETRIEVAL”	28
7.1.	Overview	28
7.2.	Requirements	28
8.	REQUIREMENT CLASS “DATA SUBSETTING”	31
8.1.	Overview	31
8.2.	Requirements	31

9. REQUIREMENT CLASS “DATA CUSTOM DEPTHS”	35
9.1. Overview	35
9.2. Requirements	35
10. REQUIREMENT CLASS “ZONE QUERY”	38
10.1. Overview	38
10.2. Requirements	38
11. REQUIREMENT CLASS “FILTERING ZONE QUERIES WITH CQL2”	47
11.1. Overview	47
11.2. Requirements	47
12. REQUIREMENT CLASS “ROOT DGGS”	50
12.1. Overview	50
12.2. Requirements	50
13. REQUIREMENT CLASS “COLLECTION DGGS”	52
13.1. Overview	52
13.2. Requirements	52
14. REQUIREMENTS CLASSES FOR ENCODINGS OF ZONE DATA	54
14.1. Media Types (for zone data)	54
14.2. Requirements Class “DGGS-JSON Zone data encoding”	55
14.3. Requirements Class “DGGS-UB-JSON Zone data encoding”	60
14.4. Requirements Class “GeoTIFF Zone data encoding”	61
14.5. Requirements Class “GeoJSON Zone data encoding”	62
14.6. Requirements Class “FG-JSON Zone data encoding”	64
14.7. Requirements Class “netCDF zone data encoding”	65
14.8. Requirements Class “CoverageJSON zone data encoding”	67
14.9. Requirements Class “JPEG-XL Zone data encoding”	68
14.10. Requirements Class “PNG Zone data encoding”	69
15. REQUIREMENTS CLASSES FOR ENCODINGS OF ZONE LIST	72
15.1. Media Types (for zone list)	72
15.2. Requirements Class “JSON zone list encoding”	73
15.3. Requirements Class “HTML zone list encoding”	74
15.4. Requirements Class “Binary 64-bit integer zone list encoding”	76
15.5. Requirements Class “GeoJSON zone list encoding”	77
15.6. Requirements Class “FG-JSON zone list encoding”	78
15.7. Requirements Class “GeoTIFF zone list encoding”	79
16. REQUIREMENTS CLASS FOR API DEFINITION OPERATION IDS	83
16.1. Overview	83
16.2. Requirements	83
ANNEX A (NORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE	87

A.1. Conformance Class “Core”	87
A.2. Conformance Class “Data Retrieval”	88
A.3. Conformance Class “Zone Query”	88
A.4. Conformance Class “Filtering Zone Queries with CQL2”	88
A.5. Conformance Class “Root DGGS”	89
A.6. Conformance Class “Collection DGGS”	89
A.7. Conformance Class “Data Subsetting”	89
A.8. Conformance Class “Data Custom Depths”	90
A.9. Conformance Class “DGGS-JSON encoding for Zone Data”	90
A.10. Conformance Class “GeoJSON encoding for Zone Data”	90
A.11. Conformance Class “FG-JSON encoding for Zone Data”	91
A.12. Conformance Class “GeoTIFF encoding for Zone Data”	91
A.13. Conformance Class “netCDF encoding for Zone Data”	91
A.14. Conformance Class “CoverageJSON encoding for Zone Data”	92
A.15. Conformance Class “JPEG XL Encoding for Zone Data”	92
A.16. Conformance Class “PNG encoding for Zone Data”	93
A.17. Conformance Class “JSON encoding for Zone Data”	93
A.18. Conformance Class “HTML encoding for Zone Listing”	93
A.19. Conformance Class “Binary 64-bit integer encoding for Zone Listing”	94
A.20. Conformance Class “GeoJSON encoding for Zone Listing”	94
A.21. Conformance Class “FG-JSON encoding for Zone Listing”	94
A.22. Conformance Class “GeoTIFF encoding for Zone Listing”	95
A.23. Conformance Class “Operation IDs”	95
ANNEX B (INFORMATIVE) DISCRETE GLOBAL GRID REFERENCE SYSTEM DEFINITIONS	97
B.1. JSON Schema for defining a DGGRS	97
B.2. Example DGGRS definitions	103
ANNEX C (INFORMATIVE) EXAMPLES	111
C.1. Collection description	111
C.2. Listing available DGGRSs	112
C.3. Retrieving the description of a specific DGGRS	113
C.4. Simple zone queries	114
ANNEX D (INFORMATIVE) REVISION HISTORY	118
BIBLIOGRAPHY	120

LIST OF TABLES

Table 1 – Conformance class URIs	7
Table 2 – Media Types used for zone data encoding requirements classes	54
Table 3 – Media Types used for zone list encoding requirements classes	72

Table 4 – API operation identifier suffixes	84
Table D.1	118

LIST OF FIGURES

Figure 6 – Example encoding for DGGS-JSON	55
Figure 7 – A more complex example encoding for DGGS-JSON with more variables and additional dimensions beyond those of the DGGRS	56
Figure 8 – JSON Schema for DGGS-JSON	58
Figure 9 – JSON Schema for a DGGS Zone Query response	73
Figure B.1 – JSON Schema for the DGGRS Definition	97
Figure B.2 – DGGRS Definition for ISEA9R	103
Figure B.3 – The ISEA9R squared root rhombuses (level 0) in the rotated and sheared ISEA planar CRS mapped to a 5×6 space whose axes are aligned with the zone edges, compatible with a 2DTMS definition (imagery from NASA Earth Observatory’s Blue Marble: Next Generation)	105
Figure B.4 – The ISEA9R level 0 zone identifiers, shown in the original ISEA planar CRS (GEBCO 2014 bathymetry)	106
Figure B.5 – The ISEA9R level 1 zone identifiers, shown in the original ISEA planar CRS (GEBCO 2014 bathymetry)	106
Figure B.6 – DGGRS Definition for ISEA3H using indexing based on ISEA9R	107
Figure B.7 – The ISEA3H level 0 zones and associated identifiers (derived from ISEA9R level 0), shown on an ISEA planar projection (GEBCO 2014 bathymetry)	108
Figure B.8 – The ISEA3H level 1 zones and associated identifiers (derived from ISEA9R level 0), shown on an ISEA planar projection (GEBCO 2014 bathymetry)	109
Figure B.9 – The ISEA3H level 2 zones and associated identifiers (derived from ISEA9R level 1), shown on an ISEA planar projection (GEBCO 2014 bathymetry)	109

LIST OF RECOMMENDATIONS

REQUIREMENTS CLASS 1	23
REQUIREMENTS CLASS 2	28
REQUIREMENTS CLASS 3	31
REQUIREMENTS CLASS 4	35
REQUIREMENTS CLASS 5	38
REQUIREMENTS CLASS 6	47
REQUIREMENTS CLASS 7	50

REQUIREMENTS CLASS 8	52
REQUIREMENTS CLASS 9: REQUIREMENTS CLASS JSON ZONE DATA	58
REQUIREMENTS CLASS 10: REQUIREMENTS CLASS UB-JSON	60
REQUIREMENTS CLASS 11: REQUIREMENTS CLASS GEOTIFF DATA	61
REQUIREMENTS CLASS 12: REQUIREMENTS CLASS GEOJSON	62
REQUIREMENTS CLASS 13: REQUIREMENTS CLASS FG-JSON DATA	64
REQUIREMENTS CLASS 14: REQUIREMENTS CLASS NETCDF	65
REQUIREMENTS CLASS 15: REQUIREMENTS CLASS COVERAGEJSON DATA	67
REQUIREMENTS CLASS 16: REQUIREMENTS CLASS JPEG XL DATA	68
REQUIREMENTS CLASS 17: REQUIREMENTS CLASS PNG DATA	70
REQUIREMENTS CLASS 18: REQUIREMENTS CLASS JSON ZONE LIST	73
REQUIREMENTS CLASS 19: REQUIREMENTS CLASS HTML ZONE LIST	75
REQUIREMENTS CLASS 20: REQUIREMENTS CLASS 64-BIT BINARY ZONE LIST	76
REQUIREMENTS CLASS 21: REQUIREMENTS CLASS GEOJSON ZONE LIST	77
REQUIREMENTS CLASS 22: REQUIREMENTS CLASS FG-JSON ZONE LIST	78
REQUIREMENTS CLASS 23: REQUIREMENTS CLASS GEOTIFF ZONE LIST	80
REQUIREMENTS CLASS 24	83
REQUIREMENT 1	23
REQUIREMENT 2	24
REQUIREMENT 3	25
REQUIREMENT 4	28
REQUIREMENT 5	31
REQUIREMENT 6	32
REQUIREMENT 7	35
REQUIREMENT 8	38
REQUIREMENT 9	39
REQUIREMENT 10	40
REQUIREMENT 11	40
REQUIREMENT 12	41
REQUIREMENT 13	42
REQUIREMENT 14	43
REQUIREMENT 15	44
REQUIREMENT 16	45

REQUIREMENT 17	47
REQUIREMENT 18	50
REQUIREMENT 19	52
REQUIREMENT 20	58
REQUIREMENT 21	60
REQUIREMENT 22	61
REQUIREMENT 23	63
REQUIREMENT 24	64
REQUIREMENT 25	66
REQUIREMENT 26	67
REQUIREMENT 27	68
REQUIREMENT 28	70
REQUIREMENT 29	73
REQUIREMENT 30	75
REQUIREMENT 31	76
REQUIREMENT 32	77
REQUIREMENT 33	79
REQUIREMENT 34	80
REQUIREMENT 35	83
RECOMMENDATION 1	25
RECOMMENDATION 2	26
RECOMMENDATION 3	41
RECOMMENDATION 4	62
RECOMMENDATION 5	62
RECOMMENDATION 6	63
RECOMMENDATION 7	63
RECOMMENDATION 8	63
RECOMMENDATION 9	64
RECOMMENDATION 10	65
RECOMMENDATION 11	65
RECOMMENDATION 12	65
RECOMMENDATION 13	66
RECOMMENDATION 14	66

RECOMMENDATION 15	67
RECOMMENDATION 16	68
RECOMMENDATION 17	69
RECOMMENDATION 18	69
RECOMMENDATION 19	70
RECOMMENDATION 20	70
RECOMMENDATION 21	74
RECOMMENDATION 22	74
RECOMMENDATION 23	75
RECOMMENDATION 24	75
RECOMMENDATION 25	78
RECOMMENDATION 26	78
RECOMMENDATION 27	79
RECOMMENDATION 28	79
RECOMMENDATION 29	80
RECOMMENDATION 30	81
RECOMMENDATION 31	81
CONFORMANCE CLASS A.1	87
CONFORMANCE CLASS A.2	88
CONFORMANCE CLASS A.3	88
CONFORMANCE CLASS A.4	88
CONFORMANCE CLASS A.5	89
CONFORMANCE CLASS A.6	89
CONFORMANCE CLASS A.7	89
CONFORMANCE CLASS A.8	90
CONFORMANCE CLASS A.9	90
CONFORMANCE CLASS A.10	90
CONFORMANCE CLASS A.11	91
CONFORMANCE CLASS A.12	91
CONFORMANCE CLASS A.13	92
CONFORMANCE CLASS A.14	92
CONFORMANCE CLASS A.15	92
CONFORMANCE CLASS A.16	93

CONFORMANCE CLASS A.17	93
CONFORMANCE CLASS A.18	93
CONFORMANCE CLASS A.19	94
CONFORMANCE CLASS A.20	94
CONFORMANCE CLASS A.21	94
CONFORMANCE CLASS A.22	95
CONFORMANCE CLASS A.23	95

ABSTRACT

This specification defines building blocks which can be used as part of a Web API to retrieve geospatial data for a specific area, time and resolution of interest, based on a specific Discrete Global Grid System (DGGS) and indexing scheme, as defined in [OGC Abstract Topic 21](#), as well to query the list of DGGS zones from which data is available and/or matching a specified query, in combination with other building blocks defining queries, such as a filter defined using the [OGC Common Query Language \(CQL2\)](#).

KEYWORDS

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, API, openapi, html, ogcapi, DGGS, discrete global grid, ISEA, hexagonal grids

PREFACE

NOTE: OGC API Standards define modular API building blocks to spatially enable Web APIs in a consistent way. OGC API Standards use the OpenAPI specification for describing the API building blocks.

OGC API – Discrete Global Grid Systems provides API building blocks to retrieve data and query zones based on Discrete Global Grid Systems (DGGS) concepts defined in [OGC Abstract Topic 21](#). Additional parts for *OGC API – Discrete Global Grid Systems* may be defined in the future to provide additional capabilities.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

SECURITY CONSIDERATIONS

No security considerations have been made for this document.

SUBMITTING ORGANIZATIONS

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- Pangaea Innovations Pty. Ltd.
- Ecere Corporation
- Landcare Research New Zealand
- Peking University Collaborative Innovation Center for Geospatial Big Data
- European Commission Joint Research Centre

SUBMITTERS

All questions regarding this submission should be directed to the editors or the submitters:

Name	Affiliation
Matthew Brian John Purss (editor)	Pangaea Innovations Pty. Ltd.
Jérôme Jacovella-St-Louis (editor)	Ecere Corporation
Robert Gibb	Landcare Research New Zealand
Fuhu Ren / 任伏虎	Peking University Collaborative Innovation Center for Geospatial Big Data
Peter Strobl	European Commission Joint Research Centre

1

SCOPE

SCOPE

This OGC Standard specifies a Web API that enables the direct retrieval of geospatial data for a specified area, time and resolution of interest, based on a specific DGGS and indexing scheme and/or the query of DGGS resources to return a list of DGGS Zones from which data is available. Zone queries can include building blocks designed for geospatial queries such as a filter expressed using the [OGC Common Query Language \(CQL2\)](#).

This standard also specifies a number of encodings for retrieving both DGGS data and lists of zones, including JSON and compact binary representations.

An informative annex presents a JSON schema for describing a Discrete Global Grid Reference System (DGGRS), as well as examples of such DGGRS definitions which can be implemented in connection with this standard.

2

CONFORMANCE

CONFORMANCE

The one Standardization Target for this standard is Web APIs.

OGC API – Common provides a common foundation for OGC API Standards. Some conformance classes of this standard have a dependency on, or are designed to be easily integrated with, conformance classes defined in [OGC API – Common – Part 1](#) and/or [Part 2](#), as well as within a Web API conforming to additional OGC API Standards.

This standard identifies twenty one Conformance Classes. Each Conformance Class has an associated Requirements Class. The Requirements Classes define the functional requirements which will be tested through the associated Conformance Class. Only the Core requirements class is mandatory, all others are optional. However, a Web API with practical use needs to implement either the Data Retrieval and/or the Zone Query requirement class.

Conformance with this standard shall be checked using all the relevant tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to be achieved to claim conformance are specified in the OGC Compliance Testing Policies and Procedures and the OGC Compliance Testing web site.

In order to conform to this OGC® interface standard, a software implementation shall implement at minimum the “Core” requirements class, as well as either the “Data Retrieval” and/or the “Zone Query” requirements class, defined in Annex A (normative).

All requirements-classes and conformance-classes described in this document are owned by the standard(s) identified.

The Requirements Classes for OGC API – Discrete Global Grid Systems are:

2.1. Requirements classes defining resources

In addition to the Core requirement class defining the `../dggs`, `../dggs/{dggrsId}` and `./dggs/{dggrsId}/zones/{zoneId}` resources, either the Zone Data retrieval (`../dggs/{dggrsId}/zones/{zoneId}/data`) or Zone Query requirement classes (`../dggs/{dggrsId}/zones` with support for parameters such as `zone-level=`, `parent-zone=`, `compact-zones=`, `bbox=` and `datetime=`) need to be implemented for a DGGS API implementation to have practical use.

- **Core**
- **Zone Data Retrieval**
- **Zone Query**

2.2. Requirements classes defining origins

These requirement classes define DGGS resources for the API (/dggs) and collections (/collections/{collectionId}/dggs).

- Root DGGS
- Collection DGGS

2.3. Requirements classes defining parameters

Two requirement classes adds support for the subset and zone-depth parameters to zone data resources:

- Zone data subsetting
- Zone data custom depths

A requirement classes adds support for the filter parameter for zone query resources:

- Filtering Zone Queries with CQL2

2.4. Requirements classes defining resource representations

2.4.1. Zone data encodings

The Data Encoding Requirements Classes address support for formats commonly used for encoding geospatial data, as well as encodings based on JSON and UB-JSON using a schema specifically designed for the purpose of encoding one or more depths of zone data referenced to a DGGS, including optional support for multiple fields (properties) and additional dimensions beyond those of the DGGS.

- DGGS-JSON Data
- DGGS-UB-JSON Data
- GeoJSON Data

- FG-JSON Data
- GeoTIFF Data
- netCDF Data
- CoverageJSON Data
- JPEG XL Data
- PNG Data

2.4.2. Zone list encodings

The Zone List Encoding Requirements Classes address support for formats efficiently and/or intuitively encoding a list of DGGS zone identifiers.

- JSON Zone List
- HTML Zone List
- 64-bit Binary Zone List
- GeoJSON Zone List
- FG-JSON Zone List
- GeoTIFF Zone List

2.4.3. Operation IDs in API definitions

The *Operation IDs* Requirements Class defines requirements for using specific operation IDs in API definitions, which can be combined with requirement classes for specific API definition, such as the OpenAPI 3.0 requirement class of OGC API – Common – Part 1: Core, facilitating the identification of DGGS resources.

- Operation IDs

2.5. Summary of conformance URIs

Table 1 – Conformance class URIs

CORRESPONDING REQUIREMENTS CLASS	CONFORMANCE CLASS URI
Core	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/core
Zone Data Retrieval	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-retrieval
Zone Query	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-query
Filtering Zone Queries with CQL2	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/cql2-query
Root DGGS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/root-dggs
Collection DGGS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/collection-dggs
Data subsetting	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-subsetting
Data custom depths	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-custom-depths
DGGS-JSON Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-json
DGGS-UB-JSON Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-ubjson
GeoJSON Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-geojson
FG-JSON Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-fgjson
GeoTIFF Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-tiff
netCDF Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-netcdf
CoverageJSON Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-coveragejson
JPEG XL Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-jpegxl
PNG Data	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/data-png
JSON Zone List	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-json
HTML Zone List	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-html
64-bit Binary Zone List	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-uint64
GeoJSON Zone List	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-geojson

CORRESPONDING REQUIREMENTS CLASS	CONFORMANCE CLASS URI
FG-JSON Zone List	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-fgjson
GeoTIFF Zone List	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/zone-tiff
Operation IDs	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/conf/operation-ids

3

NORMATIVE REFERENCES

NORMATIVE REFERENCES

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Robert Gibb: OGC 20-040r3, *Topic 21 – Discrete Global Grid Systems – Part 1 Core Reference system and Operations and Equal Area Earth Reference System*. Open Geospatial Consortium (2021). <http://www.opengis.net/doc/AS/dggs/2.0>.

T. Bray (ed.): IETF RFC 8259, *The JavaScript Object Notation (JSON) Data Interchange Format*. RFC Publisher (2017). <https://www.rfc-editor.org/info/rfc8259>.

Charles Heazel: OGC 19-072, *OGC API – Common – Part 1: Core*. Open Geospatial Consortium (2023). <http://www.opengis.net/doc/is/ogcapi-common-1/1.0.0>.

Charles Heazel: *OGC API – Common – Part 2: Geospatial Data (Draft)*. OGC 20-024, Open Geospatial Consortium, <https://docs.ogc.org/DRAFTS/20-024.html>

Open API Initiative: OpenAPI Specification 3.0.3, <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.3.md>

Ben Domenico: OGC 10-090r3, *OGC Network Common Data Form (NetCDF) Core Encoding Standard version 1.0*. Open Geospatial Consortium (2011) https://portal.ogc.org/files/?artifact_id=43732

Panagiotis (Peter) A. Vretanos: *OGC Common Query Language (CQL2) (Draft)*. OGC 21-065, Open Geospatial Consortium, <https://docs.ogc.org/DRAFTS/21-065.html>

H. Butler, M. Daly, A. Doyle, S. Gillies, S. Hagen, T. Schaub: IETF RFC 7946, *The GeoJSON Format*. RFC Publisher (2016). <https://www.rfc-editor.org/info/rfc7946>.

OGC Features & Geometry JSON (Draft), <https://docs.ogc.org/DRAFTS/21-045r1.html>

Adobe Developers Association: *TIFF Specification Revision 6.0*. (1992) <https://www.itu.int/tudoc/itu-t/com16/tiff-fx/docs/tiff6.pdf>

Emmanuel Devys, Ted Habermann, Chuck Heazel, Roger Lott, Even Rouault: OGC 19-008r4, *OGC GeoTIFF Standard*. Open Geospatial Consortium (2019). <http://www.opengis.net/doc/IS/GeoTIFF/1.1.0>.

ISO/IEC: ISO/IEC 18181-1, ISO, IEC

ISO/IEC: ISO/IEC 18181-2, ISO, IEC

ISO/IEC: ISO/IEC 15948, *ISO/IEC 15948:2004, Information technology – Computer graphics and image processing – Portable Network Graphics (PNG): Functional specification*. ISO, IEC

Chris Little, Jon Blower, Maik Riechert: OGC 21-069r2, OGC CoverageJSON Community Standard. Open Geospatial Consortium (2023). <http://www.opengis.net/doc/CS/covjson/1.0>.

4

TERMS AND DEFINITIONS

TERMS AND DEFINITIONS

This document uses the terms defined in [OGC Policy Directive 49](#), which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word “shall” (not “must”) is the verb form used to indicate a requirement to be strictly followed to conform to this document and OGC documents do not use the equivalent phrases in the ISO/IEC Directives, Part 2.

This document also uses terms defined in the OGC Standard for Modular specifications ([OGC 08-131r3](#)), also known as the ‘ModSpec’. The definitions of terms such as standard, specification, requirement, and conformance test are provided in the ModSpec.

For the purposes of this document, the following additional terms and definitions apply.

4.1. child zone

immediate descendant of a parent zone

Note 1 to entry: adapted from *child cell* in OGC Abstract Specification Topic 21

[**SOURCE:** OGC 20-040r3]

4.2. discrete global grid (DGG)

set of zones at the same refinement level, that uniquely and completely cover a globe

Note 1 to entry: Adapted to use zones rather than cells to avoid potential confusion with the similar concept of grid cells in a *coverage*. As noted in OGC Abstract Specification Topic 21, “While the terms *cell* and *zone* are often used interchangeably, strictly *zone* is the preferred term.”.

[**SOURCE:** OGC 20-040r3]

4.3. discrete global grid reference system (DGGRS)

integrated system comprised of a specific discrete global grid system (a parameterized hierarchy of discrete global grids fully establishing zone geometry), spatio-temporal referencing by zonal identifiers and deterministic sub-zone ordering

Note 1 to entry: partially adapted from *discrete global grid system* in OGC Abstract Specification Topic 21

Note 2 to entry: Annex B provides an informative schema for defining a DGGRS with accompanying examples

[SOURCE: OGC 20-040r3]

4.4. discrete global grid system (DGGS)

system comprised of a hierarchy of discrete global grids organized in successive levels of zone refinement, using a specific set of parameters such as its underlying Earth model spheroid and orientation of a base polyhedron, fully establishing the geometry of all zones.

Note 1 to entry: This definition differs from the OGC Abstract Specification Topic 21 definition, following earlier DGGS literature where the term DGGS often refers strictly to a “system of discrete global grids” in the sense of a “set” of grids (e.g., “A Discrete Global Grid System (DGGS) is a series of discrete global grids” [Sahr2003]), excluding the concepts of zonal identifiers (which is re-introduced as part of a discrete global grid reference system) and excluding notions of software functionality or interoperability so as to remain purely a data structure. This definition more closely corresponds to the term DGGS “hierarchy” (4.26) in OGC Abstract Specification Topic 21.

[SOURCE: OGC 20-040r3]

4.5. globe

region of space-time enclosing a celestial body

[SOURCE: OGC 20-040r3]

4.6. parent zone

zone in a lower refinement level of a discrete global grid with immediate descendants

Note 1 to entry: adapted from *parent cell* in OGC Abstract Specification Topic 21

Note 2 to entry: Adapted to say *lower* rather than *higher*, where *lower* refers to a zone covering a larger area of space-time which would normally correspond to lower resolution data.

[SOURCE: OGC 20-040r3]

4.7. refinement level

numerical order of a discrete global grid in the tessellation sequence

Note 1 to entry: The discrete global grid with the least number of zones has a refinement level of 0.

[SOURCE: OGC 20-040r3]

4.8. relative depth

the number of refinement levels separating a finer discrete global grid from a coarser discrete global grid in a discrete global grid system

4.9. sub-zone

zone at a greater refinement level than a parent zone whose geometry is at least partially contained within the geometry of the parent zone

Note 1 to entry: At a relative depth of 1, the sub-zones of the parent zone are its immediate children.

Note 2 to entry: In some DGGSs, the children of the children of a parent zone (relative depth of 2) are not all sub-zones of that parent zone.

Note 3 to entry: A discrete global grid reference system defines a deterministic order for sub-zones

4.10. Web API

An Application Programming Interface (API) using an architectural style that is founded on the technologies of the Web

Note 1 to entry: See Best Practice 24: Use Web Standards as the foundation of APIs (W3C Data on the Web Best Practices) for more detail.

[SOURCE: OGC 19-072]

4.11. zonal identifier

spatio-temporal reference in the form of a label or code that uniquely identifies a zone

Note 1 to entry: synonym of “zone identifier” and “zone ID”.

Note 2 to entry: This standard and the DGGRS definitions described in Annex B require textual identifiers, while optionally supporting integer identifiers for the purpose of compact transmission and internal representations.

[SOURCE: OGC 20-040r3]

4.12. zonal identifier reference system (ZIRS)

reference system establishing a specific association of zone identifiers to zones for one or more discrete global grid systems

Note 1 to entry: synonym of “zone identifier reference system” and “zone indexing scheme”

4.13. zone

particular region of space-time

[SOURCE: OGC 20-040r3]

5

CONVENTIONS

CONVENTIONS

This section provides details of conventions used in this document.

5.1. Identifiers

The normative provisions in this standard are denoted by the URI <https://www.opengis.net/spec/ogcapi-dggs-1/1.0>.

All requirements and conformance tests that appear in this document are denoted by partial URLs which are relative to this base.

5.2. Link relations

To express relationships between resources, [RFC 8288 \(Web Linking\)](#) is used.

Note that the CURIE based on the pattern [ogc-rel:<relation>] is also considered equivalent. For example, [ogc-rel:dggrs-definition] corresponds to <https://www.opengis.net/def/rel/ogc/1.0/dggrs-definition>.

The following [IANA link relation types](#) are used in this document:

- **alternate**: Refers to a substitute for this context.
- **self**: Conveys an identifier for the link's context.
- **service-desc**: Identifies service description for the context that is primarily intended for consumption by machines (Web API definitions are considered service descriptions).
- **service-doc**: Identifies service documentation for the context that is primarily intended for human consumption.

The following link relation types which were previously defined for other OGC API standards are applicable:

- <https://www.opengis.net/def/rel/ogc/1.0/dataset>: The target IRI points to a resource representing the dataset (e.g., the root of an OGC Web API).
- <https://www.opengis.net/def/rel/ogc/1.0/geodata>: The target IRI points to a resource representing a collection of geospatial data.

In addition, the following link relation types are used for which no applicable registered link relation type could be identified:

- <https://www.opengis.net/def/rel/ogc/1.0/dggrs>: The target IRI points to the description, which includes a link to the definition as well as deployment-specific elements, of the Discrete Global Grid Reference System related to the link's context.
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-list>: The target IRI points to the descriptive list of the Discrete Global Grid Reference Systems available for the resource of the link's context.
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-definition>: The target IRI points to the definition of the Discrete Global Grid Reference System using a well-defined schema (see Annex B), for example as available from an authoritative DGGRS registry.
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-zone-info>: The target IRI points to information about a particular zone of a Discrete Global Grid Reference System, such as its geometry, area/volume, and any relevant links (e.g., to retrieve data from the zone).
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-zone-data>: The target IRI points to data pertaining to a particular zone of a Discrete Global Grid Reference System. This link relation is typically used with a link template where a zone identifier can be substituted.
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-zone-parent>: The target IRI points to the information resource of a zone which is a parent of the link's context zone.
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-zone-child>: The target IRI points to the information resource of a zone which is an immediate child of the link's context zone.
- <https://www.opengis.net/def/rel/ogc/1.0/dggrs-zone-neighbor>: The target IRI points to the information resource of a zone which is a neighbor of the link's context zone.

Each resource representation includes an array of links. Implementations are free to add additional links for all resources provided by the Web API implementing OGC API – DGGS requirement(s).

Used in combination OGC API – Common – Part 1: Core, other link relation types will be used, including:

- <https://www.opengis.net/def/rel/ogc/1.0/conformance>: Refers to a resource that identifies the specifications that the link's context conforms to.

Used in combination with OGC API – Common – Part 2: Geospatial Data, other link relation types will be used, including:

- <https://www.opengis.net/def/rel/ogc/1.0/data>: Refers to the list of collections available for a dataset.

5.3. Use of HTTPS

For simplicity, OGC API – DGGS only refers to the HTTP protocol. This is not meant to exclude the use of HTTPS and simply is a shorthand notation for “HTTP or HTTPS.” Following the recent push towards enhancing web security, public facing web servers are expected to use [HTTPS](#) rather than [HTTP](#). In the context of the OGC API – DGGS Standard, use of HTTPS provides a layer of security to prevent leaking of information related to users requesting dggs data or zones list for a particular geographical area, which may be private or sensitive in nature (for example, their own location, or the location of endangered species).

6

REQUIREMENT CLASS “CORE”

REQUIREMENT CLASS “CORE”

6.1. Overview

The “Core” Requirement Class allows a client to list available DGGRSs for a given resource, retrieve additional information about a particular DGGRS, and retrieve information about a particular DGGRS zone.

The “Core” Requirement Class is the only mandatory Requirements Class, but an implementation with practical use is expected to additionally implement either the “Zone Data Retrieval” Requirement Class, the “Zone Query” Requirement Class, or both.

REQUIREMENTS CLASS 1

TARGET TYPE Web API

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/core>

6.2. Requirements

6.2.1. Listing available DGGRS (.../dggs)

REQUIREMENT 1

LABEL /req/core/dggrs-list

STATEMENT For retrieving the list of available discrete global grid reference systems:

- A The Implementation SHALL support an HTTP GET operation at a resource path ending with .../dggs.
- B The Implementation SHALL support a JSON representation of this .../dggs resource.
- C The .../dggs resource SHALL include a dggrs array property listing all discrete global grid reference systems supported by the Implementation.

REQUIREMENT 1

- D Each element of the dggrs array SHALL include a subset of the information available in the individual DGGRS information described below, including at minimum the id, title, uri (if applicable), and links.
- E The links property SHALL include at minimum a link to the discrete global grid reference system using the self link relation type, as well as a link to the discrete global grid reference system using the [ogc-rel:dggrs-definition] relation type.
- F The link relation type to use for linking from the corresponding resource to the list of available DGGRSs for that resource SHALL be [ogc-rel:dggrs-list].

6.2.2. Discrete global grid reference system information (.../dggs/{dggrsId})

REQUIREMENT 2

LABEL /req/core/dggrs-info

STATEMENT For retrieving information for a particular available discrete global grid reference system:

- A The Implementation SHALL support an HTTP GET operation at a resource path ending with .../dggs/{dggrsId}.
- B The Implementation SHALL support a JSON representation of this .../dggs/{dggrsId} resource.
- C The .../dggs/{dggrsId} resource SHALL include an id property consistent with the {dggrsId} resource path parameter.
- D The .../dggs/{dggrsId} resource SHALL include a link to the resource itself using the self link relation type.
- E The .../dggs/{dggrsId} resource SHALL include a link to a definition of the discrete global grid reference system (describing both the discrete global grid as well as the particular indexing scheme to identify zones by identifiers), using the link relation type [ogc-rel:dggrs-definition]. The schema for that definition is likely to evolve in order to support describing a growing number of classes of DGGS. A first draft of this schema is available in Annex B – Discrete Global Grid Reference System Definitions.
- F The .../dggs/{dggrsId} resource SHALL include a templated link in the linkTemplates array to request information for a particular zone using the link relation type [ogc-rel:dggrs-zone-info] and the template variable {zoneId}.
- G If the discrete global grid reference system (the combination of the discrete global grid and indexing system) is registered with an authority, the resource SHALL include uri property corresponding to that registered discrete global grid reference system.
- H If the discrete global grid reference system is based on a particular coordinate reference system, the resource shall specify that CRS in a crs property, preferably as a URI (if one is available).
- I The Implementation SHALL include a short title property identifying the discrete global grid reference system intended for display to a human.

REQUIREMENT 2

- J The Implementation SHALL include a description property providing a summary description of the discrete global grid reference system.

6.2.3. Retrieving zone information (`.../dggs/{dggrsId}/zones/{zoneId}`)

REQUIREMENT 3

LABEL /req/core/zone-info

STATEMENT For retrieving information for a particular DGGRS zone:

- A The Implementation SHALL support an HTTP GET operation at a resource path ending with `.../dggs/{dggrsId}/zones/{zoneId}` providing information for a valid individual zones of the discrete global grid reference system.
- B The zone information resource SHALL support a JSON representation.
- C The zone information resource SHALL include an `id` property corresponding to the `{zoneId}` resource path parameter.
- D The zone information resource SHALL include a link back to the corresponding DGGRS resource (`.../dggs`) using the `[ogc-rel:dggrs]` link relation type.

RECOMMENDATION 1

LABEL /rec/core/zone-info

- A The zone information resource SHOULD include links to its parent(s) zone(s) using link relation `[ogc-rel:dggrs-zone-parent]`.
- B The zone information resource SHOULD include links to its immediate children zone using link relation `[ogc-rel:dggrs-zone-child]`.
- C The zone information resource SHOULD include links to its neighboring zones using link relation `[ogc-rel:dggrs-zone-neighbor]`.
- D The zone information resource SHOULD include an `areaMetersSquare` property indicating the surface area of the zone in square meters.
- E For a DGGS with three spatial dimension, the zone information resource SHOULD include a `volumeMetersCube` property indicating the volume of the zone in cubic meters.
- F For a temporal DGGS, the zone information resource SHOULD include a `temporalDurationSeconds` property indicating the amount of time covered by the zone in seconds.
- G The zone information resource SHOULD include a `geometry` property indicating the 2D and/or 3D spatial geometry of the zone using GeoJSON or OGC Features & Geometry JSON for the JSON encoding, and

RECOMMENDATION 1

including intermediate points between the vertices of the geometry so as to accurately represent the shape of the zones for DGGRSs not in CRS84.

- H For a temporal DGGS, the zone information resource SHOULD include a `temporalInterval` property indicating the start and end time of the zone.
- I The implementation SHOULD support a GeoJSON and/or OGC Features & Geometry JSON representation of the zone information resource where the top-level object is a feature representing the zone geometry, a `zoneID` property of that feature corresponds to the textual identifier (the `{zoneId}`), the `id` of the feature corresponds to either the textual identifier or the 64-bit unsigned integer identifier of the zone, and the other properties described in this recommendation are properties of that feature.
- J For a zone associated with a particular collection, the implementation SHOULD provide summary statistics (minimum, maximum, average, `stdDev`) pertaining to this zone for each field (fields of the range of a coverage, or relevant numeric properties of a feature collection) of the data. In the JSON encoding, this SHOULD be implemented as a JSON dictionary mapping field names to an object with each statistic.
- K For a zone associated with a particular collection, the implementation SHOULD provide `areaMetersSquareWithData`, `volumeMetersCubeWithData`, `temporalDurationSecondsWithData` properties corresponding to the respective properties defined above for the overall zones, but considering only the portions of the zone where there is data (e.g., regions of the zone excluding NODATA values for a gridded coverage, or within geometry for a feature collection).

RECOMMENDATION 2

LABEL /rec/core/robots-txt

- A Implementations SHOULD include a [robots.txt](#) file at the root of their Web API discouraging robots from crawling the DGGS zone resources.
- B The content of that Robots.txt file SHOULD include `Disallow: */dggs/*/zones/*` to prevent crawling all DGGS resources under the `/zones/` resource path.

NOTE: The presence of a `robots.txt` file is not a security measure and relies on the voluntary compliance of well-intended crawlers to minimize unnecessary requests. This measure does not prevent malicious clients from overwhelming the server with numerous requests which may result in Denial of Service attacks.

7

REQUIREMENT CLASS “DATA RETRIEVAL”

REQUIREMENT CLASS “DATA RETRIEVAL”

7.1. Overview

The Data Retrieval requirement class allows to retrieve data from a specific Discrete Global Grid Reference System (DGGRS), that is a specific hierarchy of Discrete Global Grids combined with a particular zone indexing reference system (ZIRS), for an individual zone. It describes an HTTP GET operation, as well as its response. The selected DGGRS is listed as available and described in the Core requirement class, and conforms to [OGC Topic 21](#).

The data for a particular zone is retrieved based on a URI template including a variable representing a Zone ID.

The resource from which data is retrieved can either be for a particular collection of geospatial data, for a dataset as a whole, or in connection with [OGC API – Processes – Part 3: Workflows & Chaining](#), the output of a processing workflow.

REQUIREMENTS CLASS 2

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-common-1/1.0/req/core>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

7.2. Requirements

7.2.1. Retrieving data from a zone (`.../dggs/{dggrsId}/zones/{zoneId}/data`)

The following requirements describe how a client can retrieve data from a single DGGS zone at the resource path `.../dggs/{dggrsId}/zones/{zoneId}/data`.

REQUIREMENT 4

LABEL /req/data-retrieval/zone-data

REQUIREMENT 4

STATEMENT For retrieving data for a single DGGS zone:

- A The operation SHALL support an HTTP GET operation at a resource path ending with .../dggs/{dggrsId}/zones/{zoneId}/data.
- B The operation SHALL include a templated link to this resource path in the “Core” .../dggs/{dggrsId} resource link templates, and regular link in the .../dggs/{dggrsId}/zones/{zoneId} resource links using the link relation type [ogc-rel:dggrs-zone-data].
- C The response of the HTTP GET operation SHALL have a status code of 200.
- D The content of the response SHALL be a data packet corresponding precisely to the area covered by the DGGS zone.
- E The selection of an encoding for the response SHALL be consistent with HTTP content negotiation.
- F The .../dggs/{dggrsId} resource SHALL include a defaultDepth property indicating the implementation’s default depth for when the zone-depth parameter is omitted. This default value could be any valid value and/or form as defined in the /req/data-custom-depths/zone-depth-parameter requirement (single depth, range of depths, or list of depths, relative to the {zoneId} hierarchy level).
- G Unless a zone-depth parameter is specified, the response SHALL return a data packet consistent with this defaultDepth property, in accordance with the capabilities of the negotiated data packet encoding.

8

REQUIREMENT CLASS “DATA SUBSETTING”

REQUIREMENT CLASS “DATA SUBSETTING”

8.1. Overview

The Data Subsetting requirements class extends the zone data retrieval requirements with the ability to subset data on additional dimensions beyond those defined by the discrete global grid reference systems (DGGRS), for example along time or vertical dimension if those axes are not part the DGGRS definition, or along additional dimensions such as atmospheric pressure levels. Two parameters are defined for this purpose: `datetime` (specifically for time) and `subset` (for any dimension, including time).

REQUIREMENTS CLASS 3

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-subsetting>

8.2. Requirements

8.2.1. Parameter `subset`

REQUIREMENT 5

LABEL /req/data-subsetting/subset

STATEMENT For specifying a multi-dimensional subset for the zone data being retrieved (excluding dimensions of the discrete global grid reference system):

A The Implementation SHALL support a subset query parameter for the zone data retrieval operation (resource path ending with .../dggs/{dggrsId}/zones/{zoneId}/data) conforming to the following

Augmented Backus Naur Form (ABNF) fragment:

```
SubsetSpec:      "subset"=axisName(intervalOrPoint)
axisName:        {text}
intervalOrPoint: interval \| point
interval:        low : high
```

REQUIREMENT 5

```
low:          point \| *
high:         point \| *
point:        {number} \| "{text}"
```

Where:

\" = double quote = ASCII code 0x42,
{number} is an integer or floating-point number, and
{text} is some general ASCII text (such as a time and date notation in ISO 8601).

- B The implementation SHALL support axis names time for a temporal dataset, unless this temporal axis is an axis of the discrete global grid reference system.
- C If a third vertical spatial dimension is supported (if the resource's spatial extent bounding box is three dimensional) and that dimension is not part of the discrete global grid system definition, the implementation SHALL also support a h dimension (elevation above the ellipsoid in EPSG:4979 or CRS84h) for geographic CRS and z for projected CRS, which are to be interpreted as the vertical axis in the CRS definition.
- D The implementation SHALL support axis names any additional dimension (beyond spatial and temporal) as described in the extent property of the collection or dataset description.
- E The implementation SHALL return a 400 error status code if an axis name does not correspond to one of the axes of the Coordinate Reference System (CRS) of the data or an axis defined in the relevant extent property.
- F If a subset parameter including any of the dimensions corresponding to the axes of the discrete global grid reference system is used, the server SHALL return a 400 client error.
- G The implementation SHALL interpret multiple subset parameters, as if all dimension subsetting values were provided in a single subset parameter (comma separated). Example: subset=time("2018-02-12T16:00:0Z":"2018-02-12T20:00:00Z")&subset=atm_pressure_hpa(500:750) is equivalent to subset=time("2018-02-12T16:00:0Z":"2018-02-12T20:00:00Z"),atm_pressure_hpa(500:750)

NOTE: When the *interval* values fall partially outside of the range of valid values defined by the CRS for the identified axis, the service is expected to return the non-empty portion of the data resulting from the subset.

8.2.2. Parameter `datetime`

REQUIREMENT 6

LABEL /req/data-subsetting/datetime

STATEMENT For specifying a time instant or interval for which to retrieve data from a zone for a non-temporal DGGS:

- A The implementation SHALL support a datetime parameter expressed corresponding to either a date-time instant or a time interval, conforming to the following syntax (using ABNF):
interval-closed = date-time "/" date-time

REQUIREMENT 6

```
interval-open-start = [ ".." ] "/" date-time
interval-open-end   = date-time "/" [ ".." ]
interval           = interval-closed / interval-open-start / interval-open-
end
datetime          = date-time / interval
```

- B** The syntax of date-time is specified by [RFC 3339, 5.6](#).
- C** Only the portions of the data within the specified interval SHALL be part of the zone data response, performing a trim operation for an interval or a slicing operation for an instant (in the case of a gridded coverage), or a filtering operation for feature data.
- D** The implementation SHALL support a double-dot (..) or an empty string for the start/end as indicating an unbounded or half-bounded interval (only having a start or end).
- E** If a datetime parameter is specified requesting zone data where no temporal dimension applies, the implementation SHALL either ignore the parameter or return a 4xx client error.

Note: ISO 8601-2 distinguishes unbounded start/end timestamps (double-dot) and unknown start/end timestamps (empty string). For queries, an unspecified start/end has the same effect as an unbounded start/end.

Examples:

Example 1 — A date-time: February 12, 2018, 23:20:52 GMT:

datetime=2018-02-12T23:20:52Z

Example 2 — Intervals: February 12, 2018, 00:00:00 GMT to March 18, 2018, 12:31:12 GMT:

datetime=2018-02-12T00:00:00Z/2018-03-18T12:31:12Z

February 12, 2018, 00:00:00 UTC or later:

datetime=2018-02-12T00:00:00Z/..

March 18, 2018, 12:31:12 UTC or earlier:

datetime=../2018-03-18T12:31:12Z

9

REQUIREMENT CLASS “DATA CUSTOM DEPTHS”

REQUIREMENT CLASS “DATA CUSTOM DEPTHS”

9.1. Overview

The Data Custom Depths requirements class extends the zone data retrieval requirements class allowing a client to customize which depths to include as part of a zone data response relative to the requested hierarchy level for which data is being requested. This can be either a single depth, a range of depths, or a list of depths. The depths to include in the response are specified using the zone-depth query parameter. This depth customization ability can be restricted by the capability of the particular zone data response encoding negotiated.

REQUIREMENTS CLASS 4

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-custom-depths>

9.2. Requirements

9.2.1. Parameter `zone-depth`

REQUIREMENT 7

LABEL /req/data-custom-depths/zone-depth-parameter

STATEMENT Parameter to specify the DGGS resolution levels beyond the specified DGGS zone’s hierarchy level to include in the response, when retrieving data for that zone

A The implementation SHALL support a zone-depth parameter for the HTTP GET operation on a resource path ending with .../dggs/{dggrsId}/zones/{zoneId}/data.

REQUIREMENT 7

The implementation SHALL accept the following types of values for the zone-depth parameter:

- A single positive integer value – representing a specific zone depth to return (e.g., zone-depth=5);
- A range of positive integer values in the form “[low]-[high]” – representing a continuous range of zone depths to return (e.g., zone-depth=1-8); or,
- A comma separated list of at least two (2) positive integer values – representing a set of specific zone depths to return (e.g., zone-depth=1, 3, 7). Some or all of these forms of the zone-depth parameter may not be supported with particular data packet encodings (the data encoding may support a fixed depth, a range of depths, and/or an arbitrary selection of depths).

For each zone depth to be included in the response, the interpretation of a selected depth (whether requesting a single depth, a range of depths, or a list of depths) SHALL be:

- 0 corresponding to a single set of range (properties / field) value(s) for the requested zone,
- 1 corresponding to all zones of the next deeper hierarchy level associated with the requested zone by the indexing scheme,
- ..
- n corresponding to all zones for the n'th deeper level in the hierarchy level associated with the requested zone by the indexing scheme.

The association of zones of deeper hierarchy levels with the requested zone SHALL be based on the DGGS reference system, which takes into consideration both the grid definition as well as the indexing system in use for the DGGS resource.

If a zone-depth is specified, the operation SHALL return the data at the resolution(s) / scale(s) specified.

NOTE 1: A use case for a zone-depth of 0 would be to query the single set of values for a specific DGGS zone.

NOTE 2: For use cases such as visualization and performing analysis over a certain area, a non-zero zone-depth would normally be used to avoid an overwhelming number of server round-trips. In this case, more than a single value would be returned for each zone request, with values returned for descendent zones at zone-depth levels deeper than the requested zone's level. For example, requesting data for a level 10 zone with a zone-depth of 8 would return individual values for each level 18 zones contained within that level 10 zone being requested.

10

REQUIREMENT CLASS “ZONE QUERY”

REQUIREMENT CLASS “ZONE QUERY”

10.1. Overview

The Zone Query requirement class allows to request the list of DGGS zones from a specific Discrete Global Grid Reference System (DGGRS), that is a specific hierarchy of Discrete Global Grids combined with a particular zone indexing reference system (ZIRS), for which there is data available, or matching a particular query (e.g., using a filtering parameter). It describes an HTTP GET operation, as well as its response. The selected DGGRS is listed as available and described in the Core requirement class, and conforms to [OGC Topic 21](#). The list of zones from a Web API using this requirement class can either be for a particular collection of geospatial data, for a dataset as a whole, or in connection with [OGC API – Processes – Part 3: Workflows & Chaining](#), the output of a processing workflow.

REQUIREMENTS CLASS 5

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/core>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query>

10.2. Requirements

10.2.1. Listing zones (`.../dggs/{dggrsId}/zones`)

The following requirements describe how a client can retrieve the list of zones from which data is available at the resource path `.../dggs/{dggrsId}/zones`.

REQUIREMENT 8

LABEL /req/zone-query/zones-list

STATEMENT For retrieving a list of DGGS zones:

REQUIREMENT 8

- A The Implementation SHALL support an HTTP GET operation at a resource path ending with .../dggs/{dggrsId}/zones.
- B The Implementation SHALL include a link to this resource path in the “Core” .../dggs/{dggrsId} resource links using the link relation type <https://www.opengis.net/def/rel/ogc/1.0/dggs-zone-query>.
- C The response of the HTTP GET operation SHALL have a status code of 200.
- D The content of the response SHALL be a list of zones fully covering where data is available (in the case where the resource is associated with a particular dataset), and matching any additional query parameters specified by the client (e.g., a filtering query parameter), without any redundancy.
- E Unless the zones is a compact list of zones (see compact-zones parameter), the zones returned SHALL all be of the same DGGS hierarchy level.
- F The selection of an encoding for the returned list of zones SHALL be consistent with HTTP content negotiation.
- G The implementation SHALL support at minimum a JSON encoding (media type application/json) where each zone ID is specified as a string within an array of zones assigned to a zones property within a JSON object (e.g, { “zones”: [“1-E-14”, “1-E-15”, “1-F-14”, “1-F-15”, “1-F-16”] }.

10.2.2. Parameter zone-level

The following requirements describe how a client can specify the DGGS hierarchy level at which to retrieve the list of zones.

REQUIREMENT 9

LABEL /req/zone-query/zone-level

STATEMENT For specifying a level at which to return a list of DGGS zones using a zone-level query parameter:

- A The Implementation SHALL support a zone-level query parameter for the zone query operation (resource path ending with .../dggs/{dggrsId}/zones).
- B If a compact zones list is used (the default), the zones returned in the response SHALL be of the DGGS hierarchy level specified by the zone-level query parameter, or of a lower hierarchy level standing in for a compact representation of multiple zones at the requested hierarchy level.
- C If a compact zones list is not used, the zones returned in the response SHALL be of the DGGS hierarchy level specified by the zone-level query parameter.

10.2.3. Parameter compact-zones

By default, implementations return a compact list of zones where children zones fully covering a parent are recursively replaced by the parent zones, allowing to express large areas in a much more compact list of zones. The following requirements describe how a client can disable returning a compact list of zones.

REQUIREMENT 10

LABEL /req/zone-query/compact-zones

STATEMENT For specifying whether to retrieve a list of DGGS zones using a compact-zones parameter:

- A The Implementation SHALL support a boolean compact-zones query parameter for the zone query operation (resource path ending with .../dggs/{dggrsId}/zones), where a value of true corresponds to the default behavior when the parameter is not specified, and a value of false disables the use of compact-zones in the response.
- B When the compact-zones parameter is to false, the zones list response SHALL NOT be a compact list, and SHALL explicitly list every individual zone at the requested or default DGGS hierarchy level.
- C When the compact-zones parameter is set to true (or unspecified), the zones list response SHALL be a compact list, where children zones completely covering the area of a parent zone SHALL be replaced by that parent zone, in a recursive manner all the way to the lowest DGGS hierarchy level.

10.2.4. Parameter parent-zone for hierarchical exploration

The following requirement describe how a client can specify a parent zone to only return zones within this parent zone, allowing to explore a large list in a hierarchical manner (in combination with zone-level) as multiple requests and responses.

REQUIREMENT 11

LABEL /rec/zone-query/parent-zone

STATEMENT For specifying a parent zone within which to restrict zone listing using a parent-zone query parameter:

- A The Implementation SHALL support a parameter parent-zone zone identifier query parameter.
- B When specified, the response SHALL NOT contain zones which are not this parent zone itself or a descendant of that zone.

10.2.5. Parameter limit for paging

The following recommendation describe how a client can specify a limit to the number of zones to be returned and page through large list of zones as multiple requests and responses.

RECOMMENDATION 3

LABEL /req/zone-query/limit

STATEMENT For specifying a paging limit for the list of zones using a `limit` query parameter:

- A The Implementation SHOULD support a parameter `limit` integer query parameter, with a minimum value of 1.
- B The response SHOULD not contain more zones than specified by the optional `limit` parameter (if specified).
- C If the API definition specifies a maximum value for the `limit` parameter, the response SHOULD not contain more zones than this maximum value.
- D If the value of the `limit` parameter is larger than the maximum value, this SHOULD NOT result in an error (but instead be replaced by the maximum as the parameter value).
- E If using compact zones, the parent zones SHOULD count as a single zone, rather than the number of children zones they stand in for.
- F If an implementation does not return the full list of zones for the request, a link with relation type `next` SHOULD be included in a `links` array property of the response, which a client can request to resume listing the zones.

10.2.6. Parameter bbox

REQUIREMENT 12

LABEL /req/zone-query/bbox

STATEMENT For specifying a spatial bounding box for which to return a list of DGGS zones:

The Implementation SHALL support a `bbox` query parameter for the zone query operation (resource path ending with .../dggs/{dggrsId}/zones) with the characteristics defined in the OpenAPI Specification 3.0 fragment:

- A

```
bbox:  
  name: bbox  
  in: query  
  description:  
    Bounding box of the rendered map. The bounding box is provided as four or six coordinates
```

REQUIREMENT 12

- * Lower left corner, coordinate axis 1
- * Lower left corner, coordinate axis 2
- * Minimum value, coordinate axis 3 (optional)
- * Upper right corner, coordinate axis 1
- * Upper right corner, coordinate axis 2
- * Maximum value, coordinate axis 3 (optional)

The coordinate reference system and axis order of the values are indicated in the `bbox-crs` parameter or if the parameter is missing in <https://www.opengis.net/def/crs/OGC/1.3/CRS84>

```
required: false
schema:
  type: array
  oneOf:
    - minItems: 4
      maxItems: 4
    - minItems: 6
      maxItems: 6
  items:
    type: number
    format: double
  style: form
  explode: false
```

- B** bbox SHALL be a comma separated list of four or six floating point numbers. If the bounding box consists of six numbers, the first three numbers are the coordinates of the lower bound corner of a three-dimensional bounding box and the last three are the coordinates of the upper bound corner. The axis order is determined by the bbox-crs parameter value or longitude and latitude if the parameter is missing (<https://www.opengis.net/def/crs/OGC/1.3/CRS84> axis order for a 2D bounding box, <https://www.opengis.net/def/crs/OGC/1.3/CRS84h> for a 3D bounding box). For example in <https://www.opengis.net/def/crs/OGC/1.3/CRS84> the order is left_lon, lower_lat, right_lon, upper_lat.
- C** The returned list of zone IDs SHALL only contain zones inside or intersecting with the spatial extent of the geographical area of bounding box.

10.2.7. Parameter bbox-crs

REQUIREMENT 13

LABEL /req/zone-query/bbox-crs

STATEMENT For specifying the CRS in used for the bbox parameter using the bbox-crs parameter

- A** The list of zones resource SHALL support a bbox-crs parameter specifying the CRS used for the bbox parameter.
- B** For Earth centric data, the implementation SHALL support <https://www.opengis.net/def/crs/OGC/1.3/CRS84> as a value.
- C** If the bbox-crs is not indicated <https://www.opengis.net/def/crs/OGC/1.3/CRS84> SHALL be assumed.

REQUIREMENT 13

- D The native CRS (storageCRS) SHALL be supported as a value. Other conformance classes may allow additional values (see crs parameter definition).
- E The CRS expressed as URIs or as safe CURIEs SHALL be supported.
- F If the bbox parameter is not used, the bbox-crs SHALL be ignored.

10.2.8. Parameter subset

REQUIREMENT 14

LABEL /req/zone-query/subset

STATEMENT For specifying a multi-dimensional subset for which to return a list of DGGS zones:

The Implementation SHALL support a subset query parameter for the zone query operation (resource path ending with .../dggs/{dggrsId}/zones) conforming to the following Augmented Backus Naur Form (ABNF) fragment:

- A

```
SubsetSpec:          "subset"=axisName(intervalOrPoint)
axisName:           {text}
intervalOrPoint:   interval \| point
interval:          low : high
low:                point \| *
high:               point \| *
point:              {number} \| "{text}"
```

Where:
\" = double quote = ASCII code 0x42,
{number} is an integer or floating-point number, and
{text} is some general ASCII text (such as a time and date notation in ISO 8601).

B The implementation SHALL support as axis names Lat and Lon for geographic CRS and x and y for projected CRS, which are to be interpreted as the best matching spatial axis in the CRS definition.

C If a third spatial dimension is supported (if the resource's spatial extent bounding box is three dimensional), the implementation SHALL also support a h dimension (elevation above the ellipsoid in EPSG:4979 or CRS84h) for geographic CRS and z for projected CRS, which are to be interpreted as the vertical axis in the CRS definition.

D The implementation SHALL support as axis names time for a temporal dataset.

E The implementation SHALL support as axis names any additional dimension (beyond spatial and temporal) as described in the extent property of the collection or dataset description.

F The implementation SHALL return a 400 error status code if an axis name does not correspond to one of the axes of the Coordinate Reference System (CRS) of the data or an axis defined in the relevant extent property.

REQUIREMENT 14

- G For a CRS where an axis can wrap around, such as subsetting across the dateline (anti-meridian) in a geographic CRS, a *low* value greater than *high* SHALL be supported to indicate an extent crossing that wrapping point.
- H The implementation SHALL interpret the coordinates as values for the named axis of the CRS specified in the subset-crs parameter value or in <https://www.opengis.net/def/crs/OGC/1.3/CRS84> (<https://www.opengis.net/def/crs/OGC/1.3/CRS84h> for vertical dimension) if the subset-crs parameter is missing.
- I If the subset parameter including any of the dimensions corresponding to those of the map bounding box is used with a bbox, the server SHALL return a 400 client error.
- J The implementation SHALL interpret multiple subset parameters, as if all dimension subsetting values were provided in a single subset parameter (comma separated). Example: subset=Lat(-90:90)&subset=Lon(-180:180) is equivalent to subset=Lat(-90:90),Lon(-180:180)

NOTE 1: A subset parameter for <https://www.opengis.net/def/crs/OGC/1.3/CRS84> will read as subset=Lon(left_lon:right_lon),Lat(lower_lat:upper_lat).

NOTE 2: When the *interval* values fall partially outside of the range of valid values defined by the CRS for the identified axis, the service is expected to return the non-empty portion of the resource resulting from the subset.

NOTE 3: For the operation of returning a list of zone IDs, there normally is no value in preserving dimensionality, therefore a *slicing* operation (using the *point* notation) is usually equivalent to a *trimming* operation (using the *interval* notation) when the low and high bounds of an interval are the same. Therefore, use of the point notation is encouraged in these cases.

10.2.9. Parameter subset-crs

REQUIREMENT 15

LABEL /req/zone-query/subset-crs

STATEMENT For specifying the CRS in used for the subset parameter using the subset-crs parameter

- A The zone listing operation SHALL support a parameter subset-crs with the characteristics identifying the CRS in which the subset parameter is specified with a URI or safe CURIE.
- B For Earth centric data, <https://www.opengis.net/def/crs/OGC/1.3/CRS84> as a value SHALL be supported.
- C If the subset-crs is not indicated, <https://www.opengis.net/def/crs/OGC/1.3/CRS84> SHALL be assumed.
- D The native CRS (storageCRS) SHALL be supported as a value. Other requirements classes may allow additional values (see crs parameter definition).

REQUIREMENT 15

- E CRSs expressed as URIs or as safe CURIEs SHALL be supported.
- F If no subset parameter referring to an axis of the CRS is used, the subset-crs SHALL be ignored.

10.2.10. Parameter `datetime`

REQUIREMENT 16

LABEL /req/zone-query/datetime

STATEMENT For specifying a multi-dimensional subset for which to return a list of DGGS zones:

The implementation SHALL support a datetime parameter expressed corresponding to either a date-time instant or a time interval, conforming to the following syntax (using ABNF):

A interval-closed = date-time "/" date-time
 interval-open-start = [". . ."] "/" date-time
 interval-open-end = date-time "/" [". . ."]
 interval = interval-closed / interval-open-start / interval-open-end
 datetime = date-time / interval

B The syntax of date-time is specified by [RFC 3339, 5.6](#).

C Only the zones with data whose geometry intersect with the specified temporal interval SHALL be part of the zone list response.

D The implementation SHALL support a double-dot (..) or an empty string for the start/end as indicating an unbounded or half-bounded interval (only having a start or end).

E If a datetime parameter is specified requesting zone data where no temporal dimension applies, the implementation SHALL either ignore the parameter or return a 4xx client error.

11

REQUIREMENT CLASS “FILTERING ZONE QUERIES WITH CQL2”

REQUIREMENT CLASS “FILTERING ZONE QUERIES WITH CQL2”

11.1. Overview

The Filtering Zone Queries with CQL2 conformance class defines a filter query parameter where an OGC Common Query Language (CQL2) expression can be used to filter the list of returned zones, for example based on the properties / fields of the data, or for performing spatial and/or temporal intersections.

REQUIREMENTS CLASS 6

TARGET TYPE	Web API
PREREQUISITES	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query https://www.opengis.net/spec/cql2/1.0/req/cql2-text
LABEL	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/cql2-query

11.2. Requirements

11.2.1. Parameter filter

The following requirements describe how a client can specify a filtering CQL2 expression querying a list of zones.

REQUIREMENT 17

LABEL	/req/cql2-query/filter
-------	------------------------

STATEMENT For specifying a CQL2 expression filtering the zones returned from a zone query:

- A The Implementation SHALL support a filter query parameter specified using the CQL2-Text encoding of the OGC Common Query Language for the zone query operation (resource path ending with .../dggs/{dggrsId}/zones).

REQUIREMENT 17

- B The list of returned zones SHALL only be those for which the CQL2 expression evaluates to true when considering the geometry and the data of the DGGS zones resource being queried.

12

REQUIREMENT CLASS “ROOT DGGS”

REQUIREMENT CLASS “ROOT DGGS”

12.1. Overview

The “Root DGGS” Requirement Class defines the availability of DGGS resources applying to a whole dataset or API, as defined by OGC API – Common – Part 1: Core.

REQUIREMENTS CLASS 7

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-common-1/1.0/req/core>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/root-dggs>

12.2. Requirements

12.2.1. Root DGGS (/dggs)

REQUIREMENT 18

LABEL /req/root-dggs/dggs

STATEMENT For API/dataset-wide DGGS resources:

A The Implementation SHALL support DGGS resources for the dataset as a whole, for the “Core” requirement class, as well as any resources defined in additional supported requirements classes.

B The Implementation SHALL include a link to the list of available DGGRSs for the API/dataset at /dggs in the links of the landing page using the link relation type [ogc-rel:dggrs-list].

C If the DGGS API allows querying or retrieving data from a dataset, the /dggs and /dggs/{dggrsId} resources SHALL include a link to the landing page using the link relation type [ogc-rel:dataset].

13

REQUIREMENT CLASS “COLLECTION DGGS”

REQUIREMENT CLASS “COLLECTION DGGS”

13.1. Overview

The “Collection DGGS” Requirement Class defines the availability of DGGS resources applying to one or more collections of geospatial data, as defined by OGC API – Common – Part 2: *Geospatial data*.

REQUIREMENTS CLASS 8

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-common-2/1.0/req/collections>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/collection-dggs>

13.2. Requirements

13.2.1. Collection DGGS (`/collections/{collectionId}/dggs`)

REQUIREMENT 19

LABEL /req/collection-dggs/dggs

STATEMENT For collection DGGS resources:

A The Implementation SHALL support DGGS resources for at least one collection, for the “Core” requirement class, as well as any resources defined in additional supported requirements classes.

B The Implementation SHALL include a link to the list of available DGGRSs for the collection at /collections/{collectionId}/dggs in the links of the collection using the link relation type [ogc-rel:dggrs-list].

C The /collections/{collectionId}/dggs and /collections/{collectionId}/dggs/{dggrsId} resources SHALL include a link to the collection using the link relation type [ogc-rel:geodata].

14

REQUIREMENTS CLASSES FOR ENCODINGS OF ZONE DATA

REQUIREMENTS CLASSES FOR ENCODINGS OF ZONE DATA

This standard does not mandate any particular encoding or format in which to return the `./dggs/{dggrsId}/zones/{zoneId}/data` resources. DGGS Zone Data can be encoded in any suitable data format. However, it does define requirements class for zone data encodings which are expected to be commonly supported in implementations of this standard. These requirements classes include:

- DGGS-JSON Data
- DGGS-UB-JSON Data
- GeoJSON Data
- FG-JSON Data
- GeoTIFF Data
- netCDF Data
- CoverageJSON Data
- JPEG XL Data
- PNG Data

14.1. Media Types (for zone data)

A table of the media types used in the encoding of the Zone Data requirements class defined in this standard follows.

Table 2 – Media Types used for zone data encoding requirements classes

Encoding	media type
DGGS-JSON zone data	application/json
DGGS-UB-JSON zone data	application/ubjson
GeoJSON data	application/geo+json

JSON-FG data	application/fg+json
GeoTIFF data	image/tiff; application=geotiff
netCDF zone data	application/x-netcdf
CoverageJSON zone data	application/prs.coverage+json
PNG zone data	image/png
JPEG XL zone data	image/jxl

14.2. Requirements Class “DGGS-JSON Zone data encoding”

14.2.1. Overview

The JSON Zone Data encoding requirements class defines support for encoding a DGGS Zone data response in JSON, using a schema defined below named “DGGS-JSON”.

This encoding is intended to support one-to-one mapping of sub-zones values, for one or more zone depths, regardless of zone geometry type, in a human-readable format.

Values are encoded as a one-dimensional array following a sub-zone order defined by the DGGRS.

Example encodings follow:

```
{
  "$schema" : "https://schemas.opengis.net/ogcapi/dggs/part1/1.0/openapi/
schemas/dggs-json/schema",
  "dggrs": "https://www.opengis.net/def/dggrs/OGC/1.0/ISEA3H",
  "zoneId": "C0-2B-A",
  "depths": [ 0, 1 ],
  "schema":
  {
    "$schema" : "https://json-schema.org/draft/2020-12/schema",
    "$id" : "https://example.com/ogcapi/collections/climate/schema",
    "title" : "Temperature",
    "type": "object",
    "properties":
    {
      "t": {
        "type": "number",
        "title": "air temperature in celsius",
      }
    }
  }
}
```

```

        "x-ogc-propertySeq" : 1,
        "x-ogc-definition": "https://qudt.org/vocab/quantitykind/Temperatur
e",
        "x-ogc-unit": "C"
    }
},
"values":
{
    "t": [
        {
            "depth": 0,
            "shape": { "count": 1, "subZones": 1 },
            "data": [ 22.8 ]
        },
        {
            "depth": 1,
            "shape": { "count": 7, "subZones": 7 },
            "data": [ 25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1 ]
        }
    ]
}
}

```

Figure 6 – Example encoding for DGGS-JSON

```

{
    "$schema" : "https://schemas.opengis.net/ogcapi/dggs/part1/1.0/openapi/
schemas/dggs-json/schema",
    "dggrs": "https://www.opengis.net/def/dggrs/OGC/1.0/ISEA3H",
    "zoneId": "C0-2B-A",
    "depths": [ 0, 1 ],
    "schema":
    {
        "$schema" : "https://json-schema.org/draft/2020-12/schema",
        "$id" : "https://example.com/ogcapi/collections/climate/schema",
        "title" : "Climate Variables",
        "type": "object",
        "properties":
        {
            "rh": {
                "type": "number",
                "title": "relative humidity",
                "x-ogc-propertySeq" : 1,
                "x-ogc-definition": "https://qudt.org/vocab/quantitykind/RelativeHu
midity"
            },
            "t": {
                "type": "number",
                "title": "air temperature in celsius",
                "x-ogc-propertySeq" : 2,
                "x-ogc-definition": "https://qudt.org/vocab/quantitykind/Temperatur
e",
                "x-ogc-unit": "C"
            },
            "ua": {
                "type": "number",
                "title": "Eastward wind",
                "x-ogc-propertySeq" : 3,
                "x-ogc-definition": "https://qudt.org/vocab/quantitykind/Speed",
                "x-ogc-unit": "m/s"
            }
        }
    }
}

```

```

        },
        "va": {
            "type": "number",
            "title": "Northward wind",
            "x-ogc-propertySeq": 4,
            "x-ogc-definition": "https://qudt.org/vocab/quantitykind/Speed",
            "x-ogc-unit": "m/s"
        }
    }
},
"dimensions": [
{
    "name": "time",
    "interval": [ "2020-01-01", "2020-03-31" ],
    "grid": { "cellsCount": 3, "resolution": "P1M" }
},
{
    "name": "pressure",
    "definition": "https://qudt.org/vocab/quantitykind/AtmosphericPressure",
    "unit": "hPa",
    "interval": [ 850.0, 50.0 ],
    "grid": { "cellsCount": 3, "coordinates": [ 850.0, 250.0, 50.0 ] }
}
],
"values":
{
    "rh": [
        {
            "depth": 0,
            "shape": { "count": 9, "subZones": 1, "dimensions": { "pressure": 3, "time": 3 } },
            "data": [
                25.1, 25.8, 22.0,
                23.1, 22.8, 20.0,
                17.1, 12.8, 14.0,
            ]
        },
        {
            "depth": 1,
            "shape": { "count": 63, "subZones": 7, "dimensions": { "pressure": 3, "time": 3 } },
            "data": [
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0,
                25.1, 25.8, 22.0, 23.1, 22.8, 20.0, 17.1, 12.8, 14.0
            ]
        }
    ],
    "t": [ ... ],
    "ua": [ ... ],
    "va": [ ... ]
}
}

```

Figure 7 – A more complex example encoding for DGGS-JSON with more variables and additional dimensions beyond those of the DGGRS

REQUIREMENTS CLASS 9: REQUIREMENTS CLASS JSON ZONE DATA

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-json
TARGET TYPE	Web API
CONFORMANCE CLASS	Conformance class A.9: https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-json
PREREQUISITES	JSON https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval

REQUIREMENT 20

IDENTIFI /req/data-json/content

- A Every 200 response of the server for zone data with the media type application/json SHALL be a JSON document representing the data values for all selected fields for a single zone.
- B The schema for the JSON document SHALL follow the JSON Schema for DGGS-JSON described below.
- C Every zone depth requested using the zone-depth parameter SHALL be included in the response.
- D At every depth, each individual value SHALL correspond exactly to the data sampled representative of that zone geometry.
- E The list of data values SHALL follow the default zone order as specified by the Discrete Global Grid Reference System (for example based on a scanline or space-filling curved defined therein) for which the request is made.
- F Null values SHALL use the null JSON value.

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$id": "https://schemas.opengis.net/ogcapi/dggs/part1/1.0/openapi/schemas/dggs-json/schema",
  "type": "object",
  "properties": {
    "dggrs": { "type": "string", "format": "uri" },
    "zoneId": { "type": "string" },
    "depths": { "type": "array", "items": { "type": "integer", "minimum": 0 } },
  },
  "schema": { "$ref": "https://json-schema.org/draft/2020-12/schema" },
  "dimensions": {
    "type": "array",
    "items": [
      {
        "type": "array",
        "items": [
          {
            "type": "string"
          }
        ]
      }
    ]
  }
}
```

```

    "type": "object",
    "properties":
    {
        "name": { "type": "string" },
        "definition": { "type": "string", "format": "uri" },
        "unit": { "type": "string" },
        "unitLang": { "type": "string", "format": "uri" },
        "grid":
        {
            "type": "object",
            "properties":
            {
                "cellsCount" : { "type": "integer" },
                "resolution" : { },
                "coordinates": { "type": "array" }
            }
        },
        "interval": { "type": "array" }
    },
    "required": [ "name", "interval" ]
},
"values" :
{
    "additionalProperties":
    {
        "type": "array",
        "items":
        {
            "type": "object",
            "properties":
            {
                "depth": { "type": "integer" },
                "shape":
                {
                    "type": "object",
                    "properties":
                    {
                        "count": { "type": "integer" },
                        "subZones": { "type": "integer" },
                        "dimensions":
                        {
                            "type": "object",
                            "additionalProperties": { "type": "integer" }
                        }
                    },
                    "required": [ "count", "subZones" ]
                },
                "data":
                {
                    "type": "array",
                    "item": "number"
                }
            }
        }
    }
},
"required": [ "dggrs", "zoneId", "depths", "values" ]
}

```

Figure 8 – JSON Schema for DGGS-JSON

14.3. Requirements Class “DGGS-UB-JSON Zone data encoding”

14.3.1. Overview

The UB-JSON Zone Data encoding requirements class defines support for encoding a DGGS Zone data response using the same JSON structure as the above JSON data requirement class, but using the binary UB-JSON encoding.

REQUIREMENTS CLASS 10: REQUIREMENTS CLASS UB-JSON

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-ubjson>

TARGET TYPE Web API

PREREQUISITES <https://ubjson.org/>
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

REQUIREMENT 21

IDENTIFI /req/data-ubjson/content

- A** Every 200 response of the server for zone data with the media type application/ubjson SHALL be a Universal Binary JSON document representing the data values for all selected fields for a single zone.
- B** The schema for the UB-JSON document SHALL follow the same JSON Schema as for DGGS-JSON described above.
- C** Every zone depth requested using the zone-depth parameter SHALL be included in the response.
- D** At every depth, each individual value SHALL correspond exactly to the data sampled representative of that zone geometry.
- E** The list of data values SHALL follow the default zone order as specified by the Discrete Global Grid Reference System (for example based on a scanline or space-filling curved defined therein) for which the request is made.
- F** Null values SHALL use the null JSON value.

14.4. Requirements Class “GeoTIFF Zone data encoding”

14.4.1. Overview

The GeoTIFF Zone Data encoding requirements class defines support for encoding a DGGS Zone data response according to the [OGC GeoTIFF standard](#).

GeoTIFF is a commonly used format for representing 2-dimensional gridded coverages.

For a DGGS with non-rectangular zones (e.g., hexagonal zones), a GeoTIFF representation can be the minimal bounding rectangle of the zone shape, with NODATA values used outside the bounds of the zone.

REQUIREMENTS CLASS 11: REQUIREMENTS CLASS GEOTIFF DATA

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-geotiff
TARGET TYPE	Web API
PREREQUISITES	TIFF V6.0 GeoTIFF https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval

REQUIREMENT 22

IDENTIFIER /req/data-geotiff/content

- A Every 200 response of the server for zone data with the media type `image/tiff` SHALL be a TIFF image representing the data values for all selected fields for a single zone.
- B If the TIFF encoding incorporates a GeoTIFF georeference, this information SHALL be consistent with the DGGRS Zone ID.
- C If the zone geometry is not rectangular, the closest bounding rectangle SHALL be used for referencing the image.
- D A distinct value for each sub-zone implied from the requested zone-depth SHALL correspond to at least one distinct cell value in the response.
- E For implementations supporting Data Custom Depths, each depth of the requested zone depth pyramid SHALL be a separate image (overview) in the response.

RECOMMENDATION 4

IDENTIFIER /rec/data-geotiff/null-values

A Null values SHOULD be used for cells lying outside the zone geometry.

RECOMMENDATION 5

IDENTIFIER /rec/data-geotiff/crs

A The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

14.5. Requirements Class “GeoJSON Zone data encoding”

14.5.1. Overview

The GeoJSON Zone Data encoding requirements class defines support for encoding a DGGS Zone data response according to the [GeoJSON specification](#).

GeoJSON is a commonly used format for representing features with simple geometries and related properties. GeoJSON is simple to understand and well supported by tools and software libraries. Since most Web developers are comfortable with using JSON-based formats, supporting GeoJSON is recommended for a vector representation of DGGS Zone data.

REQUIREMENTS CLASS 12: REQUIREMENTS CLASS GEOJSON

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-geojson>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.10: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-geojson>

PREREQUISITES GeoJSON
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

REQUIREMENT 23

IDENTIFI /req/data-geojson/content

- A Every 200 response of the server for zone data with the media type application/geo+json SHALL be a GeoJSON document representing the features, including their geometry and associated properties, for a single zone.
- B Unless otherwise specified by a prior arrangement (for example, a crs output parameter), the coordinate reference system SHALL be CRS84(h) in longitude and latitude (and optional height above the WGS84 ellipsoid).
- C Features whose geometry lie wholly outside of the zone geometry SHALL not be included in the response.

RECOMMENDATION 6

IDENTIFI /rec/data-geojson/clipping

- A For features partially inside of the zone geometry, the geometry included in the response SHOULD be clipped to the boundaries of the zone geometry.

RECOMMENDATION 7

IDENTIFI /rec/data-geojson/generalization

- A The geometry of the features in the response SHOULD be generalized to the scale associated with the hierarchy level implied from the zone-depth relative to the requested zone.

RECOMMENDATION 8

IDENTIFI /rec/data-geojson/omission

- A For datasets whose features have either a size (such as areal or linear feature) or other properties making some features irrelevant at lower hierarchy levels, such irrelevant features SHOULD be omitted from the response based on the hierarchy level implied from the zone-depth relative to the requested zone.

14.6. Requirements Class “FG-JSON Zone data encoding”

14.6.1. Overview

The FG-JSON Zone Data encoding requirements class defines support for encoding a DGGS Zone data response according to the [FG JSON candidate Standard](#).

FG JSON is an OGC format for representing features with simple geometries and related properties, with extending GeoJSON with greater flexibility. FG JSON is simple to understand and well supported by tools and software libraries. Since most Web developers are comfortable with using JSON-based formats, supporting FG JSON is recommended for a vector representation of DGGS Zone data.

REQUIREMENTS CLASS 13: REQUIREMENTS CLASS FG-JSON DATA

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-fgjson>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.11: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-fgjson>

PREREQUISITES OGC 21-045r1
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

REQUIREMENT 24

IDENTIFI /req/data-fgjson/content

- A Every 200 response of the server for zone data with the media type application/fg+json SHALL be a [Feature & Geometries JSON](#) document representing the features, including their geometry and associated properties, for a single zone.
- B Features whose geometry lie wholly outside of the zone geometry SHALL not be included in the response.

RECOMMENDATION 9

IDENTIFI /rec/data-fgjson/clipping

- A For features partially inside of the zone geometry, the geometry included in the response SHOULD be clipped to the boundaries of the zone geometry.

RECOMMENDATION 10

IDENTIFIE /rec/data-fgjson/generalization

- A The geometry of the features in the response SHOULD be generalized to the scale associated with the hierarchy level implied from the zone-depth relative to the requested zone.

RECOMMENDATION 11

IDENTIFIE /rec/data-fgjson/omission

- A For datasets whose features have either a size (such as areal or linear feature) or other properties making some features irrelevant at lower hierarchy levels, such irrelevant features SHOULD be omitted from the response based on the hierarchy level implied from the zone-depth relative to the requested zone.

RECOMMENDATION 12

IDENTIFIE /rec/data-fgjson/crs

- A The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

14.7. Requirements Class “netCDF zone data encoding”

14.7.1. Overview

The netCDF Zone Data encoding requirements class defines support for encoding a DGGS Zone data response according to the [OGC netCDF standard](#).

REQUIREMENTS CLASS 14: REQUIREMENTS CLASS NETCDF

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-netcdf>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.13: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-netcdf>

REQUIREMENTS CLASS 14: REQUIREMENTS CLASS NETCDF

PREREQUISITES

OGC Network Common Data Form (NetCDF) Core Encoding Standard version 1.0
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

REQUIREMENT 25

IDENTIFII/req/data-netcdf/content

- A Every 200 response of the server for zone data with the media type application/netcdf SHALL be a netCDF file representing the data values for all selected fields for a single zone.
- B If the netCDF encoding incorporates georeferencing information, this information SHALL be consistent with the DGGRS Zone ID.
- C If the zone geometry is not rectilinear, the closest bounding rectangle (or volume) SHALL be used for referencing the data.
- D A distinct value for each sub-zone implied from the requested zone-depth SHALL correspond to at least one distinct cell value in the response.

RECOMMENDATION 13

IDENTIFIR/rec/data-netcdf/null-values

- A Null values SHOULD be used for cells lying outside the zone geometry.

RECOMMENDATION 14

IDENTIFIR/rec/data-netcdf/crs

- A The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

14.8. Requirements Class “CoverageJSON zone data encoding”

14.8.1. Overview

The CoverageJSON requirements class defines support for encoding a DGGS Zone data response according to the [OGC CoverageJSON Community Standard](#).

REQUIREMENTS CLASS 15: REQUIREMENTS CLASS COVERAGEJSON DATA

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-coveragejson
TARGET TYPE	Web API
CONFORMANCE CLASS	Conformance class A.14: https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-coveragejson
PREREQUISITES	OGC 21-069r2 https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval

REQUIREMENT 26

IDENTIFIER /req/data-coveragejson/content

- A Every 200 response of the server for zone data with the media type application/prs.coverage+json SHALL be a [CoverageJSON](#) file representing the data values for all selected fields for a single zone.
- B If the CoverageJSON encoding incorporates georeferencing information, this information SHALL be consistent with the DGGRS Zone ID.
- C If the zone geometry is not rectilinear, the closest bounding rectangle (or volume) SHALL be used for referencing the data.
- D A distinct value for each sub-zone implied from the requested zone-depth SHALL correspond to at least one distinct cell value in the response.

RECOMMENDATION 15

IDENTIFIER /rec/data-coveragejson/null-values

RECOMMENDATION 15

A Null values SHOULD be used for cells lying outside the zone geometry.

RECOMMENDATION 16

IDENTIFIE /rec/data-coveragejson/crs

A The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

14.9. Requirements Class “JPEG-XL Zone data encoding”

14.9.1. Overview

The JPEG XL Zone Data encoding requirements class defines support for encoding a DGGS Zone data response according to the [JPEG XL ISO/IEC 18181 Standard](#).

JPEG XL supports a large number of bands, image dimensions, and floating point values.

REQUIREMENTS CLASS 16: REQUIREMENTS CLASS JPEG XL DATA

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-jpegxl>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.15: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-jpegxl>

PREREQUISITES ISO/IEC 18181-1
ISO/IEC 18181-2
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

REQUIREMENT 27

IDENTIFI /req/data-jpegxl/content

A Every 200 response of the server for zone data with the media type `image/jxl` SHALL be a [JPEG XL](#) image representing the data values for all selected fields for a single zone.

REQUIREMENT 27

- B If the zone geometry is not rectangular, the closest bounding rectangle SHALL be used for referencing the image.
- C A distinct value for each sub-zone implied from the requested zone-depth SHALL correspond to at least one distinct cell value in the response.
- D For implementations supporting Data Custom Depths, each depth of the requested zone depth pyramid SHALL be a separate image (overview) in the response.

RECOMMENDATION 17

IDENTIFIER /rec/data-jpegxl/null-values

- A Null values SHOULD be used for cells lying outside the zone geometry.

RECOMMENDATION 18

IDENTIFIER /rec/data-jpegxl/crs

- A The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

14.10. Requirements Class “PNG Zone data encoding”

14.10.1. Overview

The PNG Zone Data encoding requirements class defines support for encoding a DGGS Zone data response according to the [W3C Portable Network Graphics \(PNG\) Specification \(ISO/IEC 15948:2003\)](#).

Because PNG encoding is limited to an integer data values, this requirements class defines additional parameters and response headers allowing a client to request a specific scale factor and offset to be used to quantize data values, and allowing the implementation to inform the client of the scale factor and offset used for that quantization.

REQUIREMENTS CLASS 17: REQUIREMENTS CLASS PNG DATA

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-png>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.16: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-png>

PREREQUISITES ISO/IEC 15948
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval>

REQUIREMENT 28

IDENTIFI /req/data-png/content

- A** Every 200 response of the server for zone data with the media type image/png SHALL be a PNG image representing the data values for all selected fields for a single zone.
- B** If the zone geometry is not rectangular, the closest bounding rectangle SHALL be used for referencing the image.
- C** A distinct value for each sub-zone implied from the requested zone-depth SHALL correspond to at least one distinct cell value in the response.
- D** For implementations supporting Data Custom Depths, each depth of the requested zone depth pyramid SHALL be a separate image (overview) in the response.

RECOMMENDATION 19

IDENTIFIER /rec/data-png/null-values

- A** Null values SHOULD be used for cells lying outside the zone geometry.

RECOMMENDATION 20

IDENTIFI /rec/data-png/crs

- A** The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

15

REQUIREMENTS CLASSES FOR ENCODINGS OF ZONE LIST

REQUIREMENTS CLASSES FOR ENCODINGS OF ZONE LIST

This standard does not mandate any particular encoding or format in which to return the .. /dggs/{dggrsId}/zones resources. DGGS Zone Lists can be encoded in any suitable data format. However, it does define requirements class for zone list encodings which are expected to be commonly supported in implementations of this standard. These requirements classes include:

- JSON Zone List
- 64-bit Binary Zone List
- HTML Zone List
- GeoJSON Zone List
- FG-JSON Zone List
- GeoTIFF Zone List

15.1. Media Types (for zone list)

A table of the media types used in the zone list encoding requirements classes defined in this standard follows.

Table 3 – Media Types used for zone list encoding requirements classes

Encoding	media type
GeoTIFF zone list	image/tiff; application=geotiff
GeoJSON zone list	application/geo+json
JSON-FG zone list	application/fg+json
JSON zone list	application/json
HTML zone list	text/html
Binary 64-bit zone list	application/x-binary

15.2. Requirements Class “JSON zone list encoding”

15.2.1. Overview

The JSON zone list encoding requirements class defines the ability to retrieve a JSON response for the DGGS zone list resource.

The response consists of a simple JSON object with a “zones” array property listing the zone identifiers as strings. The object can also include a “links” objects linking back to other resources of the DGGS.

This requirement class provides an easy to implement, reasonably efficient and interoperable mechanism to exchange lists of zone identifiers.

REQUIREMENTS CLASS 18: REQUIREMENTS CLASS JSON ZONE LIST

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-json>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.17: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-json>

PREREQUISITES JSON
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query>

REQUIREMENT 29

IDENTIFI /req/zone-json/content

- A Every 200 response of the server for zone query with the media type application/json SHALL be a JSON document listing the textual identifiers for all zones matching the query.
- B The schema for the JSON document SHALL follow the JSON Schema for DGGS Zone Query described below, where the zone identifiers are strings within a zones array property.
- C The links property SHALL include an [ogc-rel:dggrs] link to the Discrete Global Grid Reference System description resource.
- D The links property SHALL include an [ogc-rel:dggrs-definition] link to the DGGRS definition, using the schema defined in Annex B – DGGRS Definitions or a later version.

```
{  
  "$schema" : "https://json-schema.org/draft/2020-12/schema",
```

```

"$id" : "https://schemas.opengis.net/ogcapi/dggs/part1/1.0/openapi/schemas/
dggs-core/dggs-zones.json",
  "type": "object",
  "required": [ "zones" ],
  "properties":
  {
    "zones" : { "type": "array", "items": { "type": "string" } },
    "links" :
    {
      "description": "Links to related resources."
      "items": { "$ref" : "https://schemas.opengis.net/ogcapi/dggs/part1/1.
0/openapi/schemas/common-core/link.yaml"
    }
  }
}

```

Figure 9 – JSON Schema for a DGGS Zone Query response

RECOMMENDATION 21

IDENTIFIE /rec/zone-json/additional-links

- A If DGGS Zone Data Retrieval is supported, the linkTemplates property SHOULD include an [ogc-rel:dggrs-zone-data] link with a {zoneId} variable to retrieve data from each of these DGGRS zones.
- B The links property SHOULD include an [ogc-rel:geodata] link for zone listing pertaining to a particular collection (for Collection DGGS requirement class).

RECOMMENDATION 22

IDENTIFIE /rec/zone-json/zone-order

- A For responses where zones of multiple hierarchy levels are returned when compact-zones is true, the zones SHOULD be listed with the coarser resolution level first (larger zones).

15.3. Requirements Class “HTML zone list encoding”

15.3.1. Overview

The HTML zone list encoding requirements class defines at a high level the ability to retrieve an HTML response for the DGGS zone list resource intended primarily for users accessing the API from a Web browser.

The exact content of the HTML response is not prescribed, leaving the flexibility for implementations to choose a preferred approach.

HTML is the core language of the World Wide Web. An API that supports HTML will support browsing the spatial resources with a web browser and will also enable search engines to crawl and index those resources.

REQUIREMENTS CLASS 19: REQUIREMENTS CLASS HTML ZONE LIST

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-html>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.18: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-html>

PREREQUISITES <https://html.spec.whatwg.org/>
<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query>

REQUIREMENT 30

IDENTIFI /req/zone-html/content

A Every 200 response of the server for zone query with the media type text/html SHALL be an HTML document listing the textual identifiers for all zones matching the query.

RECOMMENDATION 23

IDENTIFI /rec/zone-html/zone-information

A The implementation SHOULD include additional information for each zone ID, such as the area, bounding box and/or a preview of the data available for this zone.

RECOMMENDATION 24

IDENTIFI /rec/zone-html/zone-data

A If the implementation also supports Zone Data Retrieval, the implementation SHOULD include a link for each zone to download the associated data .

15.4. Requirements Class “Binary 64-bit integer zone list encoding”

15.4.1. Overview

The binary 64-bit integer zone list encoding requirements class defines the ability to retrieve a binary response for the DGGS zone list resource for DGGRS whose zone identifiers can be expressed as a single 64-bit integer.

The response consists of a 64-bit integer count of zones, followed by that count of zones, also 64-bit integers. With compact zones and additional HTTP content encoding compression, this provides an optimal way to exchange DGGS zone lists.

REQUIREMENTS CLASS 20: REQUIREMENTS CLASS 64-BIT BINARY ZONE LIST

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-uint64>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.19: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-uint64>

PREREQUISITE <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query>

REQUIREMENT 31

IDENTIFI /req/zone-uint64/content

- A Every 200 response of the server for zone query with the media type application/x-binary SHALL be a binary response consisting of a first 64-bit integer count defining the number of zones returned, followed by one 64-bit integer for each zone matching the query.
- B The 64-bit integer identifiers SHALL be the one defined by the DGGRS.
- C The endianness of the returned count and zones integers SHALL be little endian.
- D If the DGGRS does not define a 64-bit integer identifier, a 406 “Not Acceptable” response SHALL be returned.

15.5. Requirements Class “GeoJSON zone list encoding”

15.5.1. Overview

The GeoJSON zone list encoding requirements class defines support for encoding a DGGS Zone list response according to the [GeoJSON specification](#).

The response is a feature collection where each feature represents a zone in the list. The geometry of the zone should be polygons or multipolygons (e.g., in the case of zone geometry which must be split on the anti-meridian or pole). The zone identifier is represented in the `id` field of each feature.

While not intended to efficiently exchange zone list, as the response carries the geometry of the zones which could easily be computed client-side which takes considerable bandwidth and is not necessary for a DGGS client working natively with the same DGGRS, this requirement class provides an easy way to readily visualize the response in a variety of tools. This requirements class is therefore intended for convenience, demonstration and educational purposes.

REQUIREMENTS CLASS 21: REQUIREMENTS CLASS GEOJSON ZONE LIST

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-geojson
TARGET TYPE	Web API
CONFORMANCE CLASS	Conformance class A.20: https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-geojson
PREREQUISITES	GeoJSON https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query

REQUIREMENT 32

IDENTIFI /req/zone-geojson/content

- A Every 200 response of the server for zone query with the media type application/geo+json SHALL be a GeoJSON document consisting of a FeatureCollection, where every Feature represents a single zone.
- B Every feature SHALL have a zoneID property corresponding to the textual identifier of the zone.
- C The geometry of each feature SHALL be the geometry of the zone.

RECOMMENDATION 25

IDENTIFIE /rec/zone-geojson/id

- A The Feature id SHOULD have the same value as the zoneID property or use the 64-bit integer identifier.

RECOMMENDATION 26

IDENTIFIE /rec/zone-geojson/mid-points

- A For DGGRSs not in CRS84, the geometry SHOULD include intermediate points between the vertices of the zone geometry so as to accurately represent the shape of the zones.

15.6. Requirements Class “FG-JSON zone list encoding”

15.6.1. Overview

The FG-JSON zone list encoding requirements class defines support for encoding a DGGS Zone list response according to the [FG-JSON specification](#).

The response is a feature collection where each feature represents a zone in the list. The geometry of the zone should be polygons or multipolygons (e.g., in the case of zone geometry which must be split on the anti-meridian or pole). The zone identifier is represented in the `id` field of each feature.

While not intended to efficiently exchange zone list, as the response carries the geometry of the zones which could easily be computed client-side which takes considerable bandwidth and is not necessary for a DGGS client working natively with the same DGGRS, this requirement class provides an easy way to readily visualize the response in a variety of tools. This requirements class is therefore intended for convenience, demonstration and educational purposes.

REQUIREMENTS CLASS 22: REQUIREMENTS CLASS FG-JSON ZONE LIST

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-fgjson>

TARGET TYPE Web API

CONFORMANCE CLASS Conformance class A.21: <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-fgjson>

REQUIREMENTS CLASS 22: REQUIREMENTS CLASS FG-JSON ZONE LIST

PREREQUISITES

OGC 21-045r1

<https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query>

REQUIREMENT 33

IDENTIFI /req/zone-fgjson/content

- A Every 200 response of the server for zone query with the media type application/fg+json SHALL be a Features & Geometry JSON document consisting of a FeatureCollection, where every Feature represents a single zone.
- B Every feature SHALL have a zoneID property corresponding to the textual identifier of the zone.
- C The geometry of each feature SHALL be the geometry of the zone.

RECOMMENDATION 27

IDENTIFI /rec/zone-fgjson/id

- A The Feature id SHOULD have the same value as the zoneID property or use the 64-bit integer identifier.

RECOMMENDATION 28

IDENTIFI /rec/zone-fgjson/mid-points

- A For DGGRSs not in CRS84, the geometry SHOULD include intermediate points between the vertices of the zone geometry so as to accurately represent the shape of the zones.

15.7. Requirements Class “GeoTIFF zone list encoding”

15.7.1. Overview

The GeoTIFF zone list encoding requirements class defines support for encoding a DGGS Zone list response according to the [OGC GeoTIFF standard](#), intended primarily for DGGS with rectangular zones.

The response is a 2D gridded coverage where each cell is a zone in the list, in the coordinate reference system of that DGGS.

For DGGS with non-rectangular zones, the resolution would need to be higher than a single pixel per the most detailed zone to be returned in order to be able to recognize the zone geometry, and would therefore be very sub-optimal. While for rectangular zones it would be easy to identify zones with a one-to-one correspondence, recognizing non-rectangular zones would be significantly more difficult.

While not intended to efficiently exchange zone list, this requirement class provides an easy way to readily visualize the response in a variety of tools. This requirements class is therefore intended for convenience, demonstration and educational purposes.

REQUIREMENTS CLASS 23: REQUIREMENTS CLASS GEOTIFF ZONE LIST

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-geotiff
TARGET TYPE	Web API
PREREQUISITES	TIFF V6.0 GeoTIFF https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query

REQUIREMENT 34

IDENTIFI /req/zone-geotiff/content

- A Every 200 response of the server for zone query with the media type `image/tiff` SHALL be a Geo TIFF document representing the zones matching the query in a geo-referenced image where each zone corresponds to at least one pixel.
- B The GeoTIFF SHALL be encoded as Pixel-Is-Area.

RECOMMENDATION 29

IDENTIFIE /rec/zone-geotiff/crs

- A The CRS of the response SHOULD be consistent with either the DGGRS or the underlying geographic CRS (e.g., CRS84).

RECOMMENDATION 30

IDENTIFIE /rec/zone-geotiff/values

- A The value of the pixel SHOULD be a 64-bit integer identifier representing the zone, if the DGGRS provides for such an identifier.

RECOMMENDATION 31

IDENTIFIE /rec/zone-geotiff/non-rectilinear

- A For DGGRS where the zones do not correspond to a rectilinear structure, the resolution of the response image SHOULD be high enough so that the shape of the zone geometry is recognizable.

16

REQUIREMENTS CLASS FOR API DEFINITION OPERATION IDS

REQUIREMENTS CLASS FOR API DEFINITION OPERATION IDS

This standard does not mandate any particular API definition language, but if the API is described using a definition language supporting operation identifiers, such as OpenAPI 3.0, allowing to associate the functionality described in these requirements with an operation defined in the language, this requirement class defines how this is achieved.

16.1. Overview

REQUIREMENTS CLASS 24

TARGET TYPE Web API

PREREQUISITE <https://www.opengis.net/spec/ogcapi-common-1/1.0/req/landing-page>

LABEL <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/operation-ids>

16.2. Requirements

16.2.1. Operation IDs

REQUIREMENT 35

LABEL /req/operation-ids/

STATEMENT For specifying the operation identifiers associated with the capabilities defined in OGC API – DGGS

A The API definition SHALL identify the supported operations defined in this Standard using the identifier suffixes defined in table Table 4.

Table 4 – API operation identifier suffixes

ORIGIN	RESOURCE	OPERATION ID SUFFIXES
<i>With the origins described in this document</i>		
DataSet ⁴	DGGRS List ¹	.dataset.getDGGRSList
DataSet ⁴	DGGRS Description ¹	.dataset.getDGGRS
DataSet ⁴	DGGRS Zones ²	.dataset.getDGGRSZones
DataSet ⁴	DGGRS Zone Information ¹	.dataset.getDGGRSZoneInfo
DataSet ⁴	DGGRS Zone Data ³	.dataset.getDGGRSZoneData
Collection ⁵	DGGRS List ¹	.collection.getDGGRSList
Collection ⁵	DGGRS Description ¹	.collection.getDGGRS
Collection ⁵	DGGRS Zones ²	.collection.getDGGRSZones
Collection ⁵	DGGRS Zone Information ¹	.collection.getDGGRSZoneInfo
Collection ⁵	DGGRS Zone Data ³	.collection.getDGGRSZoneData
<i>With other potential origins⁶</i>		
other	DGGRS List ¹	#.getDGGRSList
other	DGGRS Description ¹	#.getDGGRS
other	DGGRS Zones ²	#.getDGGRSZones
other	DGGRS Zone Information ¹	#.getDGGRSZoneInfo
other	DGGRS Zone Data ³	#.getDGGRSZoneData
¹ The DGGRS List (.../dggs), DGGRS Description (.../dggs/{dggrsId}) and DGGRS Zone Information (.../dggs/{dggrsId}/zones/{zoneId}) resources are defined in requirements class “Core”.		
² The DGGRS Zones resource (.../dggs/{dggrsId}/zones) is defined in the “Zone Query” requirements class.		
³ The DGGRS Zone Data resource (.../dggs/{dggrsId}/zones/{zoneId}/data) is defined in the “Data Retrieval” requirements class.		

ORIGIN	RESOURCE	OPERATION ID SUFFIXES
⁴	The DataSet origin is defined in requirements class “Root DGGS” and depends on OGC API – Common – Part 1: Core.	
⁵	The Collection origin is defined in requirements class “Collection DGGS” and depends on the Collections requirements class defined in OGC API – Common – Part 2: Geospatial data.	
⁶	#	represents an optional origin that could be defined in another relevant standard.



A

ANNEX A (NORMATIVE) CONFORMANCE CLASS ABSTRACT TEST SUITE

ANNEX A (NORMATIVE)

CONFORMANCE CLASS ABSTRACT TEST SUITE

A.1. Conformance Class “Core”

CONFORMANCE CLASS A.1

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/core>

**REQUIREMENTS
CLASS** <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/core>

TARGET TYPE Web API

**CONFORMANCE
TESTS**
Abstract test A.1-1: /req/core/dggrs-list
Abstract test A.1-2: /req/core/dggrs-info
Abstract test A.1-3: /req/core/zone-info

A.1.1. Abstract Test for Requirement Listing available DGGRS

ABSTRACT TEST A.1

IDENTIFIER /conf/core/dggrs-list

REQUIREMENT Abstract test A.1-1: /req/core/dggrs-list

TEST PURPOSE Verify that the implementation supports listing the available DGGRS

TEST METHOD
Given: When: Then:
- assert that
- assert that

A.2. Conformance Class “Data Retrieval”

CONFORMANCE CLASS A.2

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-retrieval
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-retrieval
TARGET TYPE	Web API

A.3. Conformance Class “Zone Query”

CONFORMANCE CLASS A.3

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-query
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-query
TARGET TYPE	Web API

A.4. Conformance Class “Filtering Zone Queries with CQL2”

CONFORMANCE CLASS A.4

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/cql2-query
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/cql2-query
TARGET TYPE	Web API

A.5. Conformance Class “Root DGGS”

CONFORMANCE CLASS A.5

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/root-dggs
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/root-dggs
TARGET TYPE	Web API

A.6. Conformance Class “Collection DGGS”

CONFORMANCE CLASS A.6

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/collection-dggs
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/collection-dggs
TARGET TYPE	Web API

A.7. Conformance Class “Data Subsetting”

CONFORMANCE CLASS A.7

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-subsetting
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-subsetting
TARGET TYPE	Web API

A.8. Conformance Class “Data Custom Depths”

CONFORMANCE CLASS A.8

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-custom-depths
REQUIREMENTS CLASS	https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-custom-depths
TARGET TYPE	Web API

A.9. Conformance Class “DGGS-JSON encoding for Zone Data”

CONFORMANCE CLASS A.9

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-json
REQUIREMENTS CLASS	Requirements class 9: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-json
TARGET TYPE	Web API

A.10. Conformance Class “GeoJSON encoding for Zone Data”

CONFORMANCE CLASS A.10

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-geojson
REQUIREMENTS CLASS	Requirements class 12: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-geojson

CONFORMANCE CLASS A.10

TARGET TYPE Web API

A.11. Conformance Class “FG-JSON encoding for Zone Data”

CONFORMANCE CLASS A.11

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-fgjson>

REQUIREMENTS CLASS Requirements class 13: <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-fgjson>

TARGET TYPE Web API

A.12. Conformance Class “GeoTIFF encoding for Zone Data”

CONFORMANCE CLASS A.12

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-tiff>

REQUIREMENTS CLASS <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-tiff>

TARGET TYPE Web API

A.13. Conformance Class “netCDF encoding for Zone Data”

CONFORMANCE CLASS A.13

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-netcdf
REQUIREMENTS CLASS	Requirements class 14: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-netcdf
TARGET TYPE	Web API

A.14. Conformance Class “CoverageJSON encoding for Zone Data”

CONFORMANCE CLASS A.14

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-coveragejson
REQUIREMENTS CLASS	Requirements class 15: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-coveragejson
TARGET TYPE	Web API

A.15. Conformance Class “JPEG XL Encoding for Zone Data”

CONFORMANCE CLASS A.15

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-jpegxl
REQUIREMENTS CLASS	Requirements class 16: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-jpegxl
TARGET TYPE	Web API

A.16. Conformance Class “PNG encoding for Zone Data”

CONFORMANCE CLASS A.16

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/data-png
REQUIREMENTS CLASS	Requirements class 17: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/data-png
TARGET TYPE	Web API

A.17. Conformance Class “JSON encoding for Zone Data”

CONFORMANCE CLASS A.17

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-json
REQUIREMENTS CLASS	Requirements class 18: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-json
TARGET TYPE	Web API

A.18. Conformance Class “HTML encoding for Zone Listing”

CONFORMANCE CLASS A.18

IDENTIFIER	https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-html
REQUIREMENTS CLASS	Requirements class 19: https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-html
TARGET TYPE	Web API

A.19. Conformance Class “Binary 64-bit integer encoding for Zone Listing”

CONFORMANCE CLASS A.19

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-uint64>

REQUIREMENTS CLASS Requirements class 20: <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-uint64>

TARGET TYPE Web API

A.20. Conformance Class “GeoJSON encoding for Zone Listing”

CONFORMANCE CLASS A.20

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-geojson>

REQUIREMENTS CLASS Requirements class 21: <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-geojson>

TARGET TYPE Web API

A.21. Conformance Class “FG-JSON encoding for Zone Listing”

CONFORMANCE CLASS A.21

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-fgjson>

CONFORMANCE CLASS A.21

REQUIREMENTS CLASS Requirements class 22: <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-fgjson>

TARGET TYPE Web API

A.22. Conformance Class “GeoTIFF encoding for Zone Listing”

CONFORMANCE CLASS A.22

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/zone-tiff>

REQUIREMENTS CLASS <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/zone-tiff>

TARGET TYPE Web API

A.23. Conformance Class “Operation IDs”

CONFORMANCE CLASS A.23

IDENTIFIER <https://www.opengis.net/spec/ogcapi-dggs/1.0/conf/operation-ids>

REQUIREMENTS CLASS <https://www.opengis.net/spec/ogcapi-dggs-1/1.0/req/operation-ids>

TARGET TYPE Web API

B

ANNEX B (INFORMATIVE) DISCRETE GLOBAL GRID REFERENCE SYSTEM DEFINITIONS

B

ANNEX B (INFORMATIVE)

DISCRETE GLOBAL GRID REFERENCE SYSTEM DEFINITIONS

The following informative schema describes the expected response of the resource linked to by using the [ogc-rel:dggrs-definition] link relation from the DGGRS description, as specified by the Core requirement class. An important objective for this schema is to support establishing authoritative registries of DGGRSs providing a URI for a DGGRS corresponding to a specific definition.

Note that this schema is preliminary, and a normative version may be defined by a later version of this standard or by a future part of OGC Abstract Specification Topic 21. The schema may change to allow for better description of existing and new classes of DGGS.

The DGGRS definition consists of three main components:

- the definition of the hierarchy of discrete global grids (dggs), including any parameterization such as the spheroid or orientation, establishing both the topology as well as the geometry of every zone,
 - the Zonal Identifier Reference System (*zirs*), with textual identifiers being mandatory while 64-bit integer identifiers (which support the 64-bit integer zone list encoding requirement class) are optional,
 - the sub-zone ordering (*subZoneOrder*), which allows for retrieving zone data using e.g., DGGS-JSON at a zone-depth other than 0 (the values of sub-zones can be provided as a 1D array of values with a pre-established association to sub-zones).

B.1. JSON Schema for defining a DGGRS

```
{  
  "$schema": "https://json-schema.org/draft/2019-09/schema",  
  "description": "Discrete Global Grid System Reference System (DGGRS)  
Definition.",  
  "type": "object",  
  "required": [  
    "dggs",  
    "zirs".  
  ]  
}
```

```

        "subZoneOrder"
    ],
    "properties": {
        "title": {
            "type": "string"
        },
        "description": {
            "type": "string"
        },
        "uri": {
            "type": "string",
            "format": "uri",
            "description": "The authoritative URI associated with this DGGRS definition"
        },
        "dggs": {
            "type": "object",
            "description": "The hierarchical series of Discrete Global Grid upon which this DGGRS is based, including any parameters.",
            "properties": {
                "definition": {
                    "description": "The base definition of the hierarchical series of Discrete Global Grid, which may be parameterized.",
                    "type": "object",
                    "required": [
                        "spatialDimensions",
                        "temporalDimensions"
                    ],
                    "properties": {
                        "crs": {
                            "allOf": [
                                {
                                    "description": "The native Coordinate Reference System (CRS) in which the geometry of the zones for this DGGS is defined."
                                },
                                {
                                    "anyOf": [
                                        {
                                            "type": "string",
                                            "format": "uri",
                                            "example": "EPSG:7789"
                                        }
                                    ]
                                }
                            ]
                        },
                        "basePolyhedron": {
                            "type": "string",
                            "description": "The Type/Class of Polyhedron used to construct the Discrete Global Grid System - if it is constructed using a Base Polyhedron.",
                            "example": "icosahedron"
                        },
                        "refinementRatio": {
                            "description": "The ratio of the area of zones between two consecutive hierarchy level (the ratio of child zones to parent zones, also called the aperture).",
                            "example": 9,
                            "type": "integer"
                        },
                        "constraints": {
                            "type": "object",
                            "properties": {

```

```

        "cellAxisAligned": {
            "description": "Set to true if all edges of the geometry of
all zones are aligned with one of the axis of the `crs`.",
            "type": "boolean",
            "default": false
        },
        "cellConformal": {
            "type": "boolean",
            "default": false
        },
        "cellEquiAngular": {
            "type": "boolean",
            "default": false
        },
        "cellEquiDistant": {
            "type": "boolean",
            "default": false
        },
        "cellEqualSized": {
            "description": "Set to true if the area of all zones is the
same for a particular zone geometry type of any specific discrete global grid
of the DGGS hierarchy.",
            "type": "boolean",
            "default": false
        }
    },
    "spatialDimensions": {
        "description": "Number of Spatial Dimensions defined by the
Discrete Global Grid System.",
        "example": 2,
        "type": "integer"
    },
    "temporalDimensions": {
        "description": "Number of Temporal Dimensions defined by the
Discrete Global Grid System.",
        "example": 0,
        "type": "integer"
    },
    "zoneTypes": {
        "type": "array",
        "items": {
            "type": "string",
            "enum": [
                "triangle",
                "square",
                "hexagon",
                "pentagon",
                "rhombus"
            ]
        },
        "example": [
            "hexagon",
            "pentagon"
        ]
    },
    "refinementStrategy": {
        "description": "The refinement strategy used by the Discrete
Global Grid System",
        "type": "array",
        "items": {
            "type": "string",
            "enum": [

```

```

        "centredChildCell",
        "nestedChildCell",
        "nodeCentredChildCell",
        "edgeCentredChildCell",
        "faceCentredChildCell",
        "solidCentredChildCell"
    ],
},
"example": [ "nestedChildCell" ]
}
}
},
"parameters": {
  "description": "The optional parameters establishing a very specific Discrete Global Grid System, where each zone has a well-defined geometry.",
  "type": "object",
  "properties": {
    "ellipsoid": {
      "type": "string",
      "format": "uri",
      "description": "Globe Reference System Identifier/Specification",
      "example": [
        "EPSG:7019"
      ]
    },
    "orientation": {
      "type": "object",
      "properties": {
        "latitude": {
          "description": "Reference Latitude in decimal degrees to fix the orientation of the polyhedron.",
          "example": 0,
          "type": "number"
        },
        "longitude": {
          "description": "Reference Longitude in decimal degrees to fix the orientation of the polyhedron.",
          "example": 0,
          "type": "number"
        },
        "description": {
          "type": "string"
        }
      },
      "required": [
        "longitude",
        "latitude"
      ]
    }
  }
},
"zirs": {
  "description": "The Zone Identifier Reference System used for this Discrete Global Grid System Reference System.",
  "type": "object",
  "required": [
    "textZIRS"
  ],
  "properties": {
    "textZIRS": {
      "description": "textual zone identifier indexing scheme",

```

```

    "type": "object",
    "required": [
        "description"
    ],
    "properties": {
        "description": {
            "type": "string",
            "examples": [
                "Topological Morton Code (Space Filling Curve) Identifier.  

With a Level 0 alphabetical identifier from 'A' to 'S' followed by a numeric  

reference from 1 to 9 for all subsequent levels representing the arrangement  

of child zones following a Morton (Z-code) subdivision of the parent zone. The  

length of the identifier represents the level of refinement.",
                "Universal Morton Code (Space Filling Curve) Identifier.  

An ellipsoidal bitwise concatenation of longitude and latitude direct  

position to form a direct Morton code. This can be used across multiple DGGS  

infrastructures to provide a common index structure that is fixed in nature  

regardless of the topological zone index used by each DGGS.",
                "An identifier comprised of three separate level, row and  

column components corresponding to an OGC 2D Tile Matrix Set tile identifier,  

where the individual component are represented by uppercase hexadecimal  

numbers separated by a hyphen.",
                "An identifier comprised of an uppercase hexadecimal letter  

representing a level (A for level 0, B for level 1...), followed by a number  

from 0 to 9 representing the root rhombus corresponding to the faces of an  

icosahedron, in a staircase order from the top-left to the bottom right of  

an ISEA planar projection after a 60 degrees clockwise rotation, followed  

by a hyphen, then by an uppercase hexadecimal number identifying a sub-zone  

starting to count from 0 in row-major order.",
                "An identifier comprised of an uppercase hexadecimal letter  

representing the ISEA9R level corresponding to the current even or immediate  

lower odd ISEA3H level (A for level 0, B for level 1...), followed by a number  

from 0 to 9 representing the root rhombus corresponding to the faces of an  

icosahedron, in a staircase order from the top-left to the bottom right of  

an ISEA planar projection after a 60 degrees clockwise rotation, followed  

by a hyphen, then by an uppercase hexadecimal number identifying a sub-zone  

starting to count from 0 in row-major order, followed by a second hyphen,  

then by a letter identifying a hexagonal or pentagonal zone intersecting  

the sub-rhombus: A: even level regular zone B: even level North pole zone C:  

even level South pole zone D: odd level zone centered on rhombus vertex E:  

odd level zone top-right of rhombus vertex F: odd level zone bottom-right of  

rhombus vertex G: odd level North pole zone H: odd level South pole zone\n"
            ]
        }
    ],
    "type": {
        "anyOf": [
            {
                "type": "string"
            },
            {
                "type": "string",
                "enum": [
                    "hierarchicalConcatenation",
                    "ogc2DTMSHexLevelRowCol",
                    "levelRootFaceHexRowMajorSubZone"
                ]
            }
        ]
    }
},
"uint64ZIRS": {
    "description": "64-bit unsigned integer zone indexing scheme",

```

```

    "type": "object",
    "required": [
        "description"
    ],
    "properties": {
        "description": {
            "type": "string",
            "examples": [
                "A 64-bit integer with the 30 least significant bits corresponds to a column, the next 29 bits corresponding to a row, and the 5 most significant bits correspond to a level of an OGC 2D Tile Matrix Set identifier, with individual components using little endian.",
                "A 64-bit integer with the 3 least significant bits corresponding to a hexagonal or pentagonal zone intersecting a sub-rhombus: 0: even level regular zone 1: even level North pole zone 2: even level South pole zone 3: odd level zone centered on rhombus vertex 4: odd level zone top-right of rhombus vertex 5: odd level zone bottom-right of rhombus vertex 6: odd level North pole zone 7: odd level South pole zone, the next 51 bits corresponding to a sub-rhombus index, the next 4 bits corresponding to a root rhombus, the next 5 bits corresponding to an associated ISEA9R level, and the last most significant bit always 0 for a valid zone identifier.\n"
            ]
        },
        "type": {
            "anyOf": [
                {
                    "type": "string"
                },
                {
                    "type": "string",
                    "enum": [
                        "ogc2DTMSHexLevelRowCol"
                    ]
                }
            ]
        }
    }
},
"subZoneOrder": {
    "description": "The ordering used for this Discrete Global Grid System Reference System when encoding the values associated with sub-zones at any given depth relative to a parent zone.",
    "type": "object",
    "required": [
        "description"
    ],
    "properties": {
        "description": {
            "type": "string",
            "examples": [
                "The zones are ordered in tightly packed scanlines. Considering the ISEA planar projection, for odd level parent, zones are ordered left to right along a scanline and scanlines are ordered from top to bottom. For an even level parent, zones are ordered top to bottom along a scanline and scanlines are ordered from left to right. For an odd depth, scanlines start along a hexagon edge, whereas for even depths, scanlines start on a hexagon vertex."
            ]
        },
        "type": {
            "anyOf": [

```

```
        {
          "type": "string"
        },
        {
          "type": "string",
          "enum": [
            "scanline",
            "spiralFromCenter",
            "mortonCurve",
            "hilbertCurve"
          ]
        }
      ]
    }
  }
}
```

Figure B.1 – JSON Schema for the DGGRS Definition

The following example JSON DGGRS definitions conform to this schema.

B.2. Example DGGRS definitions

B.2.1. ISEA9R DGGRS definition

The following DGGRS is for an axis-aligned and equal-area DGGS based on the [Icosahedral Snyder Equal-Area \(ISEA\)](#) planar projection using rhombuses with a refinement ratio of 9. When the ISEA projection is rotated 60 degrees, sheared horizontally by 30 degrees and units are mapped to a 5×6 space, the zones become square and their edges are aligned with the CRS axes, while remaining equal-area. A [2D Tile Matrix Set](#) can also be defined in this transformed CRS, allowing for compatibility with [OGC API – Tiles](#), [WMTS](#) and traditional client and visualization software with no built-in DGGS functionality. This transformed CRS no longer preserves angles and distances, although the topology, indexing and surface geometry on the Earth model remains the same as in the original ISEA CRS where angles and distances are preserved.

```
{  
  "title": "ISEA9R",  
  "description": "An ISEA9R Discrete Global Grid Reference System using the  
standard ISEA orientation and WGS84 authalic sphere, a {level}{rootRhombus}-  
{hexSubZone} indexing system, and scanline-based sub-zone ordering. The ten  
root rhombuses are formed by combining two icosahedron triangles at their base.  
  Depending on whether the ISEA planar CRS is rotated, sheared and scaled or  
not, the geometry of the zones are either squares or rhombuses, and the zone  
edges are either axis-aligned, or the angles and distances are preserved. In  
either case, the topology, indexing and surface geometry on the Earth model  
remains the same. The ISEA9R DGGS is a dual of the ISEA3H DGGS even levels (a  
vertex/node in ISEA9R is the centroid of an ISEA3H zone).",  
  "uri": "https://www.opengis.net/def/dggrs/OGC/1.0/ISEA9R",
```

```

"links": [ { "rel": "describedby", "href": "https://portal.ogc.org/files/?artifact_id=107432" } ],
  "dggs": {
    "definition": {
      "spatialDimensions": 2,
      "temporalDimensions": 0,
      "crs": "https://www.opengis.net/def/crs/OGC/0/ISEAr60hs30",
      "links": [
        { "rel": "related", "href": "https://doi.org/10.3138/27H7-8K88-4882-1752" },
        { "rel": "related", "href": "https://proj.org/en/9.3/operations/projections/isea.html" }
      ],
      "basePolyhedron": "icosahedron",
      "refinementRatio": 9,
      "refinementStrategy": [ "nestedChildCell" ],
      "constraints": {
        "cellAxisAligned": true,
        "cellEqualSized": true
      },
      "zoneTypes": [ "square" ],
    },
    "parameters": {
      "ellipsoid": "Authalic sphere based on [EPSG:7030] (WGS84) -- NOTE: No identifier defined yet? [EPSG:7048] exists for Authalic sphere based on GRS80 [EPSG:7019]",
      "orientation": {
        {
          "description": "Standard ISEA orientation with a single icosahedron vertex falling on land",
          "latitude": 58.28252559,
          "longitude": 11.25
        }
      }
    },
    "zirs": {
      "textZIRS": {
        "description": "An identifier comprised of an uppercase hexadecimal letter representing a level (A for level 0, B for level 1...), followed by a number from 0 to 9 representing the root rhombus corresponding to the faces of an icosahedron, in a staircase order from the top-left to the bottom right of an ISEA planar projection after a 60 degrees clockwise rotation, followed by a hyphen, then by an uppercase hexadecimal number identifying a sub-zone starting to count from 0 in row-major order.",
        "type": "levelRootFaceHexRowMajorSubZone"
      },
      "uint64ZIRS": {
        "description": "A 64-bit integer with the 30 least significant bits corresponds to a column, the next 29 bits corresponding to a row, and the 5 most significant bits correspond to a level of an OGC 2D Tile Matrix Set identifier, with individual components using little endian.",
        "type": "ogc2DTMSHexLevelRowCol"
      }
    },
    "subZoneOrder": {
      "description": "The zones are ordered as scanlines in row-major order, left to right, then top to bottom, based on a CRS derived from the planar ISEA projection after rotating it 60 degrees clockwise and applying a 30 degrees horizontal shear.",
      "type": "scanline"
    }
  }
}

```

}

Figure B.2 – DGGRS Definition for ISEA9R




Figure B.3 – The ISEA9R squared root rhombuses (level 0) in the rotated and sheared ISEA planar CRS mapped to a 5×6 space whose axes are aligned with the zone edges, compatible with a 2DTMS definition (imagery from NASA Earth Observatory's [Blue Marble: Next Generation](#))




Figure B.4 – The ISEA9R level 0 zone identifiers, shown in the original ISEA planar CRS (GEBCO 2014 bathymetry)




Figure B.5 – The ISEA9R level 1 zone identifiers, shown in the original ISEA planar CRS (GEBCO 2014 bathymetry)

B.2.2. ISEA3H DGGRS definition

The following DGGRS is for an ISEA3H DGGS, also based on the ISEA planar projection, with hexagonal and pentagonal zones, and a refinement ratio of 3, using a zone reference system based in part on its dual relationship with the ISEA9R DGGS. The DGGS is considered equal-

area, although the 12 pentagonal zones at any level occupy 5/6th of the area of hexagonal zones.

```
{  
    "title": "ISEA3H",  
    "description": "An ISEA3H Discrete Global Grid Reference System using the standard ISEA orientation and WGS84 authalic sphere, a zone indexing system based on an ISEA9R, and scanline-based ordering",  
    "uri": "https://www.opengis.net/def/dggrs/OGC/1.0/ISEA3H",  
    "links": [ { "rel": "describedby", "href": "https://portal.ogc.org/files/?artifact_id=107432" } ],  
    "dggs": {  
        "definition": {  
            "spatialDimensions": 2,  
            "temporalDimensions": 0,  
            "crs": "https://www.opengis.net/def/crs/OGC/0/ISEA",  
            "links": [  
                { "rel": "related", "href": "https://doi.org/10.3138/27H7-8K88-4882-1752" },  
                { "rel": "related", "href": "https://proj.org/en/9.3/operations/projections/isea.html" }  
            ],  
            "basePolyhedron": "icosahedron",  
            "refinementRatio": 3,  
            "refinementStrategy": [ "nestedChildCell", "nodeCentredChildCell" ],  
            "constraints": {  
                "cellEqualSized": true,  
                "cellEquiAngular": true,  
                "cellEquiDistant": true  
            },  
            "zoneTypes": [ "hexagon", "pentagon" ]  
        },  
        "parameters": {  
            "ellipsoid": "Authalic sphere based on [EPSG:7030] (WGS84) -- NOTE:  
No identifier defined yet? [EPSG:7048] exists for Authalic sphere based on  
GRS80 [EPSG:7019]",  
            "orientation": {  
                "description": "Standard ISEA orientation with a single  
icosahedron vertex falling on land",  
                "latitude": 58.28252559,  
                "longitude": 11.25  
            }  
        }  
    },  
    "zirs": {  
        "textZIRS": {  
            "description": "An identifier comprised of an uppercase hexadecimal letter representing the ISEA9R level corresponding to the current even or immediate lower odd ISEA3H level (A for level 0, B for level 1...), followed by a number from 0 to 9 representing the root rhombus corresponding to the faces of an icosahedron, in a staircase order from the top-left to the bottom right of an ISEA planar projection after a 60 degrees clockwise rotation, followed by a hyphen, then by an uppercase hexadecimal number identifying a sub-zone starting to count from 0 in row-major order, followed by a second hyphen, then by a letter identifying a hexagonal or pentagonal zone intersecting the sub-rhombus: A: even level regular zone B: even level North pole zone C: even level South pole zone D: odd level zone centered on rhombus vertex E: odd level zone top-right of rhombus vertex F: odd level zone bottom-right of rhombus vertex G: odd level North pole zone H: odd level South pole zone\\n",  
        }  
    }  
}
```

```

        "type": "levelRootFaceHexRowMajorSubZone"
    },
    "uint64ZIRS": {
        "description": "A 64-bit integer with the 3 least significant bits corresponding to a hexagonal or pentagonal zone intersecting a sub-rhombus: 0: even level regular zone 1: even level North pole zone 2: even level South pole zone 3: odd level zone centered on rhombus vertex 4: odd level zone top-right of rhombus vertex 5: odd level zone bottom-right of rhombus vertex 6: odd level North pole zone 7: odd level South pole zone, the next 51 bits corresponding to a sub-rhombus index, the next 4 bits corresponding to a root rhombus, the next 5 bits corresponding to an associated ISEA9R level, and the last most significant bit always 0 for a valid zone identifier."
    }
},
"subZoneOrder": {
    "description": "The zones are ordered in tightly packed scanlines. Considering the ISEA planar projection, for odd level parent, zones are ordered left to right along a scanline and scanlines are ordered from top to bottom. For an even level parent, zones are ordered top to bottom along a scanline and scanlines are ordered from left to right. For an odd depth, scanlines start along a hexagon edge, whereas for even depths, scanlines start on a hexagon vertex.",
    "type": "scanline"
}
}

```

Figure B.6 – DGGRS Definition for ISEA3H using indexing based on ISEA9R




Figure B.7 – The ISEA3H level 0 zones and associated identifiers (derived from ISEA9R level 0), shown on an ISEA planar projection ([GEBCO 2014 bathymetry](#))




Figure B.8 – The ISEA3H level 1 zones and associated identifiers (derived from ISEA9R level 0), shown on an ISEA planar projection (GEBCO 2014 bathymetry)




Figure B.9 – The ISEA3H level 2 zones and associated identifiers (derived from ISEA9R level 1), shown on an ISEA planar projection (GEBCO 2014 bathymetry)

C

ANNEX C (INFORMATIVE) EXAMPLES

ANNEX C (INFORMATIVE) EXAMPLES

This annex provides a set of examples illustrating requests and responses for retrieving DGGS zone data and performing zone queries using capabilities defined by this DGGS API.

C.1. Collection description

DGGS resources can be attached to an *OGC API – Common – Part 2* collection origin. The following global GEBCO 2014 bathymetry collection will be used as an example:

<https://maps.gnosis.earth/ogcapi/collections/gebco>

An example JSON response for this collection description resource, as defined by Common – Part 2 and the Collection DGGS Requirement Class, is presented below, including a link to the list of available DGGRSSs:

```
{
  "id" : "gebco",
  "title" : "GEBCO 2014",
  "description" : "General Bathymetric Chart of the Oceans (2014)",
  "attribution" : "General Bathymetric Chart of the Oceans (<a href='https://www.gebco.net/news_and_media/gebco_2014_grid.html'>GEBCO_2014</a>)",
  "extent" : {
    "spatial" : {
      "bbox" : [ [ -180, -90, 180, 90 ] ],
      "grid" : [
        { "cellsCount" : 65537, "resolution" : 0.0054931640625 },
        { "cellsCount" : 32769, "resolution" : 0.0054931640625 }
      ]
    } },
  "minScaleDenominator" : 2183915.0938621787354,
  "minCellSize" : 0.0054931640625,
  "links" : [
    { "rel" : "self", "title" : "Information about this GEBCO data collection",
      "href" : "/ogcapi/collections/gebco"
    },
    { "rel" : "[ogc-rel:schema]", "title" : "Schema",
      "href" : "/ogcapi/collections/gebco/schema"
    },
    { "rel" : "[ogc-rel:queryables]", "title" : "Queryables",
      "href" : "/ogcapi/collections/gebco/queryables"
    },
  ],
}
```

```

        { "rel" : "[ogc-rel:dggrs-list]", "title" : "Available DGGRSs for this
GEBCO data collection",
          "href" : "/ogcapi/collections/gebco/dggs"
        }
      ]
    }
  ]
}

```

C.2. Listing available DGGRSs

Whether accessing DGGS resources for the root of an API/dataset or for a particular collection, the first DGGS-specific request made by a client would be to list the available DGGRSs. Following the link obtained from the previous example response, a client can determine which DGGRSs are supported by the API at that end-point:

<https://maps.gnosis.earth/ogcapi/collections/gebco/dggs>

An example JSON response for this DGGRS list, as defined by the Core requirement class, is presented below:

```

{
  "links" : [
    { "rel" : "[ogc-rel:geodata]", "href" : "/ogcapi/collections/gebco" }
  ],
  "dggrs" : [
    {
      "id" : "GNOSISGlobalGrid",
      "title" : "GNOSIS Global Grid",
      "uri" : "[ogc-dggrs:GNOSISGlobalGrid]",
      "links" : [
        { "rel" : "self", "title" : "GNOSISGlobalGrid DGGRS for GEBCO",
          "href" : "/ogcapi/collections/gebco/dggs/GNOSISGlobalGrid" },
        { "rel" : "[ogc-rel:dggrs-definition]", "title" :
"GNOSISGlobalGrid DGGRS definition",
          "href" : "/ogcapi/dggrs/GNOSISGlobalGrid"
        }
      ]
    },
    {
      "id" : "ISEA9R",
      "title" : "ISEA Aperture 9 Rhombic",
      "uri" : "[ogc-dggrs:ISEA9R]",
      "links" : [
        { "rel" : "self", "title" : "ISEA9R DGGRS for GEBCO",
          "href" : "/ogcapi/collections/gebco/dggs/ISEA9R"
        },
        { "rel" : "[ogc-rel:dggrs-definition]", "title" : "ISEA9R DGGRS
definition",
          "href" : "/ogcapi/dggrs/ISEA9R"
        }
      ]
    },
    {
      "id" : "ISEA3H",
      "title" : "ISEA Aperture 3 Hexagonal",
      "uri" : "[ogc-dggrs:ISEA3H]"
      "links" : [

```

```

        {
          "rel" : "self", "title" : "ISEA3H DGGRS for GEBCO",
          "href" : "/ogcapi/collections/gebco/dggs/ISEA3H"
        },
        {
          "rel" : "[ogc-rel:dggrs-definition]", "title" : "ISEA3H DGGRS
definition",
          "href" : "/ogcapi/dggrs/ISEA3H"
        }
      ]
    }
}

```

See annex B for examples of DGGRS definition responses which the client could obtain by following the [ogc-rel:dggrs-definition] links.

C.3. Retrieving the description of a specific DGGRS

A client would then select a particular DGGRS of which it already has built-in knowledge, possibly using a software library implementing support for one or more DGGRS available from the server.

NOTE: This DGGS API is intended primarily for client / server exchanges where both parties are familiar and can efficiently deal with the same DGGRS. Use cases where the client itself also acts as a server as part of a data integration workflows are particularly relevant, where the combination of advanced spatial queries with the ability to request data for specific zones of interest can potentially greatly accelerate analytic processing through parallel distributed processing and lazy evaluation.

As a fallback, a client without native support for a particular DGGRS can still retrieve and interpret data from a server implementing support for both zone queries and data retrieval by performing a two-steps operation. First, the client can perform a zone query for an area of interest using the bbox query parameter. Then, the client can request data for the zones returned by this query in a georeferenced encoding which it understands and which is not tightly coupled with the DGGS (excluding e.g.,the DGGS-JSON encoding), such as GeoJSON or GeoTIFF. However, for such use cases, OGC API – DGGS does not present significant advantages over other OGC API data access mechanisms such as [OGC API – Coverages](#), [OGC API – Features](#) or [OGC API – Tiles](#).

In this example, the client selects the ISEA3H DGGRS (because it has built-in support for it) and follows the link to obtain a complete description of the DGGRS:

\<https://maps.gnosis.earth/ogcapi/collections/gebco/dggs/ISEA3H>

An example JSON response for this DGGRS description, as defined by the Core requirement class, is presented below. Note how the description is more comprehensive than the summary description included for each item in the previous DGGRS list response, including a description, a default (relative) depth as well as additional links and link templates.

```
{
  "id" : "ISEA3H",
  "title" : "ISEA Aperture 3 Hexagonal",
  "description" : "The ISEA Aperture 3 Hexagonal DGGRS contains data for the ISEA Aperture 3 Hexagonal feature. It includes a description of the feature, its geometry, and various properties such as depth, aperture size, and material type. The feature is located in the ISEA3H collection and is defined by the hexagonal aperture shape.",

  "defaultDepth" : 1000,
  "links" : [
    {
      "rel" : "self", "title" : "ISEA Aperture 3 Hexagonal DGGRS", "href" : "/ogcapi/dggrs/ISEA3H"
    },
    {
      "rel" : "[ogc-rel:dggrs-definition]", "title" : "ISEA Aperture 3 Hexagonal DGGRS Definition", "href" : "/ogcapi/collections/gebco/dggs/ISEA3H"
    }
  ]
}
```

```

    "description" : "A Discrete Global Grid Reference System based on the Icosahedral Snyder Equal Area projection, with aperture 3 hexagonal zones, using an indexing scheme based on ISEA9R.",
    "uri" : "[ogc-dggrs:ISEA3H]",
    "defaultDepth": 10,
    "links" : [
        { "rel" : "self", "title" : "ISEA3H DGGRS for GEBCO",
          "href" : "/ogcapi/collections/gebco/dggs/ISEA3H"
        },
        { "rel" : "[ogc-rel:dggrs-definition]", "title" : "ISEA3H DGGRS definition",
          "href" : "/ogcapi/dggrs/ISEA3H"
        },
        { "rel" : "[ogc-rel:dggrs-zone-query]", "title" : "ISEA3H DGGRS Zone Query",
          "href" : "/ogcapi/collections/gebco/dggs/ISEA3H/zones"
        },
        { "rel" : "[ogc-rel:geodata]", "href" : "/ogcapi/collections/gebco" }
    ],
    "linkTemplates" : [
        {
            "rel" : "[ogc-rel:dggrs-zone-info]",
            "title" : "DGGRS zone information for a particular ISEA3H zone",
            "href" : "/ogcapi/collections/gebco/dggs/ISEA3H/zones/{zoneId}"
        },
        {
            "rel" : "[ogc-rel:dggrs-zone-data]",
            "title" : "Data retrieval for a particular ISEA3H zone",
            "href" : "/ogcapi/collections/gebco/dggs/ISEA3H/zones/{zoneId}/data"
        }
    ]
}

```

C.4. Simple zone queries

Having selected a particular DGGRS, one use case for the API is for a client to perform spatial queries by requesting a list of zones. The simplest case is to simply request a list of all available zones, which in the case of a particular collection implies zones for which the collection has data.

If no zone-level parameter is provided, the server is free to pick a default zone level for such queries, which would result in a reasonable number of zones returned, based on the area and resolution of the data collection. In this example, the client will explicitly request a list of zones at refinement level 1.

By default, if compact-zones=false is not specified by the client, zone queries are compacted, meaning that if all sub-zones of a parent zone would be included in the response, they get replaced by that parent zone so that fewer zones need to be enumerated. This can result in zones of a lower refinement level being returned than the requested zone-level. A full globe response would therefore always result in the list of all zones of refinement level 0. In this example, the client will explicitly set compact-zones=false.

Following the [ogc-rel:dggrs-zone-query] link, specifying these parameters, and negotiating a JSON zone list response using an Accept: application/json header, the client requests from the end-point:

\https://maps.gnosis.earth/ogcapi/collections/gebco/dggs/ISEA3H/zones?zone-level=1&compact-zones=false

An example JSON response for this Zone Query JSON, as defined by the Zone Query requirement class, is presented below:

```
{
  "zones" : [
    "A0-0-D", "A0-0-E", "A0-0-F", "A0-0-G", "A1-0-D", "A1-0-E",
    "A1-0-F", "A2-0-D", "A2-0-E", "A2-0-F", "A3-0-D", "A3-0-E",
    "A3-0-F", "A4-0-D", "A4-0-E", "A4-0-F", "A5-0-D", "A5-0-E",
    "A5-0-F", "A6-0-D", "A6-0-E", "A6-0-F", "A7-0-D", "A7-0-E",
    "A7-0-F", "A8-0-D", "A8-0-E", "A8-0-F", "A9-0-D", "A9-0-E",
    "A9-0-F", "A9-0-H"
  ],
  "links" : [
    { "rel" : "[ogc-rel:dggrs]", "title" : "ISEA3H DGGS for GEBCO",
      "href" : "/ogcapi/collections/gebco/dggs/ISEA3H"
    },
    { "rel" : "[ogc-rel:dggrs-definition]", "title" : "ISEA3H DGGS definition",
      "href" : "/ogcapi/dggrs/ISEA3H"
    },
    { "rel" : "[ogc-rel:geodata]", "href" : "/ogcapi/collections/gebco" }
  ],
  "linkTemplates" : [
    { "rel" : "[ogc-rel:dggrs-zone-data]", "title" : "ISEA3H data for GEBCO",
      "href" : "/ogcapi/collections/gebco/dggs/ISEA3H/zones/{zoneId}/data",
    }
  ]
}
```

The server returned all 32 zones of ISEA3H level 1 (which corresponds to the traditional soccer ball pattern), because the collection has global coverage.

To request a list of zones for an area of interest, the bbox or subset query parameter can be used. For restricting the same zone query to a bounding box area from (40°N, 30°E) to (60°N,50°E), the client could make either of the following requests:

\https://maps.gnosis.earth/ogcapi/collections/gebco/dggs/ISEA3H/zones?
bbox=30,40,50,60&zone-level=1&compact-zones=false

and obtain the following response (negotiating a JSON zone list again):

```
{
  "zones" : [ "A0-0-E", "A0-0-G", "A4-0-E", "A6-0-E", "A6-0-F", "A8-0-D", "A8-0-E" ],
  "links" : [
    { "rel" : "[ogc-rel:dggrs]", "title" : "ISEA3H DGGS for GEBCO",
      "href" : "/ogcapi/collections/gebco/dggs/ISEA3H"
    },
    { "rel" : "[ogc-rel:dggrs-definition]", "title" : "ISEA3H DGGS definition",
      "href" : "/ogcapi/dggrs/ISEA3H"
    },
    { "rel" : "[ogc-rel:geodata]", "href" : "/ogcapi/collections/gebco" }
  ]
}
```

```
],
  "linkTemplates" : [
    { "rel" : "[ogc-rel:dggrs-zone-data]", "title" : "ISEA3H data for GEBCO",
      "href" : "/ogcapi/collections/gebco/dggs/ISEA3H/zones/{zoneId}/data",
    }
  ]
}
```

This time, the server returned 7 zones of ISEA3H level 1.

D

ANNEX D (INFORMATIVE) REVISION HISTORY

ANNEX D (INFORMATIVE) REVISION HISTORY

Table D.1

DATE	RELEASE EDITOR	PRIMARY CLAUSES MODIFIED	DESCRIPTION
2021-05-17	0.1	Matthew Purss	all initial version
2022-07-22	0.2	Jerome St Louis	all Renamed Part 1 to core – github commit – 316d37f
2022-07-22	0.3	Jerome St Louis	all Initial set up of conformance classes clauses – github commit – b76073c
2022-07-26	0.4	Gobe Hobona	all Fixes problem that was breaking auto-build – github commit – a13c2a8
2022-10-04	0.5	Jerome St Louis	7-Data Retrieval Initial take at Data Retrieval Conformance Class – github commit – b67f290
2022-11-11	0.6	Jerome St Louis	7-Data Retrieval Split multi-done retrieval into separate conformance class – github commit – 06a4260
2022-11-11	0.7	Jerome St Louis	8-zone query Initial progress on Zone Query conformance class – github commit – a208502
2022-11-11	0.8	Jerome St Louis	21-038; 0-front material Added preface, abstract, Jerome added as editor – github commit – 71e76c6
2022-11-11	0.9	Jerome St Louis	7-Data Retrieval Clarification regarding resolution – github commit – c43bfad
2022-11-11	0.10	Jerome St Louis	8-zone query Clarifications – github commit – cee3685
2023-02-17	0.11	Jerome St Louis	7-Data Retrieval Added zone-depth parameter – github commit – 2b8fa58
2024-06-18	1.0. Orc1	Jerome St Louis	all Initial draft ready for OAB review



BIBLIOGRAPHY



BIBLIOGRAPHY

1. Robert Thomas, Sara Saeedi: OGC 23-010, *Towards a Federated Marine SDI: Connecting Land and Sea to Protect the Arctic Environment Engineering Report*. Open Geospatial Consortium (2023). <http://www.opengis.net/doc/PER/FMSDI3>.
2. Robert Gibb, Byron Cochrane, Matthew Purss: OGC 20-039r2, *OGC Testbed-16: DGGS and DGGS API Engineering Report*. Open Geospatial Consortium (2021). <http://www.opengis.net/doc/PER/t16-D017>.
3. Jérôme Jacovella-St-Louis, Flexible real-time data processing and visualization workflows emerging from OGC API modules (Draft), OGC 21-033 (2021). <https://maps.ecere.com/moaw/DiscussionPaper-Draft3.pdf>
4. Universal Binary JSON Specification. <https://ubjson.org/>
5. Snyder, J. P., An Equal-Area Map Projection for Polyhedral Globes, *Cartographica*, 29(1), 10-21. urn:doi:10.3138/27H7-8K88-4882-1752 (1992). <https://doi.org/10.3138/27H7-8K88-4882-1752>
6. Kevin Sahr, Denis White, A. Jon Kimerling, Geodesic Discrete Global Grid Systems, *Cartography and Geographic Information Science*, Vol. 30, No. 2, pp. 121-134 (2003). <https://cs.sou.edu/~sahrk/dgg/pubs/gdggs03.pdf>
7. Robert Gibb, The rHEALPix Discrete Global Grid System. *IOP Conference Series: Earth and Environmental Science*. 34. 012012. 10.1088/1755-1315/34/1/012012 (2016). <https://dx.doi.org/10.1088/1755-1315/34/1/012012>