Open Geospatial Consortium

OGC DOCUMENT TITLE

COMMUNITY STANDARD

APPROVED

CONTENTS

LIST OF TABLES

LIST OF FIGURES

LIST OF NORMATIVE STATEMENTS

I ABSTRACT

<Insert Abstract Text here>

II KEYWORDS

The following are keywords to be used by search engines and document catalogues.

keyword_1, keyword_2, keyword_3, etc.

PREFACE

This document establishes the OGC CRS ontology and its submodules. The definition of elements of coordinate reference systems is an essential part of geospatial data provision. However, until now, coordinate reference systems and their components could not be represented in an OGC-standardized semantic web vocabulary. This document introduces the ontology model, its classes and properties, application examples and can serve as the foundation of a semantic web based coordinate system registry at OGC. Special attention is given to the compatibility of the CRS Ontology vocabulary to other OGC-endorsed Semantic Web standards such as GeoSPARQL and alignments to other data standards are provided as part of this specification.

NOTE: Insert Preface Text here. Give OGC specific commentary: describe the technical content, reason for document, history of the document and precursors, and plans for future work.

There are two ways to specify the Preface: "simple clause" or "full clasuse"

If the Preface does not contain subclauses, it is considered a simple preface clause. This one is entered as text after the `.Preface` label and must be placed between the AsciiDoc document attributes and the first AsciiDoc section title. It should not be give a section title of its own.

If the Preface contains subclauses, it needs to be encoded as a full preface clause. This one is recognized as a full Metanorma AsciiDoc section with te title "Preface", i.e. `== Preface`. (Simple preface content can also be encoded like full preface.)

IV SECURITY CONSIDERATIONS

No security considerations have been made for this Standard.

V SUBMITTERS

All questions regarding this submission should be directed to the editor or the submitters:

NAME	AFFILIATION	OGC MEMBER
Luís Moreira de Sousa	Instituto Superior Técnico: Lisbon, PT	Yes
Timo Homburg	Mainz University Of Applied Sciences	No
Nathalie Abadie	IGN France	Yes
Ghislain Atemezing	European Union Agency for Railways (ERA)	Yes

VI SOURCE OF THE CONTENT FOR THIS OGC DOCUMENT

VII VALIDITY OF CONTENT

VIII FUTURE WORK

NOTE: If you need to place any further sections in the preface area use the `[.preface]` attribute.

IX CONTRIBUTORS

Additional contributors to this Standard include the following:

Individual name(s), Organization

1

SCOPE

1 SCOPE

<Insert Scope text here>

NOTE: Give the subject of the document and the aspects of that scope covered by the document.

2

CONFORMANCE

---

2 CONFORMANCE

<Insert conformance content here>

NOTE: Provide a short description of the content approached in subsequent sections and the main subject of the document

3

NORMATIVE REFERENCES

3 NORMATIVE REFERENCES

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Identification of Common Molecular Subsequences. Smith, T.F., Waterman, M.S., J. Mol. Biol. 147, 195–197 (1981)

ZIB Structure Prediction Pipeline: Composing a Complex Biological Workflow through Web Services. May, P., Ehrlich, H.C., Steinke, T. In: Nagel, W.E., Walter, W.V., Lehner, W. (eds.) Euro-Par 2006. LNCS, vol. 4128, pp. 1148–1158. Springer, Heidelberg (2006)

The Grid: Blueprint for a New Computing Infrastructure., Foster, I., Kesselman, C.. Morgan Kaufmann, San Francisco (1999).

Grid Information Services for Distributed Resource Sharing. Czajkowski, K., Fitzgerald, S., Foster, I., Kesselman, C. In: 10th IEEE International Symposium on High Performance Distributed Computing, pp. 181–184. IEEE Press, New York (2001)

4

TERMS AND DEFINITIONS

___

4   TERMS AND DEFINITIONS

This document uses the terms defined in <u>OGC Policy Directive 49</u>, which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word "shall" (not "must") is the verb form used to indicate a requirement to be strictly followed to conform to this document and OGC documents do not use the equivalent phrases in the ISO/IEC Directives, Part 2.

This document also uses terms defined in the OGC Standard for Modular specifications (<u>OGC 08-131r3</u>), also known as the 'ModSpec'. The definitions of terms such as standard, specification, requirement, and conformance test are provided in the ModSpec.

For the purposes of this document, the following additional terms and definitions apply.

4.1. example term

term used for exemplary purposes

Note 1 to entry: An example note.

Example   Here's an example of an example term.

[**SOURCE:**]

5

CONVENTIONS

___

5 CONVENTIONS

NOTE: This section provides details and examples for any conventions used in the document. Examples of conventions are symbols, abbreviations, use of XML schema, or special notes regarding how to read the document.

5.1. Identifiers

The normative provisions in this standard are denoted by the URI

`http://www.opengis.net/spec/{standard}/{m.n}`

All requirements and conformance tests that appear in this document are denoted by partial URIs which are relative to this base.

5.2. Other conventions

<Place any other convention needed with its corresponding title>

6

CORE

---

6 CORE

This clause establishes the **Core** Requirements class, with IRI `/req/core`, which has a corresponding Conformance Class, **Core**, with IRI `/conf/core`.

The Core module establishes a set of classes and properties which define the building blocks of a spatial reference system definition. Some of the definitions are extended in specialized modules related to the Core module.

Figure 1

From a base class SpatialReferenceSystem, we define a class for a coordinate system, as the superclass of all spatial reference systems describing locations using coorindates. These SpatialReferenceSystems are described using a Datum and a coordinate system definitions with at least one coordinate axis. Together with several subtypes of coordnate reference system, these definitions complete the Core module.

REQUIREMENTS CLASS 1: 06-CORE.ADOC EXTENSION	
IDENTIFIER	`/req/06-core.adoc`
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/Coordinate_Reference_System_Parameters
	/req/Coordinate_Reference_System_Types
	/req/Coordinate_Reference_System_Properties

6.1. Coordinate Reference System Parameters

REQUIREMENT 1: COORDINATE REFERENCE SYSTEM PARAMETERS	
IDENTIFIER	/req/Coordinate_Reference_System_Parameters
STATEMENT	Implementations shall allow the RDFS classes geosrs:AreaOfUse, geosrs:Extent, geosrs:GeographicBoundingBox, geosrs:AxesList, geosrs:SingleCRSList to be used in SPARQL graph patterns.

6.1.1. Class: geosrs:AreaOfUse

Table 1 — geosrs:AreaOfUse

URI	https://w3id.org/geosrs/srs/AreaOfUse
Definition	Area within which a coordinate operation may be used.
Example	geosrs:AreaOfUse

6.1.2. Class: geosrs:Extent

Table 2 — geosrs:Extent

URI	https://w3id.org/geosrs/srs/Extent
Definition	Geographic area or time interval in which the referring object is valid. Cf. ISO 19115-1:2014:2014-04, part 6.6.1 and table B.15 line 335.

6.1.3. Class: geosrs:GeographicBoundingBox

Table 3 — geosrs:GeographicBoundingBox

URI	https://w3id.org/geosrs/srs/GeographicBoundingBox
Definition	Frame delimiting an area of interest. See ISO 19115-1:2014:2014-04, part 6.6.1 and table B.15.1 line 344.

6.1.4. Class: geosrs:AxesList

Table 4 — geosrs:AxesList

URI	https://w3id.org/geosrs/srs/AxesList
Definition	Ordered list of coordinate system axes.

6.1.5. Class: geosrs:SingleCRSList

Table 5 — geosrs:SingleCRSList

URI	https://w3id.org/geosrs/srs/SingleCRSList
Definition	Ordered list of simple reference coordinate systems.

6.2. Coordinate Reference System Properties

REQUIREMENT 2: COORDINATE REFERENCE SYSTEM PROPERTIES	
IDENTIFIER	/req/Coordinate_Reference_System_Properties
STATEMENT	Implementations shall allow the RDFS properties geosrs:baseCRS, geosrs:conversion, geosrs:coordinateSystem, geosrs:datum, geosrs:datumEnsemble, geosrs:domainOfValidity, geosrs:method, geocrs:asProj4, geocrs:asProjJSON, geocrs:asWKT, geosrs:EPSGcode to be used in SPARQL graph patterns.

6.2.1. Property: geosrs:baseCRS

Table 6 — geosrs:baseCRS

URI	https://w3id.org/geosrs/srs/baseCRS
Type	owl:ObjectProperty

Definition	The geodetic coordinate reference system on which a projected coordinate reference system is based. Cf. ISO 19111:2007:2007-07, table 11, association role base CRS.
Range	GeodeticCRS
Domain	ProjectedCRS

6.2.2. Property: geosrs:conversion

Table 7 — geosrs:conversion

URI	https://w3id.org/geosrs/srs/conversion
Type	owl:ObjectProperty
Definition	The conversion used to define a projected coordinate reference system. Cf. ISO 19111:2007:2007-07, table 7, named association Definition.
Range	Conversion
Domain	CRS

6.2.3. Property: geosrs:coordinateSystem

Table 8 — geosrs:coordinateSystem

URI	https://w3id.org/geosrs/srs/coordinateSystem
Type	owl:ObjectProperty
Definition	The property relates a coordinate reference system to its coordinate system
Range	CoordinateSystem
Domain	CRS

6.2.4. Property: geosrs:datum

Table 9 — geosrs:datum

URI	https://w3id.org/geosrs/srs/datum
Type	owl:ObjectProperty
Definition	The property relates a coordinate reference system to a datum
Range	Datum
Domain	CRS

6.2.5. Property: geosrs:datumEnsemble

Table 10 — geosrs:datumEnsemble

URI	https://w3id.org/geosrs/srs/datumEnsemble
Type	owl:ObjectProperty
Definition	Indicates a single CRS referring to a collection of one or more datums (Datum Ensemble)
Range	DatumEnsemble
Domain	SingleCRS

6.2.6. Property: geosrs:domainOfValidity

Table 11 — geosrs:domainOfValidity

URI	https://w3id.org/geosrs/srs/domainOfValidity
Type	owl:ObjectProperty
Definition	Geographic area or time interval in which the referring object is valid. Cf. ISO 19111:2007:2007-07, tables 4, 33 and 42, attribute domainOfValidity.

Range	AreaOfUse
Domain	CRS

6.2.7. Property: geosrs:method

Table 12 — geosrs:method

URI	https://w3id.org/geosrs/srs/method
Type	owl:ObjectProperty
Range	CoordinateOperation
Domain	CRS

6.2.8. Property: geocrs:asProj4

Table 13 — geocrs:asProj4

URI	geocrs:asProj4
Type	owl:DatatypeProperty
Definition	PROJ4 string defining a CRS. Note: this paradigm is ambiguous and presently considered outdated.
Range	proj4Literal
Domain	CRS

6.2.9. Property: geocrs:asProjJSON

Table 14 — geocrs:asProjJSON

URI	geocrs:asProjJSON
Type	owl:DatatypeProperty

Definition	CRS definition encoded as a JSON object interpretable by PROJ4.
Range	projJSONLiteral
Domain	CRS

6.2.10. Property: geocrs:asWKT

Table 15 — geocrs:asWKT

URI	geocrs:asWKT
Type	owl:DatatypeProperty
Definition	CRS definition encoded according to the Well Known Text structure. Cf. ISO 19162:2019.
Range	wktLiteral
Domain	CRS

6.2.11. Property: geosrs:EPSGcode

Table 16 — geosrs:EPSGcode

URI	https://w3id.org/geosrs/srs/EPSGcode
Type	owl:DatatypeProperty
Definition	Identifier of this resource in the EPSG Geodetic Parameter Dataset.
Range	xsd:string[xsd:string]

6.3. Coordinate Reference System Types

REQUIREMENT 3: COORDINATE REFERENCE SYSTEM TYPES

IDENTIFIER	/req/Coordinate_Reference_System_Types
STATEMENT	Implementations shall allow the RDFS classes geosrs:BoundCRS, geosrs:CompoundCRS, geosrs: CRS, geosrs:EngineeringCRS, geosrs:GeocentricCRS, geosrs:GeodeticCRS, geosrs:GeographicCRS, geosrs:ParametricCRS, geosrs:ProjectedCRS, geosrs:SelenographicCRS, geosrs:ReferenceSystem, geosrs:SingleCRS, geosrs:SpatialReferenceSystem, geosrs:SpatioParametricCompoundCRS, geosrs: SpatioParametricTemporalCompoundCRS, geosrs:SpatioTemporalCompoundCRS, geosrs:StaticCRS, geosrs:TemporalCRS, geosrs:VerticalCRS to be used in SPARQL graph patterns.

6.3.1. Class: geosrs:BoundCRS

Table 17 — geosrs:BoundCRS

URI	https://w3id.org/geosrs/srs/BoundCRS
Super-classes	BoundCRS

6.3.2. Class: geosrs:CompoundCRS

Table 18 — geosrs:CompoundCRS

URI	https://w3id.org/geosrs/srs/CompoundCRS
Definition	Coordinate reference system using at least two independent single coordinate reference systems. Cf. ISO 19111:2007:2007-07, parts 8.2.3.c, 8.2.4, table 6 and annex B.1.2.4.
Super-classes	CompoundCRS
Example	geosrs:CompoundCRS

6.3.3. Class: geosrs:CRS

Table 19 — geosrs:CRS

URI	https://w3id.org/geosrs/srs/CRS

Definition	Depending on the spatial dimension of coordinates (1D, 2D, 3D), this piece of metadata is used for specifying the elements of definition associated to a given set of coordinates: its datum, its ellipsoid, its prime meridian, the type of coordinates (geocentric, geographic, projected,...), the coordinates units of measure, when appropriate the cartographic projection used, the vertical coordinate reference system.
Super-classes	CRS

6.3.4. Class: geosrs:EngineeringCRS

Table 20 — geosrs:EngineeringCRS

URI	https://w3id.org/geosrs/srs/EngineeringCRS
Definition	A contextually local coordinate reference system which can be divided into two broad categories: — earth-fixed systems applied to engineering activities on or near the surface of the earth; — CRSs on moving platforms such as road vehicles, vessels, aircraft or spacecraft.
Super-classes	EngineeringCRS

6.3.5. Class: geosrs:GeocentricCRS

Table 21 — geosrs:GeocentricCRS

URI	https://w3id.org/geosrs/srs/GeocentricCRS
Definition	A cartesian coordinate reference system that represents locations in the vicinity of the Earth (including its surface, interior, atmosphere, and surrounding outer space) as X, Y, and Z measurements from its center of mass. Commonly used to track the orbits of satellites.
Super-classes	GeocentricCRS
Example	geosrs:GeocentricCRS

6.3.6. Class: geosrs:GeodeticCRS

Table 22 — geosrs:GeodeticCRS

URI	https://w3id.org/geosrs/srs/GeodeticCRS
Definition	Coordinate Reference System associated with a geodetic datum. Cf. ISO 19111:2007:2007-07, part 8.2.2.a, table 10 and annex B.1.2.1.a.
Super-classes	GeodeticCRS

6.3.7. Class: geosrs:GeographicCRS

Table 23 — geosrs:GeographicCRS

URI	https://w3id.org/geosrs/srs/GeographicCRS
Definition	Coordinate Reference System that has a geodetic reference frame and an ellipsoidal coordinate system
Super-classes	GeographicCRS
Example	geosrs:GeographicCRS

6.3.8. Class: geosrs:ParametricCRS

Table 24 — geosrs:ParametricCRS

URI	https://w3id.org/geosrs/srs/ParametricCRS
Definition	Coordinate Reference System based on a parametric datum
Super-classes	ParametricCRS

6.3.9. Class: geosrs:ProjectedCRS

Table 25 — geosrs:ProjectedCRS

URI	https://w3id.org/geosrs/srs/ProjectedCRS
Definition	Coordinate Reference System derived from a two-dimensional geodetic coordinate reference system by applying a map projection. Cf. ISO 19111:2007:2007-07, part 8.2.3.b, table 11 and annex B.1.2.3.
Super-classes	ProjectedCRS
Example	geosrs:ProjectedCRS

6.3.10. Class: geosrs:SelenographicCRS

Table 26 — geosrs:SelenographicCRS

URI	https://w3id.org/geosrs/srs/SelenographicCRS
Definition	Coordinate Reference System to refer locations on the surface of the Earth's Moon.
Super-classes	SelenographicCRS

6.3.11. Class: geosrs:ReferenceSystem

Table 27 — geosrs:ReferenceSystem

URI	https://w3id.org/geosrs/srs/ReferenceSystem
Definition	An abstract coordinate system, whose origin, orientation and scale are specified in physical space. It is based on a set of reference points, defined as geometric points whose position is identified physically and mathematically.

6.3.12. Class: geosrs:SingleCRS

Table 28 — geosrs:SingleCRS

URI	https://w3id.org/geosrs/srs/SingleCRS

Definition	Coordinate reference system consisting of one coordinate system and one datum. Cf. ISO 19111:2007:2007-07, table 5.
Super-classes	SingleCRS

6.3.13. Class: geosrs:SpatialReferenceSystem

Table 29 — geosrs:SpatialReferenceSystem

URI	https://w3id.org/geosrs/srs/SpatialReferenceSystem
Definition	A spatial reference system (SRS) is a system for establishing spatial position. A spatial reference system can use geographic identifiers (place names, for example), coordinates (in which case it is a coordinate reference system), or identifiers with structured geometry (in which case it is a discrete global grid system).
Super-classes	SpatialReferenceSystem

6.3.14. Class: geosrs:SpatioParametricCompoundCRS

Table 30 — geosrs:SpatioParametricCompoundCRS

URI	https://w3id.org/geosrs/srs/SpatioParametricCompoundCRS
Definition	A spatio-parametric coordinate reference system is a compound CRS in which one component is a geographic 2D, projected 2D or engineering 2D CRS, supplemented by a parametric CRS to create a three-dimensional CRS
Super-classes	SpatioParametricCompoundCRS

6.3.15. Class: geosrs:SpatioParametricTemporalCompoundCRS

Table 31 — geosrs:SpatioParametricTemporalCompoundCRS

URI	https://w3id.org/geosrs/srs/SpatioParametricTemporalCompoundCRS

Definition	Coordinate reference system combining a spatio-parametric reference system with at least one temporal reference system
Super-classes	SpatioParametricTemporalCompoundCRS

6.3.16. Class: geosrs:SpatioTemporalCompoundCRS

Table 32 — geosrs:SpatioTemporalCompoundCRS

URI	https://w3id.org/geosrs/srs/SpatioTemporalCompoundCRS
Definition	Coordinate reference system combining a spatial reference system with at least one temporal reference system
Super-classes	SpatioTemporalCompoundCRS

6.3.17. Class: geosrs:StaticCRS

Table 33 — geosrs:StaticCRS

URI	https://w3id.org/geosrs/srs/StaticCRS
Definition	Coordinate Reference System that has a static reference frame
Super-classes	StaticCRS

6.3.18. Class: geosrs:TemporalCRS

Table 34 — geosrs:TemporalCRS

URI	https://w3id.org/geosrs/srs/TemporalCRS
Definition	Coordinate Reference System based on a temporal datum
Super-classes	TemporalCRS

6.3.19. Class: geosrs:VerticalCRS

Table 35 — geosrs:VerticalCRS

URI	https://w3id.org/geosrs/srs/VerticalCRS
Definition	One-dimensional coordinate reference system associated with a vertical datum and used for recording heights or depths.Ellipsoidal heights are not captured in a vertical coordinate reference system but as part of a 3D coordinates tuple defined in a geodetic 3D coordinate reference system. Cf. ISO 19111:2007:2007-07, parts 8.2.2.b, table 14 and annex B.1.2.1.b.
Super-classes	VerticalCRS
Example	geosrs:VerticalCRS

7

COORDINATE OPERATION MODULE

7 COORDINATE OPERATION MODULE

This clause establishes the **Co** Requirements class, with IRI `/req/co`, which has a corresponding Conformance Class, **Co**, with IRI `/conf/co`.

REQUIREMENTS CLASS 2: 07-CO_EXTENSION.ADOC EXTENSION	
IDENTIFIER	`/req/07-co_extension.adoc`
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/Coordinate_Operation_Methods
	/req/Coordinate_Operation_Parameters
	/req/Coordinate_Operation_Categories
	/req/Coordinate_Operation_Properties

7.1. Coordinate Operation Categories

REQUIREMENT 4: COORDINATE OPERATION CATEGORIES	
IDENTIFIER	`/req/Coordinate_Operation_Categories`
STATEMENT	Implementations shall allow the RDFS classes geosrs:GeographicObject, geosrs:Register Operations, geosrs:ScaleOperation, geosrs:RotationOperation, geosrs:IdentityOperation, geosrs:ShearOperation, geosrs:TranslationOperation, geosrs:AffineTransformationOperation, geocrs:CoordinateTransformationOperation to be used in SPARQL graph patterns.

7.1.1. Class: geosrs:GeographicObject

Table 36 — geosrs:GeographicObject

URI	https://w3id.org/geosrs/co/GeographicObject
Definition	Identifier of a geographic feature of which the coordinates are used as operation parameters.

Super-classes	GeographicObject

7.1.2. Class: geosrs:RegisterOperations

Table 37 — geosrs:RegisterOperations

URI	https://w3id.org/geosrs/co/RegisterOperations
Definition	Operations supported in the Coordinate Operations package.

7.1.3. Class: geosrs:ScaleOperation

Table 38 — geosrs:ScaleOperation

URI	https://w3id.org/geosrs/co/ScaleOperation
Definition	Scale transformation operation
Super-classes	ScaleOperation

7.1.4. Class: geosrs:RotationOperation

Table 39 — geosrs:RotationOperation

URI	https://w3id.org/geosrs/co/RotationOperation
Definition	Rotation transformation operation
Super-classes	RotationOperation

7.1.5. Class: geosrs:IdentityOperation

Table 40 — geosrs:IdentityOperation

URI	https://w3id.org/geosrs/co/IdentityOperation

Definition	Identity transformation operation
Super-classes	IdentityOperation

7.1.6. Class: geosrs:ShearOperation

Table 41 — geosrs:ShearOperation

URI	https://w3id.org/geosrs/co/ShearOperation
Definition	Shear transformation operation
Super-classes	ShearOperation

7.1.7. Class: geosrs:TranslationOperation

Table 42 — geosrs:TranslationOperation

URI	https://w3id.org/geosrs/co/TranslationOperation
Definition	Translation transformation operation
Super-classes	TranslationOperation

7.1.8. Class: geosrs:AffineTransformationOperation

Table 43 — geosrs:AffineTransformationOperation

URI	https://w3id.org/geosrs/co/AffineTransformationOperation
Definition	Affine coordinate transformation operation
Super-classes	CoordinateTransformationOperation []

7.1.9. Class: geocrs:CoordinateTransformationOperation

Table 44 — geocrs:CoordinateTransformationOperation

URI	geocrs:CoordinateTransformationOperation[]
Definition	Coordinate operation in which the two coordinate reference systems are based on different datums.
Super-classes	geocrs:CoordinateTransformationOperation[geocrs: CoordinateTransformationOperation]

7.2. Coordinate Operation Methods

REQUIREMENT 5: COORDINATE OPERATION METHODS	
IDENTIFIER	/req/Coordinate_Operation_Methods
STATEMENT	Implementations shall allow the RDFS classes geosrs:CoordinateOperation, geosrs:PassThrough Operation, geosrs:ConcatenatedOperation, geosrs:SingleOperation, geosrs:Transformation, geosrs:Conversion, geosrs:PointMotionOperation, geosrs:OperationMethod to be used in SPARQL graph patterns.

7.2.1. Class: geosrs:PassThroughOperation

Table 45 — geosrs:PassThroughOperation

URI	https://w3id.org/geosrs/co/PassThroughOperation
Definition	Specification of a subset of coordinate tuples that is subject to a coordinate operation
Super-classes	PassThroughOperation

7.2.2. Class: geosrs:ConcatenatedOperation

Table 46 — geosrs:ConcatenatedOperation

URI	https://w3id.org/geosrs/co/ConcatenatedOperation
Definition	Ordered sequence of two or more single coordinate operations. Note: The sequence of coordinate operations is constrained by the requirement that the source

	coordinate reference system of step (n + 1) shall be the same as the target coordinate reference system of step (n). The source coordinate reference system of the first step and the target coordinate reference system of the last step are the source and target coordinate reference system associated with the concatenated coordinate operation. For a concatenated coordinate operation sequence of n coordinate operations: source CRS (concatenated coordinate operation) .eq. source CRS (coordinate operation step 1) target CRS (coordinate operation step i) .eq. source CRS (coordinate operation step i + 1); i .eq. 1 …(n — 1) target CRS (concatenated coordinate operation) .eq. target CRS (coordinate operation step n) Instead of a forward coordinate operation, an inverse coordinate operation may be used for one or more of the coordinate operation steps mentioned above, if the inverse coordinate operation is uniquely defined by the forward coordinate operation method.
Super-classes	ConcatenatedOperation

7.2.3. Class: geosrs:PointMotionOperation

Table 47 — geosrs:PointMotionOperation

URI	https://w3id.org/geosrs/co/PointMotionOperation
Definition	Mathematical operation that decribes the change of coordinate values within one coordinate reference system due to the motion of the point between one coordinate epoch and another coordinate epoch Note: In this document the motion is due to tectonic plate movement or deformation.
Super-classes	PointMotionOperation

7.3. Coordinate Operation Parameters

REQUIREMENT 6: COORDINATE OPERATION PARAMETERS

IDENTIFIER	/req/Coordinate_Operation_Parameters
STATEMENT	Implementations shall allow the RDFS classes geosrs:GeneralOperationParameter, geosrs: OperationParameterGroup, geosrs:OperationParameter, geosrs:GeneralParameterValue, geosrs: ParameterValueGroup, geosrs:OperationParameterValue to be used in SPARQL graph patterns.

7.3.1. Class: geosrs:OperationParameterGroup

Table 48 — geosrs:OperationParameterGroup

URI	https://w3id.org/geosrs/co/OperationParameterGroup
Definition	Definition of a group of related parameters used by a coordinate operation method.
Super-classes	OperationParameterGroup

7.3.2. Class: geosrs:ParameterValueGroup

Table 49 — geosrs:ParameterValueGroup

URI	https://w3id.org/geosrs/co/ParameterValueGroup
Definition	Group of related parameter values. Note: The same group can be repeated more than once in a coordinate operation or higher level ParameterValueGroup, if those instances contain different values of one or more ParameterValues which suitably distinguish among those groups.
Super-classes	ParameterValueGroup

7.4. Coordinate Operation Properties

7.4.1. Property: geosrs:derivingConversion

Table 50 — geosrs:derivingConversion

URI	https://w3id.org/geosrs/co/derivingConversion
Type	owl:ObjectProperty
Definition	Relates a derived CRS to a conversion
Range	Conversion
Domain	DerivedCRS

7.4.2. Property: geosrs:parameter

Table 51 — geosrs:parameter

URI	https://w3id.org/geosrs/co/parameter
Type	owl:ObjectProperty
Definition	Value of the datum-defining parameter
Range	OperationParameter
Domain	Conversion

7.4.3. Property: geosrs:sourceCRS

Table 52 — geosrs:sourceCRS

URI	https://w3id.org/geosrs/co/sourceCRS
Type	owl:ObjectProperty
Definition	The coordinate reference system associated to the data used as input of a given operation. Cf. ISO 19111:2007:2007-07, table 42, named association Source.
Range	CRS
Domain	CoordinateOperation

7.4.4. Property: geosrs:targetCRS

Table 53 — geosrs:targetCRS

URI	https://w3id.org/geosrs/co/targetCRS
Type	owl:ObjectProperty
Definition	The coordinate reference system associated to the data obtained as output of a given operation. Cf. ISO 19111:2007:2007-07, table 42, named association Target.
Range	CRS
Domain	CoordinateOperation

8

COORDINATE SYSTEM MODULE

8 COORDINATE SYSTEM MODULE

This clause establishes the **CS** Requirements class, with IRI `/req/cs`, which has a corresponding Conformance Class, **CS**, with IRI `/conf/cs`.

The coordinate system module introduces different types of coordinate systems which are distinguished in geospatial science and applications. Coordinate systems are distinguished by their area of use, i.e planetary or interstellar and by their multidimensionality.

REQUIREMENTS CLASS 3: 08-CS_EXTENSION.ADOC EXTENSION	
IDENTIFIER	`/req/08-cs_extension.adoc`
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/Coordinate_System_Types
	/req/Celestial_Coordinate_Systems
	/req/Orthogonal_Coordinate_Systems
	/req/3D_Coordinate_Systems
	/req/Temporal_Coordinate_Systems
	/req/Coordinate_System_Parameters

8.1. 3D Coordinate Systems

REQUIREMENT 8: 3D COORDINATE SYSTEMS	
IDENTIFIER	`/req/3D_Coordinate_Systems`
STATEMENT	Implementations shall allow the RDFS classes geosrs:CylindricalCoordinateSystem, geosrs:SphericalCoordinateSystem to be used in SPARQL graph patterns.

8.1.1. Class: geosrs:CylindricalCoordinateSystem

Table 54 — geosrs:CylindricalCoordinateSystem

URI	https://w3id.org/geosrs/cs/CylindricalCoordinateSystem
Definition	Three-dimensional coordinate system in Euclidean space in which position is specified by two linear coordinates and one angular coordinate
Super-classes	CylindricalCoordinateSystem

8.2. Celestial Coordinate Systems

REQUIREMENT 9: CELESTIAL COORDINATE SYSTEMS	
IDENTIFIER	/req/Celestial_Coordinate_Systems
STATEMENT	Implementations shall allow the RDFS classes geosrs:CelestialCoordinateSystem, geosrs:Ecliptic CoordinateSystem, geosrs:EquatorialCoordinateSystem, geosrs:GalacticCoordinateSystem, geosrs: HorizontalCoordinateSystem, geosrs:PerifocalCoordinateSystem, geosrs:SuperGalacticCS to be used in SPARQL graph patterns.

8.2.1. Class: geosrs:CelestialCoordinateSystem

Table 55 — geosrs:CelestialCoordinateSystem

URI	https://w3id.org/geosrs/cs/CelestialCoordinateSystem
Definition	A coordinate system for specifying positions of celestial objects relative to physical reference points
Super-classes	CelestialCoordinateSystem

8.2.2. Class: geosrs:EclipticCoordinateSystem

Table 56 — geosrs:EclipticCoordinateSystem

URI	https://w3id.org/geosrs/cs/EclipticCoordinateSystem
Definition	An ecliptic coordinate system is used for representing the apparent positions and orbits of solar system objects.

Super-classes	EclipticCoordinateSystem

8.2.3. Class: geosrs:EquatorialCoordinateSystem

Table 57 — geosrs:EquatorialCoordinateSystem

URI	https://w3id.org/geosrs/cs/EquatorialCoordinateSystem
Definition	A celestial coordinate system in which an object's position on the celestial sphere is described in terms of its north-south declination and east-west right ascension, measured relative to the celestial equator and vernal equinox, respectively.
Super-classes	EquatorialCoordinateSystem

8.2.4. Class: geosrs:GalacticCoordinateSystem

Table 58 — geosrs:GalacticCoordinateSystem

URI	https://w3id.org/geosrs/cs/GalacticCoordinateSystem
Definition	A coordinate system with the Sun as its center, the primary direction aligned with the approximate center of the Milky Way Galaxy, and the fundamental plane parallel to an approximation of the galactic plane but offset to its north.
Super-classes	CelestialCoordinateSystem 3DCoordinateSystem

8.2.5. Class: geosrs:HorizontalCoordinateSystem

Table 59 — geosrs:HorizontalCoordinateSystem

URI	https://w3id.org/geosrs/cs/HorizontalCoordinateSystem
Definition	A horizontal coordinate system is a celestial coordinate system that uses the observer's local horizon as the fundamental plane.
Super-classes	HorizontalCoordinateSystem

8.2.6. Class: geosrs:PerifocalCoordinateSystem

Table 60 — geosrs:PerifocalCoordinateSystem

URI	https://w3id.org/geosrs/cs/PerifocalCoordinateSystem
Definition	A frame of reference centered at the focus of the orbit, i. e. the celestial body about which the orbit is centered.
Super-classes	PerifocalCoordinateSystem

8.2.7. Class: geosrs:SuperGalacticCS

Table 61 — geosrs:SuperGalacticCS

URI	https://w3id.org/geosrs/cs/SuperGalacticCS
Definition	A reference frame for the supercluster of galaxies that contains the Milky Way galaxy, referenced to a local relatively flat collection of galaxy clusters used to define the supergalactic plane.
Super-classes	CelestialCoordinateSystem 3DCoordinateSystem

8.3. Coordinate System Parameters

REQUIREMENT 10: COORDINATE SYSTEM PARAMETERS	
IDENTIFIER	/req/Coordinate_System_Parameters
STATEMENT	Implementations shall allow the RDFS classes geosrs:axis, geosrs:axisDirection to be used in SPARQL graph patterns.

8.3.1. Property: geosrs:axis

Table 62 — geosrs:axis

URI	https://w3id.org/geosrs/cs/axis
Type	owl:ObjectProperty
Definition	The property relates a coordinate system to one of its axis
Range	Axis
Domain	CoordinateSystem

8.3.2. Property: geosrs:axisDirection

Table 63 — geosrs:axisDirection

URI	https://w3id.org/geosrs/cs/axisDirection
Type	owl:ObjectProperty
Definition	The direction of an axis. Cf. ISO 19111:2007:2007-07, table 27, attribute coordinate system axis direction.
Range	AxisDirection
Domain	Axis

8.4. Coordinate System Types

REQUIREMENT 11: COORDINATE SYSTEM TYPES	
IDENTIFIER	/req/Coordinate_System_Types
STATEMENT	Implementations shall allow the RDFS classes geosrs:1DCoordinateSystem, geosrs:3DCoordinate System, geosrs:AffineCoordinateSystem, geosrs:BarycentricCoordinateSystem, geosrs:Cartesian CoordinateSystem, geosrs:CurvilinearCoordinateSystem, geosrs:EngineeringCoordinateSystem, geosrs:GeodeticCoordinateSystem, geosrs:GridCoordinateSystem, geosrs:HexagonalCoordinate System, geosrs:LocalCoordinateSystem, geosrs:ObliqueCoordinateSystem, geosrs:OrdinalCoordinate System, geosrs:PlanarCoordinateSystem, geosrs:PolarCoordinateSystem to be used in SPARQL graph patterns.

8.4.1. Class: geosrs:1DCoordinateSystem

Table 64 — geosrs:1DCoordinateSystem

URI	https://w3id.org/geosrs/cs/1DCoordinateSystem
Definition	Non-repeating sequence of coordinate system axes that spans a given coordinate space in one dimension
Super-classes	1DCoordinateSystem

8.4.2. Class: geosrs:3DCoordinateSystem

Table 65 — geosrs:3DCoordinateSystem

URI	https://w3id.org/geosrs/cs/3DCoordinateSystem
Definition	Non-repeating sequence of coordinate system axes that spans a given coordinate space in three dimensions
Super-classes	3DCoordinateSystem
Example	geosrs:3DCoordinateSystem

8.4.3. Class: geosrs:AffineCoordinateSystem

Table 66 — geosrs:AffineCoordinateSystem

URI	https://w3id.org/geosrs/cs/AffineCoordinateSystem
Definition	Coordinate system in Euclidean space with straight axes that are not necessarily mutually perpendicular
Super-classes	AffineCoordinateSystem

8.4.4. Class: geosrs:BarycentricCoordinateSystem

Table 67 — geosrs:BarycentricCoordinateSystem

URI	https://w3id.org/geosrs/cs/BarycentricCoordinateSystem
Definition	A coordinate system in which the location of a point is specified by reference to a simplex (a triangle for points in a plane, a tetrahedron for points in three-dimensional space, etc.)
Super-classes	BarycentricCoordinateSystem

8.4.5. Class: geosrs:CurvilinearCoordinateSystem

Table 68 — geosrs:CurvilinearCoordinateSystem

URI	https://w3id.org/geosrs/cs/CurvilinearCoordinateSystem
Definition	A coordinate system for the Euclidean space in which the coordinate lines may be curved
Super-classes	CurvilinearCoordinateSystem

8.4.6. Class: geosrs:EngineeringCoordinateSystem

Table 69 — geosrs:EngineeringCoordinateSystem

URI	https://w3id.org/geosrs/cs/EngineeringCoordinateSystem
Definition	Coordinate system used by an engineering coordinate reference system, one of an affine coordinate system, a Cartesian coordinate system, a cylindrical coordinate system, a linear coordinate sytem, an ordinal coordinate system, a polar coordinate system or a spherical coordinate system
Super-classes	EngineeringCoordinateSystem

8.4.7. Class: geosrs:GeodeticCoordinateSystem

Table 70 — geosrs:GeodeticCoordinateSystem

URI	https://w3id.org/geosrs/cs/GeodeticCoordinateSystem

Definition	Coordinate system used by a Geodetic CRS, one of a Cartesian coordinate system or a spherical coordinate system.
Super-classes	GeodeticCoordinateSystem

8.4.8. Class: geosrs:GridCoordinateSystem

Table 71 — geosrs:GridCoordinateSystem

URI	https://w3id.org/geosrs/cs/GridCoordinateSystem
Definition	A grid coordinate system identifies areas within a grid.
Super-classes	GridCoordinateSystem

8.4.9. Class: geosrs:HexagonalCoordinateSystem

Table 72 — geosrs:HexagonalCoordinateSystem

URI	https://w3id.org/geosrs/cs/HexagonalCoordinateSystem
Definition	A hexagonal coordinate system identifies areas within a hexagonal lattice.
Super-classes	HexagonalCoordinateSystem

8.4.10. Class: geosrs:LocalCoordinateSystem

Table 73 — geosrs:LocalCoordinateSystem

URI	https://w3id.org/geosrs/cs/LocalCoordinateSystem
Definition	Coordinate system with a point of local reference.
Super-classes	LocalCoordinateSystem

8.4.11. Class: geosrs:ObliqueCoordinateSystem

Table 74 — geosrs:ObliqueCoordinateSystem

URI	https://w3id.org/geosrs/cs/ObliqueCoordinateSystem
Definition	A plane coordinate system whose axes are not perpendicular.
Super-classes	ObliqueCoordinateSystem

8.4.12. Class: geosrs:PlanarCoordinateSystem

Table 75 — geosrs:PlanarCoordinateSystem

URI	https://w3id.org/geosrs/cs/PlanarCoordinateSystem
Definition	A two-dimensional measurement system that locates features on a plane based on their distance from an origin (0,0) along two perpendicular axes.
Super-classes	PlanarCoordinateSystem
Example	geosrs:PlanarCoordinateSystem

8.5. Orthogonal Coordinate Systems

REQUIREMENT 12: ORTHOGONAL COORDINATE SYSTEMS	
IDENTIFIER	/req/Orthogonal_Coordinate_Systems
STATEMENT	Implementations shall allow the RDFS classes geosrs:ConicalCoordinateSystem, geosrs:EllipsoidalCoordinateSystem to be used in SPARQL graph patterns.

8.5.1. Class: geosrs:ConicalCoordinateSystem

Table 76 — geosrs:ConicalCoordinateSystem

URI	https://w3id.org/geosrs/cs/ConicalCoordinateSystem
Definition	A conical coordinate system is a three-dimensional orthogonal coordinate system consisting of concentric spheres (described by their radius r) and by two families of perpendicular cones, aligned along the z- and x-axes, respectively
Super-classes	ConicalCoordinateSystem

8.6. Temporal Coordinate Systems

REQUIREMENT 13: TEMPORAL COORDINATE SYSTEMS	
IDENTIFIER	/req/Temporal_Coordinate_Systems
STATEMENT	Implementations shall allow the RDFS classes geosrs:DateTimeTemporalCoordinateSystem, geosrs:TemporalCountCoordinateSystem, geosrs:TemporalCoordinateSystem, geosrs:Temporal MeasureCoordinateSystem to be used in SPARQL graph patterns.

8.6.1. Class: geosrs:DateTimeTemporalCoordinateSystem

Table 77 — geosrs:DateTimeTemporalCoordinateSystem

URI	https://w3id.org/geosrs/cs/DateTimeTemporalCoordinateSystem
Definition	One-dimensional coordinate system used to record time in dateTime representation as defined in ISO 8601.
Super-classes	DateTimeTemporalCoordinateSystem

8.6.2. Class: geosrs:TemporalCountCoordinateSystem

Table 78 — geosrs:TemporalCountCoordinateSystem

URI	https://w3id.org/geosrs/cs/TemporalCountCoordinateSystem

Definition	One-dimensional coordinate system used to record time as an integer count.
Super-classes	TemporalCountCoordinateSystem

8.6.3. Class: geosrs:TemporalCoordinateSystem

Table 79 — geosrs:TemporalCoordinateSystem

URI	https://w3id.org/geosrs/cs/TemporalCoordinateSystem
Definition	One-dimensionalcoordinate system where the axis is time.
Super-classes	TemporalCoordinateSystem

8.6.4. Class: geosrs:TemporalMeasureCoordinateSystem

Table 80 — geosrs:TemporalMeasureCoordinateSystem

URI	https://w3id.org/geosrs/cs/TemporalMeasureCoordinateSystem
Definition	One-dimensional coordinate system used to record a time as a real number.
Super-classes	TemporalMeasureCoordinateSystem

9

DATUM MODULE

9 DATUM MODULE

This clause establishes the **Datum** Requirements class, with IRI `/req/datum`, which has a corresponding Conformance Class, **Datum**, with IRI `/conf/datum`.

REQUIREMENTS CLASS 4: 09-DATUM_EXTENSION.ADOC EXTENSION	
IDENTIFIER	`/req/09-datum_extension.adoc`
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/Datum_Types
	/req/Datum_Parameters
	/req/Spheroid_Types
	/req/Datum_Properties
	/req/Spheroid_Properties

9.1. Datum Parameters

REQUIREMENT 14: DATUM PARAMETERS	
IDENTIFIER	`/req/Datum_Parameters`
STATEMENT	Implementations shall allow the RDFS classes geosrs:PrimeMeridian, geosrs:DefiningParameter to be used in SPARQL graph patterns.

9.1.1. Class: geosrs:DefiningParameter

Table 81 — geosrs:DefiningParameter

URI	https://w3id.org/geosrs/datum/DefiningParameter
Definition	Parameter value, an ordered sequence of values, or a reference to a file of parameter values that define

9.2. Datum Properties

REQUIREMENT 15: DATUM PROPERTIES	
IDENTIFIER	/req/Datum_Properties
STATEMENT	Implementations shall allow the RDFS properties geosrs:datumDefiningParameter, geosrs:ellipsoid, geosrs:primeMeridian to be used in SPARQL graph patterns.

9.2.1. Property: geosrs:datumDefiningParameter

Table 82 — geosrs:datumDefiningParameter

URI	https://w3id.org/geosrs/datum/datumDefiningParameter
Type	owl:ObjectProperty
Definition	Parameter used to define the parametric datum
Range	DefiningParameter
Domain	ParametricDatum

9.2.2. Property: geosrs:ellipsoid

Table 83 — geosrs:ellipsoid

URI	https://w3id.org/geosrs/datum/ellipsoid
Type	owl:ObjectProperty
Definition	The properties relates a datum to its ellipsoid definition
Range	Ellipsoid

Domain	Datum

9.2.3. Property: geosrs:primeMeridian

Table 84 — geosrs:primeMeridian

URI	https://w3id.org/geosrs/datum/primeMeridian
Type	owl:ObjectProperty
Definition	The prime meridian used by a geodetic datum. Cf. ISO 19111:2007:2007-07, table 34, association role prime Meridian.
Range	PrimeMeridian
Domain	Datum

9.3. Datum Types

REQUIREMENT 16: DATUM TYPES	
IDENTIFIER	/req/Datum_Types
STATEMENT	Implementations shall allow the RDFS classes geosrs:Datum, geosrs:GeodeticDatum, geosrs:DynamicGeodeticReferenceFrame, geosrs:VerticalDatum, geosrs:DynamicVerticalDatum, geosrs:ParametricDatum, geosrs:EngineeringDatum, geosrs:TemporalDatum, geosrs:DatumEnsemble to be used in SPARQL graph patterns.

9.3.1. Class: geosrs:DynamicGeodeticReferenceFrame

Table 85 — geosrs:DynamicGeodeticReferenceFrame

URI	https://w3id.org/geosrs/datum/DynamicGeodeticReferenceFrame
Definition	Geodetic reference frame in which some of the parameters describe time evolution of defining station

	coordinatesExample: defining station coordinates having linear velocities to account for crustal motion.
Super-classes	DynamicGeodeticReferenceFrame

9.3.2. Class: geosrs:DynamicVerticalDatum

Table 86 — geosrs:DynamicVerticalDatum

URI	https://w3id.org/geosrs/datum/DynamicVerticalDatum
Definition	Vertical reference frame in which some of the defining parameters have time dependencyExample: Defining station heights have velocity to account for post-glacial isostatic rebound motion. Cf. ISO 19111:2019 Geographic information — Referencing by coordinates.
Super-classes	DynamicVerticalDatum

9.3.3. Class: geosrs:ParametricDatum

Table 87 — geosrs:ParametricDatum

URI	https://w3id.org/geosrs/datum/ParametricDatum
Definition	Textual description and/or a set of parameters identifying a particular reference surface used as the origin of a parametric coordinate system, including its position with respect to the Earth. Cf. ISO 19111:2019 Geographic information — Referencing by coordinates.
Super-classes	ParametricDatum

9.3.4. Class: geosrs:EngineeringDatum

Table 88 — geosrs:EngineeringDatum

URI	https://w3id.org/geosrs/datum/EngineeringDatum
Definition	Definition of the origin and orientation of an engineering coordinate reference systemNote: The origin can be fixed with respect to the Earth (such as a defined point at a

	construction site), or be a defined point on a moving vehicle (such as on a ship or satellite), or a defined point of an image. Cf. ISO 19111:2019 Geographic information — Referencing by coordinates.
Super-classes	EngineeringDatum

9.3.5. Class: geosrs:TemporalDatum

Table 89 — geosrs:TemporalDatum

URI	https://w3id.org/geosrs/datum/TemporalDatum
Definition	Definition of the relationship of a temporal coordinate system to an objectNote: The object is normally time on the Earth. Cf. ISO 19111:2019 Geographic information — Referencing by coordinates.
Super-classes	TemporalDatum

9.3.6. Class: geosrs:DatumEnsemble

Table 90 — geosrs:DatumEnsemble

URI	https://w3id.org/geosrs/datum/DatumEnsemble
Definition	A collection of two or more datums (or if geodetic or vertical, a collection of two or more reference frames) that are realizations of one Conventional Reference System and which for all but the highest accuracy requirements may be considered to be insignificantly different from each other. Note: Within the datum ensemble every frame or datum is constrained to be a realization of the same reference system. Cf. ISO 19111:2019 Geographic information — Referencing by coordinates.

9.4. Spheroid Properties

REQUIREMENT 17: SPHEROID PROPERTIES

IDENTIFIER	`/req/Spheroid_Properties`
STATEMENT	Implementations shall allow the RDFS properties geosrs:eccentricity, geosrs:inverseFlattening, geosrs:isSphere, geosrs:semiMajorAxis, geosrs:semiMinorAxis to be used in SPARQL graph patterns.

9.4.1. Property: geosrs:eccentricity

Table 91 — geosrs:eccentricity

URI	https://w3id.org/geosrs/datum/eccentricity
Type	owl:DatatypeProperty
Definition	A measure of how much an ellipse deviates from a perfect circle.
Range	xsd:double[xsd:double]
Domain	Ellipsoid

9.4.2. Property: geosrs:inverseFlattening

Table 92 — geosrs:inverseFlattening

URI	https://w3id.org/geosrs/datum/inverseFlattening
Type	owl:DatatypeProperty
Definition	Indicates the inverse flattening value of an ellipsoid, expressed as a number or a ratio (percentage rate, parts per million, etc.). Cf. ISO 19111:2007:2007-07, table 37, attribute inverse flattening
Range	xsd:double[xsd:double]
Domain	Ellipsoid

9.4.3. Property: geosrs:isSphere

Table 93 — geosrs:isSphere

URI	https://w3id.org/geosrs/datum/isSphere
Type	owl:DatatypeProperty
Definition	Indicates whether the ellipsoid is a sphere. Cf. ISO 19111:2007:2007-07, table 37, attribute ellipsoid= sphere indicator.
Range	xsd:boolean[xsd:boolean]
Domain	Ellipsoid

9.4.4. Property: geosrs:semiMajorAxis

Table 94 — geosrs:semiMajorAxis

URI	https://w3id.org/geosrs/datum/semiMajorAxis
Type	owl:DatatypeProperty
Definition	Indicates the length of the semi major axis of an ellipsoid. Cf. ISO 19111:2007:2007-07, table 36, attribute length of semi-major axis.
Range	xsd:double[xsd:double]
Domain	Ellipsoid

9.4.5. Property: geosrs:semiMinorAxis

Table 95 — geosrs:semiMinorAxis

URI	https://w3id.org/geosrs/datum/semiMinorAxis
Type	owl:DatatypeProperty

Definition	Indicates the length of the semi minor axis of an ellipsoid. Cf. ISO 19111:2007:2007-07, table 37, attribute length of semi-minor axis.
Range	xsd:double[xsd:double]
Domain	Ellipsoid

9.5. Spheroid Types

REQUIREMENT 18: SPHEROID TYPES	
IDENTIFIER	/req/Spheroid_Types
STATEMENT	Implementations shall allow the RDFS classes geosrs:Ellipsoid, geosrs:TriaxialEllipsoid to be used in SPARQL graph patterns.

9.5.1. Class: geosrs:TriaxialEllipsoid

Table 96 — geosrs:TriaxialEllipsoid

URI	https://w3id.org/geosrs/datum/TriaxialEllipsoid
Definition	Surface of an analytic ellipsoid defined by three axes of different length. Also referred as scalene ellipsoid.

10

SRS APPLICATION MODULE

---

10 SRS APPLICATION MODULE

This clause establishes the **SRSAPP** Requirements class, with IRI `/req/srsapp`, which has a corresponding Conformance Class, **SRSAPP**, with IRI `/conf/srsapp`.

REQUIREMENTS CLASS 5: 10-SRSAPPLICATION_EXTENSION.ADOC EXTENSION	
IDENTIFIER	`/req/10-srsapplication_extension.adoc`
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/SRS_Application_Types /req/Map_Types

10.1. Map Types

REQUIREMENT 19: MAP TYPES	
IDENTIFIER	`/req/Map_Types`
STATEMENT	Implementations shall allow the RDFS classes geosrs:CadastreMap, geosrs:NauticalChart, geosrs:ThematicMap, geosrs:TopographicMap, geosrs:WeatherMap to be used in SPARQL graph patterns.

10.1.1. Class: geosrs:CadastreMap

Table 97 — geosrs:CadastreMap

URI	https://w3id.org/geosrs/application/CadastreMap
Definition	A map displaying a cadastre.
Super-classes	CadastreMap

10.1.2. Class: geosrs:NauticalChart

Table 98 — geosrs:NauticalChart

URI	https://w3id.org/geosrs/application/NauticalChart
Definition	A graphic representation of a sea area and adjacent coastal regions.
Super-classes	NauticalChart

10.1.3. Class: geosrs:ThematicMap

Table 99 — geosrs:ThematicMap

URI	https://w3id.org/geosrs/application/ThematicMap
Definition	A map used to highlight a specific phenomenon.
Super-classes	ThematicMap

10.1.4. Class: geosrs:TopographicMap

Table 100 — geosrs:TopographicMap

URI	https://w3id.org/geosrs/application/TopographicMap
Definition	A type of map characterized by large-scale detail and quantitative representation of relief.
Super-classes	TopographicMap

10.1.5. Class: geosrs:WeatherMap

Table 101 — geosrs:WeatherMap

URI	https://w3id.org/geosrs/application/WeatherMap

Definition	A map for showing the local direction in which weather systems are moving.
Super-classes	WeatherMap

10.2. SRS Application Types

REQUIREMENT 20: SRS APPLICATION TYPES	
IDENTIFIER	/req/SRS_Application_Types
STATEMENT	Implementations shall allow the RDFS classes geosrs:SRSApplication, geosrs:SpatialReferencing, geosrs:EngineeringSurvey, geosrs:SatelliteSurvey, geosrs:SatelliteNavigation, geosrs:Coastal Hydrography, geosrs:OffshoreEngineering, geosrs:Hydrography, geosrs:Drilling, geosrs:OilAndGas Exploration to be used in SPARQL graph patterns.

10.2.1. Class: geosrs:SRSApplication

Table 102 — geosrs:SRSApplication

URI	https://w3id.org/geosrs/application/SRSApplication
Definition	An application for which a spatial reference system is used.

10.2.2. Class: geosrs:SpatialReferencing

Table 103 — geosrs:SpatialReferencing

URI	https://w3id.org/geosrs/application/SpatialReferencing
Super-classes	SpatialReferencing

10.2.3. Class: geosrs:EngineeringSurvey

Table 104 — geosrs:EngineeringSurvey

URI	https://w3id.org/geosrs/application/EngineeringSurvey
Super-classes	EngineeringSurvey

10.2.4. Class: geosrs:SatelliteSurvey

Table 105 — geosrs:SatelliteSurvey

URI	https://w3id.org/geosrs/application/SatelliteSurvey
Super-classes	SatelliteSurvey

10.2.5. Class: geosrs:SatelliteNavigation

Table 106 — geosrs:SatelliteNavigation

URI	https://w3id.org/geosrs/application/SatelliteNavigation
Super-classes	SatelliteNavigation

10.2.6. Class: geosrs:CoastalHydrography

Table 107 — geosrs:CoastalHydrography

URI	https://w3id.org/geosrs/application/CoastalHydrography
Super-classes	CoastalHydrography

10.2.7. Class: geosrs:OffshoreEngineering

Table 108 — geosrs:OffshoreEngineering

URI	https://w3id.org/geosrs/application/OffshoreEngineering
Super-classes	OffshoreEngineering

10.2.8. Class: geosrs:Hydrography

Table 109 — geosrs:Hydrography

URI	https://w3id.org/geosrs/application/Hydrography
Super-classes	Hydrography

10.2.9. Class: geosrs:Drilling

Table 110 — geosrs:Drilling

URI	https://w3id.org/geosrs/application/Drilling
Super-classes	Drilling

10.2.10. Class: geosrs:OilAndGasExploration

Table 111 — geosrs:OilAndGasExploration

URI	https://w3id.org/geosrs/application/OilAndGasExploration
Super-classes	OilAndGasExploration

11

PROJECTIONS MODULE

11 PROJECTIONS MODULE

This clause establishes the **PROJ** Requirements class, with IRI `/req/proj`, which has a corresponding Conformance Class, **PROJ**, with IRI `/conf/proj`.

REQUIREMENTS CLASS 6: 11-PROJECTIONS_EXTENSION.ADOC EXTENSION	
IDENTIFIER	`/req/11-projections_extension.adoc`
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/Lenticular_Projections
	/req/Conformal_Projections
	/req/Minimum_Error_Projections
	/req/Pseudo_Azimuthal_Projections
	/req/Equal_Area_Projections
	/req/Pseudo_Conical_Projections
	/req/Globular_Projections
	/req/Pseudo_Cylindrical_Projections
	/req/Cylindrical_Projections
	/req/Compromise_Projections
	/req/Polyhedral_Projections
	/req/Equidistant_Projections
	/req/Conical_Projections
	/req/Azimuthal_Projections
	/req/Perspective_Projections
	/req/Polyconic_Projections
	/req/Stereographic_Projections

11.1. Azimuthal Projections

REQUIREMENT 21: AZIMUTHAL PROJECTIONS	
IDENTIFIER	/req/Azimuthal_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:BreusingGeometricProjection, geosrs: BreusingHarmonicProjection, geosrs:GinzburgIIProjection, geosrs:GinzburgIProjection, geosrs: GnomonicProjection, geosrs:JamesAzimuthalProjection to be used in SPARQL graph patterns.

11.1.1. Class: geosrs:BreusingGeometricProjection

Table 112 — geosrs:BreusingGeometricProjection

URI	https://w3id.org/geosrs/projection/ BreusingGeometricProjection
Super-classes	BreusingGeometricProjection

11.1.2. Class: geosrs:BreusingHarmonicProjection

Table 113 — geosrs:BreusingHarmonicProjection

URI	https://w3id.org/geosrs/projection/ BreusingHarmonicProjection
Super-classes	BreusingHarmonicProjection

11.1.3. Class: geosrs:GinzburgIIProjection

Table 114 — geosrs:GinzburgIIProjection

URI	https://w3id.org/geosrs/projection/GinzburgIIProjection
Super-classes	GinzburgIIProjection

11.1.4. Class: geosrs:GinzburgIProjection

Table 115 — geosrs:GinzburgIProjection

URI	https://w3id.org/geosrs/projection/GinzburgIProjection
Super-classes	GinzburgIProjection

11.1.5. Class: geosrs:GnomonicProjection

Table 116 — geosrs:GnomonicProjection

URI	https://w3id.org/geosrs/projection/GnomonicProjection
Super-classes	GnomonicProjection

11.1.6. Class: geosrs:JamesAzimuthalProjection

Table 117 — geosrs:JamesAzimuthalProjection

URI	https://w3id.org/geosrs/projection/JamesAzimuthalProjection
Super-classes	JamesAzimuthalProjection

11.2. Compromise Projections

REQUIREMENT 22: COMPROMISE PROJECTIONS	
IDENTIFIER	/req/Compromise_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:ArmadilloProjection, geosrs:BakerDinomic Projection, geosrs:BertinProjection, geosrs:ChamberlinTrimetricProjection, geosrs:DenoyerSemi EllipticalProjection, geosrs:FairgrieveProjection, geosrs:LarriveeProjection, geosrs:PetermannStar Projection, geosrs:SpilhausOceanicProjection, geosrs:VanDerGrintenIIIProjection, geosrs:Winkel

llProjection, geosrs:WinkellProjection, geosrs:WinkelSnyderProjection to be used in SPARQL graph patterns.

11.2.1. Class: geosrs:ArmadilloProjection

Table 118 — geosrs:ArmadilloProjection

URI	https://w3id.org/geosrs/projection/ArmadilloProjection
Super-classes	ArmadilloProjection

11.2.2. Class: geosrs:BakerDinomicProjection

Table 119 — geosrs:BakerDinomicProjection

URI	https://w3id.org/geosrs/projection/ BakerDinomicProjection
Super-classes	BakerDinomicProjection

11.2.3. Class: geosrs:BertinProjection

Table 120 — geosrs:BertinProjection

URI	https://w3id.org/geosrs/projection/BertinProjection
Super-classes	BertinProjection

11.2.4. Class: geosrs:ChamberlinTrimetricProjection

Table 121 — geosrs:ChamberlinTrimetricProjection

URI	https://w3id.org/geosrs/projection/ ChamberlinTrimetricProjection
Super-classes	ChamberlinTrimetricProjection

11.2.5. Class: geosrs:DenoyerSemiEllipticalProjection

Table 122 — geosrs:DenoyerSemiEllipticalProjection

URI	https://w3id.org/geosrs/projection/DenoyerSemiEllipticalProjection
Super-classes	DenoyerSemiEllipticalProjection

11.2.6. Class: geosrs:FairgrieveProjection

Table 123 — geosrs:FairgrieveProjection

URI	https://w3id.org/geosrs/projection/FairgrieveProjection
Super-classes	FairgrieveProjection

11.2.7. Class: geosrs:LarriveeProjection

Table 124 — geosrs:LarriveeProjection

URI	https://w3id.org/geosrs/projection/LarriveeProjection
Super-classes	LarriveeProjection

11.2.8. Class: geosrs:PetermannStarProjection

Table 125 — geosrs:PetermannStarProjection

URI	https://w3id.org/geosrs/projection/PetermannStarProjection
Super-classes	PetermannStarProjection

11.2.9. Class: geosrs:SpilhausOceanicProjection

Table 126 — geosrs:SpilhausOceanicProjection

URI	https://w3id.org/geosrs/projection/SpilhausOceanicProjection
Super-classes	SpilhausOceanicProjection

11.2.10. Class: geosrs:VanDerGrintenIIIProjection

Table 127 — geosrs:VanDerGrintenIIIProjection

URI	https://w3id.org/geosrs/projection/VanDerGrintenIIIProjection
Super-classes	VanDerGrintenIIIProjection

11.2.11. Class: geosrs:WinkelIIIProjection

Table 128 — geosrs:WinkelIIIProjection

URI	https://w3id.org/geosrs/projection/WinkelIIIProjection
Super-classes	WinkelIIIProjection

11.2.12. Class: geosrs:WinkelIIProjection

Table 129 — geosrs:WinkelIIProjection

URI	https://w3id.org/geosrs/projection/WinkelIIProjection
Super-classes	WinkelIIProjection

11.2.13. Class: geosrs:WinkelSnyderProjection

Table 130 — geosrs:WinkelSnyderProjection

URI	https://w3id.org/geosrs/projection/WinkelSnyderProjection

Super-classes	WinkelSnyderProjection

11.3. Conformal Projections

REQUIREMENT 23: CONFORMAL PROJECTIONS

IDENTIFIER	/req/Conformal_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:AdamsProjection, geosrs:AdamsWorld InASquareIIProjection, geosrs:AdamsWorldInASquareIProjection, geosrs:AugustEpicycloidal Projection, geosrs:CoxConformalProjection, geosrs:EisenlohrProjection, geosrs:GS50Projection, geosrs:PeirceQuincuncialProjection, geosrs:StereographicProjection to be used in SPARQL graph patterns.

11.3.1. Class: geosrs:AdamsProjection

Table 131 — geosrs:AdamsProjection

URI	https://w3id.org/geosrs/projection/AdamsProjection
Super-classes	AdamsProjection

11.3.2. Class: geosrs:AdamsWorldInASquareIIProjection

Table 132 — geosrs:AdamsWorldInASquareIIProjection

URI	https://w3id.org/geosrs/projection/AdamsWorldInASquareIIProjection
Super-classes	AdamsWorldInASquareIIProjection

11.3.3. Class: geosrs:AdamsWorldInASquareIProjection

Table 133 — geosrs:AdamsWorldInASquareIProjection

URI	https://w3id.org/geosrs/projection/AdamsWorldInASquareIProjection
Super-classes	AdamsWorldInASquareIProjection

11.3.4. Class: geosrs:AugustEpicycloidalProjection

Table 134 — geosrs:AugustEpicycloidalProjection

URI	https://w3id.org/geosrs/projection/AugustEpicycloidalProjection
Definition	A projection in which every angle between two curves that crosss each other on a celestical body is preserved in the image of the projection
Super-classes	AugustEpicycloidalProjection

11.3.5. Class: geosrs:CoxConformalProjection

Table 135 — geosrs:CoxConformalProjection

URI	https://w3id.org/geosrs/projection/CoxConformalProjection
Super-classes	CoxConformalProjection

11.3.6. Class: geosrs:EisenlohrProjection

Table 136 — geosrs:EisenlohrProjection

URI	https://w3id.org/geosrs/projection/EisenlohrProjection
Super-classes	EisenlohrProjection

11.3.7. Class: geosrs:GS50Projection

Table 137 — geosrs:GS50Projection

URI	https://w3id.org/geosrs/projection/GS50Projection
Super-classes	GS50Projection

11.3.8. Class: geosrs:PeirceQuincuncialProjection

Table 138 — geosrs:PeirceQuincuncialProjection

URI	https://w3id.org/geosrs/projection/PeirceQuincuncialProjection
Super-classes	PeirceQuincuncialProjection

11.3.9. Class: geosrs:StereographicProjection

Table 139 — geosrs:StereographicProjection

URI	https://w3id.org/geosrs/projection/StereographicProjection
Super-classes	StereographicProjection
Example	geosrs:StereographicProjection

11.4. Conical Projections

REQUIREMENT 24: CONICAL PROJECTIONS	
IDENTIFIER	/req/Conical_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:BipolarObliqueConicConformalProjection, geosrs:CentralConicProjection, geosrs:HerschelConformalConicProjection, geosrs:Krovak, geosrs:LambertConformalConicProjection, geosrs:MurdochIIIProjection, geosrs:MurdochIIProjection, geosrs:MurdochIProjection, geosrs:SchjerningIProjection, geosrs:VitkovskyIProjection to be used in SPARQL graph patterns.

11.4.1. Class: geosrs:BipolarObliqueConicConformalProjection

Table 140 — geosrs:BipolarObliqueConicConformalProjection

URI	https://w3id.org/geosrs/projection/ BipolarObliqueConicConformalProjection
Super-classes	BipolarObliqueConicConformalProjection

11.4.2. Class: geosrs:CentralConicProjection

Table 141 — geosrs:CentralConicProjection

URI	https://w3id.org/geosrs/projection/ CentralConicProjection
Super-classes	CentralConicProjection

11.4.3. Class: geosrs:HerschelConformalConicProjection

Table 142 — geosrs:HerschelConformalConicProjection

URI	https://w3id.org/geosrs/projection/ HerschelConformalConicProjection
Super-classes	HerschelConformalConicProjection

11.4.4. Class: geosrs:Krovak

Table 143 — geosrs:Krovak

URI	https://w3id.org/geosrs/projection/Krovak
Super-classes	Krovak
Example	geosrs:Krovak

11.4.5. Class: geosrs:LambertConformalConicProjection

Table 144 — geosrs:LambertConformalConicProjection

URI	https://w3id.org/geosrs/projection/ LambertConformalConicProjection
Super-classes	LambertConformalConicProjection
Example	geosrs:LambertConformalConicProjection

11.4.6. Class: geosrs:MurdochIIIProjection

Table 145 — geosrs:MurdochIIIProjection

URI	https://w3id.org/geosrs/projection/MurdochIIIProjection
Super-classes	MurdochIIIProjection

11.4.7. Class: geosrs:MurdochIIProjection

Table 146 — geosrs:MurdochIIProjection

URI	https://w3id.org/geosrs/projection/MurdochIIProjection
Super-classes	MurdochIIProjection

11.4.8. Class: geosrs:MurdochIProjection

Table 147 — geosrs:MurdochIProjection

URI	https://w3id.org/geosrs/projection/MurdochIProjection
Super-classes	MurdochIProjection

11.4.9. Class: geosrs:SchjerningIProjection

Table 148 — geosrs:SchjerningIProjection

URI	https://w3id.org/geosrs/projection/SchjerningIProjection
Super-classes	SchjerningIProjection

11.4.10. Class: geosrs:VitkovskyIProjection

Table 149 — geosrs:VitkovskyIProjection

URI	https://w3id.org/geosrs/projection/VitkovskyIProjection
Super-classes	VitkovskyIProjection

11.5. Cylindrical Projections

REQUIREMENT 25: CYLINDRICAL PROJECTIONS

IDENTIFIER	/req/Cylindrical_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:ArdenCloseProjection, geosrs:BraunPerspectiveProjection, geosrs:CompactMillerProjection, geosrs:CylindricalStereographicProjection, geosrs:KarchenkoShabanovaProjection, geosrs:LabordeProjection, geosrs:MercatorProjection, geosrs:MillerProjection, geosrs:PattersonCylindricalProjection, geosrs:PavlovProjection, geosrs:ToblerCylindricalIIProjection, geosrs:ToblerCylindricalIProjection, geosrs:UrmayevIIIProjection, geosrs:WebMercatorProjection to be used in SPARQL graph patterns.

11.5.1. Class: geosrs:ArdenCloseProjection

Table 150 — geosrs:ArdenCloseProjection

URI	https://w3id.org/geosrs/projection/ArdenCloseProjection

Super-classes	ArdenCloseProjection

11.5.2. Class: geosrs:BraunPerspectiveProjection

Table 151 — geosrs:BraunPerspectiveProjection

URI	https://w3id.org/geosrs/projection/BraunPerspectiveProjection
Super-classes	BraunPerspectiveProjection

11.5.3. Class: geosrs:CompactMillerProjection

Table 152 — geosrs:CompactMillerProjection

URI	https://w3id.org/geosrs/projection/CompactMillerProjection
Super-classes	CompactMillerProjection

11.5.4. Class: geosrs:CylindricalStereographicProjection

Table 153 — geosrs:CylindricalStereographicProjection

URI	https://w3id.org/geosrs/projection/CylindricalStereographicProjection
Super-classes	CylindricalStereographicProjection

11.5.5. Class: geosrs:KarchenkoShabanovaProjection

Table 154 — geosrs:KarchenkoShabanovaProjection

URI	https://w3id.org/geosrs/projection/KarchenkoShabanovaProjection
Super-classes	KarchenkoShabanovaProjection

11.5.6. Class: geosrs:LabordeProjection

Table 155 — geosrs:LabordeProjection

URI	https://w3id.org/geosrs/projection/LabordeProjection
Super-classes	LabordeProjection
Example	geosrs:LabordeProjection

11.5.7. Class: geosrs:MercatorProjection

Table 156 — geosrs:MercatorProjection

URI	https://w3id.org/geosrs/projection/MercatorProjection
Super-classes	MercatorProjection
Example	geosrs:MercatorProjection

11.5.8. Class: geosrs:MillerProjection

Table 157 — geosrs:MillerProjection

URI	https://w3id.org/geosrs/projection/MillerProjection
Super-classes	MillerProjection

11.5.9. Class: geosrs:PattersonCylindricalProjection

Table 158 — geosrs:PattersonCylindricalProjection

URI	https://w3id.org/geosrs/projection/PattersonCylindricalProjection
Super-classes	PattersonCylindricalProjection

11.5.10. Class: geosrs:PavlovProjection

Table 159 — geosrs:PavlovProjection

URI	https://w3id.org/geosrs/projection/PavlovProjection
Super-classes	PavlovProjection

11.5.11. Class: geosrs:ToblerCylindricalIIProjection

Table 160 — geosrs:ToblerCylindricalIIProjection

URI	https://w3id.org/geosrs/projection/ToblerCylindricalIIProjection
Super-classes	ToblerCylindricalIIProjection

11.5.12. Class: geosrs:ToblerCylindricalIProjection

Table 161 — geosrs:ToblerCylindricalIProjection

URI	https://w3id.org/geosrs/projection/ToblerCylindricalIProjection
Super-classes	ToblerCylindricalIProjection

11.5.13. Class: geosrs:UrmayevIIIProjection

Table 162 — geosrs:UrmayevIIIProjection

URI	https://w3id.org/geosrs/projection/UrmayevIIIProjection
Super-classes	UrmayevIIIProjection

11.5.14. Class: geosrs:WebMercatorProjection

Table 163 — geosrs:WebMercatorProjection

URI	https://w3id.org/geosrs/projection/WebMercatorProjection
Super-classes	WebMercatorProjection

11.6. Equal Area Projections

REQUIREMENT 26: EQUAL AREA PROJECTIONS	
IDENTIFIER	/req/Equal_Area_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:AlbersEqualAreaProjection, geosrs:AzimuthalEqualAreaProjection, geosrs:CylindricalEqualArea, geosrs:GallPetersProjection, geosrs:HoboDyerProjection, geosrs:LambertAzimuthalEqualArea, geosrs:TrystanEdwardsProjection, geosrs:WiechelProjection to be used in SPARQL graph patterns.

11.6.1. Class: geosrs:AlbersEqualAreaProjection

Table 164 — geosrs:AlbersEqualAreaProjection

URI	https://w3id.org/geosrs/projection/AlbersEqualAreaProjection
Super-classes	AlbersEqualAreaProjection
Example	geosrs:AlbersEqualAreaProjection

11.6.2. Class: geosrs:AzimuthalEqualAreaProjection

Table 165 — geosrs:AzimuthalEqualAreaProjection

URI	https://w3id.org/geosrs/projection/AzimuthalEqualAreaProjection
Super-classes	AzimuthalEqualAreaProjection

11.6.3. Class: geosrs:CylindricalEqualArea

Table 166 — geosrs:CylindricalEqualArea

URI	https://w3id.org/geosrs/projection/CylindricalEqualArea
Super-classes	CylindricalEqualArea
Example	geosrs:CylindricalEqualArea

11.6.4. Class: geosrs:GallPetersProjection

Table 167 — geosrs:GallPetersProjection

URI	https://w3id.org/geosrs/projection/GallPetersProjection
Super-classes	GallPetersProjection

11.6.5. Class: geosrs:HoboDyerProjection

Table 168 — geosrs:HoboDyerProjection

URI	https://w3id.org/geosrs/projection/HoboDyerProjection
Super-classes	HoboDyerProjection

11.6.6. Class: geosrs:LambertAzimuthalEqualArea

Table 169 — geosrs:LambertAzimuthalEqualArea

URI	https://w3id.org/geosrs/projection/LambertAzimuthalEqualArea
Super-classes	LambertAzimuthalEqualArea

11.6.7. Class: geosrs:TrystanEdwardsProjection

Table 170 — geosrs:TrystanEdwardsProjection

URI	https://w3id.org/geosrs/projection/TrystanEdwardsProjection
Super-classes	TrystanEdwardsProjection

11.6.8. Class: geosrs:WiechelProjection

Table 171 — geosrs:WiechelProjection

URI	https://w3id.org/geosrs/projection/WiechelProjection
Super-classes	WiechelProjection

11.7. Equidistant Projections

REQUIREMENT 27: EQUIDISTANT PROJECTIONS	
IDENTIFIER	/req/Equidistant_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:AzimuthalEquidistantProjection, geosrs:BerghausStarProjection, geosrs:CassiniProjection, geosrs:EquidistantConicProjection, geosrs:EquidistantCylindricalProjection, geosrs:EquirectangularProjection, geosrs:ObliquePlateCarreeProjection, geosrs:PlateCarreeProjection, geosrs:TwoPointEquidistantProjection to be used in SPARQL graph patterns.

11.7.1. Class: geosrs:AzimuthalEquidistantProjection

Table 172 — geosrs:AzimuthalEquidistantProjection

URI	https://w3id.org/geosrs/projection/AzimuthalEquidistantProjection

Super-classes	AzimuthalEquidistantProjection

11.7.2. Class: geosrs:BerghausStarProjection

Table 173 — geosrs:BerghausStarProjection

URI	https://w3id.org/geosrs/projection/BerghausStarProjection
Super-classes	BerghausStarProjection

11.7.3. Class: geosrs:CassiniProjection

Table 174 — geosrs:CassiniProjection

URI	https://w3id.org/geosrs/projection/CassiniProjection
Definition	A map projection first described in an approximate form by César-François Cassini de Thury in 1745
Super-classes	CassiniProjection
Example	geosrs:CassiniProjection

11.7.4. Class: geosrs:EquidistantConicProjection

Table 175 — geosrs:EquidistantConicProjection

URI	https://w3id.org/geosrs/projection/EquidistantConicProjection
Super-classes	EquidistantConicProjection

11.7.5. Class: geosrs:EquidistantCylindricalProjection

Table 176 — geosrs:EquidistantCylindricalProjection

URI	https://w3id.org/geosrs/projection/EquidistantCylindricalProjection

Super-classes	EquidistantCylindricalProjection
Example	geosrs:EquidistantCylindricalProjection

11.7.6. Class: geosrs:EquirectangularProjection

Table 177 — geosrs:EquirectangularProjection

URI	https://w3id.org/geosrs/projection/ EquirectangularProjection
Super-classes	EquirectangularProjection

11.7.7. Class: geosrs:ObliquePlateCarreeProjection

Table 178 — geosrs:ObliquePlateCarreeProjection

URI	https://w3id.org/geosrs/projection/ ObliquePlateCarreeProjection
Super-classes	ObliquePlateCarreeProjection

11.7.8. Class: geosrs:PlateCarreeProjection

Table 179 — geosrs:PlateCarreeProjection

URI	https://w3id.org/geosrs/projection/ PlateCarreeProjection
Super-classes	PlateCarreeProjection

11.7.9. Class: geosrs:TwoPointEquidistantProjection

Table 180 — geosrs:TwoPointEquidistantProjection

URI	https://w3id.org/geosrs/projection/ TwoPointEquidistantProjection
Super-classes	TwoPointEquidistantProjection

11.8. Globular Projections

REQUIREMENT 28: GLOBULAR PROJECTIONS	
IDENTIFIER	/req/Globular_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:ApianGlobularIProjection, geosrs:Bacon GlobularProjection, geosrs:FournierGlobularIProjection to be used in SPARQL graph patterns.

11.8.1. Class: geosrs:ApianGlobularIProjection

Table 181 — geosrs:ApianGlobularIProjection

URI	https://w3id.org/geosrs/projection/ApianGlobularIProjection
Super-classes	ApianGlobularIProjection

11.8.2. Class: geosrs:BaconGlobularProjection

Table 182 — geosrs:BaconGlobularProjection

URI	https://w3id.org/geosrs/projection/BaconGlobularProjection
Super-classes	BaconGlobularProjection

11.8.3. Class: geosrs:FournierGlobularIProjection

Table 183 — geosrs:FournierGlobularIProjection

URI	https://w3id.org/geosrs/projection/FournierGlobularIProjection
Super-classes	FournierGlobularIProjection

11.9. Lenticular Projections

REQUIREMENT 29: LENTICULAR PROJECTIONS	
IDENTIFIER	/req/Lenticular_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:A4Projection, geosrs:BriesemeisterProjection, geosrs:CiriclProjection, geosrs:CupolaProjection, geosrs:DedistortProjection, geosrs:DietrichKitada Projection, geosrs:FranculaIIIProjection, geosrs:FranculaIVProjection, geosrs:FranculaIXProjection, geosrs:FranculaVIIIProjection, geosrs:FranculaVProjection, geosrs:FranculaXIIIProjection, geosrs:FranculaXIIProjection, geosrs:FranculaXIVProjection, geosrs:HamusoidalProjection, geosrs:Kiss Projection to be used in SPARQL graph patterns.

11.9.1. Class: geosrs:A4Projection

Table 184 — geosrs:A4Projection

URI	https://w3id.org/geosrs/projection/A4Projection
Super-classes	A4Projection

11.9.2. Class: geosrs:BriesemeisterProjection

Table 185 — geosrs:BriesemeisterProjection

URI	https://w3id.org/geosrs/projection/BriesemeisterProjection
Super-classes	BriesemeisterProjection

11.9.3. Class: geosrs:CiriclProjection

Table 186 — geosrs:CiriclProjection

URI	https://w3id.org/geosrs/projection/CiriclProjection
Super-classes	CiriclProjection

11.9.4. Class: geosrs:CupolaProjection

Table 187 — geosrs:CupolaProjection

URI	https://w3id.org/geosrs/projection/CupolaProjection
Super-classes	CupolaProjection

11.9.5. Class: geosrs:DedistortProjection

Table 188 — geosrs:DedistortProjection

URI	https://w3id.org/geosrs/projection/DedistortProjection
Super-classes	DedistortProjection

11.9.6. Class: geosrs:DietrichKitadaProjection

Table 189 — geosrs:DietrichKitadaProjection

URI	https://w3id.org/geosrs/projection/DietrichKitadaProjection
Super-classes	DietrichKitadaProjection

11.9.7. Class: geosrs:FranculaIIIProjection

Table 190 — geosrs:FranculaIIIProjection

URI	https://w3id.org/geosrs/projection/FranculaIIIProjection
Super-classes	FranculaIIIProjection

11.9.8. Class: geosrs:FranculaIVProjection

Table 191 — geosrs:FranculaIVProjection

URI	https://w3id.org/geosrs/projection/FranculaIVProjection
Super-classes	FranculaIVProjection

11.9.9. Class: geosrs:FranculaIXProjection

Table 192 — geosrs:FranculaIXProjection

URI	https://w3id.org/geosrs/projection/FranculaIXProjection
Super-classes	FranculaIXProjection

11.9.10. Class: geosrs:FranculaVIIIProjection

Table 193 — geosrs:FranculaVIIIProjection

URI	https://w3id.org/geosrs/projection/FranculaVIIIProjection
Super-classes	FranculaVIIIProjection

11.9.11. Class: geosrs:FranculaVProjection

Table 194 — geosrs:FranculaVProjection

URI	https://w3id.org/geosrs/projection/FranculaVProjection
Super-classes	FranculaVProjection

11.9.12. Class: geosrs:FranculaXIIIProjection

Table 195 — geosrs:FranculaXIIIProjection

URI	https://w3id.org/geosrs/projection/FranculaXIIIProjection
Super-classes	FranculaXIIIProjection

11.9.13. Class: geosrs:FranculaXIIProjection

Table 196 — geosrs:FranculaXIIProjection

URI	https://w3id.org/geosrs/projection/FranculaXIIProjection
Super-classes	FranculaXIIProjection

11.9.14. Class: geosrs:FranculaXIVProjection

Table 197 — geosrs:FranculaXIVProjection

URI	https://w3id.org/geosrs/projection/FranculaXIVProjection
Super-classes	FranculaXIVProjection

11.9.15. Class: geosrs:HamusoidalProjection

Table 198 — geosrs:HamusoidalProjection

URI	https://w3id.org/geosrs/projection/HamusoidalProjection
Super-classes	HamusoidalProjection

11.9.16. Class: geosrs:KissProjection

Table 199 — geosrs:KissProjection

URI	https://w3id.org/geosrs/projection/KissProjection
Super-classes	KissProjection

11.10. Minimum Error Projections

REQUIREMENT 30: MINIMUM ERROR PROJECTIONS	
IDENTIFIER	/req/Minimum_Error_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:AiryProjection to be used in SPARQL graph patterns.

11.10.1. Class: geosrs:AiryProjection

Table 200 — geosrs:AiryProjection

URI	https://w3id.org/geosrs/projection/AiryProjection
Definition	An azimuthal minimum error projection for the region within the small or great circle defined by an angular distance, from the tangency point of the plane
Super-classes	AiryProjection

11.11. Perspective Projections

REQUIREMENT 31: PERSPECTIVE PROJECTIONS	
IDENTIFIER	/req/Perspective_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:CentralCylindricalProjection, geosrs:General VerticalPerspectiveProjection, geosrs:GilbertTwoWorldPerspectiveProjection, geosrs:LaHire Projection, geosrs:LorgnaProjection, geosrs:LowryProjection, geosrs:OrthographicProjection, geosrs:PerspectiveConicProjection, geosrs:TiltedPerspectiveProjection, geosrs:VerticalPerspective Projection to be used in SPARQL graph patterns.

11.11.1. Class: geosrs:CentralCylindricalProjection

Table 201 — geosrs:CentralCylindricalProjection

URI	https://w3id.org/geosrs/projection/CentralCylindricalProjection
Super-classes	CentralCylindricalProjection

11.11.2. Class: geosrs:GeneralVerticalPerspectiveProjection

Table 202 — geosrs:GeneralVerticalPerspectiveProjection

URI	https://w3id.org/geosrs/projection/GeneralVerticalPerspectiveProjection
Super-classes	GeneralVerticalPerspectiveProjection

11.11.3. Class: geosrs:GilbertTwoWorldPerspectiveProjection

Table 203 — geosrs:GilbertTwoWorldPerspectiveProjection

URI	https://w3id.org/geosrs/projection/GilbertTwoWorldPerspectiveProjection
Super-classes	GilbertTwoWorldPerspectiveProjection

11.11.4. Class: geosrs:LaHireProjection

Table 204 — geosrs:LaHireProjection

URI	https://w3id.org/geosrs/projection/LaHireProjection
Super-classes	LaHireProjection

11.11.5. Class: geosrs:LorgnaProjection

Table 205 — geosrs:LorgnaProjection

URI	https://w3id.org/geosrs/projection/LorgnaProjection

Super-classes	LorgnaProjection

11.11.6. Class: geosrs:LowryProjection

Table 206 — geosrs:LowryProjection

URI	https://w3id.org/geosrs/projection/LowryProjection
Super-classes	LowryProjection

11.11.7. Class: geosrs:OrthographicProjection

Table 207 — geosrs:OrthographicProjection

URI	https://w3id.org/geosrs/projection/OrthographicProjection
Super-classes	OrthographicProjection

11.11.8. Class: geosrs:PerspectiveConicProjection

Table 208 — geosrs:PerspectiveConicProjection

URI	https://w3id.org/geosrs/projection/PerspectiveConicProjection
Super-classes	PerspectiveConicProjection

11.11.9. Class: geosrs:TiltedPerspectiveProjection

Table 209 — geosrs:TiltedPerspectiveProjection

URI	https://w3id.org/geosrs/projection/TiltedPerspectiveProjection
Super-classes	TiltedPerspectiveProjection

11.11.10. Class: geosrs:VerticalPerspectiveProjection

Table 210 — geosrs:VerticalPerspectiveProjection

URI	https://w3id.org/geosrs/projection/ VerticalPerspectiveProjection
Super-classes	VerticalPerspectiveProjection

11.12. Polyconic Projections

REQUIREMENT 32: POLYCONIC PROJECTIONS	
IDENTIFIER	/req/Polyconic_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:GinzburgIVProjection, geosrs:Ginzburg IXProjection, geosrs:GinzburgVIProjection, geosrs:GinzburgVProjection, geosrs:GottWagner Projection, geosrs:HillEucyclicProjection, geosrs:LagrangeProjection, geosrs:LaskowskiProjection, geosrs:RectangularPolyconicProjection, geosrs:StabiusWernerIIIProjection, geosrs:StabiusWerner IProjection, geosrs:VanDerGrintenIIProjection, geosrs:VanDerGrintenIProjection, geosrs:Van DerGrintenIVProjection, geosrs:WagnerIXProjection, geosrs:WagnerVIIIProjection, geosrs:Wagner VIIProjection to be used in SPARQL graph patterns.

11.12.1. Class: geosrs:GinzburgIVProjection

Table 211 — geosrs:GinzburgIVProjection

URI	https://w3id.org/geosrs/projection/GinzburgIVProjection
Super-classes	GinzburgIVProjection

11.12.2. Class: geosrs:GinzburgIXProjection

Table 212 — geosrs:GinzburgIXProjection

URI	https://w3id.org/geosrs/projection/GinzburgIXProjection

Super-classes	GinzburgIXProjection

11.12.3. Class: geosrs:GinzburgVIProjection

Table 213 — geosrs:GinzburgVIProjection

URI	https://w3id.org/geosrs/projection/GinzburgVIProjection
Super-classes	GinzburgVIProjection

11.12.4. Class: geosrs:GinzburgVProjection

Table 214 — geosrs:GinzburgVProjection

URI	https://w3id.org/geosrs/projection/GinzburgVProjection
Super-classes	GinzburgVProjection

11.12.5. Class: geosrs:GottWagnerProjection

Table 215 — geosrs:GottWagnerProjection

URI	https://w3id.org/geosrs/projection/GottWagnerProjection
Super-classes	GottWagnerProjection

11.12.6. Class: geosrs:HillEucyclicProjection

Table 216 — geosrs:HillEucyclicProjection

URI	https://w3id.org/geosrs/projection/HillEucyclicProjection
Super-classes	HillEucyclicProjection

11.12.7. Class: geosrs:LagrangeProjection

Table 217 — geosrs:LagrangeProjection

URI	https://w3id.org/geosrs/projection/LagrangeProjection
Super-classes	LagrangeProjection

11.12.8. Class: geosrs:LaskowskiProjection

Table 218 — geosrs:LaskowskiProjection

URI	https://w3id.org/geosrs/projection/LaskowskiProjection
Super-classes	LaskowskiProjection

11.12.9. Class: geosrs:RectangularPolyconicProjection

Table 219 — geosrs:RectangularPolyconicProjection

URI	https://w3id.org/geosrs/projection/RectangularPolyconicProjection
Super-classes	RectangularPolyconicProjection

11.12.10. Class: geosrs:StabiusWernerIIIProjection

Table 220 — geosrs:StabiusWernerIIIProjection

URI	https://w3id.org/geosrs/projection/StabiusWernerIIIProjection
Super-classes	StabiusWernerIIIProjection

11.12.11. Class: geosrs:StabiusWernerIProjection

Table 221 — geosrs:StabiusWernerIProjection

URI	https://w3id.org/geosrs/projection/StabiusWernerIProjection
Super-classes	StabiusWernerIProjection

11.12.12. Class: geosrs:VanDerGrintenIIProjection

Table 222 — geosrs:VanDerGrintenIIProjection

URI	https://w3id.org/geosrs/projection/VanDerGrintenIIProjection
Super-classes	VanDerGrintenIIProjection

11.12.13. Class: geosrs:VanDerGrintenIProjection

Table 223 — geosrs:VanDerGrintenIProjection

URI	https://w3id.org/geosrs/projection/VanDerGrintenIProjection
Super-classes	VanDerGrintenIProjection

11.12.14. Class: geosrs:VanDerGrintenIVProjection

Table 224 — geosrs:VanDerGrintenIVProjection

URI	https://w3id.org/geosrs/projection/VanDerGrintenIVProjection
Super-classes	VanDerGrintenIVProjection

11.12.15. Class: geosrs:WagnerIXProjection

Table 225 — geosrs:WagnerIXProjection

URI	https://w3id.org/geosrs/projection/WagnerIXProjection

Super-classes	WagnerIXProjection

11.12.16. Class: geosrs:WagnerVIIIProjection

Table 226 — geosrs:WagnerVIIIProjection

URI	https://w3id.org/geosrs/projection/WagnerVIIIProjection
Super-classes	WagnerVIIIProjection

11.12.17. Class: geosrs:WagnerVIIProjection

Table 227 — geosrs:WagnerVIIProjection

URI	https://w3id.org/geosrs/projection/WagnerVIIProjection
Super-classes	WagnerVIIProjection

11.13. Polyhedral Projections

REQUIREMENT 33: POLYHEDRAL PROJECTIONS	
IDENTIFIER	/req/Polyhedral_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:AuthaGraphProjection, geosrs:CahillKeyes Projection, geosrs:CollignonButterflyProjection, geosrs:DodecahedralProjection, geosrs:Dymaxion Projection, geosrs:GnomonicButterflyProjection, geosrs:GnomonicCubedSphereProjection, geosrs: GnomonicIcosahedronProjection, geosrs:GuyouProjection, geosrs:IcosahedralProjection, geosrs:Lee Projection, geosrs:MyrahedalProjection, geosrs:OctantProjection, geosrs:QuadrilateralizedSpherical CubeProjection, geosrs:WatermanButterflyProjection to be used in SPARQL graph patterns.

11.13.1. Class: geosrs:AuthaGraphProjection

Table 228 — geosrs:AuthaGraphProjection

URI	https://w3id.org/geosrs/projection/AuthaGraphProjection
Super-classes	AuthaGraphProjection

11.13.2. Class: geosrs:CahillKeyesProjection

Table 229 — geosrs:CahillKeyesProjection

URI	https://w3id.org/geosrs/projection/CahillKeyesProjection
Super-classes	CahillKeyesProjection

11.13.3. Class: geosrs:CollignonButterflyProjection

Table 230 — geosrs:CollignonButterflyProjection

URI	https://w3id.org/geosrs/projection/CollignonButterflyProjection
Super-classes	CollignonButterflyProjection

11.13.4. Class: geosrs:DodecahedralProjection

Table 231 — geosrs:DodecahedralProjection

URI	https://w3id.org/geosrs/projection/DodecahedralProjection
Super-classes	DodecahedralProjection

11.13.5. Class: geosrs:DymaxionProjection

Table 232 — geosrs:DymaxionProjection

URI	https://w3id.org/geosrs/projection/DymaxionProjection

Super-classes	DymaxionProjection

11.13.6. Class: geosrs:GnomonicButterflyProjection

Table 233 — geosrs:GnomonicButterflyProjection

URI	https://w3id.org/geosrs/projection/GnomonicButterflyProjection
Super-classes	GnomonicButterflyProjection

11.13.7. Class: geosrs:GnomonicCubedSphereProjection

Table 234 — geosrs:GnomonicCubedSphereProjection

URI	https://w3id.org/geosrs/projection/GnomonicCubedSphereProjection
Super-classes	GnomonicCubedSphereProjection

11.13.8. Class: geosrs:GnomonicIcosahedronProjection

Table 235 — geosrs:GnomonicIcosahedronProjection

URI	https://w3id.org/geosrs/projection/GnomonicIcosahedronProjection
Super-classes	GnomonicIcosahedronProjection

11.13.9. Class: geosrs:GuyouProjection

Table 236 — geosrs:GuyouProjection

URI	https://w3id.org/geosrs/projection/GuyouProjection
Super-classes	GuyouProjection

11.13.10. Class: geosrs:IcosahedralProjection

Table 237 — geosrs:IcosahedralProjection

URI	https://w3id.org/geosrs/projection/IcosahedralProjection
Super-classes	IcosahedralProjection

11.13.11. Class: geosrs:LeeProjection

Table 238 — geosrs:LeeProjection

URI	https://w3id.org/geosrs/projection/LeeProjection
Super-classes	LeeProjection

11.13.12. Class: geosrs:MyrahedalProjection

Table 239 — geosrs:MyrahedalProjection

URI	https://w3id.org/geosrs/projection/MyrahedalProjection
Super-classes	MyrahedalProjection

11.13.13. Class: geosrs:OctantProjection

Table 240 — geosrs:OctantProjection

URI	https://w3id.org/geosrs/projection/OctantProjection
Super-classes	OctantProjection

11.13.14. Class: geosrs:QuadrilateralizedSphericalCubeProjection

Table 241 — geosrs:QuadrilateralizedSphericalCubeProjection

URI	https://w3id.org/geosrs/projection/QuadrilateralizedSphericalCubeProjection
Super-classes	QuadrilateralizedSphericalCubeProjection

11.13.15. Class: geosrs:WatermanButterflyProjection

Table 242 — geosrs:WatermanButterflyProjection

URI	https://w3id.org/geosrs/projection/WatermanButterflyProjection
Super-classes	WatermanButterflyProjection

11.14. Pseudo Azimuthal Projections

REQUIREMENT 34: PSEUDO AZIMUTHAL PROJECTIONS	
IDENTIFIER	/req/Pseudo_Azimuthal_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:AitoffObliqueProjection, geosrs:Aitoff Projection, geosrs:HammerProjection, geosrs:Strebe1995Projection, geosrs:WinkelTripel Projection to be used in SPARQL graph patterns.

11.14.1. Class: geosrs:AitoffObliqueProjection

Table 243 — geosrs:AitoffObliqueProjection

URI	https://w3id.org/geosrs/projection/AitoffObliqueProjection
Super-classes	AitoffObliqueProjection

11.14.2. Class: geosrs:AitoffProjection

Table 244 — geosrs:AitoffProjection

URI	https://w3id.org/geosrs/projection/AitoffProjection
Definition	A modified azimuthal projection whose graticule takes the form of an ellipse
Super-classes	AitoffProjection

11.14.3. Class: geosrs:HammerProjection

Table 245 — geosrs:HammerProjection

URI	https://w3id.org/geosrs/projection/HammerProjection
Super-classes	HammerProjection

11.14.4. Class: geosrs:Strebe1995Projection

Table 246 — geosrs:Strebe1995Projection

URI	https://w3id.org/geosrs/projection/Strebe1995Projection
Super-classes	Strebe1995Projection

11.14.5. Class: geosrs:WinkelTripelProjection

Table 247 — geosrs:WinkelTripelProjection

URI	https://w3id.org/geosrs/projection/WinkelTripelProjection
Super-classes	WinkelTripelProjection

11.15. Pseudo Conical Projections

11.15.1. Class: geosrs:AmericanPolyconicProjection

Table 248 — geosrs:AmericanPolyconicProjection

URI	https://w3id.org/geosrs/projection/AmericanPolyconicProjection
Super-classes	AmericanPolyconicProjection
Example	geosrs:AmericanPolyconicProjection

11.15.2. Class: geosrs:BonneProjection

Table 249 — geosrs:BonneProjection

URI	https://w3id.org/geosrs/projection/BonneProjection
Super-classes	BonneProjection

11.15.3. Class: geosrs:BottomleyProjection

Table 250 — geosrs:BottomleyProjection

URI	https://w3id.org/geosrs/projection/BottomleyProjection
Super-classes	BottomleyProjection

11.15.4. Class: geosrs:NicolosiGlobularProjection

Table 251 — geosrs:NicolosiGlobularProjection

URI	https://w3id.org/geosrs/projection/ NicolosiGlobularProjection
Super-classes	NicolosiGlobularProjection

11.15.5. Class: geosrs:PtolemyIIProjection

Table 252 — geosrs:PtolemyIIProjection

URI	https://w3id.org/geosrs/projection/PtolemyIIProjection
Super-classes	PtolemyIIProjection

11.15.6. Class: geosrs:WernerProjection

Table 253 — geosrs:WernerProjection

URI	https://w3id.org/geosrs/projection/WernerProjection
Super-classes	WernerProjection

11.16. Pseudo Cylindrical Projections

REQUIREMENT 36: PSEUDO CYLINDRICAL PROJECTIONS	
IDENTIFIER	/req/Pseudo_Cylindrical_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:ApianIIProjection, geosrs:AtlantisProjection, geosrs:BaranyiIIIProjection, geosrs:BaranyiIIProjection, geosrs:BaranyiIProjection, geosrs:Baranyi IVProjection, geosrs:BoggsEumorphicProjection, geosrs:BromleyProjection, geosrs:CabotProjection, geosrs:CollignonProjection, geosrs:CrasterParabolicProjection, geosrs:DeakinMinimumError Projection, geosrs:Eckert1Projection, geosrs:Eckert2Projection, geosrs:Eckert3Projection, geosrs: Eckert4Projection, geosrs:Eckert5Projection, geosrs:Eckert6Projection, geosrs:EqualEarth Projection, geosrs:FaheyProjection, geosrs:FoucautProjection, geosrs:FoucautSinusoidalProjection, geosrs:FournierIIProjection, geosrs:GinzburgVIIIProjection, geosrs:GoodeHomolosineProjection, geosrs:HEALPixProjection, geosrs:HufnagelProjection, geosrs:Kavrayskiy7Projection, geosrs: LoximuthalProjection, geosrs:MayrProjection, geosrs:McBrydeThomasFlatPolarParabolicProjection,

geosrs:McBrydeThomasFlatPolarQuarticProjection, geosrs:McBrydeThomasFlatPolarSinusoidal Projection, geosrs:McBrydeThomasIIProjection, geosrs:McBrydeThomasIProjection, geosrs:Natural Earth2Projection, geosrs:NaturalEarthProjection, geosrs:NellHammerProjection, geosrs:Nell Projection, geosrs:OrteliusOvalProjection, geosrs:PutninsP1Projection, geosrs:PutninsP2Projection, geosrs:PutninsP3Projection, geosrs:PutninsP5Projection, geosrs:PutninsP6Projection, geosrs: QuarticAuthalicProjection, geosrs:RobinsonProjection, geosrs:SinusoidalProjection, geosrs:The TimesProjection, geosrs:ToblerG1Projection, geosrs:ToblerHyperellipticalProjection, geosrs:Wagner IIIProjection, geosrs:WagnerIIProjection, geosrs:WagnerIProjection, geosrs:WagnerIVProjection, geosrs:WagnerVIProjection, geosrs:WagnerVProjection, geosrs:WerenskioldIProjection, geosrs: PutninsP3'Projection, geosrs:PutninsP4'Projection, geosrs:PutninsP5'Projection, geosrs:Putnins P6'Projection to be used in SPARQL graph patterns.

11.16.1. Class: geosrs:ApianIIProjection

Table 254 — geosrs:ApianIIProjection

URI	https://w3id.org/geosrs/projection/ApianIIProjection
Super-classes	ApianIIProjection

11.16.2. Class: geosrs:AtlantisProjection

Table 255 — geosrs:AtlantisProjection

URI	https://w3id.org/geosrs/projection/AtlantisProjection
Super-classes	AtlantisProjection

11.16.3. Class: geosrs:BaranyiIIIProjection

Table 256 — geosrs:BaranyiIIIProjection

URI	https://w3id.org/geosrs/projection/BaranyiIIIProjection
Super-classes	BaranyiIIIProjection

11.16.4. Class: geosrs:BaranyiIIProjection

Table 257 — geosrs:BaranyiIIProjection

URI	https://w3id.org/geosrs/projection/BaranyiIIProjection
Super-classes	BaranyiIIProjection

11.16.5. Class: geosrs:BaranyiIProjection

Table 258 — geosrs:BaranyiIProjection

URI	https://w3id.org/geosrs/projection/BaranyiIProjection
Super-classes	BaranyiIProjection

11.16.6. Class: geosrs:BaranyiIVProjection

Table 259 — geosrs:BaranyiIVProjection

URI	https://w3id.org/geosrs/projection/BaranyiIVProjection
Super-classes	BaranyiIVProjection

11.16.7. Class: geosrs:BoggsEumorphicProjection

Table 260 — geosrs:BoggsEumorphicProjection

URI	https://w3id.org/geosrs/projection/BoggsEumorphicProjection
Super-classes	BoggsEumorphicProjection

11.16.8. Class: geosrs:BromleyProjection

Table 261 — geosrs:BromleyProjection

URI	https://w3id.org/geosrs/projection/BromleyProjection
Super-classes	BromleyProjection

11.16.9. Class: geosrs:CabotProjection

Table 262 — geosrs:CabotProjection

URI	https://w3id.org/geosrs/projection/CabotProjection
Super-classes	CabotProjection

11.16.10. Class: geosrs:CollignonProjection

Table 263 — geosrs:CollignonProjection

URI	https://w3id.org/geosrs/projection/CollignonProjection
Definition	An equal-area pseudocylindrical projection that maps the sphere onto a triangle or diamond
Super-classes	CollignonProjection

11.16.11. Class: geosrs:CrasterParabolicProjection

Table 264 — geosrs:CrasterParabolicProjection

URI	https://w3id.org/geosrs/projection/CrasterParabolicProjection
Super-classes	CrasterParabolicProjection

11.16.12. Class: geosrs:DeakinMinimumErrorProjection

Table 265 — geosrs:DeakinMinimumErrorProjection

URI	https://w3id.org/geosrs/projection/ DeakinMinimumErrorProjection
Super-classes	DeakinMinimumErrorProjection

11.16.13. Class: geosrs:Eckert1Projection

Table 266 — geosrs:Eckert1Projection

URI	https://w3id.org/geosrs/projection/Eckert1Projection
Super-classes	Eckert1Projection

11.16.14. Class: geosrs:Eckert2Projection

Table 267 — geosrs:Eckert2Projection

URI	https://w3id.org/geosrs/projection/Eckert2Projection
Super-classes	Eckert2Projection

11.16.15. Class: geosrs:Eckert3Projection

Table 268 — geosrs:Eckert3Projection

URI	https://w3id.org/geosrs/projection/Eckert3Projection
Super-classes	Eckert3Projection

11.16.16. Class: geosrs:Eckert4Projection

Table 269 — geosrs:Eckert4Projection

URI	https://w3id.org/geosrs/projection/Eckert4Projection
Super-classes	Eckert4Projection

11.16.17. Class: geosrs:Eckert5Projection

Table 270 — geosrs:Eckert5Projection

URI	https://w3id.org/geosrs/projection/Eckert5Projection
Super-classes	Eckert5Projection

11.16.18. Class: geosrs:Eckert6Projection

Table 271 — geosrs:Eckert6Projection

URI	https://w3id.org/geosrs/projection/Eckert6Projection
Super-classes	Eckert6Projection

11.16.19. Class: geosrs:EqualEarthProjection

Table 272 — geosrs:EqualEarthProjection

URI	https://w3id.org/geosrs/projection/EqualEarthProjection
Super-classes	EqualEarthProjection
Example	geosrs:EqualEarthProjection

11.16.20. Class: geosrs:FaheyProjection

Table 273 — geosrs:FaheyProjection

URI	https://w3id.org/geosrs/projection/FaheyProjection
Super-classes	FaheyProjection

11.16.21. Class: geosrs:FoucautProjection

Table 274 — geosrs:FoucautProjection

URI	https://w3id.org/geosrs/projection/FoucautProjection
Super-classes	FoucautProjection

11.16.22. Class: geosrs:FoucautSinusoidalProjection

Table 275 — geosrs:FoucautSinusoidalProjection

URI	https://w3id.org/geosrs/projection/FoucautSinusoidalProjection
Super-classes	FoucautSinusoidalProjection

11.16.23. Class: geosrs:FournierIIProjection

Table 276 — geosrs:FournierIIProjection

URI	https://w3id.org/geosrs/projection/FournierIIProjection
Super-classes	FournierIIProjection

11.16.24. Class: geosrs:GinzburgVIIIProjection

Table 277 — geosrs:GinzburgVIIIProjection

URI	https://w3id.org/geosrs/projection/GinzburgVIIIProjection
Super-classes	GinzburgVIIIProjection

11.16.25. Class: geosrs:GoodeHomolosineProjection

Table 278 — geosrs:GoodeHomolosineProjection

URI	https://w3id.org/geosrs/projection/ GoodeHomolosineProjection
Super-classes	GoodeHomolosineProjection

11.16.26. Class: geosrs:HEALPixProjection

Table 279 — geosrs:HEALPixProjection

URI	https://w3id.org/geosrs/projection/HEALPixProjection
Super-classes	HEALPixProjection

11.16.27. Class: geosrs:HufnagelProjection

Table 280 — geosrs:HufnagelProjection

URI	https://w3id.org/geosrs/projection/HufnagelProjection
Super-classes	HufnagelProjection

11.16.28. Class: geosrs:Kavrayskiy7Projection

Table 281 — geosrs:Kavrayskiy7Projection

URI	https://w3id.org/geosrs/projection/ Kavrayskiy7Projection
Super-classes	Kavrayskiy7Projection

11.16.29. Class: geosrs:LoximuthalProjection

Table 282 — geosrs:LoximuthalProjection

URI	https://w3id.org/geosrs/projection/LoximuthalProjection
Super-classes	LoximuthalProjection

11.16.30. Class: geosrs:MayrProjection

Table 283 — geosrs:MayrProjection

URI	https://w3id.org/geosrs/projection/MayrProjection
Super-classes	MayrProjection

11.16.31. Class: geosrs:McBrydeThomasFlatPolarParabolicProjection

Table 284 — geosrs:McBrydeThomasFlatPolarParabolicProjection

URI	https://w3id.org/geosrs/projection/McBrydeThomasFlatPolarParabolicProjection
Super-classes	McBrydeThomasFlatPolarParabolicProjection

11.16.32. Class: geosrs:McBrydeThomasFlatPolarQuarticProjection

Table 285 — geosrs:McBrydeThomasFlatPolarQuarticProjection

URI	https://w3id.org/geosrs/projection/McBrydeThomasFlatPolarQuarticProjection
Super-classes	McBrydeThomasFlatPolarQuarticProjection

11.16.33. Class: geosrs:McBrydeThomasFlatPolarSinusoidalProjection

Table 286 — geosrs:McBrydeThomasFlatPolarSinusoidalProjection

URI	https://w3id.org/geosrs/projection/McBrydeThomasFlatPolarSinusoidalProjection
Super-classes	McBrydeThomasFlatPolarSinusoidalProjection

11.16.34. Class: geosrs:McBrydeThomasIIProjection

Table 287 — geosrs:McBrydeThomasIIProjection

URI	https://w3id.org/geosrs/projection/McBrydeThomasIIProjection
Super-classes	McBrydeThomasIIProjection

11.16.35. Class: geosrs:McBrydeThomasIProjection

Table 288 — geosrs:McBrydeThomasIProjection

URI	https://w3id.org/geosrs/projection/McBrydeThomasIProjection
Super-classes	McBrydeThomasIProjection

11.16.36. Class: geosrs:NaturalEarth2Projection

Table 289 — geosrs:NaturalEarth2Projection

URI	https://w3id.org/geosrs/projection/NaturalEarth2Projection
Super-classes	NaturalEarth2Projection

11.16.37. Class: geosrs:NaturalEarthProjection

Table 290 — geosrs:NaturalEarthProjection

URI	https://w3id.org/geosrs/projection/NaturalEarthProjection
Definition	A pseudocylindrical map projection designed by Tom Patterson and introduced in 2008
Super-classes	NaturalEarthProjection

11.16.38. Class: geosrs:NellHammerProjection

Table 291 — geosrs:NellHammerProjection

URI	https://w3id.org/geosrs/projection/ NellHammerProjection
Super-classes	NellHammerProjection

11.16.39. Class: geosrs:NellProjection

Table 292 — geosrs:NellProjection

URI	https://w3id.org/geosrs/projection/NellProjection
Super-classes	NellProjection

11.16.40. Class: geosrs:OrteliusOvalProjection

Table 293 — geosrs:OrteliusOvalProjection

URI	https://w3id.org/geosrs/projection/ OrteliusOvalProjection
Super-classes	OrteliusOvalProjection

11.16.41. Class: geosrs:PutninsP1Projection

Table 294 — geosrs:PutninsP1Projection

URI	https://w3id.org/geosrs/projection/PutninsP1Projection
Super-classes	PutninsP1Projection

11.16.42. Class: geosrs:PutninsP2Projection

Table 295 — geosrs:PutninsP2Projection

URI	https://w3id.org/geosrs/projection/PutninsP2Projection
Super-classes	PutninsP2Projection

11.16.43. Class: geosrs:PutninsP3Projection

Table 296 — geosrs:PutninsP3Projection

URI	https://w3id.org/geosrs/projection/PutninsP3Projection
Super-classes	PutninsP3Projection

11.16.44. Class: geosrs:PutninsP5Projection

Table 297 — geosrs:PutninsP5Projection

URI	https://w3id.org/geosrs/projection/PutninsP5Projection
Super-classes	PutninsP5Projection

11.16.45. Class: geosrs:PutninsP6Projection

Table 298 — geosrs:PutninsP6Projection

URI	https://w3id.org/geosrs/projection/PutninsP6Projection
Super-classes	PutninsP6Projection

11.16.46. Class: geosrs:QuarticAuthalicProjection

Table 299 — geosrs:QuarticAuthalicProjection

URI	https://w3id.org/geosrs/projection/QuarticAuthalicProjection
Super-classes	QuarticAuthalicProjection

11.16.47. Class: geosrs:RobinsonProjection

Table 300 — geosrs:RobinsonProjection

URI	https://w3id.org/geosrs/projection/RobinsonProjection
Super-classes	RobinsonProjection

11.16.48. Class: geosrs:SinusoidalProjection

Table 301 — geosrs:SinusoidalProjection

URI	https://w3id.org/geosrs/projection/SinusoidalProjection
Super-classes	SinusoidalProjection

11.16.49. Class: geosrs:TheTimesProjection

Table 302 — geosrs:TheTimesProjection

URI	https://w3id.org/geosrs/projection/TheTimesProjection
Super-classes	TheTimesProjection

11.16.50. Class: geosrs:ToblerG1Projection

Table 303 — geosrs:ToblerG1Projection

URI	https://w3id.org/geosrs/projection/ToblerG1Projection
Super-classes	ToblerG1Projection

11.16.51. Class: geosrs:ToblerHyperellipticalProjection

Table 304 — geosrs:ToblerHyperellipticalProjection

URI	https://w3id.org/geosrs/projection/ToblerHyperellipticalProjection
Super-classes	ToblerHyperellipticalProjection

11.16.52. Class: geosrs:WagnerIIIProjection

Table 305 — geosrs:WagnerIIIProjection

URI	https://w3id.org/geosrs/projection/WagnerIIIProjection
Super-classes	WagnerIIIProjection

11.16.53. Class: geosrs:WagnerIIProjection

Table 306 — geosrs:WagnerIIProjection

URI	https://w3id.org/geosrs/projection/WagnerIIProjection
Super-classes	WagnerIIProjection

11.16.54. Class: geosrs:WagnerIProjection

Table 307 — geosrs:WagnerIProjection

URI	https://w3id.org/geosrs/projection/WagnerIProjection
Super-classes	WagnerIProjection

11.16.55. Class: geosrs:WagnerIVProjection

Table 308 — geosrs:WagnerIVProjection

URI	https://w3id.org/geosrs/projection/WagnerIVProjection
Super-classes	WagnerIVProjection

11.16.56. Class: geosrs:WagnerVIProjection

Table 309 — geosrs:WagnerVIProjection

URI	https://w3id.org/geosrs/projection/WagnerVIProjection
Super-classes	WagnerVIProjection

11.16.57. Class: geosrs:WagnerVProjection

Table 310 — geosrs:WagnerVProjection

URI	https://w3id.org/geosrs/projection/WagnerVProjection
Super-classes	WagnerVProjection

11.16.58. Class: geosrs:WerenskioldIProjection

Table 311 — geosrs:WerenskioldIProjection

URI	https://w3id.org/geosrs/projection/WerenskioldIProjection
Super-classes	WerenskioldIProjection

11.16.59. Class: geosrs:PutninsP3'Projection

Table 312 — geosrs:PutninsP3'Projection

URI	https://w3id.org/geosrs/projection/PutninsP3'Projection
Super-classes	PutninsP3'Projection

11.16.60. Class: geosrs:PutninsP4'Projection

Table 313 — geosrs:PutninsP4'Projection

URI	https://w3id.org/geosrs/projection/PutninsP4'Projection
Super-classes	PutninsP4'Projection

11.16.61. Class: geosrs:PutninsP5'Projection

Table 314 — geosrs:PutninsP5'Projection

URI	https://w3id.org/geosrs/projection/PutninsP5'Projection
Super-classes	PutninsP5'Projection

11.16.62. Class: geosrs:PutninsP6'Projection

Table 315 — geosrs:PutninsP6'Projection

URI	https://w3id.org/geosrs/projection/PutninsP6'Projection
Super-classes	PutninsP6'Projection

11.17. Stereographic Projections

REQUIREMENT 37: STEREOGRAPHIC PROJECTIONS	
IDENTIFIER	/req/Stereographic_Projections
STATEMENT	Implementations shall allow the RDFS classes geosrs:MillerOblatedStereographicProjection, geosrs:RoussilheProjection to be used in SPARQL graph patterns.

11.17.1. Class: geosrs:MillerOblatedStereographicProjection

Table 316 — geosrs:MillerOblatedStereographicProjection

URI	https://w3id.org/geosrs/projection/ MillerOblatedStereographicProjection
Super-classes	MillerOblatedStereographicProjection

11.17.2. Class: geosrs:RoussilheProjection

Table 317 — geosrs:RoussilheProjection

URI	https://w3id.org/geosrs/projection/RoussilheProjection
Super-classes	RoussilheProjection

12

PLANET MODULE

12 PLANET MODULE

This clause establishes the **PLANET** Requirements class, with IRI `/req/planet`, which has a corresponding Conformance Class, **PLANET**, with IRI `/conf/planet`.

REQUIREMENTS CLASS 7: 12-PLANET_EXTENSION.ADOC EXTENSION	
IDENTIFIER	/req/12-planet_extension.adoc
TARGET TYPE	Implementation Specification
REQUIREMENT	/req/Interstellar_Body

12.1. Interstellar Body

REQUIREMENT 38: INTERSTELLAR BODY	
IDENTIFIER	/req/Interstellar_Body
STATEMENT	Implementations shall allow the RDFS classes geosrs:ArtificialSatellite, geosrs:Asteroid, geosrs:Comet, geosrs:DwarfPlanet, geosrs:InterstellarBody, geosrs:Moon, geosrs:NaturalSatellite, geosrs:Planet, geosrs:PlanetStatus, geosrs:Plutoid, geosrs:Star to be used in SPARQL graph patterns.

12.1.1. Class: geosrs:ArtificialSatellite

Table 318 — geosrs:ArtificialSatellite

URI	https://w3id.org/geosrs/planet/ArtificialSatellite

12.1.2. Class: geosrs:Asteroid

Table 319 — geosrs:Asteroid

URI	https://w3id.org/geosrs/planet/Asteroid

12.1.3. Class: geosrs:Comet

Table 320 — geosrs:Comet

URI	https://w3id.org/geosrs/planet/Comet

12.1.4. Class: geosrs:DwarfPlanet

Table 321 — geosrs:DwarfPlanet

URI	https://w3id.org/geosrs/planet/DwarfPlanet

12.1.5. Class: geosrs:InterstellarBody

Table 322 — geosrs:InterstellarBody

URI	https://w3id.org/geosrs/planet/InterstellarBody

12.1.6. Class: geosrs:Moon

Table 323 — geosrs:Moon

URI	https://w3id.org/geosrs/planet/Moon

12.1.7. Class: geosrs:NaturalSatellite

Table 324 — geosrs:NaturalSatellite

URI	https://w3id.org/geosrs/planet/NaturalSatellite

12.1.8. Class: geosrs:Planet

Table 325 — geosrs:Planet

URI	https://w3id.org/geosrs/planet/Planet

12.1.9. Class: geosrs:PlanetStatus

Table 326 — geosrs:PlanetStatus

URI	https://w3id.org/geosrs/planet/PlanetStatus

12.1.10. Class: geosrs:Plutoid

Table 327 — geosrs:Plutoid

URI	https://w3id.org/geosrs/planet/Plutoid

12.1.11. Class: geosrs:Star

Table 328 — geosrs:Star

URI	https://w3id.org/geosrs/planet/Star

A

ANNEX A (INFORMATIVE) ALIGNMENTS

ANNEX A (INFORMATIVE) ALIGNMENTS

Overview

Overview

The prefixes used for the ontologies mapped to in all following sections are given in the following table.

Table A.1 — Alignment: Namespaces

ign:	http://data.ign.fr/def/ignf#
iso19111:	http://def.isotc211.org/iso19112/2019/SpatialReferencingByGeographicIdentifier#
geosrs:	http://www.opengis.net/ont/geosparql#
ifc:	https://standards.buildingsmart.org/IFC/DEV/IFC4/ADD2_TC1/OWL/
owl:	http://www.w3.org/2002/07/owl#
prov:	http://www.w3.org/ns/prov#
rdf:	http://www.w3.org/1999/02/22-rdf-syntax-ns#
rdfs:	http://www.w3.org/2000/01/rdf-schema#

A.1. IGN Ontology

Table A.2 — Alignment: IGN Ontology

FROM ELEMENT	MAPPING RELATION	TO ELEMENT	NOTES
geosrs:CoordinateSystem	owl:equivalentClass	ign:CoordinateSystem	-
geosrs:Datum	owl:equivalentClass	ign:Datum	-
geosrs:Ellipsoid	owl:equivalentClass	ign:Ellipsoid	-
geosrs:Conversion	owl:equivalentClass	ign:Conversion	-
geosrs:CoordinateOperation	owl:equivalentClass	ign:CoordinateOperation	-
geosrs:OperationMethod	owl:equivalentClass	ign:OperationMethod	-
geosrs:OperationParameter	owl:equivalentClass	ign:OperationParameter	-
geosrs:OperationParameterValue	owl:equivalentClass	ign:OperationParameterValue	-
geosrs:SingleOperation	owl:equivalentClass	ign:SingleOperation	-
geosrs:Transformation	owl:equivalentClass	ign:Transformation	-
geosrs:CartesianCoordinateSystem	owl:equivalentClass	ign:CartesianCS	-
geosrs:CoordinateSystem	owl:equivalentClass	ign:CoordinateSystem	-
geosrs:CoordinateSystemAxis	owl:equivalentClass	ign:CoordinateSystemAxis	-
geosrs:EllipsoidalCoordinateSystem	owl:equivalentClass	ign:EllipsoidalCS	-
geosrs:VerticalCoordinateSystem	owl:equivalentClass	ign:VerticalCS	-
geosrs:Datum	owl:equivalentClass	ign:Datum	-
geosrs:Ellipsoid	owl:equivalentClass	ign:Ellipsoid	-
geosrs:GeodeticDatum	owl:equivalentClass	ign:GeodeticDatum	-
geosrs:PrimeMeridian	owl:equivalentClass	ign:PrimeMeridian	-
geosrs:VerticalDatum	owl:equivalentClass	ign:VerticalDatum	-
geosrs:AxesList	owl:equivalentClass	ign:AxesList	-

FROM ELEMENT	MAPPING RELATION	TO ELEMENT	NOTES
geosrs:CRS	owl:equivalentClass	ign:CRS	-
geosrs:CompoundCRS	owl:equivalentClass	ign:CompoundCRS	-
geosrs:Extent	owl:equivalentClass	ign:Extent	-
geosrs:GeodeticCRS	owl:equivalentClass	ign:GeodeticCRS	-
geosrs:GeographicBoundingBox	owl:equivalentClass	ign:GeographicBoundingBox	-
geosrs:ProjectedCRS	owl:equivalentClass	ign:ProjectedCRS	-
geosrs:SingleCRS	owl:equivalentClass	ign:SingleCRS	-
geosrs:SingleCRSList	owl:equivalentClass	ign:SingleCRSList	-
geosrs:VerticalCRS	owl:equivalentClass	ign:VerticalCRS	-

A.2. ISO19111 Ontology

Table A.3 — Alignment: ISO19111 Ontology

FROM ELEMENT	MAPPING RELATION	TO ELEMENT	NOTES
geosrs:CoordinateSystem	owl:equivalentClass	iso19111:CoordinateSystem	-
geosrs:Datum	owl:equivalentClass	iso19111:Datum	-
geosrs:Ellipsoid	owl:equivalentClass	iso19111:Ellipsoid	-
geosrs:CRS	owl:equivalentClass	iso19111:CRS	-
geosrs:CompoundCRS	owl:equivalentClass	iso19111:CompoundCRS	-
geosrs:EngineeringCRS	owl:equivalentClass	iso19111:EngineeringCRS	-
geosrs:GeodeticCRS	owl:equivalentClass	iso19111:GeodeticCRS	-

FROM ELEMENT	MAPPING RELATION	TO ELEMENT	NOTES
geosrs:GeographicCRS	owl:equivalentClass	iso19111:GeographicCRS	-
geosrs:ParametricCRS	owl:equivalentClass	iso19111:ParametricCRS	-
geosrs:ProjectedCRS	owl:equivalentClass	iso19111:ProjectedCRS	-
geosrs:SingleCRS	owl:equivalentClass	iso19111:SingleCRS	-
geosrs:TemporalCRS	owl:equivalentClass	iso19111:TemporalCRS	-
geosrs:VerticalCRS	owl:equivalentClass	iso19111:VerticalCRS	-

A.3. IFC Ontology

Table A.4 — Alignment: IFC Ontology

FROM ELEMENT	MAPPING RELATION	TO ELEMENT	NOTES
geosrs:AxisDirection	owl:equivalentClass	ifc:IfcDirection	-
geosrs:CRS	owl:equivalentClass	ifc:IfcCoordinateReferenceSystem	-
geosrs:CoordinateOperation	owl:equivalentClass	ifc:IfcCoordinateOperation	-
geosrs:ProjectedCRS	owl:equivalentClass	ifc:IfcProjectedCRS	-
geosrs:axis	owl:equivalentProperty	ifc:axis_IfcAxis1Placement	-
geosrs:sourceCRS	owl:equivalentProperty	ifc:sourceCRS	-
geosrs:targetCRS	owl:equivalentProperty	ifc:targetCRS	-

B

ANNEX B (INFORMATIVE) SHACL SHAPES

B

ANNEX B (INFORMATIVE) SHACL SHAPES

Overview

Overview

C

ANNEX C (INFORMATIVE) REVISION HISTORY

——

C ANNEX C (INFORMATIVE) REVISION HISTORY

DATE	RELEASE	AUTHOR	PRIMARY CLAUSES MODIFIED	DESCRIPTION
2016-04-28	0.1	G. Editor	all	initial version

BIBLIOGRAPHY

BIBLIOGRAPHY

NOTE: The TC has approved Springer LNCS as the official document citation type. Springer LNCS is widely used in technical and computer science journals and other publications For citations in the text please use square brackets and consecutive numbers: [1], [2], [3] Actual References: [n] Journal: Author Surname, A.: Title. Publication Title. Volume number, Issue number, Pages Used (Year Published)

[1]   ISO: ISO 19142, *Geographic information — Web Feature Service*. International Organization for Standardization, Geneva https://www.iso.org/standard/42136.html.

[2]   W3C: **Data Catalog Vocabulary,** W3C Recommendation 16 January 2014, https://www.w3.org/TR/vocab-dcat/

[3]   IANA: **Link Relation Types,** https://www.iana.org/assignments/link-relations/link-relations.xml

[4]   W3C/OGC: **Spatial Data on the Web Best Practices,** W3C Working Group Note 28 September 2017, https://www.w3.org/TR/sdw-bp/

[5]   W3C: **Data on the Web Best Practices,** W3C Recommendation 31 January 2017, https://www.w3.org/TR/dwbp/

[6]   Ben-Kiki, O., Evans, C., Ingy döt Net: **YAML Ain't Markup Language,** https://yaml.org/

[7]   OGC: **Web Feature Service 2.0,** http://docs.opengeospatial.org/is/09-025r2/09-025r2.html

[8]   Berners-Lee, T., Fielding, R., Masinter, L.: **IETF RFC 3986 — Uniform Resource Identifier (URI): Generic Syntax,** http://tools.ietf.org/rfc/rfc3986.txt