

- evolved: open software for teaching Evolutionary
- biology through virtual inquiries
- Matheus Januario 1,2, Jennifer P. Auler 3, Andressa L. Viol, and Daniel L.
- 4 Rabosky (1) 1,2
- ⁵ 1 Museum of Zoology, University of Michigan, Ann Arbor, MI, USA 2 Department of Ecology and
- Evolutionary Biology, University of Michigan, Ann Arbor, MI, USA 3 Programa de Pós-Graduação em
- Ecologia, Universidade de São Paulo, Rua do Matão, 321, Travessa 14, São Paulo, SP, Brazil

DOI: 10.xxxxx/draft

Software

- Review d
- Repository ♂
- Archive □

Submitted: 23 December 2024 **Published:** unpublished

License

Authors of papers retain copyright¹⁴ and release the work under a $15 Creative Commons Attribution 4.Q6 International License (CC BY 4.0)_{L7}

Summary

25

evolved (EVOLutionary Virtual EDucation) is an open-source R package (Team, 2024) designed for graduate or advanced undergraduate courses in evolutionary biology. It provides tools for inquiry-based learning, where students engage in scientific practices to actively build knowledge (Pedaste et al., 2015). The package includes vignettes (tutorials) to facilitate classroom investigations (Tables 1 & 2). However, educators are encouraged to develop their own content modules depending on class context and/or learning objectives. Most of evolved's core functions are oriented towards either (i) developing student intuition for classic models in evolutionary biology using simulations, or (ii) analyzing (parameter estimation, hypothesis testing, visualization) datasets associated with key questions in evolutionary biology (Tables 1 & 2). Importantly, these datasets correspond structurally (e.g., organization and data types) to real datasets used by scientists, and they are compatible with widely-used software for evolutionary analysis (e.g., ape - (Paradis & Schliep, 2019)).

evolved's functions can be loosely classified into "high level" and "low level" (Table 1), thus providing tools for inquiries that assume different levels of student independence (e.g., as categorized by Banchi & Bell (2008) - see Table 2). High-level functions execute complex sequences of operations while hiding many details, thus making minimal assumptions of R proficiency and allowing users to focus on results. They are either optimized for performance, or work as a simplified interface ("wrappers") of simulators from standard scientific packages (e.g., functions from packages ape (Paradis & Schliep, 2019), diversitree (FitzJohn, 2012), or phytools (Revell, 2024)). These functions will likely work better in inquiries with more student freedom and a greater focus on analyzing data (Table 2). In contrast, "low level" functions focus on making explicit connections between every sequential operation and are thus more easily applicable to structured inquiries (Banchi & Bell, 2008). They are also internally designed to be readable by students with intermediate skills in R, allowing further engagement with simulation parameters and outcomes.

The package is designed to reduce barriers to data- and simulation-driven inquiries and one vignette (intro_R) aims to introduce students/educators to R and its pedagogical capabilities. We do not provide answers to the investigation prompts in the vignettes, but educators can request answer keys from the corresponding author (MJ).

Statement of need

- Evolutionary biology is a complex discipline that affords many opportunities for students
- to practice interrogating, analyzing, and discussing data, but advanced classes still need



- $_{\rm 42}$ $\,$ effective educational resources. evolved addresses this need by focusing on core evidence
- 43 used to study evolution: molecular/fossil data, simulations, and sound mathematical
- 44 principles in evolutionary biology. The package helps teach programming, analytical, and
- 45 reasoning skills through interactive, hands-on activities, and its open-source design allows
- direct engagement with algorithms and methods.
- 47 evolved began in 2022 as a set of standalone functions used in an advanced evolutionary
- 48 biology course at the University of Michigan, originally designed for use in hands-on classes
- of 2 hours per topic module. However, valuable class time was lost on data setup and
- formatting, reducing student engagement with core material. In 2023, the functions were
- consolidated into an R package to free up class time by simplifying data loading, now
- made with a simple command: data(dataset name).

Software installation and use

- evolved's stable version is available on the Comprehensive R Archive Network (CRAN).
- 55 The available vignettes draw inspiration from the authors' teaching experiences, but they
- ₅₆ are not essential for the software to function and should be interpreted as suggestions.
- Instructors should feel free to adapt evolved's functionalities as they see fit.
- To access a vignette, type vignette("vignette_name") in R, replacing "vignette_name" with
- 59 the vignette name (see Table 2). The development version, more detailed information on
- the package/vignettes, and instructions for installing and using R/RStudio/RMarkdown
- $_{61}$ are provided at https://github.com/mjanuario/evolved. Questions should be sent to MJ
- 62 (correspondence author).
- Table 1. Selected functions illustrating the range of topics covered, with notes on their level (low =
- 64 intended to be opened by students, high = wrapper function). A full list and descriptions of all
- functions, including helper and plotting functions, are available in the package manual (Januario et
- al., 2024).

Function name	Associated subfield	Function purpose	Function Level	Vignette name
calcFossilDivTT()	Paleobiology	Estimate diversity through time from fossil occurrences	Low	deeptime_rocks
countSeqDiffs()	Comparative molecular evolution and Phylogenetics	Calculates the number of different sites between two protein sequences	Low	deeptime_clocks
NatSelSim()	Population genetics	Compute allele frequency dynamics under natural selection	Low	pongen_selection
OneGenHWSim()	Population genetics	Simulates independent assortment of gametes under Hardy-Weinberg equilibrium in a finite population	Low	pongen_intro
WEDriftSim()	Population genetics	Simulates allele frequency change through time under genetic drift	Low	pongen_drift
simulateBirthDeath()	Macroevolution	Simulates the number of species following a birth-death model	High	birthdeath_deeptime
SimulateTree()	Macroevolution	Simulates a phylogenetic tree following a birth-death model	High	birthdeath_phylogenies

- Table 2. Different datasets and their suggested applications. The inquiry level follows the terminology and definitions of Banchi & Bell (2008). Legend: occs. = Occurrences; Ver. = Version
- of the package (stable = hosted on CRAN, Devel. = development version hosted on github).

Dataset name	Short description	Suggested inquiry level	Possible topic in inquiry	Name of vignette with example activity	Data source	Ver.
data_whales	Cetacean body size and speciation rates	Structured inquiry	Statistical non-independence among closely related species	birthdeath_phylogenies	(Jones et al., 2009; Rabosky et al., 2014)	Stable
whale_nbvlo	Cetacean molecular phylogeny	Structured inquiry	Handling of phylogenies in analysis software	birthdeath_phylogenies	(Steeman et al., 2009)	Stable
cvt0xidase	Metazoan (homologous) protein sequence	Open inquiry	Comparative analysis of molecular data	deeptime_clocks	(Benson et al., 2012)	Stable
birds_spp	Extant species list of birds	Structured inquiry	Richness differences among clades	deeptime_rocks	(Jetz et al., 2012)	Stable
mammals_spp	Extant species list of mammals	Structured inquiry	Richness differences among clades	deeptime_rocks	(Upham et al., 2019)	Devel.
ammonoidea_fossil	Ammonoid fossil occs.	Open inquiry	Large-scale biodiversity patterns in the fossil record	deeptime_rocks	https: //paleobiodb.org	Devel.
mammals_fossil	Mammal fossil occs.	Open inquiry	Large-scale biodiversity patterns in the fossil record	deeptime_rocks	https: //paleobiodb.org	Devel.
dinos_fossil	Dinosaur fossil occs.	Open inquiry	Large-scale biodiversity patterns in the fossil record	deeptime_rocks	https: //paleobiodb.org	Stable
trilob_fossil	Trilobite fossil occs.	Open inquiry	Large-scale biodiversity patterns in the fossil record	deeptime_rocks	https: //paleobiodb.org	Devel.
timeseries_fossil	Timeseries of fossil species numbers for many clades	Guided inquiry	Large-scale biodiversity patterns in the fossil record	birthdeath_deeptime	(Rabosky & Benson, 2021)	Stable



Author contributions:

- MJ and DLR designed most of the code, internal functions, and educational components.
- ₇₂ JPA joined later, contributing to visualization functions, documentation, implementation
- improvements, and preparing the package for CRAN standards. MJ, DLR, and ALV
- developed the vignettes. MJ wrote the first drafts of the paper, help pages, and vignettes,
- with all authors reviewing the material afterward.

76 Acknowledgements

77 We thank Theodore Matel, Tristan Schramer, and Yu Kai Tanfor their suggestions.

78 References

- Banchi, H., & Bell, R. (2008). The many levels of inquiry. Science & Children, 46(2).
- Benson, D. A., Cavanaugh, M., Clark, K., Karsch-Mizrachi, I., Lipman, D. J., Ostell, J., & Sayers, E. W. (2012). GenBank. *Nucleic Acids Research*, 41(D1), D36–D42.
- FitzJohn, R. G. (2012). Diversitree: Comparative phylogenetic analyses of diversification in r. *Methods in Ecology and Evolution*, 3(6), 1084–1092.
- Januario, M., Auler, J., Viol, A., & Rabosky, D. (2024). Package 'evolved'.
- Jetz, W., Thomas, G. H., Joy, J. B., Hartmann, K., & Mooers, A. O. (2012). The global
 diversity of birds in space and time. *Nature*, 491(7424), 444–448.
- Jones, K. E., Bielby, J., Cardillo, M., Fritz, S. A., O'Dell, J., Orme, C. D. L., Safi, K., Sechrest, W., Boakes, E. H., Carbone, C., & others. (2009). PanTHERIA: A species-level database of life history, ecology, and geography of extant and recently extinct mammals: Ecological archives E090-184. *Ecology*, 90(9), 2648–2648.
- Paradis, E., & Schliep, K. (2019). Ape 5.0: An environment for modern phylogenetics and evolutionary analyses in r. *Bioinformatics*, 35(3), 526–528.
- Pedaste, M., Mäeots, M., Siiman, L. A., De Jong, T., Van Riesen, S. A., Kamp, E. T.,
 Manoli, C. C., Zacharia, Z. C., & Tsourlidaki, E. (2015). Phases of inquiry-based
 learning: Definitions and the inquiry cycle. Educational Research Review, 14, 47–61.
- Rabosky, D. L., & Benson, R. B. (2021). Ecological and biogeographic drivers of biodiversity cannot be resolved using clade age-richness data. *Nature Communications*, 12(1), 2945.
- Rabosky, D. L., Grundler, M., Anderson, C., Title, P., Shi, J. J., Brown, J. W., Huang, H., & Larson, J. G. (2014). BAMM tools: An r package for the analysis of evolutionary dynamics on phylogenetic trees. *Methods in Ecology and Evolution*, 5(7), 701–707.
- Revell, L. J. (2024). Phytools 2.0: An updated r ecosystem for phylogenetic comparative methods (and other things). *PeerJ*, 12, e16505.
- Steeman, M. E., Hebsgaard, M. B., Fordyce, R. E., Ho, S. Y., Rabosky, D. L., Nielsen, R., Rahbek, C., Glenner, H., Sørensen, M. V., & Willerslev, E. (2009). Radiation of extant cetaceans driven by restructuring of the oceans. *Systematic Biology*, 58(6), 573–585.
- Team, R. C. (2024). R: A language and environment for statistical computing. Foundation for Statistical Computing, Vienna, Austria.
- Upham, N. S., Esselstyn, J. A., & Jetz, W. (2019). Inferring the mammal tree: Species-level sets of phylogenies for questions in ecology, evolution, and conservation. *PLoS Biology*, 17(12), e3000494.