

# Pyrception: A Python package for biologically plausible neuromorphic perception

Alexander Hadjiivanov<sup>1,2</sup> and Giulia D'Angelo<sup>3</sup>

<sup>1</sup> Advanced Concepts Team, European Space Agency <sup>2</sup> Adapsent <sup>3</sup> Czech Technical University in Prague

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [✉](#)

Submitted: 09 April 2025

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

Neuromorphic perception is enjoying a resurgence in attention from the scientific community as event-based cameras (ECs) (Lichtsteiner et al., 2008) become increasingly capable and commercially available (Posch et al., 2014). ECs build upon decades of research on retinomorphic vision, display superior characteristics compared to frame-based cameras (FCs) and highlight the advantages of neuromorphic perception. Here, we present Pyrception – a Python library for bio-plausible retinomorphic modelling, simulation and processing of raw visual input. The library builds upon a generalisation of sparse convolution using Toeplitz matrices (outlined below), which allows for efficient processing and modelling of various features of the mammalian retina, such as complex receptive fields, eccentricity-dependent receptive field sizes and log-polar cell arrangement (Chessa et al., 2016).

## Statement of need

Hardware prototyping is a difficult and time-consuming process. This is especially valid for neuromorphic vision sensors as the technology is new, and investing effort into developing a new sensor implementing innovative on-sensor features may not be justified unless it has already been demonstrated that the processing pipeline works as intended. Pyrception can be used to simulate retinal processing circuits, with envisioned applications in the fields of neuromorphic vision and neuroscience. The ability to perform accurate simulations of various retinal circuits is an efficient way to demonstrate any potential advantages of such circuits and subsequently presenting a strong case for their implementation in hardware. Similarly, such simulation can prove beneficial in neuroscience, for instance, for modelling atypical or poorly understood visual mechanisms to gain insight into the causes and mechanisms behind of certain vision-related medical conditions.

## Implementation

The implementation of convolution in deep learning libraries such as PyTorch (Paszke et al., 2017) and TensorFlow (Abadi et al., 2015) is based on the Im2Col mechanism (Chellapilla et al., 2006). Since in the case of digital visual input the convolution operation is discrete, in the Im2Col approach the input (an image) is partitioned into patches corresponding to each convolved location, which is determined by factors such as kernel size, stride, dilation and so forth. Each of these patches is unrolled into a column vector and concatenated to form the columns of a dense matrix, hence the term Im2Col (Fig. 1a). The same operation is performed on all kernels – they are unrolled and concatenated as the rows of a separate dense matrix (Fig. 1b). This operation reduces the convolution operation to a simple dense matrix-matrix multiplication.


40 While the Im2Col approach makes the convolution operation well suited for implementation on  
41 GPUs, it has several limitations that make it unsuitable for modelling the working principle of  
42 the retina. For instance, Im2Col requires that all kernels be of the same size, precluding the  
43 emulation of log-polar dependent receptive field architecture. Similarly, it makes it exceedingly  
44 difficult to implement non-rectangular (e.g., elliptic or irregular) kernels.

45 In contrast, in Pyrception the image is not segmented into patches. Instead, it is unrolled into  
46 a single long vector by concatenating all columns of the image (Fig. 1c). As a consequence, the  
47 parts of the image that correspond to the receptive field of a kernel are no longer contiguous.  
48 To be able to still perform convolution as a simple matrix-matrix (strictly, matrix-vector)  
49 multiplication, each corresponding kernel must be unrolled into a *sparse* row in such a way  
50 that multiplying the sparse row with the entire image column vector gives the same result as if  
51 performed with the Im2Col approach (Fig. 1d). This type of convolution is based on Toeplitz  
52 matrices (Gnacik & Łapa, 2022), where all diagonals contain identical elements, which is  
53 equivalent to shifting consecutive rows by one element to the right. In Pyrception, kernels are  
54 unravelled into sparse rows, one for each convolved patch of the image, resulting in a sparse  
55 Toeplitz matrix.


56 The versatility of Pyrception stems from using a *generalised* version of the sparse convolution  
57 approach with a Toeplitz matrix. The 'generalised' part refers to the fact that each patch  
58 of the image can be convolved with a *different* kernel since each sparse rows in the kernel  
59 matrix encodes an entire kernel. Since each row in the kernel matrix has the same length  
60 as the image vector, each kernel can potentially have a full 'view' of the entire image. This  
61 gives us complete freedom to choose the parameters of each kernel independently, making it  
62 possible to construct convolutional matrices populated with arbitrary kernels with different  
63 sizes, orientations and arrangements. Notably, the kernels themselves can be sparse, making it  
64 possible to convolve sparse inputs (e.g., inputs arriving from an event camera).

65 Currently, Pyrception implements all five major layers of the mammalian retina, each of which  
66 can be emulated with different types of cell arrangements and dynamics, as well as excitatory  
67 / inhibitory connections forming receptive fields of different shapes, sizes and orientations.  
68 With the default parameters, the Pyrception layers implement a generic retinal processing  
69 pipeline consisting of a receptor layer followed by horizontal, bipolar, amacrine and ganglion  
70 cell layers (Masland, 2011). By simply deriving from the existing layer classes and overriding  
71 the forward() method, it is possible to implement different retinal circuits, such as motion  
72 segmentation (Baccus et al., 2008; Clerico et al., 2024; Olveczky et al., 2003), looming  
73 detection for detecting approaching objects (Gollisch & Meister, 2010), optical flow estimation  
74 and visual tracking (Angelo et al., 2025; Javier Traver & Bernardino, 2010). We welcome  
75 contributions to Pyrception that would make the library as useful as possible, including  
76 implementing bio-plausible modalities other than vision.

## 77 Figures



**Figure 1:** Visualisation of dense and sparse operations on images and kernels for convolution. (a) Unrolling image patches into a dense matrix (Im2Col operation) and (b) a corresponding kernel into a dense row (Ker2Row operation). (c) Unrolling an image column-wise into a vector (Im2Vec operation). The (non-contiguous) elements corresponding to the same patches as those in (a) are illustrated. (d) Unrolling a kernel into a sparse row (Ker2SpRow operation). (e, f) Examples of circular kernels with radii of 3 and 5 pixels, respectively, with the corresponding unrolled Ker2SpRow representations shown below each kernel.



**Figure 2:** A visualisation of kernels of different sizes and orientations. (a) Kernels arranged and a phyllotactic log-polar distribution (similar to the seeds of a sunflower). Kernels towards the center of the image are smaller than ones towards the edges, emulating the eccentricity-dependent receptive field size observed in the mammalian retina. Due to the different sizes of the kernels, the 'stride' (and therefore the overlap) is non-uniform. (b) A zoomed-in version of the top left corner of the plot in (a). (c) A plot of the kernels for a subset of 10 sectors of kernels (a sector is a group of kernels whose centers are located along the same radial line). (d) The same kernel arrangement as in (a), but with elliptic kernels oriented at 45°. (e) A raw image (credit: [Von.grzanka / Wikimedia](#)) and (f) the corresponding activation map resulting from convolving the image with the kernel map in (a).

## Acknowledgements

A.H. is grateful for the support of the [Advanced Concepts Team of the European Space Agency](#), where the conceptualisation and a large portion of the development of this library took place. G.D. acknowledges the financial support from the European Union's HORIZON-MSCA-2023-PF-01-01 research and innovation programme under the Marie Skłodowska-Curie grant agreement ENDEAVOR No 101149664.

## References

- Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., ... Zheng, X. (2015). *TensorFlow: Large-scale machine learning on heterogeneous systems*. <https://www.tensorflow.org/>
- Angelo, G. D., Clerico, V., Bartolozzi, C., Hoffmann, M., Furlong, P. M., & Hadjiivanov, A. (2025). Wandering around: A bioinspired approach to visual attention through object motion sensitivity. *arXiv Preprint arXiv:2502.06747*.
- Baccus, S. A., Ölveczky, B. P., Manu, M., & Meister, M. (2008). A retinal circuit that computes object motion. *Journal of Neuroscience*, 28(27), 6807–6817.
- Chellapilla, K., Puri, S., & Simard, P. (2006). High Performance Convolutional Neural Networks for Document Processing. In G. Lorette (Ed.), *Tenth International Workshop on Frontiers in Handwriting Recognition*. Suvisoft. <https://inria.hal.science/inria-00112631>
- Chessa, M., Maiello, G., Bex, P. J., & Solari, F. (2016). A space-variant model for motion interpretation across the visual field. *Journal of Vision*, 16(2), 12–12.
- Clerico, V., Snyder, S., Lohia, A., Kaiser, M. A.-A., Schwartz, G., Jaiswal, A., & Parsa, M. (2024). *Retina-inspired object motion segmentation for event-cameras*. <https://arxiv.org/abs/2408.09454>
- Gnacik, M., & Łapa, K. (2022, October 27). *Using Toeplitz Matrices to obtain 2D convolution*. <https://doi.org/10.21203/rs.3.rs-2195496/v1>
- Gollisch, T., & Meister, M. (2010). Eye Smarter than Scientists Believed: Neural Computations in Circuits of the Retina. *Neuron*, 65(2), 150–164. <https://doi.org/10.1016/j.neuron.2009.12.009>
- Javier Traver, V., & Bernardino, A. (2010). A review of log-polar imaging for visual perception in robotics. *Robotics and Autonomous Systems*, 58(4), 378–398. <https://doi.org/10.1016/j.robot.2009.10.002>
- Lichtsteiner, P., Posch, C., & Delbruck, T. (2008). A 128X128 120 dB 15us latency asynchronous temporal contrast vision sensor. *IEEE Journal of Solid-State Circuits*, 43(2), 566–576.
- Masland, R. H. (2011). Cell Populations of the Retina: The Proctor Lecture. *Investigative Ophthalmology & Visual Science*, 52(7), 4581–4591. <https://doi.org/10.1167/iovs.10-7083>
- Ölveczky, B. P., Baccus, S. A., & Meister, M. (2003). Segregation of object and background motion in the retina. *Nature*, 423(6938), 401–408.
- Paszke, A., Gross, S., Chintala, S., Chanan, G., Yang, E., DeVito, Z., Lin, Z., Desmaison, A., Antiga, L., & Lerer, A. (2017). *Automatic differentiation in PyTorch*.
- Posch, C., Serrano-Gotarredona, T., Linares-Barranco, B., & Delbruck, T. (2014). Retinomorphic Event-Based Vision Sensors: Bioinspired Cameras With Spiking Output. *Proceedings of the IEEE*, 102(10), 1470–1484. <https://doi.org/10.1109/JPROC.2014.2346153>