

containerit: Generating Dockerfiles for reproducible research with R

Daniel Nüst¹ and Matthias Hinz²

¹ Institute for Geoinformatics, University of Münster, Germany ² Professorship for Geoinformatics and Geodesy, Faculty of Agricultural and Environmental Sciences, University of Rostock, Germany

DOI: [10.21105/joss.01603](https://doi.org/10.21105/joss.01603)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted: 25 July 2019

Published: 21 August 2019

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

Statement of Need

[Linux containers](#) have become a promising tool to increase transparency, portability, and reproducibility of research in several domains and use cases: data science (Boettiger, 2015), software engineering research (Cito & Gall, 2016), multi-step bioinformatics pipelines (Kim, Ali, Lijeron, Afgan, & Krampis, 2017), standardised environments for exchangeable software (Belmann et al., 2015), computational archaeology (Marwick, 2017), packaging algorithms (Hosny, Vera-Licona, Laubenbacher, & Favre, 2016), or geographic object-based image analysis (Knoth & Nüst, 2017). Running an analysis in a container increases reliability of a workflow, as it can execute packaged code independently of the author's computer and its available configurations and dependencies. However, capturing a computational environment in containers can be complex, making container use difficult for domain scientists with limited programming experience. *containerit* opens up the advantages of containerisation to a much larger user base by assisting researchers, who are unfamiliar with Linux, command lines or containerisation, in packaging workflows based on R (R Core Team, 2018) in container images by using only user-friendly R commands.

Recently containerisation took off as a technology for packaging applications and their dependencies for fast, scalable, and secure [sandboxed](#) deployments in cloud-based infrastructures (cf. Osnat, 2018). The most widely used containerisation software is [Docker](#) with the following core building blocks (cf. [Docker: Get Started](#)): The *image* is built from the instructions in a recipe called Dockerfile. The image is executed as a *container* using a *container runtime*. An image can be moved between systems as a file (image tarball) or based on an *image registry*. A Dockerfile may use the image created by another Dockerfile as the starting point, a so-called *base image*. While containers can be manually altered, the common practice is to conduct all configurations with the scripts and instructions originating in the Dockerfile.

An important advantage of containers over [virtual machines](#) is that their duality between recipe and image provides an additional layer of transparency and safeguarding. The Dockerfile and image can be published alongside a scientific paper to support peer review and, to some extent, preserve the original results (Nüst et al., 2017). Even if an image cannot be executed or a Dockerfile can no longer be built, the instructions in the Dockerfile are human-readable, and files in the image can be extracted to recreate an environment that closely resembles the original. Further useful features are (a) portability, thanks to a single runtime dependency, which allows readers to explore an author's virtual laboratory, including complex dependencies or custom-made code, either on their machines or in cloud-based infrastructures (e.g., by using Binder, see Project Jupyter et al., 2018), and (b) transparency, because an image's filesystem can be easily inspected. This way, containers can enable verification of reproducibility and auditing without requiring reviewers to manually download, install, and re-run analyses (Beaulieu-Jones & Greene, 2017).

Container preservation is an active field of research (Emsley & De Roure, 2018; Rechert et al., 2017). It is reasonable to assume that key stakeholders interested in workflow preservation, such as universities or scientific publishers, should be able to operate container runtimes on a time scale comparable to data storage requirements by funding agencies, e.g., 10 years in case of the [German DFG](#) or [British EPSRC](#). To enable and leverage the stakeholders' infrastructure, container creation must become easier and more widespread.

Summary

The package `containerit` automates the generation of Dockerfiles for workflows in R, based on images by the [Rocker project](#) (Boettiger & Eddelbuettel, 2017). The core feature of `containerit` is that it transforms the local session information into a set of instructions which can be serialised as a Dockerfile, as shown in the code snippet below:

```
> suppressPackageStartupMessages(library("containerit"))
> my_dockerfile <- containerit::dockerfile(from = utils::sessionInfo())
> print(my_dockerfile)
FROM rocker/r-ver:3.5.2
LABEL maintainer="daniel"
RUN export DEBIAN_FRONTEND=noninteractive; apt-get -y update \
    && apt-get install -y git-core \
        libcurl4-openssl-dev \
        libssl-dev \
        pandoc \
        pandoc-citeproc
RUN ["install2.r", "curl", "digest", "evaluate", "formatR", \
    "futile.logger", "futile.options", "htmltools", "jsonlite", \
    "knitr", "lambda.r", "magrittr", "Rcpp", "rjson", \
    "rmarkdown", "rsconnect", "semver", "stevedore", "stringi", \
    "stringr", "xfun", "yaml"]
WORKDIR /payload/
CMD ["R"]
```

The created Dockerfile has installation instructions for the loaded packages and their system dependencies. It uses the `r-ver` stack of Rocker images, matching the R version to the environment encountered locally by `containerit`. These images use [MRAN](#) snapshots to control installed R package versions in a reproducible way. The system dependencies required by these packages are identified using the `sysreqs` package (Csardi, 2019) and the corresponding [database and API](#).

`dockerfile(...)` is the package's main user function and accepts session information objects, session information saved in a file, a set of R commands, an R script file, a [DESCRIPTION](#) file, or an R Markdown document (Allaire et al., 2018). [Static program analysis](#) using the package `automagic` (Brokamp, 2017) is used to increase the chances that the capturing environment has all required packages available, such as when creating Dockerfiles for R Markdown documents as a service (Nüst, 2018). To capture the workflow environment, `containerit` executes the whole workflow in a new R session using the package `callr` (Csárdi & Chang, 2018), because static program analysis can be broken by using helper functions, such as `xfun::pkg_attach()` (Xie, 2018), by unintended side effects, or by seemingly clever or user-friendly yet customised ways of loading packages (cf. first lines in R script file `tgis_a_1579333_sm7524.r` in <https://doi.org/10.6084/m9.figshare.7757069.v1>). Further parameters for the function comprise, for example, image metadata, base image, versioned installations, and filtering of R packages already installed in the base image.

The package `containerit`'s main contribution is that it allows for automated capturing of runtime environments as Dockerfiles based on literate programming workflows (Gentleman & Lang, 2007) to support reproducible research. Together with `stevedore` (FitzJohn, 2019), `containerit` enables a completely R-based creation and manipulation of Docker containers. Using `containerit` only minimally affects researchers' workflows because it can be applied after completing a workflow, while at the same time the captured snapshots can enhance the scholarly publication process (in particular review, interaction, and preservation) and may form a basis for more reusable and transparent publications. In the future, `containerit` may support alternative container software such as Singularity (Kurtzer, Sochat, & Bauer, 2017), enable parametrisation of container executions and pipelines as demonstrated by Kliko (Molenaar, Makhathini, Girard, & Smirnov, 2018), or support proper accreditation of software (Jones et al., 2017; D. S. Katz & Chue Hong, 2018).

Related Work

`renv` is an R package for managing reproducible environments for R providing isolation, portability, and pinned versions of R packages, but it does not handle system dependencies. [The Experiment Factory](#) similarly focuses on ease of use for creating Dockerfiles for behavioural experiments, yet it uses a CLI-based interaction and generates extra shell scripts to be included in the images. [ReproZip](#) (Chirigati, Rampin, Shasha, & Freire, 2016) packages files identified by `tracing` in a self-contained bundle, which can be unpacked to a Docker container/Dockerfile. In the R domain, the package `dockerfiler` (Fay, 2018) provides an object-oriented API for manual Dockerfile creation, and `liftr` (Xiao, 2018) creates a Dockerfile based on fields added to the metadata header of an R Markdown document. `automagic` (Brokamp, 2017), `Whales`, `dockter`, and `repo2docker` use static program analysis to create environment descriptions from common project configuration files for multiple programming languages. Namely, `automagic` analyses R code and can store dependencies in a bespoke `YAML` format. `Whales` and `dockter` provide different formats, including Dockerfile. Finally, `repo2docker` primarily creates containers for interactive notebooks to run as a Binder (Project Jupyter et al., 2018) but does not actively expose a Dockerfile. None of them apply the strict code execution approach as `containerit` does.

Acknowledgements

This work is supported by the project [Opening Reproducible Research](#) ([Offene Reproduzierbare Forschung](#)) funded by the German Research Foundation ([DFG](#)) under project numbers PE 1 632/10-1 and 1632/17-1.

References

- Allaire, J., Xie, Y., McPherson, J., Luraschi, J., Ushey, K., Atkins, A., Wickham, H., et al. (2018). *rmarkdown: Dynamic documents for R*. Retrieved from <https://rmarkdown.rstudio.com>
- Beaulieu-Jones, B. K., & Greene, C. S. (2017). Reproducibility of computational workflows is automated using continuous analysis. *Nature Biotechnology*, advance online publication. doi:[10.1038/nbt.3780](https://doi.org/10.1038/nbt.3780)
- Belmann, P., Dröge, J., Bremges, A., McHardy, A. C., Sczyrba, A., & Barton, M. D. (2015). Bioboxes: Standardised containers for interchangeable bioinformatics software. *GigaScience*, 4(1), 47. doi:[10.1186/s13742-015-0087-0](https://doi.org/10.1186/s13742-015-0087-0)
- Boettiger, C. (2015). An introduction to Docker for reproducible research, with examples from the R environment. *ACM SIGOPS Operating Systems Review*, 49(1), 71–79. doi:[10.1145/2723872.2723882](https://doi.org/10.1145/2723872.2723882)

- Boettiger, C., & Eddelbuettel, D. (2017). An Introduction to Rocker: Docker Containers for R. *The R Journal*, 9(2), 527–536. doi:[10.32614/RJ-2017-065](https://doi.org/10.32614/RJ-2017-065)
- Brokamp, C. (2017). *Automagic: Automagically document and install packages necessary to run R code*. Retrieved from <https://CRAN.R-project.org/package=automagic>
- Chirigati, F., Rampin, R., Shasha, D., & Freire, J. (2016). ReproZip: Computational reproducibility with ease. In *Proceedings of the 2016 international conference on management of data*, SIGMOD '16 (pp. 2085–2088). San Francisco, California, USA: ACM. doi:[10.1145/2882903.2899401](https://doi.org/10.1145/2882903.2899401)
- Cito, J., & Gall, H. C. (2016). Using Docker Containers to Improve Reproducibility in Software Engineering Research. In *Proceedings of the 38th International Conference on Software Engineering Companion*, ICSE '16 (pp. 906–907). ACM. doi:[10.1145/2889160.2891057](https://doi.org/10.1145/2889160.2891057)
- Csardi, G. (2019). *Sysreqs: Install systemrequirements of packages*. Retrieved from <https://github.com/r-hub/sysreqs>
- Csárdi, G., & Chang, W. (2018). *Callr: Call R from R*. Retrieved from <https://CRAN.R-project.org/package=callr>
- Emsley, I., & De Roure, D. (2018). A Framework for the Preservation of a Docker Container International Journal of Digital Curation. *International Journal of Digital Curation*, 12(2). doi:[10.2218/ijdc.v12i2.509](https://doi.org/10.2218/ijdc.v12i2.509)
- Fay, C. (2018). *Dockerfiler: Easy Dockerfile creation from R*. Retrieved from <https://CRAN.R-project.org/package=dockerfiler>
- FitzJohn, R. (2019). *Stevedore: Docker client*. Retrieved from <https://CRAN.R-project.org/package=stevedore>
- Gentleman, R., & Lang, D. T. (2007). Statistical Analyses and Reproducible Research. *Journal of Computational and Graphical Statistics*, 16(1), 1–23. doi:[10.1198/106186007X178663](https://doi.org/10.1198/106186007X178663)
- Hosny, A., Vera-Licona, P., Laubenbacher, R., & Favre, T. (2016). AlgoRun: A Docker-based packaging system for platform-agnostic implemented algorithms. *Bioinformatics*, 32(15), 2396–2398. doi:[10.1093/bioinformatics/btw120](https://doi.org/10.1093/bioinformatics/btw120)
- Jones, M. B., Boettiger, C., Mayes, A. C., Arfon Smith, Slaughter, P., Niemeyer, K., Gil, Y., et al. (2017). CodeMeta: An exchange schema for software metadata. KNB Data Repository. doi:[10.5063/schema/codemeta-2.0](https://doi.org/10.5063/schema/codemeta-2.0)
- Katz, D. S., & Chue Hong, N. P. (2018). Software Citation in Theory and Practice. In J. H. Davenport, M. Kauers, G. Labahn, & J. Urban (Eds.), *Mathematical Software – ICMS 2018*, Lecture Notes in Computer Science (pp. 289–296). Springer International Publishing. doi:[10.1007/978-3-319-96418-8_34](https://doi.org/10.1007/978-3-319-96418-8_34)
- Kim, B., Ali, T. A., Lijeron, C., Afgan, E., & Krampis, K. (2017). Bio-Docklets: Virtualization Containers for Single-Step Execution of NGS Pipelines. *bioRxiv*, 116962. doi:[10.1101/116962](https://doi.org/10.1101/116962)
- Knoth, C., & Nüst, D. (2017). Reproducibility and Practical Adoption of GEOBIA with Open-Source Software in Docker Containers. *Remote Sensing*, 9(3), 290. doi:[10.3390/rs9030290](https://doi.org/10.3390/rs9030290)
- Kurtzer, G. M., Sochat, V., & Bauer, M. W. (2017). Singularity: Scientific containers for mobility of compute. *PLOS ONE*, 12(5), e0177459. doi:[10.1371/journal.pone.0177459](https://doi.org/10.1371/journal.pone.0177459)
- Marwick, B. (2017). Computational Reproducibility in Archaeological Research: Basic Principles and a Case Study of Their Implementation. *Journal of Archaeological Method and Theory*, 24(2), 424–450. doi:[10.1007/s10816-015-9272-9](https://doi.org/10.1007/s10816-015-9272-9)
- Molenaar, G., Makhathini, S., Girard, J. N., & Smirnov, O. (2018). Klico—The scientific compute container format. *Astronomy and Computing*, 25, 1–9. doi:[10.1016/j.ascom.2018.08.003](https://doi.org/10.1016/j.ascom.2018.08.003)

- Nüst, D. (2018, December). Reproducibility Service for Executable Research Compendia: Technical Specifications and Reference Implementation. Zenodo. doi:[10.5281/zenodo.2203844](https://doi.org/10.5281/zenodo.2203844)
- Nüst, D., Konkol, M., Pebesma, E., Kray, C., Schutzzeichel, M., Przibytzin, H., & Lorenz, J. (2017). Opening the Publication Process with Executable Research Compendia. *D-Lib Magazine*, 23(1/2). doi:[10.1045/january2017-nuest](https://doi.org/10.1045/january2017-nuest)
- Osnat, R. (2018, March). A Brief History of Containers: From the 1970s to 2017. Retrieved from <https://blog.aquasec.com/a-brief-history-of-containers-from-1970s-chroot-to-docker-2016>
- Project Jupyter et al. (2018). Binder 2.0 - reproducible, interactive, sharable environments for science at scale. In *Proceedings of the 17th python in science conference*. doi:[10.25080/Majora-4af1f417-011](https://doi.org/10.25080/Majora-4af1f417-011)
- R Core Team. (2018). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org/>
- Rechert, K., Liebetraut, T., Kombrink, S., Wehrle, D., Mocken, S., & Rohland, M. (2017). Preserving Containers. In J. Kratzke & V. Heuveline (Eds.), *Forschungsdaten managen* (pp. 143–151). doi:[10.11588/heibooks.285.377](https://doi.org/10.11588/heibooks.285.377)
- Xiao, N. (2018). *Liftr: Containerize R Markdown documents for continuous reproducibility*. Retrieved from <https://CRAN.R-project.org/package=liftr>
- Xie, Y. (2018). *Xfun: Miscellaneous functions by 'Yihui Xie'*. Retrieved from <https://CRAN.R-project.org/package=xfun>