

Macapype: An open multi-software framework for non-human primate brain anatomical MRI processing

David Meunier¹, Kep Kee Loh⁴, Bastien Cagna^{2,3}, Regis Trapeau¹, Julien Sein¹, and Olivier Coulon¹

¹ Aix Marseille Univ, CNRS, INT, Inst Neurosci Timone, Marseille, France ² CATI, US52-UAR2031, CEA, ICM, Sorbonne Université, CNRS, INSERM, APHP, Ile de France, France ³ Paris Brain Institute - Institut du Cerveau (ICM), Inserm U1127, CNRS UMR 7225, Sorbonne Universités UMR S 1127, ICM, F-75013 Paris, France. ⁴ Department of Psychology, National University of Singapore, Singapore

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Adam Tyson](#)

Submitted: 05 September 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Although brain anatomical Magnetic Resonance Imaging (MRI) processing is largely standardized and functional in humans, it remains a challenge to define robust processing pipelines for the segmentation of non-human primate (NHP) images. To unify the processing of NHP anatomical MRI, we propose Macapype, an open-source framework to create custom pipelines for data preparation, brain extraction, and brain segmentation.

Statement of Need

Non-human primates (NHPs) are increasingly used for neuroimaging studies due to the progress of MR acquisitions and the promises it holds in the field of neuroscience (Milham et al., 2018). Despite the standardization of MRI processing in humans with several well-known software options available, such as AFNI (Cox, 1996), FSL (Smith et al., 2004), SPM12 (Frackowiak et al., 1997), and ANTs (Avants et al., 2011), defining robust processing pipelines for NHP anatomical image segmentation remains difficult.

State of the field

Two categories of methods have been proposed to address the issue of NHP anatomical MR image segmentation. The first category corresponds to particular implementations for NHP images of existing human-MRI softwares such as **NHP-Freesurfer** and **CIVET-Macaque**, respectively relying on human-MRI softwares FreeSurfer (Fischl, 2012) and CIVET (Lepage et al., 2021). The second category relies on the use of deep-learning and machine learning techniques, such as **U-Nets**, for example **nBEST** to provide brain mask, segmentation of GM, WM and subcortical nuclei (Zhong et al., 2024). The latter requires the use of GPUs, most existing softwares performs relatively badly on small NHP species such as marmoset due to the lack of flexibility in the processing steps and the variability of brain peculiarities among NHP species.

Software design

In this context, we propose a general framework for the tissue segmentation of non-human primate brain MR images that can provide multiple pipelines to adapt to a variety of image qualities and species. This open-source framework, named Macapype, is built upon Nipype, a widely used Python framework for human MRI analysis.

38 The Macapype package was specifically designed to provide wrappers of custom tools specific
39 to NHP anatomical MRI preprocessing, as well as pipelines and workflows to achieve high-
40 quality automated tissue segmentation of NHP anatomical images. In particular, the tuning of
41 parameters for different species, should be possible if needed via the use of parameter files.




Figure 1: Different pipelines are chained

42 **Pipelines**

43 Macapype provides configurable pipelines organized in three steps: data preparation, brain
44 extraction, and brain segmentation. Post-processing allows for conversion to format for further

45 processing outside Macapype.

46 ▪ Data Preparation Pipeline

47 The data preparation pipeline is specified in a JSON parameters file and depends on individual
48 parameters. If cropping parameters are absent, Macapype performs an automated but low-
49 precision crop. The input volume is reoriented in a standard space, and denoising and debiasing
50 steps are performed.

51 ▪ Brain Extraction Pipeline

52 For the skull-stripping step, Macapype offers a choice between AtlasBRex (Lohmeier et al.,
53 2019) and bet4animal, an optimized version of the brain extraction tool (BET in FSL) for
54 NHP. HD-BET (Isensee et al., 2019) is also available for deep-learning-based brain extraction.

55 ▪ Tissue Segmentation Pipeline

56 Tissue segmentation is template-based and can be done in template or native space. Macapype
57 provides templates for macaque, marmoset, baboon, and chimpanzee. T1xT2 debias is applied,
58 followed by normalization and segmentation using ANTs-based Atropos or SPM12-based old
59 segment.

60 ▪ Post-Processing Pipeline

61 For compatibility with further processing, Macapype provides formatting options, such as the
62 5tt file from MRtrix (Tournier et al., 2019) for further processing of diffusion MRI and meshes
63 in STL format for 3D printing.

64 Research impact statement

65 Macapype is compatible with FAIR principles, storing all processing steps and parameters in
66 a JSON file. It allows evaluation of results at different preprocessing steps and is tested on
67 images from the PRIME-DE database (Milham et al., 2018) and is listed as a software solution
68 on PRIME-RE (Messinger et al., 2021).

69 AI usage disclosure

70 No generative AI tools were used in the development of this software, or the preparation
71 of supporting materials. This manuscript has been written with the help of Mistral AI for
72 formatting, as well as syntax and language checking.

73 Acknowledgements

74 We are grateful to Adrien Meguerditchian, Paul Apicella, and Guilhem Ibos for providing MRI
75 datasets for testing.

76 References

- 77 Avants, B., Tustison, N., & others. (2011). A reproducible evaluation of ANTs similarity
78 metric performance in brain image registration. *NeuroImage*, 54, 2033–2044. <https://doi.org/10.1016/j.neuroimage.2010.09.025>
79
80 Cox, R. (1996). AFNI: Software for analysis and visualization of functional magnetic resonance
81 neuroimages. *Computers and Biomedical Research*, 29, 162–173. <https://doi.org/10.1006/cbmr.1996.0014>
82

- 83 Fischl, B. (2012). FreeSurfer. *NeuroImage*, 62, 774–781. [https://doi.org/10.1016/j.](https://doi.org/10.1016/j.neuroimage.2012.01.021)
84 [neuroimage.2012.01.021](https://doi.org/10.1016/j.neuroimage.2012.01.021)
- 85 Frackowiak, R., Friston, K., Frith, C., Dolan, R., & Mazziotta, J. (1997). *Human brain*
86 *function*. Academic Press USA. <https://psycnet.apa.org/doi/10.1027/0269-8803.14.2.128>
- 87 Isensee, F., Schell, M., & others. (2019). Automated brain extraction of multisequence
88 MRI using artificial neural networks. *Human Brain Mapping*, 40(17), 4952–4964. [https:](https://doi.org/10.1002/hbm.24750)
89 [//doi.org/10.1002/hbm.24750](https://doi.org/10.1002/hbm.24750)
- 90 Lepage, C., Wagstyl, K., & others. (2021). CIVET-macaque: An automated pipeline for
91 MRI-based cortical surface generation and cortical thickness in macaques. *Neuroimage*,
92 227, 117622. <https://doi.org/10.1016/j.neuroimage.2020.117622>
- 93 Lohmeier, J., Kaneko, T., & others. (2019). AtlasBEX: Automated template-derived brain
94 extraction in animal MRI. *Sci Rep*, 9(1), 12219. [https://doi.org/10.1038/s41598-019-](https://doi.org/10.1038/s41598-019-48489-3)
95 [48489-3](https://doi.org/10.1038/s41598-019-48489-3)
- 96 Messinger, A., Sirmipilatz, N., & others. (2021). A collaborative resource platform for
97 non-human primate neuroimaging. *NeuroImage*, 226, 117519. [https://doi.org/10.1101/](https://doi.org/10.1101/2020.07.31.230185)
98 [2020.07.31.230185](https://doi.org/10.1101/2020.07.31.230185)
- 99 Milham, M., Ai, L., & others. (2018). An open resource for non-human primate imaging.
100 *Neuron*, 100, 61–74. <https://doi.org/10.1016/j.neuron.2018.08.039>
- 101 Smith, S., Jenkinson, M., & others. (2004). Advances in functional and structural MR image
102 analysis and implementation as FSL. *NeuroImage*, 23, 208–219. [https://doi.org/10.1016/j.](https://doi.org/10.1016/j.neuroimage.2004.07.051)
103 [neuroimage.2004.07.051](https://doi.org/10.1016/j.neuroimage.2004.07.051)
- 104 Tournier, J.-D., Smith, R., & others. (2019). MRtrix3: A fast, flexible and open software
105 framework for medical image processing and visualisation. *NeuroImage*, 202, 116–137.
106 <https://doi.org/10.1016/j.neuroimage.2019.116137>
- 107 Zhong, T., Wu, X., & others. (2024). nBEST: Deep-learning-based non-human primates
108 brain extraction and segmentation toolbox across ages, sites and species. *NeuroImage*, 295,
109 120652. <https://doi.org/10.1016/j.neuroimage.2024.120652>