

# <sup>1</sup> PiperABM: A Python Library for Resilience-Based Agent Modeling

<sup>3</sup> **Aslan Noorghasemi**  <sup>1</sup> , **Sierra Hicks**  <sup>2</sup>, and **Christopher McComb**  <sup>1</sup>

<sup>4</sup> 1 Department of Mechanical Engineering, Carnegie Mellon University, USA  <sup>5</sup> 2 Department of Natural Resources and the Environment, Cornell University, USA  

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: Anastassia Vybornova 

## Reviewers:

- [@EwoutH](#)
- [@emilydolson](#)
- [@nikos-salamanos](#)

Submitted: 13 October 2025

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#))

## <sup>6</sup> Summary

<sup>7</sup> *PiperABM* is an open-source Python library for building agent-based simulations that couple <sup>8</sup> human behavior with degrading infrastructure on real-world geospatial layouts. It provides <sup>9</sup> lightweight primitives to enable agents with a customizable decision loop, infrastructure with <sup>10</sup> spatial graphs whose effective travel costs evolve, and built-in analysis for accessibility to <sup>11</sup> resources and travel distance, plus optional animation. Because it is implemented with familiar <sup>12</sup> scientific tools like NumPy and NetworkX, researchers can inspect and extend models directly, <sup>13</sup> integrate empirical data, and reuse standard workflows. *PiperABM* targets research questions <sup>14</sup> centered on resilience, where people's choices and infrastructure conditions co-evolve, seeking <sup>15</sup> to reduce the setup overhead typical of one-off models while remaining flexible enough for <sup>16</sup> diverse hazards, places, and policies.

## <sup>17</sup> Statement of Need

<sup>18</sup> Agent-based models (ABMs) represent systems "from the bottom up" using heterogeneous, <sup>19</sup> interacting agents whose local rules and behaviors generate macro-level patterns macro-level <sup>20</sup> patterns (Joshua M. Epstein, 1999; Joshua M. Epstein & Axtell, 1996; Schelling, 2006). <sup>21</sup> ABM has also been highlighted as a framework that engages diverse stakeholders, enables <sup>22</sup> the forecasting of equitable futures, and empowers policy (Hicks et al., 2021; Noorghasemi et <sup>23</sup> al., 2025). Over the several decades, ABM has matured from theoretical demonstrations to a <sup>24</sup> practical research method supported by accessible tooling and the scientific Python ecosystem <sup>25</sup> (Hoeven et al., 2025). This paradigm is well-suited to infrastructure and community resilience, <sup>26</sup> particularly within the Food–Energy–Water (FEW) nexus, where access to essential resources <sup>27</sup> depends on both physical networks and human decisions, and where nonlinear feedbacks, <sup>28</sup> thresholds, and cascades are common (Cansino-Loeza et al., 2022; Xue et al., 2024; Zhang et <sup>29</sup> al., 2019).


<sup>30</sup> Resilience studies pose several practical modeling needs that are not well served by ad hoc <sup>31</sup> scripts or purely equation-based approaches:

- **Partial service levels and progressive degradation:** Models should represent graded performance (e.g., rougher roads increasing cost/time) rather than only binary failure, reflecting well-studied pavement deterioration processes and performance impacts, e.g., IRI-based assessments (Altarabsheh et al., 2021; Llopis-Castelló et al., 2024).
- **Two-way coupling of behavior and infrastructure:** People adapt routes, priorities, and exchanges as networks evolve; these adaptations, in turn, load and degrade networks. Coupled human–infrastructure ABMs have demonstrated such feedbacks in flood-risk systems and related reviews emphasize capturing co-evolution (Anshuka et al., 2022; Michaelis et al., 2020).

- 41     ▪ **Real geospatial layouts for place-based analysis:** Integrating GIS data (maps/satellite-derived inputs) enables site-specific scenarios and stakeholder communication; recent work in the Python ABM ecosystem formalizes GIS ingestion and spatial operations for ABMs ([Wang et al., 2022](#)).
- 42
- 43
- 44
- 45     ▪ **Ensemble experiments and reproducibility:** Parameter sweeps, stochastic replications, and uncertainty and sensitivity analysis require clear, standardized reporting and careful data handling; community guidelines for documenting agent-based models and recent work on calibration and sensitivity analysis support replicable workflows ([Grimm et al., 2020](#); [McCulloch et al., 2022](#); [Razavi et al., 2021](#)).
- 46
- 47
- 48
- 49
- 50     ▪ **Custom metrics and analysis pipelines:** Familiar data structures expose model state for domain-specific metrics, such as spatiotemporal accessibility under disruption ([Enderami et al., 2024](#); [Tariverdi et al., 2023](#)).
- 51
- 52
- 53     PiperABM is built to meet these needs. It offers simple building blocks in pure Python: a society network comprised of agents and their relationships; an infrastructure network that can wear down over time; tools to load real maps; built-in measures such as accessibility and travel distance; and optional animation for evaluating face validity. With these pieces, researchers can quickly pose hypotheses, run “what-if” scenarios, and study how people’s choices and the infrastructure around them influence one another and analyze socio-technical feedbacks.
- 54
- 55
- 56
- 57
- 58
- 59     Intended users are researchers and practitioners in infrastructure and community resilience, including urban planners, policymakers, and decision-makers who need transparent, reproducible, place-based simulations.
- 60
- 61
- 62

## Model Overview

63     At each time step, agents follow OODA-style decision logic—observing current conditions, 64     orienting, deciding, and acting ([Brehmer, 2005](#); [Johnson, 2023](#)). Agents choose actions such 65     as where to travel, whom to meet, and whether to trade. Routing between locations uses an A\* 66     search on the evolving network to approximate human-like paths ([Foead et al., 2021](#)). Trades 67     between agents are resolved using a Nash bargaining formulation ([Nash, 1950](#)). Infrastructure 68     elements degrade due to both exogenous aging and endogenous usage by agents, increasing 69     effective travel cost and feeding back into subsequent decisions. Simulation results are stored 70     using human-readable delta differencing (KeepDelta), which is compact and easy to debug 71     ([Noorghasemi & McComb, 2025](#)).



72  
73     Figure 1. The computational model of PiperABM emulates the relation between the elements  
74     of infrastructure and social networks.

## 75 Comparison to Existing Tools

76 We group related work into two domains: (1) General frameworks intended to be reusable  
77 across problems, and (2) Purpose-built models created for a single, specific study.

### 78 Domain 1: General frameworks (Python)

79 Mesa is a widely used general-purpose ABM framework that makes it easy to define agents,  
80 schedule steps, collect data, and visualize models in the browser, ideal for rapid prototyping and  
81 analysis (Hoeven et al., 2025). Trade-off: domain logic is do-it-yourself; researchers typically  
82 hand-roll infrastructure degradation, accessibility metrics, and behavior-infrastructure coupling.  
83 InfraRisk is an infrastructure-centric Python platform for interdependent networks (power,  
84 water, transport) with hazard, cascade, recovery, and resilience modules that is strong on  
85 network physics and restoration (Balakrishnan & Cassottana, 2022). Human decision-making  
86 and accessibility-driven behavior are typically added on top, so tight socio-technical feedbacks  
87 can be awkward. Repast4Py is a Python interface to an HPC engine for distributed/parallel  
88 ABMs; models can run across many cores or machines for large studies (Collier & Ozik, 2022).  
89 It does not provide resilience-specific logic (e.g., continuous degradation, accessibility metrics),  
90 which the modeler must supply.

91 Like Mesa and Repast4Py, PiperABM stays flexible and Pythonic, but it elevates resilience  
92 features to first-class concepts: continuous infrastructure degradation (e.g., rougher roads  
93 increasing travel cost), built-in accessibility/travel metrics, a lightweight OODA-style policy  
94 interface, geospatial ingestion, and optional animation. Unlike InfraRisk's "network-first with  
95 agents layered on," PiperABM starts from coupled behavior-infrastructure dynamics, making  
96 socio-technical feedbacks straightforward to model and analyze.

### 97 Domain 2: Purpose-built, one-off models

98 Examples include multilayer post-disaster recovery (e.g., Hurricane Harvey) (Xue et al., 2024),  
99 RecovUS for household recovery after Sandy (Moradi & Nejat, 2020), storm-induced power-  
100 outage restoration with crew dispatch (Walsh et al., 2018), community resilience under tornado  
101 hazards (Aghababaei & Koliou, 2023), and flood risk-insurance dynamics (Dubbelboer et  
102 al., 2017). These models capture exactly what they need but are hard to reuse and often  
103 re-implement similar scaffolding.

104 PiperABM offers the custom feel of bespoke models while reducing rework: degradation and  
105 accessibility are built in; OODA-style decision logic is plug-and-play; infrastructure and agents  
106 live on an inspectable NetworkX backend; and results can be analyzed with standard Python  
107 tools. This makes it easier to adapt a single codebase to new hazards, geographies, and  
108 policies, and to compare scenarios consistently.

## 109 Acknowledgements

110 This work was supported by the U.S. National Science Foundation through Grant RISE-1927718.  
111 Any opinions, findings, conclusions, or recommendations expressed in this article are those of  
112 the authors and do not necessarily reflect the views of the sponsors.

## 113 References

- 114 Aghababaei, M., & Koliou, M. (2023). Community resilience assessment via agent-based  
115 modeling approach. *Computer-Aided Civil and Infrastructure Engineering*, 38(7), 920–939.  
116 <https://doi.org/https://doi.org/10.1111/mice.12916>

- 117 Altarabsheh, A., Altarabsheh, R., Altarabsheh, S., & Asi, I. (2021). Prediction of pavement  
118 performance using multistate survival models. *Journal of Transportation Engineering, Part*  
119 *B: Pavements*, 147(1), 04020082. <https://doi.org/10.1061/JPEODX.0000241>
- 120 Anshuka, A., Ogtrop, F. F. van, Sanderson, D., & Leao, S. Z. (2022). A systematic review of  
121 agent-based model for flood risk management and assessment using the ODD protocol.  
122 *Natural Hazards*, 112(3), 2739–2771. <https://doi.org/10.1007/s11069-022-05286-y>
- 123 Balakrishnan, S., & Cassottana, B. (2022). InfraRisk: An open-source simulation platform for  
124 resilience analysis in interconnected power–water–transport networks. *Sustainable Cities*  
125 *and Society*, 83, 103963. <https://doi.org/10.1016/j.scs.2022.103963>
- 126 Brehmer, B. (2005). The dynamic OODA loop: Amalgamating boyd's OODA loop and the  
127 cybernetic approach to command and control. *Proceedings of the 10th International*  
128 *Command and Control Research Technology Symposium*, 365–368.
- 129 Cansino-Loeza, B., Munguía-López, A. del C., & Ponce-Ortega, J. M. (2022). A water-energy-  
130 food security nexus framework based on optimal resource allocation. *Environmental Science*  
131 *& Policy*, 133, 1–16. <https://doi.org/10.1016/j.envsci.2022.03.006>
- 132 Collier, N., & Ozik, J. (2022). Distributed agent-based simulation with Repast4Py. 2022  
133 *Winter Simulation Conference (WSC)*, 192–206. <https://doi.org/10.1109/WSC57314.2022.10015389>
- 135 Dubbelboer, J., Nikolic, I., Jenkins, K., & Hall, J. (2017). An agent-based model of flood  
136 risk and insurance. *Journal of Artificial Societies and Social Simulation*, 20(1), 6. <https://doi.org/10.18564/jasss.3135>
- 138 Enderami, S. A., Sutley, E., Helgeson, J., Dueñas-Osorio, L., Watson, M., & Lindt, J. W. van  
139 de. (2024). Measuring post-disaster accessibility to essential goods and services: Proximity,  
140 availability, adequacy, and acceptability dimensions. *Journal of Infrastructure Preservation*  
141 *and Resilience*, 5(1). <https://doi.org/10.1186/s43065-024-00104-0>
- 142 Epstein, Joshua M. (1999). Agent-based computational models and generative social science.  
143 *Complexity*, 4(5), 41–60.
- 144 Epstein, Joshua M., & Axtell, R. (1996). *Growing artificial societies: Social science from the*  
145 *bottom up*. Brookings Institution Press; MIT Press. ISBN: 9780262550253
- 146 Foead, D., Ghifari, A., Kusuma, M. B., Hanafiah, N., & Gunawan, E. (2021). A Systematic  
147 Literature Review of A\* Pathfinding. *Procedia Computer Science*, 179, 507–514. <https://doi.org/10.1016/j.procs.2021.01.034>
- 149 Grimm, V., Railsback, S. F., Vincenot, C. E., Berger, U., Gallagher, C., DeAngelis, D. L.,  
150 Edmonds, B., Ge, J., Giske, J., Groeneveld, J., Johnston, A. S. A., Milles, A., Nabe-Nielsen,  
151 J., Polhill, J. G., Radchuk, V., Rohwäder, M.-S., Stillman, R. A., Thiele, J. C., & Ayllón,  
152 D. (2020). The ODD protocol for describing agent-based and other simulation models: A  
153 second update to improve clarity, replication, and structural realism. *Journal of Artificial*  
154 *Societies and Social Simulation*, 23(2), 7. <https://doi.org/10.18564/jasss.4259>
- 155 Hicks, S., McComb, C., & Alessa, L. (2021). *Agents and the Arctic: The Case for Increased*  
156 *Use of Agent-Based Modeling to Study Permafrost — thearcticinstitute.org*. <https://www.thearcticinstitute.org/agents-arctic-case-increased-use-agent-based-modeling-study-permafrost/>
- 158 Hoeven, E. ter, Kwakkel, J., Hess, V., Pike, T., Wang, B., rht, & Kazil, J. (2025). Mesa 3:  
159 Agent-based modeling with Python in 2025. *Journal of Open Source Software*, 10(107),  
160 7668. <https://doi.org/10.21105/joss.07668>
- 161 Johnson, J. (2023). Automating the OODA loop in the age of intelligent machines: Reaffirming  
162 the role of humans in command-and-control decision-making in the digital age. *Defence*  
163 *Studies*, 23(1), 43–67. <https://doi.org/10.1080/14702436.2022.2102486>

- 164 Llopis-Castelló, D., Camacho-Torregrosa, F. J., Romeral-Pérez, F., & Tomás-Martínez, P.  
165 (2024). Estimation of pavement condition based on data from connected and autonomous  
166 vehicles. *Infrastructures*, 9(10). <https://doi.org/10.3390/infrastructures9100188>
- 167 McCulloch, J., Ge, J., Ward, J., Heppenstall, A., Polhill, J. G., & Malleson, N. (2022).  
168 Calibrating agent-based models using uncertainty quantification methods. *Journal of  
169 Artificial Societies and Social Simulation*, 25(2), 1. <https://doi.org/10.18564/jasss.4791>
- 170 Michaelis, T., Brandimarte, L., & Mazzoleni, M. (2020). Capturing flood-risk dynamics with a  
171 coupled agent-based and hydraulic modelling framework. *Hydrological Sciences Journal*,  
172 65(9), 1458–1473. <https://doi.org/10.1080/02626667.2020.1750617>
- 173 Moradi, S., & Nejat, A. (2020). RecovUS: An agent-based model of post-disaster household  
174 recovery. *Journal of Artificial Societies and Social Simulation*, 23(4), 13. <https://doi.org/10.18564/jasss.4445>
- 176 Nash, J. F. (1950). The Bargaining Problem. *Econometrica*, 18(2), 155–162. <https://doi.org/10.2307/1907266>
- 178 Noorghasemi, A., & McComb, C. (2025). KeepDelta: A Python Library for Human-Readable  
179 Data Differencing. *Journal of Open Source Software*, 10(110), 8075. <https://doi.org/10.21105/joss.08075>
- 181 Noorghasemi, A., Xiao, M., & McComb, C. (2025). *Evaluating community well-being and  
182 resilience via agent-based models*. <https://doi.org/10.22541/essoar.173687385.52831340/v1>
- 184 Razavi, S., Jakeman, A., Saltelli, A., Prieur, C., Iooss, B., Borgonovo, E., Plischke, E., Lo  
185 Piano, S., Iwanaga, T., Becker, W., Tarantola, S., Guillaume, J. H. A., Jakeman, J.,  
186 Gupta, H., Melillo, N., Rabitti, G., Chabridon, V., Duan, Q., Sun, X., ... Maier, H. R.  
187 (2021). The future of sensitivity analysis: An essential discipline for systems modeling and  
188 policy support. *Environmental Modelling & Software*, 137, 104954. <https://doi.org/https://doi.org/10.1016/j.envsoft.2020.104954>
- 190 Schelling, T. C. (2006). *Micromotives and macrobehavior* (Revised). W. W. Norton &  
191 Company. <https://doi.org/10.2307/134812>
- 192 Tariverdi, M., Nunez-del-Prado, M., Leonova, N., & Rentschler, J. (2023). Measuring  
193 accessibility to public services and infrastructure criticality for disasters risk management.  
194 *Scientific Reports*, 13(1). <https://doi.org/10.1038/s41598-023-28460-z>
- 195 Walsh, T., Layton, T., Wanik, D., & Mellor, J. (2018). Agent based model to estimate time  
196 to restoration of storm-induced power outages. *Infrastructures*, 3(3). <https://doi.org/10.3390/infrastructures3030033>
- 198 Wang, B., Hess, V., & Crooks, A. (2022). Mesa-Geo: A GIS Extension for the Mesa  
199 Agent-Based Modeling Framework in Python. *Proceedings of the 5th ACM SIGSPATIAL  
200 International Workshop on GeoSpatial Simulation*, 1–10. <https://doi.org/10.1145/3557989.3566157>
- 202 Xue, J., Park, S., Mondal, W. U., Reia, S. M., Yao, T., & Ukkusuri, S. V. (2024). An agent-  
203 based model of post-disaster recovery in multilayer socio-physical networks. *Sustainable  
204 Cities and Society*, 115, 105863. <https://doi.org/https://doi.org/10.1016/j.scs.2024.105863>
- 206 Zhang, P., Zhang, L., Chang, Y., Xu, M., Hao, Y., Liang, S., Liu, G., Yang, Z., & Wang,  
207 C. (2019). Food-energy-water (FEW) nexus for urban sustainability: A comprehensive  
208 review. *Resources, Conservation and Recycling*, 142, 215–224. <https://doi.org/https://doi.org/10.1016/j.resconrec.2018.11.018>