

# <sup>1</sup> pynxtools: A Python framework for generating and <sup>2</sup> validating NeXus files in experimental data workflows

<sup>3</sup> **Sherjeel Shabih**  <sup>1\*</sup>, **Lukas Pielsticker**  <sup>1,2\*</sup>, **Florian Dobener**  <sup>1,3</sup>, **Andrea**  
<sup>4</sup> **Albino**  <sup>1</sup>, **Theodore Chang**  <sup>1</sup>, **Carola Emminger**  <sup>1,4</sup>, **Lev Ginzburg**  <sup>1</sup>,  
<sup>5</sup> **Ron Hildebrandt**  <sup>1,4</sup>, **Markus Kühbach**  <sup>1</sup>, **Rubel Mozumder**  <sup>1</sup>, **Tommaso**  
<sup>6</sup> **Pincelli**  <sup>5</sup>, **Martin Aeschlimann**  <sup>3</sup>, **Marius Grundmann**  <sup>4</sup>, **Walid**  
<sup>7</sup> **Hetaba**  <sup>2</sup>, **Carlos-Andres Palma**  <sup>1,6</sup>, **Laurenz Rettig**  <sup>5</sup>, **Markus**  
<sup>8</sup> **Scheidgen**  <sup>1</sup>, **José Antonio Márquez Prieto**  <sup>1</sup>, **Claudia Draxl**  <sup>1</sup>, **Sandor**  
<sup>9</sup> **Brockhauser**  <sup>1</sup>, **Christoph Koch**  <sup>1</sup>, and **Heiko B. Weber**  <sup>7</sup>

<sup>10</sup> **1** Physics Department and CSMB, Humboldt-Universität zu Berlin, Zum Großen Windkanal 2, D-12489  
<sup>11</sup> Berlin, Germany  **2** Department Heterogeneous Reactions, Max Planck Institute for Chemical Energy  
<sup>12</sup> Conversion, Stiftstraße 34-36, D-45470 Mülheim an der Ruhr, Germany  **3** Department of Physics,  
<sup>13</sup> RPTU Kaiserslautern-Landau, Erwin-Schrödinger-Str. 46, D-67663 Kaiserslautern, Germany  **4** Felix  
<sup>14</sup> Bloch Institute for Solid State Physics, Leipzig University, Linnestr. 5, D-04103 Leipzig, Germany  **5**  
<sup>15</sup> Department of Physical Chemistry, Fritz Haber Institute of the Max Planck Society, Faradayweg 4-6,  
<sup>16</sup> D-14195 Berlin, DE  **6** Institute of Physics, Chinese Academy of Sciences, No.8, 3rd South Street,  
<sup>17</sup> Zhongguancun, Haidian District, Beijing, China  **7** Lehrstuhl für Angewandte Physik,  
<sup>18</sup> Friedrich-Alexander-Universität Erlangen-Nürnberg, Staudtstr. 7, D-91058 Erlangen, Germany  \*  
<sup>19</sup> These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- <sup>20</sup> [Review](#) 
- <sup>21</sup> [Repository](#) 
- <sup>22</sup> [Archive](#) 

Editor: 

Submitted: 14 October 2025

Published: unpublished

## License

Authors of papers retain copyright <sup>29</sup> and release the work under a <sup>30</sup> Creative Commons Attribution 4.0 <sup>31</sup> International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/))<sup>32</sup>. <sup>33</sup> pynxtools is a Python software development framework with a <sup>34</sup> command line interface (CLI) that standardizes data conversion for scientific experiments in <sup>35</sup> materials science to the NeXus format ([Kłosowski et al., 1997; Könnecke, 2006; Könnecke et al., 2015](https://www.nexusformat.org/)) across diverse scientific domains. <sup>36</sup> NeXus defines data storage specifications <sup>37</sup> for different experimental techniques through application definitions. <sup>38</sup> pynxtools provides a <sup>39</sup> fixed, versioned set of NeXus application definitions that ensures convergence and alignment <sup>40</sup> in data specifications across, among others, atom probe tomography, electron microscopy, <sup>41</sup> optical spectroscopy, photoemission spectroscopy, scanning probe microscopy, and X-ray <sup>42</sup> diffraction. Through its modular plugin architecture pynxtools provides conversion of data <sup>43</sup> and metadata from instruments and electronic lab notebooks to these unified definitions, while <sup>44</sup> performing validation to ensure data correctness and NeXus compliance. <sup>45</sup> pynxtools can be <sup>46</sup> integrated directly into Research Data Management Systems (RDMS) to facilitate parsing <sup>47</sup> and normalization. We detail one example for the RDM system NOMAD. By simplifying <sup>48</sup> the adoption of NeXus, the framework enables true data interoperability and FAIR data <sup>49</sup> management across multiple experimental techniques.

## <sup>21</sup> Summary

<sup>22</sup> Scientific data across physics, materials science, and materials engineering often lacks adherence <sup>23</sup> to FAIR principles ([Barker et al., 2022; Jacobsen et al., 2020; M. D. Wilkinson et al., 2016; S. R. Wilkinson et al., 2025](https://doi.org/10.1101/2022.01.05.475375)) due to incompatible instrument-specific formats and diverse <sup>24</sup> standardization practices. <sup>25</sup> pynxtools is a Python software development framework with a <sup>26</sup> command line interface (CLI) that standardizes data conversion for scientific experiments in <sup>27</sup> materials science to the NeXus format ([Kłosowski et al., 1997; Könnecke, 2006; Könnecke et al., 2015](https://www.nexusformat.org/)) across diverse scientific domains. <sup>28</sup> NeXus defines data storage specifications <sup>29</sup> for different experimental techniques through application definitions. <sup>30</sup> pynxtools provides a <sup>31</sup> fixed, versioned set of NeXus application definitions that ensures convergence and alignment <sup>32</sup> in data specifications across, among others, atom probe tomography, electron microscopy, <sup>33</sup> optical spectroscopy, photoemission spectroscopy, scanning probe microscopy, and X-ray <sup>34</sup> diffraction. Through its modular plugin architecture pynxtools provides conversion of data <sup>35</sup> and metadata from instruments and electronic lab notebooks to these unified definitions, while <sup>36</sup> performing validation to ensure data correctness and NeXus compliance. <sup>37</sup> pynxtools can be <sup>38</sup> integrated directly into Research Data Management Systems (RDMS) to facilitate parsing <sup>39</sup> and normalization. We detail one example for the RDM system NOMAD. By simplifying <sup>40</sup> the adoption of NeXus, the framework enables true data interoperability and FAIR data <sup>41</sup> management across multiple experimental techniques.

## <sup>42</sup> Statement of need

<sup>43</sup> Achieving FAIR (Findable, Accessible, Interoperable, and Reproducible) data principles in <sup>44</sup> experimental physics and materials science requires consistent implementation of standardized <sup>45</sup>

42 data formats. NeXus provides comprehensive data specifications for structured storage of  
43 scientific data. pynxtools simplifies the use of NeXus for developers and researchers by by  
44 providing guided workflows and automated validation to ensure complete compliance. Existing  
45 solutions (Jemian et al., 2025; Könnecke et al., 2024) provide individual capabilities, but none  
46 offers a comprehensive end-to-end workflow for proper NeXus adoption. pynxtools addresses  
47 this critical gap by providing a framework that enforces complete NeXus application definition  
48 compliance through automated validation, detailed error reporting for missing required data  
49 points, and clear implementation pathways via configuration files and extensible plugins. This  
50 approach transforms NeXus from a complex specification into a practical solution, enabling  
51 researchers to achieve true data interoperability without deep technical expertise in the  
52 underlying standards.

## 53 Dataconverter and validation

54 The dataconverter, core module of pynxtools, combines instrument output files and data  
55 from electronic lab notebooks into NeXus-compliant HDF5 files. The converter performs three  
56 key operations: extracting experimental data through specialized readers, validating against  
57 NeXus application definitions to ensure compliance with existence and format constraints, and  
58 writing valid NeXus/HDF5 output files.

59 The dataconverter provides a command-line interface (CLI) for generating NeXus files,  
60 supporting both built-in readers for general-purpose functionality and technique-specific reader  
61 plugins, which are distributed as separate Python packages.

62 For developers, the dataconverter provides an abstract reader class for building plugins  
63 that process experiment-specific formats and populate the NeXus specification. It passes a  
64 Template, a subclass of Python's dictionary, to the reader as a form to fill. The Template  
65 ensures structural compliance with the chosen NeXus application definition and organizes data  
66 by NeXus's required, recommended, and optional levels.

67 The dataconverter validates reader output against the selected NeXus application definition,  
68 checking for instances of required concepts, complex dependencies (like inheritance and nested  
69 group rules), and data integrity (type, shape, constraints). It validates required concepts,  
70 reporting errors for any violations, and issues warnings for invalid data, facilitating reliable and  
71 practical NeXus file generation.

72 All reader plugins are tested using the pynxtools.testing suite, which runs automatically  
73 via GitHub CI to ensure compatibility with the dataconverter, the NeXus specification, and  
74 integration across plugins.

75 The dataconverter includes eln\_mapper that creates either a fillable YAML file or a NOMAD  
76 (Scheidgen et al., 2023) ELN schema based on a selected NeXus application definition.

## 77 NeXus reader and annotator

78 read\_nexus enables semantic access to NeXus files by linking data items to NeXus concepts,  
79 allowing applications to locate relevant data without hardcoding file paths. It supports concept-  
80 based queries that return all data items associated with a specific NeXus vocabulary term.  
81 Each data item is annotated by traversing its group path and resolving its corresponding NeXus  
82 concept, included inherited definitions.

83 Items not part of the NeXus schema are explicitly marked as such, aiding in validation and  
84 debugging. Targeted documentation of individual data items is supported through path-specific  
85 annotation. The tool also identifies and summarizes the file's default plottable data based on  
86 the NXdata definition.

## 87 NOMAD integration

88 While pynxtools works independently, it can also be integrated directly into any Research Data  
89 Management System (RDMS). The package works as a plugin within the NOMAD platform ([Draxl](#)  
90 & Scheffler, 2019; [Scheidgen et al., 2023](#)) out of the box. This enables data in the NeXus  
91 format to be integrated into NOMAD's metadata model, making it searchable and interoperable  
92 with other data from theory and experiment. The plugin consists of several key components  
93 (so called entry points):

94 pynxtools extends NOMAD's data schema, known as Metainfo ([Ghiringhelli et al., 2017](#)),  
95 by integrating NeXus definitions as a NOMAD Schema Package. This integration introduces  
96 NeXus-specific quantities and enables interoperability by linking to other standardized data  
97 representations within NOMAD. The dataconverter is integrated into NOMAD, making the con-  
98 version of data to NeXus accessible via the NOMAD GUI. The dataconverter also processes  
99 manually entered NOMAD ELN data in the conversion.

100 The NOMAD Parser module in pynxtools (NexusParser) extracts structured data from NeXus  
101 HDF5 files to populate NOMAD with Metainfo object instances as defined by the pynxtools  
102 schema package. This enables ingestion of NeXus data directly into NOMAD. Parsed data is  
103 post-processed using NOMAD's Normalization pipeline. This includes automatic handling of  
104 units, linking references (including sample and instrument identifiers defined elsewhere in  
105 NOMAD), and populating derived quantities needed for advanced search and visualization.

106 pynxtools contains an integrated Search Application for NeXus data within NOMAD, powered  
107 by Elasticsearch ([Elasticsearch B.V., 2025](#)). This provides a search dashboard whereby users  
108 can efficiently filter uploaded data based on parameters like experiment type, upload timestamp,  
109 and domain- and technique-specific quantities. The entire pynxtools workflow (conversion,  
110 parsing, and normalization) is exemplified in a representative NOMAD Example Upload that is  
111 shipped with the package. This example helps new users understand the workflow and serves  
112 as a template to adapt the plugin to new NeXus applications.

## 113 Funding

114 The work is funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Founda-  
115 tion) - project 460197019 (FAIRmat).

## 116 Acknowledgements

117 We acknowledge the following software packages our package depends on: h5py ([Collette &](#)  
118 [al., 2008](#)), numpy ([Harris et al., 2020](#)), click ([The Pallets development team, 2014](#)), CFF  
119 ([Druskat et al., 2021](#)), xarray ([S. Hoyer & Hamman, 2017](#)), ([Stephan Hoyer et al., 2025](#)),  
120 pandas ([The pandas development team, 2020](#)), scipy ([McKinney, 2010](#)), lxml ([Behnel et](#)  
121 [al., 2005](#)), mergedeep ([Clarke, 2019](#)), Atomic Simulation Environment ([Larsen et al., 2017](#)),  
122 pint ([The Pint development team, 2012](#)).

## 123 References

- 124 Barker, M., Chue Hong, N. P., Katz, D. S., Lamprecht, A.-L., Martinez-Ortiz, C., Psomopoulos,  
125 F., Harrow, J., Castro, L. J., Gruenpeter, M., & Martinez, P. A. et. al. (2022). Introducing  
126 the FAIR principles for research software. *Scientific Data*, 9(1), 622. <https://doi.org/10.1038/s41597-022-01710-x>
- 128 Behnel, S., Faassen, M., & Bicking, I. (2005). *lxml: XML and HTML with python*. <https://lxml.de>

- 130 Clarke, T. (2019). *Mergeddeep: A deep merge function for python*. <https://github.com/clarketm/mergeddeep>
- 131
- 132 Collette, A., & al., et. (2008). *h5py: HDF5 for python*. <https://github.com/h5py/h5py>
- 133 Draxl, C., & Scheffler, M. (2019). The NOMAD laboratory: From data sharing to artificial  
134 intelligence. *Journal of Physics: Materials*, 2(3), 036001. <https://doi.org/10.1088/2515-7639/ab13bb>
- 135
- 136 Druskat, S., Spaaks, J. H., Chue Hong, N., Haines, R., Baker, J., Bliven, S., Willighagen, E.,  
137 Pérez-Suárez, D., & Konovalov, O. (2021). *Citation file format*. <https://doi.org/10.5281/zenodo.1003149>
- 138
- 139 Elasticsearch B.V. (2025). Elasticsearch-py: Official python client for elasticsearch. In *GitHub repository*. GitHub. <https://github.com/elastic/elasticsearch-py>
- 140
- 141 Ghiringhelli, L. M., Carbogno, C., Levchenko, S., Mohamed, F., Huhs, G., Lüders, M., Oliveira,  
142 M., & Scheffler, M. (2017). Towards efficient data exchange and sharing for big-data  
143 driven materials science: Metadata and data formats. *Npj Computational Materials*, 3(1),  
144 46. <https://doi.org/10.1038/s41524-017-0048-5>
- 145 Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,  
146 Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk,  
147 M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., ... Oliphant,  
148 T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. <https://doi.org/10.1038/s41586-020-2649-2>
- 149
- 150 Hoyer, S., & Hamman, J. (2017). Xarray: N-D labeled arrays and datasets in Python. *J. Open  
151 Res. Software*. <https://doi.org/10.5334/jors.148>
- 152
- 153 Hoyer, Stephan, Roos, M., Joseph, H., Magin, J., Cherian, D., Fitzgerald, C., Hauser, M.,  
154 Fujii, K., Maussion, F., Imperiale, G., Clark, S., Kleeman, A., Nicholas, T., Kluyver, T.,  
155 Westling, J., Munroe, J., Amici, A., Barghini, A., Banahirwe, A., ... Littlejohns, O. (2025).  
156 *Xarray* (Version v2025.03.1). Zenodo. <https://doi.org/10.5281/zenodo.15110615>
- 157
- 158 Jacobsen, A., Miranda Azevedo, R. de, Juty, N., Batista, D., Coles, S., Cornet, R., Courtot, M.,  
159 Crosas, M., Dumontier, M., & Evelo, C. T. et. al. (2020). FAIR principles: Interpretations  
160 and implementation considerations. *Data Intelligence*, 2(1-2), 10–29. [https://doi.org/10.1162/dint\\_r\\_00024](https://doi.org/10.1162/dint_r_00024)
- 161
- 162 Jemian, P. R., Ching, D., De Nolf, W., & Stöckli, P. (2025). *Prjemian/punx*. <https://github.com/prjemian/punx>
- 163
- 164 Kłosowski, P., Koennecke, M., Tischler, J. Z., & Osborn, R. (1997). NeXus: A common  
165 format for the exchange of neutron and synchrotron data. *Physica B: Condensed Matter*,  
166 241-243, 151–153. [https://doi.org/10.1016/S0921-4526\(97\)00865-X](https://doi.org/10.1016/S0921-4526(97)00865-X)
- 167
- 168 Könncke, M. (2006). The state of the NeXus data format. *Physica B: Condensed Matter*,  
169 385-386, 1343–1345. <https://doi.org/10.1016/j.physb.2006.06.106>
- 170
- Könnecke, M., Akeroyd, F. A., Bernstein, H. J., Brewster, A. S., Campbell, S. I., Clausen,  
171 B., Cottrell, S., Hoffmann, J. U., Jemian, P. R., & Männicke, D. et. al. (2015). The  
172 NeXus data format. *Applied Crystallography*, 48(1), 301–305. <https://doi.org/10.1107/S1600576714027575>
- 173
- 174 Könnecke, M., Bernstein, H. J., Richter, T., Caswell, T. A., Jemian, P. R., & Levinsen, Y.  
175 (2024). *Nexusformat/cnxvalidate*. <https://github.com/nexusformat/cnxvalidate>
- 176 Larsen, A. H., Mortensen, J. J., Blomqvist, J., Castelli, I. E., Christensen, R., Dułak, M.,  
177 Friis, J., Groves, M. N., Hammer, B., Hargas, C., Hermes, E. D., Jennings, P. C.,  
178 Jensen, P. B., Kermode, J., Kitchin, J. R., Kolsbjergr, E. L., Kubal, J., Kaasbjergr, K.,  
179 Lysgaard, S., ... Jacobsen, K. W. (2017). The atomic simulation environment—a python

- 177 library for working with atoms. *Journal of Physics: Condensed Matter*, 29(27), 273002.  
178 <https://doi.org/10.1088/1361-648X/aa680e>
- 179 McKinney, Wes. (2010). Data Structures for Statistical Computing in Python. In Stéfan van  
180 der Walt & Jarrod Millman (Eds.), *Proceedings of the 9th Python in Science Conference*  
181 (pp. 56–61). <https://doi.org/10.25080/Majora-92bf1922-00a>
- 182 Scheidgen, M., Himanen, L., Ladines, A. N., Sikter, D., Nakhaee, M., Fekete, Á., Chang, T.,  
183 Golparvar, A., Márquez, J. A., Brockhauser, S., Brückner, S., Ghiringhelli, L. M., Dietrich,  
184 F., Lehmberg, D., Denell, T., Albino, A., Näsström, H., Shabih, S., Dobener, F., ... Draxl, C.  
185 (2023). NOMAD: A distributed web-based platform for managing materials science research  
186 data. *Journal of Open Source Software*, 8(90), 5388. <https://doi.org/10.21105/joss.05388>
- 187 The Pallets development team. (2014). *Click: Command line interface creation kit*. <https://github.com/pallets/click>
- 188
- 189 The pandas development team. (2020). *Pandas-dev/pandas: pandas*. Zenodo. <https://doi.org/10.5281/zenodo.3509134>
- 190
- 191 The Pint development team. (2012). *Pint: Operate and manipulate physical quantities in*  
192 *Python*. <https://github.com/hgrecco/pint>. <https://github.com/hgrecco/pint>
- 193 Wilkinson, M. D., Dumontier, M., Aalbersberg, IJ. J., Appleton, G., Axton, M., Baak, A.,  
194 Blomberg, N., Boiten, J.-W., Silva Santos, L. B. da, & Bourne, P. E. et. al. (2016). The  
195 FAIR guiding principles for scientific data management and stewardship. *Scientific Data*,  
196 3(1), 1–9. <https://doi.org/10.1038/sdata.2016.18>
- 197 Wilkinson, S. R., Aloqalaa, M., Belhajjame, K., Crusoe, M. R., Paula Kinoshita, B. de, Gadelha,  
198 L., Garijo, D., Gustafsson, O. J. R., Juty, N., Kanwal, S., Khan, F. Z., Köster, J., Peters-von  
199 Gehlen, K., Pouchard, L., Rannow, R. K., Soiland-Reyes, S., Soranzo, N., Sufi, S., Sun, Z.,  
200 ... Goble, C. (2025). Applying the FAIR principles to computational workflows. *Sci. Data*,  
201 12(1), 328. <https://doi.org/10.1038/s41597-025-04451-9>