

JaxLayerLumos: A JAX-based Differentiable Optical and Radio Frequency Simulator for Multilayer Structures

Mingxuan Li  ^{1*}, Jungtaek Kim  ^{2*}, and Paul W. Leu  ^{1,3¶}

1 Department of Chemical Engineering, University of Pittsburgh, Pittsburgh, PA 15261, United States of America 2 Department of Electrical and Computer Engineering, University of Wisconsin–Madison, Madison, WI 53706, United States of America 3 Department of Industrial Engineering, University of Pittsburgh, Pittsburgh, PA 15261, United States of America ¶ Corresponding author * These authors contributed equally.

DOI: [10.21105/joss.08572](https://doi.org/10.21105/joss.08572)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: Bonan Zhu  

Reviewers:

- [@arendMoerman](#)
- [@brandondubé](#)

Submitted: 23 May 2025

Published: 02 October 2025

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

JaxLayerLumos is an open-source Python package for simulating electromagnetic wave interactions with multilayer structures using the transfer-matrix method (TMM). It is designed for researchers and engineers working with applications in optics, photonics, and related fields. The software efficiently computes reflection, transmission, and absorption across a broad spectral range, including ultraviolet, visible, infrared, microwave, and radio frequencies (RF), with support for magnetic effects in the microwave and radio regimes. A key feature of JaxLayerLumos is its implementation in JAX, which enables automatic differentiation with respect to any input parameter, e.g., layer thicknesses and refractive indices, and supports seamless execution on graphics processing units (GPUs) and tensor processing units (TPUs). This differentiability is valuable for gradient-based optimization and for integrating simulations into machine learning pipelines, accelerating the discovery of novel devices and materials.

Statement of need

Multilayer structures are essential in a wide range of technologies, including structural color coatings (ElKabbash et al., 2023; Sun et al., 2013), next-generation solar cells (Bati et al., 2023; Gao et al., 2014, 2016; Wang & Leu, 2015), radar-absorbing materials (Michielssen et al., 1993; Vinoy & Jha, 1996), and electromagnetic interference (EMI) shielding (Kim et al., 2023, 2024; Li et al., 2022; Zhao et al., 2024), as presented in Figure 1. They are also key components in optical filters, antireflection coatings (Haghafifar et al., 2020), and other photonic devices.



Figure 1: Applications of JaxLayerLumos

TMM ([Born & Wolf, 1999](#)) is a foundational analytical technique for modeling wave interactions in these systems. Table 1 compares several TMM implementations, including [Ansys Optics](#), [TMM-Fast](#), [tmm](#), and our package. Most TMM tools, such as ([Byrnes, 2012](#)) and ([Luce et al., 2022](#)), use the complex refractive index formulation and lack support for magnetic materials or frequencies relevant to RF and microwave applications. There is a growing need for simulation tools that

- Operate efficiently across a broader spectral range including optical, RF, and microwave frequencies,
- Handle magnetic and lossy materials with complex permittivities and complex permeabilities,
- Support modern workflows that integrate machine learning and large-scale optimization.

Table 1: Comparison of other TMM packages with JaxLayerLumos

Feature	Ansys Optics (stackrt)	TMM-Fast (Py- Torch/NumPy)	tmm (Pure Python)	JaxLayerLumos (JAX)
Lightweight	✗ Bulky	✓	✓	✓
Speed on CPUs	✗ Slow	✓ Fast	✗ Slow	~ Moderate
Gradient	✗	✓	✗	✓
Support				
GPU Support	✗	✓	✗	✓
TPU Support¹	✗	✗	✗	✓
Position-Dependent Absorption	✗	✗	✓	✓
Optical Simulations	✓	✓	✓	✓
Infrared Simulations	~ Limited	~ Limited	✗	✓
Radio Wave Simulations	~ Limited	✗	✗	✓ Handles magnetic materials ✓ MIT
Open Source	✗ Commercial	✓ MIT	✓ BSD-3-Clause	✓ MIT

JaxLayerLumos addresses this need by offering a JAX-based TMM framework. Its core advantages include:

- **Differentiability:** Automatically computes gradients with respect to any simulation parameters (e.g., layer thicknesses and refractive indices).
- **Seamless Execution:** Utilizes JAX's just-in-time compilation and hardware acceleration with CPUs, GPUs, or TPUs for efficient computation.
- **Broad Spectral and Material Support:** Accommodates complex permittivities and permeabilities (necessary for magnetic and RF materials), customizable layer structures, oblique incidence, and both TE and TM polarizations.
- **Ecosystem Integration:** Easily integrates with Python's scientific computing stack, including optimization libraries and machine learning frameworks such as JAX ([Bradbury et al., 2018](#)) and Scikit-learn ([Pedregosa et al., 2011](#)).

These capabilities make JaxLayerLumos particularly valuable for researchers working at the intersection of computational electromagnetics and machine learning. As an open-source,

¹Because TPUs are optimized for low-precision computation, their simulation results may show reduced numerical precision.

lightweight alternative to commercial tools, it offers speed, flexibility, and ease of use for advanced research.

Methodology




Figure 2: Schematic of TMM showing a multilayer structure with incident, reflected, and transmitted waves. Each layer is characterized by its thickness d_j , permittivity $\epsilon_{r,j}$, and permeability $\mu_{r,j}$.

The core of JaxLayerLumos implements TMM, which calculates the propagation of electromagnetic waves through a stack of L planar layers (Born & Wolf, 1999). It calculates key optical properties, such as reflection $R(f)$, transmission $T(f)$, and absorption $A(f)$, as functions of frequency f or wavelength λ . The software also supports position-resolved absorption and per-layer absorption calculations. Each layer j is defined by thickness d_j , complex relative permittivity $\epsilon_{r,j}$, and complex relative permeability $\mu_{r,j}$.

For a given frequency f and incidence angle θ_0 , the propagation of light is described by interface matrices \mathbf{D}_j that capture Fresnel coefficients at the boundary between layer j and its following layer, and propagation matrices \mathbf{P}_j representing full wave propagation within each layer and captures both phase shift and attenuation due to absorption in lossy media. The total transfer matrix \mathbf{M} for the entire stack is the product of these individual matrices:

$$\mathbf{M} = (\mathbf{P}_0 \mathbf{D}_0)(\mathbf{P}_1 \mathbf{D}_1) \cdots (\mathbf{P}_L \mathbf{D}_L) \mathbf{P}_{L+1}$$

JaxLayerLumos includes a growing library of materials, which are specified using either complex refractive indices or complex permittivities and permeabilities, which can be sourced from the literature or specified by users based on experimental data. When only complex refractive indices are provided, magnetic effects are assumed to be negligible, and the relative permeability is set to unity ($\mu_{r,j} = 1$), an assumption typically valid at optical frequencies. In the RF and microwave regimes, the electromagnetic properties of metals are derived from their electrical conductivity and magnetic susceptibility, while dielectrics are generally modeled with constant permittivity and negligible loss.

Mention of use

Diverse use cases demonstrate the versatility of JaxLayerLumos:

- **Radar-absorbing materials and frequency-selective surfaces:** Simulate spectral responses in the microwave and RF ranges ([Michielssen et al., 1993](#)), with full support for magnetic materials.
- **Thin-film structural optimization:** Use Bayesian optimization ([Garnett, 2023](#)) or gradient-based methods ([Boyd & Vandenberghe, 2004](#)) to tailor spectral responses across both optical and RF domains.
- **Solar cell design:** Model and analyze single- and multi-junction solar cell architectures ([Gao et al., 2014, 2016; Wang & Leu, 2015](#)).
- **Structural color:** Explore engineered structural coloration for novel material design ([ElKabbash et al., 2023; Sun et al., 2013](#)).
- **Inverse design with machine learning:** Train Transformer-based models ([Vaswani et al., 2017](#)) to design optical coatings and RF devices.

Jupyter notebook examples are available in the [examples directory](#).

Acknowledgements

We thank the open-source community for contributions and feedback. This work was supported by the Center for Materials Data Science for Reliability and Degradation ([MDS-Rely](#)), an Industry–University Cooperative Research Center of the National Science Foundation (NSF), through NSF awards EEC-2052662, EEC-2052776, and EEC-2435402. Additionally, the University of Pittsburgh Center for Research Computing and Data (RRID:SCR_022735) provided essential resources for this work, supported by National Institutes of Health (NIH) award S10OD028483 and NSF award OAC-2117681.

References

- Bati, A. S. R., Zhong, Y. L., Burn, P. L., Nazeeruddin, M. K., Shaw, P. E., & Batmunkh, M. (2023). Next-generation applications for integrated perovskite solar cells. *Communications Materials*, 4(1), 2. <https://doi.org/10.1038/s43246-022-00325-4>
- Born, M., & Wolf, E. (1999). *Principles of optics: Electromagnetic theory of propagation, interference and diffraction of light* (7th ed.). Cambridge University Press. <https://doi.org/10.1017/CBO9781139644181>
- Boyd, S. P., & Vandenberghe, L. (2004). *Convex optimization*. Cambridge university press. <https://doi.org/10.1017/CBO9780511804441>
- Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G., Paszke, A., VanderPlas, J., Wanderman-Milne, S., & Zhang, Q. (2018). *JAX: Composable transformations of Python+NumPy programs* (Version 0.3.13). <http://github.com/jax-ml/jax>
- Byrnes, S. (2012). *tmm: Multilayer optical calculations* (Version 0.2.0). <https://doi.org/10.48550/arXiv.1603.02720>
- ElKabbash, M., Hoffman, N., Lininger, A. R., Jalil, S. A., Letsou, T., Hinczewski, M., Strangi, G., & Guo, C. (2023). Fano resonant optical coatings platform for full gamut and high purity structural colors. *Nature Communications*, 14(1), 3960. <https://doi.org/10.1038/s41467-023-39602-2>
- Gao, T., Stevens, E., Lee, J.-K., & Leu, P. W. (2014). Designing metal hemispheres on silicon ultrathin film solar cells for plasmonic light trapping. *Optics Letters*, 39(16), 4647–4650. <https://doi.org/10.1364/OL.39.004647>
- Gao, T., Wang, B., & Leu, P. W. (2016). Plasmonic nanomesh sandwiches for ultrathin film silicon solar cells. *Journal of Optics*, 19(2), 025901. <https://doi.org/10.1088/2040-8986/>

19/2/025901

- Garnett, R. (2023). *Bayesian optimization*. Cambridge University Press. <https://doi.org/10.1017/9781108348973>
- Haghanifar, S., McCourt, M., Cheng, B., Wuenschell, J., Ohodnicki, P., & Leu, P. W. (2020). Discovering high-performance broadband and broad angle antireflection surfaces by machine learning. *Optica*, 7(7), 784–789. <https://doi.org/10.1364/OPTICA.387938>
- Kim, J., Li, M., Hinder, O., & Leu, P. W. (2023). Datasets and benchmarks for nanophotonic structure and parametric design simulations. *Advances in Neural Information Processing Systems (NeurIPS)*, 36, 4685–4715. <https://doi.org/10.48550/arXiv.2310.19053>
- Kim, J., Li, M., Li, Y., Gómez, A., Hinder, O., & Leu, P. W. (2024). Multi-BOWS: Multi-fidelity multi-objective Bayesian optimization with warm starts for nanophotonic structure design. *Digital Discovery*, 3(2), 381–391. <https://doi.org/10.1039/D3DD00177F>
- Li, M., McCourt, M., Galante, A. J., & Leu, P. W. (2022). Bayesian optimization of nanophotonic electromagnetic shielding with very high visible transparency. *Optics Express*, 30(18), 33182–33194. <https://doi.org/10.1364/OE.468843>
- Luce, A., Mahdavi, A., Marquardt, F., & Wankerl, H. (2022). TMM-Fast, a transfer matrix computation package for multilayer thin-film optimization: tutorial. *Journal of the Optical Society of America A*, 39(6), 1007–1013. <https://doi.org/10.1364/JOSAA.450928>
- Michielssen, E., Sajer, J.-M., Ranjithan, S., & Mittra, R. (1993). Design of lightweight, broadband microwave absorbers using genetic algorithms. *IEEE Transactions on Microwave Theory and Techniques*, 41(6), 1024–1031. <https://doi.org/10.1109/22.238519>
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, É. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12(85), 2825–2830. <https://doi.org/10.48550/arXiv.1201.0490>
- Sun, J., Bhushan, B., & Tong, J. (2013). Structural coloration in nature. *RSC Advances*, 3(35), 14862–14889. <https://doi.org/10.1039/C3RA41096J>
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., & Polosukhin, I. (2017). Attention is all you need. *Advances in Neural Information Processing Systems*, 30, 5998–6008. <https://doi.org/10.48550/arXiv.1706.03762>
- Vinoy, K. J., & Jha, R. M. (1996). *Radar absorbing materials: From theory to design and characterization*. Springer. <https://doi.org/10.1007/978-1-4613-0473-9>
- Wang, B., & Leu, P. W. (2015). High index of refraction nanosphere coatings for light trapping in crystalline silicon thin film solar cells. *Nano Energy*, 13, 226–232. <https://doi.org/10.1016/j.nanoen.2014.10.040>
- Zhao, H., Wang, J., He, M., Li, S., Guo, H., Kan, D., Qiu, H., Chen, L., & Gu, J. (2024). Electromagnetic interference shielding films: Structure design and prospects. *Small Methods*, 2401324. <https://doi.org/10.1002/smtd.202401324>