

OApkg: A Python package for generation and analysis of orthogonal arrays, optimal designs and conference designs

Pieter Thijs Eendebak^{1, 2} and Alan Roberto Vazquez^{1, 3}

¹ Department of Engineering Management, University of Antwerp, Belgium ² Netherlands Organisation for Applied Scientific Research (TNO), P.O. Box 155, 2600 AD Delft, The Netherlands ³ Department of Biosystems, KU Leuven, Leuven, Belgium

DOI: [10.21105/joss.01097](https://doi.org/10.21105/joss.01097)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted: 11 November 2018

Published: 27 February 2019

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

Summary

Orthogonal arrays, optimal designs and conference designs are important tools for the design of experiments (Elster & Neumaier, 1995), (Hedayat, Sloane, & Stufken, 2012), (Wu & Hamada, 2009). The OApkg (Orthogonal Array package) contains functionality to generate and analyse these types of designs. More specifically, the OApkg allows the user to:

- Efficiently generate orthogonal arrays, optimal designs and conference designs
- Reduce the designs to their normal form and perform isomorphism testing
- Calculate a wide variety of statistical properties of the designs

The data analysis of the experiments conducted using the generated designs is left to existing statistical software such as R (R Core Team, 2018) and JMP (Wikipedia contributors, 2018).

To generate orthogonal arrays and conference designs, the OApkg uses an exhaustive generation procedure with isomorphism pruning (Schoen, Eendebak, & Nguyen, 2010), (Schoen, Eendebak, & Goos, 2019). To generate optimal designs, the package uses a flexible optimality criterion and a coordinate-exchange optimization algorithm (Eendebak & Schoen, 2017).

The reduction of the designs to their normal form is done by either reduction to a minimal form (such as lexicographically minimal in columns or delete-one-factor projection normal form (P. Eendebak, 2014)) or reduction using graph algorithms. For designs with a specified isomorphism group, the OApkg provides a generic interface to the graph reduction algorithms that effectively perform isomorphism testing and reduction to normal form.

The OApkg evaluates the orthogonal arrays, optimal designs and conference designs using well-known statistical criteria. For instance, the package can calculate the generalized wordlength pattern and confounding frequency vector (Tang & Deng, 1999), which are based on the J-characteristics (Deng & Tang, 1999), and the number of degrees of freedom available for estimating selected factors' effects. The package can also calculate the F_4 vector of conference designs (Schoen et al., 2019) and the D-efficiency of optimal designs (Goos & Jones, 2011).

The OApkg consists of a C++ library with a Python interface generated by SWIG. The source code is available at <https://github.com/eendebakpt/oapkg>. Examples for

both generation and analysis of designs are available in the OApkg documentation (P. Eendebak & Vazquez, 2018). The Orthogonal Array package website (P. Eendebak, 2018) contains a large collection of orthogonal arrays, optimal designs and conference designs generated with the package.

Acknowledgements

We acknowledge useful discussions with Eric Schoen during the development of this project.

References

- Deng, L.-Y., & Tang, B. (1999). Generalized resolution and minimum aberration criteria for Plackett-Burman and other nonregular factorial designs. *Statistica Sinica*, 9(4), 1071–1082. Retrieved from <http://www.jstor.org/stable/24306636>
- Eendebak, P. (2014). A canonical form for non-regular arrays based on generalized wordlength pattern values of delete-one-factor projections.
- Eendebak, P. (2018). The Orthogonal Array Package: Results. Retrieved January 1, 2019, from <http://www.pietereendebak.nl/oapackage/>
- Eendebak, P. T., & Schoen, E. D. (2017). Two-level designs to estimate all main effects and two-factor interactions. *Technometrics*, 59(1), 69–79. doi:10.1080/00401706.2016.1142903
- Eendebak, P., & Vazquez, A. R. (2018). The Orthogonal Array package. Retrieved from <https://oapackage.readthedocs.io/en/latest/>
- Elster, C., & Neumaier, A. (1995). Screening by conference designs. *Biometrika*, 82(3), 589–602. doi:10.1093/biomet/82.3.589
- Goos, P., & Jones, B. (2011). Optimal design of experiments: A case study approach. doi:10.1002/9781119974017
- Hedayat, A. S., Sloane, N. J. A., & Stufken, J. (2012). *Orthogonal arrays: Theory and applications*. Springer Science & Business Media.
- R Core Team. (2018). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org>
- Schoen, E. D., Eendebak, P. T., & Goos, P. (2019). A classification criterion for definitive screening designs. *Ann. Statist.*, 47(2), 1179–1202. doi:10.1214/18-AOS1723
- Schoen, E. D., Eendebak, P. T., & Nguyen, M. V. M. (2010). Complete enumeration of pure-level and mixed-level orthogonal arrays. *Journal of Combinatorial Designs*, 18(2), 123–140. doi:10.1002/jcd.20236
- Tang, B., & Deng, L.-Y. (1999). Minimum G_2 -aberration for nonregular fractional factorial designs. *The Annals of Statistics*, 27(6), 1914–1926. doi:10.1214/aos/1017939244
- Wikipedia contributors. (2018). JMP (statistical software) — Wikipedia, the free encyclopedia. Retrieved from [https://en.wikipedia.org/w/index.php?title=JMP_\(statistical_software\)&oldid=858334218](https://en.wikipedia.org/w/index.php?title=JMP_(statistical_software)&oldid=858334218)
- Wu, C., & Hamada, M. (2009). *Experiments: Planning, analysis and optimization*. Wiley.