

PileupCaller: A command-line tool to sample genotypes from low-coverage sequencing data of ancient DNA

Stephan Schiffels¹

¹ Max Planck Institute for Evolutionary Anthropology, Leipzig, Germany

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [AHM Mahfuzur Rahman](#)



Reviewers:

- [@dkoptekin](#)
- [@josecediel25](#)

Submitted: 09 May 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Next generation sequencing data is ubiquitous in medical and biological sciences. It has also become the primary tool in archaeogenetics, where ancient DNA is extracted from archaeological organic (often human skeletal) material, processed into DNA sequencing libraries and then sequenced ([Orlando et al., 2021](#)). As a testimony to the rapid and accelerating growth of the field, we today have close to ten thousand published ancient human genomes available in the public record ([Mallick et al., 2024](#); [Schmid et al., 2024](#)), and many smaller datasets of other organisms. A key step in processing raw sequencing data is the estimation of genotypes at specific variable positions along the genome. Such positions are often pre-selected because they are informative about ancestry or of particular biological relevance ([Haak et al., 2015](#); [Mathieson et al., 2015](#); [Rohland et al., 2022](#)). While established tools exist for this task for high-quality modern sequencing data ([Danecek et al., 2021](#); [Van der Auwera & O'Connor, 2020](#)), these are often not appropriate for ancient DNA, which has often too low sequencing-coverage and a higher error rate due to post-mortem DNA damage. PileupCaller is a command-line tool written in Haskell, which randomly samples genotypes from raw alignment data at predefined bi-allelic positions. Several modes can be selected, geared towards specific input data features and research questions.

Statement of need

Present-day DNA, for example from medical studies results in raw sequencing data with relatively low per-base error rates and sequencing-coverages of at least several multiples of 1 (for example ([1000 Genomes Project Consortium et al., 2015](#))) but in fact up to 20-30x coverage. Dedicated tools to process such data include samtools/bcftools ([Danecek et al., 2021](#)) and GATK ([Van der Auwera & O'Connor, 2020](#)) among many other tools. Ancient DNA sequencing data often comes with substantially lower coverage and substantially higher error rates. In terms of coverage, most ancient genomes have genome-wide coverage often below 1x and in fact very often even below 0.1x. Such low coverage means that any given genomic site is more likely not covered by a sequencing read than covered. At the same time, the low fraction of sites that is actually covered has higher error rates than modern DNA, due to ancient-DNA damage. These two factors violate the assumptions behind statistical genotype callers like bcftools call or HaplotypeCaller from GATK.

As is widely used practice in the field, very low-coverage ancient DNA data is often “called”, simply by randomly selecting reads at a given position of interest. PileupCaller is a command-line tool that does exactly that, by reading in a list of SNP positions and a stream of sequencing data, some optional filtering options, and then performs random samples at every position of interest for multiple individuals. Even before this paper, pileupCaller has been widely used

41 since its creation in 2017, mostly because of its simple use and low-memory footprint thanks
42 to streaming.

43 Usage and key functionality

44 pileupCaller relies on the pileup format defined in (Danecek et al., 2021). This format lists
45 for each site the nucleotides from all reads covering that site, including base-qualities. An
46 example pileup-file can be found in the repository. These files are rarely saved, but used as
47 an intermediate format for streaming, specifically from samtools mpileup(). A typical usage
48 command line for pileupCaller could be:

```
samtools mpileup -R -B -q30 -Q30 -f <reference_genome.fasta> \
  Sample1.bam Sample2.bam Sample3.bam | \
pileupCaller --randomHaploid --sampleNames Sample1,Sample2,Sample3 \
  --samplePopName MyPop -f <Eigenstrat.snp> \
  -e <My_output_prefix>
```

49 Among the options passed to samtools mpileup, we highlight the -B flag, which switches
50 off base-alignment quality recalibration and is critical for avoiding reference bias with low-
51 coverage ancient DNA. A key input ingredient is the SNP list, which needs to be given in
52 Eigenstrat-format (Price et al., 2006), defined in (Mah et al., 2021). Example files for Pileup
53 and Eigenstrat-formatted data can be found under test/testDat in the software repository.
54 The SNP file not only lists the positions of the variants that should be called, but also the two
55 possible alleles at each site. This is important, as pileupCaller will ensure that only those two
56 alleles are called. Sites at which a third allele is called will be output as missing.

57 In terms of output formats, pileupCaller currently supports Eigenstrat, Plink (<https://www.cog-genomics.org/plink/2.0/>) and VCF (Danecek et al., 2011), with an option to additionally
58 compress the output in gzip-format. Command line options are documented inline via
59 pileupCaller --help.

61 PileupCaller is part of the “sequenceTools” package, which contains multiple other minor
62 scripts and command-line tools, with pileupCaller being the central and most popular tool.
63 The sequenceTools package makes key use of the “sequence-formats” Haskell library (Schiffels,
64 2025), which contains parsers for the Pileup-, the Plink-, the Eigenstrat and the VCF-Format.

65 References

- 66 1000 Genomes Project Consortium, Corresponding authors, Steering committee, Production
67 group, Baylor College of Medicine, Coriell Institute for Medical Research, Max
68 Planck Institute for Molecular Genetics, US National Institutes of Health, Analysis
69 group, Affymetrix, Albert Einstein College of Medicine, Harvard University, Human
70 Gene Mutation Database, Icahn School of Medicine at Mount Sinai, Massachusetts
71 General Hospital, McGill University, New York Genome Center, Ontario Institute
72 for Cancer Research, Pennsylvania State University, ... Peruvian in Lima, P. (pel).
73 (2015). A global reference for human genetic variation. *Nature*, 526(7571), 68–74.
74 <http://www.nature.com/doifinder/10.1038/nature15393>
- 75 Danecek, P., Auton, A., Abecasis, G., Albers, C. A., Banks, E., DePristo, M. A., Handsaker,
76 R. E., Lunter, G., Marth, G. T., Sherry, S. T., McVean, G., Durbin, R., & 1000 Genomes
77 Project Analysis Group. (2011). The variant call format and VCFtools. *Bioinformatics*
78 (*Oxford, England*), 27(15), 2156–2158. <https://doi.org/10.1093/bioinformatics/btr330>
- 79 Danecek, P., Bonfield, J. K., Liddle, J., Marshall, J., Ohan, V., Pollard, M. O., Whitwham, A.,
80 Keane, T., McCarthy, S. A., Davies, R. M., & Li, H. (2021). Twelve years of SAMtools
81 and BCFtools. *GigaScience*, 10(2). <https://doi.org/10.1093/gigascience/giab008>

- 82 Haak, W., Lazaridis, I., Patterson, N., Rohland, N., Mallick, S., Llamas, B., Brandt, G.,
 83 Nordenfelt, S., Harney, E., Stewardson, K., Fu, Q., Mittnik, A., Bánffy, E., Economou,
 84 C., Francken, M., Friederich, S., Pena, R. G., Hallgren, F., Khartanovich, V., ... Reich, D.
 85 E. (2015). Massive migration from the steppe was a source for indo-european languages
 86 in europe. *Nature*, 522(7555), 207–211. [http://www.nature.com/doifinder/10.1038/](http://www.nature.com/doifinder/10.1038/nature14317)
 87 [nature14317](http://www.nature.com/doifinder/10.1038/nature14317)
- 88 Mah, M., Patterson, N., & Price, A. (2021). Eigensoft. In *GitHub repository*. GitHub.
 89 <https://github.com/DReichLab/EIG>
- 90 Mallick, S., Micco, A., Mah, M., Ringbauer, H., Lazaridis, I., Olalde, I., Patterson, N., &
 91 Reich, D. (2024). The allen ancient DNA resource (AADR) a curated compendium of
 92 ancient human genomes. *Scientific Data*, 11(1), 1–10. [https://doi.org/10.1038/s41597-](https://doi.org/10.1038/s41597-024-03031-7)
 93 [024-03031-7](https://doi.org/10.1038/s41597-024-03031-7)
- 94 Mathieson, I., Lazaridis, I., Rohland, N., Mallick, S., Patterson, N., Roodenberg, S. A.,
 95 Harney, E., Stewardson, K., Fernandes, D., Novak, M., Sirak, K., Gamba, C., Jones, E. R.,
 96 Llamas, B., Dryomov, S., Pickrell, J., Arsuaga, J. L., Castro, J. M. B. de, Carbonell, E., ...
 97 Reich, D. E. (2015). Genome-wide patterns of selection in 230 ancient eurasians. *Nature*.
 98 <http://www.nature.com/doifinder/10.1038/nature16152>
- 99 Orlando, L., Allaby, R., Skoglund, P., Der Sarkissian, C., Stockhammer, P. W., Ávila-Arcos, M.
 100 C., Fu, Q., Krause, J., Willerslev, E., Stone, A. C., & Warinner, C. (2021). Ancient DNA
 101 analysis. *Nature Reviews. Methods Primers*, 1(1). [https://doi.org/10.1038/s43586-020-](https://doi.org/10.1038/s43586-020-00011-0)
 102 [00011-0](https://doi.org/10.1038/s43586-020-00011-0)
- 103 Price, A. L., Patterson, N. J., Plenge, R. M., Weinblatt, M. E., Shadick, N. A., & Reich, D. E.
 104 (2006). Principal components analysis corrects for stratification in genome-wide association
 105 studies. *Nature Genetics*, 38(8), 904–909. [http://www.nature.com/doifinder/10.1038/](http://www.nature.com/doifinder/10.1038/ng1847)
 106 [ng1847](http://www.nature.com/doifinder/10.1038/ng1847)
- 107 Rohland, N., Mallick, S., Mah, M., Maier, R., Patterson, N., & Reich, D. (2022). Three assays
 108 for in-solution enrichment of ancient human DNA at more than a million SNPs. *Genome*
 109 *Research*, 32(11-12), 2068–2078. <https://doi.org/10.1101/gr.276728.122>
- 110 Schiffels, S. (2025). Sequence-formats. In *GitHub repository*. GitHub. [https://github.com/](https://github.com/stschiff/sequence-formats)
 111 [stschiff/sequence-formats](https://github.com/stschiff/sequence-formats)
- 112 Schmid, C., Ghalichi, A., Lamnidis, T. C., Mudiyansele, D. B. A., Haak, W., & Schiffels, S.
 113 (2024). *Poseidon – a framework for archaeogenetic human genotype data management*.
 114 <https://doi.org/10.7554/elife.98317>
- 115 Van der Auwera, G. A., & O'Connor, B. D. (2020). *Genomics in the cloud: Using docker,*
 116 *GATK, and WDL in terra*. O'Reilly Media.