

VST: A Python-based deep learning tool for segmenting electron microscopy samples

Yuyao (Daniel) Huang¹, Nickhil Jadav¹, Georgia Rutter¹, Mihnea Bostina^{1,2}, Duane Harland³, and Lech Szymanski¹

¹ University of Otago, New Zealand ² Okinawa Institute of Science and Technology Graduate University, Japan ³ AgResearch Group, New Zealand Institute for Bioeconomy Science Ltd, New Zealand

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Richard Liu

Reviewers:

- @ibro45
- @ductho-le
- @ClementCaporal

Submitted: 03 December 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

Volume Segmentation Tool (VST) is a Python based deep learning tool designed specifically to segment three-dimensional VEM biological data without extensive requirements for cross disciplinary knowledge in deep learning. The tool is made accessible through a user-friendly interface with visualisations and a one-click installer.

Recognising the current rapid expansion of the VEM field, we have built VST with flexibility and instance segmentation in mind, hoping to ease and accelerate statistical analysis of large datasets in biological and medical research contexts. VST is composed of two main parts: the PyTorch (Paszke et al., 2019)-based deep learning core that performs semantic/instance segmentation on volumetric grey scale image datasets, and a user interface that operates on top of it, responsible for constructing CLI commands to the core components for tasking. The general pipeline of VST is shown in Figure 1. We had put in efforts to ensure VST could automatically handle issues associated with large dataset sizes, instance segmentation, anisotropic voxels and imbalanced classes.




Figure 1: Schematic diagram for VST

Statement of need

Volume Electron Microscopy (VEM) enables the capture of 3D structure beyond planar samples, which is crucial for understanding biological mechanisms. With automation, improved resolution, and increased data storage capacity, VEM has led to an explosion of large three-dimensional datasets. Large datasets offer the opportunity to generate statistical data, but analysing them often requires assigning each voxel (3D pixel) to its corresponding structure, a process known as image segmentation. Manually segmenting hundreds or thousands of image slices is tedious and time-consuming. Computer-aided, especially Machine Learning (ML) based segmentation is now a routinely used method, with Trainable Weka Segmentation (Arganda-Carreras et al., 2017) and Ilastik (Berg et al., 2019) being two leading options. Emerging methods for EM image segmentation are often based on Deep Learning (DL) (Mekuč et al., 2020) because this approach has potential to outperform traditional ML in terms of accuracy and adaptivity (Erickson, 2019; Minaee et al., 2021).

Many earlier DL tools developed are highly specific to single sample types, like in connectomics (Kamnitsas et al., 2017; W. Li et al., 2017), MRI (Milletari et al., 2016) or X-ray tomography (A. Li et al., 2022), they use a subject-optimised design at the cost of adaptability to non-target datasets. Dedicated DL segmentation tools for generalised VEM data are gradually becoming available but each have short-comings. One example, CDeep3M (Haberl et al., 2018), which uses cloud computing. Although easy to use, it was designed for anisotropic data (where the z-resolution is much lower than xy-resolution) which creates limitations when applied to isotropic data (Gallusser et al., 2022). Another example is DeepImageJ (Gómez-de-Mariscal et al., 2021), which runs on local hardware and integrates easily with the ImageJ suit (Schneider et al., 2012). However, it only supports pre-trained models and does not have the functionality

to train new ones. ZeroCostDL4Mic (Von Chamier et al., 2021) utilises premade notebooks running on Google Colab, but it requires user interaction during the entire segmentation process, which can take hours and thus is inconvenient. A more recent and advanced example is nnU-Net (Isensee et al., 2021), which auto-configurates itself based on dataset properties and has a good support for volumetric dataset, but it focuses exclusively on semantic segmentation and lacks a user friendly interface.

In short, there is a lack of tools that can handle a wide range of VEM data well for generating both semantic and instance segmentation, while at the same time been easy to use, scalable and can be run locally. Which is what motivated us to develop VST - an easy-to-use and adaptive DL tools specifically optimised for generalised VEM image segmentation.

Software design

The core principles of VST lie in the user-friendliness and scalability. The software comes with a one-click installer and full documentation on all user-accessible features, with the aim to enable accessibility for domain experts without machine learning expertise. In terms of scalability, VST uses Zarr (Abernathey, n.d.), a framework for distributed storage, which allows just-in-time, chunked access for datasets much larger than the user's system memory. Which is a common situation within VEM, where datasets of hundreds or thousands of gigabytes scales are present.

In terms of design, the software provides a graphical interface over a set of scripts handling various aspects of the deep learning and inference workload. The internal training framework utilises PyTorch (Paszke et al., 2019), the interface compiles terminal commands and activates the Python scripts as needed (Figure 1). For the DL model underneath, VST uses a heavily modified U-Net (Ronneberger et al., 2015), a proven DL architecture for segmentation tasks that is known for its fast convergence and adaptability. The size, depth and other details of the model are configured automatically based on the characteristics of the user's dataset.

Much of VST's internal logic is optimised for single-class semantic and instance segmentation and cannot easily be transferred to the multi-class case or 2D image segmentation. This trade-off was made to keep workloads manageable, simplify the codebase, and maximise the ease of use for those with minimal machine learning expertise.

Research impact statement

VST has been used in postgraduate projects at the University of Otago in New Zealand for segmentation of the entire mitochondrial complement of tumorsphere (Jadav et al., 2023), as well as poorly demarked cell remnants within wool fibres. VST's competitive performance to nnU-Net (Huang et al., 2025), an MIT open-source licence, and comprehensive documentation make it ready for use by the wider community.

The graphical user interface

VST's GUI is supported by the Gradio package (Abid et al., 2019) and hosted on the user's browser.

The GUI is divided into three sections: Main, Activations Visualisation and Extras.

The main section (Figure 2) contains settings regarding training and using segmenting networks. Two segmentation modes are supported: semantic segmentation, in which the foreground objects are separated from the background, and instance segmentation, in which individual foreground objects are separated from each other as well. User can either train a new network,

load an existing network and use it for predictions on new data, or train one and use it immediately.

Upon training, it automatically opens a TensorBoard interface (Pang et al., 2020) to provides various real time visualisations for the training process.




Figure 2: The main interface of VST

The activations visualisation section requires a trained network and an example image. Given that image, it plots the activation across each channel through all layers of the network.

The extra section contains two functionalities: exporting the TensorBoard log to an Excel table, calculating segmentation metrics between (potentially) generated labels and ground truth labels.

97 AI Usage Disclosure

98 ChatGPT and DeepSeek were used to generate some Python functions. All generated functions
99 were thoroughly analysed, tested with real-world data, modified and verified to satisfy desired
100 input and output conditions. No generative AI tools were used in the writing of this manuscript,
101 or the preparation of supporting materials.

102 Acknowledgements

103 We want to thank to the New Zealand Institute for Bioeconomy Science for their support
104 during the MSc study and University of Otago Postgraduate Publishing Bursary (Master's) for
105 their support with the time of writing.

106 References

- 107 Abernathey, R. (n.d.). Zarr (Web Page Jan 20th; Vol. 2026). <https://zarr.dev/>
- 108 Abid, A., Abdalla, A., Abid, A., Khan, D., Alfozan, A., & Zou, J. (2019). Gradio: Hassle-free
109 sharing and testing of ml models in the wild. *arXiv Preprint arXiv:1906.02569*.
- 110 Arganda-Carreras, I., Kaynig, V., Rueden, C., Eliceiri, K. W., Schindelin, J., Cardona, A., &
111 Sebastian Seung, H. (2017). Trainable weka segmentation: A machine learning tool for
112 microscopy pixel classification. *Bioinformatics*, 33(15), 2424–2426.
- 113 Berg, S., Kutra, D., Kroeger, T., Straehle, C. N., Kausler, B. X., Haubold, C., Schiegg, M.,
114 Ales, J., Beier, T., Rudy, M., & others. (2019). Ilastik: Interactive machine learning for
115 (bio) image analysis. *Nature Methods*, 16(12), 1226–1232.
- 116 Erickson, B. J. (2019). Deep learning and machine learning in imaging: Basic principles. In
117 *Artificial intelligence in medical imaging: Opportunities, applications and risks* (pp. 39–46).
118 Springer.
- 119 Gallusser, B., Maltese, G., Di Caprio, G., Vadakkan, T. J., Sanyal, A., Somerville, E.,
120 Sahasrabudhe, M., O'connor, J., Weigert, M., & Kirchhausen, T. (2022). Deep neural
121 network automated segmentation of cellular structures in volume electron microscopy.
122 *Journal of Cell Biology*, 222(2), e202208005.
- 123 Gómez-de-Mariscal, E., García-López-de-Haro, C., Ouyang, W., Donati, L., Lundberg, E., Unser,
124 M., Muñoz-Barrutia, A., & Sage, D. (2021). DeeplmageJ: A user-friendly environment to
125 run deep learning models in ImageJ. *Nature Methods*, 18(10), 1192–1195.
- 126 Haberl, M. G., Churas, C., Tindall, L., Boassa, D., Phan, S., Bushong, E. A., Madany, M.,
127 Akay, R., Deerinck, T. J., Peltier, S. T., & others. (2018). CDeep3M—plug-and-play
128 cloud-based deep learning for image segmentation. *Nature Methods*, 15(9), 677–680.
- 129 Huang, Y., Jadav, N., Rutter, G., Szymanski, L., Bostina, M., & Harland, D. P. (2025).
130 A generalist deep-learning volume segmentation tool for volume electron microscopy of
131 biological samples. *Journal of Structural Biology*, 217(3), 108214.
- 132 Isensee, F., Jaeger, P. F., Kohl, S. A., Petersen, J., & Maier-Hein, K. H. (2021). nnU-net: A
133 self-configuring method for deep learning-based biomedical image segmentation. *Nature*
134 *Methods*, 18(2), 203–211.
- 135 Jadav, N., Velamoor, S., Huang, D., Cassin, L., Hazelton, N., Eruera, A.-R., Burga, L. N., &
136 Bostina, M. (2023). Beyond the surface: Investigation of tumorsphere morphology using
137 volume electron microscopy. *Journal of Structural Biology*, 215(4), 108035.
- 138 Kamnitsas, K., Ledig, C., Newcombe, V. F., Simpson, J. P., Kane, A. D., Menon, D. K.,
139 Rueckert, D., & Glocker, B. (2017). Efficient multi-scale 3D CNN with fully connected

- 140 CRF for accurate brain lesion segmentation. *Medical Image Analysis*, 36, 61–78.
- 141 Li, A., Zhang, X., Singla, J., White, K., Loconte, V., Hu, C., Zhang, C., Li, S., Li, W., Francis,
142 J. P., & others. (2022). Auto-segmentation and time-dependent systematic analysis of
143 mesoscale cellular structure in β -cells during insulin secretion. *Plos One*, 17(3), e0265567.
- 144 Li, W., Wang, G., Fidon, L., Ourselin, S., Cardoso, M. J., & Vercauteren, T. (2017). On the
145 compactness, efficiency, and representation of 3D convolutional networks: Brain parcellation
146 as a pretext task. *International Conference on Information Processing in Medical Imaging*,
147 348–360.
- 148 Mekuč, M. Ž., Bohak, C., Hudoklin, S., Kim, B. H., Kim, M. Y., Marolt, M., & others.
149 (2020). Automatic segmentation of mitochondria and endolysosomes in volumetric electron
150 microscopy data. *Computers in Biology and Medicine*, 119, 103693.
- 151 Milletari, F., Navab, N., & Ahmadi, S.-A. (2016). V-net: Fully convolutional neural networks
152 for volumetric medical image segmentation. *2016 Fourth International Conference on 3D
153 Vision (3DV)*, 565–571.
- 154 Minaee, S., Boykov, Y., Porikli, F., Plaza, A., Kehtarnavaz, N., & Terzopoulos, D. (2021).
155 Image segmentation using deep learning: A survey. *IEEE Transactions on Pattern Analysis
156 and Machine Intelligence*, 44(7), 3523–3542.
- 157 Pang, B., Nijkamp, E., & Wu, Y. N. (2020). Deep learning with tensorflow: A review. *Journal
158 of Educational and Behavioral Statistics*, 45(2), 227–248.
- 159 Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin,
160 Z., Gimelshein, N., Antiga, L., & others. (2019). Pytorch: An imperative style, high-
161 performance deep learning library. *Advances in Neural Information Processing Systems*,
162 32.
- 163 Ronneberger, O., Fischer, P., & Brox, T. (2015). U-net: Convolutional networks for biomedical
164 image segmentation. *International Conference on Medical Image Computing and Computer-
165 Assisted Intervention*, 234–241.
- 166 Schneider, C. A., Rasband, W. S., & Eliceiri, K. W. (2012). NIH image to ImageJ: 25 years of
167 image analysis. *Nature Methods*, 9(7), 671–675.
- 168 Von Chamier, L., Laine, R. F., Jukkala, J., Spahn, C., Krentzel, D., Nehme, E., Lerche, M.,
169 Hernández-Pérez, S., Mattila, P. K., Karinou, E., & others. (2021). Democratising deep
170 learning for microscopy with ZeroCostDL4Mic. *Nature Communications*, 12(1), 2276.