

# nestcheck: error analysis, diagnostic tests and plots for nested sampling calculations

Edward Higson<sup>1, 2</sup>

<sup>1</sup> Astrophysics Group, Cavendish Laboratory, J.J.Thomson Avenue, Cambridge, CB3 0HE, UK <sup>2</sup> Kavli Institute for Cosmology, Madingley Road, Cambridge, CB3 0HA, UK

DOI: [10.21105/joss.00874](https://doi.org/10.21105/joss.00874)

## Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted: 04 August 2018

Published: 05 August 2018

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

## Summary

Nested sampling (Skilling 2006) is a popular Monte Carlo method for Bayesian analysis which, given some likelihood and prior, provides both samples from the posterior distribution and an estimate of the Bayesian evidence. Due to the distinctive manner in which the nested sampling algorithm explores the parameter space, it produces posterior samples with different statistical properties to those generated from alternative techniques such as Markov chain Monte Carlo (MCMC)-based approaches. As a result, posterior inferences and estimates of their associated uncertainties require methods specific to nested sampling.

**nestcheck** is a Python package for analysing samples produced by nested sampling, and estimating uncertainty on posterior inferences. Most importantly, **nestcheck** contains fast and well-tested implementations of the error analysis methods introduced in (Higson, Handley, et al. 2018a) and the diagnostic tests and plots described in (???). The code has been profiled for computational efficiency and uses fast **numpy** functions and parallelisation with **concurrent.futures**. The diagnostic plots make use of the **matplotlib** (Hunter 2007) and **fgivenx** (Handley 2018) packages.

**nestcheck** can analyse samples from the popular **MultiNest** (Feroz and Hobson 2008; Feroz, Hobson, and Bridges 2008; Feroz et al. 2013) and **PolyChord** (W. J. Handley, Hobson, and Lasenby 2015a, 2015b) packages, and functions for loading samples from other software packages with different formats can easily be added. **nestcheck** is also compatible with samples produced by the dynamic nested sampling algorithm (Higson et al. 2017), and its functions for storing and manipulating nested sampling output are used by the **dyPolyChord** (Higson 2018a) and **perfectns** (Higson 2018c) dynamic nested sampling packages.

**nestcheck** is designed to allow nested sampling software users to quickly calculate results and uncertainty estimates, as well as to apply diagnostics for checking their software has explored the posterior correctly. It was used for the diagnostic tests and plots in (???), and for error analysis in (Higson et al. 2017) and (Higson, Handley, et al. 2018b). An earlier version of the code was used in the analysis of black hole mergers in (Chua et al. 2018). The source code for **nestcheck** has been archived to Zenodo (Higson 2018b).

## Acknowledgements

I am grateful to Will Handley, Anthony Lasenby and Mike Hobson for their help and advice.

## References

- Chua, Alvin J. K., Sonke Hee, Will J. Handley, Edward Higson, Christopher J. Moore, Jonathan R. Gair, Michael P. Hobson, and Anthony N. Lasenby. 2018. “Towards a framework for testing general relativity with extreme-mass-ratio-inspiral observations.” *Monthly Notices of the Royal Astronomical Society* 478 (1):28–40. <https://doi.org/10.1093/mnras/sty1079>.
- Feroz, F., and M. P. Hobson. 2008. “Multimodal nested sampling: An efficient and robust alternative to Markov Chain Monte Carlo methods for astronomical data analyses.” *Monthly Notices of the Royal Astronomical Society* 384 (2):449–63. <https://doi.org/10.1111/j.1365-2966.2007.12353.x>.
- Feroz, F., M. P. Hobson, and M. Bridges. 2008. “MultiNest: an efficient and robust Bayesian inference tool for cosmology and particle physics.” *Monthly Notices of the Royal Astronomical Society* 398 (4):1601–14. <https://doi.org/10.1111/j.1365-2966.2009.14548.x>.
- Feroz, F., M. P. Hobson, E. Cameron, and A. N. Pettitt. 2013. “Importance Nested Sampling and the MultiNest Algorithm.” *arXiv Preprint arXiv:1306.2144*.
- Handley, W. J., M. P. Hobson, and A. N. Lasenby. 2015a. “PolyChord: Nested sampling for cosmology.” *Monthly Notices of the Royal Astronomical Society: Letters* 450 (1):L61–L65. <https://doi.org/10.1093/mnrasl/slv047>.
- . 2015b. “PolyChord: next-generation nested sampling.” *Monthly Notices of the Royal Astronomical Society* 15:1–15. <https://doi.org/10.1093/mnras/stv1911>.
- Handley, Will. 2018. “Fgivenx.” <https://doi.org/10.5281/zenodo.1310715>.
- Higson, Edward. 2018a. “dyPolyChord: dynamic nested sampling with PolyChord.” <https://doi.org/10.5281/zenodo.1328175>.
- . 2018b. “Nestcheck: Error Analysis, Diagnostic Tests and Plots for Nested Sampling Calculations.” <https://doi.org/10.5281/zenodo.1329513>.
- . 2018c. “Perfectns: Dynamic and Standard Nested Sampling for Spherically Symmetric Likelihoods and Priors.” <https://doi.org/10.5281/zenodo.1327591>.
- Higson, Edward, Will Handley, Mike Hobson, and Anthony Lasenby. 2017. “Dynamic nested sampling : an improved algorithm for parameter estimation and evidence calculation.” *arXiv Preprint arXiv:1704.03459*. <https://arxiv.org/abs/1704.03459>.
- . 2018a. “Sampling errors in nested sampling parameter estimation.” *Bayesian Analysis* 13 (3):873–96. <https://doi.org/doi:10.1214/17-BA1075>.
- Higson, Edward, William Handley, Anthony Lasenby, and Mike Hobson. 2018b. “Bayesian Sparse Reconstruction: a brute-force approach to astronomical imaging and machine learning.” *In Preparation*.
- Hunter, John D. 2007. “Matplotlib: A 2D graphics environment.” *Computing in Science and Engineering* 9 (3):90–95.
- Skilling, John. 2006. “Nested sampling for general Bayesian computation.” *Bayesian Analysis* 1 (4):833–60. <https://doi.org/10.1214/06-BA127>.