

GridTest: testing and metrics collection for Python

Vanessa Sochat¹

¹ Stanford University Research Computing

DOI: [10.21105/joss.02284](https://doi.org/10.21105/joss.02284)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Bruce E. Wilson](#) ↗

Reviewers:

- [@cbrueffer](#)
- [@khinsen](#)

Submitted: 20 May 2020

Published: 05 July 2020

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Creating reproducible testing and parameterization is a consistent challenge in research because it is hard to do (Koteska, Pejov, & Mishev, 2015). Researchers often don't have the bandwidth to think about tests, and consequently, creating tools for this use case is often overlooked. GridTest ("GridTest on GitHub," 2020) is a library that specializes in generating parameter grids. The grids are most obviously used for testing, but can extend to other use cases. In the context of testing, GridTest makes it easy to discover functions, classes, and arguments for Python scripts or modules, and then generate a template to easily populate. Outside of testing, grids can be created that are version controlled, programatically defined with functions, and easy to interact with from the command line or Python interpreter. Grids can be used with tests that can further be parameterized and configured to collect metrics for each case run. Both grid and test specifications are stored in a simple YAML configuration that the library helps to generate, and features include interactive debugging, interactive report generation, and provided metrics (Python decorators) that can assist with research.

Background

While several scientific libraries (Beilsten-Edmands et al., 2020; Pedregosa et al., 2011) make it possible to generate parameter grids within code, they require a substantial list of numerical library dependencies that might be overkill for the user's needs, and further, they don't allow for representation of grids outside of the code. Additionally, these libraries do not natively allow for interactive debugging, collection of metrics around grids, or report generation. Another subset of grid generation libraries are specifically intended for hyperparameter tuning (Chollet & others, 2015; "Grid (hyperparameter) search — H2O 3.30.0.5 documentation," 2020; Koehrsen, 2018), and are thus packaged alongside machine learning libraries. While these libraries are rich and hugely useful for their intended purposes, none of them present a domain-agnostic, simple grid definition that can be defined outside of the programming language (e.g., R, Python) code that uses it. The landscape is missing a library that places grids alongside code, and can define them without needing it. GridTest offers this ability, and further, introduces a new paradigm that grids might be shared between code bases as their own entity, and are not required to be embedded within it.

Grids as First Class Citizens

Parameters always come as a second thought when writing tests, and this is why they are commonly applied as decorators. The author of this software realized that she might want to define just sets of parameters that expand into matrices that can be useful across many use cases. This makes the grids "first class citizens." For example, instead of a top to bottom script that loops over some set of datasets, parameters, and algorithms, you could define grids to generate each in a modular fashion. This is explained in detail for the [clustering grids](#) example derived from scikit-learn. As another example, you might just want to parameterize

some set of inputs to randomly generate a cohort. This example is detailed [in another tutorial here](#). The overall idea is simple. The current practice is generally to write parameterizations alongside code, whether that means nested for loops or decorators for testing. GridTest allows for this same kind of functionality, but storing the parameterization alongside the code and not embedded with it. This makes it easy to change grids or tests without touching the code.

Concepts

Testing

A **gridtest**: is one that is run over a grid of parameter settings. Each test can include a set of argument specifications, and optionally mapping these arguments to functions so they can be programatically defined. A grid can be inline to the test (if not used elsewhere) or defined globally and shared. For an example of command line usage, the reader is directed to the “[How does it work](#)” section in the Getting Started guide.

Parameterization

A **grid** is a global definition of a parameter matrix. You can define arguments, and optionally functions to run to be mapped to arguments. Grids are generated on demand, meaning when you iterate over a grid object, so that they are more efficient to use because we don't store a large list in memory. Grids can be put to many uses. You might share a repository that only defines grids that people can use across many different kinds of machine learning models, likely to collect metrics and compare different analysis strategies being used. An introduction to grids is available [here](#).

Metrics

A **metric** is a Python decorator that is paired with a test that will measure some attribute of a test. For example: - you might run a function across a grid of arguments, and then measure the time that each combination takes (the metric), and generate a report for inspection. - you might be doing text processing and having functions to parse text. Each function might be run over a grid of sentences and counts, and for each result, we want to count the number of unique words, and total words (metrics).

Metrics are fully described in the [metrics](#) section of the documentation.

Use Cases

GridTest has use cases well beyond testing, because parameterization is used widely across data science, and version control for reproducibility of those parameters is essential for reproducible, sustainable science. The following set of examples are good use cases.

1. Parameter Grids

GridTest extends the traditional definition (“`sklearn.model_selection.ParameterGrid` — scikit-learn 0.23.1 documentation,” 2020) of a grid to include:

- [generating random samples](#)
- [loading grids via a GridRunner](#) class separate from the application's Python code.
- generating grids as you go (meaning as an iterator)

- previewing grids on the command line before you use them
- generating content of grids via external functions, and optionally unwrapping list values


Grids are generated on demand for more efficient memory allocation, and can be extended to any use case that requires some combination of arguments, and optionally functions to run to be mapped to arguments. See the section on the concept of a grid for more detail.

2. Capturing Metrics

How long does your function take when you provide parameter X as one value, versus another? By way of allowing you to specify one or more metrics alongside tests, you can easily capture metrics (Python decorators to your functions to test) to output in an interactive report. For example, if we write a test that runs a machine learning algorithm across a grid of datasets and algorithms, we can easily add a metric to record the time that each takes, and save this result to a file. GridTest provides a standard set of [decorators](#) for ease of use, and the user is also free to write their own functions to collect metrics.

3. Generating Reports

If you need to save results to a data file (e.g., results.json) or generate an interactive report for GitHub pages, this is easy to do with running GridTest with the `--save` or `--save-web` flags. An example web report is shown in Figure 1. Any grid can also be exported to JSON for archiving in a repository or extension to other custom visualizations.



Module	Name	Success	Args	Raises	Result
script.multiply_sentence	script.multiply_sentence.0	true			He ran for the hills.
script	script.multiply_sentence.1	true			Skiddery-a rinky dinky dinky, skittery rinky doo.
script	script.multiply_sentence.2	true			You are my sunshine, my only sunshine.
script	script.multiply_sentence.3	true			He ran for the hills. He ran for the hills. He ran for the hills. He ran for the h
script	script.multiply_sentence.4	true			Skiddery-a rinky dinky dinky, skittery rinky doo. Skiddery-a rinky dinky dinky,
script	script.multiply_sentence.5	true			You are my sunshine, my only sunshine. You are my sunshine, my only sunshine. You
script	script.multiply_sentence.6	true			He ran for the hills. He ran for the hills. He ran for the hills. He ran for the h
script	script.multiply_sentence.7	true			Skiddery-a rinky dinky dinky, skittery rinky doo. Skiddery-a rinky dinky dinky,
script	script.multiply_sentence.8	true			You are my sunshine, my only sunshine. You are my sunshine, my only sunshine. You

Figure 1: Figure 1. An example GridTest web report

An interactive, live report is available to view [here](#), and more information about reports and export formats is provided [here](#). More domain-specific reports can be developed as requested.

4. Debugging

What programmer hasn't been in the scenario of running a group of tests, and then having some fail? What do you do in that case? You can start an interactive shell, import what you need, and try to reproduce, or you can turn up verbosity and add a bunch of print statements to figure out what is going on. GridTest makes this much easier with its `--interactive` mode, which will let you simply shell into an interpreter right before the function is run, and let you debug away. A detailed walkthrough of debugging is provided [here](#).

5. Running Reproducible Tests

When you write tests for a file, local, or system module, you store them in a YAML file that is stored alongside the code, and can be tested with CI. The YAML file can have grids of parameters defined so you can easily test many different combinations.

6. Knowing the tests to write

Whether you write tests as you go or at the end, you have to look back at your files to know the function names and arguments that need to be tested. GridTest solves this problem by way of discovery - give it a module name, a file name, or an entire directory with Python files, and it will generate a template for you to easily fill in that already includes arguments and functions.

Once you've written your tests, you can run GridTest with the `--check` feature to find newly added functions in your code. For more details about creating, checking, and updating tests, see the [testing](#) documentation.

In summary, GridTest:

1. Lets you define grids to be generated programmatically, version controlled, and used for multiple purposes
2. Allows measuring metrics alongside tests
3. Stores tests in a YAML file that can be stored in version control
4. Generates data exports and interactive reports for results
5. Provides an easy way to interactively debug
6. Helps you to discover the tests that you need to write, and creates a template to fill in
7. Makes it easy to define and interact with expanded parameter grids

Conclusion

GridTest aims to be a general tool for data scientists and research software engineers alike. If there is a need to create a collection of grids, regardless of being used for testing or another use case, GridTest can solve this problem. By way of saving to YAML, GridTest can represent grids separately from code. By way of providing JSON export with interactive web reports, GridTest can be used in a continuous integration setup to generate a report for some tests or metrics of interest. The author had amazing fun creating this library, and is excited for its potential generalizability to support many different kinds of research tasks. For more examples, tutorials, and details, see the official documentation at <https://vsoch.github.io/gridtest> ("GridTest," 2020).

References

- Beilsten-Edmands, J., Winter, G., Gildea, R., Parkhurst, J., Waterman, D., & Evans, G. (2020). Scaling diffraction data in the *DIALS* software package: algorithms and new approaches for multi-crystal scaling. *Acta Crystallographica Section D*, 76(4), 385–399. doi:[10.1107/S2059798320003198](https://doi.org/10.1107/S2059798320003198)
- Chollet, F., & others. (2015). Keras. GitHub. Retrieved from <https://github.com/fchollet/keras>
- Grid (hyperparameter) search — H2O 3.30.0.5 documentation. (2020). <https://docs.h2o.ai/h2o/latest-stable/h2o-docs/grid-search.html>.
- GridTest. (2020). <https://vsoch.github.io/gridtest>.

GridTest on GitHub. (2020). <https://github.com/vsoch/gridtest/>.

Koehrsen, W. (2018, July). Intro to model tuning: Grid and random search. <https://kaggle.com/willkoehrsen/intro-to-model-tuning-grid-and-random-search>.

Koteska, B., Pejov, L., & Mishev, A. (2015). Scientific software testing: A practical example. In *SQAMIA*.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., et al. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12, 2825–2830.

sklearn.model_selection.ParameterGrid — scikit-learn 0.23.1 documentation. (2020). https://scikit-learn.org/stable/modules/generated/sklearn.model_selection.ParameterGrid.html.