

DeepInverse: A Python package for solving imaging inverse problems with deep learning

Julián Tachella^{1*}, Matthieu Terris^{2*}, Samuel Hurault^{3*}, Andrew Wang^{4*}, Dongdong Chen⁵, Minh-Hai Nguyen⁸, Maxime Song¹⁴, Thomas Davies^{4,5}, Leo Davy¹, Jonathan Dong⁷, Paul Escande⁹, Johannes Hertrich¹⁵, Zhiyuan Hu⁷, Tobías I. Liaudat¹³, Nils Laurent⁶, Brett Levac¹², Mathurin Massias¹⁰, Thomas Moreau², Thibaut Modrzyk¹¹, Brayan Monroy⁶, Sebastian Neumayer¹⁶, Jérémy Scanvic¹, Florian Sarron⁸, Victor Sechaud¹, Georg Schramm¹⁷, Romain Vo¹, and Pierre Weiss⁸

¹ CNRS, ENS de Lyon, France ² Université Paris-Saclay, Inria, CEA, Palaiseau, France ³ CNRS, ENS Paris, PSL, France ⁴ University of Edinburgh, UK ⁵ Heriot-Watt University, Edinburgh, UK ⁶ Universidad Industrial de Santander, Bucaramanga, Colombia ⁷ EPFL, Lausanne, Switzerland ⁸ IRIT, CBI, CNRS, Université de Toulouse, France ⁹ IMT, CNRS, Université de Toulouse, France ¹⁰ Inria, ENS de Lyon, France ¹¹ INSA de Lyon, France ¹² University of Texas at Austin, USA ¹³ IRFU, CEA, Université Paris-Saclay, Gif-sur-Yvette, France ¹⁴ CNRS UAR 851, Université Paris-Saclay Orsay, France ¹⁵ Université Paris Dauphine - PSL, Paris, France ¹⁶ Chemnitz University of Technology, Chemnitz, Germany ¹⁷ Department of Imaging and Pathology, KU Leuven, Belgium * Corresponding author * These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Vissarion Fisikopoulos](#)

Reviewers:

- [@ScepticalRabbit](#)
- [@HectorMozo3110](#)

Submitted: 26 May 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

DeepInverse is an open-source PyTorch-based library for imaging inverse problems. DeepInverse implements all steps for image reconstruction, including efficient forward operators, defining and solving variational problems and designing and training advanced neural networks, for a wide set of domains (medical imaging, astronomical imaging, remote sensing, computational photography, compressed sensing and more).

Statement of Need

Deep neural networks have become ubiquitous in various imaging inverse problems. Despite the ever-increasing research effort, most learning-based algorithms are built from scratch, are hard to generalize beyond their specific training setting, and the reported results are often hard to reproduce. DeepInverse overcomes these limitations by providing a modular unified framework, leveraging the popular PyTorch deep learning library ([Paszke et al., 2019](#)). For our audience of researchers (experts in optimization, deep learning etc.), practitioners (biologists, physicists etc.) and imaging software engineers, DeepInverse is:

1. **Accelerating research** by enabling efficient testing, deployment and transfer of new ideas across imaging domains;
2. Enlarging the **adoption of deep learning in inverse problems** by lowering the entrance bar to new users;
3. Enhancing **research reproducibility** via a common modular framework of problems and algorithms.

To the best of our knowledge, DeepInverse is the only library with a strong focus on and a wide set of modern learning-based methods across domains. SCICO ([Balke et al., 2022](#))

and Pyxu (Simeoni et al., 2024) focus on optimization-based methods. CUQIpy (Riis et al., 2024) focuses on Bayesian uncertainty quantification. ASTRA (Van Aarle et al., 2016), pytomography (Polson et al., 2025), TIGRE (Biguri et al., 2025), ODL (Adler et al., 2018) and CIL (Jørgensen et al., 2021) focus on tomography, sigpy (Ong & Lustig, 2019) on magnetic resonance imaging, and PyLops (Ravasi & Vasconcelos, 2019) on certain linear operators. MATLAB libraries (Soubies et al., 2019) (Gazzola et al., 2019) are restricted to handcrafted methods without automatic differentiation.




Figure 1: Schematic of the modular DeepInverse framework.

Inverse Problems

Imaging inverse problems can be expressed as

$$y = N_{\sigma}(A_{\xi}(x)), \quad (1)$$

where $x \in \mathcal{X}$ is an image, $y \in \mathcal{Y}$ are the measurements, $A_{\xi}: \mathcal{X} \mapsto \mathcal{Y}$ is a deterministic (linear or non-linear) operator capturing the physics of the acquisition and $N_{\sigma}: \mathcal{Y} \mapsto \mathcal{Y}$ is a noise model parameterized by σ . The `physics module` provides a scalable and modular framework, writing the forward operation as `y = physics(x, **params)`, unifying the wide variety of forward operators across various domains.

The library crucially introduces optional physics params (ξ, σ) , allowing for advanced problems, including calibration, blind inverse problems (Debarnot & Weiss, 2024) (Chung, Kim, Kim, et al., 2023), co-design (Lazarus et al., 2019) (Nehme et al., 2020), and robust training (Gossard & Weiss, 2024) (Terris & Moreau, 2023).

The current implemented physics, noise models, parameters ξ and tools for manipulating them are enumerated in the [documentation](#).

Reconstruction Methods

DeepInverse unifies the wide variety of commonly-used imaging solvers in the literature, written as:

$$\hat{x} = R_{\theta}(y, A_{\xi}, \sigma) \quad (2)$$

where R_{θ} is a reconstruction algorithm with optional trainable parameters θ and \hat{x} is the reconstructed image, written as `x_hat = model(y, physics)`. The current library of algorithms is enumerated in the [documentation](#), categorized as:

- **Optimization-based** methods (Chambolle & Pock, 2016) solve

$$R_{\theta}(y, A_{\xi}, \sigma) \in \underset{x}{\operatorname{argmin}} f_{\sigma}(y, A_{\xi}(x)) + g(x). \quad (3)$$

The `optim module` implements classical data fidelity terms $f_\sigma: \mathcal{Y} \times \mathcal{Y} \mapsto \mathbb{R}$ and a variety of regularization priors $g: \mathcal{X} \mapsto \mathbb{R}$, including:

- Traditional explicit priors (Candès & Wakin, 2008);
- Learned regularizers (Zoran & Weiss, 2011) (Altekrüger et al., 2023);
- Plug-and-Play priors (Venkatakrishnan et al., 2013) using a pretrained denoiser D_σ (K. Zhang et al., 2021).

To solve these problems, `optim` includes:

- Classical algorithms (Dossal et al., 2024);
- Unfolded networks (Gregor & LeCun, 2010), that unroll a fixed number of iterations of an optimization algorithm and train the parameters end-to-end;
- Deep equilibrium methods (Bai et al., 2019) that implicitly differentiate the fixed point of the algorithm.

- **Sampling-based** methods defined by differential equations:

$$x_{t+1} \sim p(x_{t+1}|x_t, y, D_\sigma, A_\xi, \sigma) \text{ for } t = 0, \dots, T-1, \quad (4)$$

such that x_T is approximately sampled from the posterior $p(x|y)$. Sampling multiple times enables uncertainty quantification.

The `sampling module` implements generalized, modular frameworks for:

- Diffusion model posterior sampling (Chung, Kim, Mccann, et al., 2023) (Kawar et al., 2022) (Zhu et al., 2023);
- Langevin-type algorithms (Laumont et al., 2022) (Pereyra et al., 2020) that sample using Markov Chain Monte Carlo.

- **Non-iterative:** The `models module` implements:

- Artifact removal models $R_\theta(y, A_\xi, \sigma) = D_\sigma(A_\xi^\top y)$, which simply backproject y to the image domain and apply an image-to-image denoiser D_σ (Jin et al., 2017);
- Conditional/unconditional generative networks (Bora et al., 2018) (Bendel et al., 2023) (Ulyanov et al., 2018) that add a latent z to a generator $R_\theta(y, z): \mathcal{Y} \times \mathcal{Z} \mapsto \mathcal{X}$;
- Foundation models (Terris et al., 2025), trained end-to-end across a wide variety of (A_ξ, N_σ) , and can be finetuned to new problems.

Training

Reconstruction networks R_θ can be trained using the modular `Trainer class`.

Losses

The `loss module` framework unifies training loss functions that are widely used across various domains. Losses are written as `loss(x_hat, x, y, physics, model)` and are enumerated in the [documentation](#):

- Supervised loss between x and y ;
- Self-supervised losses which only use y (Yaman et al., 2020) (Wang & Davies, 2025);
- Network regularization losses (Pesquet et al., 2021);
- Adversarial losses (Bora et al., 2017) (Bora et al., 2018).

The `transform module` implements geometric image transforms for data augmentation and equivariance (Chen et al., 2023) (Wang & Davies, 2024).

108 Datasets

109 The [datasets module](#) implements a variety of domain-specific datasets that return ground-
110 truth and measurements pairs $\{(x_i, y_i)\}_{i=1}^N$ and optional parameters ξ_i , and allows simulating
111 paired datasets given $\{x_i\}_{i=1}^N$ and physics A_{ξ_i} .

112 Evaluation

113 The [metric module](#) provides metrics for evaluating reconstruction methods. These are written
114 as `m = metric(x_hat, x)` (full-reference), or `m = metric(x_hat)` (no-reference) ([Yeganeh &](#)
115 [Wang, 2012](#)), including distortion ([R. Zhang et al., 2018](#)) and perceptual ([Blau & Michaeli,](#)
116 [2018](#)) metrics.

117 Philosophy

118 Coding Practices

119 DeepInverse is written in Python following modern test-driven practices. The code is unit-,
120 integration- and performance-tested using `pytest` and verified using `codecov`, and is compliant
121 with PEP8 using `black`. We adopt an object-oriented framework where base classes provide
122 abstract functionality and interfaces, subclasses provide specific method implementations or
123 special cases, reducing code duplication, facilitating users to implement new or specialized
124 functionality while inheriting existing methods.

125 Documentation

126 The library provides a [user guide](#), which also serves as a tutorial on computational imaging,
127 [quickstart](#) and in-depth [examples](#) for all levels of user, and individual [API documentation](#) for
128 classes. The documentation is generated using Sphinx and Sphinx-Gallery ([Najera et al., 2023](#)),
129 tested using `doctest`, and uses consistent mathematical notation throughout.

130 Perspectives

131 DeepInverse is a dynamic and evolving project and this paper is merely a snapshot of ongoing
132 progress. The community is continuously contributing more methods reflecting state-of-the-
133 art in imaging with deep learning, addressing the needs and interests of researchers and
134 practitioners.

135 Acknowledgements

136 J. Tachella acknowledges support by the French ANR grant UNLIP (ANR-23-CE23-0013) and
137 the CNRS PNRIA DeepInverse project. M. Terris acknowledges support by the BrAIN grant
138 (ANR-20-CHIA-0016). F. Sarron, P. Weiss, M.H. Nguyen were supported by ANR Micro-Blind
139 ANR-21-CE48-0008. T. Moreau was supported by the ExaDoST project under NumPEX
140 PEPR (ANR-22-EXNU-0004). J. Hertrich is supported by DFG (project 530824055). Z. Hu
141 acknowledges funding from the Swiss National Science Foundation (grant PZ00P2_216211). T.
142 Davies is supported by UKRI EPSRC (grants EP/V006134/1, EP/V006177/1). S. Neumayer
143 acknowledges funding from DFG (project 543939932). We thank the [BASP Laboratory at](#)
144 [Heriot-Watt University](#) for insightful discussions and contributions to the radioastronomy appli-
145 cation. The authors acknowledge the Jean-Zay HPC (GENCI-IDRIS grants 2021-AD011012210,
146 2024-AD011015191).

References

- Adler, J., Kohr, H., Ringh, A., Moosmann, J., Sbanert, Ehrhardt, M. J., Lee, G. R., Niinimäki, B. G., Verdier, O., Karlsson, J., Zickert, Palenstijn, W. J., Öktem, O., Chen, C., Loarca, H. A., & Lohmann, M. (2018). *Odlgroup/odl: ODL 0.7.0* (Version v0.7.0). Zenodo. <https://doi.org/10.5281/zenodo.1442734>
- Altekrüger, F., Denker, A., Hagemann, P., Hertrich, J., Maass, P., & Steidl, G. (2023). PatchNR: Learning from very few images by patch normalizing flow regularization. *Inverse Problems*, 39(6), 064006. <https://doi.org/10.1088/1361-6420/acce5e>
- Bai, S., Kolter, J. Z., & Koltun, V. (2019). Deep equilibrium models. *Advances in Neural Information Processing Systems*, 32. <https://doi.org/10.48550/arXiv.1909.01377>
- Balke, T., Davis, F., Garcia-Cardona, C., Majee, S., McCann, M., Pfister, L., & Wohlberg, B. (2022). Scientific computational imaging code (SCICO). *Journal of Open Source Software*, 7(78), 4722. <https://doi.org/10.21105/joss.04722>
- Bendel, M., Ahmad, R., & Schniter, P. (2023). A regularized conditional GAN for posterior sampling in image recovery problems. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, & S. Levine (Eds.), *Advances in neural information processing systems* (Vol. 36, pp. 68673–68684). Curran Associates, Inc. <https://doi.org/10.48550/arXiv.2210.13389>
- Biguri, A., Sadakane, T., Lindroos, R., Liu, Y., Landman, M. S., Du, Y., Lohvithee, M., Kaser, S., Hatamikia, S., Bryll, R., & others. (2025). TIGRE v3: Efficient and easy to use iterative computed tomographic reconstruction toolbox for real datasets. *Engineering Research Express*, 7(1), 015011. <https://doi.org/10.1088/2631-8695/adbb3a>
- Blau, Y., & Michaeli, T. (2018). The perception-distortion tradeoff. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 6228–6237. <https://doi.org/10.1109/CVPR.2018.00652>
- Bora, A., Jalal, A., Price, E., & Dimakis, A. G. (2017). Compressed sensing using generative models. *International Conference on Machine Learning*, 537–546. <https://doi.org/10.48550/arXiv.1703.03208>
- Bora, A., Price, E., & Dimakis, A. G. (2018). AmbientGAN: Generative models from lossy measurements. *International Conference on Learning Representations*. <https://openreview.net/forum?id=Hy7fDog0b>
- Candès, E. J., & Wakin, M. B. (2008). An introduction to compressive sampling. *IEEE Signal Processing Magazine*, 25(2), 21–30. <https://doi.org/10.1109/MSP.2007.914731>
- Chambolle, A., & Pock, T. (2016). An introduction to continuous optimization for imaging. *Acta Numerica*, 25, 161–319. <https://doi.org/10.1017/s096249291600009x>
- Chen, D., Davies, M., Ehrhardt, M. J., Schönlieb, C.-B., Sherry, F., & Tachella, J. (2023). Imaging With Equivariant Deep Learning: From unrolled network design to fully unsupervised learning. *IEEE Signal Processing Magazine*, 40, 134–147. <https://doi.org/10.1109/MSP.2022.3205430>
- Chung, H., Kim, J., Kim, S., & Ye, J. C. (2023). Parallel diffusion models of operator and image for blind inverse problems. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 6059–6069. <https://doi.org/10.1109/cvpr52729.2023.00587>
- Chung, H., Kim, J., McCann, M. T., Klasky, M. L., & Ye, J. C. (2023). Diffusion posterior sampling for general noisy inverse problems. *The Eleventh International Conference on Learning Representations*. <https://doi.org/10.48550/arXiv.2209.14687>
- Debarnot, V., & Weiss, P. (2024). Deep-blur: Blind identification and deblurring with convolutional neural networks. *Biological Imaging*, 4, e13. <https://doi.org/10.1017/s2633903x24000096>

- 194 Dossal, C., Hurault, S., & Papadakis, N. (2024). Optimization with first order algorithms.
195 *arXiv Preprint arXiv:2410.19506*. <https://doi.org/10.48550/arXiv.2410.19506>
- 196 Gazzola, S., Hansen, P. C., & Nagy, J. G. (2019). IR tools: A MATLAB package of iterative
197 regularization methods and large-scale test problems. *Numerical Algorithms*, 81(3), 773–811.
198 <https://doi.org/10.1007/s11075-018-0570-7>
- 199 Gossard, A., & Weiss, P. (2024). Training adaptive reconstruction networks for blind inverse
200 problems. *SIAM Journal on Imaging Sciences*, 17(2), 1314–1346. <https://doi.org/10.1137/23m1545628>
- 202 Gregor, K., & LeCun, Y. (2010). Learning fast approximations of sparse coding. *Proceedings
203 of the 27th International Conference on International Conference on Machine Learning*,
204 399–406. <https://doi.org/10.5555/3104322.3104374>
- 205 Jin, K. H., McCann, M. T., Froustey, E., & Unser, M. (2017). Deep convolutional neural
206 network for inverse problems in imaging. *IEEE Transactions on Image Processing*, 26(9),
207 4509–4522. <https://doi.org/10.1109/TIP.2017.2713099>
- 208 Jørgensen, J. S., Ametova, E., Burca, G., Fardell, G., Papoutsellis, E., Pasca, E., Thielemans,
209 K., Turner, M., Warr, R., Lionheart, W. R., & others. (2021). Core Imaging Library-part I:
210 A versatile python framework for tomographic imaging. *Philosophical Transactions of the
211 Royal Society A*, 379(2204), 20200192. <https://doi.org/10.1098/rsta.2020.0192>
- 212 Kawar, B., Elad, M., Ermon, S., & Song, J. (2022). Denoising diffusion restoration models.
213 *Advances in Neural Information Processing Systems*, 35, 23593–23606. <https://doi.org/10.48550/arXiv.2201.11793>
- 214 Laumont, R., Bortoli, V. D., Almansa, A., Delon, J., Durmus, A., & Pereyra, M. (2022).
215 Bayesian imaging using plug & play priors: When Langevin meets Tweedie. *SIAM Journal
216 on Imaging Sciences*, 15(2), 701–737. <https://doi.org/10.1137/21M1406349>
- 218 Lazarus, C., Weiss, P., Chauffert, N., Mauconduit, F., El Gueddari, L., Destrieux, C., Zemmoura,
219 I., Vignaud, A., & Ciuciu, P. (2019). SPARKLING: Variable-density k-space filling curves
220 for accelerated T2*-weighted MRI. *Magnetic Resonance in Medicine*, 81(6), 3643–3661.
221 <https://doi.org/10.1002/mrm.27678>
- 222 Najera, O., Larson, E., Liu, L., Esteve, L., Varoquaux, G., Grobler, J., Andrade, E. S. de,
223 Holdgraf, C., Gramfort, A., Jas, M., Nothman, J., Rehberg, S., Grisel, O., Varoquaux,
224 N., Hiscocks, S., alexis, Gouillart, E., Hoffmann, T., Lee, A., ... Kunzmann, P. (2023).
225 *Sphinx-gallery/sphinx-gallery: v0.12.2* (Version v0.12.2). Zenodo. <https://doi.org/10.5281/zenodo.7716999>
- 227 Nehme, E., Freedman, D., Gordon, R., Ferdman, B., Weiss, L. E., Alalouf, O., Naor, T.,
228 Orange, R., Michaeli, T., & Shechtman, Y. (2020). DeepSTORM3D: Dense 3D localization
229 microscopy and PSF design by deep learning. *Nature Methods*, 17(7), 734–740. <https://doi.org/10.1038/s41592-020-0853-5>
- 231 Ong, F., & Lustig, M. (2019). *SigPy: A python package for high performance iterative
232 reconstruction*. ISMRM. <https://archive.ismrm.org/2019/4819.html>
- 233 Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin,
234 Z., Gimelshein, N., Antiga, L., & others. (2019). PyTorch: An imperative style, high-
235 performance deep learning library. *Advances in Neural Information Processing Systems*, 32.
236 <https://doi.org/10.48550/arXiv.1912.01703>
- 237 Pereyra, M., Miele, L. V., & Zygalakis, K. C. (2020). Accelerating proximal markov chain
238 monte carlo by using an explicit stabilized method. *SIAM Journal on Imaging Sciences*,
239 13(2), 905–935. <https://doi.org/10.1137/19M1283719>
- 240 Pesquet, J.-C., Repetti, A., Terris, M., & Wiaux, Y. (2021). Learning maximally monotone
241 operators for image recovery. *SIAM Journal on Imaging Sciences*, 14(3), 1206–1237.

- 242 <https://doi.org/10.1137/20m1387961>
- 243 Polson, L. A., Fedrigo, R., Li, C., Sabouri, M., Dzikunu, O., Ahamed, S., Karakatsanis, N.,
244 Kurkowska, S., Sheikhzadeh, P., Esquinas, P., & others. (2025). Pytomography: A python
245 library for medical image reconstruction. *SoftwareX*, 29, 102020. [https://doi.org/10.2139/](https://doi.org/10.2139/ssrn.4865134)
246 [ssrn.4865134](https://doi.org/10.2139/ssrn.4865134)
- 247 Ravasi, M., & Vasconcelos, I. (2019). PyLops—a linear-operator python library for large scale
248 optimization. *arXiv Preprint arXiv:1907.12349*. [https://doi.org/10.48550/arXiv.1907.](https://doi.org/10.48550/arXiv.1907.12349)
249 [12349](https://doi.org/10.48550/arXiv.1907.12349)
- 250 Riis, N. A., Alghamdi, A. M., Uribe, F., Christensen, S. L., Afkham, B. M., Hansen, P.
251 C., & Jørgensen, J. S. (2024). CUQIpy: I. Computational uncertainty quantification for
252 inverse problems in python. *Inverse Problems*, 40(4), 045009. [https://doi.org/10.1088/](https://doi.org/10.1088/1361-6420/ad22e7)
253 [1361-6420/ad22e7](https://doi.org/10.1088/1361-6420/ad22e7)
- 254 Simeoni, M., Kashani, S., Rué-Queralt, J., & Developers, P. (2024). *Pyxu-org/pyxu: pyxu*.
255 Zenodo. <https://doi.org/10.5281/zenodo.4486431>
- 256 Soubies, E., Soulez, F., McCann, M. T., Pham, T., Donati, L., Debarre, T., Sage, D., & Unser,
257 M. (2019). Pocket guide to solve inverse problems with GlobalBiolm. *Inverse Problems*,
258 35(10), 104006. <https://doi.org/10.1088/1361-6420/ab2ae9>
- 259 Terris, M., Hurault, S., Song, M., & Tachella, J. (2025). Reconstruct anything model: A
260 lightweight foundation model for computational imaging. *arXiv Preprint arXiv:2503.08915*.
261 <https://doi.org/10.48550/arXiv.2503.08915>
- 262 Terris, M., & Moreau, T. (2023). Meta-prior: Meta learning for adaptive inverse problem
263 solvers. *arXiv Preprint arXiv:2311.18710*. <https://doi.org/10.48550/arXiv.2311.18710>
- 264 Ulyanov, D., Vedaldi, A., & Lempitsky, V. (2018). Deep image prior. *Proceedings of*
265 *the IEEE Conference on Computer Vision and Pattern Recognition*, 9446–9454. <https://doi.org/10.1109/CVPR.2018.00984>
266 <https://doi.org/10.1109/CVPR.2018.00984>
- 267 Van Aarle, W., Palenstijn, W. J., Cant, J., Janssens, E., Bleichrodt, F., Dabrovolski, A.,
268 De Beenhouwer, J., Joost Batenburg, K., & Sijbers, J. (2016). Fast and flexible x-ray
269 tomography using the ASTRA toolbox. *Optics Express*, 24(22), 25129–25147. <https://doi.org/10.1364/oe.24.025129>
270 <https://doi.org/10.1364/oe.24.025129>
- 271 Venkatakrishnan, S. V., Bouman, C. A., & Wohlberg, B. (2013). Plug-and-play priors for
272 model based reconstruction. *2013 IEEE Global Conference on Signal and Information*
273 *Processing*, 945–948. <https://doi.org/10.1109/globalsip.2013.6737048>
- 274 Wang, A., & Davies, M. (2024). Perspective-equivariance for unsupervised imaging with
275 camera geometry. *IEEE/CVF European Conference on Computer Vision (ECCV) Workshop*
276 *on Traditional Computer Vision in the Age of Deep Learning*. [https://doi.org/10.1007/](https://doi.org/10.1007/978-3-031-91585-7_8)
277 [978-3-031-91585-7_8](https://doi.org/10.1007/978-3-031-91585-7_8)
- 278 Wang, A., & Davies, M. (2025). Benchmarking self-supervised methods for accelerated MRI
279 reconstruction. *arXiv Preprint arXiv:2502.14009*. [https://doi.org/10.48550/arXiv.2502.](https://doi.org/10.48550/arXiv.2502.14009)
280 [14009](https://doi.org/10.48550/arXiv.2502.14009)
- 281 Yaman, B., Hosseini, S. A. H., Moeller, S., Ellermann, J., Uğurbil, K., & Akçakaya, M.
282 (2020). Self-supervised learning of physics-guided reconstruction neural networks without
283 fully sampled reference data. *Magnetic Resonance in Medicine*, 84(6), 3172–3191. <https://doi.org/10.1002/mrm.28378>
284 <https://doi.org/10.1002/mrm.28378>
- 285 Yeganeh, H., & Wang, Z. (2012). Objective quality assessment of tone-mapped images. *IEEE*
286 *Transactions on Image Processing*, 22(2), 657–667. [https://doi.org/10.1109/TIP.2012.](https://doi.org/10.1109/TIP.2012.2221725)
287 [2221725](https://doi.org/10.1109/TIP.2012.2221725)
- 288 Zhang, K., Li, Y., Zuo, W., Zhang, L., Van Gool, L., & Timofte, R. (2021). Plug-and-play

- 289 image restoration with deep denoiser prior. *IEEE Transactions on Pattern Analysis and*
290 *Machine Intelligence*, 44(10), 6360–6376. <https://doi.org/10.1109/TPAMI.2021.3088914>
- 291 Zhang, R., Isola, P., Efros, A. A., Shechtman, E., & Wang, O. (2018). The unreasonable
292 effectiveness of deep features as a perceptual metric. *Proceedings of the IEEE Conference*
293 *on Computer Vision and Pattern Recognition*, 586–595. [https://doi.org/10.1109/cvpr.](https://doi.org/10.1109/cvpr.2018.00068)
294 [2018.00068](https://doi.org/10.1109/cvpr.2018.00068)
- 295 Zhu, Y., Zhang, K., Liang, J., Cao, J., Wen, B., Timofte, R., & Van Gool, L. (2023). Denoising
296 diffusion models for plug-and-play image restoration. *Proceedings of the IEEE/CVF*
297 *Conference on Computer Vision and Pattern Recognition*, 1219–1229. [https://doi.org/10.](https://doi.org/10.1109/cvprw59228.2023.00129)
298 [1109/cvprw59228.2023.00129](https://doi.org/10.1109/cvprw59228.2023.00129)
- 299 Zoran, D., & Weiss, Y. (2011). From learning models of natural image patches to whole
300 image restoration. *2011 International Conference on Computer Vision*, 479–486. [https:](https://doi.org/10.1109/ICCV.2011.6126278)
301 [//doi.org/10.1109/ICCV.2011.6126278](https://doi.org/10.1109/ICCV.2011.6126278)

DRAFT