

kdensity: An R package for kernel density estimation with parametric starts and asymmetric kernels

Jonas Moss¹ and Martin Tveten¹

1 University of Oslo

DOI: 10.21105/joss.01566

Software

■ Review 🗗

■ Repository 🗗

■ Archive 🗗

Submitted: 11 July 2019 Published: 01 October 2019

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC-BY).

Summary

Kernel density estimation (Silverman, 2018) is a popular method for non-parametric density estimation based on placing kernels on each data point. Hjort & Glad (1995) extended kernel density estimation with *parametric starts*. The parametric start is a parametric density that is multiplied with the kernel estimate. When the data-generating density is reasonably close to the parametric start density, kernel density estimation with that parametric start will outperform ordinary kernel density estimation.

Asymmetric kernels are useful for estimating densities on the half-open interval $[0,\infty)$ and bounded intervals such as [0,1]. On such intervals symmetric kernels are prone to serious boundary bias that should be corrected (Marron & Ruppert, 1994). Asymmetric kernels are designed to avoid boundary bias.

kdensity is an R package (R Core Team, 2019) to calculate and display kernel density estimates using non-parametric starts and potentially asymmetric kernels. In addition to the classical symmetric kernels, kdensity supports the following asymmetric kernels: For the unit interval, the Gaussian copula kernel of M. Jones & Henderson (2007) and the beta kernels of Chen (1999) are supported. On the half-open interval the gamma kernel of Chen (2000) is supported. The supported non-parametric starts include the normal, Laplace, Gumbel, exponential, gamma, log-normal, inverse Gaussian, Weibull, Beta, and Kumaraswamy densities. The parameters of all parametric starts are estimated using maximum likelihood. The implemented bandwidth selectors are the classical bandwidth selectors from stats, unbiased cross-validation, the Hermite polynomial method from Hjort & Glad (1995), and the tailored bandwidth selector for the Gaussian copula method of M. Jones & Henderson (2007). User defined parametric starts, kernels and bandwidth selectors are also supported.

Several R packages deal with kernel estimation, see Deng & Wickham (2011) for an overview. While no other R package handles density estimation with parametric starts, several packages supports methods that handle boundary bias. Hu & Scarrott (2018) provides a variety of boundary bias correction methods in the bckden functions. Nagler & Vatter (2019) corrects for boundary bias using probit or logarithmically transformed local polynomial kernel density estimation. A. T. Jones, Nguyen, & McLachlan (2018) corrects for boundary bias on the half line using a logarithmic transform. Duong (2019) supports boundary correction through the kde.boundary function, while Wansouwé, Somé, & Kokonendji (2015) corrects for boundary bias using asymmetric kernels.

The following example uses the airquality data set from the built-in R package data sets. Since the data is positive we use Chen's gamma kernel. As the data is likely to be better approximated by a gamma distribution than a uniform distribution, we use the gamma parametric start. The plotted density is in figure 1, where the gamma distribution with parameters estimated by maximum likelihood is in red and the ordinary kernel density estimate in blue. Notice the boundary bias of the ordinary kernel density estimator.



```
# install.packages("kdensity")
library("kdensity")
kde = kdensity(airquality$Wind, start = "gamma", kernel = "gamma")
plot(kde, main = "Wind speed (mph)")
lines(kde, plot_start = TRUE, col = "red")
lines(density(airquality$Wind, adjust = 2), col = "blue")
rug(airquality$Wind)
```

Wind speed (mph)




Figure 1: The *airquality* data set. Kernel density estimate in black and estimated gamma distribution in red.

References

Chen, S. X. (1999). Beta kernel estimators for density functions. *Computational Statistics & Data Analysis*, 31(2), 131–145. doi:doi:10.1016/S0167-9473(99)00010-9

Chen, S. X. (2000). Probability density function estimation using gamma kernels. *Annals of the Institute of Statistical Mathematics*, 52(3), 471–480. doi:doi:10.1023/A:1004165218295

Deng, H., & Wickham, H. (2011). Density estimation in r. Retrieved from http://vita.had.co.nz/papers/density-estimation.pdf

Duong, T. (2019). *Ks: Kernel smoothing*. Retrieved from https://CRAN.R-project.org/package=ks

Hjort, N. L., & Glad, I. K. (1995). Nonparametric density estimation with a parametric start. *The Annals of Statistics*, 882–904. doi:doi:10.1214/aos/1176324627

Hu, Y., & Scarrott, C. (2018). evmix: An R package for extreme value mixture modeling, threshold estimation and boundary corrected kernel density estimation. *Journal of Statistical Software*, *84*(5), 1–27. doi:10.18637/jss.v084.i05



Jones, A. T., Nguyen, H. D., & McLachlan, G. J. (2018). LogKDE: Log-transformed kernel density estimation. *Journal of Open Source Software*, 3(28), 870. doi:10.21105/joss.00870

Jones, M., & Henderson, D. (2007). Kernel-type density estimation on the unit interval. *Biometrika*, 94(4), 977–984. doi:doi:10.1093/biomet/asm068

Marron, J. S., & Ruppert, D. (1994). Transformations to reduce boundary bias in kernel density estimation. *Journal of the Royal Statistical Society: Series B (Methodological)*, *56*(4), 653–671. doi:doi:10.2307/2346189

Nagler, T., & Vatter, T. (2019). *Kde1d: Univariate kernel density estimation*. Retrieved from https://CRAN.R-project.org/package=kde1d

R Core Team. (2019). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from https://www.R-project.org/

Silverman, B. W. (2018). *Density estimation for statistics and data analysis*. Routledge. doi:doi:10.1201/9781315140919

Wansouwé, W. E., Somé, S. M., & Kokonendji, C. C. (2015). *Ake: Associated kernel estimations*. Retrieved from https://CRAN.R-project.org/package=Ake