

oxDNA: coarse-grained simulations of nucleic acids made simple

Erik Poppleton¹, Michael Matthies¹, Debesh Mandal², Flavio Romano³, Petr Šulc¹, and Lorenzo Rovigatti^{4,5}✉

¹ School of Molecular Sciences and Center for Molecular Design and Biomimetics, The Biodesign Institute, Arizona State University, USA ² Department of Materials, Imperial College London, UK ³ Dipartimento di Scienze Molecolari e Nanosistemi, Università Ca Foscari di Venezia, Italy ⁴ Department of Physics, Sapienza University of Rome, Italy ⁵ CNR-ISC UoS Sapienza, Rome, Italy ✉ Corresponding author

DOI: [10.21105/joss.04693](https://doi.org/10.21105/joss.04693)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Antonia Mey](#) ↗ 

Reviewers:

- [@ptmerz](#)
- [@degiacon](#)

Submitted: 07 July 2022

Published: 20 January 2023

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

The fields of DNA and RNA nanotechnology have progressed from pioneering, proof-of-principle experiments to fully-fledged applications in material science, biology and medicine. These applications exploit the intrinsic programmability of nucleic acids to generate nano- and even micro-scale structures with tailored properties. However, the design of the DNA/RNA sequences that self-assemble into a desired structure is not straightforward and often relies on expensive trial-and-error experimental protocols. A complementary approach is provided by computer simulations, which can model biomacromolecules at different levels of detail, ranging from atomistic to continuous, and can be leveraged to investigate the whole range of time- and length-scales relevant for applications. Here we present oxDNA, a software package that has been designed to efficiently run coarse-grained simulations of DNA and RNA and also features an analysis suite aimed at post-processing the analysis of oxDNA/oxRNA trajectories.

Statement of need

The simulation of nucleic acids has become an important tool from the fundamental point of view to understand how these biomacromolecules behave and, from an application standpoint, to predict their behaviour under specific conditions ([Dans et al., 2016](#)). The ideal model for each specific problem, and therefore the level of detail with which DNA and RNA are to be described, depends on the time and length scales of interest: at one end of the spectrum there is quantum chemistry modelling, which can be used to probe the microscopic properties of a small number of nucleotides ([Šponer et al., 2008](#)), while at the other end there are continuum descriptions based on polymer theories such as the worm-like chain model ([Nomidis et al., 2019](#)) that can be used to study the behaviour of long DNA strands. A middle road is provided by coarse-grained models that describe nucleic acids at the nucleotide level ([Doye et al., 2013](#)). At this level of detail the oxDNA, oxDNA2 and oxRNA models has become popular choices to investigate the dynamics, thermodynamics and self-assembly behaviour of DNA and RNA systems ([Sengar et al., 2021](#); [Šulc et al., 2014](#)), and have been used in more than a [hundred publications](#) to date.

Functionality

Here we present an updated version of the oxDNA code, an efficient, multi-technique simulation package written in C++ and specifically developed to carry out simulations of coarse-grained

nucleic acid systems described with the oxDNA and oxRNA models. The package, which is named after the original oxDNA model, can perform both molecular dynamics (MD) and Monte Carlo (MC) simulations. MD simulations can be run on single CPUs or single CUDA-enabled GPUs, while MC simulations, which can only be run serially, can exploit the Virtual Move Monte Carlo algorithm (Whitelam & Geissler, 2007) to greatly speed-up equilibration and sampling, and Umbrella Sampling biasing to efficiently obtain free-energy profiles. The package also features a Forward-Flux Sampling interface to study the kinetics of rare events (Allen et al., 2009), and makes it possible to alter the behaviour of the systems by adding *external forces* that can be used, for instance, to pull on or apply torques to strands or confine nucleotides within semi-planes or spheres.

The package can also be used to compute nucleic-acid-related quantities such as the energy due to hydrogen bonding or stacking, the distance between groups of nucleotides, the list of hydrogen-bonded nucleotides or of over-stretched bonds, and much more. The analysis can be performed while the simulation is running or on trajectory files produced by finished simulations.

The version of the code we present here is hosted on GitHub and has been modernized with respect to earlier versions (see e.g. (Rovigatti et al., 2015)) to exploit the C++-14 and CUDA 11 standards. This new version also includes oxpy, a Python library which makes it possible to control the behavior of the simulation using Python scripts, as well as examples that demonstrate how to leverage oxpy to write backends to run replica-exchange (Sugita & Okamoto, 1999) and well-tempered metadynamics (Barducci et al., 2008) simulations which are popular techniques in modern molecular dynamics to improve sampling efficiency.

The simulation engine is complemented by an updated version of oxDNA_analysis_tools (oat) (Poppleton et al., 2020), a Python library aimed at facilitating the analysis of oxDNA/oxRNA trajectories. Oat provides numerous common simulation trajectory analysis tools including alignment, mean structures, subsetting trajectories, distances between nucleotides, interduplex angles, and comparison in hydrogen bonding patterns between the trajectory and an idealized structure. Oat was previously published as a standalone Python package (Poppleton et al., 2020), however, since the initial publication, substantial improvements have been made including a new Cython-based random access file parser which accelerated computation of mean structures by more than 10x, and close integration with oxpy, which sped up and simplified calculation of nucleotide interactions by more than 100x. Oat was developed with the intention of facilitating other, more specific, analysis tasks. The file readers and utility functions are available for import into users' Python projects and the scripts themselves are well-commented to serve as examples for users to extend them for their own needs.

Related software

Molecular dynamics simulations of oxDNA and oxRNA can also be performed with the LAMMPS software package, whose efficient parallel-computing algorithms make it possible to simulate large systems on HPC clusters (Henrich et al., 2018). However, at the moment it lacks GPU support, it cannot be used to build free-energy profiles by biasing discrete reaction coordinates (e.g. number of correct basepairs) and there are no tools to analyse LAMMPS-generated trajectories such as oat (Poppleton et al., 2020) or oxview (Bohlin et al., 2022). In addition, the LAMMPS engine supports many more (often oxDNA-unrelated) options, which may make it harder to correctly setup oxDNA simulations compared to oxDNA. Therefore, the oxDNA simulation package presented here complements the LAMMPS version, which also bears the "oxdna" name, rather than competing with it.

Finally, we note that there are many software packages that either use oxDNA or take as input, output or manipulate configurations generated with the oxDNA package. The list comprises MrDNA (Maffeo & Aksimentiev, 2020), Adenita (Llano et al., 2020), TacoxDNA (Suma et al., 2019), oxDNA.org (Poppleton et al., 2021), scadnano (Doty et al., 2020), MagicDNA (Huang

et al., 2021) and ENSnano (Levy & Schabanel, 2021).

Acknowledgements

We acknowledge contributions from R. Harrison, C. Matek, F. Randisi, W. Smith and Benedict E. K. Snodin. LR acknowledges support from the CINECA award under the ISCRA initiative for the availability of high performance computing resources and support (Iskra B “AssoPoN”), PS acknowledges support from ONR grant no N000142012094, and DM acknowledges support from the Engineering and Physical Sciences Research Council [grant number EP/N509486/1].

References

- Allen, R. J., Valeriani, C., & Wolde, P. R. ten. (2009). Forward flux sampling for rare event simulations. *Journal of Physics: Condensed Matter*, 21(46), 463102. <https://doi.org/10.1088/0953-8984/21/46/463102>
- Barducci, A., Bussi, G., & Parrinello, M. (2008). Well-tempered metadynamics: A smoothly converging and tunable free-energy method. *Phys. Rev. Lett.*, 100, 020603. <https://doi.org/10.1103/PhysRevLett.100.020603>
- Bohlin, J., Matthies, M., Poppleton, E., Procyk, J., Mallya, A., Yan, H., & Šulc, P. (2022). Design and simulation of DNA, RNA and hybrid protein–nucleic acid nanostructures with oxView. *Nature Protocols*, 1–27.
- Dans, P. D., Walther, J., Gómez, H., & Orozco, M. (2016). Multiscale simulation of DNA. *Current Opinion in Structural Biology*, 37, 29–45. <https://doi.org/10.1016/j.sbi.2015.11.011>
- Doty, D., Lee, B. L., & Stérin, T. (2020). Scadnano: A browser-based, scriptable tool for designing DNA nanostructures. In C. Geary & M. J. Patitz (Eds.), *DNA 2020: Proceedings of the 26th international meeting on DNA computing and molecular programming* (Vol. 174, pp. 9:1–9:17). Schloss Dagstuhl–Leibniz-Zentrum für Informatik. <https://doi.org/10.4230/LIPIcs.DNA.2020.9>
- Doye, J. P. K., Ouldrige, T. E., Louis, A. A., Romano, F., Šulc, P., Matek, C., Snodin, B. E. K., Rovigatti, L., Schreck, J. S., Harrison, R. M., & Smith, W. P. J. (2013). Coarse-graining DNA for simulations of DNA nanotechnology. *Phys. Chem. Chem. Phys.*, 15, 20395–20414. <https://doi.org/10.1039/C3CP53545B>
- Henrich, O., Gutiérrez Fosado, Y. A., Curk, T., & Ouldrige, T. E. (2018). Coarse-grained simulation of DNA using LAMMPS: An implementation of the oxDNA model and its applications. *European Physical Journal E*, 41(5). <https://doi.org/10.1140/epje/i2018-11669-8>
- Huang, C.-M., Kucinic, A., Johnson, J. A., Su, H.-J., & Castro, C. E. (2021). Integrated computer-aided engineering and design for DNA assemblies. *Nature Materials*, 20(9), 1264–1271.
- Levy, N., & Schabanel, N. (2021). ENSnano: A 3D Modeling Software for DNA Nanostructures. In M. R. Lakin & P. Šulc (Eds.), *27th international conference on DNA computing and molecular programming (DNA 27)* (Vol. 205, pp. 5:1–5:23). Schloss Dagstuhl – Leibniz-Zentrum für Informatik. <https://doi.org/10.4230/LIPIcs.DNA.27.5>
- Llano, E. de, Miao, H., Ahmadi, Y., Wilson, A. J., Beeby, M., Viola, I., & Barisic, I. (2020). Adenita: interactive 3D modelling and visualization of DNA nanostructures. *Nucleic Acids Research*, 48(15), 8269–8275. <https://doi.org/10.1093/nar/gkaa593>
- Maffeo, C., & Aksimentiev, A. (2020). MrDNA: A multi-resolution model for predicting the structure and dynamics of DNA systems. *Nucleic Acids Research*. <https://doi.org/10.1093/nar/gkaa593>

[1093/nar/gkaa200](https://doi.org/10.1093/nar/gkaa200)

- Nomidis, S. K., Skoruppa, E., Carlon, E., & Marko, J. F. (2019). Twist-bend coupling and the statistical mechanics of the twistable wormlike-chain model of DNA: Perturbation theory and beyond. *Phys. Rev. E*, 99, 032414. <https://doi.org/10.1103/PhysRevE.99.032414>
- Poppleton, E., Bohlin, J., Matthies, M., Sharma, S., Zhang, F., & Šulc, P. (2020). Design, optimization and analysis of large DNA and RNA nanostructures through interactive visualization, editing and molecular simulation. *Nucleic Acids Research*, 48(12), e72–e72. <https://doi.org/10.1093/nar/gkaa417>
- Poppleton, E., Romero, R., Mallya, A., Rovigatti, L., & Šulc, P. (2021). OxDNA.org: a public webserver for coarse-grained simulations of DNA and RNA nanostructures. *Nucleic Acids Research*, 49(W1), W491–W498. <https://doi.org/10.1093/nar/gkab324>
- Rovigatti, L., Šulc, P., Reguly, I. Z., & Romano, F. (2015). A comparison between parallelization approaches in molecular dynamics simulations on GPUs. *Journal of Computational Chemistry*, 36(1), 1–8.
- Sengar, A., Ouldrige, T. E., Henrich, O., Rovigatti, L., & Šulc, P. (2021). A primer on the oxDNA model of DNA: When to use it, how to simulate it and how to interpret the results. *Frontiers in Molecular Biosciences*, 8. <https://doi.org/10.3389/fmolb.2021.693710>
- Šponer, J., Riley, K. E., & Hobza, P. (2008). Nature and magnitude of aromatic stacking of nucleic acid bases. *Phys. Chem. Chem. Phys.*, 10, 2595–2610. <https://doi.org/10.1039/B719370J>
- Sugita, Y., & Okamoto, Y. (1999). Replica-exchange molecular dynamics method for protein folding. *Chemical Physics Letters*, 314(1), 141–151. [https://doi.org/10.1016/S0009-2614\(99\)01123-9](https://doi.org/10.1016/S0009-2614(99)01123-9)
- Šulc, P., Romano, F., Ouldrige, T. E., Doye, J. P. K., & Louis, A. A. (2014). A nucleotide-level coarse-grained model of RNA. *The Journal of Chemical Physics*, 140(23), 235102. <https://doi.org/10.1063/1.4881424>
- Suma, A., Poppleton, E., Matthies, M., Šulc, P., Romano, F., Louis, A. A., Doye, J. P. K., Micheletti, C., & Rovigatti, L. (2019). TacoxDNA: A user-friendly web server for simulations of complex DNA structures, from single strands to origami. *Journal of Computational Chemistry*, 40(29), 2586–2595. <https://doi.org/10.1002/jcc.26029>
- Whitelam, S., & Geissler, P. L. (2007). Avoiding unphysical kinetic traps in monte carlo simulations of strongly attractive particles. *The Journal of Chemical Physics*, 127(15), 154101. <https://doi.org/10.1063/1.2790421>