




# Spectral Connectivity: a python package for computing multitaper spectral estimates and frequency-domain brain connectivity measures on the CPU and GPU

Eric L. Denovellis <sup>1,2,3</sup>, Maxym Myroshnychenko <sup>4</sup>, Mehrad Sarmashghi <sup>5</sup>, and Emily P. Stephen <sup>6,7</sup>

**1** Howard Hughes Medical Institute, University of California, San Francisco, San Francisco, California **2** Departments of Physiology and Psychiatry, University of California, San Francisco, San Francisco, California **3** Kavli Institute for Fundamental Neuroscience, University of California, San Francisco, San Francisco, California **4** National Institute of Neurological Disorders and Stroke, Bethesda, Maryland **5** Division of Systems Engineering, Boston University, Boston, Massachusetts **6** Department of Mathematics and Statistics, Boston University, Boston, Massachusetts **7** Center for Systems Neuroscience, Boston University, Boston, Massachusetts

DOI: [10.21105/joss.04840](https://doi.org/10.21105/joss.04840)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Elizabeth DuPre](#)  

## Reviewers:

- [@AJQuinn](#)
- [@sappelhoff](#)
- [@EtienneCmb](#)

Submitted: 15 September 2022

Published: 09 December 2022

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

In neuroscience, characterizing the oscillatory dynamics of the brain is critical to understanding how brain areas interact and function. Neuronal activity tends to fluctuate rhythmically – both through intrinsic currents at the cellular level and through groups of neurons. Brain oscillations and their relationships can indicate the difference between normal and pathological brain states such as Alzheimer’s and epilepsy. Spectral analysis techniques such as multitaper and wavelet analysis are widely used for decomposing signals into oscillatory components. Connectivity measures are used to determine the relationships between those oscillatory components, indicating possible communication between brain areas. Because these analyses are central to neuroscience and technological advances in recording are increasing the amount of simultaneously recorded signals, it is important to have a well-tested, standardized, and lightweight software package to compute these brain connectivity measures at scale.

## Statement of Need

spectral\_connectivity is a Python software package that computes multitaper spectral estimates and frequency-domain brain connectivity measures. The programming language Python is increasingly being used in the neurosciences ([Muller et al., 2015](#); [Schlafly et al., 2020](#)), but the two main packages for spectral analysis in Python, *nitime* ([Rokem et al., 2020](#)) and *mne-python* ([Gramfort et al., 2013](#)), have issues that make them more difficult to use in many situations. For example, *nitime* implements several estimators of the power spectrum, but lacks spectrograms and windowed spectral estimators. *mne-python* is a much larger package designed as a full-featured analysis library for EEG and MEG data, and works best when the data is represented using its ecosystem (i.e. *Epochs* and *Raw* objects). While some of the spectral connectivity functionality can work with *array\_like* objects, users of other data modalities such as non-human electrophysiology data may find *mne-python* too cumbersome for their application. This is an important problem because the non-human neurosciences are undergoing a period of great technological development; more and more signals are being collected simultaneously, and the duration of these signals is becoming longer as chronic recordings become possible. This rapid increase in the size and duration of datasets demands a lightweight, fast, and efficient

spectral estimation package. `spectral_connectivity` is designed to handle multiple time series flexibly<sup>1</sup> and can exploit GPUs for faster and more efficient computation. In addition, it can block compute important quantities such as the cross-spectral matrix in order to reduce memory burdens caused by large datasets. `spectral_connectivity` is also designed to be a lightweight package that has a simple user interface and can be easily be incorporated with other packages. Finally, `spectral_connectivity` also implements several connectivity measures that have not previously been implemented in Python such as the non-parametric version of the spectral granger causality and canonical coherence.

`spectral_connectivity` has already shown its utility to the neuroscience field. The package has already been used in a number of publications and pre-prints in neuroscience (Kühnert et al., 2019; Lauro et al., 2021; Varga et al., 2021; Delgado-Sallent et al., 2021). Interestingly, it has also contributed to a publication in physics (Cliff et al., 2022), showing its versatility and easy of use. We hope this package will continue to be useful to the neuroscience community, particularly for non-human electrophysiology data.

## Acknowledgements

We thank Uri T. Eden for support and mentorship during the creation of this package.

## Citations

- Cliff, O. M., Lizier, J. T., Tsuchiya, N., & Fulcher, B. D. (2022). *Unifying pairwise interactions in complex dynamics*. <https://doi.org/10.48550/ARXIV.2201.11941>
- Delgado-Sallent, C., Nebot, P., Gener, T., Timplalexi, M., Fath, A. B., & Puig, M. V. (2021). Phencyclidine-induced psychosis causes hypersynchronization and disruption of connectivity within prefrontal-hippocampal circuits that is rescued by antipsychotic drugs. *bioRxiv*. <https://doi.org/10.1101/2021.02.03.429582>
- Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., Goj, R., Jas, M., Brooks, T., Parkkonen, L., & Hämäläinen, M. S. (2013). MEG and EEG data analysis with MNE-Python. *Frontiers in Neuroscience*, 7(267), 1–13. <https://doi.org/10.3389/fnins.2013.00267>
- Kühnert, C., Frey, C., & Seyboldt, R. (2019). Detection of Directed Connectivities in Dynamic Systems for Different Excitation Signals using Spectral Granger Causality. In *Machine Learning for Cyber Physical Systems* (pp. 97–106). Springer. [https://doi.org/10.1007/978-3-662-58485-9\\_11](https://doi.org/10.1007/978-3-662-58485-9_11)
- Lauro, P. M., Lee, S., Akbar, U., & Asaad, W. F. (2021). Subthalamic–Cortical Network Reorganization during Parkinson's Tremor. *Journal of Neuroscience*, 41(47), 9844–9858. <https://doi.org/10.1523/JNEUROSCI.0854-21.2021>
- Muller, E., Bednar, J. A., Diesmann, M., Gewaltig, M.-O., Hines, M., & Davison, A. P. (Eds.). (2015). *Python in Neuroscience*. Frontiers Media SA. <https://doi.org/10.3389/978-2-88919-608-1>
- Rokem, A., Ivanov, P., Perez, F., Trumpis, M., & Gramfort, A. (2020). *Nitime: Timeseries analysis for neuroscience data* (Version 0.9) [Computer software]. <https://github.com/nipy/nitime>
- Schlaflly, E., Cheung, A., Michalka, S. W., Lipton, P. A., Kochlacs, C. M., Bohland, J., Eden, U. T., & Kramer, M. (2020). *Python for the practicing neuroscientist: An online educational resource*. <https://doi.org/10.22541/au.159363438.81020330>

<sup>1</sup>For example, the `expectation_type` parameter of the `Connectivity` class gives the user the option to average over trials, tapers, or both, allowing the same module to yield single-trial or summarized estimates.

Varga, B., Soós, B., Jákli, B., Bálint, E., Somogyvári, Z., & Négyessy, L. (2021). Network Path Convergence Shapes Low-Level Processing in the Visual Cortex. *Frontiers in Systems Neuroscience*, 15, 645709. <https://doi.org/10.3389/fnsys.2021.645709>