

MPI-Rockstar: a Hybrid MPI and OpenMP Parallel Implementation of the Rockstar Halo finder

Tomoyuki Tokuue¹, Tomoaki Ishiyama², Ken Osato^{3,4,5}, Satoshi Tanaka⁶, and Peter Behroozi⁷

¹ Department of Applied and Cognitive Informatics, Division of Mathematics and Informatics, Graduate School of Science and Engineering, Chiba University, Chiba 263-8522, Japan ² Digital Transformation Enhancement Council, Chiba University, Chiba 263-8522, Japan ³ Center for Frontier Science, Chiba University, Chiba 263-8522, Japan ⁴ Department of Physics, Graduate School of Science, Chiba University, Chiba 263-8522, Japan ⁵ Kavli Institute for the Physics and Mathematics of the Universe (WPI), The University of Tokyo, Kashiwa, Chiba 277-8583, Japan ⁶ Centre for Gravitational Physics and Quantum Information, Yukawa Institute for Theoretical Physics, Kyoto University, Kyoto 606-8502, Japan ⁷ Department of Astronomy, University of Arizona, AZ 85721, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Christoph Junghans](#)

Reviewers:

- [@yymao](#)
- [@kyleaoman](#)

Submitted: 20 December 2024

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#))

Summary

According to the concordance cosmological theory, structure formation and evolution proceeds hierarchically in the Universe. Smaller-scale dark matter structures gravitationally collapse first everywhere in the Universe, then merge into larger-scale structures. Such dense gravitationally bound structures of dark matter are called halos. Halos can host smaller halos, so-called subhalos (or substructures). Cosmological N -body simulations are vital in understanding the formation and evolution of halos and subhalos. Halo/subhalo finders are a post-processing step to identify those dense structures in the particle dataset of cosmological N -body simulations.

MPI-Rockstar is a massively parallel halo finder based on the [Rockstar](#) phase-space temporal halo finder code ([Behroozi et al., 2013](#)), which is one of the most extensively used halo finding codes. Compared to the original code, parallelized by a primitive socket communication library, we parallelized it in a hybrid way using MPI and OpenMP, which is suitable for analysis on the hybrid shared and distributed memory environments of modern supercomputers. This implementation can easily handle the analysis of more than a trillion particles on more than 100,000 parallel processes, enabling the production of a huge dataset for the next generation of cosmological surveys.


Statement of need

Owing to the advance of supercomputing power and highly scalable parallel gravitational N -body codes ([Garrison et al., 2021](#); [Ishiyama et al., 2009, 2012](#); [Potter et al., 2017](#); [Wang et al., 2018](#)), the number of particles in recent massive cosmological simulations exceeds a trillion ([Ishiyama et al., 2021](#); [Potter et al., 2017](#); [Wang et al., 2022](#)), posing significant challenges for halo finding. Several halo finding algorithms have been suggested ([Knebe et al., 2013](#)), and some of their implementation are publicly available ([Behroozi et al., 2013](#); [Elahi et al., 2019](#); [Knollmann & Knebe, 2009](#); [Springel et al., 2021](#)). The computational performance of these implementations differs substantially, and they have not been uniformly tested yet on the large-scale hybrid shared and distributed memory environments of modern supercomputers. MPI-Rockstar addresses these issues and is designed to run on more than 100,000 parallel processes in a hybrid way using MPI and OpenMP. As new functions to the original Rockstar code, MPI-Rockstar supports HDF5 as an output format and can output additional halo properties such as the inertia tensor.

43 Parallelization

44 As a process parallelization, the original Rockstar divides a simulation box by the number of
45 parallel processes and assigns each sub-box to each process. Then, each process performs
46 3D Friends-of-Friends (FoF) to find overdense regions, and FoF halos across processes are
47 linked by communicating boundary regions. Rockstar then performs the subhalo finding for
48 each FoF halo using 6D phase space information. Data communications between multiple
49 processes are performed by one-to-one communications using sockets. As a result, many
50 sockets (file descriptors) are issued simultaneously in the case of analysis with many processes,
51 complicating analysis on modern supercomputers because the number of file descriptors issued
52 simultaneously is normally limited.

53 In MPI-Rockstar, we replaced all socket communications in the original Rockstar with Message
54 Passing Interface (MPI) communications, while maintaining compatibility with the analysis
55 results. Rather than simply using MPI one-to-one communication, we changed the order of
56 communication and computation to utilize collective communications and to run efficiently
57 on large supercomputers. Furthermore, we parallelized MPI-Rockstar in a hybrid way, where
58 thread parallelization is implemented within each process using OpenMP. The subhalo finding
59 is parallelized not only on a process level but also on a thread level, improving the overall
60 performance of MPI-Rockstar. This hybrid parallel design also reduces the risk of per-process
61 out-of-memory compared with a flat-MPI configuration. The below figure illustrates this
62 parallelization strategy.



63 The below figure shows a strong scaling of MPI-Rockstar using up to 1,024 nodes (48 CPU
64 cores per node) on supercomputer Fugaku. The horizontal and vertical axes represent the
65 number of computational nodes and the time taken for the halo and subhalo finding of one
66 snapshot, respectively. The blue and green curves show the strong scaling for simulations with
67 40963 particles in a 2 Gpc/h box and with 25603 particles in a 400 Mpc/h box, respectively.
68 The redshift of the snapshot analyzed was 2.0. We measured the code's performance using 2
69 MPI processes per node and 24 OpenMP threads per process. This choice gives an optimal
70 configuration for these snapshots, considering the balance between the computation and I/O
71 time. The parallel efficiency is excellent, ~90% for both the 40963 box from 256 to 1024
72 nodes and the 25603 box from 256 to 1024 nodes. Thanks to the communication optimization

and hybrid parallelization, MPI-Rockstar could run up to three times faster than the original Rockstar when compared in the same execution environment. We confirm that MPI-Rockstar can analyze 2 trillion particle simulations on 16,384 nodes (786,432 CPU cores) of Fugaku.




Figure 2: Strong scaling of MPI-Rockstar

Acknowledgements

This work has been supported by IAAR Research Support Program in Chiba University Japan, MEXT/JSPS KAKENHI (Grant Number JP23H04002), MEXT as “Program for Promoting Researches on the Supercomputer Fugaku” (JPMXP1020230406 and JPMXP1020230407), and JICFuS. This work was partially supported by the Sasakawa Scientific Research Grant from The Japan Science Society. Numerical computations were carried out on the supercomputer Fugaku provided by the RIKEN Center for Computational Science (Project ID: hp230173, and hp240184).

References

- Behroozi, P. S., Wechsler, R. H., & Wu, H.-Y. (2013). The ROCKSTAR Phase-space Temporal Halo Finder and the Velocity Offsets of Cluster Cores. 762, 109. <https://doi.org/10.1088/0004-637X/762/2/109>
- Elahi, P. J., Cañas, R., Poulton, R. J. J., Tobar, R. J., Willis, J. S., Lagos, C. del P., Power, C., & Robotham, A. S. G. (2019). Hunting for galaxies and halos in simulations with VELOCraptor. 36, e021. <https://doi.org/10.1017/pasa.2019.12>
- Garrison, L. H., Eisenstein, D. J., Ferrer, D., Maksimova, N. A., & Pinto, P. A. (2021). The ABACUS cosmological N-body code. 508(1), 575–596. <https://doi.org/10.1093/mnras/stab2482>
- Ishiyama, T., Fukushige, T., & Makino, J. (2009). GreeM: Massively Parallel TreePM Code

- 95 for Large Cosmological N -body Simulations. 61, 1319. [https://doi.org/10.1093/pasj/61.](https://doi.org/10.1093/pasj/61.6.1319)
96 6.1319
- 97 Ishiyama, T., Nitadori, K., & Makino, J. (2012). 4.45 pflops astrophysical n-body simulation on
98 k computer: The gravitational trillion-body problem. *Proc. Int. Conf. High Performance*
99 *Computing, Networking, Storage and Analysis, SC'12 (Los Alamitos, CA: IEEE Computer*
100 *Society Press)*, 5, (arXiv:1211.4406). <https://doi.org/10.1109/SC.2012.3>
- 101 Ishiyama, T., Prada, F., Klypin, A. A., Sinha, M., Metcalf, R. B., Jullo, E., Altieri, B., Cora, S.
102 A., Croton, D., de la Torre, S., Millán-Calero, D. E., Oogi, T., Ruedas, J., & Vega-Martínez,
103 C. A. (2021). The Uchuu simulations: Data Release 1 and dark matter halo concentrations.
104 506(3), 4210–4231. <https://doi.org/10.1093/mnras/stab1755>
- 105 Knebe, A., Pearce, F. R., Lux, H., Ascasibar, Y., Behroozi, P., Casado, J., Moran, C. C.,
106 Diemand, J., Dolag, K., Dominguez-Tenreiro, R., Elahi, P., Falck, B., Gottlöber, S., Han,
107 J., Klypin, A., Lukić, Z., Maciejewski, M., McBride, C. K., Merchán, M. E., ... Zemp,
108 M. (2013). Structure finding in cosmological simulations: the state of affairs. 435(2),
109 1618–1658. <https://doi.org/10.1093/mnras/stt1403>
- 110 Knollmann, S. R., & Knebe, A. (2009). AHF: Amiga's Halo Finder. 182(2), 608–624.
111 <https://doi.org/10.1088/0067-0049/182/2/608>
- 112 Potter, D., Stadel, J., & Teyssier, R. (2017). PKDGRAV3: beyond trillion particle cosmological
113 simulations for the next era of galaxy surveys. *Computational Astrophysics and Cosmology*,
114 4(1), 2. <https://doi.org/10.1186/s40668-017-0021-1>
- 115 Springel, V., Pakmor, R., Zier, O., & Reinecke, M. (2021). Simulating cosmic structure
116 formation with the GADGET-4 code. 506(2), 2871–2949. [https://doi.org/10.1093/mnras/](https://doi.org/10.1093/mnras/stab1855)
117 [stab1855](https://doi.org/10.1093/mnras/stab1855)
- 118 Wang, Q., Cao, Z.-Y., Gao, L., Chi, X.-B., Meng, C., Wang, J., & Wang, L. (2018). PHoToNs-
119 A parallel heterogeneous and threads oriented code for cosmological N-body simulation.
120 *Research in Astronomy and Astrophysics*, 18(6), 062. [https://doi.org/10.1088/1674-4527/](https://doi.org/10.1088/1674-4527/18/6/62)
121 [18/6/62](https://doi.org/10.1088/1674-4527/18/6/62)
- 122 Wang, Q., Gao, L., & Meng, C. (2022). The ultramarine simulation: properties of dark matter
123 haloes before redshift 5.5. 517(4), 6004–6012. <https://doi.org/10.1093/mnras/stac3072>