

- WaterBalanceR: An R-Package for Estimating Water
- ² Balance for Starch Potatoes in Germany Based on
- ₃ NDVI Values Provided by Sentinel-2, PlanetScope or
- a DJI Phantom 4 Multispectral UAV
- 5 Thomas Piernicke 1 , Matthias Kunz 1 , Sibylle Itzerott 1 , and
- 6 Christopher Conrad © 2
- 1 GFZ Helmholtz Centre for Geosciences, 14473 Potsdam, Germany ROR 2 Martin-Luther-University,
- 06108 Halle-Wittenberg, Germany ROR ¶ Corresponding author

DOI: 10.xxxxx/draft

Software

- Review 🗗
- Archive ♂

Editor: ♂

Submitted: 06 August 2025 Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

WaterBalanceR is an R package developed within the BMEL-funded project *AgriSens-DEMMIN 4.0* (GFZ, 2021) and is distributed under the AGPL-3.0-only license. It enables the calculation of spatially distributed, daily water balance maps for starch potatoes at a precision farming scale. This is achieved by combining NDVI data derived from multispectral UAV DJI Phantom 4M, PlanetScope or Sentinel-2 imagery with freely available meteorological data and reference evapotranspiration from the German Weather Service (DWD) (Deutscher Wetterdienst (DWD), 2023), using the FAO56 Penman-Monteith method (Allen et al., 1998) along with specified or downloaded irrigation amounts.

Although originally based on a three-year time series of experiments conducted in the DEMMIN area in northeastern Germany (Heinrich et al., 2018), the package is applicable across Germany and potentially worldwide. Its modular structure allows for easy extension to other crops. The related experiments and resulted models are currently being published in the open-access journal *Remote Sensing* (MDPI). Results can be exported as shapefiles (.shp) for further analysis or as PNGs (.png) for quick visual inspection, making it a reproducible and practical tool for researchers and practitioners in precision agriculture.

Statement of Need

Efficient water management is crucial in agriculture, especially under increasing climatic uncertainty and water scarcity. Potato cultivation in Germany requires significant supplemental irrigation, and from an economic pont of view, irrigated potatoes currently yield the highest additional returns among arable crops due to both increased yields and high market prices (Bernhardt et al., 2025; Fricke, 2022; Lüttger et al., 2005; Pfleger et al., 2010).

The amount of supplemental water needed is highly intra site-specific. Farmers may over- or underestimate crop water demand, creating potential for optimization at the precision farming level (Cecilia et al., 2022; Delgado et al., 2019; Lakhiar et al., 2024; Wenzel et al., 2022).

WaterBalanceR addresses this gap by offering a high-resolution, data-driven decision support

tool for intra site-specific irrigation planning, i.e. giving as much water as necessary to cover the plants needs, but as less as possible to avoid any water waste.

By leveraging NDVI data from UAVs and satellites, the package calculates daily water balances at a default spatial resolution of 5 meters. This granularity enables precise irrigation targeting, which can improve yields while conserving water. Although initially developed for DEMMIN,



- the package is applicable throughout Germany using nationwide available datasets, and (with
- 41 further validation) globally. Its spatial resolution of up to 3 meters allows optimization of both
- sprinkler and drip irrigation systems.
- 43 Due to its modular architecture, the tool can be easily adapted to other crops in future
- 44 research. WaterBalanceR serves both applied agricultural decision-making and scientific model
- 45 development, meeting the growing need for scalable, open-source tools in digital and precision
- 46 farming.

51

52

53

57

59

60

62

63

78

79

81

47 Comparison to Existing Software

- There are already several software solutions that support irrigation decision-making in agriculture.
- In Germany, public and partly freely available tools include:
 - AMBAV (Löpmeier, Franz-Josef & Deutscher Wetterdienst, Zentrale Agrarmeteorologische Forschungsstelle Braunschweig, 1983)
 - ISABEL (Deutscher Wetterdienst (DWD), 2018)
 - Agrowetter Beregnung (based on the Geisenheimer method, not freely available)
 (Deutscher Wetterdienst (DWD), 2004)
- These services are provided by the German Weather Service (DWD). Commercial offerings include:
 - Raindancer
 - ZEPHYR (Rickmann, 2009)
 - Irricrop by Sencrop
 - GrowSphere by Netafim
- 61 International options include:
 - Arable Labs Inc.
 - Pessl Instruments
- 64 While many of these tools focus on soil moisture conditions for irrigation decision support, which
- is a more valuable variable than evapotranspiration, since it directly refers to soil conditions,
- they often lack spatial resolution. Soil moisture sensors are limited to specific points of interest
- 67 (POIs), and cannot practically be deployed at high densities without interfering with farming
- practices. As a result, large areas between sensors must be interpolated, risking loss of spatial
 - detail
- Satellite or UAV imagery allows full-field observations, which can resolve this issue. While some
- providers (e.g. Pessl Instruments) already integrate satellite data, their platforms are neither
- 72 free nor open source. Moreover, cloud cover is a persistent limitation of satellite imagery that
- can be addressed by integrating UAV imagery.
- 74 WaterBalanceR fills this gap by offering a free, open-source solution capable of processing
- both satellite and UAV imagery for water balance modeling at high spatial resolution.

76 Functionality

- 77 WaterBalanceR provides the following core functionalities:
 - Calculation of crop coefficient, crop evapotranspiration (ETc), and daily water balance for starch potatoes using NDVI data and FAO56 Penman-Monteith-based ET₀ from DWD Figure 1
 - Output of water balance and further results as shapefiles (.shp) and/or PNGs (.png) at a precision farming scale



84

85

87

88

91

92

93

- Processing of NDVI data from DJI Phantom 4 Multispectral, PlanetScope or Sentinel-2
 freely mixable as input
- Autonomous download and processing of precipitation data:
 - From DWD (RADOLAN)
 - From Furuno X-band radar (if available)
 - From Arable ground stations via API (if deployed on AOI)
- Autonomous download of ET₀ data from DWD or Arable (if deployed on AOI)
- Scraping of irrigation logs (.xlsx) from Raindancer portal and processing into shapefiles (requires user account)
- compatibility with other irrigation data (if available as shapefile)
- Optional download of Sentinel-2 imagery (requires user account)




Figure 1: Daily and cumulative maps and time series of NDVI, crop coefficient (Kc), precipitation, irrigation, evapotranspiration (ETc), and water balance for starch potatoes at DOY 182 (73 days after planting). Left: Spatial distribution of variables across the study site. Middle: Time series of key indicators for four selected sample plots. Right: Cumulative values until DOY 182, visualized both spatially and per plot. This figure demonstrates intra-field variability and highlights site-specific irrigation demand and crop water dynamics for precision irrigation management.

Modules, Routine, and Process Chain

- 95 WaterBalanceR is composed of eight modular scripts that can be run individually or in sequence
- using the configuration script run_calcWB.R Figure 2 to calculate and visualize the water
- balance. Each module corresponds to an R script and function of the same name.
- 98 The process chain is initiated through the configuration module run_calcWB, which initiates
- the core module calc_wb. This module performs the main processing tasks:
 - Loads NDVI data

100

101

102

103

- Retrieves ETo from either DownloadETOfromDWD or DownloadETOfromArable
- Obtains precipitation data from DownloadRadolanfromDWD, or alternatively reads usersupplied RADOLAN or FURUNO shapefiles

104 Irrigation data can be downloaded and processed using the DownloadRaindancer module, 105 generating shapefiles that are compatible with the processing chain. Alternatively, users may 106 provide their own shapefiles containing irrigation depths (in mm).



After preprocessing steps such as resampling, co-registration, correction, and interpolation, the results can be saved as shapefiles, GeoTIFFs or .RData files. The .RData outputs can be passed to the calcWBplots module to generate .png visualizations showing intra-site water balance dynamics across the growing season. Optionally, a shapefile of points of interest (POIs) can be included to enable detailed temporal analysis at specific field locations.




Figure 2: Workflow of the WaterBalanceR package showing the integration of remote sensing data (Sentinel-2, PlanetScope, and DJI Phantom 4 Multispectral UAV), meteorological data (from German Weather Service, Arable Mark 2 Ground stations or Raindancer) and irrigation information. The main module handles data download, pre-processing, model-based calculation of daily crop evapotranspiration and water balance, and output generation for decision support. Color-coded elements indicate manual and automatic input, processing steps, and output formats.

Quality Control and Sample Data

113

114

116

117

120 121

122

123 124

125

126 127

128

130

131 132 In order to ensure functionality and to release a working R package, the package was tested using devtools::check(). Although this resulted in a "warning", it is caused by a non-ASCII-compliant character contained in the Excel files (.xlsx) that were scraped from the Raindancer website. This issue cannot be resolved at the primary data source but is corrected during the processing stage.

To get familiar with the workflow and test the functionality of the package, a folder containing a sample data set (sample_data) is provided in the main branch. It includes:

- A sample set of NDVI files for a site where starch potatoes were cultivated in 2023
- A folder named Radolan_2023_processed_daily containing corresponding RADOLAN precipitation shapefiles
- A folder named shapefiles, which contains:
 - The AOI shapefile (sample_2023.shp)
 - Shapefiles of irrigation data
 - * Original: Buffer_36m_all_orig.shp
 - * Interpolated: Buffer_36m_all_interp.shp
 - POI shapefile (Buffer_5_WB.shp)



135 136

137

138

141

- DWD_ET0_2023.csv containing reference evapotranspiration data for the specified AOI
 - run_calcWB_2023_sample.R the configuration script that runs the water balance model for the sample AOI
- run_raindancerscraping.R a configuration script to scrape data from the Raindancer user portal, if access credentials are available

The entire folder should be copied to a desired directory to act as a sandbox for testing, as each execution generates and saves results to the local file system.

Additionally, an installation script named install_WaterBalanceR.R is available in the main directory and can be used to install the package.

Acknowledgements

We would like to thank Arable Labs, Inc. for providing several Arable Mark 2 and Mark 3 ground stations and for their close cooperation. We also extend our gratitude to the German Weather Service (DWD) — especially Falk Böttcher — as well as Dr. Julia Pöhlitz and Jan-Lukas Wenzel from Martin-Luther-University Halle-Wittenberg for their valuable collaboration.

Funding Information

This work was funded by the **German Federal Ministry of Food and Agriculture** (based on a decision by the German Bundestag) under project numbers FKZ 28DE114A18 and FKZ 28DE114A22 within the scope of the **AgriSens-DEMMIN 4.0** project.

56 References

Allen, R., Pereira, L., Raes, D., & Smith, M. (1998). FAO Irrigation and drainage paper No. 56. Rome: Food and Agriculture Organization of the United Nations, 56, 26–40. https://www.fao.org/4/x0490e/x0490e00.htm

Bernhardt, J. J., Stupak, N., Neuenfeldt, S., & Potts, F. (2025). Status quo der Bewässerung in Deutschland (No. 258; p. 101). Johann Heinrich von Thünen-Institut Bundes-forschungsinstitut für Ländliche Räume, Wald und Fischerei. https://doi.org/10.3220/WP1736495260000

Cecilia, B., Francesca, A., Dalila, P., Carlo, S., Antonella, G., Francesco, F., Marco, R., & Mauro, C. (2022). On-line monitoring of plant water status: Validation of a novel sensor based on photon attenuation of radiation through the leaf. *Science of The Total Environment*, 817, 152881. https://doi.org/10.1016/j.scitotenv.2021.152881

Delgado, J. A., Short, N. M., Roberts, D. P., & Vandenberg, B. (2019). Big Data Analysis for
 Sustainable Agriculture on a Geospatial Cloud Framework. Frontiers in Sustainable Food
 Systems, Volume 3 - 2019. https://doi.org/10.3389/fsufs.2019.00054

Deutscher Wetterdienst (DWD). (2004). Agrowetter Beregnung model explanation.

https://www.dwd.de/DE/fachnutzer/landwirtschaft/dokumentationen/agrowetter/

Modellbeschreibung.html

Deutscher Wetterdienst (DWD). (2018). ISABEL. https://isabel.dwd.de/

Deutscher Wetterdienst (DWD). (2023). *Tägliche Raster der FAO Grasreferenzverdunstung,*Version v1.0. https://opendata.dwd.de/climate_environment/CDC/grids_germany/daily/



208

209

```
evaporation_fao/BESCHREIBUNG_gridsgermany_daily_evaporation_fao_de.pdf
177
    Fricke, E. (2022). ) Einstieg in die Bewässerung – was ist zu beachten? Landwirtschaftskammer
178
       Niedersachsen. https://www.lwk-niedersachsen.de/lwk/news/39063_Einstieg_in_die_
179
       Bew%C3%A4sserung_%E2%80%93_was_ist_zu_beachten
180
    GFZ. (2021). Https://www.gfz.de/en/section/remote-sensing-and-geoinformatics/projects/agrisens-
181
       demmin-40.
    Heinrich, I., Balanzategui, D., Bens, O., Blasch, G., Blume, T., Böttcher, F., Borg, E.,
183
       Brademann, B., Brauer, A., Conrad, C., Dietze, E., Dräger, N., Fiener, P., Gerke, H.
184
       H., Güntner, A., Heine, I., Helle, G., Herbrich, M., Harfenmeister, K., ... Wilken, F.
185
       (2018). Interdisciplinary Geo-ecological Research across Time Scales in the Northeast
       German Lowland Observatory (TERENO-NE). Vadose Zone Journal, 17(1), 180116. https:
187
       //doi.org/10.2136/vzj2018.06.0116
188
    Lakhiar, I. A., Yan, H., Zhang, C., Wang, G., He, B., Hao, B., Han, Y., Wang, B., Bao, R.,
       Syed, T. N., Chauhdary, J. N., & Rakibuzzaman, Md. (2024). A Review of Precision
190
       Irrigation Water-Saving Technology under Changing Climate for Enhancing Water Use
191
       Efficiency, Crop Yield, and Environmental Footprints. Agriculture, 14(7). https://doi.org/
192
       10.3390/agriculture14071141
                Franz-Josef, & Deutscher Wetterdienst, Zentrale Agrarmeteorologische
194
       Forschungsstelle Braunschweig. (1983). Agrarmeteorologisches Modell zur Berechnung der
195
       aktuellen Verdunstung (AMBAV). https://opendata.dwd.de/climate_environment/CDC/
       derived_germany/soil/daily/recent/AMBAV.pdf
197
    Lüttger, A., Dittmann, B., & Sourell, H. (2005). Leitfaden zur Beregnung landwirtschaftlicher
198
       Kulturen, hg. V. Ministerium für Ländliche Entwicklung, Umwelt und Verbraucherschutz
199
       des Landes Brandenburg (No. 2005/7; p. 12). Ministerium für Ländliche Entwicklung,
200
       Umwelt und Verbraucherschutz des Landes Brandenburg. https://www.openagrar.de/
201
       receive/timport_mods_00005662
202
    Pfleger, I., Rößler, U., Michel, H., Knoblauch, S., Nußbaum, G., Werner, A., Krumbein,
       M., & Penzler, R. (2010). Untersuchungsergebnisse zur Bewässerung in Thüringen (No.
204
       6/2010). Thüringer Landesanstalt für Landwirtschaft. https://www.tll.de/www/daten/
205
       publikationen/schriftenreihe/h2ot1110.pdf
206
```

Rickmann, M. (2009). ZEPHYR - Ein Simulationsmodell zur Bewässerungssteuerung.

Wenzel, J. L., Conrad, C., Piernicke, T., Spengler, D., & Pöhlitz, J. (2022). Assessing the

Impact of Different Irrigation Levels on Starch Potato Production. Agronomy, 12(11).

https://doi.org/10.3390/agronomy12112685