

# nestcheck: error analysis, diagnostic tests and plots for nested sampling calculations

Edward Higson<sup>1, 2</sup>

<sup>1</sup> Astrophysics Group, Cavendish Laboratory, J.J.Thomson Avenue, Cambridge, CB3 0HE, UK <sup>2</sup> Kavli Institute for Cosmology, Madingley Road, Cambridge, CB3 0HA, UK

DOI: [10.21105/joss.00916](https://doi.org/10.21105/joss.00916)

## Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted: 04 August 2018

Published: 11 September 2018

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

## Summary

Nested sampling (Skilling, 2006) is a popular Monte Carlo method for Bayesian analysis which, given some likelihood and prior, provides both samples from the posterior distribution and an estimate of the Bayesian evidence. Due to the distinctive manner in which the nested sampling algorithm explores the parameter space, it produces posterior samples with different statistical properties to those generated from alternative techniques such as Markov chain Monte Carlo (MCMC)-based approaches. As a result, posterior inferences and estimates of their associated uncertainties require methods specific to nested sampling.

**nestcheck** is a Python package for analysing samples produced by nested sampling, and estimating uncertainty on posterior inferences. Most importantly, **nestcheck** contains fast and well-tested implementations of the error analysis methods introduced in (Higson, Handley, Hobson, & Lasenby, 2018a) and the diagnostic tests and plots described in (Higson, Handley, Hobson, & Lasenby, 2018b). The code has been profiled for computational efficiency and uses fast **numpy** functions and parallelisation with **concurrent.futures**. The diagnostic plots make use of the **matplotlib** (Hunter, 2007) and **fgivenx** (Handley, 2018) packages.

**nestcheck** can analyse samples from the popular **MultiNest** (Feroz & Hobson, 2008; Feroz, Hobson, & Bridges, 2008; Feroz, Hobson, Cameron, & Pettitt, 2013) and **PolyChord** (W. J. Handley, Hobson, & Lasenby, 2015a, 2015b) packages, and functions for loading samples from other software packages with different formats can easily be added. **nestcheck** is also compatible with samples produced by the dynamic nested sampling algorithm (Higson, Handley, Hobson, & Lasenby, 2017), and its functions for storing and manipulating nested sampling output are used by the **dyPolyChord** (Higson, 2018a) and **perfectns** (Higson, 2018b) dynamic nested sampling packages.

**nestcheck** is designed to allow nested sampling software users to quickly calculate results and uncertainty estimates, as well as to apply diagnostics for checking their software has explored the posterior correctly. It was used for the diagnostic tests and plots in (Higson et al., 2018b), and for error analysis in (Higson et al., 2017) and (Higson, Handley, Lasenby, & Hobson, 2018). An earlier version of the code was used in the analysis of black hole mergers in (Chua et al., 2018). The source code for **nestcheck** has been archived to Zenodo (Higson, 2018c).

## Acknowledgements

I am grateful to Will Handley, Anthony Lasenby and Mike Hobson for their help and advice.

## References

- Chua, A. J. K., Hee, S., Handley, W. J., Higson, E., Moore, C. J., Gair, J. R., Hobson, M. P., et al. (2018). Towards a framework for testing general relativity with extreme-mass-ratio-inspiral observations. *Monthly Notices of the Royal Astronomical Society*, 478(1), 28–40. doi:[10.1093/mnras/sty1079](https://doi.org/10.1093/mnras/sty1079)
- Feroz, F., & Hobson, M. P. (2008). Multimodal nested sampling: An efficient and robust alternative to Markov Chain Monte Carlo methods for astronomical data analyses. *Monthly Notices of the Royal Astronomical Society*, 384(2), 449–463. doi:[10.1111/j.1365-2966.2007.12353.x](https://doi.org/10.1111/j.1365-2966.2007.12353.x)
- Feroz, F., Hobson, M. P., & Bridges, M. (2008). MultiNest: an efficient and robust Bayesian inference tool for cosmology and particle physics. *Monthly Notices of the Royal Astronomical Society*, 398(4), 1601–1614. doi:[10.1111/j.1365-2966.2009.14548.x](https://doi.org/10.1111/j.1365-2966.2009.14548.x)
- Feroz, F., Hobson, M. P., Cameron, E., & Pettitt, A. N. (2013). Importance Nested Sampling and the MultiNest Algorithm. *arXiv preprint arXiv:1306.2144*. Retrieved from <https://arxiv.org/abs/1306.2144>
- Handley, W. (2018). fgivex: A Python package for functional posterior plotting. *Journal of Open Source Software*, 3(28), 849. doi:[10.21105/joss.00849](https://doi.org/10.21105/joss.00849)
- Handley, W. J., Hobson, M. P., & Lasenby, A. N. (2015a). PolyChord: Nested sampling for cosmology. *Monthly Notices of the Royal Astronomical Society: Letters*, 450(1), L61–L65. doi:[10.1093/mnrasl/slv047](https://doi.org/10.1093/mnrasl/slv047)
- Handley, W. J., Hobson, M. P., & Lasenby, A. N. (2015b). PolyChord: next-generation nested sampling. *Monthly Notices of the Royal Astronomical Society*, 15, 1–15. doi:[10.1093/mnras/stv1911](https://doi.org/10.1093/mnras/stv1911)
- Higson, E. (2018a). dyPolyChord: dynamic nested sampling with PolyChord. doi:[10.5281/zenodo.1328175](https://doi.org/10.5281/zenodo.1328175)
- Higson, E. (2018b). perfectns: perfect dynamic and standard nested sampling for spherically symmetric likelihoods and priors. doi:[10.5281/zenodo.1327591](https://doi.org/10.5281/zenodo.1327591)
- Higson, E. (2018c). nestcheck: error analysis, diagnostic tests and plots for nested sampling calculations. doi:[10.5281/zenodo.1329513](https://doi.org/10.5281/zenodo.1329513)
- Higson, E., Handley, W., Hobson, M., & Lasenby, A. (2017). Dynamic nested sampling : an improved algorithm for parameter estimation and evidence calculation. *arXiv preprint arXiv:1704.03459*. Retrieved from <https://arxiv.org/abs/1704.03459>
- Higson, E., Handley, W., Hobson, M., & Lasenby, A. (2018a). Sampling errors in nested sampling parameter estimation. *Bayesian Analysis*, 13(3), 873–896. doi:[doi:10.1214/17-BA1075](https://doi.org/10.1214/17-BA1075)
- Higson, E., Handley, W., Hobson, M., & Lasenby, A. (2018b). Diagnostic Tests for Nested Sampling Calculations. *arXiv preprint arXiv:1804.06406*. Retrieved from <https://arxiv.org/abs/1804.06406>
- Higson, E., Handley, W., Lasenby, A., & Hobson, M. (2018). Bayesian sparse reconstruction: a brute-force approach to astronomical imaging and machine learning. *in preparation*.
- Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science and Engineering*, 9(3), 90–95. doi:<https://doi.org/10.1109/MCSE.2007.55>
- Skilling, J. (2006). Nested sampling for general Bayesian computation. *Bayesian Analysis*, 1(4), 833–860. doi:[10.1214/06-BA127](https://doi.org/10.1214/06-BA127)