THz Image Explorer - An Interactive Cross-Platform Open-Source THz Image Analysis Tool

**Linus Leo Stöckli** [1]¶, **Arnaud Demion** [2], and **Nicolas Thomas** [1]

1 Space Research & Planetary Sciences Division, University of Bern, Bern, Switzerland ROR **2** University of Applied Sciences and Arts Western Switzerland Valais, HES-SO Valais-Wallis, Sion, Switzerland ROR ¶ Corresponding author

Introduction

THz time-domain spectroscopy (TDS) is a fast-growing field with applications to perform non-destructive studies of material properties (Neu & Schmuttenmaer, 2018). This involves measuring the interaction of pulses of radiation with a sample, where the pulses are measured after either passing through (transmission spectrum) or being reflected by (reflection spectrum) the sample. Through Fourier analysis (FFT), we can investigate the complex refractive index and absorption coefficient of the sample. By placing either the sample or the optical setup on a moving stage, the sample can be imaged in 2D.

Figure 1: THz Image Explorer icon.

We developed an interactive graphical user interface (GUI), written in Rust (Matsakis & Klock II, 2014), to aid in investigating acquired 2D scans. The application implements the dotTHz standard (Lee et al., 2023) and is platform independent and open-source, making it easier to maintain and increasing its reach.

Figure 2: THz Image Explorer screenshot.

Statement of need

Interactive analysis tools for THz spectroscopy are essential to browse through images and analyse different regions of interest efficiently. Commercial suppliers (e.g., Menlo Systems) provide closed-source analysis tools where the code cannot be adapted by the user, which is often essential in research environments and can extend the maintainability of the code. Solutions published by the scientific community are not available on all platforms, are only applicable on single pixel measurements, and/or are not focused on an interactive workflow (Loaiza et al., 2024; Peretti et al., 2019). With this application, we provide a high-performance solution written in Rust that allows an interactive analysis of 2D THz scans with multiple filters and a 3D viewer. The work is open-source, and pre-built bundles are provided for Linux, macOS, and Windows, ensuring broad accessibility for the scientific community.

Structure

The application is multithreaded with two main threads:

- GUI thread
- Data thread

The GUI uses egui, an immediate-mode GUI library for Rust.

The structure of the software is shown in Figure 3.

Figure 3: Software Architecture.

Usage

A sample scan (of a resolution target) is available in the `sample_data` directory. The measurement has been acquired using the COCoNuT setup (Stöckli et al., 2025).

Optical Properties Calculation

The user can select a source and reference scan in the drop-down menu, after which the refractive index n and absorption coefficient α are computed according to Jepsen (2019):

$$n(\omega) = 1 + \frac{c\Delta\phi(\omega)}{\omega d},$$

$$\alpha(\omega) = -\frac{2}{d}\ln\left(\frac{(n+1)^2}{4n} \cdot \frac{A_{\text{sample}}(\omega)}{A_{\text{reference}}(\omega)}\right),$$

where

- $\Delta\phi(\omega) = \phi_{\text{sample}}(\omega) - \phi_{\text{reference}}(\omega)$ is the phase difference
- $A_{\text{sample}}(\omega)$ and $A_{\text{reference}}(\omega)$ are the amplitude spectra
- c is the speed of light
- $\omega = 2\pi f$ is the angular frequency
- d is the sample thickness

Interactive 3D Viewer

A THz time domain scan produces a 3D data array with dimensions $n_x \times n_y \times n_t$, where (n_x, n_y) represent the spatial coordinates and n_t represents the time axis.

Scans performed in reflection can be visualized in 3D. First, we transform each time trace into an intensity value by computing the squared amplitude and applying a Gaussian envelope function

$$I(x, y, t) = |s(x, y, t)|^2 * G_\sigma(t),$$

where $G_\sigma(t)$ is a normalized 1D Gaussian kernel with standard deviation $\sigma = 6.0$ and radius of 12 samples, applied via convolution to smooth the squared signal and extract the envelope as shown in Figure 4.

Figure 4: The convoluted envelope of the signal. All datapoints below the indicated threshold are treated as transparent.

The time axis is converted to a spatial distance coordinate by assuming a refractive index of $n = 1$ and using the relation $z = ct/2$, where c is the speed of light and the factor of 2 accounts for the signal's round-trip. This transformation yields a 3D intensity cube $I(x, y, z)$.

Each element (voxel) in this cube represents the THz signal intensity at a specific point in 3D space, enabling visualization of reflections from internal interfaces and sub-surface structures.

The computed intensities are mapped to voxel opacity values; regions with high intensity appear opaque while low-intensity regions become transparent.

The 3D viewer is implemented using the bevy game engine (Bevy Contributors, 2025) with a custom WGSL shader, available as a separate crate under the name bevy_voxel_plot.

Filtering pipeline

The filtering process is a simple linear pipeline, where the output of one filter is the input of the next filter. Filters can be placed in the following specific domains:

- Time Domain Before FFT
- Frequency Band Pass Filter
- Time Domain After FFT

Band-pass filters are already implemented in the application for each domain. The band-pass filter in time domain before FFT can be used to trim off trailing pulses. By selecting a slice in time domain after FFT, it is possible to scan through the z-axis of the scan and analyse sub-surface layers (Koch-Dandolo et al., 2015).

Deconvolution

The deconvolution filter is an implementation of the Frequency-dependent Richardson – Lucy algorithm described in Demion et al. (2025).

Custom Filters

The code-base can easily be extended with custom filters. The user needs to create a custom file in the `src/filters` directory with a struct that implements the `Filter` trait.

Summary

THz Image Explorer primarily serves as a high-performance data analysis tool for THz 2D images. Its main focus lies on preliminary browsing of measurements, rough analysis of scans and identifying regions of interest in each scan. It is designed in a modular way to allow possible implementation of more thorough analysis features in the future.

Declaration of the use of AI-based tools

AI-based tools, including ChatGPT and GitHub Copilot, were used to support this work. These tools assisted with code generation but did not replace the author's critical thinking or original contributions in any way. All content has been reviewed and validated by the authors to ensure accuracy and integrity.

AI-based tool	Model	Use Case	Remarks
ChatGPT	GPT-3, GPT-4, GPT-4o, GPT-5	Code generation	Rust, Python
GitHub Copilot	GPT-4o, GPT-5, Claude Sonnet 3.5, Claude Sonnet 3.7, Gemini 2.5	Code generation	Rust, Python, Swift

Acknowledgements

References

Bevy Contributors. (2025). *Bevy engine* (Version 0.16.1). https://github.com/bevyengine/bevy/releases/tag/v0.16.1.

Demion, A., Stöckli, L. L., Thomas, N., & Zahno, S. (2025). Frequency-dependent deconvolution for enhanced THz-TDS scans: Accounting for beam width variations in time traces. *IEEE Transactions on Terahertz Science and Technology*, *15*(3), 505–513. https://doi.org/10.1109/TTHZ.2025.3546756

Jepsen, P. U. (2019). Phase retrieval in terahertz time-domain measurements: A "how to" tutorial. *Journal of Infrared, Millimeter, and Terahertz Waves*, *40*(4), 395–411. https://doi.org/10.1007/s10762-019-00578-0

Koch-Dandolo, C. L., Filtenborg, T., Fukunaga, K., Skou-Hansen, J., & Jepsen, P. U. (2015). Reflection terahertz time-domain imaging for analysis of an 18th century neoclassical easel painting. *Applied Optics*, *54*(16), 5123–5123. https://doi.org/10.1364/ao.54.005123

Lee, J., Leung, C. K., Ma, M., Ward-Berry, J., Santitewagun, S., & Zeitler, J. A. (2023). The dotTHz project: A standard data format for terahertz time-domain data. *Journal of Infrared, Millimeter, and Terahertz Waves*, *44*(11-12), 795–813. https://doi.org/10.1007/s10762-023-00947-w

Loaiza, J. P., Higuera-Quintero, S., Noori, A., Mohtashemi, L., Hall, R. P., Yimam, N. A., & Dodge, J. S. (2024). THzTools: Data analysis software for terahertz time-domain spectroscopy. *Journal of Open Source Software*, *9*(104), 7542. https://doi.org/10.21105/joss.07542

Matsakis, N. D., & Klock II, F. S. (2014). The Rust language. *ACM SIGAda Ada Letters*, *34*, 103–104. https://doi.org/10.1145/2692956.2663188

Neu, J., & Schmuttenmaer, C. A. (2018). Tutorial: An introduction to terahertz time domain spectroscopy (THz-TDS). *Journal of Applied Physics*, *124*(23), 231101. https://doi.org/10.1063/1.5047659

Peretti, R., Mitryukovskiy, S., Froberger, K., Mebarki, M. A., Eliet, S., Vanwolleghem, M., & Lampin, J.-F. (2019). THz-TDS time-trace analysis for the extraction of material and metamaterial parameters. *IEEE Transactions on Terahertz Science and Technology*, *9*(2), 136–149. https://doi.org/10.1109/TTHZ.2018.2889227

Stöckli, L. L., Brändli, M., Piazza, D., Ottersberg, R., Pommerol, A., Murk, A., & Thomas, N. (2025). Design and commissioning of a THz time-domain spectro-goniometer in a cryogenic comet simulation chamber. *Review of Scientific Instruments*, *96*(3), 034502. https://doi.org/10.1063/5.0252742