




# multipers : Multiparameter Persistence for Machine Learning

David Loiseaux<sup>1</sup> and Hannah Schreiber<sup>1</sup>

<sup>1</sup> Centre Inria d'Université Côte d'Azur, France

DOI: [10.21105/joss.06773](https://doi.org/10.21105/joss.06773)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Rocco Meli](#) 

## Reviewers:

- [@yossibokorbleile](#)
- [@peekxc](#)

Submitted: 13 May 2024


Published: 31 October 2024

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

**multipers** is a Python library for Topological Data Analysis, focused on **Multiparameter Persistence** computation and visualizations for Machine Learning. It features several efficient computational and visualization tools, with integrated, easy to use, auto-differentiable Machine Learning pipelines, that can be seamlessly interfaced with `scikit-learn` ([Pedregosa et al., 2011](#)) and `PyTorch` ([Paszke et al., 2019](#)). This library is meant to be usable for non-experts in Topological or Geometrical Machine Learning. Performance-critical functions are implemented in C++ or in Cython ([Behnel et al., 2011-03/2011-04](#)), are parallelizable with TBB ([Robison, 2011](#)), and have Python bindings and interface. It can handle a very diverse range of datasets that can be framed into a (finite) multi-filtered simplicial or cell complex, including, e.g., point clouds, graphs, time series, images, etc.




**Figure 1:** (Left) Topological 2-filtration grid. The color corresponds to the density estimation of the sampling measure of the point cloud. More formally, a point  $x \in \mathbb{R}^2$  belongs to the grid cell with coordinates  $(r, d)$  iff  $d(x, \text{point cloud}) \leq r$  and  $\text{density}(x) \geq d$ . The green background shape corresponds to the lifetime of the annulus in this 2-parameter grid. (Right) A visualization of the lifetimes of geometric structures given by **multipers**; here each colored shape corresponds to a cycle appearing in the bi-filtration on the left, and the shape represents its lifetime. The biggest green shape on the right is the same as the one on the left.


**Some motivation.** In the example of Figure 1, a point cloud is given from sampling a probability measure whose mass is, for the most part, located on an annulus, with some diffuse background noise. The goal here is to recover this information in a topological descriptor. For this, the point cloud can be analyzed at some geometric scale  $r > 0$  and density scale  $d$  by centering balls of radius  $r$  around each point whose density is above  $d$ , and looking at the topology induced by the union of balls. However, notice that neither a fixed geometric scale nor

density scale alone can retrieve (canonically) meaningful information due to the diffuse noise in the background; which is the main limitation of the prevalent approach. Nevertheless, by considering *all* possible combinations of geometric or density scales, also called a bi-filtration, it becomes straightforward with multipers to retrieve some of the underlying geometrical structures without relying on any arbitrary scale choice.

Furthermore, multipers seamlessly integrates several Rust and C++ libraries such as Gudhi ([TheGudhiProject, 2023](#)), filtration-domination ([Alonso et al., 2023](#)), mpfree ([Kerber & Rolle, 2020](#)), and function-delaunay ([Alonso et al., 2024](#)), and leverages on state-of-the-art Machine Learning libraries for fast computations, such as scikit-learn ([Pedregosa et al., 2011](#)), Python Optimal Transport ([Flamary et al., 2021](#)), PyKeops ([Charlier et al., 2021](#)), or PyTorch ([Paszke et al., 2019](#)). This makes multipers a very efficient and fully-featured library, showcasing a wide variety of mathematically-grounded multiparameter topological invariants, including, e.g., Multiparameter Module Approximation ([Loiseaux et al., 2022](#)), Euler, Hilbert, and Rectangle Signed Barcodes ([Botnan et al., 2022](#)) ([Oudot & Scoccola, 2024](#)), Multiparameter Persistent Landscapes ([Vipond, 2020](#)); each of them computable from several multi-filtrations, e.g., Rips-Density-like filtrations, Cubical, Degree-Rips, Function-Delaunay, or any  $k$ -critical multi-filtration. These topological descriptors can then directly be used in auto-differentiable Machine Learning pipelines, using the differentiability framework developed in ([Scoccola et al., 2024](#)), through several methods, such as, e.g., Decomposable Module Representations ([Loiseaux, Carrière, et al., 2023](#)), Sliced Wasserstein Kernels or Convolutions from Signed Measures ([Loiseaux, Scoccola, et al., 2023](#)). As a result, multipers is capable of handling, within a single minute of computation, datasets of  $\sim 50k$  points with only 5 lines of Python code. See Figures 2, 3.



**Figure 2:** Typical interpretation of a “Geometric & Density” bi-filtration with multipers. **(Left)** Point cloud with color induced by density estimation (same as Figure 1). **(Right)** A visualization of the topological structure lifetimes computed from a Delaunay-Codensity bi-filtration; here the three cycles can be retrieved using their radii (x-axis) and their co-densities (y-axis). The first cycle is the densest, and smallest, and thus corresponds to the one that appears in the bottom(high-density)-left(small-radius) of the bi-filtration. The second is less dense (thus above the first one) and bigger (thus more on the right). The same goes for the last one.



**Figure 3:** Different Signed Barcodes from the same dataset as Figure 1. **(Left)** Euler Decomposition Signed Barcode, and the Euler Surface in the background. **(Middle)** Hilbert Decomposition Signed Barcode, with its Hilbert Function surface. **(Right)** Rank invariant Signed Barcode, with the Hilbert Function as a background.

The core functions of the Python library are automatically tested on Linux and macOS, using pytest (Krekel et al., 2004) alongside GitHub Actions.

## Related work and statement of need

There exists several libraries for computation or pre-processing of very specific tasks related to multiparameter persistence. However, to the best of our knowledge, none of them are able to tackle the challenges that *multipers* is dealing with, i.e., (1) computing and unifying the computations of multiparameter persistent structures, in a non-expert friendly approach, and (2) provide ready-to-use general tools to use these descriptors for Machine Learning pipelines and projects.

**Eulearning.** This library features different approaches for computing and using the Euler Characteristic of a multiparameter filtration (Hacquard & Lebovici, 2023). Although relying on distinct methods, *multipers* can also be used to compute Machine Learning descriptors from the Euler Characteristic, i.e., the Euler Decomposition Signed Barcode, or Euler Surfaces. Moreover, *multipers* computations are faster (especially on point cloud datasets), easier to use, and available on a wider range of multi-filtrations.

**Multiparameter Persistent Landscape.** Implemented on top of *Rivet* (Lesnick & Wright, 2015), this library computes a multiparameter persistent descriptor by computing 1-parameter persistence landscape vectorizations of slices in multi-filtrations (Vipond, 2020), called Multiparameter Persistent Landscape (MPL). This library also features some multiparameter persistence visualizations. However, it is limited to *Rivet* capabilities and landscapes computations, which on one hand does not leverage on recently developed optimizations, e.g., (Alonso et al., 2023), or (Kerber & Rolle, 2020), and on the other hand can only work with very specific text file inputs.

**GRIL.** This library provides code to compute a specific, generalized version of the Multiparameter Persistent Landscapes (Xin et al., 2023), relying on 1-parameter persistence zigzag computations. This library however is limited to this invariant, can only deal with 2-parameter persistence, and is not as much integrated as *multipers* with other multiparameter persistence and Machine Learning libraries.

**Elder Rule Staircode.** This library features a descriptor for 2-parameter, degree-0 homology, rips-density-like filtrations (Cai et al., 2021). Once again, this library is very specific and not linked with other libraries.

**Persistable.** is a GUI interactive library for clustering, using degree-0 multiparameter persistence (Scoccola & Rolle, 2023) (Rolle & Scoccola, 2020). Although aiming at distinct goals and using very different approaches, *multipers* can also be used for clustering, by computing

(differentiable) descriptors that can be used afterward with standard clustering methods, e.g., K-means.

We contribute to this variety of task-specific libraries by providing a **general purpose** library, multipers, with novel and efficient topological invariant computations, integrated state-of-the-art Machine Learning topological pipelines, and interfaces to standard Machine Learning and Deep Learning libraries.

## Acknowledgements

David Loiseaux was supported by ANR grant 3IA Côte d'Azur (ANR-19-P3IA-0002). The authors would like to thank Mathieu Carrière, and Luis Scoccola for their help on Sliced Wasserstein, and Möbius inversion code.

## References

- Alonso, Á. J., Kerber, M., Lam, T., & Lesnick, M. (2024). Delaunay Bifiltrations of Functions on Point Clouds. In *Proceedings of the 2024 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)* (pp. 4872–4891). Society for Industrial and Applied Mathematics. <https://doi.org/10.1137/1.9781611977912.173>
- Alonso, Á. J., Kerber, M., & Pritam, S. (2023). Filtration-domination in bifiltered graphs. In *2023 proceedings of the symposium on algorithm engineering and experiments (ALENEX)* (pp. 27–38). <https://doi.org/10.1137/1.9781611977561.ch3>
- Behnel, S., Bradshaw, R., Citro, C., Dalcin, L., Seljebotn, D. S., & Smith, K. (2011-03/2011-04). Cython: The best of both worlds. *Computing in Science Engineering*, 13(2), 31–39. <https://doi.org/10.1109/MCSE.2010.118>
- Botnan, M. B., Oppermann, S., & Oudot, S. (2022). Signed Barcodes for Multi-Parameter Persistence via Rank Decompositions. In X. Goaoc & M. Kerber (Eds.), *38th International Symposium on Computational Geometry (SoCG 2022)* (Vol. 224, pp. 19:1–19:18). Schloss Dagstuhl – Leibniz-Zentrum für Informatik. <https://doi.org/10.4230/LIPIcs.SoCG.2022.19>
- Cai, C., Kim, W., Memoli, F., & Wang, Y. (2021). Elder-Rule-Staircodes for Augmented Metric Spaces. *SIAM Journal on Applied Algebra and Geometry*, 5(3), 417–454. <https://doi.org/10.1137/20M1353605>
- Charlier, B., Feydy, J., Glaunès, J. A., Collin, F. ois-D., & Durif, G. (2021). Kernel Operations on the GPU, with Autodiff, without Memory Overflows. *Journal of Machine Learning Research*, 22(74), 1–6.
- Flamary, R., Courty, N., Gramfort, A., Alaya, M. Z., Boissunon, A., Chambon, S., Chapel, L., Corenflos, A., Fatras, K., Fournier, N., Gautheron, L., Gayraud, N. T. H., Janati, H., Rakotomamonjy, A., Redko, I., Rolet, A., Schutz, A., Seguy, V., Sutherland, D. J., ... Vayer, T. (2021). POT: Python optimal transport. *The Journal of Machine Learning Research*, 22(1), 78:3571–78:3578.
- Hacquard, O., & Lebovici, V. (2023). Euler Characteristic Tools For Topological Data Analysis. *arXiv.org*. <https://doi.org/10.48550/arxiv.2303.14040>
- Kerber, M., & Rolle, A. (2020). Fast Minimal Presentations of Bi-graded Persistence Modules. *arXiv:2010.15623 [Cs, Math]*. <https://doi.org/10.1137/1.9781611976472.16>
- Krekel, H., Oliveira, B., Pfannschmidt, R., Bruynooghe, F., Laughner, B., & Bruhin, F. (2004). *Pytest 8.3*.
- Lesnick, M., & Wright, M. (2015). Interactive visualization of 2-D persistence modules. *arXiv:1512.00180 [Cs, Math]*. <https://doi.org/10.48550/arXiv.1512.00180>

- Loiseaux, D., Carrière, M., & Blumberg, A. (2023). A Framework for Fast and Stable Representations of Multiparameter Persistent Homology Decompositions. *Advances in Neural Information Processing Systems*, 36, 35774–35798.
- Loiseaux, D., Carrière, M., & Blumberg, A. J. (2022). *Fast, Stable and Efficient Approximation of Multi-parameter Persistence Modules with MMA*. <https://doi.org/10.48550/arXiv.2206.02026>
- Loiseaux, D., Scoccola, L., Carrière, M., Botnan, M. B., & Oudot, S. (2023). Stable Vectorization of Multiparameter Persistent Homology using Signed Barcodes as Measures. *Advances in Neural Information Processing Systems*, 36, 68316–68342.
- Oudot, S., & Scoccola, L. (2024). On the Stability of Multigraded Betti Numbers and Hilbert Functions. *SIAM Journal on Applied Algebra and Geometry*, 8(1), 54–88. <https://doi.org/10.1137/22M1489150>
- Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch: An imperative style, high-performance deep learning library. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems* (pp. 8026–8037). Curran Associates Inc.
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, É. (2011). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research*, 12(85), 2825–2830.
- Robison, A. D. (2011). Intel® Threading Building Blocks (TBB). In D. Padua (Ed.), *Encyclopedia of Parallel Computing* (pp. 955–964). Springer US. [https://doi.org/10.1007/978-0-387-09766-4\\_51](https://doi.org/10.1007/978-0-387-09766-4_51)
- Rolle, A., & Scoccola, L. (2020). Stable and consistent density-based clustering via multiparameter persistence. *arXiv.org*. <https://doi.org/10.48550/arXiv.2005.09048>
- Scoccola, L., & Rolle, A. (2023). Persistable: Persistent and stable clustering. *Journal of Open Source Software*, 8(83), 5022. <https://doi.org/10.21105/joss.05022>
- Scoccola, L., Setlur, S., Loiseaux, D., Carrière, M., & Oudot, S. (2024). Differentiability and Optimization of Multiparameter Persistent Homology. *Proceedings of the 41st International Conference on Machine Learning*, 235, 43986–44011.
- TheGudhiProject. (2023). *GUDHI*. GUDHI Editorial Board.
- Vipond, O. (2020). Multiparameter persistence landscapes. *Journal of Machine Learning Research*, 21, 61:1–61:38.
- Xin, C., Mukherjee, S., Samaga, S. N., & Dey, T. K. (2023). GRIL: A  $\$2\$$ -parameter Persistence Based Vectorization for Machine Learning. *Proceedings of 2nd Annual Workshop on Topology, Algebra, and Geometry in Machine Learning (TAG-ML)*, 313–333.