

TEGAT: A Lightweight and Reusable Gateway for Scientific Sensor Networks

Lars Frölich^{1*}, Patrick Aigner^{1*}, and Jia Chen¹

¹ Environmental Sensing and Modeling, Technical University of Munich (TUM), Munich, Germany
Corresponding author * These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Abhishek Tiwari](#)

Reviewers:

- [@Puneetha-Ramachandra](#)
- [@Ahanaf-Aziz](#)
- [@brpat07](#)

Submitted: 04 June 2026

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

TEGAT (Telemetry Edge Gateway) is a lightweight, general-purpose open source software built for managing and monitoring networks of IoT devices. It is built to integrate with the ThingsBoard platform and was designed specifically for operating distributed sensor networks for scientific research. Originally developed for and validated in the ACROPOLIS urban CO2 sensor network, it is network-agnostic and can be used with a wide range of sensor hardware. TEGAT offers a stable and reusable architectural baseline for distributed sensor networks, enabling users to focus on application-specific logic while relying on a field-tested software solution for communication, data persistence, and remote management of sensor devices. It is designed to be robust against network and power outages, crashes, and other failures, thus reducing the risk of data loss, system downtime, or the need for physical intervention. Application-specific and hardware interfacing logic is delegated to a user-provided controller software which is managed and deployed by TEGAT, thus separating infrastructure and application logic.

Statement of need

Distributed sensor networks are a critical tool in scientific research and widely used across disciplines, enabling long-term, continuous sensor measurements. While they vary in the size and type of sensor hardware and data processing protocols used, such networks often face common infrastructure challenges: Physical access to sensor devices is often limited or costly, which can be exacerbated by challenges in scaling networks to large numbers of deployed sensors. Sensor networks often need to provide continuous measurements while operating unattended for extended periods of time, all while network connectivity and system power can be intermittent or unreliable. Although these challenges vary across deployments, they translate into a common set of infrastructure requirements:

- Reliable bidirectional communication
- Local buffering of data during network outages
- Remote configuration and maintenance capabilities
- Safe remotely initiated software updates
- Ability to recover from failures without physical intervention
- Seamless addition and removal of devices from the network

TEGAT addresses these infrastructure requirements to significantly reduce the engineering overhead associated with deploying and maintaining sensor networks. This enables network operators to focus on application-specific software instead. TEGAT leverages the ThingsBoard IoT platform (thingsboard contributors (2025)), a robust open source software, which was chosen for its maturity (10+ yrs in development) and scalability. The flexible design of TEGAT, combined with the ThingsBoard IoT platform, enables users to configure customized sensor

41 networks, seamlessly integrate additional sensors into existing networks, as well as making it
42 possible to reuse infrastructure across multiple research projects.

43 State of the Field

44 Other existing solutions already cover a variety of the features provided by the combination of
45 TEGAT and ThingsBoard, though there are different tradeoffs and limitations to consider with
46 each approach: Some solutions are designed around an on-site centralized “edge” server which
47 collects data from multiple connected sensor devices. Examples include thin-edge.io (thin-
48 edge.io contributors (2026)) and ThingsBoard’s own product Thingsboard Edge (thingsboard-
49 edge contributors (2026)). These architectures benefit from sensor network layouts where
50 many sensor devices share a local network, such as large factory or office buildings, but
51 face limitations when sensors are deployed individually in remote locations. Some subset of
52 our features can be covered with commercial solutions: For example, Amazon’s AWS IoT
53 (Amazon Web Services (2026)) and Microsoft Azure IoT Edge (azure-iotedge contributors
54 (2026)) products are IoT cloud-platforms similar to ThingsBoard, and Balena Cloud (Balena
55 (2025)) offers reliable device management and software updates of IoT device fleets similar to
56 TEGAT’s OTA and RPC functionality. However, projects building on top of such products
57 are dependent on their future pricing and availability, and require continuous funding. Finally,
58 a combination of open source solutions can offer a similar feature set: Examples are the
59 Eclipse Foundation’s Kura (kura contributors (2025)) and Kapua (kapua contributors (2024))
60 projects, as well as the Linux Foundation’s Fledge (fledge contributors (2025)) and Kube
61 Edge (kubedge contributors (2026)) projects. In both cases, these unfortunately lack data
62 visualization dashboards and software maturity. Finally, the Ivy project (Makowski & Chen
63 (2025)) doesn’t separate application and infrastructure logic, making software updates brittle.
64 For example, any crashes not covered by the test suite may result in permanent downtime
65 requiring on-site fixes.

66 Software Architecture

67 The software is based on a three-component architecture (see Figure 1):

- 68 ▪ (1) TEGAT (this software)
- 69 ▪ (2) Controller Software (user provided)
- 70 ▪ (3) ThingsBoard IoT Platform

71 Both TEGAT (1) and the Controller Software (2) are deployed on the same IoT sensor device,
72 with TEGAT acting as intermediary between the Controller Software and the ThingsBoard
73 platform which runs on a remote server. This design strictly separates the infrastructure and
74 application logic, and divides responsibilities between all three components: TEGAT (1) is
75 designed to be lightweight and robust, performing only essential functions like forwarding
76 telemetry to ThingsBoard and managing the deployment of the Controller Software. It
77 communicates with the ThingsBoard platform via a secure MQTT (MQTT.org (2024))
78 connection. The Controller Software (2) is provided by the user and is responsible for handling
79 application-specific logic such as controlling actuators and collecting and processing sensor
80 data. It is deployed inside a Docker (Merkel (2014)) container environment and communicates
81 with TEGAT via an intermediary database. Finally, the ThingsBoard platform (3) is deployed
82 remotely and acts as a centralized data storage and network management system. It is built
83 to be highly scalable, both in the number of connected devices and in the amount of data
84 received and stored. It is also highly customizable, supporting arbitrary sensor data formats
85 and protocols. Decoupling TEGAT from the Controller software ensures that corrective actions,
86 such as reverting to a stable software version or adjusting configurations, can be performed
87 remotely without risking system connectivity or requiring on-site intervention. In case a
88 newly deployed Controller Software version fails to start or contains errors, TEGAT remains

89 operational and continues to communicate with the ThingsBoard platform.




Figure 1: Software architecture for on-device (green) and off-premise (blue) components. Purple boxes show the three main architecture components TEGAT (1), Controller Software (2), and the ThingsBoard IoT Platform (3). Dashed boxes show local files.

90 Software Design and Implementation

91 The TEGAT software is written in Python (Python Software Foundation (2026)). It follows a
 92 modular design, encapsulating independent functionality such as logging, database access, or
 93 communication into separate software modules. During an initial setup phase, communication is
 94 established with the ThingsBoard platform using MQTT via TLS, and the device is provisioned
 95 in the ThingsBoard platform if needed. The software subsequently enters a steady-state main
 96 loop which performs one task per iteration, with higher priority tasks, such as processing
 97 incoming MQTT messages, executed first. This design ensures operational reliability and
 98 efficiency. TEGAT receives telemetry data from the Controller Software via a local sqlite
 99 database (Hipp & sqlite contributors (2026)), which is used to buffer messages between the

two software components for additional fault tolerance. TEGAT then forwards the telemetry data to the ThingsBoard platform via MQTT, and stores a copy of the data in a local database for additional redundancy (e.g. to backfill data gaps on-demand). TEGAT also manages the deployment of the Controller Software through the host system's Docker daemon: If the Controller Software's docker container is not running or has not provided a recent heartbeat, TEGAT attempts to start it using an exponential backoff strategy. Besides managing the Controller Software and forwarding telemetry data, TEGAT provides the following core features:

- (1) Remote procedure calls (RPC)
- (2) Over-the-air (OTA) updates of the Controller Software
- (3) Remote file management

RPCs (1) enable users to invoke one of several predefined commands on TEGAT, e.g. remotely rebooting the sensor device. This mechanism is primarily intended for operational control and diagnostics that must be executed on-demand without direct access to the device. The OTA update feature (2) enables users to remotely deploy new versions of the Controller Software to the device, for example to fix bugs or add new features. By the same mechanism, users can also easily downgrade the Controller Software back to a previous version if needed. This feature leverages the Git (Torvalds et al. (2026)) version control system to manage the software version history: Users can specify a specific commit hash or tag. TEGAT then builds a docker image based on the corresponding source code. TEGAT also provides a mechanism for directly creating, reading, and writing files on the sensor device using the remote file management feature (3). As Linux (Torvalds & linux kernel contributors (2026)) systems provide extensive access to operating system functionality through files, this feature has a particularly wide range of applications. Typical use cases are managing software configuration files for the Controller Software and configuring on-device drivers and system daemons. More technical details can be found in the documentation¹, which is built on Sphinx (KOMIYA et al. (2025)). To make TEGAT's source code more robust, its codebase is statically typed. Developers can perform local type checks using mypy (mypy contributors (2026)), which is also deployed as a continuous integration pipeline using GitHub actions. For integration testing, a demo application is provided which deploys a ThingsBoard server alongside TEGAT and an example implementation of the Controller Software. This example implementation also serves as a starting point for developers.

Research impact statement

TEGAT has been validated in the ACROPOLIS urban CO₂ sensor network (Aigner et al. (2026)) within the ICOS Cities project. ACROPOLIS-edge (Aigner et al. (2025)) serves as an example of a successful deployment of TEGAT in a real world use case. During this deployment, it continuously ran over 18 months across 17 devices, transmitted over 100 million messages to ThingsBoard, deployed over 250 OTA updates across the network, and processed over 1000 triggers from remote procedure calls and remote file management operations.

Author contributions

LF, PA, designed the software architecture, implemented the software, wrote documentation and user guides, deployed and validated the software as part of the ACROPOLIS sensor network, and wrote the manuscript. JC is the principal investigator and scientific lead of the ICOS cities project in Munich. All authors reviewed the manuscript.

¹<https://tum-esm.github.io/TEGAT/user-guide/>

Acknowledgements and funding

This work has been funded by: PAUL, Pilot Applications in Urban Landscapes – Towards integrated city observatories for greenhouse gases (ICOS Cities), funded by the European Union's Horizon 2020 Research and Innovation Programme (grant agreement no. 101037319). Furthermore, the work is partly supported by the HORIZON EUROPE European Research Council (ERC) consolidator grant CoSense4Climate (grant no. 101089203, PI: Jia Chen).

AI usage disclosure

Generative AI tools were used to assist with language refinement, formatting, and editorial support during manuscript preparation, and to aid documentation of the codebase and online materials. All AI-assisted outputs were reviewed and approved by the authors.

References

- Aigner, P., Chen, J., Böhm, F., Chariot, M., Emmenegger, L., Frölich, L., Grange, S., Kühbacher, D., Kürzinger, K., Laurent, O., Makowski, M., Rubli, P., Schmitt, A., & Wenzel, A. (2026). ACROPOLIS: Munich urban CO₂ sensor network. *Atmospheric Measurement Techniques*, 19(2), 745–773. <https://doi.org/10.5194/amt-19-745-2026>
- Aigner, P., Frölich, L., & Chen, J. (2025). ACROPOLIS-edge (Version 0.0.118). <https://doi.org/10.5281/zenodo.17913263>
- Amazon Web Services. (2026). *AWS-IoT: Unlock your IoT data and accelerate business growth*. <https://aws.amazon.com/iot>.
- azure-iotedge contributors. (2026). *Azure IoT Edge: The Azure IoT Edge product* (Version 1.5.39). <https://github.com/azure/azure-iotedge>
- Balena. (2025). *Belana cloud: The container-based platform for deploying IoT fleets*. <https://aws.amazon.com/iot>.
- fledge contributors. (2025). *FL Edge: An open source platform for the Industrial Internet of Things, it acts as an edge gateway between sensor devices and cloud storage systems*. (Version 3.1.0). <https://github.com/fledge-iot/fledge>
- Hipp, D. R., & sqlite contributors. (2026). *SQLite Source Repository: Official Git mirror of the SQLite source tree* (Version a2116f86b09b23220eb9dd94ba6a54e1450f0c67). <https://github.com/sqlite/sqlite>
- kapua contributors. (2024). *Eclipse Kapua* (Version 1.6.12). <https://github.com/eclipse-kapua/kapua>
- KOMIYA, T., Brandl, G., Turner, A., B., J.-F., SHIMIZUKAWA, T., Andersen, J. L., Neuhäuser, D., Finucane, S., Lehmann, R., jacobmason, Kampik, T., Addison, J., Magin, J., Dufresne, J., Waltman, J., danielades, Rodríguez, J. L. C., Ronacher, A., Geier, M., ... Freitag, F. (2025). *Sphinx-doc/sphinx: Sphinx 9.1.0* (Version v9.1.0). Zenodo. <https://doi.org/10.5281/zenodo.18109073>
- kubeedge contributors. (2026). *Cloud Native Computing Foundation: Kubernetes Native Edge Computing Framework (project under CNCF)* (Version 1.23.0). <https://github.com/kubeedge/kubeedge>
- kura contributors. (2025). *Eclipse Kura: The extensible open source Java/OSGi IoT Edge Framework* (Version 5.6.1). <https://github.com/eclipse-kura/kura>
- Makowski, M., & Chen, J. (2025). Ivy: A data acquisition system for distributed sensor networks supporting remote configuration and software updates. *Journal of Open Source*

- 186 Software, 10(114), 8862. <https://doi.org/10.21105/joss.08862>
- 187 Merkel, D. (2014). Docker: Lightweight linux containers for consistent development and
188 deployment. *Linux Journal*, 2014(239), 2.
- 189 MQTT.org. (2024). *MQTT specifications: MQTT is an OASIS standard. The specification is*
190 *managed by the OASIS MQTT technical committee.* <https://mqtt.org/mqtt-specification/>.
- 191 mypy contributors. (2026). *Mypy: Optional static typing for python* (Version 1.20.1).
192 <https://github.com/python/mypy>
- 193 Python Software Foundation. (2026). *Python 3.12.13.* <https://www.python.org/>.
- 194 thin-edge.io contributors. (2026). *thin-edge.io: The open edge framework for lightweight IoT*
195 *devices* (Version 2.0.0). <https://github.com/thin-edge/thin-edge.io>
- 196 thingsboard contributors. (2025). *ThingsBoard: Open-source IoT Platform - Device*
197 *management, data collection, processing and visualization.* (Version 4.2.1).
198 <https://github.com/thingsboard/thingsboard>
- 199 thingsboard-edge contributors. (2026). *ThingsBoard Edge: Open Source IoT Edge Computing*
200 *ThingsBoard Edge: IoT that works when the internet doesn't* (Version 4.3.1.1). <https://github.com/thingsboard/thingsboard-edge>
- 201
- 202 Torvalds, L., Hamano, J. C., & git contributors. (2026). *Git* (Version 2.53.0). [https://git-](https://git-scm.com/)
203 [scm.com/](https://git-scm.com/)
- 204 Torvalds, L., & linux kernel contributors. (2026). *Linux Kernel: Linux kernel source tree*
205 (Version 7.0). <https://github.com/torvalds/linux>