The Journal of Open Source Software

# substrateminer: A Python package to investigate protein substrate repertoires

**Robert QIAO** [1,2]

**1** School of Biological Sciences, Flinders University, Bedford Park, SA 5042, Australia **2** Digital Research Services, Flinders University, Bedford Park, SA 5042, Australia

**DOI:** 10.xxxxxx/draft

**Software**

- Review
- Repository
- Archive

**Editor:** Charlotte Soneson

**Reviewers:**

- @tushardave26
- @RiesBen

**Submitted:** 26 February 2025
**Published:** unpublished

**License**
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

## Abstract

`Substrateminer` is a Python library that provides a suite of modular investigative methods that are based on protein sequence and cellular properties to support rapid development of *in silico* pipelines to discover and interrogate potential substrates for a target protease of interest. Three categories of methods included in `substrateminer` are consensus analysis, substrate mining, and pathological investigation, which together provide a well-suited toolkit to explore substrate repertoires also known as substrate degradome for a target protease.

## Statement of need

The ability to identify and discover novel protease *in situ* substrates is often a powerful first step towards understanding the biological functions of proteases and their implications in human health and disease. However, in traditional enzymology, substrates of a target enzyme are studied in a one-to-one relationship, arguably due to prohibitive cost involved in designing and deploying experimental assays with large quantity. Modern proteomics methods particularly the advancement in mass spectrometry, drastically reduce the cost associated with detecting substrate hydrolysis events at molecular level and now the study of substrates of a target enzyme at proteome level is no longer a distant fantasy. With these new possibilities, the lack of a modular system to enable rapid development of *in silico* pipeline to support preliminary discovery has been a bottleneck for new studies. Therefore, the introduction of `substrateminer` here aims to provide a versatile toolkit that enables fast modular development of *in silico* pipelines to facilitate the preliminary discovery that complement and accelerate the emerging experimental efforts.

## Background

Proteolytic cleavage is a fundamental biochemical process in biology, which underpins many important biological processes that surround us from common food processing and digestion (Campbell & Reece, 2005) to cutting-edge industrial renewable energy production of cellulosic ethanol (Guo et al., 2023; Wright, 1988). Almost all proteolytic processes in nature are catalysed by enzymes and proteases are such an enzyme class that facilitates the biochemical reaction of cleaving peptide bonds. The inhibition of proteases has been a major intervention strategy in modern clinics to modulate molecular proteolytic processes to treat many physiological conditions including viral infections like HIV, hepatitis-C; metabolic dysfunctions like type-2 diabetes (Scott, 2017); and cancers (Manasanch & Orlowski, 2017). In the wake of the COVID-19 pandemic, proteases have emerged as a major therapeutic target for curbing fatality due to viral infections.(Borges et al., 2024; Papaneophytou, 2024; Sojka et al., 2021)

Nevertheless, one constraining factor that confronts the rapid development of protease inhibitory

The Journal of Open Source Software

therapy is the undiscriminating nature of inhibition. This is a major challenge because most proteases are involved in a complex network of biological processes and a complete inhibition of one protease can lead to unintended consequences on many other biological processes. Therefore, identifying and understanding the substrate degradome of a target protease is an important preliminary step towards inhibitory therapy. Traditionally, the identification of protease substrates is often challenging due to the prohibitive cost of large scale deployment of target-designed immuno-based biochemistry assays and scarcity of adequate animal models. Modern advancements in proteomics, particularly the maturation of mass spectrometry (Han et al., 2008) and soft-ionisation methods (Challen & Cramer, 2022), started to become a cost effective alternative in identification of protease substrates at a proteome level. Therefore, the ability to rapidly develop *in silico* pipelines to support preliminary discovery of protease substrates is increasingly needed to complement the emerging experimental efforts. Here, the introduction of `substrateminer` aims to streamline the modular development of *in silico* pipelines for the preliminary discovery of substrate degradome for a target protease based on cleavage sequence consensus.

# Methods

`Substrateminer` contains three main classes of functions (with a schematic depicted in Figure 1), namely consensus investigation (via submodules msa and consensus), substrate mining (via submodule miner) and substrate biopathological pathway searching (via submodule pathfinder).




**Figure 1:** Substrateminer workflow

A typical workflow for adopting `substrateminer` to investigate substrate degradome for a given protease often involves the following three main stages:

## Consensus investigation

`Substrateminer` provides a mechanism to visualise the cleavage consensus motif and calculate the strength of conservation at each site along the motif. The strength of conservation is calculated based on entropy and `substrateminer` is also packaged with auxiliary tools to provide multi-sequence alignment (MSA) access to help prepare the input data for consensus investigation. Consensus visualisation is created by calling implementation of weblogo (Crooks et al., 2004). (Figure 2)

As of the current release, `substrateminer` supports two popular multi-alignment tools for proteins, namely `MUSCLE` (on default) (Edgar, 2004) and `MAFFT` (Katoh et al., 2002), while the Linux distribution supports additional implementation of `Clustal0` (Sievers & Higgins, 2014). The cleavage motif consensus is calculated based on the frequency of amino acid residues at

DRAFT

each position along the motif and the visualisation is proportional to the information content at each site. The information content $R$ at position $i$ for protein is defined by Equation 1:

$$R_i = -\log_2(20) - H(X_i) \tag{1}$$

The strength of conservation is calculated based on Shannon entropy (Shannon, 1948) with the formulation in Equation 2, and the consensus motif is defined as the most frequent amino acid residue at each position along the motif.

$$H(X) = -\sum_{i=1}^{n} p_i \log_2 p_i \tag{2}$$




**Figure 2:** Consensus investigation - Visualisation Example

## Substrate mining

Upon the identification of a cleavage consensus, `substrateminer` provides a mechanism to mine potential substrates based on three filter strategies:

1. *Cellular location*: filter potential substrates based on the cellular localisation of the intended target. For example, if the target protease is a secreted protease, the substrates mined should be extracellular proteins.
2. *Target Size*: filter potential substrates based on the size of the intended target. For example, if the target substrate is a small protease, the substrates mined should be small proteins or peptides of a specified size.
3. *Consensus*: filter potential substrates based on the conservation of the cleavage consensus. At the current release, both intra-protein cleavage (i.e., endopeptidase) and terminal cleavage (both C and N-terminal) (i.e., exopeptidase) consensus are supported.

## Substrate pathobiological pathway searching

To further investigate the pathobiological relevance of novel substrates, `substrateminer` implemented a search strategy to retrieve known biological processes and disease associations based on the *de facto* standard KEGG database (Kanehisa, 2019; Kanehisa & Goto, 2000). In this present release, the `pathfinder` module in the `substrateminer` provides three main functions namely KEGG accession conversion, biological processes tracing and human disease mapping, where KEGG accession conversion enables a gateway to KEGG databases where further information including enzyme nomenclature and diseases-related network databases can be easily accessible. Biological processes tracing allows users to trace the biological processes associated with a given substrate, and human disease mapping enables users to map the potential substrates to known human diseases based on KEGG disease database.

DRAFT

As of the current release, `pathfinder` submodule queries all 580 KEGG molecular pathway maps and covers 1205 eukaryotes, 9375 bacteria and 449 archaea. (Kanehisa & Goto, 2025) Nevertheless, the diseases covered are limited to human context.

# Limitations

The current release of `substrateminer` is limited to the investigation of protease substrates based on substrate primary sequence consensus in model organisms. In cases where proteases have very loose consensus like metalloproteinase ADAM10(Caescu et al., 2009) that is arguably best-known for its protective effects in prion diseases like mad cow in cattle, additional structural factors and contexts may need to be taken into consideration. Additionally, the efficacy of `substrateminer` investigative power expanding beyond well-studied organisms is limited by the availability of a comprehensive proteome database for underlying species. In the future, we aim to expand the scope of `substrateminer` to scrutinise substrate structural characteristics and provide a more comprehensive suite of tools for substrate investigation.

# Conflict of Interests

The author declares no conflict of interests.

# References


Borges, P. H. O., Ferreira, S. B., & Silva, F. P. (2024). Recent advances on targeting proteases for antiviral development. *Viruses*, *16*(3). https://doi.org/10.3390/v16030366

Caescu, C. I., Jeschke, G. R., & Turk, B. E. (2009). Active-site determinants of substrate recognition by the metalloproteinases TACE and ADAM10. *Biochemical Journal*, *424*(1), 79–88. https://doi.org/10.1042/BJ20090549

Campbell, N. A., & Reece, J. B. (2005). *Biology*. Pearson, Benjamin Cummings. ISBN: 9780805371710

Challen, B., & Cramer, R. (2022). Advances in ionisation techniques for mass spectrometry-based omics research. *PROTEOMICS*, *22*(15-16), 2100394. https://doi.org/10.1002/pmic.202100394

Crooks, G. E., Hon, G., Chandonia, J.-M., & Brenner, S. E. (2004). WebLogo: A sequence logo generator. *Genome Research*, *14*(6), 1188–1190. https://doi.org/10.1101/gr.849004

Edgar, R. C. (2004). MUSCLE: Multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Research*, *32*(5), 1792–1797. https://doi.org/10.1093/nar/gkh340

Guo, H., Zhao, Y., Chang, J.-S., & Lee, D.-J. (2023). Enzymes and enzymatic mechanisms in enzymatic degradation of lignocellulosic biomass: A mini-review. *Bioresource Technology*, *367*, 128252. https://doi.org/10.1016/j.biortech.2022.128252

Han, X., Aslanian, A., & Yates, J. R. (2008). Mass spectrometry for proteomics. *Current Opinion in Chemical Biology*, *12*(5), 483–490. https://doi.org/10.1016/j.cbpa.2008.07.024

Kanehisa, M. (2019). Toward understanding the origin and evolution of cellular organisms. *Protein Science*, *28*(11), 1947–1951. https://doi.org/10.1002/pro.3715

Kanehisa, M., & Goto, S. (2000). KEGG: Kyoto Encyclopedia of Genes and Genomes. *Nucleic Acids Research*, *28*(1), 27–30. https://doi.org/10.1093/nar/28.1.27

Kanehisa, M., & Goto, S. (2025). *KEGG database current statistics*. Kanehisa Laboratories. https://www.genome.jp/kegg/docs/statistics.html


DRAFT

Katoh, K., Misawa, K., Kuma, K., & Miyata, T. (2002). MAFFT: A novel method for rapid multiple sequence alignment based on fast fourier transform. *Nucleic Acids Research*, *30*(14), 3059–3066. https://doi.org/10.1093/nar/gkf436

Manasanch, E. E., & Orlowski, R. Z. (2017). Proteasome inhibitors in cancer therapy. *Nature Reviews Clinical Oncology*, *14*, 417–433. https://doi.org/10.1038/nrclinonc.2016.206

Papaneophytou, C. (2024). Breaking the chain: Protease inhibitors as game changers in respiratory viruses management. *International Journal of Molecular Sciences*, *25*(15). https://doi.org/10.3390/ijms25158105

Scott, L. J. (2017). Sitagliptin: A review in type 2 diabetes. *Drugs*, *77*, 209–224. https://doi.org/10.1007/s40265-016-0686-9

Shannon, C. E. (1948). A mathematical theory of communication. *The Bell System Technical Journal*, *27*(3), 379–423. https://doi.org/10.1002/j.1538-7305.1948.tb01338.x

Sievers, F., & Higgins, D. G. (2014). Clustal omega. *Current Protocols in Bioinformatics*, *48*(1), 3.13.1–3.13.16. https://doi.org/10.1002/0471250953.bi0313s48

Sojka, D., Šnebergerová, P., & Robbertse, L. (2021). Protease inhibition—an established strategy to combat infectious diseases. *International Journal of Molecular Sciences*, *22*(11). https://doi.org/10.3390/ijms22115762

Wright, J. D. (1988). Ethanol from biomass by enzymatic hydrolysis. *Chem. Eng. Prog.; (United States)*, *84:8*. https://www.osti.gov/biblio/6943966

DRAFT