The Journal of Open Source Software

TorchSurv: A Lightweight Package for Deep Survival Analysis

Mélodie Monod [1], **Peter Krusche**[1], **Qian Cao**[2], **Berkman Sahiner**[2], **Nicholas Petrick**[2], **David Ohlssen**[3], **and Thibaud Coroller** [3¶]

1 Novartis Pharma AG, Switzerland **2** Center for Devices and Radiological Health, Food and Drug Administration, MD, USA **3** Novartis Pharmaceuticals Corporation, NJ, USA ¶ Corresponding author

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Kanishka B. Narayan

Submitted: 24 July 2024
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

TorchSurv is a Python package that serves as a companion tool to perform deep survival modeling within the PyTorch environment (Paszke et al., 2019). With its lightweight design, minimal input requirements, full PyTorch backend, and freedom from restrictive parameterizations, TorchSurv facilitates efficient deep survival model implementation and is particularly beneficial for high-dimensional and complex data scenarios. At its core, TorchSurv features calculations of log-likelihoods for prominent survival models (Cox proportional hazards model (Cox, 1972), Weibull Accelerated Time Failure (AFT) model (Carroll, 2003)) and offers evaluation metrics, including the time-dependent Area Under under the Receiver operating characteristic (ROC) curve (AUC), the Concordance index (C-index) and the Brier Score. TorchSurv has been rigorously tested using both open-source and synthetically generated survival data, against R and python packages. The package is thoroughly documented and includes illustrative examples. The latest documentation for TorchSurv can be found on our website.

Statement of need

Survival analysis plays a crucial role in various domains, such as medicine, economics or engineering. Thus, sophisticated survival models sugin deep learning opens new opportunities to leverage complex dataset and relationships. However, no existing library provides the flexibility to define the survival model's parameters using a custom PyTorch-based neural network.

Figure 1 compares the functionalities of TorchSurv with those of auton-survival (Nagpal et al., 2022), pycox (Kvamme et al., 2019), torchlife (Abeywardana, 2021), scikit-survival (Pölsterl, 2020), lifelines (Davidson-Pilon, 2019), and deepsurv (Katzman et al., 2018). Existing libraries constrain users to predefined forms for defining the parameters (e.g., linear function of covariates). While there exist log-likelihood functions in the libraries, they cannot be leveraged. The limitations on the log-likelihood functions include protected functions (locked model architecture), specialized input requirements (format or class type), and reliance on external libraries like NumPy or Pandas. Dependence on external libraries hinders automatic gradient calculation within PyTorch. Additionally, the implementation of likelihood functions instead of log-likelihood functions, as done by some packages, introduces numerical instability.

The Journal of Open Source Software

	TorchSurv	auton_survival[1]	pycox[2]	torchlife[3]	scitkit-survival[4]	lifelines[5]	deepsurv[6]
PyTorch	✓	✓	✓	✓	✗	✗	✗
Standalone loss functions							
Weibull loss function	✓	✗	✗	✓	✗	✓	✗
Cox loss function	✓	✓	✓	✓	✓	✓	✗
Handle ties in event time	✓	✗	✗	✗	✓̸	✓	✗
Logarithm scale	✓	✓	✓	✗	✓	✓	✗
Standalone evaluation metrics							
Concordance index	✓	✗	✓̸	✗	✓	✓	✗
AUC	✓	✗	✗	✗	✓	✗	✗
Brier-Score	✓	✗	✓	✗	✓	✗	✗
Time-dependent risk score	✓	✗	✓̸	✗	✓̸	✗	✗
Subject-specific weights	✓	✗	✓̸	✗	✓̸	✗	✗
Confidence interval	✓	✗	✗	✗	✗	✗	✗
Compare two metrics	✓	✗	✗	✗	✗	✗	✗
Momentum	✓	✗	✗	✗	✗	✗	✗

Figure 1: Survival analysis libraries in Python. [1](Nagpal et al., 2022), [2](Kvamme et al., 2019), [3](Abeywardana, 2021), [4](Pölsterl, 2020), [5](Davidson-Pilon, 2019), [6](Katzman et al., 2018). A green tick indicates a fully supported feature, a red cross indicates an unsupported feature, a blue crossed tick indicates a partially supported feature. For computing the concordance index, `pycox` requires the use of the estimated survival function as the risk score and does not support other types of time-dependent risk scores. `scikit-survival` does not support time-dependent risk scores in both the concordance index and AUC computation. Additionally, both `pycox` and `scikit-survival` impose the use of inverse probability of censoring weighting (IPCW) for subject-specific weights. `scikit-survival` only offers the Breslow approximation of the Cox partial log-likelihood in case of ties in the event time.

	TorchSurv	survival[1]	survAUC[2]	timeROC[3]	RisksetROC[4]	survcomp[5]
Standalone evaluation metrics						
Concordance index	✓	✓̸	✓	✗	✓̸	✓
AUC	✓	✗	✓	✓	✓̸	✓̸
Brier-Score	✓	✗	✓	✗	✗	✗
Time-dependent risk score	✓	✓	✗	✗	✗	✗
Subject-specific weights	✓	✓	✓	✓̸	✗	✗
Confidence interval	✓	✗	✗	✓	✗	✓
Compare two metrics	✓	✗	✗	✓	✗	✓
Competing risks setting	✗	✗	✗	✓	✗	✗

	TorchSurv	SurvivalROC[6]	riskRegression[7]	SurvMetrics[8]	pec[9]
Standalone evaluation metrics					
Concordance index	✓	✗	✗	✓̸	✓̸
AUC	✓	✓̸	✓̸	✗	✗
Brier-Score	✓	✗	✓̸	✓̸	✓̸
Time-dependent risk score	✓	✗	✓̸	✓	✓
Subject-specific weights	✓	✗	✓̸	✗	✓̸
Confidence interval	✓	✗	✓	✗	✓
Compare two metrics	✓	✗	✓	✗	✗
Competing risks setting	✗	✗	✓	✓	✓

Figure 2: Survival analysis libraries in R. [1](Therneau, 2024), [2](Potapov et al., 2023), [3](Blanche, 2019), [4](Heagerty, 2022a), [5](Schröder et al., 2011), [6](Heagerty, 2022b), [7](Thomas Alexander Gerds et al., 2023), [8](Zhou et al., 2022), [9](Thomas A. Gerds, 2023). A green tick indicates a fully supported feature, a red cross indicates an unsupported feature, a blue crossed tick indicates a partially supported feature. For obtaining the evaluation metrics, packages `survival`, `riskRegression`, `SurvMetrics` and `pec` require the fitted model object as input (a specific object format) and `RisksetROC` imposes to use a smoothing method. Packages `timeROC`, `riskRegression` and `pec` force the user to choose a form for subject-specific weights (e.g., inverse probability of censoring weighting (IPCW)). Packages `survcomp` and `SurvivalROC` do not implement the general AUC but the censoring-adjusted AUC estimator proposed by Heagerty et al. (2000).

Functionality

Loss functions

Cox loss function is defined as the negative of the Cox proportional hazards model's partial log-likelihood (Cox, 1972). The function requires the subject-specific log relative hazards and the survival response (i.e., event indicator and time-to-event or censoring). In case of ties in the event times, the user can choose between the Breslow method (Breslow, 1975) and the Efron method (Efron, 1977) to approximate the Cox partial log-likelihood.

```
from torchsurv.loss import cox

# PyTorch model outputs ONE log hazard per observation
my_model = MyPyTorchCoxModel()

for data in dataloader:
    x, event, time = data  # covariate, event indicator, time
    log_hzs = my_model(x)  # torch.Size([64, 1]), if batch size is 64
    loss = cox.neg_partial_log_likelihood(log_hzs, event, time)
    loss.backward()  # native torch backend
```

Weibull loss function is defined as the negative of the Weibull AFT's log-likelihood (Carroll, 2003). The function requires the subject-specific log parameters of the Weibull distribution (i.e., the log scale and the log shape) and the survival response. The log parameters of the Weibull distribution should be obtained from a PyTorch-based model pre-specified by the user.

```
from torchsurv.loss import weibull

# PyTorch model outputs TWO Weibull parameters per observation
my_model = MyPyTorcWeibullhModel()

for data in dataloader:
    x, event, time = data
    log_params = my_model(x)  # torch.Size([64, 2]), if batch size is 64
    loss = weibull.neg_log_likelihood(log_params, event, time)
    loss.backward()
```

Momentum helps training model when the batch size is greatly limited by computational resources (i.e. large files). This impacts the stability of model optimization, especially when rank-based loss is used. Inspired from MoCO (He et al., 2020), we implemented a momentum loss that decouples batch size from survival loss, increasing the effective batch size and allowing robust train of a model, even when using a very limited batch size (e.g., ≤ 16).

```
from torchsurv.loss import Momentum
my_model = MyPyTorchXCoxModel()
my_loss = cox.neg_partial_log_likelihood  # Works with any TorchSurv loss
momentum = Momentum(backbone=my_model, loss=my_loss)

for data in dataloader:
    x, event, time = data
    loss = model_momentum(x, event, time)  # torch.Size([16, 1])
    loss.backward()

# Inference is computed with target network (k)
log_hzs = model_momentum.infer(x)  # torch.Size([16, 1])
```

DRAFT

Evaluation Metrics Functions

The `TorchSurv` package offers a comprehensive set of metrics to evaluate the predictive performance of survival models, including the `AUC`, `C-index`, and `Brier score`. The inputs of the evaluation metrics functions are the subject-specific risk score estimated on the test set and the survival response on the test set. The risk score measures the risk (or a proxy thereof) that a subject has an event. We provide definitions for each metric and demonstrate their use through illustrative code snippets.

AUC. The AUC measures the discriminatory capacity of the survival model at a given time t, i.e., the ability to provide a reliable ranking of times-to-event based on estimated subject-specific risk scores (Blanche et al., 2013; Heagerty & Zheng, 2005; Uno et al., 2007).

```
from torchsurv.metrics import Auc
auc = Auc()
auc(log_hzs, event, time)  # AUC at each time
auc(log_hzs, event, time, new_time=torch.tensor(10.))  # AUC at time 10
```

C-index. The C-index is a generalization of the AUC that represents the assessment of the discriminatory capacity of the survival model across the entire time period (Harrell et al., 1996; Uno et al., 2011).

```
from torchsurv.metrics import ConcordanceIndex
cindex = ConcordanceIndex()
cindex(log_hzs, event, time)
```

Brier Score. The Brier score evaluates the accuracy of a model at a given time t (Graf et al., 1999). It represents the average squared distance between the observed survival status and the predicted survival probability. The Brier score cannot be obtained for the Cox proportional hazards model because the survival function is not available, but it can be obtained for the Weibull ATF model.

```
from torchsurv.metrics import Brier
surv = survival_function(log_params, time)
brier = Brier()
brier(surv, event, time)  # Brier score at each time
brier.integral()  # Integrated Brier score over time
```

Additional features. In `TorchSurv`, the evaluation metrics can be obtained for time-dependent and time-independent risk scores (e.g., for proportional and non-proportional hazards). Additionally, subjects can be optionally weighted (e.g., by the inverse probability of censoring weighting (IPCW)). Lastly, functionalities including the confidence interval, one-sample hypothesis test to determine whether the metric is better than that of a random predictor, and two-sample hypothesis test to compare two evaluation metrics between different models are implemented. The following code snippet exemplifies the aforementioned functionalities for the C-index.

```
cindex.confidence_interval()  # CI, default alpha=.05
cindex.p_value(alternative='greater')  # pvalue, H0:c=0.5, HA:c>0.5
cindex.compare(cindex_other)  # pvalue, H0:c1=c2, HA:c1>c2
```

Conflicts of interest

MM, PK, DO and TC are employees and stockholders of Novartis, a global pharmaceutical company.

DRAFT

References

Abeywardana, S. (2021). *Torchlife: Survival analysis using pytorch*. https://doi.org/10.32614/CRAN.package.survival

Blanche, P. (2019). *Time-dependent ROC curve and AUC for censored survival data*. https://doi.org/10.32614/CRAN.package.timeROC

Blanche, P., Dartigues, J., & Jacqmin-Gadda, H. (2013). Review and comparison of ROC curve estimators for a time-dependent outcome with marker-dependent censoring. *Biometrical Journal*, *55*(5), 687–704. https://doi.org/10.1002/bimj.201200045

Breslow, N. E. (1975). Analysis of survival data under the proportional hazards model. *International Statistical Review / Revue Internationale de Statistique*, *43*(1), 45. https://doi.org/10.2307/1402659

Carroll, K. J. (2003). On the use and utility of the weibull model in the analysis of survival data. *Controlled Clinical Trials*, *24*(6), 682–701. https://doi.org/10.1016/s0197-2456(03)00072-2

Cox, D. R. (1972). Regression models and life-tables. *Journal of the Royal Statistical Society: Series B (Methodological)*, *34*(2), 187–202. https://doi.org/10.1007/978-1-4612-4380-9_37

Davidson-Pilon, C. (2019). Lifelines: Survival analysis in python. *Journal of Open Source Software*, *4*(40), 1317. https://doi.org/10.21105/joss.01317

Efron, B. (1977). The efficiency of cox's likelihood function for censored data. *Journal of the American Statistical Association*, *72*(359), 557–565. https://doi.org/10.1080/01621459.1977.10480613

Gerds, Thomas A. (2023). *Prediction error curves for risk prediction models in survival analysis*. https://doi.org/10.32614/CRAN.package.pec

Gerds, Thomas Alexander, Ohlendorff, J. S., Blanche, P., Mortensen, R., Wright, M., Tollenaar, N., Muschelli, J., Mogensen, U. B., & Ozenne, B. (2023). *Risk regression models and prediction scores for survival analysis with competing risks*. https://doi.org/10.32614/CRAN.package.riskRegression

Graf, E., Schmoor, C., Sauerbrei, W., & Schumacher, M. (1999). Assessment and comparison of prognostic classification schemes for survival data. *Statistics in Medicine*, *18*(17–18), 2529–2545. https://doi.org/10.1002/(sici)1097-0258(19990915/30)18:17/18%3C2529::aid-sim274%3E3.0.co;2-5

Harrell, F. E., Lee, K. L., & Mark, D. B. (1996). Multivariate prognostic models: Issues in developing models, evaluating assumptions and adequacy, and measuring and reducing errors. *Statistics in Medicine*, *15*(4), 361–387. https://doi.org/10.1002/(sici)1097-0258(19960229)15:4%3C361::aid-sim168%3E3.0.co;2-4

He, K., Fan, H., Wu, Y., Xie, S., & Girshick, R. (2020). Momentum contrast for unsupervised visual representation learning. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 9729–9738. https://doi.org/10.1109/cvpr42600.2020.00975

Heagerty, P. J. (2022a). *Riskset ROC curve estimation from censored survival data*. https://doi.org/10.32614/CRAN.package.risksetROC

Heagerty, P. J. (2022b). *Time-dependent ROC curve estimation from censored survival data*. https://doi.org/10.32614/CRAN.package.survivalROC

Heagerty, P. J., Lumley, T., & Pepe, M. S. (2000). Time-dependent ROC curves for censored survival data and a diagnostic marker. *Biometrics*, *56*(2), 337–344. https://doi.org/10.1111/j.0006-341x.2000.00337.x

DRAFT

Heagerty, P. J., & Zheng, Y. (2005). Survival model predictive accuracy and ROC curves. *Biometrics*, *61*(1), 92–105. https://doi.org/10.1111/j.0006-341x.2005.030814.x

Katzman, J. L., Shaham, U., Cloninger, A., Bates, J., Jiang, T., & Kluger, Y. (2018). DeepSurv: Personalized treatment recommender system using a cox proportional hazards deep neural network. *BMC Medical Research Methodology*, *18*(1), 1–12. https://doi.org/10.1186/s12874-018-0482-1

Kvamme, H., Borgan, Ørnulf, & Scheel, I. (2019). Time-to-event prediction with neural networks and cox regression. *Journal of Machine Learning Research*, *20*(129), 1–30. http://jmlr.org/papers/v20/18-424.html

Nagpal, C., Potosnak, W., & Dubrawski, A. (2022). Auton-survival: An open-source package for regression, counterfactual estimation, evaluation and phenotyping with censored time-to-event data. *Machine Learning for Healthcare Conference*, 585–608. https://doi.org/10.48550/arXiv.2204.07276

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S. (2019). *PyTorch: An imperative style, high-performance deep learning library*. https://doi.org/10.48550/arXiv.1912.01703

Pölsterl, S. (2020). Scikit-survival: A library for time-to-event analysis built on top of scikit-learn. *The Journal of Machine Learning Research*, *21*(1), 8747–8752. https://doi.org/10.5281/zenodo.3352342

Potapov, S., Adler, W., & Schmid, M. (2023). *Estimators of prediction accuracy for time-to-event data*. https://doi.org/10.32614/CRAN.package.survAUC

Schröder, M. S., Culhane, A. C., Quackenbush, J., & Haibe-Kains, B. (2011). Survcomp: An r/bioconductor package for performance assessment and comparison of survival models. *Bioinformatics*, *27*(22), 3206–3208. https://doi.org/10.1093/bioinformatics/btr511

Therneau, T. M. (2024). *A package for survival analysis in r*. https://doi.org/10.32614/CRAN.package.survival

Uno, H., Cai, T., Pencina, M. J., D'Agostino, R. B., & Wei, L. J. (2011). On the c-statistics for evaluating overall adequacy of risk prediction procedures with censored survival data. *Statistics in Medicine*, *30*(10), 1105–1117. https://doi.org/10.1002/sim.4154

Uno, H., Cai, T., Tian, L., & Wei, L. J. (2007). Evaluating prediction rules fort-year survivors with censored regression models. *Journal of the American Statistical Association*, *102*(478), 527–537. https://doi.org/10.1198/016214507000000149

Zhou, H., Cheng, X., Wang, S., Zou, Y., & Wang, H. (2022). *Predictive evaluation metrics in survival analysis*. https://doi.org/10.32614/CRAN.package.SurvMetrics

DRAFT