

1 utdf2gmns: A Python Package for Mobility Simulation 2 from UTDF to SUMO

Xiangyong Luo¹, **Yiran Zhang**², and **Xuesong (Simon) Zhou**³

⁴ **1** Oak Ridge National Laboratory, United States **2** University of Washington, Seattle, WA, United States

5 **3 Arizona State University, Tempe, AZ, United States**

DOI: [10.xxxxxx/draft](#)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: Fangzhou Xie

Reviewers:

- @anitagraser
- @georgiastuart

Submitted: 11 April 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).

6 Summary

UTDF2GMNS¹ implements an automated workflow for network coordination, traffic signal integration, and traffic flow conversion from Synchro to SUMO. The process begins with a comparative analysis of network topologies, data representations, and signal timing schemas in both environments. Converting Synchro UTDF data to a network ready for microsimulation poses several challenges, including accurate signal integration, spatial transformation, and preservation of turning flow fidelity. Signal conversion represents a primary bottleneck, as it demands precise mapping of phasing plans, timing parameters, and coordination strategies to ensure valid simulation results. Network conversion is further complicated by translating Synchro's relative coordinate system into georeferenced formats compatible with geographic information system tools. Furthermore, accurate transformation of turning movement data is essential for realistic intersection modeling.

Existing methods address only isolated conversion tasks and lack a fully automated, scalable end-to-end workflow. To fill this gap, we introduce [utdf2gmns](#), an open-source Python library that automates the transformation of Synchro UTDf files into GMNS-compliant SUMO networks. [utdf2gmns](#) provides automatic geocoding, Sigma-X engine integration for intersection analysis, robust SUMO network generation, and extensibility to other microsimulation platforms. Future work will extend support for adaptive signal control, integrate real-time data inputs, and enhance interoperability with additional simulation frameworks to promote reproducibility and collaborative traffic-modeling research.

26 Statement of need

Traffic microsimulation is essential for evaluating and improving urban transportation systems by providing high-resolution analysis of flow, congestion, and infrastructure performance. Such simulations depend on precise modeling of signal control, network geometry, and turning movements. Although Synchro's Universal Traffic Data Format (UTDF) delivers comprehensive intersection data, converting UTDF into simulation-ready networks remains manual, labor-intensive, and error-prone, limiting seamless interoperability with microsimulation platforms.

Several critical challenges remain when converting Synchro UTDF data into microsimulation-compatible networks, such as those required by Simulation of Urban Mobility (SUMO) (Lopez et al., 2018). First, accurate signal conversion demands detailed extraction and mapping of phasing, timing, and coordination parameters into standardized control formats; errors here can substantially degrade simulation fidelity. Second, network conversion requires transforming Synchro’s relative coordinate system into georeferenced longitude–latitude coordinates for

¹This manuscript has been authored in part by UT-Battelle, LLC, under contract DE-AC05-00OR22725 with the US Department of Energy (DOE). The publisher acknowledges the US government license to provide public access under the [DOE Public Access Plan](#)

39 seamless GIS integration, a labor-intensive and error-prone process that limits scalability. Third,
40 realistic intersection dynamics hinge on precise turning movement conversion, which typically
41 involves extensive manual preprocessing; inaccuracies at this stage can propagate through the
42 simulation, undermining the validity of subsequent analyses.

43 To address these gaps(Ban et al., 2022; Coogan et al., 2021; Singh et al., 2017; Udomsilp et
44 al., 2017; Zhang et al., 2024), we present utdf2gmns (Luo and Zhou 2022), an open-source
45 Python tool that automates the conversion of Synchro UTDF files into GMNS-compliant
46 networks (Smith et al., 2020) and generates simulation-ready inputs for SUMO. By leveraging
47 the GMNS, a robust framework for standardized network representation (Berg et al., 2022;
48 Lu & Zhou, 2023; Luo, 2024; Luo et al., 2024), utdf2gmns enhances data consistency,
49 reproducibility, and collaboration through four core capabilities: it automates geocoding
50 of Synchro's relative coordinates into accurate longitude–latitude pairs; integrates with the
51 Sigma-X engine (Milan 2022) to extract and optimize key intersection metrics (phasing
52 diagrams, turning volumes, movement capacities, volume-to-capacity ratios, and control delays);
53 generates GMNS-compliant SUMO networks that fully preserve signal coordination, traffic
54 flows, and turning movements; and provides a modular architecture for extension to additional
55 microsimulation platforms, thereby promoting broader standardization and community-driven
56 development.

57 For detailed documentation, please refer to [Official Documentation](#)

58 State of the field

59 Traffic microsimulation scenarios are commonly created from open GIS/map data, built directly
60 in a simulator's native formats, or derived from proprietary planning and operations tools. GIS-
61 based pipelines scale well for network geometry, but key operational inputs (turning movements,
62 lane connectivity, detectors, and signal timing) are typically added manually. When a study
63 starts from Synchro exports, UTDF provides many of these operational details, but they are
64 not available in an open-source simulator-ready representation.

65 SUMO offers flexible signal control modeling and is widely used for research on controller
66 representation and validation (Halbach & Erdmann, 2022; Schrader et al., 2022). These
67 capabilities primarily address how to represent and execute control once a scenario is specified;
68 they do not provide a standard, reusable pathway for translating Synchro's phasing, timing,
69 and coordination plans from UTDF into consistent, reproducible simulation inputs.

70 To our knowledge, there is no commonly used research software package that converts Synchro
71 UTDF directly into a complete, SUMO-ready simulation scenario (network, flows, and signal
72 control). Instead, published and practical workflows are typically assembled from project-
73 specific scripts and manual steps, and they often cover only subsets of the required information
74 (e.g., geometry, turning counts, or a subset of timing). Extending general-purpose GIS/OSM
75 import utilities is therefore insufficient: supporting UTDF requires a dedicated parser and a
76 semantics-preserving mapping of signal control and demand, plus validation tooling to ensure
77 fidelity across intersections and time plans.

78 utdf2gmns provides this missing conversion layer as an end-to-end workflow from Synchro
79 UTDF to a standardized intermediate representation (GMNS) and then to simulation-ready
80 SUMO artifacts. The software's contribution is a reproducible translation of UTDF operational
81 semantics (signal structure, timing/coordination plans, and turning movement demand) into
82 open outputs suitable for large-scale scenario generation and comparative experiments, with
83 optional Sigma-X integration to support intersection-level diagnostics and auditing.

Software design

The `utdf2gmns` package is designed with a modular architecture to facilitate the conversion of Synchro UDF data into GMNS-compliant networks and SUMO simulations. The core component is the `UTDF2GMNS` class, which orchestrates the entire conversion process through a series of method calls. The software is organized into several key modules:

- **Main Module (`_utdf2gmns.py`):** Contains the primary `UTDF2GMNS` class, which initializes with UDF file paths and region names. It provides high-level methods such as `geocode_udf_intersections()`, `udf_to_gmns()`, and `udf_to_sumo()` to perform the conversions.
- **Functional Libraries (`func_lib/`):** Divided into submodules for specific functionalities:
 - `udf/`: Handles reading and processing UDF data, including geocoding intersections and converting lane data.
 - `gmns/`: Manages the conversion to GMNS format, including node and link generation, and integration with the Sigma-X engine for signal intersection processing.
 - `sumo/`: Generates SUMO-compatible XML files for nodes, edges, connections, and traffic flows, while also handling signal controls and U-turn removal.
 - `plot_net.py`: Provides visualization capabilities using libraries like Matplotlib and Kepler.gl.
- **Utility Libraries (`util_lib/`):** Includes helper functions for tasks such as distance calculations, time conversions, and package settings.
- **Engine (`engine/`):** Integrates the Sigma-X engine for advanced signalized intersection analysis, enabling the extraction of phasing diagrams, turning volumes, and control delays.

This modular design ensures extensibility, allowing users to customize or extend functionalities for other microsimulation platforms. The package leverages external libraries like Pandas for data manipulation and `pyufunc` for utility functions, promoting code reusability and maintainability.

Research impact statement

The `utdf2gmns` package has demonstrated impact in traffic microsimulation by facilitating the conversion of Synchro UDF data into SUMO-compatible networks. A peer-reviewed Winter Simulation Conference paper presents `utdf2gmns` as an automated workflow for converting UDF network representation, signalized intersections, and turning volumes into GMNS-compliant SUMO inputs, and reports case-study validation for complex urban corridors (Luo et al., 2025). The same workflow directly addresses the manual Synchro-to-SUMO preparation steps identified in earlier traffic simulation studies (Singh et al., 2017; Udomsilp et al., 2017; Zhang et al., 2024).

Furthermore, the integration of `utdf2gmns` with the Sigma-X engine supports visualization and auditing of signalized intersections, including phasing diagrams, turning volumes, volume-to-capacity ratios, and control delays (Luo et al., 2025). These capabilities provide practical tools for urban planners, traffic engineers, and researchers who need reproducible network preparation rather than project-specific scripts.

`utdf2gmns` has been downloaded more than 36,000 times from PyPI as of June 16, 2026 (PePy.tech, 2026), indicating sustained use within the transportation modeling and microsimulation community. This adoption highlights `utdf2gmns` as a community-facing tool that lowers barriers to data preparation and reproducible simulation workflows.

128 Hands-On tutorial

```
import utdf2gmns as ug

if __name__ == "__main__":

    region_name = " Bullhead City, AZ"
    path_utdf = "datasets/data_bullhead_seg4/UTDF.csv"

    # Step 1: Initialize the UTDF2GMNS
    net = ug.UTDF2GMNS(utdf_filename=path_utdf, region_name=region_name)

    # Step 2: Geocode intersections from one known intersection coordinate
    single_coord = {
        "INTID": "39",
        "x_coord": -114.59807666698381,
        "y_coord": 35.02605198650903,
    }
    net.geocode_utdf_intersections(single_intersection_coord=single_coord)

    # Step 3: convert UTDF network to GMNS format (csv)
    net.utdf_to_gmns(incl_utdf=True)

    # Step 4: convert UTDF network to SUMO
    net.utdf_to_sumo(sim_name="", remove_U_turn=True, sim_duration=7200)

    # Step 5 (optional): visualize the network
    net_map = ug.plot_net_mpl(net, save_fig=True, fig_name="Bullhead_City.png")
    net_map = ug.plot_net_keplergl(net,
                                    save_fig=True,
                                    fig_name="Bullhead_City.html")

    # Step 6: Sigma-X visualize signalized intersection
    # net.utdf_to_gmns_signal_ints()
```

129 AI usage disclosure

130 No generative AI tools were used in the development of this software, ChatGPT-5.2 was used
131 to improve the clarity and readability of the manuscript.

132 Acknowledgements

133 Prof. Milan Zlatkovic from University of Wyoming, for the power of sigma-x engine to visualize
134 signalized intersections.

135 Additional support was provided by the U.S. Department of Energy (DOE), Office of Energy
136 Efficiency and Renewable Energy (EERE), Vehicle Technologies Office. Any opinions, findings,
137 and conclusions or recommendations expressed in this material are those of the author(s) and
138 do not necessarily reflect the views of the USDOT, DOE, and the U.S. Government assumes
139 no liability for the contents or use thereof.

References

- Ban, J., Angah, O., Zhang, Y., Guo, Q., & others. (2022). A multiscale simulation platform for connected and automated transportation systems. *Connected Cities for Smart Mobility Toward Accessible and Resilient ...*
- Berg, I., Smith, S., & Zhou, X. S. (2022). *GMNS: A Specification for Sharing Routable Road Networks*.
- Coogan, S., Thitsa, M., & others. (2021). *Coordinated Anti-Congestion Control Algorithms for Diverging Diamond Interchanges*. Georgia. Department of Transportation. Office of Performance-Based ...
- Halbach, M., & Erdmann, J. (2022). High fidelity modelling of traffic light control with XML logic representation. *SUMO Conference Proceedings*, 3, 45–68. <https://doi.org/10.52825/scp.v3i.114>
- Lopez, P. A., Behrisch, M., Bieker-Walz, & others. (2018). Microscopic traffic simulation using sumo. *2018 21st International Conference on Intelligent Transportation Systems (ITSC)*, 2575–2582. <https://doi.org/10.1109/ITSC.2018.8569938>
- Lu, J., & Zhou, X. S. (2023). Virtual track networks: A hierarchical modeling framework and open-source tools for simplified and efficient connected and automated mobility (CAM) system design based on general modeling network specification (GMNS). *Transportation Research Part C: Emerging Technologies*, 153, 104223. <https://doi.org/10.1016/j.trc.2023.104223>
- Luo, X. (2024). Strategic Planning for Scalable Electric Vehicle Charging Networks: Integrating Operational Dynamics and Spatial-Temporal Analysis [PhD thesis]. In *Arizona State University*.
- Luo, X., Kuby, M. J., Honma, Y., Kchaou-Boujelben, M., & Zhou, X. S. (2024). Innovation diffusion in EV charging location decisions: Integrating demand & supply through market dynamics. *Transportation Research Part C: Emerging Technologies*, 165, 104733. <https://doi.org/10.1016/j.trc.2024.104733>
- Luo, X., Zhang, Y., Xu, G., Li, W., Wang, R., & Zhou, X. S. (2025). Automating Traffic Microsimulation from SYNCHRO UTDF to SUMO. *2025 Winter Simulation Conference, WSC 2025*, 2320–2331. <https://doi.org/10.1109/WSC68292.2025.11338949>
- PePy.tech. (2026). *utdf2gmns PyPI Download Statistics*. <https://pepy.tech/projects/utdf2gmns>
- Schrader, M., Wang, Q., & Bittle, J. (2022). Extension and validation of nema-style dual-ring controller in sumo. *SUMO Conference Proceedings*, 3, 1–13. <https://doi.org/10.52825/scp.v3i.115>
- Singh, S. K., Komolkiti, P., & Aswakul, C. (2017). Impact analysis of start-up lost time at major intersections on sathorn road using a synchro optimization and a microscopic SUMO traffic simulation. *IEEE Access*, 6, 6327–6340. <https://doi.org/10.1109/ACCESS.2017.2739240>
- Smith, S., Berg, I., Yang, C., John, A., & others. (2020). *General Modeling Network Specification: documentation, software, and data*. <https://doi.org/10.21949/1518740>
- Udomsilp, K., Arayakarnkul, T., Watarakitpaisarn, S., Komolkiti, P., Rudjanakanoknad, J., & Aswakul, C. (2017). Traffic data analysis on sathorn road with synchro optimization and traffic simulation. *Engineering Journal*, 21(6), 57–67. <https://doi.org/10.4186/ej.2017.21.6.57>
- Zhang, Y., Fu, M., & Ban, X. (2024). Integration Traffic Signal Control From Synchro to SUMO. *SUMO Conference Proceedings*, 5, 147–162. <https://doi.org/10.52825/scp.v5i.1112>