The Journal of Open Source Software

NN-Lite: Automated Benchmarking of PyTorch Models on Android Devices

Dmitry Ignatov [1], **Faraz Kayani** [1¶], **Sarmad Kayani** [1], **and Radu Timofte** [1]

1 Computer Vision Lab, CAIDAS & IFI, University of Würzburg, Germany ¶ Corresponding author

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Tobias Buck

Reviewers:

- @selimfirat
- @manunicholasjacob

Submitted: 05 October 2026
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

A modern smartphone contains several processors that can run neural networks: the central processing unit (CPU), the graphics processing unit (GPU) and often a neural processing unit (NPU). Researchers train their models with PyTorch (Paszke et al., 2019), and transferring each model to a phone by hand becomes impractical when many models must be measured.

NN-Lite automates the deployment and measurement of user-supplied PyTorch vision models that satisfy the documented input and conversion requirements. With an Android phone connected by USB, the following procedure is used for each model: conversion to LiteRT at full (FP32) and at reduced (INT8) precision is attempted and can fail. The converted file is then copied to the phone. On the phone, latency is measured for the supported configurations of CPU, GPU-delegate and Android Neural Networks API (NNAPI) execution. These configurations are requested explicitly and recorded with their outcomes. Models come from the user's own files or from the LEMUR model collection (Goodarzi et al., 2025) installed with NN-Lite. A multi-day unattended run resumes after a disconnection or a restart.

Statement of need

Research on efficient deep learning (hardware-aware architecture search, quantization, latency prediction, model compression) requires measurements across many architectures and real devices, because an emulator does not reproduce the vendor-specific GPU and NPU software stack of a phone. Some operators are not supported (Almeida et al., 2021; Ignatov et al., 2019). On a real device, the same model can succeed with one accelerator and be rejected by another.

NN-Lite, which evolved from the pipeline that produced the latency dataset of Din, Hussain, et al. (2026), serves researchers who need reproducible latency and feasibility measurements, specific to a device and to an accelerator configuration. This paper documents release 1.0.1, its design and tests, and its changes with respect to the campaign pipeline. Five of the changes listed in the changelog matter most.

User-supplied vision models. The campaign pipeline operated only on the collection it was written for. A file is now also accepted: a program exported with `torch.export`, which retains its input shape, or a Python module with a checkpoint or the saved model. Each model must have a single four-dimensional (NCHW) image input. Correct preprocessing for INT8 calibration remains the user's responsibility.

Packaged installation. The dependence on nightly builds that were later withdrawn from the Python Package Index made the campaign impossible to reproduce. Release 1.0.1 fixes the exact versions of its dependencies, all of which are published on the Python Package Index,

DRAFT

is installed under the name `nn-lit`, and its console command is `nn-lite-bench`. Linux and Apple Silicon are supported.

Measurements attributable to the intended model. Models are now built at their training resolution, not at a fixed size. The VisionTransformer configuration of the collection, for example, loads its weights only at its training resolution of 299×299. Verifying each transfer to the phone keeps a stale file from being timed. CPU timing uses the built-in LiteRT kernels with XNNPACK disabled (`--use_xnnpack=false`), as in the campaign.

Quantization calibrated on representative data. Integer export in the campaign pipeline used a set of synthetic random noise. Such a set misrepresents the activation statistics and can reduce the accuracy. The calibration now uses real images, processed with the input transformation of the model itself.

A tested programming interface. Output parsing, error extraction and record construction are separated from the device control into documented importable modules. These modules need neither the deep learning frameworks nor the Android Debug Bridge (ADB). An explicit serial number in every device command lets several phones be benchmarked at the same time, one process per phone.

State of the field

AI Benchmark (Ignatov et al., 2018, 2019) and *MLPerf Mobile* (Janapa Reddi et al., 2022) execute fixed curated sets of reference models in order to compare *devices*. Measured latency serves as ground truth for latency predictors such as *nn-Meter* (L. L. Zhang et al., 2021) and *BRP-NAS* (Dudziak et al., 2020), for search methods such as *MnasNet* (Tan et al., 2019) and *ProxylessNAS* (Cai et al., 2019), and for benchmarks such as *HW-NAS-Bench* (Li et al., 2021). *nn-Meter* includes backend preparation for Android profiling, while the other works do not provide the measurement infrastructure. The closest work in spirit is Q. Zhang et al. (2022), where 15 models are benchmarked with six mobile deep learning libraries on ten devices. That study, however, covers a fixed set of models and is not a tool that researchers can apply to their own models and devices. Compiler stacks like *TVM* (Chen et al., 2018) tune individual models. *Qualcomm AI Hub* (Qualcomm Technologies, Inc., 2026) offers hosted profiling, but only on devices with Qualcomm chips. Compared to *ExecuTorch* (PyTorch Foundation, 2025), which provides PyTorch edge deployment workflows, NN-Lite orchestrates LiteRT campaigns over many models and devices. The `benchmark_model` utility of LiteRT (Google AI Edge, 2026b) measures one converted model per invocation and supports structured profiling output, but it does not provide conversion, failure bookkeeping or one record for many models and devices.

NN-Lite uses existing components and does not replace them: LiteRT Torch (Google AI Edge, 2026a) for conversion, the LiteRT runtime (Abadi et al., 2016; Google AI Edge, 2025) with the official `benchmark_model` binary for execution, and ADB (Android Open Source Project, 2026a) for device control. NNAPI (Android Open Source Project, 2026b) is used to request accelerator execution. The contribution of NN-Lite consists in the orchestration layer, which integrates the components into a reproducible and fault-tolerant workflow from PyTorch models to structured records.

DRAFT

The Journal of Open Source Software

Software design




Figure 1: How NN-Lite benchmarks one model: (1) the model is read from a local file or from LEMUR (Goodarzi et al., 2025); (2) it is rebuilt and converted to FP32 and INT8 LiteRT files; (3) each file is timed on the phone with benchmark_model in the CPU, GPU-delegate and NNAPI configurations, which are requested, not verified on the hardware; (4) one record per model, precision and device is written. The safeguards at the bottom support unattended multi-day runs.

Host-driven execution using standard Android tooling. Transferring Google's prebuilt `benchmark_model` binary once to the phone and invoking it per model and configuration avoids root access and signed applications. Android tends to run processes started over ADB on the slower cores of a phone, so `benchmark_model` is pinned with `taskset` to all cores except the slowest group. End-to-end application latency is not reported.

Models are rebuilt rather than assumed to be portable. A model taken from the collection consists of PyTorch code, hyperparameters and a checkpoint. NN-Lite reinstantiates the network and restores its weights. A model from a file is self-describing in case of `torch.export`. For every other model from a file, reconstruction from its own module avoids naming collisions under a shared class name.

Every configuration is measured, and failures are data. Each model is exported in FP32. INT8 export with full integer post-training quantization (Jacob et al., 2018) follows for every model that supports it. If quantization fails on an unsupported operator, the FP32 model is still measured. Requesting every configuration explicitly, and not delegating it to the default of the runtime, means that each latency is labelled with the requested backend. Recording the diagnostic output of a failed configuration in the result and in the per-device log, and retaining a model whose configurations all fail and marking it invalid, makes failures available for explicit analysis. Not every failure establishes an operator support gap.

Fault-tolerant, resumable runs. NN-Lite pauses between models, restarts its process from time to time to release the memory held by the conversion toolchain, with a longer pause for cooling at each restart, and waits for a disconnected device.

DRAFT

One schema for every model source. Results are written as one file per model, quantization setting and device, in the training statistics layout of the collection. Each record contains the mean, minimum, maximum and standard deviation of the latency over repeated executions for every configuration, the fastest configuration (the one with the lowest valid mean latency), and the input shape, memory state and device telemetry needed for interpretation. The requested number of timed runs (20 by default) is stored as `iterations`. Each configuration performs exactly this number of runs after a warm-up, and the statistics are computed from these runs only.

Two limitations have to be mentioned. NN-Lite reports wall-clock latency and does not isolate the frequency governor state or the energy per operator. The second limitation is that NPU execution is mediated by NNAPI, whose behaviour depends on the installed runtime and drivers: NNAPI can fall back to CPU execution when compilation or execution on an accelerator fails, and the API was deprecated in Android 15 (Android Open Source Project, 2026b). Because NN-Lite cannot guarantee that all operations ran on the intended accelerator, the label NPU in the schema denotes the NNAPI configuration. The command line of each configuration is built in a single function, and this function localizes most of the change for a replacement backend.

Research impact statement

NN-Lite is the on-device measurement component of the LEMUR ecosystem (Goodarzi et al., 2025). Inference latency measurements for more than 7,500 models in LEMUR 2 (Uzun et al., 2026) were provided by the emulator execution path of NN-Lite. The physical device path produced the delegate-resolved latency dataset reported in Din, Hussain, et al. (2026), which covers 586 architectures across five commodity phones from three chip vendors. All records of this dataset are publicly available. They have also been used to fit device-specific latency models by symbolic regression (Dhanani et al., 2026) and to show that FLOPs predict latency poorly if the backend is not taken into account (Din, Kayani, et al., 2026).

Release 1.0.1 is on the Python Package Index as `nn-lit`, with the source in the project repository. Unit tests cover the release and run in continuous integration on three Python versions. We verified both model sources end to end on a phone, including a model outside the collection (torchvision MobileNetV3).

AI usage disclosure

We designed and implemented the NN-Lite software without generative AI assistance, while Claude Opus 5.5 (Anthropic) assisted with drafting the manuscript, checking `paper.bib` and creating Figure 1. All the content produced with AI assistance was reviewed, edited and validated by the authors, who made all the final scientific and software decisions.

Acknowledgements

This work was partially supported by the Alexander von Humboldt Foundation. We thank Saif U Din and Muhammad Ahsan Hussain for the measurement campaign of Din, Hussain, et al. (2026), and the contributors to the LEMUR dataset.

References

Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., Devin, M., Ghemawat, S., Irving, G., Isard, M., Kudlur, M., Levenberg, J., Monga, R., Moore, S., Murray, D. G., Steiner, B., Tucker, P., Vasudevan, V., Warden, P., … Zheng, X. (2016). TensorFlow: A

DRAFT

system for large-scale machine learning. *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 265–283. https://doi.org/10.48550/arXiv.1605.08695

Almeida, M., Laskaridis, S., Mehrotra, A., Dudziak, L., Leontiadis, I., & Lane, N. D. (2021). Smart at what cost? Characterising mobile deep neural networks in the wild. *Proceedings of the 21st ACM Internet Measurement Conference (IMC)*, 658–672. https://doi.org/10.1145/3487552.3487863

Android Open Source Project. (2026a). *Android Debug Bridge (adb)*. https://developer.android.com/tools/adb.

Android Open Source Project. (2026b). *Neural Networks API*. https://developer.android.com/ndk/guides/neuralnetworks.

Cai, H., Zhu, L., & Han, S. (2019). ProxylessNAS: Direct neural architecture search on target task and hardware. *International Conference on Learning Representations (ICLR)*. https://doi.org/10.48550/arXiv.1812.00332

Chen, T., Moreau, T., Jiang, Z., Zheng, L., Yan, E., Shen, H., Cowan, M., Wang, L., Hu, Y., Ceze, L., Guestrin, C., & Krishnamurthy, A. (2018). TVM: An automated end-to-end optimizing compiler for deep learning. *13th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 578–594. https://doi.org/10.48550/arXiv.1802.04799

Dhanani, D. R., Kayani, F., Din, S. U., Arslanian, A., Ignatov, D., & Timofte, R. (2026). Understanding the performance of deep computer vision models: A symbolic regression approach to accuracy and latency prediction. *Sensors*, *26*(13), 4093. https://doi.org/10.3390/s26134093

Din, S. U., Hussain, M. A., Ikram, M., Kayani, F., Ignatov, D., & Timofte, R. (2026). AI on the edge: An automated pipeline for PyTorch-to-Android deployment and benchmarking. *Preprints*. https://doi.org/10.20944/preprints202511.1831.v2

Din, S. U., Kayani, F., Timofte, R., & Ignatov, D. (2026). Vision model inference on mobile devices: A large-scale delegate-aware benchmark beyond FLOPs. *Proceedings of the British Machine Vision Conference (BMVC)*.

Dudziak, L., Chau, T., Abdelfattah, M. S., Lee, R., Kim, H., & Lane, N. D. (2020). BRP-NAS: Prediction-based NAS using GCNs. *Advances in Neural Information Processing Systems (NeurIPS)*, *33*. https://doi.org/10.48550/arXiv.2007.08668

Goodarzi, A. T., Kochnev, R., Khalid, W., Goudarzi, H. T., Qin, F., Uzun, T. A., Dhameliya, Y. S., Kathiriya, Y. K., Bentyn, Z. A., Ignatov, D., & Timofte, R. (2025). LEMUR neural network dataset: Towards seamless AutoML. *arXiv Preprint arXiv:2504.10552*. https://doi.org/10.48550/arXiv.2504.10552

Google AI Edge. (2025). *LiteRT: On-device runtime and developer guide*. https://ai.google.dev/edge/litert.

Google AI Edge. (2026a). *LiteRT Torch (formerly AI Edge Torch): Converting PyTorch models to LiteRT*. https://github.com/google-ai-edge/litert-torch.

Google AI Edge. (2026b). *LiteRT: Benchmark interpreter API*. https://developers.google.com/edge/litert/models/measurement.

Ignatov, A., Timofte, R., Chou, W., Wang, K., Wu, M., Hartley, T., & Van Gool, L. (2018). AI Benchmark: Running deep neural networks on Android smartphones. *Proceedings of the European Conference on Computer Vision (ECCV) Workshops*, 288–314. https://doi.org/10.1007/978-3-030-11021-5_19

Ignatov, A., Timofte, R., Kulik, A., Yang, S., Wang, K., Baum, F., Wu, M., Xu, L., & Van Gool, L. (2019). AI Benchmark: All about deep learning on smartphones in 2019. *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops*

DRAFT

(ICCVW), 3617–3635. https://doi.org/10.1109/ICCVW.2019.00447

Jacob, B., Kligys, S., Chen, B., Zhu, M., Tang, M., Howard, A., Adam, H., & Kalenichenko, D. (2018). Quantization and training of neural networks for efficient integer-arithmetic-only inference. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2704–2713. https://doi.org/10.1109/CVPR.2018.00286

Janapa Reddi, V., Kanter, D., Mattson, P., Duke, J., Nguyen, T., Chukka, R., Shiring, K., Tan, K.-S., Charlebois, M., Chou, W., El-Khamy, M., Hong, J., St John, T., Trinh, C., Buch, M., Mazumder, M., Markovic, R., Atta, T., Cakir, F., … Zika, D. (2022). MLPerf Mobile inference benchmark: An industry-standard open-source machine learning benchmark for on-device AI. *Proceedings of Machine Learning and Systems (MLSys)*, *4*, 352–369. https://proceedings.mlsys.org/paper_files/paper/2022/hash/a2b2702ea7e682c5ea2c20e8f71efb0c-Abstract.html

Li, C., Yu, Z., Fu, Y., Zhang, Y., Zhao, Y., You, H., Yu, Q., Wang, Y., & Lin, Y. (2021). HW-NAS-Bench: Hardware-aware neural architecture search benchmark. *International Conference on Learning Representations (ICLR)*. https://doi.org/10.48550/arXiv.2103.10584

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S. (2019). PyTorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems (NeurIPS)*, *32*. https://doi.org/10.48550/arXiv.1912.01703

PyTorch Foundation. (2025). *ExecuTorch: On-device inference runtime for PyTorch models*. https://docs.pytorch.org/executorch/.

Qualcomm Technologies, Inc. (2026). *Qualcomm AI Hub*. https://aihub.qualcomm.com.

Tan, M., Chen, B., Pang, R., Vasudevan, V., Sandler, M., Howard, A., & Le, Q. V. (2019). MnasNet: Platform-aware neural architecture search for mobile. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2815–2823. https://doi.org/10.1109/CVPR.2019.00293

Uzun, T. A., Khalid, W., Din, S. U., Mulukuledu, S. R., Singh, A., Vysyaraju, C., Duvvuri, R., Goyal, A., Lukhi, Y. R., Hussain, M. A., Jesani, K., Shrestha, U., Mittal, Y., Kochnev, R., Kadam, P., Ikram, M., Moradiya, H. R., Arslanian, A., Ignatov, D., & Timofte, R. (2026). LEMUR 2: Unlocking neural network diversity for AI. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 3291–3300. https://openaccess.thecvf.com/content/CVPR2026W/CVPR-NAS26/papers/Uzun_LEMUR_2_Unlocking_Neural_Network_Diversity_for_AI_CVPRW_2026_paper.pdf

Zhang, L. L., Han, S., Wei, J., Zheng, N., Cao, T., Yang, Y., & Liu, Y. (2021). nn-Meter: Towards accurate latency prediction of deep-learning model inference on diverse edge devices. *Proceedings of the 19th Annual International Conference on Mobile Systems, Applications, and Services (MobiSys)*, 81–93. https://doi.org/10.1145/3458864.3467882

Zhang, Q., Li, X., Che, X., Ma, X., Zhou, A., Xu, M., Wang, S., Ma, Y., & Liu, X. (2022). A comprehensive benchmark of deep learning libraries on mobile devices. *Proceedings of the ACM Web Conference (WWW)*, 3298–3307. https://doi.org/10.1145/3485447.3512148

DRAFT