

DESDEO2: Core-Logic for Implementing Interactive Multiobjective Optimization Methods

Giovanni Misitano¹, Bhupinder Saini¹, Giomara Lárraga¹, Juho Roponen¹, Juuso Pajasmaa¹, Matias Nieminen¹, Babooshka Shavazipour¹, and Kaisa Miettinen²

¹ University of Jyväskylä, Faculty of Information Technology, P.O. BOX 35 (Agora), FI-40014 University of Jyväskylä, Finland ² University of Jyväskylä, P.O. Box 35 (C), FI-40014 University of Jyväskylä, Finland

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Abhishek Tiwari](#)

Reviewers:

- [@samgdotson](#)
- [@jbussemaker](#)

Submitted: 18 June 2026

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Many real-world problems involve optimizing multiple conflicting objective functions simultaneously: when designing a car, for example, reducing its manufacturing cost typically comes at the expense of passenger safety and fuel efficiency. In such multiobjective optimization problems, there is no single optimal solution but, instead, multiple compromise solutions representing different trade-offs.

To select the best compromise, a decision maker (a domain expert) must explore the trade-offs and choose the solution they find most preferred. [Interactive methods](#) ([Miettinen, 1999](#); [Miettinen et al., 2016](#)) support this task. They proceed step by step, letting the decision maker examine candidate solutions, express preferences, and steer the search toward more desirable solutions, learning along the way about the problem and which preferences are achievable.

DESDEO2 is an open source software framework that provides a foundation for implementing interactive multiobjective optimization methods. It is a full redesign of the earlier DESDEO software ([Misitano et al., 2021](#)), developed to address practical challenges in building reusable and reproducible decision-support tools. We refer to the new version as DESDEO2 to distinguish it from its predecessor; outside this context, it is simply known as DESDEO. The scope of this paper is limited on the Python-based core-logic layer of DESDEO2, which is fully self-contained and [usable as a standalone library](#). Outside the core-logic, the broader framework also includes a web API and a graphical web user interface, both under active development.

The core-logic provides explicit abstractions for problem modeling, method execution, and preference handling, enabling interactive methods to be implemented as modular, composable components that are decoupled from any particular interface or deployment technology. This improves the reproducibility of experiments, reusability, and extensibility. The core-logic has been utilized in research and teaching, and is ready for broader use.

Statement of need

Multiobjective optimization methods can be classified based on the timing when the preference information of a decision maker is used ([Miettinen, 1999](#)): *a priori* methods elicit preferences before optimization, *a posteriori* methods first generate a representative set of compromise solutions from which the decision maker selects one, while *interactive* methods incorporate preferences iteratively to generate new desirable solutions during the solution process. Because preferences unfold in an iterative dialogue with the decision maker, interactive methods are inherently software-intensive: any usable implementation must maintain state across iterations,

41 support diverse preference types, and let the decision maker drive the control flow. Providing
42 these capabilities as reusable components, rather than re-implementing them for every method,
43 is therefore valuable.

44 Existing open source frameworks do not explicitly provide reusable abstractions for these
45 iterative, preference-driven workflows. Without such software, researchers must repeatedly
46 reimplement not only optimization methods but also interaction logic, state management, and
47 preference handling, making systematic experimentation laborious and difficult to reproduce
48 (Afsar et al., 2021, 2024). DESDEO2's core-logic is designed to fill this gap. It targets
49 researchers in interactive multiobjective optimization, who can experiment with existing
50 methods and develop new ones; students learning about interactive methods; and practitioners
51 building decision-support systems.

52 The need for reusable implementations originally motivated the development of earlier versions
53 of DESDEO (Misitano et al., 2021; Ojalehto & Miettinen, 2018), which have enabled a range
54 of successful research applications and practical decision-support, e.g., (Afsar, Ruiz, et al.,
55 2023; Afsar, Silvennoinen, et al., 2023; Burkotová et al., 2024; Eyvindson et al., 2024; Kania et
56 al., 2022, 2023). However, accumulated experience revealed architectural limitations: problem
57 definitions were not clearly separated from method logic; method state, such as iteration
58 history and preference information, was not explicitly modeled; and connectivity to external
59 solvers and support for important problem types, such as mixed-integer and scenario-based
60 problems, were limited.

61 State of the field

62 Many open source frameworks support research on non-preference-based, *a priori*, and *a*
63 *posteriori* multiobjective optimization methods. Libraries, such as jMetal (Durillo et al., 2010),
64 PlatEMO (Tian et al., 2017), pymoo (Blank & Deb, 2020), Platypus (Hadka, 2024), DEAP
65 (Fortin et al., 2012), pagmo/pygmo (Biscani & Izzo, 2020), and ParMOO (Chang & Wild,
66 2023), have become commonplace, particularly for evolutionary multiobjective optimization
67 approaches; fewer software exist for scalarization-based methods, one notable exception being
68 vOptSolver and its successor MultiObjectiveAlgorithms.jl (Dowson et al., 2025). These tools
69 provide rich support for solution generation and benchmarking, and some offer preference-based
70 mechanisms, such as reference point integration. However, these features are designed mainly
71 for *a priori* use; support for the iterative, decision-maker-driven workflows that characterize
72 interactive methods is lacking. Since existing frameworks assume in their core execution model
73 a single optimization run without structured intervention, accommodating interactive workflows
74 would require changes to core abstractions rather than incremental extensions, making it
75 impractical to contribute these features to existing tools.

76 Without dedicated frameworks, implementations of interactive methods have typically been
77 standalone prototypes or tightly coupled to specific applications, making them difficult to
78 reuse, compare, or extend beyond their original context, e.g., (Siraj et al., 2015; Vetturini et
79 al., 2024). Earlier versions of DESDEO (Misitano et al., 2021; Ojalehto et al., 2016) began
80 addressing this lack by providing an open source framework specifically for interactive methods,
81 and DESDEO2 builds on this foundation with its restructured and redesigned core-logic. Rather
82 than replacing existing optimization frameworks, DESDEO2 complements them by allowing
83 solvers from other libraries, such as SciPy (Virtanen et al., 2020), to be used as computational
84 backends within its interactive method workflows.

85 Software design

86 A foundational design decision in DESDEO2 is to represent optimization problems in a
87 serializable, language-agnostic form that can be defined once and then evaluated, stored, and
88 exchanged across tools and software boundaries. Building on this, the core-logic addresses five

key challenges identified from experience with earlier versions of DESDEO: **C1** problem modeling, **C2** language-agnostic problem representation, **C3** interactive method state management, **C4** enabling extensions, and **C5** usage and contribution support.

To address C1 and C2, DESDEO2 represents problem definitions as explicit Pydantic¹ models in Python, which can be exported to and reconstructed from a [JSON representation](#). The model is designed for multiobjective optimization and supports [data-driven settings](#), where objective and constraint values may be computed by external simulations or opaque-box models. [Evaluators and parsers](#) bridge the model to external problem-definition ecosystems, and [solver interfaces](#) connect the core-logic to external optimizers; supported backends currently include Pyomo ([Hart et al., 2011](#)), SymPy ([Meurer et al., 2017](#)), CVXPY ([Diamond & Boyd, 2016](#)), Gurobi ([Gurobi Optimization, LLC, 2026](#)), Polars ([Vink et al., 2025](#)), SciPy ([Virtanen et al., 2020](#)), nevergrad ([Rapin & Teytaud, 2018](#)), and the COIN-OR solvers CBC ([Forrest et al., 2026](#)), Bonmin ([Bonami et al., 2008](#)), and Ipopt ([Wächter & Biegler, 2006](#)) (see the [documentation](#)). Problems thus need to be modeled only once to be [scalarized](#), evaluated, and solved in numerous ways (C1), while remaining storable and exchangeable across software boundaries, e.g., in databases ([Saini et al., 2023](#)) (C2).

Regarding state management (C3), earlier DESDEO versions coupled method state tightly to execution logic, making it difficult to persist, inspect, or reuse outside the running process. DESDEO2 instead provides explicit state representations with well-defined transitions, leaving persistence to the surrounding system, so interactive processes can be stored, resumed, and compared systematically, particularly when integrated with databases in decision-support systems; for standalone use, optional utility functions handle common state bookkeeping locally.

To enable extensions (C4), instead of implementing methods as monolithic algorithms, DESDEO2 decomposes functionality into reusable components for problem handling, preference processing, and solution generation, e.g., scalarization and [evolutionary operators](#). Individual components can be replaced, hybridized ([Sindhya et al., 2013](#)), or extended without re-implementing entire methods. Whereas the previous DESDEO was distributed as four separate packages, DESDEO2 is a single cohesive package whose [module structure](#) mirrors their high-level roles ([Misitano et al., 2021](#)) with fully redesigned contents: we deliberately prioritized a solid foundation for future development over backwards compatibility, supporting extensibility (C4) while keeping the code-base navigable (C5).

Finally, to support usage and contribution (C5), the [documentation](#) is inspired by the Diátaxis approach ([Procida, 2026](#)), separating tutorials, how-to guides, explanations, and reference material, and the core-logic is accompanied by unit tests targeting individual components. As a current limitation, DESDEO2's web-facing components, which would extend it into a full decision-support system, are not yet complete.

Research impact statement

DESDEO has supported a sustained body of research on interactive multiobjective optimization over several years. Earlier versions enabled comparative studies, decision-support applications, and practical deployments across multiple domains, such as engineering design, forest management, and production planning (e.g., ([Afsar, Ruiz, et al., 2023](#); [Afsar, Silvennoinen, et al., 2023](#); [Burkotová et al., 2024](#); [Eyvindson et al., 2024](#); [Kania et al., 2022, 2023](#))), establishing both the community's need for reusable interactive method implementations and the research experience that informed DESDEO2's design.

DESDEO2's redesign enables lines of research that its predecessor's architecture could not readily support. Because interactive methods are now decoupled from any particular interface and share common abstractions for problems, preferences, and state, they can be implemented,

¹<https://github.com/pydantic/pydantic>, accessed 19 August 2026.

hybridized, and compared systematically rather than rebuilt as one-off prototypes. This makes it feasible to combine scalarization-based and evolutionary methods within a single framework, to switch methods or preference types during a solution process, and to store, resume, and compare interactive sessions, which supports reproducible studies of decision maker behavior, for example. The serializable problem representation similarly extends such research to previously impractical problem classes, including mixed-integer, scenario-based, and simulation/data-driven problems.

DESDEO2's core-logic is actively used in ongoing research at the University of Jyväskylä, supporting multiple Research Council of Finland funded projects and doctoral and master-level theses; recent examples include (Pajasmaa et al., 2026; Saini et al., 2025, 2026; Tahvanainen et al., 2026). The framework has been presented at multiple international conferences and used in university-level teaching, including an international summer school in 2025, and in public demonstrations during European Researchers' Night events. Since early 2024, DESDEO2's development branches have accumulated over 2000 commits. Development is led by the Multiobjective Optimization Group (<https://optgroup.it.jyu.fi/>) at the University of Jyväskylä, and contributions from the broader research community are warmly welcomed.

AI usage disclosure

Generative tools based on large language models have been used to partly support the development of DESDEO2: for code snippet generation, refactoring, exploring the documentation and code bases of third-party libraries, and writing documentation, such as parameter descriptions. All generated code and documentation has been audited and validated by a human. Generative tools were also used to plan the initial structure of this paper based on the authors' earlier draft. All the final contents and ideas in this paper have been produced and verified by the authors.

Acknowledgements

We warmly thank the many students, trainees, researchers, and other external contributors who have contributed, and continue to contribute, to the development of DESDEO2 and its predecessors.

The development of DESDEO2 was supported by the Research Council of Finland (grant numbers 355346 and 373063). The software is related to the thematic research area DEMO (Decision Analytics utilizing Causal Models and Multiobjective Optimization, <https://jyu.fi/demo>) of the University of Jyväskylä.

References

- Afsar, B., Miettinen, K., & Ruiz, F. (2021). Assessing the performance of interactive multiobjective optimization methods: A survey. *ACM Computing Surveys*, 54(4), 1–27. <https://doi.org/10.1145/3448301>
- Afsar, B., Ruiz, A. B., & Miettinen, K. (2023). Comparing interactive evolutionary multiobjective optimization methods with an artificial decision maker. *Complex & Intelligent Systems*, 9, 1165–1181. <https://doi.org/10.1007/s40747-021-00586-5>
- Afsar, B., Silvennoinen, J., Misitano, G., Ruiz, F., Ruiz, A. B., & Miettinen, K. (2023). Designing empirical experiments to compare interactive multiobjective optimization methods. *Journal of the Operational Research Society*, 74(11), 2327–2338. <https://doi.org/10.1080/01605682.2022.2141145>

- 180 Afsar, B., Silvennoinen, J., Ruiz, F., Ruiz, A. B., Misitano, G., & Miettinen, K. (2024). An
181 experimental design for comparing interactive methods based on their desirable properties.
182 *Annals of Operations Research*, 338, 835–856. [https://doi.org/10.1007/s10479-024-05941-](https://doi.org/10.1007/s10479-024-05941-6)
183 [6](https://doi.org/10.1007/s10479-024-05941-6)
- 184 Biscani, F., & Izzo, D. (2020). A parallel global multiobjective framework for optimization:
185 pagmo. *Journal of Open Source Software*, 5(53), 2338. [https://doi.org/10.21105/joss.](https://doi.org/10.21105/joss.02338)
186 [02338](https://doi.org/10.21105/joss.02338)
- 187 Blank, J., & Deb, K. (2020). Pymoo: Multi-objective optimization in Python. *IEEE Access*, 8,
188 89497–89509. <https://doi.org/10.1109/ACCESS.2020.2990567>
- 189 Bonami, P., Biegler, L. T., Conn, A. R., Cornuéjols, G., Grossmann, I. E., Laird, C. D., Lee,
190 J., Lodi, A., Margot, F., Sawaya, N., & Wächter, A. (2008). An algorithmic framework
191 for convex mixed integer nonlinear programs. *Discrete Optimization*, 5(2), 186–204.
192 <https://doi.org/10.1016/j.disopt.2006.10.011>
- 193 Burkotová, J., Aghaei Pour, P., Krátký, T., & Miettinen, K. (2024). Interactive multiobjective
194 optimization of an extremely computationally expensive pump design problem. *Engineering*
195 *Optimization*, 56(8), 1318–1333. <https://doi.org/10.1080/0305215X.2023.2247369>
- 196 Chang, T. H., & Wild, S. M. (2023). ParMOO: A Python library for parallel multiobjective
197 simulation optimization. *Journal of Open Source Software*, 8(82), 4468. [https://doi.org/](https://doi.org/10.21105/joss.04468)
198 [10.21105/joss.04468](https://doi.org/10.21105/joss.04468)
- 199 Diamond, S., & Boyd, S. (2016). CVXPY: A Python-embedded modeling language for convex
200 optimization. *Journal of Machine Learning Research*, 17(83), 1–5. [https://www.jmlr.org/](https://www.jmlr.org/papers/v17/15-408.html)
201 [papers/v17/15-408.html](https://www.jmlr.org/papers/v17/15-408.html)
- 202 Dowson, O., Gandibleux, X., & Kof, G. (2025). *MultiObjectiveAlgorithms.jl: A Julia package for*
203 *solving multi-objective optimization problems*. <https://doi.org/10.48550/arXiv.2507.05501>
- 204 Durillo, J. J., Nebro, A. J., & Alba, E. (2010). The jMetal framework for multi-objective
205 optimization: Design and architecture. *IEEE Congress on Evolutionary Computation.*
206 *Proceedings*, 1–8. <https://doi.org/10.1109/CEC.2010.5586354>
- 207 Eyvindson, K., Burgas, D., Antón-Fernández, C., Hakanen, J., Emmerich, M., Klein, J.,
208 Mönkkönen, M., Snäll, T., Toraño Caicoya, A., Vergarechea, M., & others. (2024).
209 MultiOptForest: An interactive multi-objective optimization tool for forest planning and
210 scenario analysis. *Open Research Europe*, 3, 103. [https://doi.org/10.12688/openreseurope.](https://doi.org/10.12688/openreseurope.15812.2)
211 [15812.2](https://doi.org/10.12688/openreseurope.15812.2)
- 212 Forrest, J., Ralphs, T., Vigerske, S., Santos, H. G., Hafer, L., Kristjansson, B., Lubin, M.,
213 Saltzman, M., & others. (2026). *coin-or/Cbc: COIN-OR branch-and-cut solver*. Zenodo.
214 <https://doi.org/10.5281/zenodo.2720283>
- 215 Fortin, F.-A., De Rainville, F.-M., Gardner, M.-A., Parizeau, M., & Gagné, C. (2012). DEAP:
216 Evolutionary algorithms made easy. *Journal of Machine Learning Research*, 13, 2171–2175.
217 <https://www.jmlr.org/papers/v13/fortin12a.html>
- 218 Gurobi Optimization, LLC. (2026). *Gurobi Optimizer Reference Manual*. [https://www.gurobi.](https://www.gurobi.com)
219 [com](https://www.gurobi.com)
- 220 Hadka, D. (2024). *Platypus: A framework for evolutionary computing in Python*. [https://](https://github.com/Project-Platypus/Platypus)
221 github.com/Project-Platypus/Platypus.
- 222 Hart, W. E., Watson, J.-P., & Woodruff, D. L. (2011). Pyomo: Modeling and solving
223 mathematical programs in Python. *Mathematical Programming Computation*, 3, 219–260.
224 <https://doi.org/10.1007/s12532-011-0026-8>
- 225 Kania, A., Afsar, B., Miettinen, K., & Sipilä, J. (2023). DESMILS: A decision support approach
226 for multi-item lot sizing using interactive multiobjective optimization. *Journal of Intelligent*

- 227 *Manufacturing*, 35, 1373–1387. <https://doi.org/10.1007/s10845-023-02112-5>
- 228 Kania, A., Sipilä, J., Misitano, G., Miettinen, K., & Lehtimäki, J. (2022). Integration of
229 lot sizing and safety strategy placement using interactive multiobjective optimization.
230 *Computers & Industrial Engineering*, 173, 108731. [https://doi.org/10.1016/j.cie.2022.](https://doi.org/10.1016/j.cie.2022.108731)
231 [108731](https://doi.org/10.1016/j.cie.2022.108731)
- 232 Meurer, A., Smith, C. P., Paprocki, M., Čertík, O., Kirpichev, S. B., Rocklin, M., Kumar, A.,
233 Ivanov, S., Moore, J. K., Singh, S., & others. (2017). SymPy: Symbolic computing in
234 python. *PeerJ Computer Science*, 3, e103. <https://doi.org/10.7717/peerj-cs.103>
- 235 Miettinen, K. (1999). *Nonlinear Multiobjective Optimization*. Kluwer Academic Publishers.
236 <https://doi.org/10.1007/978-1-4615-5563-6>
- 237 Miettinen, K., Hakanen, J., & Podkopaev, D. (2016). Interactive nonlinear multiobjective
238 optimization methods. In S. Greco, M. Ehrgott, & J. Figueira (Eds.), *Multiple Criteria*
239 *Decision Analysis: State of the Art Surveys* (pp. 927–976). Springer. [https://doi.org/10.](https://doi.org/10.1007/978-1-4939-3094-4_22)
240 [1007/978-1-4939-3094-4_22](https://doi.org/10.1007/978-1-4939-3094-4_22)
- 241 Misitano, G., Saini, B. S., Afsar, B., Shavazipour, B., & Miettinen, K. (2021). DESDEO:
242 The modular and open source framework for interactive multiobjective optimization. *IEEE*
243 *Access*, 9, 148277–148295. <https://doi.org/10.1109/ACCESS.2021.3123825>
- 244 Ojalehto, V., & Miettinen, K. (2018). DESDEO: An open framework for interactive
245 multiobjective optimization. In S. Huber, M. J. Geiger, & A. T. de Almeida (Eds.), *Multiple*
246 *Criteria Decision Making and Aiding: Cases on Models and Methods with Computer*
247 *Implementations* (pp. 67–94). Springer. https://doi.org/10.1007/978-3-319-99304-1_3
- 248 Ojalehto, V., Podkopaev, D., & Miettinen, K. (2016). Towards automatic testing of reference
249 point based interactive methods. In J. Handl, E. Hart, P. R. Lewis, M. López-Ibáñez,
250 G. Ochoa, & B. Paechter (Eds.), *Parallel Problem Solving from Nature – PPSN XIV,*
251 *Proceedings* (pp. 483–492). Springer. https://doi.org/10.1007/978-3-319-45823-6_45
- 252 Pajasmaa, J., Saini, B. S., Shavazipour, B., Ruiz, F., Podkopaev, D., & Miettinen, K. (2026).
253 NAUTIL: A trade-off-free interactive multiobjective optimization method for group decision
254 making. *Journal of Global Optimization*. <https://doi.org/10.1007/s10898-026-01617-6>
- 255 Procida, D. (2026). *Diátaxis documentation framework*. <https://diataxis.fr/>
- 256 Rapin, J., & Teytaud, O. (2018). Nevergrad - A gradient-free optimization platform. In *GitHub*
257 *repository*. <https://GitHub.com/FacebookResearch/Nevergrad>; GitHub.
- 258 Saini, B. S., Kangas, A., Mehtätalo, L., Hirvelä, H., Shavazipour, B., & Miettinen, K. (2026).
259 Searching for sustainable national forest harvest levels through interactive multiobjective
260 optimization. *Canadian Journal of Forest Research*, 56, 1–13. [https://doi.org/10.1139/cjfr-](https://doi.org/10.1139/cjfr-2025-0277)
261 [2025-0277](https://doi.org/10.1139/cjfr-2025-0277)
- 262 Saini, B. S., Lárraga, G., & Miettinen, K. (2023). Using a database to support interactive
263 multiobjective optimization, visualization, and analysis. *Proceedings of the Conference on*
264 *Genetic and Evolutionary Computation, Companion*, 1703–1711. [https://doi.org/10.1145/](https://doi.org/10.1145/3583133.3596383)
265 [3583133.3596383](https://doi.org/10.1145/3583133.3596383)
- 266 Saini, B. S., Singh, H. K., Shavazipour, B., & Miettinen, K. (2025). An efficient
267 iterative approach for uniformly representing Pareto fronts. *Evolutionary Multi-Criterion*
268 *Optimization: 13th International Conference, EMO 2025, Proceedings, Part II*, 241–256.
269 https://doi.org/10.1007/978-981-96-3538-2_17
- 270 Sindhya, K., Miettinen, K., & Deb, K. (2013). A hybrid framework for evolutionary multi-
271 objective optimization. *IEEE Transactions on Evolutionary Computation*, 17(4), 495–511.
272 <https://doi.org/10.1109/TEVC.2012.2204403>
- 273 Siraj, S., Mikhailov, L., & Keane, J. A. (2015). PriEsT: An interactive decision support tool

- 274 to estimate priorities from pairwise comparison judgments. *International Transactions in*
275 *Operational Research*, 22(2), 217–235. <https://doi.org/10.1111/itor.12054>
- 276 Tahvanainen, V., Roponen, J., Saini, B. S., Pajasmaa, J., Shavazipour, B., Ruiz, F., Niemi, M.
277 T., Takala, T., Vauhkonen, J., & Miettinen, K. (2026). Advancing climate-smart forestry
278 with an interactive decision-support tool that incorporates the preferences of private forest
279 owners. *Forest Policy and Economics*, 187, 103764. [https://doi.org/10.1016/j.forpol.2026.](https://doi.org/10.1016/j.forpol.2026.103764)
280 [103764](https://doi.org/10.1016/j.forpol.2026.103764)
- 281 Tian, Y., Cheng, R., Zhang, X., & Jin, Y. (2017). PlatEMO: A MATLAB platform for
282 evolutionary multi-objective optimization. *IEEE Computational Intelligence Magazine*,
283 12(4), 73–87. <https://doi.org/10.1109/MCI.2017.2742868>
- 284 Vetturini, A. J., Cagan, J., & Taylor, R. E. (2024). Generative design-enabled exploration
285 of wireframe DNA origami nanostructures. *Nucleic Acids Research*, 53(2), gkae1268.
286 <https://doi.org/10.1093/nar/gkae1268>
- 287 Vink, R., Gooijer, S. de, Beedie, A., Burghoorn, G., Peters, O., Gorelli, M. E., & others.
288 (2025). *Pola-rs/polars: Python polars 1.35.2 (py-1.35.2)*. Zenodo. [https://doi.org/10.](https://doi.org/10.5281/zenodo.17564463)
289 [5281/zenodo.17564463](https://doi.org/10.5281/zenodo.17564463)
- 290 Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D.,
291 Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S. J., Brett, M., Wilson,
292 J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E., ... SciPy
293 1.0 Contributors. (2020). SciPy 1.0: Fundamental Algorithms for Scientific Computing in
294 Python. *Nature Methods*, 17, 261–272. <https://doi.org/10.1038/s41592-019-0686-2>
- 295 Wächter, A., & Biegler, L. T. (2006). On the implementation of an interior-point filter
296 line-search algorithm for large-scale nonlinear programming. *Mathematical Programming*,
297 106(1), 25–57. <https://doi.org/10.1007/s10107-004-0559-y>