

PatchSim: a modular simulation framework for patch-based metapopulation epidemiology

Adish Assain Illikkal¹, Shreya Mukherjee¹, and Sneha S¹

¹ AI and Robotics Technology Park (ARTPARK), Indian Institute of Science, Bengaluru, India

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [✉](#)

Submitted: 22 August 2026

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

PatchSim is an open-source Python framework for simulating infectious disease dynamics across spatially structured populations. It implements a patch-based metapopulation approach in which a landscape is partitioned into discrete geographical units (patches) — such as subdistricts, districts, or ecological zones — connected by a weighted contact network. Within each patch, disease progression is described by user-defined compartmental models (e.g., SIR, SEIR, SIRS) specified in a YAML configuration file, where each transition is written as source → target with a rate expression. PatchSim provides adaptive ordinary differential equation (ODE) and explicit-Euler solvers, Sobol sensitivity analysis via SALib (Herman & Usher, 2017), bounded least-squares calibration, and command-line and Python interfaces. Its configuration-first scope covers compartment-transfer models over supplied patch and group interaction data; scientific assumptions remain the modeller's responsibility. PatchSim is available on PyPI (`pip install patchsim`), with source code and documentation linked from the project record (Illikkal et al., 2026).

Statement of need

Mathematical modelling of infectious diseases is essential for understanding transmission dynamics, evaluating interventions, and informing public health policy (Keeling & Rohani, 2008). Metapopulation models — which capture the heterogeneity of disease spread across connected spatial units (Grenfell & Harwood, 1997) — are particularly valuable for diseases where population movement shapes outbreak trajectories, including foot-and-mouth disease in livestock (Guyver-Fletcher et al., 2025; Keeling et al., 2001; Tildesley et al., 2006), dengue in urban landscapes (Wesolowski et al., 2015), and respiratory infections across administrative regions (Balcan et al., 2009; Gatto et al., 2020).

Implementing such models commonly requires custom scientific code or a platform tied to a particular modelling abstraction. This adds software work to the scientific tasks of specifying transitions, preparing spatial inputs, and checking model assumptions.

PatchSim reduces this cost through a configuration-first design in which model structure — compartments, transitions, and parameters — is declared in a YAML file rather than implemented in code. The intended users are epidemiological modellers, researchers studying spatial disease dynamics, and public health analysts who need to rapidly prototype and compare scenarios across spatial configurations and disease systems. PatchSim was developed at ARTPARK, the AI and Robotics Technology Park at the Indian Institute of Science (IISc), to support active modelling work on livestock disease dynamics in India.

State of the field

Existing software spans several related abstractions: EpiFire (Hladish et al., 2012) and EpiModel (Jenness et al., 2018) address contact-network epidemiology; epipack (Maier, 2021) supports compartmental, stochastic, and network models; EMOD (Bershteyn et al., 2018) uses an individual-based architecture; and GLEaM (Balcan et al., 2010; Van den Broeck et al., 2011) represents global mobility-driven metapopulations.

Metapopulation frameworks closer to PatchSim include MetaWards (Woods et al., 2022), MEMilio (Bicker et al., 2026), SimInf (Widgren et al., 2019), MetaCast (Grunnill et al., 2024), and flepiMoP (Lemaitre et al., 2024). MetaWards is a stochastic metapopulation framework originally built for the electoral wards of Great Britain. MEMilio is a C++ core with Python bindings that offers graph-ODE and agent-based models. SimInf declares stochastic transitions as strings over nodes linked by scheduled livestock movements. MetaCast broadcasts a user-written Python ODE over subpopulations and bundles Latin hypercube sensitivity analysis. flepiMoP is an R and Python forecasting pipeline that declares compartments and transitions in YAML over a mobility matrix.

PatchSim is an independent implementation, but it shares both its name and its modelling lineage with an earlier package developed at the Network Systems Science and Advanced Computing division of the University of Virginia (Srini Venkatramanan et al., 2020). That package implements a metapopulation SEIR model and has been applied to seasonal influenza vaccine allocation (Srinivasan Venkatramanan et al., 2019) and to county-scale influenza forecasting in the United States (Srinivasan Venkatramanan et al., 2021). The earlier implementation was also used for age- and district-stratified COVID-19 vaccine allocation in Karnataka, as documented in a medRxiv preprint (Adiga et al., 2021). The approach was subsequently taken up in collaborative modelling work at the Indian Institute of Science and applied to foot-and-mouth disease in Indian livestock populations, which is the setting from which the present work grew. Where the earlier package provides a fixed SEIR compartmental structure serving a specific forecasting application, the framework described here generalises that approach: compartmental structure is treated as user-supplied configuration, so SIR, SEIR, SIRS, or arbitrary user-defined compartment sets are expressed in YAML without modifying source code. The name is retained to acknowledge this lineage. The earlier implementation is distributed as NSSAC/PatchSim; this package is distributed as patchsim from dsih-artpark/patchsim.

We did not build on the three closest tools for the following reasons. flepiMoP already declares compartments and transitions in YAML over a mobility matrix and offers a deterministic solver. At the time of writing it lacks variance-based sensitivity indices and bounded least-squares calibration, fits by Markov chain Monte Carlo, and its R and Python pipeline is larger than the single package the Karnataka work needed. MetaCast expresses the model as Python code, so a change in compartments is a code change. SimInf is stochastic only and moves animals by scheduled events rather than through a contact matrix, so it does not provide the deterministic comparison over district contact data that the Karnataka work needed.

PatchSim contributes the combination none of the three offers in one Python package with a command-line interface: a compartment graph and rate expressions declared in configuration, a user-supplied weighted patch matrix, categorical group stratification, a deterministic solver, Sobol sensitivity analysis, and bounded calibration. A modeller can switch between compartment structures, solvers, spatial networks, and group interaction inputs without rewriting the runtime.

Software design

PatchSim's central design principle is that compartmental model structure is declared in YAML rather than implemented in code. Transitions are written as source -> target keys, each paired with a rate formula:

```
compartments: [S, I, R]
Parameters: {beta: 0.2, gamma: 0.1}
Transitions:
  "S -> I": "beta"
  "I -> R": "gamma * I"
```

87 A rate expression that does not name its source compartment is multiplied by that compartment,
 88 so "S -> I": "beta" gives a local flow of βS_i . For focal patch i in an ungrouped multi-patch
 89 model, the infectious pressure is $\lambda_i(t) = \sum_j W_{ij} I_j(t) / N_j$, and the infection flow in this
 90 example is $\beta S_i \lambda_i$; a single ungrouped patch applies no coupling, and grouped models also
 91 multiply by the group interaction matrix. This is a residence-based coupling in the sense of the
 92 Lagrangian multi-patch models of Sattenspiel & Dietz (1995) and Citron et al. (2021). Patch
 93 populations stay fixed at N_i , and residents of patch i are exposed to the resident prevalence
 94 of each patch j in proportion to W_{ij} ; no population moves. The prevalence at patch j counts
 95 residents only, whereas the full Sattenspiel–Dietz model counts visiting infectives and visitors
 96 in both numerator and denominator.

97 A supplied W is applied as given and its rows are not normalized, so the scale of W multiplies β .
 98 The built-in contact-network generator can produce row-normalized weights with a self-share
 99 diagonal. Whether a supplied matrix should do the same, and whether it comes from a gravity
 100 kernel or observed movement data, is the modeller's choice. The spatial coupling is bound to
 101 the compartment names S, I, and E, and λ_i counts I alone.

102 ODE mode uses `scipy.integrate.odeint`, SciPy's interface to the LSODA solver, while
 103 discrete mode uses deterministic explicit Euler. Both evaluate the same derivative function;
 104 discrete results should be checked at successively smaller time steps. As a deterministic patch
 105 model, PatchSim does not represent stochastic fade-out or invasion probability in small patches
 106 (Ball et al., 2015; Riley, 2007). The current network is fixed from day zero. Patch populations,
 107 initial states, network weights, and optional group interactions are read from CSV files resolved
 108 relative to the configuration.

109 Validation checks required fields, identifiers, finite input values, population totals, matrix
 110 dimensions, transition endpoints, and an arithmetic-only expression language; these checks
 111 do not establish scientific validity. The JSON Schema is available for editors and external
 112 tooling. Reproducible analysis workflows provide seeded first- and total-order Sobol indices
 113 (Sobol', 2001) and bounded multi-start calibration with input hashes and diagnostics. Built-
 114 in SIR, SEIR, SIRS, and SIS templates and complete worked examples are included in the
 115 documentation. This bounded modularity is configuration- and API-based; adding a numerical
 116 solver still requires Python development. PatchSim is released under GPL-3.0.

117 Research impact statement

118 PatchSim is in current research use at ARTPARK for foot-and-mouth disease vaccination-
 119 scenario analysis across Karnataka districts, where it replaced a project-specific implementation.
 120 The workflow models cattle and buffalo populations stratified by age group and species. That
 121 analysis is unpublished at the time of writing, and no publication enabled by the package
 122 has yet appeared. Published spatial analysis of foot-and-mouth disease in India includes a
 123 state-level Bayesian space-time model of reported outbreaks, which estimated a roughly 50%
 124 lower outbreak risk in states covered by the vaccination programme (Gunasekera et al., 2022).
 125 The Karnataka analysis applies a mechanistic patch model to the between-district allocation
 126 question.

127 Near-term significance rests on what a third party can install, run, and check. The package has
 128 been developed in public since April 2025, with tagged releases on PyPI and an archived release
 129 record (Illikkal et al., 2026). Continuous integration runs the automated test suite, linting,
 130 and a documentation build on every pull request and push to the main branch. The tests

cover configuration validation, the expression evaluator, both solvers, group stratification, the sensitivity and calibration workflows, and the command-line interface. The seeded sensitivity and calibration outputs described above carry input hashes and diagnostics, so a third party can re-run and check a study. The documentation on Read the Docs includes worked examples.

AI usage disclosure

GitHub Copilot, OpenAI Codex CLI (GPT-5), and Anthropic Claude Code assisted with code, tests, and documentation, and with language checks and paraphrasing of the authors' draft of this paper. CodeRabbit assisted with code review. Model versions were not consistently retained for historical work. The authors reviewed, edited, tested, and validated all assisted outputs and made the scientific and architectural decisions.

Acknowledgements

The authors thank Prof. Rajesh Sundaresan and Prof. Siva Athreya for their guidance on the modelling work from which this framework grew, and Srinivasan Venkatramanan, whose earlier metapopulation modelling work informed the approach taken here. The authors also thank the ARTPARK team at the Indian Institute of Science for institutional support. This work was supported by the AI and Robotics Technology Park, ARTPARK, IISc, Bengaluru. The authors declare no conflicts of interest.

References

- Adiga, A., Athreya, S., Lewis, B., Marathe, M. V., Rathod, N., Sundaresan, R., Swarup, S., Venkatramanan, S., & Yasodharan, S. (2021). *Strategies to mitigate COVID-19 resurgence assuming immunity waning: A study for Karnataka, India* [Preprint]. medRxiv. <https://doi.org/10.1101/2021.05.26.21257836>
- Balcan, D., Colizza, V., Gonçalves, B., Hu, H., Ramasco, J. J., & Vespignani, A. (2009). Multiscale mobility networks and the spatial spreading of infectious diseases. *Proceedings of the National Academy of Sciences*, 106(51), 21484–21489. <https://doi.org/10.1073/pnas.0906910106>
- Balcan, D., Gonçalves, B., Hu, H., Ramasco, J. J., Colizza, V., & Vespignani, A. (2010). Modeling the spatial spread of infectious diseases: The GLObal Epidemic and Mobility computational model. *Journal of Computational Science*, 1(3), 132–145. <https://doi.org/10.1016/j.jocs.2010.07.002>
- Ball, F., Britton, T., House, T., Isham, V., Mollison, D., Pellis, L., & Scalia Tomba, G. (2015). Seven challenges for metapopulation models of epidemics, including households models. *Epidemics*, 10, 63–67. <https://doi.org/10.1016/j.epidem.2014.08.001>
- Bershteyn, A., Gerardin, J., Bridenbecker, D., Lorton, C. W., Bloedow, J., Baker, R. S., & others. (2018). Implementation and applications of EMOD, an individual-based multi-disease modeling platform. *Pathogens and Disease*, 76(5), fty059. <https://doi.org/10.1093/femspd/fty059>
- Bicker, J., Gerstein, C., Kerkmann, D., Korf, S., Schmieding, R., Wendler, A., & others. (2026). MEMilio: A high performance modular epidemics simulation software for multi-scale and comparative simulations of infectious disease dynamics. *Scientific Reports*, 16(1), 26950. <https://doi.org/10.1038/s41598-026-66481-6>
- Citron, D. T., Guerra, C. A., Dolgert, A. J., Wu, S. L., Henry, J. M., Sánchez C., H. M., & Smith, D. L. (2021). Comparing metapopulation dynamics of infectious diseases under

- different models of human movement. *Proceedings of the National Academy of Sciences*, 118(18), e2007488118. <https://doi.org/10.1073/pnas.2007488118>
- Gatto, M., Bertuzzo, E., Mari, L., Miccoli, S., Carraro, L., Casagrandi, R., & Rinaldo, A. (2020). Spread and dynamics of the COVID-19 epidemic in Italy: Effects of emergency containment measures. *Proceedings of the National Academy of Sciences*, 117(19), 10484–10491. <https://doi.org/10.1073/pnas.2004978117>
- Grenfell, B. T., & Harwood, J. (1997). (Meta)population dynamics of infectious diseases. *Trends in Ecology & Evolution*, 12(10), 395–399. [https://doi.org/10.1016/S0169-5347\(97\)01174-9](https://doi.org/10.1016/S0169-5347(97)01174-9)
- Grunnill, M., Arino, J., Ghasemi, A., Thommes, E. W., & Wu, J. (2024). MetaCast: A package for broadCASTing epidemiological and ecological models over META-populations. *Journal of Open Source Software*, 9(99), 6851. <https://doi.org/10.21105/joss.06851>
- Gunasekera, U., Biswal, J. K., Machado, G., Ranjan, R., Subramaniam, S., Rout, M., Mohapatra, J. K., Pattnaik, B., Singh, R. P., Arzt, J., Perez, A., & VanderWaal, K. (2022). Impact of mass vaccination on the spatiotemporal dynamics of FMD outbreaks in India, 2008–2016. *Transboundary and Emerging Diseases*, 69(5), e1936–e1950. <https://doi.org/10.1111/tbed.14528>
- Guyver-Fletcher, G., Gorsich, E. E., Jewell, C., & Tildesley, M. J. (2025). Controlling endemic foot-and-mouth disease: Vaccination is more important than movement bans. A simulation study in the Republic of Turkey. *Infectious Disease Modelling*, 10(2), 702–715. <https://doi.org/10.1016/j.idm.2025.02.006>
- Herman, J., & Usher, W. (2017). SALib: An open-source Python library for sensitivity analysis. *Journal of Open Source Software*, 2(9), 97. <https://doi.org/10.21105/joss.00097>
- Hladish, T., Melamud, E., Barrera, L. A., Galvani, A., & Meyers, L. A. (2012). EpiFire: An open source C++ library and application for contact network epidemiology. *BMC Bioinformatics*, 13, 76. <https://doi.org/10.1186/1471-2105-13-76>
- Illikkal, A. A., Mukherjee, S., & S, S. (2026). *PatchSim: A modular simulation framework for patch-based metapopulation epidemiology* (Version v0.1.1). Zenodo. <https://doi.org/10.5281/zenodo.22747707>
- Jenness, S. M., Goodreau, S. M., & Morris, M. (2018). EpiModel: An R package for mathematical modeling of infectious disease over networks. *Journal of Statistical Software*, 84(8), 1–47. <https://doi.org/10.18637/jss.v084.i08>
- Keeling, M. J., & Rohani, P. (2008). *Modeling infectious diseases in humans and animals*. Princeton University Press. ISBN: 9780691116174
- Keeling, M. J., Woolhouse, M. E. J., Shaw, D. J., Matthews, L., Chase-Topping, M., Haydon, D. T., Cornell, S. J., Kappey, J., Wilesmith, J., & Grenfell, B. T. (2001). Dynamics of the 2001 UK foot and mouth epidemic: Stochastic dispersal in a heterogeneous landscape. *Science*, 294(5543), 813–817. <https://doi.org/10.1126/science.1065973>
- Lemaitre, J. C., Loo, S. L., Kaminsky, J., Lee, E. C., McKee, C., Smith, C., Jung, S., Sato, K., Carcelen, E., Hill, A., Lessler, J., & Truelove, S. (2024). flepiMoP: The evolution of a flexible infectious disease modeling pipeline during the COVID-19 pandemic. *Epidemics*, 47, 100753. <https://doi.org/10.1016/j.epidem.2024.100753>
- Maier, B. F. (2021). EpiPack: An infectious disease modeling package for Python. *Journal of Open Source Software*, 6(60), 3097. <https://doi.org/10.21105/joss.03097>
- Riley, S. (2007). Large-scale spatial-transmission models of infectious disease. *Science*, 316(5829), 1298–1301. <https://doi.org/10.1126/science.1134695>
- Sattenspiel, L., & Dietz, K. (1995). A structured epidemic model incorporating geographic

- mobility among regions. *Mathematical Biosciences*, 128(1–2), 71–91. [https://doi.org/10.1016/0025-5564\(94\)00068-B](https://doi.org/10.1016/0025-5564(94)00068-B)
- Sobol', I. M. (2001). Global sensitivity indices for nonlinear mathematical models and their Monte Carlo estimates. *Mathematics and Computers in Simulation*, 55(1–3), 271–280. [https://doi.org/10.1016/S0378-4754\(00\)00270-6](https://doi.org/10.1016/S0378-4754(00)00270-6)
- Tildesley, M. J., Savill, N. J., Shaw, D. J., Deardon, R., Brooks, S. P., Woolhouse, M. E. J., Grenfell, B. T., & Keeling, M. J. (2006). Optimal reactive vaccination strategies for a foot-and-mouth outbreak in the UK. *Nature*, 440(7080), 83–86. <https://doi.org/10.1038/nature04324>
- Van den Broeck, W., Gioannini, C., Gonçalves, B., Quaggitto, M., Colizza, V., & Vespignani, A. (2011). The GLEaMviz computational tool, a publicly available software to explore realistic epidemic spreading scenarios at the global scale. *BMC Infectious Diseases*, 11, 37. <https://doi.org/10.1186/1471-2334-11-37>
- Venkatramanan, Srini, Bhattacharya, P., Porebski, P., & Klahn, B. (2020). *NSSAC/PatchSim: First official release* (Version v1.0). Zenodo. <https://doi.org/10.5281/zenodo.4313095>
- Venkatramanan, Srinivasan, Chen, J., Fadikar, A., Gupta, S., Higdon, D., Lewis, B., Marathe, M., Mortveit, H., & Vullikanti, A. (2019). Optimizing spatial allocation of seasonal influenza vaccine under temporal constraints. *PLOS Computational Biology*, 15(9), e1007111. <https://doi.org/10.1371/journal.pcbi.1007111>
- Venkatramanan, Srinivasan, Sadilek, A., Fadikar, A., Barrett, C. L., Biggerstaff, M., Chen, J., Dotiwala, X., Eastham, P., Gipson, B., Higdon, D., Kucuktunc, O., Lieber, A., Lewis, B. L., Reynolds, Z., Vullikanti, A. K., Wang, L., & Marathe, M. (2021). Forecasting influenza activity using machine-learned mobility map. *Nature Communications*, 12(1), 726. <https://doi.org/10.1038/s41467-021-21018-5>
- Wesolowski, A., Qureshi, T., Boni, M. F., Sundsøy, P. R., Johansson, M. A., Rasheed, S. B., Engø-Monsen, K., & Buckee, C. O. (2015). Impact of human mobility on the emergence of dengue epidemics in Pakistan. *Proceedings of the National Academy of Sciences*, 112(38), 11887–11892. <https://doi.org/10.1073/pnas.1504964112>
- Widgren, S., Bauer, P., Eriksson, R., & Engblom, S. (2019). SimInf: An R package for data-driven stochastic disease spread simulations. *Journal of Statistical Software*, 91(12), 1–42. <https://doi.org/10.18637/jss.v091.i12>
- Woods, C., Hedges, L., Edsall, C., Brooks-Pollock, E., Parton-Fenton, C., McKinley, T., Keeling, M., & Danon, L. (2022). MetaWards: A flexible metapopulation framework for modelling disease spread. *Journal of Open Source Software*, 7(70), 3914. <https://doi.org/10.21105/joss.03914>