The Journal of Open Source Software

GRBoondi: A code for evolving Generalized Proca theories on arbitrary backgrounds

Shaun David Brocus Fell [1] **and Lavinia Heisenberg** [1]

1 Institute for Theoretical Physics, Universitaet Heidelberg, Philosophenweg 12, 69120 Heidelberg, Germany

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Juanjo Bazán

Reviewers:

- @Sbozzolo
- @KAClough

Submitted: 07 May 2024
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

Proca theories are a simple massive extension of the typical electromagnetic field. Such a simple modification of the underlying theory can have tremendous phenomenological implications, particularly in the case of early-universe high-energy physics, structure formation, and various dark matter models. On the theoretical side, they arise naturally in certain string theories and axionic interactions. Phenomenologically, Proca fields can be produced in the early universe from quantum fluctuations. This leads the Proca field to be an excellent candidate for the dark matter particle. Naturally, generalizations of the Proca field can lead to even richer astrophyical implications, providing possible solutions to many challenges across a wide range of astrophysical phenomena.

Generalized Proca

Generalized Proca theories (Heisenberg, 2014, 2019) provide a rich landscape to search for solutions to deep, fundamental questions, such as the nature of dark energy and dark matter. Moreover, strong gravity regimes, like those surrounding dense, compact astrophysical entities, offer novel avenues to explore fundamental fields. To effectively probe these domains, precise models are imperative for sifting through vast quantities of data. Crafting concrete models for the entirety of generalized Proca theories represents a formidable endeavor, typically relying on numerical methods. These numerical methods are usually written to be case dependent, especially for a particular background. This makes it difficult to generalize the computational code to account for higher-order couplings or different types of backgrounds. The difficulty is especially amplified when considering the full landscape of generalized Proca theories and beyond (Heisenberg et al., 2016). Already at the level of the Lagrangian, the equations are immense,

$$\mathcal{L}_{\text{g.P.}} = \sqrt{-g}\left(-\frac{1}{4}F_{\mu\nu}F^{\mu\nu} + \sum_{n=2}^{6}\alpha_n\mathcal{L}_n\right) ,$$

where each sub-Lagranian $\mathcal{L}_n$ contains terms of different orders in the derivatives of the Proca field (Heisenberg, 2014, 2019). Even including solely $\mathcal{L}_2$, the equations of motion can be extremely cumbersome. Solving these equations of motion analytically very quickly becomes intractable.

GRBoondi provides a unified interface for computing the evolution of any generalized Proca model on an arbitrary background. Given a specific background with known expressions for the metric variables and initial data for the Proca field, GRBoondi numerically computes the time evolution of the Proca field, given user-specified generalized Proca equations of motion. While the simultaneous evolution of the metric and matter fields offers the most comprehensive depiction of their temporal progression, there are instances where the density of the Proca field is negligible in comparison to the background curvature. In such cases, fixed background

evolution routines serve as an excellent approximation to the complete mutual evolution. A core feature of GRBoondi is that it simplifies many of the boiler-plate code required to begin a simulation from scratch. The only additions a user needs to input are the initial conditions, the modifications to the equations of motion (EOM), and the background functions. GRBoondi will automatically compute various diagnostic quantities and plot files. Moreover, GRBoondi is incredibly modular and modifications to any of the in-built functions is effortless.

The fixed background approximation provides a huge speedup compared to the full evolution of the Einstein equations, since only a small fraction of the variables actually require a time integration. Not only do simulations now require far less resources, the speed up can be up to hundreds of times faster. GRBoondi is based on the publicly available numerical relativity (NR) code GRChombo (Andrade et al., 2021; Clough et al., 2015), which itself is based on the open source adaptive mesh refinement (AMR)-based differential equation solver Chombo (Adams et al., 2015). Some smaller pieces of GRBoondi are also based off the recently released open source software GRDzhadzha (Aurrekoetxea et al., 2024), which is also based off of GRChombo. These comprise the core dependencies of GRBoondi.

Statement of need

In practice, any NR software library can be used to evolve generalized Proca theories. Prominent examples of NR codes encompass the extensive Einstein toolkit (Cupp & others, 2023) and its related Cactus framework (Goodale et al., 2003), Kranc (Husa et al., 2006), LEAN (Sperhake, 2007), and Canuda (Witek et al., 2021). Other libraries worth mentioning are the non-public BAM (Bruegmann et al., 2008), AMSS-NCKU (Galaviz et al., 2010), PAMR (East et al., 2012) and HAD (Neilsen et al., 2007). The non-exhaustive list can be expanded with SPeC (Pfeiffer et al., 2003), which is a pseudo-spectral code that uses generalized harmonic coordinates. Similarly, SpECTRE (Cao et al., 2018; Deppe et al., 2021; Kidder & others, 2017) uses the Galerkin methods. NRPy (Ruchlin et al., 2018) is a python library that aims for use on non-high performance computing clusters. There are also cosmological simulation codes like CosmoGRaPH (Mertens et al., 2016) and GRAMSES (Barrera-Hinojosa & Li, 2020). Simflowny (Palenzuela et al., 2018) is a magneto-hydrodynamic simulation software. GRAthena++ (Daszuta et al., 2021) uses the oct-tree AMR for maximum scaling. ExaGRyPE is a numerical relativity program leveraging the ExaHyPRE PDE solver (Zhang et al., 2024). GRDzhadzha (Aurrekoetxea et al., 2024) is another fixed background code, based off the GRChombo (Andrade et al., 2021) framework, which GRBoondi utilizes.

This extensive list underscores the abundance of NR libraries at one's disposal. However, none of them provide a tailored unified interface for studying the vast landscape of gravity theories, like generalized Proca. Using any of the numerous frameworks requires significant work in order to evolve even a single generalized Proca theory. GRBoondi tackles this problem by providing a collection of specialized tools for computing the generalized Proca equations, relying on existing tools which allows for rapid updating and debugging. On top of this, GRBoondi offers catered plotting routines for viewing data, leveraging the highly parallelizable VisIt (Childs et al., 2012) analysis tool. In addition, since the metric variables and their derivatives are computed exactly at each grid point, the adaptability of the AMR grid can be focused solely on the matter variables.

While backreaction is neglected in GRBoondi, the error incured by this approximation is estimated by computing the norm of the energy-momentum tensor. This estimation takes into account the relativistic nature of the matter field and gauges the error in the evolution at the level of the Einstein equations.

Since GRBoondi is very similar to the GRChombo code, simulations performed with GRBoondi can easily be ported to GRChombo, should full NR simulations be required. This is particularly useful if the backreaction is found to be significant at some point in the simulation. The data from a GRBoondi simulation can be used as initial data for a GRChombo simulation,

potentially yielding much better initial data for the full NR simulation.

Key features of GRBoondi

- **Ease of use**: A central pillar of GRBoondi is its ease of use, relative to other NR software. Many of the basic boiler-plate code and complexities are kept within the source code, allowing the user to have only a basic understanding of the code in order to start researching their problem.
- **Arbitrary choice of background spacetime**: The main parts of GRBoondi are extremely modular, allowing for any arbitrary background to be plugged in, even a numerically computed one. This allows for massive versatility in the source code. Users can swap in and out backgrounds with ease. GRBoondi comes pre-equipped with four background classes ready for use, along with testing suites to verify convergence of each class. These include (starred backgrounds are inherited from GRDzhadzha and are immediately usable in GRBoondi):
  - Minkowski Space
  - Kerr-de Sitter black hole
  - *Boosted Schwarzschild black hole
  - *Kerr black hole
- **Arbitrary modifications to base Proca**: GRBoondi uses specific coding idioms that allow arbitrary modifications to the hard-coded equations of motion. This allows for numerical simulations of any generalized Proca theory. The base model is the standard electromagnetic model, subject to the usual Proca constraint. Any generalized Proca theory can be added on top of this by simply adding the additional pieces from the generalized Proca Lagrangian. Examples of simulating standard Proca and a simple non-linear model (Clough et al., 2022; Coates & Ramazanoğlu, 2022; Ünlütürk et al., 2023) are included in the codes repository.
- **Accuracy**: The metric values and their derivatives are computed exactly at each point, while the matter variables are evolved using 4th-order Runge-Kutta time integration and their spatial derivatives calculated using the same finite difference stencils as GRChombo (6th-order stencils are also available from the GRChombo dependency).
- **Various boundary conditions**: Since GRBoondi inherits from GRChombo, all the boundary conditions in GRChombo are also straight-forwardly applicable to GRBoondi. GRBoondi thus supports:
  - Periodic boundary conditions
  - Sommerfeld out-going wave conditions
  - Static boundary conditions
  - Extrapolation at linear and zeroth order
  - Reflective symmetry (e.g. simulating only the top-half of the computational box due to the background symmetry)
- **Checkpointing**: Since GRBoondi inherits from Chombo, it inherits the checkpointing feature. Simulations can be restarted from a checkpoint file saved during the previous run, allowing for arbitrarily long simulations, even on restricted computing clusters. Moreover, should a simulation fail for any reason, it can be restarted using a previous checkpoint.
- **Diagnostics**: GRBoondi comes equipped with many different diagnostic quantities that can be calculated during the course of a simulation and additional tools for users to calculate their own quantities.
  - *Computation of conserved quantities*. Computation of conserved quantities, such as energy and angular momentum densities and their associated fluxes across a

DRAFT

surface can be toggled. GRBoondi can also calculate the energy-momentum tensor trace and its square, for studying the importance of backreaction. Some of the included diagnostic quantities are the square of the Proca field, conserved energy density, Eulerian energy density, conserved angular momentum, conserved energy density flux, conserved angular momentum flux, trace of the energy-momentum tensor, and square of the energy-momentum tensor. The conserved energy and angular momentum correspond to approximate time and rotational killing vectors. These can be disabled if the spacetime does not possess these. The conserved momentums and fluxes computations are inherited from GRDzhadzha.
  - *Excision of diagnostics in user-specified regions*. Currently, only spherical excision is implemented, where the user specifies the minimum and maximum radius for the diagnostic quantities. The user can specify which quantities they wish to excise as well, as specified in a parameter file. Generalization to more complicated diagnostic regions is case dependent and left up to the user.
  - *Integration of quantities across the computational grid*. The user can specify which quantities they wish to integrate.
  - *Integration of quantities across spherical surfaces*. The user can specify which quantities they wish to integrate over a spherical surface and the radii of those surfaces as well.

- **Tailored post-processing tools**: GRBoondi comes equipped with custom-built post-processing scripts, leveraging VisIt's python interface. Any of the diagnostic quantities computed during the evolution can be plotted using these tools. It also contains a simple integral plotter, for quickly visualizing the various integrals computed during a simulation, leveraging python's Matplotlib package (Hunter, 2007)



Figure 1: Some examples of the usage of GRBoondi. The left image is the energy density of a Proca cloud superradiantly excited around a rapidly spinning black hole, superimposed with streamlines of the spatial Proca vector field. The right image is a plot in the xz-plane of the square of the Proca 4-vector in the same background. The spin axis of the black hole is orientated along the z-axis. Superimposed on both images is a slice of the computational grid, clearly showing the refinement hierarchy.

Acknowledgements

LH is supported by funding from the European Research Council (ERC) under the European Unions Horizon 2020 research and innovation programme grant agreement No 801781. LH further acknowledges support from the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy EXC 2181/1 - 390900948 (the Heidelberg STRUCTURES Excellence Cluster).

SF is indebted to Katy Clough for her stimulating discussions and extensive input to the code. Katy was an invaluable source of aid for the nuances of NR simulations and some of the finer

details of GRChombo.

The simulations performed as part of this release were carried out on the Baden-Württemberg high-performance computing cluster. The authors acknowledge support by the state of Baden-Württemberg through bwHPC.

References

Adams, M., Colella, P., Graves, D. T., Johnson, J. N., Keen, N. D., Ligocki, T. J., Martin, D. F., McCorquodale, P. W., Modiano, D., Schwartz, P. O., D., S. T., & Van Straalen, B. (2015). *Chombo software package for AMR applications - design document*. https://commons.lbl.gov/display/chombo

Andrade, T., Salo, L. A., Aurrekoetxea, J. C., & others. (2021). GRChombo: An adaptable numerical relativity code for fundamental physics. *Journal of Open Source Software*, *6*(68), 3703. https://doi.org/10.21105/joss.03703

Aurrekoetxea, J. C., Bamber, J., Brady, S. E., & others. (2024). GRDzhadzha: A code for evolving relativistic matter on analytic metric backgrounds. *Journal of Open Source Software*, *9*(96), 5956. https://doi.org/10.21105/joss.05956

Barrera-Hinojosa, C., & Li, B. (2020). GRAMSES: a new route to general relativistic N-body simulations in cosmology. Part I. Methodology and code description. *JCAP*, *01*, 007. https://doi.org/10.1088/1475-7516/2020/01/007

Bruegmann, B., Gonzalez, J. A., Hannam, M., & others. (2008). Calibration of Moving Puncture Simulations. *Phys. Rev. D*, *77*, 024027. https://doi.org/10.1103/PhysRevD.77.024027

Cao, Z., Fu, P., Ji, L.-W., & others. (2018). Application of local discontinuous Galerkin method to Einstein equations. *Int. J. Mod. Phys. D*, *28*(01), 1950014. https://doi.org/10.1142/S0218271819500147

Childs, H., Brugger, E., Whitlock, B., & others. (2012). *High Performance Visualization–Enabling Extreme-Scale Scientific Insight*. https://doi.org/10.1201/b12985

Clough, K., Figueras, P., Finkel, H., & others. (2015). GRChombo : Numerical Relativity with Adaptive Mesh Refinement. *Class. Quant. Grav.*, *32*(24), 245011. https://doi.org/10.1088/0264-9381/32/24/245011

Clough, K., Helfer, T., Witek, H., & others. (2022). Ghost instabilities in self-interacting vector fields: The problem with proca fields. *Physical Review Letters*, *129*(15). https://doi.org/10.1103/physrevlett.129.151102

Coates, A., & Ramazanoğlu, F. M. (2022). *The intrinsic pathology of self-interacting vector fields*. https://doi.org/10.48550/arXiv.2205.07784

Cupp, S., & others. (2023). *The einstein toolkit* (The "Lise Meitner" release, ET_2023_11). Zenodo. https://doi.org/10.5281/zenodo.10380404

Daszuta, B., Zappa, F., Cook, W., & others. (2021). GR-Athena++: Puncture Evolutions on Vertex-centered Oct-tree Adaptive Mesh Refinement. *Astrophys. J. Supp.*, *257*(2), 25. https://doi.org/10.3847/1538-4365/ac157b

Deppe, N., Throwe, W., Kidder, L. E., & others. (2021). *SpECTRE* (Version 2021.05.03). Zenodo. https://doi.org/10.5281/zenodo.4734670

East, W. E., Pretorius, F., & Stephens, B. C. (2012). Hydrodynamics in full general relativity with conservative AMR. *Phys. Rev. D*, *85*, 124010. https://doi.org/10.1103/PhysRevD.85.124010

Galaviz, P., Bruegmann, B., & Cao, Z. (2010). Numerical evolution of multiple black holes

DRAFT

with accurate initial data. *Phys. Rev. D*, *82*, 024005. https://doi.org/10.1103/PhysRevD.82.024005

Goodale, T., Allen, G., Lanfermann, G., & others. (2003). The Cactus framework and toolkit: Design and applications. *Vector and Parallel Processing – VECPAR'2002, 5th International Conference, Lecture Notes in Computer Science*. https://doi.org/10.1007/3-540-36569-9_13

Heisenberg, L. (2014). Generalization of the proca action. *Journal of Cosmology and Astroparticle Physics*, *2014*(05), 015–015. https://doi.org/10.1088/1475-7516/2014/05/015

Heisenberg, L. (2019). A systematic approach to generalisations of general relativity and their cosmological implications. *Physics Reports*, *796*, 1–113. https://doi.org/10.1016/j.physrep.2018.11.006

Heisenberg, L., Kase, R., & Tsujikawa, S. (2016). Beyond generalized Proca theories. *Phys. Lett. B*, *760*, 617–626. https://doi.org/10.1016/j.physletb.2016.07.052

Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, *9*(3), 90–95. https://doi.org/10.1109/MCSE.2007.55

Husa, S., Hinder, I., & Lechner, C. (2006). Kranc: A Mathematica application to generate numerical codes for tensorial evolution equations. *Comput. Phys. Commun.*, *174*, 983–1004. https://doi.org/10.1016/j.cpc.2006.02.002

Kidder, L. E., & others. (2017). SpECTRE: A Task-based Discontinuous Galerkin Code for Relativistic Astrophysics. *J. Comput. Phys.*, *335*, 84–114. https://doi.org/10.1016/j.jcp.2016.12.059

Mertens, J. B., Giblin, J. T., & Starkman, G. D. (2016). Integration of inhomogeneous cosmological spacetimes in the BSSN formalism. *Phys. Rev. D*, *93*(12), 124059. https://doi.org/10.1103/PhysRevD.93.124059

Neilsen, D., Hirschmann, E. W., Anderson, M., & others. (2007). Adaptive Mesh Refinement and Relativistic MHD. *11th Marcel Grossmann Meeting on General Relativity*, 1579–1581. https://doi.org/10.1142/9789812834300_0200

Palenzuela, C., Miñano, B., Viganò, D., & others. (2018). A Simflowny-based finite-difference code for high-performance computing in numerical relativity. *Class. Quant. Grav.*, *35*(18), 185007. https://doi.org/10.1088/1361-6382/aad7f6

Pfeiffer, H. P., Kidder, L. E., Scheel, M. A., & others. (2003). A Multidomain spectral method for solving elliptic equations. *Comput. Phys. Commun.*, *152*, 253–273. https://doi.org/10.1016/S0010-4655(02)00847-0

Ruchlin, I., Etienne, Z. B., & Baumgarte, T. W. (2018). SENR/NRPy+: Numerical Relativity in Singular Curvilinear Coordinate Systems. *Phys. Rev. D*, *97*(6), 064036. https://doi.org/10.1103/PhysRevD.97.064036

Sperhake, U. (2007). Binary black-hole evolutions of excision and puncture data. *Phys. Rev. D*, *76*, 104015. https://doi.org/10.1103/PhysRevD.76.104015

Ünlütürk, K. İ., Coates, A., & Ramazanoğlu, F. M. (2023). Loss of hyperbolicity and tachyons in generalized proca theories. *Physical Review D*, *108*(4). https://doi.org/10.1103/physrevd.108.044022

Witek, H., Zilhao, M., Bozzola, G., & others. (2021). *Canuda: a public numerical relativity library to probe fundamental physics*. Zenodo. https://doi.org/10.5281/zenodo.3565474

Zhang, H., Li, B., Weinzierl, T., & Barrera-Hinojosa, C. (2024). *ExaGRyPE: Numerical general relativity solvers based upon the hyperbolic PDEs solver engine ExaHyPE*. https://arxiv.org/abs/2406.11626

DRAFT