The Journal of Open Source Software

# DeepHyper: Massively Parallel Hyperparameter Optimization for Machine Learning

**Romain Egele**[1*¶], **Prasanna Balaprakash**[1*], **Gavin M. Wiggins**[1], and **Brett Eiffert**[1]

**1** Oak Ridge National Laboratory, Tenesse, United States ¶ Corresponding author * These authors contributed equally.

**DOI:** 10.xxxxxx/draft

**Software**

- Review
- Repository
- Archive

**Editor:** Mehmet Hakan Satman

**Reviewers:**

- @jungtaekkim
- @y0z

**Submitted:** 10 March 2025
**Published:** unpublished

**License**
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

## Summary

Machine learning models are increasingly applied across scientific disciplines, yet their effectiveness often hinges on heuristic decisions—such as data transformations, training strategies, and model architectures—that are not learned by the models themselves. Automating the selection of these heuristics and analyzing their sensitivity is crucial for building robust and efficient learning workflows. `DeepHyper` addresses this challenge by democratizing hyperparameter optimization, providing accessible tools to streamline and enhance machine learning workflows from a laptop to the largest supercomputer in the world. Building on top of hyperparameter optimization it unlock new capabilities around ensembles of models for improved accuray and uncertainty quantification. All of these organized around efficient parallel computing.

**Figure 1:** DeepHyper Logo

## Statement of need

`DeepHyper` is a Python package for parallel hyperparameter optimization or neural architecture search. It provides access to a variety of asynchronous parallel black-box optimization algorithms `deephyper.hpo`. The software offers a variety of parallel programming backends such as Asyncio, threading, processes, Ray, and MPI `deehyper.evaluator`. The hyperparameter optimization can be single or multi-objective, composed of mixed variables, using explicit or

hidden constraints, and benefit from early-discarding strategies `deephyper.stopper`. Leveraging the results of hyperparameter optimization or neural architecture search it provides parallel ensemble algorithms `deephyper.ensemble` that can help improve accuracy or quantify disentangled predictive uncertainty.




**Figure 2:** DeepHyper Software Architecture

DeepHyper was designed to help research in the field of automated machine learning and also to be used out-of-the box in scientific projects where learning workflows are being developed.

# Mathematics

DeepHyper main hyperparameter optimization algorithm is based on Bayesian optimization.

It can work with mixed-integer problems (i.e., including real, discrete, categorical values), with explicit or implicit constraints (e.g., $x_0 < x_1$, unexpected out-of-memory error), and stochastic objective functions $Y = f(x)$ where $Y$ is a random variable, $x$ is a vector of input hyperparameters and $f$ is the objective function.

The Bayesian optimization of the DeepHyper relies by default on Extremely Randomized Forest assurrogate model to estimate $E_Y[Y|X = x]$. Extremely Randomized Forest are a kind of Random Forest where the split decision involves a random process for each newly created node of a tree. It provides smoother epistemic uncertainty estimates compared to usual Random Forests that use a deterministic "best" split decision.




Then, a custom acquisition function `UCBd`, focuses on the epistemic uncertainty of this surrogate for improved efficiency. It is also combined with a periodic exponential decay (impacting exploration-exploitation parameters of BO) to escape local solutions (Egelé et al., 2023).




**Figure 3:** Periodic Exponential Decay for Bayesian Optimization

Batch parallel genetic algorithms are provided to resolve efficiently the sub-problem of optimizing the acquisition function and it is also more accurate than Monte-Carlo approches to find the optimum of the acquisition function. A cheap and efficient multi-point acquisition strategy `qUCBd` is provided for better parallel scalability (Egelé et al., 2023).

The multi-objective optimization is enabled by scalarization functions and objective rescaling (Égelé et al., 2023).

The early-discarding strategies include asynchronous successive halving and a robust learning curve extrapolation (Egele et al., 2024).

The ensemble strategies is modular to allow: exploring models tested during hyperparameter optimization, classification and regression problems to be treated, disentangled uncertainty quantification (Égelé et al., 2022).

A transfer-learning strategy for hyperparameter optimization (Dorier et al., 2022) is also available. This strategy used to be based on variational auto-encoders for tabular data. It is now based on Gaussian mixture-model for tabular data.

# Acknowledgements

We acknowledge contributions from Misha Salim, Romit Maulik, Venkat Vishwanath, Stefan Wild, Joceran Gouneau, Dipendra Jha, Kyle Felker, Matthieu Dorier, Felix Perez, Bethany Lush, Gavin M. Wiggins, Tyler H. Chang, Yixuan Sun, Shengli Jiang, rmjcs2020, Albert Lam, Taylor Childers, Z223I, Zachariah Carmichael, Hongyuan Liu, Sam Foreman, Akalanka Galappaththi, Brett Eiffert, Sun Haozhe, Sandeep Madireddy, Adrian Perez Dieguez, and Nesar Ramachandra. We also would like to thank Prof. Isabelle Guyon for her guidance on the machine learning methodologies developed in this software.

# References

Dorier, M., Égelé, R., Balaprakash, P., Koo, J., Madireddy, S., Ramesh, S., Malony, A. D., & Ross, R. (2022). HPC storage service autotuning using variational- autoencoder -guided asynchronous bayesian optimization. *2022 IEEE International Conference on Cluster Computing (CLUSTER)*, 381–393. https://doi.org/10.1109/CLUSTER51413.2022.00049

Egele, R., Mohr, F., Viering, T., & Balaprakash, P. (2024). The unreasonable effectiveness of early discarding after one epoch in neural network hyperparameter optimization. *Neurocomputing*, 127964. https://doi.org/10.1016/j.neucom.2024.127964

Egelé, R., Guyon, I., Vishwanath, V., & Balaprakash, P. (2023). Asynchronous decentralized bayesian optimization for large scale hyperparameter optimization. *2023 IEEE 19th Interna-*

DRAFT

*tional Conference on e-Science (e-Science)*, 1–10. https://doi.org/10.1109/e-Science58273.2023.10254839

Égelé, R., Chang, T., Sun, Y., Vishwanath, V., & Balaprakash, P. (2023). Parallel multi-objective hyperparameter optimization with uniform normalization and bounded objectives. *arXiv Preprint arXiv:2309.14936*.

Égelé, R., Maulik, R., Raghavan, K., Lusch, B., Guyon, I., & Balaprakash, P. (2022). AutoDEUQ: Automated deep ensemble with uncertainty quantification. *26th International Conference on Pattern Recognition (ICPR)*, 1908–1914. https://doi.org/10.1109/ICPR56361.2022.9956231

DRAFT