The Journal of Open Source Software

tobler: Spatial interpolation and areal analysis for Python

Elijah Knaap [1*], **Sergio J. Rey** [2*], **Renan X. Cortes** [3*], **Martin Fleischmann** [4*], **James D. Gaboardi** [5*], **and Daniel Arribas-Bel** [6*]

1 University of California, Irvine **2** San Diego State University **3** Federal University of Rio Grande do Sul **4** Charles University, Faculty of Science **5** Geospatial Science and Human Security, Oak Ridge National Laboratory **6** University of Liverpool ***** These authors contributed equally.

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Richard Littauer

Reviewers:

- @JazHamiltonX22
- @YahorKliutsuk
- @Zeitsperre

Submitted: 14 June 2026
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

`tobler` is an open-source Python library for spatial interpolation and areal data transformation, designed to support a wide range of workflows in geographic information science (GIScience), spatial data science, and applied spatial analysis. The package provides a unified, extensible framework for transferring data between incompatible zonal systems—an essential task when working with spatially aggregated data such as census geographies, administrative boundaries, or service areas.

Areal interpolation is a foundational problem in spatial analysis, arising whenever data collected over one set of polygons (source zones) must be reallocated to another (target zones) with different spatial configurations. `tobler` implements a suite of methods for this task, ranging from simple area-weighted interpolation to more advanced dasymetric and model-based approaches. The package is designed to operate natively on GeoPandas GeoDataFrames, enabling seamless integration into modern Python-based geospatial workflows.

As part of the Python Spatial Analysis Library (PySAL) ecosystem (S. J. Rey et al., 2022; S. J. Rey & Anselin, 2007), `tobler` emphasizes composability, transparency, and reproducibility while providing robust implementations of areal interpolation methods for both applied and methodological research.

Statement of need

Spatial data are commonly aggregated to administrative units such as census tracts, ZIP codes, or political boundaries, which often differ across datasets or change over time. As a result, transferring variables between incompatible zoning systems is a common challenge for longitudinal analysis, data integration, and cross-scale comparison, particularly in the social and behavioral sciences. While Python packages such as `PyKrige` (Murphy et al., 2025) and `pyinterpolate` (Moliński, 2022) support *continuous* spatial interpolation, they are not designed for interpolation between discrete zoning systems.

Traditional GIS software (e.g., ArcGIS, QGIS (Dawson et al., 2026)) provides tools for areal interpolation, but these implementations are often embedded in graphical interfaces, limiting reproducibility and automation. Moreover, they may not expose the full range of methodological options or allow for easy integration into data science pipelines.

Prior to `tobler`, the Python ecosystem support for areal interpolation was fragmented or limited. While foundational libraries such as GeoPandas provide data structures and geometric operations, they do not natively implement interpolation methods. As a result, users often

DRAFT

relied on *ad hoc* scripts or external tools, leading to inconsistent workflows and potential methodological errors.

`tobler` addresses these challenges by providing:

- A coherent and well-documented API for areal interpolation
- Native integration with GeoPandas and the PySAL ecosystem
- Area-weighted, dasymetric, and model-based interpolation methods
- Reproducible workflows

These capabilities make `tobler` particularly valuable for researchers and practitioners in fields such as geography, urban planning, public health, environmental science, and regional economics, where spatial data integration is a routine requirement.

State of the field

`tobler` is a component of the PySAL ecosystem (S. Rey, Stephens, et al., 2026), which provides a comprehensive suite of tools for spatial analysis in Python. This ecosystem consists of four layers of related packages:

- `libpysal` for foundational spatial data structures and utilities (S. Rey, Wolf, et al., 2026)
- `explore` for exploratory spatial analysis
- `model` for spatial modeling
- `viz` provides classification schemes for choropleth mapping

Within this ecosystem, **`tobler`** occupies a critical niche by providing the data integration and interpolation methods necessary to harmonize datasets before analysis in the **explore** or **model** phases.

`tobler` complements these packages by addressing the specific problem of spatial data transformation between incompatible zonal systems. Compared to desktop GIS platforms, `tobler` offers advantages like **Reproducibility**, **Transparency**, **Extensibility**, and **Integration**.

While similar functionality exists in other ecosystems (e.g., R packages such as `areal` (Prener et al., 2019) or `sf`-based workflows (Pebesma, 2018)), `tobler` provides a native solution for Python users.

Software design

`tobler` is designed with attention to both computational efficiency and usability. Spatial overlay operations, which are central to areal interpolation, can be computationally intensive for large datasets. The package leverages vectorized operations and efficient geometric libraries (via GeoPandas (Fleischmann et al., 2026) and Shapely (Gillies et al., 2026)) to handle these tasks.

The API design emphasizes clarity and consistency, with function signatures that explicitly distinguish between extensive and intensive variables. Intensive variables are things like rates or percentages that must be averaged when aggregating, whereas extensive variables are things like counts that must be summed during aggregation.

Additionally, `tobler` is developed with testing and documentation standards consistent with the Scientific Python ecosystem, ensuring reliability and maintainability.

Core Functionality

`tobler` organizes its functionality around several key interpolation paradigms, each corresponding to different assumptions about how variables are distributed within source zones.

DRAFT

Area-weighted interpolation

Area-weighted interpolation assumes that variables are uniformly distributed within each source zone and allocates values to target zones in proportion to the area of overlap.

`tobler` provides efficient implementations for both **extensive variables** (e.g., population counts) and **intensive variables** (e.g., rates or densities), ensuring appropriate handling of each type (Goodchild & Lam, 1980). The library also supports pycnophylactic adjustments to preserve totals where required (Tobler, 1979).

Dasymetric interpolation

Dasymetric interpolation uses ancillary data (e.g., land use or land cover) to model within-zone heterogeneity (Eicher & Brewer, 2001; Mennis & Hultgren, 2006; Reibel & Agrawal, 2007). `tobler` supports both vector- and raster-based dasymetric workflows, allowing users to integrate a wide range of auxiliary datasets. This is particularly useful in urban and environmental applications where fine-scale heterogeneity is important.

Model-based interpolation

Beyond deterministic approaches, `tobler` includes model-based methods that use statistical or machine learning techniques to estimate spatial distributions. These approaches incorporate covariates and capture more complex spatial patterns, providing improved accuracy in many contexts (Flowerdew & Aitkin, 1982; Flowerdew & Green, 1992).

Integration with GeoPandas

All interpolation methods in `tobler` operate directly on GeoPandas GeoDataFrames and return GeoDataFrames, enabling seamless integration with the broader Python geospatial ecosystem.

Example workflow

A typical area-weighted interpolation in `tobler` is implemented as follows:

```
from tobler.area_weighted import area_interpolate

result = area_interpolate(
    source_df,
    target_df,
    extensive_variables=["population"],
    intensive_variables=["income"]
)
```

This operation transfers population counts and income measures from the source geometries to the target geometries, handling each variable type (extensive/intensive) appropriately.

When additional information about within-zone heterogeneity is available, dasymetric interpolation can be used to refine estimates. For example, population counts may be redistributed using a land cover raster to exclude uninhabited areas:

```
from tobler.dasymetric import masked_area_interpolate

result = masked_area_interpolate(
    raster="raster_file_name.tif",
    source_df,
    target_df,
    pixel_values = [21,22,23,24],
    extensive_variables=["population"]
)
```

DRAFT

Similarly, the user can execute a model-based approach using the `tobler.model.glm` function.

Figure 1 illustrates an example comparing interpolated values derived from different spatial configurations, highlighting how results may vary depending on the underlying geometry and interpolation approach.




Figure 1: Example of `tobler` usage for a single extensive variable – employed male population – (no intensive variable) in Charleston, SC, comparing census tracts and ZCTAs.

Research impact statement

The package is actively used by the research community to transfer the data between various types of geographic boundaries. This is not limited to specific applications but covers use cases from continental analysis of emissions and health (La Porta & Zapperi, 2024), analysis of urban form and function (Fleischmann & Arribas-Bel, 2022), redistribution of census data to school districts for assessment of the Clean School Bus Rebate Program (Osia et al., 2025), quantification of radon exposure (Lee et al., 2026), and harmonization of vector and raster data for computer vision tasks (Fleischmann & Arribas-Bel, 2024).

Moreover, the package is relied on in downstream software such as `atlasbr` for harmonization of Brazilian urban data (Oliveira & Paiva Neto, 2025), and is referred to in the `pygridmap` package by Eurostat (Grazzini & Gaffuri, 2020) as a reference implementation. The `tobler` package has made tangible contributions to spatial science, pedagogy, and applications in government and industry. In academia, the package is used as part of a data-processing pipeline

for research that examines the spatial-contextual influence on a variety of outcomes, including segregation (Wei et al., 2022), housing policy (S. J. Rey & Knaap, 2022), education policy (Osia et al., 2025; S. J. Rey et al., 2024), and pollution exposure (La Porta & Zapperi, 2024; Lee et al., 2026). It is also used in environmental science (Hu et al., 2023) and regionalization research (Feng et al., 2022).

In spatial data science education, `tobler` has become an integral part of many curricula. It is included in popular pedagogical resources, including two textbooks (Knaap, 2026; S. J. Rey et al., 2023), and is taught in graduate and undergraduate courses in universities across the globe, including the University of California (Berkeley, Irvine, Riverside, and Santa Barbara campuses), San Diego State University, Charles University, University of Liverpool, Northern Arizona University, and Temple University, among others.

In the public sector, the `tobler` package is used as part of a processing pipeline that powers urban planning and policymaking, including the DemoLand project from the Alan Turing Institute, developed as a part of the British National Land Data Programme (Geospatial Commission, 2023). The project piloted predictive modelling based on data interpolated to a unified hexagonal grid and is scaling the approach nation-wide.

AI usage disclosure

No generative AI or LLMs were used for code production for `tobler` or the writing of this paper.

Acknowledgements

`tobler` is developed by the PySAL community and builds on decades of research in areal interpolation and spatial data science.

Funding from National Science Foundation Grants 2345820 and 1831615 have supported `tobler` development.

The following acknowledgement applies to James D. Gaboardi:

> This manuscript has been authored in part by UT-Battelle LLC under contract DE-AC05-00OR22725 with the US Department of Energy (DOE). The US government retains and the publisher, by accepting the article for publication, acknowledges that the US government retains a nonexclusive, paid-up, irrevocable worldwide license to publish or reproduce the published form of this manuscript, or allow others to do so, for US government purposes. DOE will provide public access to these results of federally sponsored research in accordance with the DOE Public Access Plan (http://energy.gov/downloads/doe-public-access-plan).

The following acknowledgement applies to Daniel Arribas-Bel and Martin Fleischmann:

> Funding is acknowledged from UK Research and Innovation (UKRI) through the Economic and Social Research Council's grant "Learning an urban grammar from satellite data through AI", project reference (ES/ T005238/1).

References

Dawson, N., Fischer, J., Kuhn, M., Pasotti, A., Rouzaud, D., mhugent, Bruy, A., Sutton, T., Dobias, M., Pellerin, M., Rouault, E., Olaya, V., Blottiere, P., Macho, W., Cabieces, J., Blazek, R., Bartoletti, L., Sherman, G., Sant-anna, H., … Jurgiel, B. (2026). *Qgis/QGIS*. Zenodo. https://doi.org/10.5281/zenodo.6139224

DRAFT

Eicher, C. L., & Brewer, C. A. (2001). Dasymetric Mapping and Areal Interpolation: Implementation and Evaluation. *Cartography and Geographic Information Science*, *28*(2), 125–138. https://doi.org/10.1559/152304001782173727

Feng, X., Rey, S. J., & Wei, R. (2022). The Max-p-Compact-Regions Problem. *Transactions in GIS*, *26*(2), 717–734. https://doi.org/10.1111/tgis.12874

Fleischmann, M., & Arribas-Bel, D. (2022). Geographical characterisation of British urban form and function using the spatial signatures framework. *Scientific Data*, *9*(1), 546. https://doi.org/10.1038/s41597-022-01640-8

Fleischmann, M., & Arribas-Bel, D. (2024). Decoding (urban) form and function using spatially explicit deep learning. *Computers, Environment and Urban Systems*, *112*, 102147. https://doi.org/10.1016/j.compenvurbsys.2024.102147

Fleischmann, M., Van den Bossche, J., Jordahl, K., Richards, M. J., McBride, J., Wasserman, J., Ward, B., & Wolf, L. J. (2026). GeoPandas: Fundamental data structures for vector spatial data in Python. *Computers, Environment and Urban Systems*, *130*, 102495. https://doi.org/10.1016/j.compenvurbsys.2026.102495

Flowerdew, R., & Aitkin, M. (1982). A Method of Fitting the Gravity Model Based on the Poisson Distribution. *Journal of Regional Science*, *22*(2), 191–202. https://doi.org/10.1111/j.1467-9787.1982.tb00744.x

Flowerdew, R., & Green, M. (1992). Developments in areal interpolation methods and GIS. *The Annals of Regional Science*, *26*(1), 67–78. https://doi.org/10.1007/BF01581481

Geospatial Commission. (2023). *Finding common ground: Integrating data, science and innovation for better use of land* [Policy Paper]. Department for Science, Innovation; Technology. https://www.gov.uk/government/publications/finding-common-ground-integrating-data-science-and-innovation-for-better-use-of-land

Gillies, S., Wel, C. van der, Van den Bossche, J., Taves, M. W., Arnott, J., Ward, B. C., & others. (2026). *shapely*. Zenodo. https://doi.org/10.5281/zenodo.5597138

Goodchild, M., & Lam, N. (1980). Areal Interpolation: A Variant of the Traditional Spatial Problem. *Geo-Processing*, *1*, 297–312.

Grazzini, J., & Gaffuri, J. (2020). *Pygridmap*. https://github.com/eurostat/pygridmap

Hu, H., Liu, X., Zheng, Y., He, X., Hart, J., James, P., Laden, F., Chen, Y., & Bian, J. (2023). Methodological Challenges in Spatial and Contextual Exposome-Health Studies. *Critical Reviews in Environmental Science and Technology*, *53*(7), 827–846. https://doi.org/10.1080/10643389.2022.2093595

Knaap, E. (2026). *Urban analysis & spatial science*. https://knaaptime.com/urban_analysis

La Porta, C. A. M., & Zapperi, S. (2024). Urban Scaling Functions: Emission, Pollution and Health. *Journal of Urban Health*, *101*(4), 752–763. https://doi.org/10.1007/s11524-024-00888-2

Lee, H., Maguire, D., Logan, J., Agasthya, G., Dewji, S., & Hanson, H. A. (2026). Quantifying mean, variability, and uncertainty in indoor radon exposure in Pennsylvania using random forest and quantile regression forest models. *Scientific Reports*. https://doi.org/10.1038/s41598-026-37891-3

Mennis, J., & Hultgren, T. (2006). Intelligent Dasymetric Mapping and Its Application to Areal Interpolation. *Cartography and Geographic Information Science*, *33*(3), 179–194. https://doi.org/10.1559/152304006779077309

Moliński, S. (2022). Pyinterpolate: Spatial interpolation in Python forpoint measurements and aggregated datasets. *Journal of Open Source Software*, *7*(70), 2869. https://doi.org/10.21105/joss.02869

DRAFT

Murphy, B., Yurchak, R., & Müller, S. (2025). *GeoStat-Framework/PyKrige: v1.7.3* (Version v1.7.3). Zenodo. https://doi.org/10.5281/zenodo.17372225

Oliveira, H., & Paiva Neto, J. B. de. (2025). *AtlasBR*. https://github.com/redemobGIT/atlasbr

Osia, U., Cutts, B. B., Pullen Fedinick, K., & Boone, K. (2025). Infrastructure as Environmental Health Policy: Lessons from the Clean School Bus Program's Challenges and Innovations. *International Journal of Environmental Research and Public Health*, *22*(8), 1232. https://doi.org/10.3390/ijerph22081232

Pebesma, E. (2018). Simple features for r: Standardized support for spatial vector data. *The R Journal*, *10*, 439–446. https://doi.org/10.32614/RJ-2018-009

Prener, C., Revord, C., & Fox, S. (2019). Areal: An r package for areal weighted interpolation. *Journal of Open Source Software*, *4*(37), 1221. https://doi.org/10.21105/joss.01221

Reibel, M., & Agrawal, A. (2007). Areal Interpolation of Population Counts Using Pre-classified Land Cover Data. *Population Research and Policy Review*, *26*(5), 619–633. https://doi.org/10.1007/s11113-007-9047-1

Rey, S. J., & Anselin, L. (2007). PySAL: A Python Library of Spatial Analytical Methods. *The Review of Regional Studies*, *37*(1), 5–27. https://doi.org/10.52324/001c.8285

Rey, S. J., Anselin, L., Amaral, P., Arribas-Bel, D., Cortes, R. X., Gaboardi, J. D., Kang, W., Knaap, E., Li, Z., Lumnitz, S., Oshan, T. M., Shao, H., & Wolf, L. J. (2022). The **PySAL** Ecosystem: Philosophy and Implementation. *Geographical Analysis*, *54*(3), 467–487. https://doi.org/10.1111/gean.12276

Rey, S. J., Arribas-Bel, D., & Wolf, L. J. (2023). *Geographic Data Science with Python* (1st edition (May 10, 2023)). Chapman and Hall/CRC.

Rey, S. J., & Knaap, E. (2022). The Legacy of Redlining: A Spatial Dynamics Perspective. *International Regional Science Review*, *0*(0). https://doi.org/10.1177/01600176221116566

Rey, S. J., Knaap, E., Wei, R., & Skrah, D. (2024). Measuring Spatial Congruence in the School-Neighborhood Nexus. *Applied Spatial Analysis and Policy*. https://doi.org/10.1007/s12061-024-09603-9

Rey, S., Stephens, P., Oshan, T., Schmidt, C., Laura, J., Wolf, L. J., Arribas-Bel, D., Folch, D. C., mhwang4, Gaboardi, J., Malizia, N., Kang, W., Amaral, P., knaap, eli, Anselin, L., Qunshan, Lumnitz, S., Mehar, S., Fleischmann, M., … Lynn, S. (2026). `pysal`. Zenodo. https://doi.org/10.5281/zenodo.2538852

Rey, S., Wolf, L. J., Gaboardi, J., Fleischmann, M., Stephens, P., Schmidt, C., Laura, J., Arribas-Bel, D., Oshan, T., Folch, D. C., knaap, eli, mhwang4, Kang, W., Malizia, N., Amaral, P., Anselin, L., Shekhar, M., Andrade, E. S. de, Shao, H., … Samardzhiev, K. (2026). `libpysal`. Zenodo. https://doi.org/10.5281/zenodo.1472807

Tobler, W. R. (1979). Smooth Pycnophylactic Interpolation for Geographical Regions. *Journal of the American Statistical Association*, *74*(367), 519–529. https://doi.org/10.1080/01621459.1979.10481647

Wei, R., Feng, X., Rey, S. J., & Knaap, E. (2022). Reducing Racial Segregation of Public School Districts. *Socio-Economic Planning Sciences*, 101415. https://doi.org/10.1016/j.seps.2022.101415

DRAFT