

MF6RTM: a Python package for predictive reactive transport modeling via the MODFLOW 6 and PHREEQC APIs

Pablo Ortega-Tong¹, Anthony Aufdenkampe², Andres Prieto-Estrada⁴, Allan Foster³, Paul Tomasula², and Lauren Mancewicz⁵

¹ INTERA Geosciences, Perth, WA, Australia ² LimnoTech, Oakdale, MN, USA ³ INTERA INC., Denver, CO, USA ⁴ INTERA INC., Houston, TX, USA ⁵ Coastal and Hydraulics Lab, Engineer Research and Development Center, Vicksburg, MS, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Mengqi Zhao](#)

Reviewers:

- [@martinvonk](#)
- [@vcantarella](#)

Submitted: 24 December 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).

Summary

Reactive transport modeling (RTM) plays a central role in predicting the coupled behavior of groundwater flow, solute transport, and geochemical reactions in subsurface systems (Prommer et al., 2019). This paper presents MF6RTM (MODFLOW 6 Reactive Transport Module), a Python package that couples MODFLOW 6 (Langevin et al., 2024) with the geochemical code PHREEQC-3 (Parkhurst & Appelo, 2013). The coupling is achieved through the MODFLOW API (Hughes et al., 2022) and PhreeqcRM (Parkhurst & Wissmeier, 2015), which implement the Basic Model Interface (BMI) version 2.0 (Hutton et al., 2020), extended in MODFLOW 6 by the eXtended Model Interface (XMI), without modifying the source code of either program.

MF6RTM supports the core features of both codes, from contaminant migration to mineral dissolution and precipitation and redox reactions, and can add geochemical reactions to existing MODFLOW 6 models built with FloPy. Chemistry-related inputs are written as external array files, so that reactive transport models can be built, run, and history-matched within a single Python workflow, with the tools already used for flow models such as PEST++ (White, 2018) and pyEMU (White et al., 2016).

State of the Field

Actively developed open-source reactive transport codes include implicitly coupled simulators such as CrunchFlow (Steeff, 2014), PFLOTRAN (Hammond, 2022), and OpenGeoSys (Kolditz et al., 2012), and codes that couple separate transport and reaction models, such as PHAST (Parkhurst et al., 2010), PHT3D (Prommer et al., 2003), and eSTOMP (Nieplocha et al., 2006) (see Steeff et al. (2015) for a review).

Within the MODFLOW ecosystem, PHREEQC has been coupled to MODFLOW-2005 in PHT3D (Prommer et al., 2003) and to MODFLOW-USG Transport in PHT-USG (Panday et al., 2020). PHT3D has been used extensively in academia and practice (Appelo & Rolle, 2010), and PHT-USG is increasingly used by practitioners. Both couplings, however, required modification of the source code, which imposes a heavy maintenance burden and has tied them to older software versions: both still rely on PHREEQC-2, and updating to PHREEQC-3 (Parkhurst & Appelo, 2013) through PhreeqcRM would require substantial refactoring.

Statement of Need

Despite the comprehensive ecosystem for reactive transport simulators, to our knowledge, no open-source software comprehensively couples the current major versions of MODFLOW and PHREEQC. This gap is significant because MODFLOW remains the dominant platform for groundwater flow and transport modeling in regulatory, consulting, and applied research contexts. Existing integrated RTM codes generally require users to rebuild models in alternative frameworks, limiting their adoption for MODFLOW-based workflows. Moreover, as MODFLOW 6 and PHREEQC continue to expand in capability and adoption, keeping a coupled code current requires an approach that does not depend on changes to either source code, and that preserves transparency, extensibility, and computational efficiency. MF6RTM addresses this need by providing a fully open, API-based integration between MODFLOW 6 and PHREEQC.

Groundwater models are also increasingly expected to represent uncertainty explicitly and to support automated history matching and optimization (Langevin & Panday, 2012; White, 2017). Historically, most reactive transport workflows have relied on manual modification of input files to perform these tasks, creating a substantial burden for modelers and limiting reproducibility. Because MF6RTM exposes the geochemical inputs as array files that can be modified in the same way as MODFLOW 6 inputs, reactive parameters such as mineral amounts in solid phase can be included directly in uncertainty analysis and multi-objective optimization. MF6RTM therefore brings reactive processes into the history-matching and uncertainty quantification workflows already applied to groundwater flow models.

Software Design

Four design requirements guided the architecture: (i) reproducing established reactive transport benchmarks and agreeing with PHT3D and PHREEQC; (ii) supporting programmatic model construction, as MODFLOW workflows increasingly rely on FloPy (Bakker et al., 2016; Hughes et al., 2024); (iii) integrating with uncertainty analysis frameworks; and (iv) separating model construction from execution, so that simulation partners like PEST++ can run a model without the Python objects used to build it.

MF6RTM is therefore organized into two main modules. `mup3d` (Model Utility Preprocessor 3D) plays for MF6RTM a role similar to that of FloPy for MODFLOW 6: it constructs the geochemical inputs and the arrays needed to build the MODFLOW 6 files, and is used once, when the model is built. `simulation` reads the files written by `mup3d` and MODFLOW 6 and coordinates initialization, time stepping, and data exchange through the APIs, from Python or from the `mf6rtm` command line. Supporting modules handle array input/output (`io`), run configuration (`config`), and shared utilities (`utils`):

```
mf6rtm
├── mup3d
│   ├── base.py
│   └── simulation
│       ├── solver.py
│       ├── mf6api.py
│       ├── phreeqcbmi.py
│       └── discretization.py
├── io
│   ├── externalio.py
│   └── yaml_reader.py
├── config.py
└── utils.py
```

85 Geochemical inputs

86 In `mup3d`, a geochemical system is defined with one class per PHREEQC input block: `Solutions`,
 87 `EquilibriumPhases`, `ExchangePhases`, `KineticPhases` (including rate parameters), and
 88 `SurfacePhases`. Each class holds a dictionary of numbered PHREEQC definitions and an
 89 integer array, matching the model grid, that assigns a definition to each cell; `ChemStress`
 90 holds the solutions assigned to MODFLOW 6 boundary conditions. The `Mup3d` class assembles
 91 these blocks and runs the initial equilibration in `PhreeqcRM`, which determines the transported
 92 components and their initial concentrations in mol m^{-3} . These arrays are passed to `FloPy` to
 93 build one MODFLOW 6 groundwater transport (GWT) model per component; alternatively,
 94 `Mup3d.from_mf6` replicates the transport model of an existing `FloPy` simulation for each
 95 component. `Mup3d` finally writes the PHREEQC input, the `PhreeqcRM` settings, and the run
 96 configuration read by simulation.

97 Coupling and data exchange

98 The simulation module wraps the MODFLOW 6 shared library through `modflowapi` and
 99 `PhreeqcRM` through its BMI implementation, and couples them by sequential non-iterative
 100 operator splitting. For each transport time step: (i) the transport models of all components
 101 are solved to convergence; (ii) the cell saturation is read from the flow model; (iii) the
 102 concentrations are read from MODFLOW 6, converted from mol m^{-3} to mol L^{-1} , and passed
 103 to `PhreeqcRM` as a single component-by-cell array; (iv) `PhreeqcRM` integrates the reactions
 104 over the same time step; and (v) the reacted concentrations are converted back and written to
 105 MODFLOW 6 before the time step is finalized. Data are exchanged by copy through the BMI
 106 `get_value` and `set_value` functions rather than shared memory, as each transfer requires a
 107 unit conversion, and porosity is applied by MODFLOW 6, with the `PhreeqcRM` porosity set to
 108 one. Reactions can be restricted to user-defined time steps and, in models without kinetic
 109 reactions, to cells whose relative concentration change exceeds a threshold, as kinetic reactions
 110 proceed even where transport leaves concentrations unchanged.

111 External input files

112 When external input is enabled, the initial amounts of the exchange, equilibrium, and kinetic
 113 phases are written as one array file per layer, from which the PHREEQC initialization file
 114 is regenerated at the start of each run. `PEST++` can therefore modify these files like any
 115 MODFLOW 6 array, and the forward run reduces to a call to the `mf6rtm` command.

116 Benchmarks

117 Nine benchmark cases are included in the codebase, covering from mineral dissolution and
 118 precipitation fronts and cation exchange to pyrite oxidation and the kinetic biodegradation of
 119 hydrocarbons with multiple electron acceptors, and are compared against PHT3D and, in a
 120 few cases, PHREEQC. A 1D case with first-order kinetic decay is also compared against the
 121 analytical solution of Genuchten & Alves (1982), isolating the integration of kinetic reactions
 122 over each transport time step. Four documentation tutorials (<https://mf6rtm.readthedocs.io>)
 123 cover both model-building workflows.

124 Example 5 is presented here to demonstrate usage and verify the implementation. It reproduces
 125 the column experiment of Appelo et al. (1998), in which marine sediment containing pyrite
 126 was equilibrated with a $280 \text{ mmol L}^{-1} \text{ MgCl}_2$ solution, flushed with a more dilute solution,
 127 and oxidized for four pore volumes with H_2O_2 . Pyrite oxidation drives the hydrochemical
 128 evolution, accompanied by competing organic matter oxidation, kinetic calcite dissolution,
 129 cation exchange, and CO_2 sorption on goethite. The geochemical model is set up with `mup3d`
 130 as follows (abbreviated from `benchmark/ex5.ipynb`):

```

from mf6rtm import mup3d

solution = mup3d.Solutions(solutions)           # PHREEQC SOLUTION definitions
solution.set_ic(1)                             # solution number per cell
exchanger = mup3d.ExchangePhases(exchanger_dict)
exchanger_ic = np.repeat([1, 2, 3, 4], 4)       # four zones of four cells
exchanger.set_ic(exchanger_ic.reshape(nlay, nrow, ncol))

# rate laws come from the database RATES block
kin_phases = {1: {"Pyrite": {"m0": 4e-2, "parms": [3.42, 0.0, 0.5, 0.0]},
                  "Orgc_sed": {"m0": 10.0, "parms": [9.5e-10],
                               "formula": "Orgc_sed -1.0 C 1.0"}}}

kinetics = mup3d.KineticPhases(kin_phases)
kinetics.set_ic(1)                             # all cells use KINETICS block 1

model = mup3d.Mup3d("ex5", solution, nlay, nrow, ncol)
model.set_database("ex5.dat")
model.set_exchange_phases(exchanger)
model.set_phases(kinetics)
model.initialize()                             # initial equilibration in PhreeqcRM

wellchem = mup3d.ChemStress("wel")
wellchem.set_spd([2, 3])                       # injected solution per stress period
model.set_chem_stress(wellchem)

# then build one mf6 GWT model per component with FloPy
model.run()

```

131 MF6RTM closely reproduces the PHT3D simulation for all major ions, pH, alkalinity, and the
 132 calcite saturation index, and both models capture the main features of the measured effluent
 133 composition (Figure 1). Both models overestimate Ca concentrations after ~250 mL of outflow
 134 relative to the measurements. As this discrepancy is shared by both codes, it is attributed to
 135 the reaction network rather than to the coupling.




Figure 1: Comparison of effluent concentrations simulated with MF6RTM and PHT3D for Example 5, with the measured data of Appelo et al. (1998).

Research Impact Statement

The main contribution of MF6RTM is to make reactive transport modeling with MODFLOW 6 and PHREEQC accessible from Python through their APIs. MF6RTM has been applied to a field-scale 3D model of a deep-well injection trial, including a PEST++ setup for history matching and uncertainty analysis (Ortega-Tong & Hugman, 2026), and to a synthetic aquifer storage and recovery case on a 3D unstructured grid (<https://github.com/LimnoTech/mf6rtm-asr-example>).

AI Usage Disclosure

Generative AI tools were used in a limited capacity during the development of MF6RTM to draft docstrings, explore causes of software bugs, suggest code optimizations, and improve the grammar of the manuscript. During the revision stage, Claude (Anthropic; Opus 5.5),

accessed through Claude Code, was also used to (i) draft docstrings, documentation tutorials, and the contribution guidelines, (ii) restructure the package modules and write unit tests, (iii) investigate software bugs reported by the reviewers, (iv) rerun and post-process benchmark simulations, and (v) help edit the revised manuscript. The architecture of the code and the coupling scheme were designed by the authors. All AI-generated content was reviewed, edited, and tested by the authors, who take full responsibility for the software and the manuscript.

Acknowledgements

The software MF6RTM was supported by INTERA INC., and its Research and Development initiative. We also thank Henning Prommer for his insights and discussions during the benchmarking of MF6RTM.

References

- Appelo, C. A. J., & Rolle, M. (2010). PHT3D: A reactive multicomponent transport model for saturated porous media. *Ground Water*, 48, 627–632. <https://doi.org/10.1111/j.1745-6584.2010.00732.x>
- Appelo, C. A. J., Verweij, E., & Schäfer, H. (1998). A hydrogeochemical transport model for an oxidation experiment with pyrite/calcite/exchangers/organic matter containing sand. *Applied Geochemistry*, 13, 257–268. [https://doi.org/10.1016/S0883-2927\(97\)00070-X](https://doi.org/10.1016/S0883-2927(97)00070-X)
- Bakker, M., Post, V., Langevin, C. D., Hughes, J. D., White, J. T., Starn, J. J., & Fienen, M. N. (2016). Scripting MODFLOW model development using python and FloPy. *Groundwater*, 54, 733–739. <https://doi.org/10.1111/gwat.12413>
- Genuchten, M. Th. van, & Alves, W. J. (1982). *Analytical solutions of the one-dimensional convective-dispersive solute transport equation* (Technical Bulletin No. 1661). U.S. Department of Agriculture, Agricultural Research Service. <https://doi.org/10.22004/ag.econ.157268>
- Hammond, G. E. (2022). The PFLOTRAN reaction sandbox. *Geoscientific Model Development*, 15. <https://doi.org/10.5194/gmd-15-1659-2022>
- Hughes, J. D., Langevin, C. D., Paulinski, S. R., Larsen, J. D., & Brakenhoff, D. (2024). FloPy workflows for creating structured and unstructured MODFLOW models. *Groundwater*, 62, 124–139. <https://doi.org/10.1111/gwat.13327>
- Hughes, J. D., Russcher, M. J., Langevin, C. D., Morway, E. D., & McDonald, R. R. (2022). The MODFLOW application programming interface for simulation control and software interoperability. *Environmental Modelling and Software*, 148. <https://doi.org/10.1016/j.envsoft.2021.105257>
- Hutton, E. W. H., Piper, M. D., & Tucker, G. E. (2020). The basic model interface 2.0: A standard interface for coupling numerical models in the geosciences. *Journal of Open Source Software*, 5, 2317. <https://doi.org/10.21105/joss.02317>
- Kolditz, O., Bauer, S., Bilke, L., Böttcher, N., Delfs, J. O., Fischer, T., Görke, U. J., Kalbacher, T., Kosakowski, G., McDermott, C. I., Park, C. H., Radu, F., Rink, K., Shao, H., Shao, H. B., Sun, F., Sun, Y. Y., Singh, A. K., Taron, J., ... Zehner, B. (2012). OpenGeoSys: An open-source initiative for numerical simulation of thermo-hydro-mechanical/chemical (THM/c) processes in porous media. *Environmental Earth Sciences*, 67. <https://doi.org/10.1007/s12665-012-1546-x>
- Langevin, C. D., Hughes, J. D., Provost, A. M., Russcher, M. J., & Panday, S. (2024). MODFLOW as a configurable multi-model hydrologic simulator. *Groundwater*, 62. <https://doi.org/10.1111/gwat.13351>

- 192 Langevin, C. D., & Panday, S. (2012). Future of groundwater modeling. *Groundwater*, 50,
193 334–339. <https://doi.org/10.1111/j.1745-6584.2012.00937.x>
- 194 Nieplocha, J., Palmer, B., Tipparaju, V., Krishnan, M., Trease, H., & Aprà, E. (2006).
195 Advances, applications and performance of the global arrays shared memory programming
196 toolkit. In *International Journal of High Performance Computing Applications* (Vol. 20).
197 <https://doi.org/10.1177/1094342006064503>
- 198 Ortega-Tong, P., & Hugman, R. (2026). *Dizon 36: A reactive transport benchmark of mf6rtm*
199 *against PHT3D* (Version v1.0.0). Zenodo. <https://doi.org/10.5281/zenodo.23095990>
- 200 Panday, S., Mori, H., Mok, C. M., Park, J., Prommer, H., & Post, V. (2020). *PHT-USG*
201 *module of BTN package, release 2, for MODFLOW-USG transport version 1.4.0*. GSI
202 Environmental. <https://www.gsienv.com/software/modflow-usg/modflow-usg/>
- 203 Parkhurst, D. L., & Appelo, C. A. J. (2013). Description of input and examples for PHREEQC
204 version 3: A computer program for speciation, batch-reaction, one-dimensional transport,
205 and inverse geochemical calculations. In *Techniques and Methods* (p. 519). USGS.
206 <https://doi.org/10.3133/tm6A43>
- 207 Parkhurst, D. L., Kipp, K. L., & Charlton, S. R. (2010). PHAST version 2 - a program for
208 simulating groundwater flow, solute transport, and multicomponent geochemical reactions.
209 *Modeling Techniques, Book 6*. <https://doi.org/10.3133/tm6a35>
- 210 Parkhurst, D. L., & Wissmeier, L. (2015). PhreeqcRM: A reaction module for transport
211 simulators based on the geochemical model PHREEQC. *Advances in Water Resources*, 83,
212 176–189. <https://doi.org/10.1016/j.advwatres.2015.06.001>
- 213 Prommer, H., Barry, D. A., & Zheng, C. (2003). MODFLOW/MT3DMS-based reactive
214 multicomponent transport modeling. *Ground Water*, 41, 247–257. <https://doi.org/10.1111/j.1745-6584.2003.tb02588.x>
- 215
216 Prommer, H., Sun, J., & Kocar, B. D. (2019). Using reactive transport models to quantify and
217 predict groundwater quality. *Elements*, 15, 87–92. <https://doi.org/10.2138/gselements.15.2.87>
- 218
219 Steefel, C. I. (2014). CrunchFlow: User's manual. *Department of Energy Report*, 6.
- 220 Steefel, C. I., Appelo, C. A. J., Arora, B., Jacques, D., Kalbacher, T., Kolditz, O., Lagneau,
221 V., Lichtner, P. C., Mayer, K. U., Meeussen, J. C. L., Molins, S., Moulton, D., Shao,
222 H., Šimůnek, J., Spycher, N., Yabusaki, S. B., & Yeh, G. T. (2015). Reactive transport
223 codes for subsurface environmental simulation. *Computational Geosciences*, 19, 445–478.
224 <https://doi.org/10.1007/s10596-014-9443-x>
- 225 White, J. T. (2017). Forecast first: An argument for groundwater modeling in reverse.
226 *Groundwater*, 55, 660–664. <https://doi.org/10.1111/gwat.12558>
- 227 White, J. T. (2018). A model-independent iterative ensemble smoother for efficient history-
228 matching and uncertainty quantification in very high dimensions. *Environmental Modelling*
229 *& Software*, 109, 191–201. <https://doi.org/10.1016/j.envsoft.2018.06.009>
- 230 White, J. T., Fienen, M. N., & Doherty, J. E. (2016). A python framework for environmental
231 model uncertainty analysis. *Environmental Modelling and Software*, 85. <https://doi.org/10.1016/j.envsoft.2016.08.017>
- 232