

mosaix-pde: Differentiable pattern-forming PDEs for machine learning, optimization, and control

Alexander E. Cohen¹, Samuel Degnan-Morgenstern¹, Simon Daubner², Jorn Dunkel¹, and Martin Z. Bazant¹

¹ Massachusetts Institute of Technology, United States ² Imperial College London, United Kingdom ¶ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- Review
- Repository
- Archive

Editor: Fruzsina Agocs

Reviewers:

- @streeve
- @p-zubieta

Submitted: 23 October 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/))

Summary

Pattern formation occurs in diverse physical systems across many length scales, from quantum systems to planetary atmospheres, and has applications in nanotechnology and biology (Barad et al., 2021; Kim et al., 2022). The physical laws and dynamics that dictate pattern formation are often expressed in the form of partial differential equations (PDEs). To learn models for these systems, optimize, control, or apply modern machine learning techniques to these systems, we need fast, differentiable, and GPU-powered numerical solvers.

The *mosaix-pde* package provides implementations of PDEs that describe pattern formation in a range of physical systems. The package also provides a framework for extending the implementation to additional PDEs. The code is written in JAX (Bradbury et al., 2018) and is fully differentiable and GPU-accelerated. To solve the time-dependent PDEs, *mosaix-pde* converts the PDEs using the method of lines into a system of ordinary differential equations (ODEs), and evolves the resulting ODEs using *diffax* (Kidger, 2021). Notably, *diffax* provides binomial checkpointed adjoint methods, which is often essential for differentiating through PDE solves with a large number of time steps, as the memory requirements of backpropagation scales linearly with the number of steps. *mosaix-pde* also provides implementations of specialized time stepping methods for many pattern forming systems, including semi-implicit Fourier methods (Zhu et al., 1999), Strang splitting (Bao & Cai, 2012), and the stabilized explicit Runge-Kutta method ROCK2 (Abdulle & Medovikov, 2001). For simple support for non-regular geometries, some PDEs are implemented using the smoothed boundary method for complex geometries (Yu et al., 2012). The goal of this package is to provide specialized code for the integration of physical simulations of pattern formation with inverse design, optimization, machine learning, and control.

Statement of need

Pattern formation and phase separation are fundamental processes across physics, chemistry, biology, and materials science, with technological applications ranging from developmental biology to nanostructured materials. At the same time, the rapid growth of scientific machine learning has shown how partial differential equation (PDE) models can be combined with modern optimization and learning techniques to accelerate discovery, most prominently in applications such as material modeling (Zhao et al., 2020, 2023), weather and climate modeling (Kochkov et al., 2024), and biophysics (Supekar et al., 2023). Building on these advances, there is growing interest in extending such capabilities to ever more complicated pattern-forming systems, where fast, differentiable, and GPU-accelerated PDE solvers can enable parameter learning, design optimization, and reinforcement learning-based control. To support this, the community needs open-source tools that are performant, easy to use, well documented,

and straightforward to extend. Existing simulation libraries for pattern formation provide valuable tools, but are often not directly integrated with these machine learning workflows (Burns et al., 2020; Daubner et al., 2026; Walker et al., 2023; Zwicker, 2020). In addition, packages that treat PDEs as reinforcement learning environments are generally restricted to a small set of select equations (Bhan et al., 2024; Werner & Peitz, 2024). Our framework extends this ecosystem by coupling performant PDE solvers with differentiability, RL interfaces, and optimization capabilities, making it easier to study and control complex spatiotemporal dynamics across disciplines. The primary intended users of *mosaix-pde* are computational researchers in physics, materials science, and biophysics who study pattern-forming or phase-separating systems and want to combine time-dependent PDE simulations with parameter inference, inverse design, optimization, or control. Researchers in other domains may extend the modular Equation, Domain, and Solver interfaces. The code is currently being used by researchers to learn models for battery nanoparticles, optimize phase separation in materials, and control pattern formation in Bose-Einstein condensates. In the future, we plan to expand the range of physical systems and PDEs supported by the package and continue advancing numerical methods for differentiable simulation, with the goal of providing an accessible and practical framework for machine learning with PDEs.

The *mosaix-pde* package is organized around Domains, Equations, and Solvers Figure 1.




Figure 1: Code structure enables Equation, Domain, and Solver modules to be combined to build PDE models for machine learning applications.

The Domain class sets up the computational region for the simulation, including the mesh and axes in both real and Fourier space. The Domain also stores the Shape, which is used in the context of the smoothed boundary method. The Shape is initialized with a binary mask where 1s indicate the geometry and 0s indicate the empty space. Upon initialization, the binary mask is converted to a mask with a smoothly varying shape parameter at the boundary, as required for the smoothed boundary method. This smoothing is accomplished by evolving an Allen-Cahn equation with a Laplacian term with reduced curvature minimization to maintain sharply curved features of the original shape. The degree of smoothing and curvature minimization

can be controlled with hyperparameters. The Equation class consists of implementations of the right hand side of the various PDEs with both finite difference and Fourier spectral methods. Each class of PDE is contained in a module, and within each module there exists different implementations of the PDE for different sets of parameters, dimensionality, and other variations. Parameters for the PDEs can in general be Equinox modules (Kidger & Garcia, 2021), making it easy to take gradients with respect to the parameters regardless of the type of function using filter or partition transformations. Several useful functions that can be used as PDE parameters are provided as Equinox modules in the functions module, including periodic CNNs and Legendre polynomial expansions. The solvers are subclasses of diffrax.AbstractSolver and provide implementations of specialized time stepping methods for specific PDEs. The specification of a Domain, Equation, and a Solver is required for all downstream use cases of mosaix-pde.

Two interfaces are provided through the PDEModel and PDEEnv class for integrating with machine learning methods. The PDEModel is initialized with a combination of a Domain, Equation, and Solver, and provides three main methods. The first is a solve method for solving the specified Equation on the given Domain with the specified Solver. In addition, the train method provides the utilities for fitting parameters or functions within the Equation to a dataset. The train method uses a multiple shooting approach which is both computationally faster and more robust to noise in the dataset than other approaches. The multiple shooting approach works by vmap-ing over multiple starting points in the dataset and evaluating the loss at future time points relative to each starting point. The specific starting points and residual evaluation points are specified through the inds argument of the train function. Currently, the optimization can be performed using the Levenberg-Marquardt or Broyden-Fletcher-Goldfarb-Shanno (BFGS) algorithms, provided through the optimistix package (Rader et al., 2024). Gradients can be computed using forward- or reverse-mode automatic differentiation methods, which scale differently with the number of parameters Figure 2 (Ma et al., 2021). The Levenberg-Marquardt method requires Jacobians of the residuals for the Hessian approximation, which can be computed using forward mode automatic differentiation. Since the Levenberg-Marquardt method uses Gauss-Newton approximations of the Hessian, this method generally converges faster than BFGS. However, BFGS does not require the Jacobian of the residuals for the Hessian approximation, and thus the gradients can be computed easily using backpropagation, which scales much better with the number of parameters Figure 2. This tradeoff between scaling with parameter numbers and convergence of optimization must be considered for these differentiable physics optimization problems. Finally, the optimize method provides an interface for minimizing a scalar function of the PDE solution. The function to minimize is specified through the objective_function argument, and BFGS is used to perform the optimization.




Figure 2: Benchmarking performance of solvers and gradients with different number of grid points and parameters.

For reference, we benchmark the performance of numerically solving and computing gradients of PDE solutions Figure 2. We report the wall time scaling as a function of grid points of 10,000 time steps of the Cahn-Hilliard equation using a semi-implicit Fourier time stepping method, run on both GPU and CPU with Float32 and Float64 precision. The CPU and

GPU timings were measured using Intel Xeon Platinum 8562Y+ processors and an NVIDIA L40S GPU with 48 GB of memory, respectively. We further show the wall time scaling with respect to the number of parameters when computing gradients through 1,000 time steps of the Cahn-Hilliard equation using forward- and reverse-mode automatic differentiation. Finally, we compare a Tsit5 time stepper with our ROCK2 implementation and semi-implicit Fourier method, all coupled with a PID step size controller for the Cahn-Hilliard equation. PDEModel streamlines model learning and optimization by unifying a Domain, Equation, and Solver.

The PDEEnv class is useful for turning a PDE into a Gymnasium-registered reinforcement learning (RL) environment that can be used to train RL agents with libraries like Stable Baselines (Raffin et al., 2021; Towers et al., 2024). In addition to the Domain, Equation, and Solver, the PDEEnv class requires a step_dt, which is the time span of one step of the environment, and a numeric_dt which is the time step to use for numerical integration. These are separate parameters because the reaction time of the agent is often larger than the time step needed for numerical stability. Beyond these fields, many other pieces of information must be provided to form the RL environment, including reward functions, observation functions, and reset functions.



Figure 3: Single episode of an RL environment created from the Gross-Pitaevskii equation.

We demonstrate an example of creating an RL environment designed to form vortices in a Bose-Einstein condensate by controlling the position of an external laser source Figure 3. The episode is simulated by sampling random actions that move the position of the laser (red line), where the reward is calculated by counting the number of vortices in the condensate (black and white circles).

Acknowledgments

The authors acknowledge the MIT Office of Research Computing and Data for providing computational resources and advice on open-source scientific computing software.

References

- Abdulle, A., & Medovikov, A. A. (2001). Second order chebyshev methods based on orthogonal polynomials. *Numerische Mathematik*, 90(1), 1–18. <https://doi.org/10.1007/s002110100292>
- Bao, W., & Cai, Y. (2012). Mathematical theory and numerical methods for bose-einstein condensation. *arXiv Preprint arXiv:1212.5341*. <https://doi.org/10.3934/krm.2013.6.1>
- Barad, H.-N., Kwon, H., Alarcón-Correa, M., & Fischer, P. (2021). Large area patterning of nanoparticles and nanostructures: Current status and future prospects. *ACS Nano*, 15(4), 5861–5875. <https://doi.org/10.1021/acsnano.0c09999>
- Bhan, L., Bian, Y., Krstic, M., & Shi, Y. (2024). *PDE control gym: A benchmark for data-driven boundary control of partial differential equations*. <https://doi.org/10.48550/>

144 [arXiv:2405.11401](https://arxiv.org/abs/2405.11401)

- 145 Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G.,
146 Paszke, A., VanderPlas, J., Wanderman-Milne, S., & Zhang, Q. (2018). *JAX: Composable*
147 *transformations of Python+NumPy programs* (Version 0.3.13). <http://github.com/google/jax>
148 [ml/jax](https://github.com/google/jax)
- 149 Burns, K. J., Vasil, G. M., Oishi, J. S., Lecoanet, D., & Brown, B. P. (2020). Dedalus:
150 A flexible framework for numerical simulations with spectral methods. *Physical Review*
151 *Research*, 2(2), 023068. <https://doi.org/10.1103/PhysRevResearch.2.023068>
- 152 Daubner, S., Cohen, A. E., Dörich, B., & Cooper, S. J. (2026). Evoxels: A differentiable
153 physics framework for voxel-based microstructure simulations. *Journal of Open Source*
154 *Software*, 11(119), 9733. <https://doi.org/10.21105/joss.09733>
- 155 Kidger, P. (2021). *On Neural Differential Equations* [PhD thesis, University of Oxford].
156 <https://doi.org/10.48550/arXiv.2202.02435>
- 157 Kidger, P., & Garcia, C. (2021). Equinox: Neural networks in JAX via callable PyTrees and
158 filtered transformations. *Differentiable Programming Workshop at Neural Information*
159 *Processing Systems 2021*. <https://doi.org/10.48550/arXiv.2111.00254>
- 160 Kim, H., Skinner, D. J., Glass, D. S., Hamby, A. E., Stuart, B. A., Dunkel, J., & Riedel-Kruse, I.
161 H. (2022). 4-bit adhesion logic enables universal multicellular interface patterning. *Nature*,
162 608(7922), 324–329. <https://doi.org/10.1038/s41586-022-04944-2>
- 163 Kochkov, D., Yuval, J., Langmore, I., Norgaard, P., Smith, J., Mooers, G., Klöwer, M., Lottes,
164 J., Rasp, S., Düben, P., & others. (2024). Neural general circulation models for weather
165 and climate. *Nature*, 632(8027), 1060–1066. <https://doi.org/10.1038/s41586-024-07744-y>
- 166 Ma, Y., Dixit, V., Innes, M. J., Guo, X., & Rackauckas, C. (2021). A comparison of automatic
167 differentiation and continuous sensitivity analysis for derivatives of differential equation
168 solutions. *2021 IEEE High Performance Extreme Computing Conference (HPEC)*, 1–9.
169 <https://doi.org/10.1109/HPEC49654.2021.9622796>
- 170 Rader, J., Lyons, T., & Kidger, P. (2024). Optimistix: Modular optimisation in JAX and
171 equinox. *arXiv:2402.09983*. <https://doi.org/10.48550/arXiv.2402.09983>
- 172 Raffin, A., Hill, A., Gleave, A., Kanervisto, A., Ernestus, M., & Dormann, N. (2021). Stable-
173 Baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning*
174 *Research*, 22(268), 1–8. <http://jmlr.org/papers/v22/20-1364.html>
- 175 Supekar, R., Song, B., Hastewell, A., Choi, G. P., Mietke, A., & Dunkel, J. (2023). Learning
176 hydrodynamic equations for active matter from particle simulations and experiments.
177 *Proceedings of the National Academy of Sciences*, 120(7), e2206994120. <https://doi.org/10.1073/pnas.2206994120>
- 178
- 179 Towers, M., Kwiatkowski, A., Terry, J., Balis, J. U., De Cola, G., Deleu, T., Goulão, M.,
180 Kallinteris, A., Krimmel, M., KG, A., & others. (2024). Gymnasium: A standard
181 interface for reinforcement learning environments. *arXiv Preprint arXiv:2407.17032*. <https://doi.org/10.52202/085713-4916>
182
- 183 Walker, B. J., Townsend, A. K., Chudasama, A. K., & Krause, A. L. (2023). VisualPDE:
184 Rapid interactive simulations of partial differential equations. *Bulletin of Mathematical*
185 *Biology*, 85(11), 113. <https://doi.org/10.1007/s11538-023-01218-4>
- 186 Werner, S., & Peitz, S. (2024). Numerical evidence for sample efficiency of model-based
187 over model-free reinforcement learning control of partial differential equations. *2024*
188 *European Control Conference (ECC)*, 2965–2971. <https://doi.org/10.23919/ECC64448.2024.10590945>
189
- 190 Yu, H.-C., Chen, H.-Y., & Thornton, K. (2012). Extended smoothed boundary method

- 191 for solving partial differential equations with general boundary conditions on complex
192 boundaries. *Modelling and Simulation in Materials Science and Engineering*, 20(7), 075008.
193 <https://doi.org/10.1088/0965-0393/20/7/075008>
- 194 Zhao, H., Deng, H. D., Cohen, A. E., Lim, J., Li, Y., Fraggadakis, D., Jiang, B., Storey, B. D.,
195 Chueh, W. C., Braatz, R. D., & others. (2023). Learning heterogeneous reaction kinetics
196 from x-ray videos pixel by pixel. *Nature*, 621(7978), 289–294. <https://doi.org/10.1038/s41586-023-06393-x>
197
- 198 Zhao, H., Storey, B. D., Braatz, R. D., & Bazant, M. Z. (2020). Learning the physics
199 of pattern formation from images. *Physical Review Letters*, 124(6), 060201. <https://doi.org/10.1103/PhysRevLett.124.060201>
200
- 201 Zhu, J., Chen, L.-Q., Shen, J., & Tikare, V. (1999). Coarsening kinetics from a variable-
202 mobility cahn-hilliard equation: Application of a semi-implicit fourier spectral method.
203 *Physical Review E*, 60(4), 3564. <https://doi.org/10.1103/PhysRevE.60.3564>
- 204 Zwicker, D. (2020). Py-pde: A python package for solving partial differential equations.
205 *Journal of Open Source Software*, 5(48), 2158. <https://doi.org/10.21105/joss.02158>

DRAFT