

Links and Nodes: A middleware for distributed real-time robotic systems

Florian Schmidt^{1*}, Johannes Nix^{1*}, Maximilian Mühlbauer¹, Jan Cremer¹, Maxime Chalon¹, Timo Bachmann¹, and Antonin Raffin¹

¹ DLR German Aerospace Center, Institute of Robotics and Mechatronics, Germany * These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Daniel S. Katz](#)

Reviewers:

- [@nitishsanghi](#)
- [@brpat07](#)

Submitted: 19 June 2026

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Links and Nodes (LN) is an open-source middleware for building distributed real-time robotic systems. It combines process management with fast publish/subscribe messaging and request/response services, so complex multi-process systems can be configured and reproduced from one text file. Developed at the German Aerospace Center (DLR) since August 2010, LN supports robotics applications that require deterministic behavior, low-latency communication, and coordinated process control across hosts and programming languages.

Statement of need

Modern robotic systems are typically composed of many independent processes running on several computers. They must exchange data in real time, manage startup and dependency ordering, and remain reproducible across teams and deployments. Several constraints motivate an integrated middleware:

- Process isolation:** Safety and reliability drive separate processes rather than threads, requiring robust inter-process communication and lifecycle control.
- Language heterogeneity:** Robotics software often spans C, C++, Python, and MATLAB/Simulink, making language-agnostic APIs essential.
- Configuration scale:** Large systems need one version-controlled source of truth for processes, communication endpoints, and dependencies.
- Network transparency:** Components should communicate the same way on one computer or across a network.
- Real-time constraints:** Priority management and low-latency transport are critical for control and perception workloads.

Existing tools cover subsets of these needs. ROS (Quigley et al., 2009) and ROS 2 (Macenski et al., 2022) provide strong messaging ecosystems but manage processes differently and often bring extensive dependencies. ZeroMQ (Hintjens, 2013) offers flexible transport patterns but leaves discovery and process control to the application. DDS (Data Distribution Service, 2006) provides a standardized, data-centric publish/subscribe model with rich QoS options, but can be complex to configure for embedded real-time systems. LN targets this intersection by combining process supervision, communication topology, and runtime introspection in one reproducible configuration.

37 State of the field

38 Robotics middleware spans from message libraries to full system frameworks. ROS 1 was
39 already influential when LN began, but its original assumptions centered on a single robot
40 with workstation-class resources, good connectivity, and no general real-time requirements
41 beyond special-purpose handling (Gerkey, 2014; Quigley et al., 2009). ROS 2 was initiated only
42 in June 2014 specifically to address use cases such as real-time systems, non-ideal networks,
43 embedded platforms, multi-robot deployments, and more structured lifecycle management
44 (Gerkey, 2014; Macenski et al., 2022). This history explains why LN was built, but today's
45 relevant comparison is what remains distinctive.

46 DDS was the strongest established option for real-time distributed communication. Its
47 decentralized discovery, UDP-based transport model, and rich QoS controls made it suitable for
48 both high-level distributed integration and embedded real-time applications (Data Distribution
49 Service, 2006; Woodall, 2014a). That technical credibility was one reason why ROS 2 later
50 adopted DDS. However, the same ROS 2 design analysis also emphasized that DDS's flexibility
51 comes with substantial API and configuration complexity, and that users often need vendor-
52 specific knowledge once they move beyond the common subset (Woodall, 2014a). For a group
53 needing dependable, repeatable architecture, that complexity was costly.

54 ZeroMQ occupied the opposite end of the design space. It offered a fast, brokerless messaging
55 library with broad language support (Hintjens, 2013), making it attractive as a low-level
56 building block, but not a complete robotics middleware. OSRF's later prototype work on a
57 ZeroMQ-based ROS stack found that discovery, higher-level communication semantics, and
58 transport-serialization glue still had to be maintained separately, and judged the prototype
59 unsuitable for soft real-time scenarios because it relied on transports such as TCP or PGM
60 (Woodall, 2014b). CORBA (Common Object Request Broker Architecture, 2004) provided
61 mature remote-object support and language bindings, but its RPC-oriented model and associated
62 complexity were poorly matched to high-rate robotics data flows.

63 LN was therefore built not for lack of alternatives, but because neither message libraries nor full
64 DDS/ROS ecosystems matched needs that recurred in DLR robotics systems. Its distinctive
65 contribution today is the integration of low-latency communication, process management,
66 reproducible deployment configuration, and debugging support in one middleware. Rather than
67 requiring users to combine a transport library, launch scripts, and separate supervision tools,
68 LN treats runtime topology and communication topology as one system. This is visible in the
69 single configuration model, daemon-managed process supervision, shared-memory data paths
70 for local topics, and in-memory ring-buffer logging.

71 Software design

72 LN is organized around the core library (`libln`), the runtime daemon (`ln_daemon`), and the
73 manager application (`ln_manager`). Auxiliary tooling includes the message-definition generator
74 (`ln_generate`) and the message-definition libraries used by the topic and service APIs.

- 75 ■ **Core library (`libln`):** A C library implementing communication primitives, services, and a
76 client API. It is LGPLv3-licensed to allow dynamic linking into proprietary applications,
77 while the rest of LN is GPLv3.
- 78 ■ **Runtime daemon (`ln_daemon`):** A C++ process managing remote process spawning,
79 priority handling, and lifecycle control via a versioned protocol.
- 80 ■ **Manager (`ln_manager`):** A Python application with GUI and CLI interfaces, configuration
81 parsing for `.lnc` files, and high-level scripting hooks.

82 The design grew from practical deployments and feasibility constraints rather than a prescriptive
83 standard, leading to several deliberate trade-offs. LN keeps processes isolated instead of
84 collapsing functionality into one address space. That increases middleware needs but improves

fault containment, supports mixed-language systems, and matches the reality of robotic stacks that combine controllers, planners, perception modules, and operator interfaces. LN also deliberately couples communication and process supervision. This is less general than a pure messaging library, but ensures one configuration specifies what runs, where, and how components exchange data.

Two orthogonal communication paradigms emerged:

- **Topics (publish/subscribe):** Optimized for low-latency signal transport. Local traffic uses shared memory, UDP provides network transparency, and TCP is available when reliable topic delivery is required. Publisher-host topic traffic can be logged into an in-memory ring buffer for lightweight introspection without external tooling.
- **Services (request/response):** Optimized for synchronization and reliable calls. Unix domain sockets are used locally for efficiency, and TCP provides network-transparent service calls.

Process management uses the same configuration model: processes declare dependencies and priorities, while the manager monitors state and output in real time. This keeps control-plane and data-plane concerns in one workflow, reducing gaps between development and deployment. Compared with DDS-style systems, LN intentionally exposes a smaller and more opinionated configuration surface. Rather than asking users to tune many per-endpoint QoS policies, LN offers a constrained set of transport choices: shared memory for local low-latency topics, UDP for network-transparent topic transport, and TCP when reliability is more important than minimum latency. This narrower design reduced configuration burden and made behavior easier to reason about for researchers who needed dependable system integration more than maximum middleware generality.

Another important design choice is the split between a small C communication core and higher-level tooling in Python. The C library keeps the runtime lightweight and embeddable, while the Python manager provides interactive inspection, configuration handling, and scripting without imposing Python on deployed client code. This separation helped LN remain usable across heterogeneous systems, including deployments that combine real-time-adjacent native code with more flexible supervisory tooling. The security model is similarly pragmatic: LN supports manager-daemon authentication, but it does not try to provide a full encrypted transport stack for all traffic. That keeps the runtime small and deployment-oriented, but means LN is intended for trusted or protected network environments.

LN targets Linux distributions such as Debian/Ubuntu and POSIX systems such as QNX, and can also run on Windows and VxWorks. The build system uses SCons, with additional distribution-specific helpers where required. The core runtime depends on a small set of system libraries (primarily glibc and libprocps), keeping deployments lightweight.

Research impact statement

LN has been used for over 15 years in DLR robotics research, including mobile manipulation, human-robot interaction, and real-time perception pipelines. Its single-configuration approach enables reproducible system setups across teams, and its low-latency transports support control loops that require deterministic behavior. The software evolved alongside real deployments, leading to a focus on debuggability, predictable performance, and stable APIs rather than rapid feature expansion.

LN has enabled research projects that rely on synchronized sensor fusion, modular control architectures, and distributed simulation environments. Representative published uses include humanoid teleoperation and Surface Avatar mission software (Bauer et al., 2025; Beik-Mohammadi et al., 2021), space-robotics control stacks for the SpaceDREAM arm and a universal robotic joint (Bahls et al., 2025; Mühlbauer et al., 2025), educational and experimental rover platforms (Bekkers et al., 2023), humanoid real-time control experiments (Loeffl et al.,

2016), and autonomous rover operation and task-execution studies (Brunner et al., 2018, 2019; Schuster et al., 2017). The platform's process-management capabilities allow complex experiments to be launched and monitored consistently, which reduces integration overhead and supports repeatable experimentation across these domains. The source repository is hosted at https://gitlab.com/links_and_nodes/links_and_nodes. Additional repositories provide Rust bindings for LN and tooling for the configuration language (Tree-sitter grammar and a language server). Developed since August 2010, LN has many tagged releases, an automated test tree covering local and remote publish/subscribe, services, console behavior, networked setups, and clean-build scenarios, plus extensive user and reference documentation. These artifacts support research reuse because LN's contribution is not only the code itself, but also the operational knowledge required to keep a distributed robotics middleware maintainable over many years.

AI usage disclosure

Software changes before March 2026 were written without AI agents. Since March 2026, Florian Schmidt used OpenAI Codex with GPT-5.5 for code or documentation in python/links_and_nodes/scope/, .gitlab*, the web UI and manager-started VNC sessions, Python parameter blocks, DSA key generation, sync/async manager clients, network-usage statistics, new documentation, and this manuscript. These contributions were steered, reviewed, edited, and fact-checked by Florian Schmidt; the GitLab CI changes were also reviewed by Antonin Raffin.

Acknowledgements

We thank contributors to Links and Nodes, particularly those at DLR's Institute of Robotics and Mechatronics who used and improved it in real robotic deployments. We also acknowledge the open-source community behind Linux, GCC, and various Python packages used by this project.

References

- Bahls, T., Beyer, A., Sedlmayr, H.-J., Stemmer, A., Burger, R., & Moser, S. (2025). The communication and computation architecture for a universal space robotic joint. *2025 IEEE Aerospace Conference (AERO 2025)*, 1–10. <https://doi.org/10.1109/AERO63441.2025.11068565>
- Bauer, A. S., Köpken, A., Batti, N., Butterfaß, J., Ehlert, T. H., Friedl, W., Gumpert, T., Lay, F. S., Luo, X., Manaparampil, A. N., Mayershofer, L., Raffin, A., Schmidt, F., Seidel, D., Exter, E. den, Luz, R., Schmidt, A., Schmaus, P., Leidner, D., ... Lii, N. Y.-S. (2025). System architecture and design considerations for the humanoid robot rollin' justin in context of the surface avatar mission. *2025 IEEE Aerospace Conference (AERO 2025)*, 1–14. <https://doi.org/10.1109/AERO63441.2025.11068600>
- Beik-Mohammadi, H., Kerzel, M., Pleintinger, B., Hulin, T., Reisich, P., Schmidt, A., Pereira, A., Wermter, S., & Lii, N. Y. (2021). *Model mediated teleoperation with a hand-arm exoskeleton in long time delays using reinforcement learning*. arXiv preprint. <https://doi.org/10.48550/arXiv.2107.00359>
- Bekkers, S., Bettendorf, M. T., Reill, J., Giubilato, R., & Wedler, A. (2023, October). The lunar rover mini: Towards a versatile, open-source mobile robotic platform for educational and experimental purposes. *17th Symposium on Advanced Space Technologies in Robotics and Automation (ASTRA 2023)*. <https://elib.dlr.de/202313/>
- Brunner, S. G., Dömel, A., Lehner, P., Beetz, M., & Stulp, F. (2019). Autonomous parallelization of resource-aware robotic task nodes. *IEEE Robotics and Automation*

- 179 *Letters*, 4(3), 2599–2606. <https://doi.org/10.1109/LRA.2019.2894463>
- 180 Brunner, S. G., Lehner, P., Schuster, M. J., Riedel, S., Belder, R., Wedler, A., Leidner, D.,
181 Beetz, M., & Stulp, F. (2018). Design, execution, and postmortem analysis of prolonged
182 autonomous robot operations. *IEEE Robotics and Automation Letters*, 3(2), 1056–1063.
183 <https://doi.org/10.1109/LRA.2018.2794580>
- 184 *Common object request broker architecture: Core specification* (Version 3.0.3). (2004). Object
185 Management Group. <https://www.omg.org/spec/CORBA/3.0.3/PDF>
- 186 *Data distribution service* (Version 1.2). (2006). Object Management Group. [https://www.](https://www.omg.org/spec/DDS/1.2/PDF)
187 [omg.org/spec/DDS/1.2/PDF](https://www.omg.org/spec/DDS/1.2/PDF)
- 188 Gerkey, B. (2014). *Why ROS 2?* ROS 2 design article. [https://design.ros2.org/articles/why_](https://design.ros2.org/articles/why_ros2.html)
189 [ros2.html](https://design.ros2.org/articles/why_ros2.html)
- 190 Hintjens, P. (2013). *ZeroMQ: Messaging for many applications*. O'Reilly Media, Inc.
- 191 Loeffl, F. C., Werner, A., Lakatos, D., Reinecke, J., Wolf, S., Burger, R., Gumpert, T., Schmidt,
192 F., Ott, C., Grebenstein, M., & Albu-Schäffer, A. O. (2016). The DLR c-runner: Concept,
193 design and experiments. *2016 IEEE-RAS International Conference on Humanoid Robots*
194 (*Humanoids*), 758–765. <https://doi.org/10.1109/HUMANOIDS.2016.7803359>
- 195 Macenski, S., Foote, T., Gerkey, B., Lalancette, C., & Woodall, W. (2022). Robot operating
196 system 2: Design, architecture, and uses in the wild. *Science Robotics*, 7(66), eabm6074.
197 <https://doi.org/10.1126/scirobotics.abm6074>
- 198 Mühlbauer, M. S., Chalon, M., Ulmer, M., & Albu-Schäffer, A. O. (2025). Software for
199 the SpaceDREAM robotic arm. *2025 IEEE Aerospace Conference (AERO 2025)*, 1–10.
200 <https://doi.org/10.1109/AERO63441.2025.11068537>
- 201 Quigley, M., Conley, K., Gerkey, B., Faust, J., Foote, T., Leibs, J., Wheeler, R., Ng, A. Y., &
202 others. (2009). ROS: An open-source Robot Operating System. *ICRA Workshop on Open*
203 *Source Software*, 3, 5.
- 204 Schuster, M. J., Brunner, S. G., Bussmann, K., Büttner, S., Dömel, A., Hellerer, M., Lehner, H.,
205 Lehner, P., Porges, O., Reill, J., Riedel, S., Vayugundla, M., Vodermayr, B., Bodenmüller,
206 T., Brand, C., Friedl, W., Grix, I., Hirschmüller, H., Kaßberger, M., ... Wedler, A. (2017).
207 Towards autonomous planetary exploration: The lightweight rover unit (LRU), its success
208 in the SpaceBotCamp challenge, and beyond. *Journal of Intelligent and Robotic Systems*,
209 93(3–4), 461–494. <https://doi.org/10.1007/s10846-017-0680-9>
- 210 Woodall, W. (2014a). *ROS on DDS*. ROS 2 design article. [https://design.ros2.org/articles/](https://design.ros2.org/articles/ros_on_dds.html)
211 [ros_on_dds.html](https://design.ros2.org/articles/ros_on_dds.html)
- 212 Woodall, W. (2014b). *ZeroMQ and friends*. ROS 2 design article. [https://design.ros2.org/](https://design.ros2.org/articles/ros_with_zeromq.html)
213 [articles/ros_with_zeromq.html](https://design.ros2.org/articles/ros_with_zeromq.html)