

PLEIADES: Python Library Extensions for Isotopic Analysis via Detailed Examination of SAMMY results

Alexander M. Long¹, Tsviki Y. Hirsh², Jean Bilheux³, and Chen Zhang³

¹ Los Alamos National Laboratory, Los Alamos, NM 87545, USA ² Soreq Nuclear Research Center, Yavne, 81800, Israel ³ Oak Ridge National Laboratory, Oak Ridge, TN 37830, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: 

Submitted: 09 April 2026

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).

Summary

Neutron resonance transmission analysis is a non-destructive technique used to determine material composition from the isotope-specific interactions between neutrons and atomic nuclei. As neutrons pass through a sample, they are absorbed or scattered in energy-dependent patterns that reflect the isotopes present. Measuring these transmission spectra allows scientists to identify isotopes and quantify their abundances without altering the material.

[TODO: Add a figure showing the workflow and how PLEIADES automates it.] Extracting these properties requires detailed physics-based modeling with R-matrix codes such as SAMMY (Larson, 2008; Wiarda et al., 2023). The fitting process is labor-intensive: users must prepare input files, run the fit, examine large output files, and iteratively adjust parameters. This cycle may repeat many times, and the workload grows significantly when analyzing energy-resolved neutron imaging data, where millions of spectra demand scaling and automation.

PLEIADES (Python Library Extensions for Isotopic Analysis via Detailed Examination of SAMMY results) is a Python software package that automates the end-to-end workflow around SAMMY. The software generates input files, manages batch execution, and extracts isotopic densities and material parameters from fitting results. By consolidating repetitive steps into a single, scriptable interface, PLEIADES reduces manual effort and enables large-scale analysis of neutron transmission data. The package supports both expert users and researchers who are not specialists in nuclear reaction theory.

PLEIADES has been used in recent neutron imaging publications (Hirsh, Leong, et al., 2025; Hirsh, Long, et al., 2025) and is the primary resonance analysis tool for the VENUS beamline at the Spallation Neutron Source (Bilheux et al., 2023) and the ERNI instrument at the Los Alamos Neutron Science Center (Nelson et al., 2018). The source code is archived on Zenodo (Long & Hirsh, 2025).

Statement of Need

R-matrix fitting with SAMMY remains the standard approach for extracting resonance parameters and isotopic densities from neutron transmission data, but the workflow is highly manual and requires deep understanding of the domain specific software. Users must craft structured input files, manage repeated fit iterations, and parse lengthy SAMMY outputs. These requirements limit throughput and create an entry barrier for researchers who need neutron resonance analysis but are not experts in nuclear reaction modeling.

PLEIADES addresses this gap by automating input generation, execution control, and output extraction in a domain-specific manner. Existing workflow tools do not integrate with SAMMY or handle the conventions of resonance analysis. PLEIADES provides SAMMY-aware automation, scaling, and data handling designed specifically for transmission analysis and energy-resolved

42 neutron imaging. This allows faster, reproducible, and more accessible workflows across a wide
43 range of applications.

44 State of the Field

45 Neutron resonance imaging produces large collections of energy-resolved transmission spectra,
46 but imaging-specific analysis software remains relatively limited. To our knowledge, TRINIDI
47 is currently the only dedicated open-source code that enables fast isotopic reconstructions
48 from time-of-flight neutron resonance imaging data (Balke et al., 2024). TRINIDI's approach
49 leverages tabulated neutron total cross sections, which is efficient for high-throughput inference
50 but does not allow direct adjustment of the underlying cross section model through resonance-
51 parameter variation.

52 In contrast, SAMMY is widely used for neutron resonance transmission analysis and provides
53 a comprehensive suite of R-matrix fitting capabilities (Larson, 2008; Wiarda et al., 2023).
54 SAMMY constructs cross sections from user-specified resonance parameters and updates those
55 parameters through Bayesian fitting (Larson, 2008), enabling physics-informed refinement when
56 resonance parameters, sample conditions, or model assumptions must be varied and validated
57 against measured transmission data. Although SAMMY is widely adopted, its primary user
58 interface is a command-line workflow based on fixed-width input files and text-based outputs.
59 The software exposes a large number of modeling options and control parameters that must
60 be specified explicitly, and its outputs can be difficult to interpret without substantial domain
61 expertise. This complexity presents a barrier for new users and can inhibit adoption beyond
62 the specialist nuclear data and resonance analysis community. As a result, many groups build
63 local scripts to generate inputs, manage repeated fit cycles, and parse outputs for downstream
64 analysis, often resulting in workflows that are difficult to reuse, audit, and scale to large imaging
65 datasets.

66 PLEIADES enables SAMMY to be used in the larger-scale and more complex workflows
67 encountered in neutron resonance imaging. Rather than re-implementing R-matrix physics,
68 PLEIADES streamlines SAMMY usage by providing a SAMMY-aware workflow layer that
69 standardizes common modes of analysis (e.g., single-spectrum studies, iterative refinement,
70 and high-throughput per-region or per-pixel fitting). It reduces user burden by handling many
71 routine decisions and bookkeeping steps “behind the scenes,” including format-validated input
72 templating, consistent file and run management, and structured extraction of fit outputs into
73 analysis-ready data products. This approach preserves SAMMY's trusted modeling capabilities
74 while improving usability, reproducibility, and scalability for imaging datasets where manual
75 trial-and-error workflows and ad hoc parsing scripts do not translate to millions of spectra.

76 Software Design

77 PLEIADES is designed as a *workflow and data-management layer* around SAMMY rather than
78 a re-implementation of R-matrix physics. The primary design goal is to make SAMMY-based
79 resonance analysis reproducible and scalable (from a single spectrum to large imaging datasets)
80 while keeping expert-level control available when needed.

81 Design principles and trade-offs

- 82 ■ **Preserve SAMMY as the fitting engine.** PLEIADES delegates cross section construction
83 and Bayesian parameter estimation to SAMMY. The trade-off is that analysis remains
84 constrained by SAMMY's file-based interfaces and run-time characteristics, which
85 PLEIADES mitigates through automation and structured inputs and outputs.
- 86 ■ **Standardize common analysis modes with override points.** The library provides high-level,
87 SAMMY-aware workflows (e.g., single-spectrum fits, iterative refinement loops, and
88 high-throughput region/pixel processing) that encode routine choices such as input
89 structure, run directory layout, and output harvesting. Advanced users can still customize

templates, fitting controls, and run options when deviating from defaults is scientifically necessary.

- **Emphasize validation and provenance to prevent runtime errors** SAMMY inputs are generated from pydantic models with format and option checks to reduce any SAMMY run-time failures and to make analysis reproducible and auditable if needed.

Research Impact Statement

PLEIADES has already demonstrated research impact through use in published neutron resonance imaging work: an earlier public release archived on Zenodo (Long & Hirsh, 2025) was used to support the analysis reported in Hirsh, Long, et al. (2025). Beyond this initial publication, PLEIADES is being adopted as the primary resonance-analysis workflow for user programs at major neutron imaging instruments, including the VENUS beamline at the Spallation Neutron Source (Bilheux et al., 2023) and the HIPPO and ERNI beamlines at the Los Alamos Neutron Science Center (LANSCE) (Nelson et al., 2018). By automating SAMMY input generation, run management, and structured extraction of fit results, PLEIADES reduces manual iteration and error-prone parsing steps that commonly dominate resonance fitting workflows. This directly shortens the acquisition-to-publication timeline for neutron resonance imaging measurements by enabling higher-throughput, more reproducible analysis across large collections of datasets at multiple facilities.

AI usage disclosure

Generative AI tools were used during development of PLEIADES and in preparation of parts of this manuscript. Specifically, we used large language model assistants (including ChatGPT, Claude, and Gemini) for code drafting, refactoring suggestions, and documentation/text editing, and we used GitHub Copilot to assist with code review (e.g., pull-request feedback) and small code completions.

All AI-suggested code and text was reviewed, edited, and approved by the authors. Code changes were validated using the project's unit tests, and SAMMY functionality was additionally verified by running against the suite of publicly available SAMMY example problems to confirm that generated inputs and parsed outputs were consistent with expected behavior. The authors take full responsibility for the final software and manuscript contents.

Key Features

- Automated creation of SAMMY input files for neutron transmission fitting
- Batch execution management for large datasets
- Extraction of isotopic densities and material parameters from SAMMY outputs
- Support for energy-resolved neutron imaging workflows with millions of spectra
- Interfaces for managing ENDF-formatted nuclear data
- Configurable templates for reproducible and scalable analysis
- Python API suitable for scripting, interactive analysis, and integration with other tools

Author Contributions

- **Alexander M. Long (AML):** Conceptualization; Software; Methodology; Validation; Writing – original draft; Writing – review & editing;
- **Chen Zhang (CZ):** Conceptualization; Software; Methodology; Validation; Writing – original draft; Writing – review & editing;
- **Jean-Christophe Bilheux (JCB):** Software; Methodology; Validation;
- **Tsviki Y. Hirsh (TYH):** Conceptualization; Software; Methodology;

Acknowledgements

Work was supported in part through the Nuclear Science User Facilities (NSUF), under DOE Idaho Operations Office Contract DE-AC07-05ID14517. This research used resources at the Spallation Neutron Source, a U.S. Department of Energy Office of Science User Facility operated by Oak Ridge National Laboratory under Contract No. DE-AC05-00OR22725. Resonance imaging measurements were carried out on the VENUS instrument at the SNS.

Balke, T., Long, A. M., Vogel, S. C., Wohlberg, B., & Bouman, C. A. (2024). TRINIDI: Time-of-flight resonance imaging with neutrons for isotopic density inference. *IEEE Transactions on Computational Imaging*, 10(1), 154–169. <https://doi.org/10.1109/TCI.2023.3345635>

Bilheux, H. Z., Hanks, R. A., Bilheux, J.-C., Skorpenske, H., Donnelly, M.-E., Molaison, J., & Byrd, A. (2023). The VENUS imaging beamline at the oak ridge national laboratory spallation neutron source. *Advanced Materials and Processes*, 181, 18–23. <https://doi.org/10.31399/asm.amp.2023-08.p018>

Hirsh, T. Y., Leong, A. F. T., Long, A. M., Losko, A. S., Wolfertz, A., Savage, D. J., Jaeger, T. T., Rakovan, J., Wall, J. J., & Vogel, S. C. (2025). Energy-resolved neutron imaging and diffraction including grain orientation mapping using event camera technology. *Scientific Reports*, 15, 12901. <https://doi.org/10.1038/s41598-025-96790-1>

Hirsh, T. Y., Long, A. M., Losko, A. S., Jaeger, T. T., Wolfertz, A., & Vogel, S. C. (2025). Large field-of-view event-mode camera for high-precision epithermal neutron resonance imaging. *Scientific Reports*, 15, 14026. <https://doi.org/10.1038/s41598-025-96789-8>

Larson, N. M. (2008). *Updated user's guide for SAMMY: Multilevel R-matrix fits to neutron data using Bayes' equations*. Oak Ridge National Laboratory.

Long, A. M., & Hirsh, T. Y. (2025). *PLEIADES: v0.1*. <https://doi.org/10.5281/zenodo.12729688>

Nelson, R. O., Vogel, S. C., Hunter, J. F., Watkins, E. B., Losko, A. S., Tremsin, A. S., Borges, N. P., Cutler, T. E., Dickman, L. T., Espy, M. A., Gautier, D. C., Madden, A. C., Majewski, J., Malone, M. W., Mayo, D. R., McClellan, K. J., Montgomery, D. S., Mosby, S. M., Nelson, A. T., ... Winch, N. M. (2018). Neutron imaging at LANSCE from cold to ultrafast. *Journal of Imaging*, 4, 45. <https://doi.org/10.3390/jimaging4020045>

Wiarda, D., Arbanas, G., Brown, J. M., Holcomb, A. M., Pigni, M. T., McDonnell, J., & Chapman, C. (2023). Modernization efforts for the R-matrix code SAMMY. *EPJ Web of Conferences*, 284, 12005. <https://doi.org/10.1051/epjconf/202328412005>