The Journal of Open Source Software

# RiverFlowDynamics v1.0: A Landlab component for computing two-dimensional river flow dynamics

**Angel Monsalve** [1*¶], **Sebastian Bernal** [1*], and **Oscar Link** [2*]

**1** Center for Ecohydraulics Research, Civil and Environmental Engineering, University of Idaho, Boise, ID, USA **2** Departamento de Ingeniería Civil, Universidad de Concepción, Concepción, Chile ¶ Corresponding author * These authors contributed equally.

**DOI:** 10.xxxxxx/draft

**Software**

- Review
- Repository
- Archive

**Editor:** Taher Chegini

**Reviewers:**

- @mcflugen
- @ZhiLiHydro
- @xiaxilin

**Submitted:** 09 December 2024
**Published:** unpublished

**License**
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

## Summary

Numerical modeling of surface water flow is a critical tool in hydrology, hydraulics, and environmental science. These models play a crucial role in predicting and analyzing flow patterns in rivers, flood plains, and coastal areas, informing decisions in water resource management, flood risk assessment, and ecosystem conservation. This paper introduces a novel two-dimensional flow model, RiverFlowDynamics, developed as a component of the Landlab Python Package (Barnhart et al., 2020; Hobley et al., 2017; Hutton et al., 2020, 2020), designed to simulate the behavior of rivers and streams under various flow conditions over natural and artificial topography.

RiverFlowDynamics is founded on the depth-averaged Saint-Venant equations, also known as the shallow water equations (Casulli, 1990, 1999). These equations, derived from the Navier-Stokes equations for incompressible flow, are simplified by integrating over the water depth. This approach assumes that vertical accelerations are negligible compared to horizontal ones, a reasonable approximation for many surface water flows. The governing equations consist of continuity and momentum balance equations in two dimensions, capturing the essential dynamics of free-surface flows.

For the numerical solution of these equations, RiverFlowDynamics employs the finite volume method, chosen for its robustness, capacity to handle complex geometries, and inherent conservation properties (Andersson et al., 2011; Fletcher, 2012). The computational domain is discretized into a uniform rectangular grid, with water surface elevation defined at cell centers and velocity components at cell interfaces. This staggered grid arrangement helps in maintaining numerical stability and accuracy. The numerical implementation results in a penta-diagonal, positive-definite system of equations. This system is solved efficiently using the preconditioned conjugate gradient method, ensuring rapid convergence even for large domains. The model's structure allows for easy parallelization, potentially enabling simulations of extensive river networks or large coastal areas.

A key feature of the model is its semi-implicit and semi-Lagrangian representation. The semi-implicit scheme treats water surface elevation and velocity implicitly, while handling advective terms explicitly. This approach allows for larger time steps compared to fully explicit schemes, enhancing computational efficiency. The semi-Lagrangian method for advection involves tracking fluid particles backwards along their flow lines, providing additional stability and accuracy, particularly for flows with strong advective components (Robert, 1981; Robert et al., 1985). The model has been validated through a comprehensive test suite including analytical solutions, numerical stability tests, sensitivity analyses, mass conservation checks, and boundary condition validations.

The advection representation uses a semi-Lagrangian scheme on an Eulerian grid, a two-step

process where particles are tracked backwards along their flow lines to their starting points (Staniforth & Côté, 1991). This method, combined with the semi-implicit time discretization, allows for a relaxation of the Courant-Friedrichs-Lewy (CFL) condition, typically a limiting factor in explicit schemes (Bates & McDonald, 1982).

Source terms in the model primarily account for bottom friction, implemented using the Manning-Chezy formula (Brufau & Garcia-Navarro, 2000; He et al., 2017). While the model framework allows for the inclusion of wind stress and Coriolis effects, these are considered negligible in the current implementation, focusing on river and stream applications where these effects are typically less significant.

Flow line tracing, crucial for the semi-Lagrangian advection scheme, employs Pollock's semi-analytical method (Pollock, 1988). This method assumes linear velocity variation within each grid cell, allowing for an efficient and accurate computation of particle trajectories. This approach is particularly effective in capturing complex flow patterns in natural river systems.

A notable feature of the model is its robust handling of dry/wet cell transitions, crucial for simulating flows over complex topography or in areas with varying water levels. RiverFLowDynamics employs the method of Casulli & Cheng (1992), in which the model automatically determines wet and dry cell faces based on local flow conditions, eliminating the need for explicit specification of internal boundaries. The current implementation supports uniform rectilinear grids only; planned extensions include support for non-uniform rectilinear and curvilinear meshes.

Boundary conditions are implemented to handle both open and closed boundaries. Dirichlet conditions are used for inlet boundaries, specifying flow rates and water depths. For open boundaries where water can freely enter or exit the domain, the model offers both gradient-based and radiation-based conditions. These allow for the realistic simulation of wave propagation and minimize artificial reflections at the domain boundaries.

RiverFlowDynamics, as a full 2D flow model, offers several advantages over simpler flow models, including traditional overland flow models available in Landlab (Adams et al., 2017; Almeida et al., 2012). While overland flow models typically focus on shallow sheet flow and often use simplified equations like the kinematic wave approximation, RiverFlowDynamics solves the complete depth-averaged Saint-Venant equations. This approach allows for a more comprehensive representation of complex flow dynamics, including subcritical and supercritical flows, hydraulic jumps, and intricate channel-floodplain interactions. The model's ability to capture these phenomena makes it superior in scenarios involving rapid flood propagation in urban areas, detailed floodplain mapping, or the analysis of complex river morphodynamics. Furthermore, the semi-Lagrangian scheme employed in RiverFlowDynamics provides enhanced stability and accuracy for advection-dominated flows, a critical advantage when modeling high-velocity currents or steep terrain where simpler models might fail. This makes RiverFlowDynamics particularly well-suited for applications in mountainous regions, urban flood modeling, from small-scale stream dynamics to large-scale flood simulations, or any situation where capturing the full range of flow regimes and their transitions is crucial for accurate predictions. The accessibility of this code within the Landlab framework will make it easier for future users to modify and contribute to its continual evolution.

Source code for RiverFlowDynamics is available as part of the Landlab Python package (v2.7.0 and later). Tutorials and examples are available in the notebook gallery of the main Landlab documentation and repository.

# Statement of need

RiverFlowDynamics is a Python-based 2D flow model developed as a component of the Landlab framework, addressing a critical gap in the modeling of complex river systems and flood dynamics. Prior to RiverFlowDynamics, Landlab lacked a comprehensive 2D flow model capable

of handling fully advective-dominated problems, particularly in rivers with complex topographies. This limitation hindered accurate simulations of diverse flow regimes and transitions crucial for advanced hydrological and environmental studies. The model's integration into Landlab's component framework enables future coupling with sediment transport components to simulate morphodynamic processes and assess impacts on aquatic habitat and riverine vegetation dynamics under changing flow conditions.

Unlike commercial alternatives such as TELEMAC and Delft3D, RiverFlowDynamics provides an open-source, Python-based solution that is more accessible to researchers and educators while maintaining comparable numerical accuracy. RiverFlowDynamics solves the complete depth-averaged Saint-Venant equations, offering a significant advancement over existing Landlab components that typically use simplified equations like the kinematic wave approximation. This approach enables the model to capture complex flow dynamics, including subcritical and supercritical flows, hydraulic jumps, and intricate channel-floodplain interactions. The model's capabilities make it particularly valuable for a wide range of applications, from small-scale stream dynamics to large-scale flood simulations. It is design to be applicable in scenarios involving rapid flood propagation in urban areas, detailed floodplain mapping, and the analysis of complex river morphodynamics in mountainous regions. By integrating RiverFlowDynamics into the Landlab framework, we provide researchers, students, and practitioners with a powerful, accessible tool for hydraulics modeling. This integration facilitates future modifications and contributions, ensuring the model's continual evolution to meet emerging challenges in river system analysis and flood risk assessment. Integration with Landlab leverages its established grid structure, visualization tools, and interoperability with other components, facilitating multi-process simulations and reducing development overhead

# Acknowledgements

This research was supported by NSF EPSCoR (Award #2242769 to AM) and Chile's ANID FONDECYT Iniciación (Grant #11200949 to AM). Landlab development was funded by NSF (Awards #1147454, #1148305, #1450409, #1450338, #1450412) and the Community Surface Dynamics Modeling System (NSF Awards #1226297, #1831623).

# References

Adams, J. M., Gasparini, N. M., Hobley, D. E. J., Tucker, G. E., Hutton, E. W. H., Nudurupati, S. S., & Istanbulluoglu, E. (2017). The Landlab v1.0 OverlandFlow component: A Python tool for computing shallow-water flow across watersheds. *Geoscientific Model Development*, *10*(4), 1645–1663. https://doi.org/10.5194/gmd-10-1645-2017

Almeida, G. A. M. de, Bates, P., Freer, J. E., & Souvignet, M. (2012). Improving the stability of a simple formulation of the shallow water equations for 2-D flood modeling. *Water Resources Research*, *48*(5). https://doi.org/10.1029/2011WR011570

Andersson, B., Andersson, R., Håkansson, L., Mortensen, M., Sudiyo, R., & Van Wachem, B. (2011). *Computational Fluid Dynamics for engineers*. Cambridge University Press. https://doi.org/10.1017/CBO9781139093590

Barnhart, K. R., Hutton, E. W. H., Tucker, G. E., Gasparini, N. M., Istanbulluoglu, E., Hobley, D. E. J., Lyons, N. J., Mouchene, M., Nudurupati, S. S., Adams, J. M., & others. (2020). Landlab v2.0: A software package for Earth surface dynamics. *Earth Surface Dynamics*, *8*(2), 379–397. https://doi.org/10.5194/esurf-8-379-2020

Bates, J. R., & McDonald, A. (1982). Multiply-upstream, semi-Lagrangian advective schemes: Analysis and application to a multi-level primitive equation model. *Monthly Weather Review*, *110*(12), 1831–1842. https://doi.org/10.1175/1520-0493(1982)110%3C1831:MUSLAS%3E2.0.CO;2

Brufau, P., & Garcia-Navarro, P. (2000). Two-dimensional dam break flow simulation. *International Journal for Numerical Methods in Fluids*, *33*(1), 35–57. https://doi.org/10.1002/(SICI)1097-0363(20000515)33:1%3C35::AID-FLD999%3E3.0.CO;2-D

Casulli, V. (1990). Semi-implicit finite difference methods for the two-dimensional shallow water equations. *Journal of Computational Physics*, *86*(1), 56–74. https://doi.org/10.1016/0021-9991(90)90091-E

Casulli, V. (1999). A semi-implicit finite difference method for non-hydrostatic, free-surface flows. *International Journal for Numerical Methods in Fluids*, *30*(4), 425–440. https://doi.org/10.1002/(SICI)1097-0363(19990630)30:4%3C425::AID-FLD847%3E3.0.CO;2-D

Casulli, V., & Cheng, R. T. (1992). Semi-implicit finite difference methods for three-dimensional shallow water flow. *International Journal for Numerical Methods in Fluids*, *15*(6), 629–648. https://doi.org/10.1002/fld.1650150602

Fletcher, C. A. J. (2012). *Computational Techniques for Fluid Dynamics 2: Specific techniques for different flow categories*. Springer Science & Business Media. https://doi.org/10.1007/978-3-642-58239-4

He, Z., Wu, T., Weng, H., Hu, P., & Wu, G. (2017). Numerical simulation of dam-break flow and bed change considering the vegetation effects. *International Journal of Sediment Research*, *32*(1), 105–120. https://doi.org/10.1016/j.ijsrc.2015.04.004

Hobley, D. E. J., Adams, J. M., Nudurupati, S. S., Hutton, E. W. H., Gasparini, N. M., Istanbulluoglu, E., & Tucker, G. E. (2017). Creative computing with Landlab: An open-source toolkit for building, coupling, and exploring two-dimensional numerical models of Earth-surface dynamics. *Earth Surface Dynamics*, *5*(1), 21–46. https://doi.org/10.5194/esurf-5-21-2017

Hutton, E., Barnhart, K., Hobley, D., Tucker, G., Nudurupati, S., Adams, J., Gasparini, N., Shobe, C., Strauch, R., Knuth, J., Mouchene, M., Lyons, N., Litwin, D., Glade, R., Giuseppecipolla95, Manaster, A., Abby, L., Thyng, K., & Rengers, F. (2020). *Landlab*. https://doi.org/10.5281/zenodo.595872

Pollock, D. W. (1988). Semianalytical Computation of Path Lines for Finite-Difference Models. *Groundwater*, *26*(6), 743–750. https://doi.org/10.1111/j.1745-6584.1988.tb00425.x

Robert, A. (1981). A stable numerical integration scheme for the primitive meteorological equations. *Atmosphere-Ocean*, *19*(1), 35–46. https://doi.org/10.1080/07055900.1981.9649098

Robert, A., Yee, T. L., & Ritchie, H. (1985). A semi-Lagrangian and semi-implicit numerical integration scheme for multilevel atmospheric models. *Monthly Weather Review*, *113*(3), 388–394. https://doi.org/10.1175/1520-0493(1985)113%3C0388:ASLASI%3E2.0.CO;2

Staniforth, A., & Côté, J. (1991). Semi-Lagrangian integration schemes for atmospheric models—A review. *Monthly Weather Review*, *119*(9), 2206–2223. https://doi.org/10.1175/1520-0493(1991)119%3C2206:SLISFA%3E2.0.CO;2

DRAFT